

## RF Exposure Evaluation Declaration

---

**FCC ID:** Z9G-EDF155

**Applicant:** Edifier International Limited

**Address:** P.O. Box 6264 General Post Office Hong Kong

**Application Type:** Certification

**Product:** Portable Bluetooth Speaker

**Model No.:** EDF100019

**Brand Name:** EDIFIER

**FCC Rule Part(s):** FCC Part 2 (Section 2.1091)

**Reviewed By:**

Sunny Sun

**Approved By:**

Robin Wu



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Shenzhen) Co., Ltd.

## Revision History

Report No.	Version	Description	Issue Date	Note
2108RSU067-U3	Rev. 01	Initial Report	11-08-2021	Valid

## CONTENTS

Description	Page
<b>1. General Information.....</b>	<b>4</b>
1.1. Applicant.....	4
1.2. Manufacturer .....	4
1.3. Test Facility.....	4
1.4. Product Information .....	5
1.5. RF Specification.....	5
1.6. Applied Standards .....	5
<b>2. RF Exposure Evaluation .....</b>	<b>6</b>
2.1. Test Limit .....	6
2.2. Test Result .....	8
<b>Appendix - EUT Photograph .....</b>	<b>9</b>

## 1. General Information

## 1.1. Applicant

Edifier International Limited

P.O. Box 6264 General Post Office Hong Kong

## 1.2. Manufacturer

Edifier International Limited

P.O. Box 6264 General Post Office Hong Kong

### 1.3. Test Facility

<input type="checkbox"/>	<b>Test Site – MRT Suzhou Laboratory</b>
	<b>Laboratory Location (Suzhou - Wuzhong)</b>
	D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China
	<b>Laboratory Location (Suzhou - SIP)</b>
	4b Building, Liando U Valley, No.200 Xingpu Rd., Shengpu Town, Suzhou Industrial Park, China
	<b>Laboratory Accreditations</b>
	A2LA: 3628.01
	CNAS: L10551
	FCC: CN1166
	ISED: CN0001
	VCCI: <input type="checkbox"/> R-20025 <input type="checkbox"/> G-20034 <input type="checkbox"/> C-20020 <input type="checkbox"/> T-20020
	<input type="checkbox"/> R-20141 <input type="checkbox"/> G-20134 <input type="checkbox"/> C-20103 <input type="checkbox"/> T-20104
<input checked="" type="checkbox"/>	<b>Test Site – MRT Shenzhen Laboratory</b>
	<b>Laboratory Location (Shenzhen)</b>
	1G, Building A, Junxiangda Building, Zhongshanyuan Road West, Nanshan District, Shenzhen, China
	<b>Laboratory Accreditations</b>
	A2LA: 3628.02
	CNAS: L10551
	FCC: CN1284
	ISED: CN0105
<input type="checkbox"/>	<b>Test Site – MRT Taiwan Laboratory</b>
	<b>Laboratory Location (Taiwan)</b>
	No. 38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)
	<b>Laboratory Accreditations</b>
	TAF: L3261-190725
	FCC: 291082, TW3261
	ISED: TW3261

#### 1.4. Product Information

Product Name	Portable Bluetooth Speaker
Model No.	EDF100019
Test Device No.	SN: 1004000197815
Bluetooth Specification	v5.0 Single mode (BR/EDR)
Power Type	USB (DC 5V)
Operating Temperature	0 ~ 45°C
Remark:	<p>The information of EUT was provided by the manufacturer, and the accuracy of the information shall be the responsibility of the manufacturer.</p>

#### 1.5. Radio Specification

Frequency Range	2402 ~ 2480 MHz
Type of Modulation	GFSK, $\pi/4$ DQPSK, 8DPSK
Data Rate	1Mbps, 2Mbps, 3Mbps
Antenna Type	PCB Antenna
Antenna Gain	2.59dBi
Declared Output Power	<p>For 1Mbps (GFSK): 1.0mW/MHz</p> <p>For 2Mbps (<math>\pi/4</math> DQPSK): 1.0mW/MHz</p> <p>For 3Mbps (8DPSK): 1.0mW/MHz</p>

#### 1.6. Applied Standards

KDB 447498 D01v06

## 2. RF Exposure Evaluation

### 2.1. Test Limit

#### SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test

Separation Distances are illustrated in the following Table. The equation and threshold in Note 1 must be applied to determine SAR test exclusion.

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	SAR Test Exclusion Threshold (mW)
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	
MHz	30	35	40	45	50	mm
150	232	271	310	349	387	SAR Test Exclusion Threshold (mW)
300	164	192	219	246	274	
450	134	157	179	201	224	
835	98	115	131	148	164	
900	95	111	126	142	158	
1500	73	86	98	110	122	
1900	65	76	87	98	109	
2450	57	67	77	86	96	
3600	47	55	63	71	79	
5200	39	46	53	59	66	
5400	39	45	52	58	65	
5800	37	44	50	56	62	

Note: The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})]^*$   
 $[\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is  $\leq$  50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $<$  5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

## 2.2. Test Result

Product	Portable Bluetooth Speaker				
Test Item	RF Exposure Evaluation				

Test Mode	Frequency Band (MHz)	Maximum Output Power (dBm)	Tune Up Power (dBm)	Tune Up Power (mW)	SAR Test Exclusion Threshold (mW) @ 5mm
Bluetooth	2402 ~ 2480	3.29	3.40	2.19	10

Note: Per FCC KDB 447498 D01v06, the SAR exclusion threshold for distances <50mm is defined by the following equation:

$$\frac{\text{Max Power of Channel (mW)}}{\text{Test Separation Dist (mm)}} * \sqrt{\text{Frequency(GHz)}} \leq 3.0$$

Based on the maximum conducted power of Bluetooth and the antenna to use separation distance, Bluetooth SAR was not required;

For Bluetooth-LE,  $(2.19/ 5) * \sqrt{2.402} = 0.69 < 3.00$

So SAR test exclusion can be applied for Portable Bluetooth Speaker.

## Appendix - EUT Photograph

Refer to "2108RSU067-UE" file.