

FCC AND ISCED CERTIFICATION TEST REPORT

FOR

Applicant	:	Edifier International Limited
Address	:	P. O. Box 6264 General Post Office Hong Kong
Equipment under Test	:	In-House Bluetooth Speaker
Model No.	:	EDF286001
Trade Mark	:	EDIFIER
FCC ID	:	Z9G-EDF198
IC	:	10004A-EDF198
Manufacturer	:	Beijing Edifier Technology Co., Ltd.
Address	:	8th floor, ZuoAn Building, NO.68 BeiSiHuanXiLu, Haidian District, Beijing 100080, CHINA

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park,

Dongguan City, Guangdong Province, China, 523808

Tel.: +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

REPORT

Table of Contents

	Test report declares.....	4
1.	Summary of Test Results.....	6
2.	General Test Information	7
2.1.	Description of EUT	7
2.2.	Accessories of EUT	7
2.3.	Assistant equipment used for test.....	7
2.4.	Block diagram of EUT configuration for test	8
2.5.	Test environment conditions	8
2.6.	Deviations of test standard.....	8
2.7.	Test laboratory	8
2.8.	Measurement uncertainty.....	9
3.	Equipment Used During Test.....	10
4.	6 dB Bandwidth and 99% Bandwidth.....	11
4.1.	Block diagram of test setup.....	11
4.2.	Limits	11
4.3.	Test procedure	11
4.4.	Test result.....	11
4.5.	Original test data	12
5.	Maximum Peak Output Power	14
5.1.	Block diagram of test setup.....	14
5.2.	Limits	14
5.3.	Test procedure	14
5.4.	Test result.....	14
5.5.	Original test data	15
6.	Power Spectral Density.....	16
6.1.	Block diagram of test setup.....	16
6.2.	Limits	16
6.3.	Test procedure	16
6.4.	Test result.....	16
6.5.	Original test data	17
7.	Band Edge Compliance (Conducted Method)	18
7.1.	Block diagram of test setup.....	18
7.2.	Limits	18
7.3.	Test procedure	18
7.4.	Test result.....	19
7.5.	Original test data	19
8.	Radiated Emission	20
8.1.	Block diagram of test setup.....	20

8.2.	Limit	21
8.3.	Test Procedure	23
8.4.	Test result	24
9.	RF Conducted Spurious Emissions	41
9.1.	Block diagram of test setup	41
9.2.	Limits	41
9.3.	Test procedure	41
9.4.	Test result	42
9.5.	Original test data	42
10.	Emissions in Restricted Frequency Bands	46
10.1.	Block diagram of test setup	46
10.2.	Limit	46
10.3.	Test procedure	46
10.4.	Test result	46
11.	Power Line Conducted Emission	51
11.1.	Block diagram of test setup	51
11.2.	Power line conducted emission limits	51
11.3.	Test procedure	51
11.4.	Test result	52
12.	Antenna Requirements	57
12.1.	Limit	57
12.2.	Result	57
13.	Test Setup Photograph	58
14.	Photos of the EUT	60

Test Report Declare

Applicant	:	Edifier International Limited
Address	:	P. O. Box 6264 General Post Office Hong Kong
Equipment under Test	:	In-House Bluetooth Speaker
Model No.	:	EDF286001
Trade mark	:	EDIFIER
Manufacturer	:	Beijing Edifier Technology Co., Ltd.
Address	:	8th floor, ZuoAn Building, NO.68 BeiSiHuanXiLu, Haidian District, Beijing 100080, CHINA

Test Standard Used:

FCC Rules and Regulations Part 15 Subpart C, RSS-247 Issue 2 February 2017.

Test procedure used:

ANSI C63.10:2013, RSS-Gen Issue 5, Apr. 2018, Amendment 2 (February 2021).

We Declare:

The equipment described above is tested by Dongguan Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Dongguan Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above FCC&ISED standards.

Report No.:	DDT-R22092912-2E02.		
Date of Receipt:	Oct. 10, 2022	Date of Test:	Oct. 10, 2022 ~ Dec. 06, 2022

Prepared By:

Jacky Huang

Jacky Huang/Engineer

Approved By:

Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Dec. 12, 2022	

1. Summary of Test Results

The EUT have been tested according to the applicable standards as referenced below.		
Description of Test Item	Standard	Results
6dB Bandwidth and 99% Bandwidth	FCC Part 15: 15.215 ANSI C63.10:2013 RSS-247 Issue 2 RSS-GEN 6.7	Pass
Peak Output Power	FCC Part 15: 15.247 ANSI C63.10:2013 RSS-247 Issue 2	Pass
Power Spectral Density	FCC Part 15:15.247 ANSI C63.10:2013 RSS-247 Issue 2	Pass
Band Edge Compliance (Conducted Method)	FCC Part 15: 15.209 FCC Part 15: 15.247 ANSI C63.10: 2013 RSS-247 Issue 2 RSS-Gen Issue 5	Pass
Radiation Emission	FCC Part 15: 15.247 ANSI C63.10:2013 RSS-247 Issue 2 RSS-Gen Issue 5	Pass
RF Conducted Spurious Emissions	FCC Part 15: 15.209 FCC Part 15: 15.247 ANSI C63.10: 2013 RSS-247 Issue 2 RSS-Gen Issue 5	Pass
Emission In Restricted Frequency Bands	FCC Part 15: 15.209 FCC Part 15: 15.247 ANSI C63.10: 2013 RSS-247 Issue 2 RSS-Gen Issue 5	Pass
Power Line Conducted Emission	FCC Part 15: 15.207 ANSI C63.10: 2013 RSS-Gen Issue 5	Pass
Antenna Requirement	FCC Part 15: 15.203 RSS-Gen Issue 5	Pass
This product will be shipped randomly with power supplies from two different manufacturers (SHENZHEN HUAKESHENG DIGITAL TECHNOLOGY CO.,LTD and LianGang Optoelectronic Technology Co.,Ltd.). Based on the judgment of the engineering, it only affects Radiated Emission (below 1G) and Power Line Conducted Emission. Therefore, these two test items have tested for the two power supplies, and the rest test items only record the worst power supply data.		

2. General Test Information

2.1. Description of EUT

EUT* Name	: In-House Bluetooth Speaker
Model Number	: EDF286001
EUT Function Description	: Please reference user manual of this device
Power Supply	: 100-240V ~, 50/60Hz, 1A
Radio Specification	: Bluetooth V5.3
Operation Frequency	: 2402 MHz - 2480 MHz
Modulation	: GFSK
Data Rate	: 1 Mbps
Antenna Type	: PCB antenna, maximum PK gain: -0.29 dBi
Sample number	: S22092912-02 for radiation, S22092912-03 for conductive

Note: EUT is the ab. of equipment under test.

Channel Information					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	14	2430	28	2458
1	2404	15	2432	29	2460
2	2406	16	2434	30	2462
3	2408	17	2436	31	2464
4	2410	18	2438	32	2466
5	2412	19	2440	33	2468
6	2414	20	2442	34	2470
7	2416	21	2444	35	2472
8	2418	22	2446	36	2474
9	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	39	2480
12	2426	26	2454		
13	2428	27	2456		

2.2. Accessories of EUT

Description of Accessories	Manufacturer	Model number	Serial No.	Other
N/A	N/A	N/A	N/A	N/A

2.3. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	EMC Compliance	SN
N/A	N/A	N/A	N/A	N/A

2.4. Block diagram of EUT configuration for test



The pathloss of external cable: 0.5dB (According to the manufacturer's claims)

Test software: BQB.exe, Version: 20200306

The test software was used to control EUT work in Continuous Tx mode, and select test channel, wireless mode as below table:

Tested Mode, Channel, Information			
Test Mode	Setting Tx Power	Channel	Frequency (MHz)
BLE_1M	default	CH0	2402
	default	CH19	2440
	default	CH39	2480

2.5. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	+15°C to +35 °C
Humidity range:	20-75%
Pressure range:	86-106 kPa

2.6. Deviations of test standard

No deviation.

2.7. Test laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

2.8. Measurement uncertainty

Test Item	Uncertainty
Bandwidth	1.1%
Peak Output Power (Conducted) (Spectrum Analyzer)	0.86 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$); 1.38 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$)
Peak Output Power (Conducted) (Power Sensor)	0.74 dB
Power Spectral Density	0.74 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$); 1.38 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$)
Frequencies Stability	6.7×10^{-8} (Antenna couple method) 5.5×10^{-8} (Conducted method)
Conducted Spurious Emissions	0.86 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$); 1.40 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$) 1.66 dB ($8 \text{ GHz} \leq f < 22 \text{ GHz}$)
Uncertainty for Radio Frequency (RBW<20 KHz)	3×10^{-8}
Temperature	0.4 °C
Humidity	2 %
Uncertainty for Radiation Emission Test (9kHz -30 Mhz)	3.44 dB
Uncertainty for Radiation Emission Test (30 Mhz-1 Ghz)	4.70 dB (Antenna Polarize: V) 4.84 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission Test (1 Ghz-40 Ghz)	4.10 dB (1-6 GHz) 4.40 dB (6 GHz-18 GHz) 3.54 dB (18 GHz-26 GHz) 4.30 dB (26 GHz-40 GHz)
Uncertainty for Power Line Conduction Emission Test	3.32 dB (150 kHz-30 MHz)


Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3. Equipment Used During Test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
☑RF Connected Test (Tonscend RF Measurement System 4#)					
MXA Signal Analyzer	Agilent	N9020A	MY49100362	Aug. 26, 2022	1 Year
Signal & Spectrum analyzer	R&S	FSV3044	101173	Apr. 13, 2022	1 Year
Wideband Radio Communication tester	R&S	CMW500	120259	May 26, 2022	1 Year
MXG Vector Signal Generator	Agilent	N5182B	MY59100192	May 18, 2022	1 Year
Vector Signal Generator	Agilent	E8267D	US49060192	Sep. 28, 2022	1 Year
RF Control Unit	Tonscend	JS0806-2	21I8060485	May. 28, 2022	1 Year
Temp&Humi Programmable	ZHIXIANG	ZXGDJS-150L	ZX170110-A	May 26, 2022	1 Year
Test Software	JS Tonscend	JS1120-3	Ver.2.6.88.0346	N/A	N/A
☑Radiation 3#chamber					
EMI Test Receiver	R&S	ESU	100472	May 18, 2022	1 Year
Spectrum analyzer	Agilent	E4447A	MY50180031	May 18, 2022	1 Year
Active Loop antenna	Schwarzbeck	FMZB-1519	1519-038	Sep. 29, 2022	1 Year
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	01429	Jul. 22, 2022	1 Year
Double Ridged Horn Antenna	Schwarzbeck	BBHA 9120 D	02468	Sep. 29, 2022	1 Year
Broad Band Horn Antenna	Schwarzbeck	BBHA 9170	790	May 06, 2022	1 Year
Pre-amplifier	COM-POWER	PAM-118A	18040084	Aug. 17, 2022	1 Year
Pre-amplifier	COM-POWER	PAM-840A	461369	Apr. 11, 2022	1 Year
RE Cable	N/A	W23.02 CP1-X2 + W23.09 AP1-X8+ JCT26S-NJ-NJ-1.5M+ JCT26S-NJ-NJ-1.5M	4.5M+8M+1.5M+1.5M	Aug.17, 2022	1 Year
RF Cable	Yuhu Technology	JCTB810-NJ-NJ-9M	21123964	May. 19,2022	1 Year
RF Cable	Yuhu Technology	ZT26S-SMAJ-SMAJ-1M	21073466	Aug.17, 2022	1 Year
Test software	Tonscend	JS32-RE	V 5.0.0.1	N/A	N/A
Test software	Audix	E3	V 6.1.1.1	N/A	N/A
☑Power Line Conducted Emissions Test 1#					
Test Receiver	R&S	ESCI	100551	Aug. 26, 2022	1 Year
LISN 1	R&S	ENV216	101109	Aug. 26, 2022	1 Year
LISN 2	R&S	ESH2-Z5	100309	Aug. 26, 2022	1 Year
Pulse Limiter	R&S	ESH3-Z2	101242	Aug. 26, 2022	1 Year
CE Cable 1	HUBSER	N/A	W10.01	Aug. 26, 2022	1 Year
Test software	Audix	E3	V 6.11111b	N/A	N/A

4. 6 dB Bandwidth and 99% Bandwidth

4.1. Block diagram of test setup



4.2. Limits

For direct sequence systems, the minimum 6dB bandwidth shall be at least 500 kHz

4.3. Test procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) 99% Bandwidth set the spectrum analyzer as follows:

RBW: 30 kHz
 VBW: 100 kHz
 Detector Mode: Peak
 Sweep time: auto
 Trace mode: Max hold

(3) 6 dB Bandwidth set the spectrum analyzer as follows:

RBW: 100 kHz
 VBW: 300 kHz
 Detector Mode: Peak
 Sweep time: auto
 Trace mode: Max hold

(4) Allow the trace to stabilize, measure the 6 dB and 99% bandwidth of signal.

Note:

1.The attenuator loss was inputted into spectrum analyzer as amplitude offset.


2.The pathloss of external cable: 0.5dB (According to the manufacturer's claims).

4.4. Test result


Test Mode	Channel	99% bandwidth Result (MHz)	6 dB bandwidth Result (MHz)	6 dB width Limit (MHz)	Verdict
BLE_1M	CH0	1.026	0.696	>0.5	Pass
	CH19	1.020	0.700	>0.5	Pass
	CH39	1.022	0.700	>0.5	Pass

4.5. Original test data

6dB bandwidth:



99% Bandwidth:



5. Maximum Peak Output Power

5.1. Block diagram of test setup

Same with 4.1

5.2. Limits

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. If transmitting antennas of directional gain greater than 6dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6dBi.

5.3. Test procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Set the spectrum analyzer as follows:

RBW: $\geq$ DTS bandwidth

VBW: $\geq 3 \times$ RBW

Span $\geq 3 \times$ RBW

Detector Mode: Peak

Sweep time: auto

Trace mode Max hold

(3) Allow the trace to stabilize, Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges measure out the PK output power.

Note:


1.The attenuator loss was inputted into spectrum analyzer as amplitude offset.

2.The pathloss of external cable: 0.5dB (According to the manufacturer's claims).

5.4. Test result

Test Mode	Frequency (MHz)	Peak Output Power (dBm)	Limit (dBm)	e.i.r.p (dBm)	Limit (dBm)	Verdict
BLE_1M	2402	0.67	≤ 30	0.38	≤ 36	Pass
	2440	-1.22	≤ 30	-1.51	≤ 36	Pass
	2480	-0.50	≤ 30	-0.79	≤ 36	Pass

5.5. Original test data



6. Power Spectral Density

6.1. Block diagram of test setup

Same with 4.1

6.2. Limits

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

6.3. Test procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Set the spectrum analyzer as follows:

Center frequency	DTS Channel center frequency
RBW:	$3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$
VBW:	$\geq 3\text{RBW}$
Span	1.5 times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.

(4) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.


Note:

- 1.The attenuator loss was inputted into spectrum analyzer as amplitude offset.
- 2.The pathloss of external cable: 0.5dB (According to the manufacturer's claims).

6.4. Test result

Test Mode	Antenna	Channel	Result (dBm/3 kHz)
BLE_1M	ANT1	CH0	-15.08
	ANT1	CH19	-16.88
	ANT1	CH39	-16.18
Limit: <8 dBm/3 kHz			Conclusion: Pass

6.5. Original test data



7. Band Edge Compliance (Conducted Method)

7.1. Block diagram of test setup

Same with 4.1

7.2. Limits

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

7.3. Test procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

Center frequency	DTS Channel center frequency
RBW:	100 kHz
VBW:	300 kHz
Span	1.5 times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.

(4) Set the spectrum analyzer as follows:

RBW:	100 kHz
VBW:	300 kHz
Span	Encompass frequency range to be measured
Number of measurement points	$\geq \text{span/RBW}$
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band


Note:

- 1.The attenuator loss was inputted into spectrum analyzer as amplitude offset.
- 2.The pathloss of external cable: 0.5dB (According to the manufacturer's claims).

7.4. Test result

Test Mode	CH or Frequency	Measured Range	Verdict
BLE_1M	CH0	2.310 GHz-2.410 GHz	Pass
	CH39	2.470 GHz-2.570 GHz	Pass


7.5. Original test data




8. Radiated Emission

8.1. Block diagram of test setup


In 3 m Anechoic Chamber, test setup diagram for 9 kHz - 30 MHz:



In 3 m Anechoic Chamber, test setup diagram for 30 MHz - 1 GHz:



In 3 m Anechoic Chamber, test setup diagram for frequency above 1 GHz:



Note: For harmonic emissions test an appropriate high pass filter was inserted in the input port of AMP.

8.2. Limit

(1) FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6

RSS-Gen section 8.10 Restricted frequency bands*

MHz	MHz	MHz	GHz
0.090-0.110	12.51975-12.52025	240-285	3.5-4.4
0.495-0.505	12.57675-12.57725	322-335.4	4.5-5.15
2.1735-2.1905	13.36-13.41	399.9-410	5.35-5.46
3.020-3.026	16.42-16.423	608-614	7.25-7.75
4.125-4.128	16.69475-16.69525	960-1427	8.025-8.5
4.1772&4.17775	16.80425-16.80475	1435-1626.5	9.0-9.2
4.2072&4.20775	25.5-25.67	1645.5-1646.5	9.3-9.5
5.677-5.683	37.5-38.25	1660-1710	10.6-12.7
6.215-6.218	73-74.6	1718.8-1722.2	13.25-13.4
6.26775-6.26825	74.8-75.2	2200-2300	14.47-14.5
6.31175-6.31225	108-138	2310-2390	15.35-16.2
8.291-8.294	149.9-150.05	2483.5-2500	17.7-21.4
8.362-8.366	156.52475-156.52525	2655-2900	22.01-23.12
8.37625-8.38675	156.7-156.9	3260-3267	23.6-24.0
8.41425-8.41475	162.0125-167.17	3332-3339	31.2-31.8
12.29-12.293	167.72-173.2	3345.8-3358	36.43-36.5
			Above 38.6

* Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

(2) FCC 15.209 Limit.

Frequency (MHz)	Measurement distance (meters)	Field strength limit	
		μV/m	dB(μV)/m
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

Note: (1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30 MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3m}(\text{dB}\mu\text{V}/\text{m}) = \text{Limit}_{30m}(\text{dB}\mu\text{V}/\text{m}) + 40\text{Log}(30m/3m)$$

(3) Limit for this EUT

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions or comply with 15.209 limits.

8.3. Test Procedure

- (1) EUT was placed on a non-metallic table, 10 mm above the ground plane inside a semi-anechoic chamber for below 1 G and 10 mm above the ground plane inside a semi-anechoic chamber for above 1 G.
- (2) Test antenna was located 3m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9 kHz-30 MHz	Active Loop antenna	3m
30 MHz-1 GHz	Trilog Broadband Antenna	3m
1 GHz-18 GHz	Double Ridged Horn Antenna(1GHz-18GHz)	3m
18 GHz-40 GHz	Horn Antenna (18 GHz-40 GHz)	1m

According ANSI C63.10:2013 clause 6.4.6 and 6.5.3, for measurements below 30 MHz, Antenna was located 3 m from EUT, the loop antenna was positioned in three antenna orientations (parallel, perpendicular, and round-parallel), for each measurement antenna alignment, the EUT shall be rotated through 0° to 360° on a turntable, and the lowest height of the magnetic antenna shall be 1 m above the ground. For measurement above 30MHz, the trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

- (3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9 kHz to 25 GHz:

- (a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1m to 4m (Except loop antenna, it's fixed 1m above ground.)
- (b) Change work frequency or channel of device if practicable.
- (c) Change modulation type of device if practicable.
- (d) Change power supply range from 85% to 115% of the rated supply voltage
- (e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9kHz to 25 GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 9kHz to 30 MHz and 18 GHz to 25 GHz, so below final test was performed with frequency range from 30 MHz to 18 GHz.

- (4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10:2013 on Radiated Emission test.
- (5) The emissions from 9 kHz to 1 GHz were measured based on CISPR QP detector except for the frequency bands 9-90 kHz, 110-490 kHz, for emissions from 9 kHz-90 kHz, 110 kHz-490 kHz and above 1 GHz were measured based on average detector, for emissions above 1GHz, peak emissions also be measured and need comply with Peak limit.
- (6) The emissions from 9 kHz to 1 GHz, QP or average values were measured with EMI receiver with below RBW

Frequency band	RBW
9 kHz-150 kHz	200 Hz
150 kHz-30 MHz	9 kHz
30 MHz-1 GHz	120 kHz

- (7) For emissions above 1 GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1 MHz, VBW is set at 3 MHz for Peak measure; RBW is set at 1 MHz, VBW is set at 10 Hz for Average measure (according ANSI C63.10:2013 clause 4.1.4.2.2 procedure for average measure).

8.4. Test result

Pass. (See below detailed test result)

All the emissions except fundamental emission from 9 kHz to 25 GHz were comply with 15.209 limits.

Note1: According exploratory test no any obvious emission was detected from 9 kHz to 30 MHz and 18 GHz to 25 GHz.

Note2: For emissions below 1GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1 GHz, the final test was only performed with EUT working in GFSK 1M Tx 2402 MHz mode.

Note3: If peak results comply with AV limit, AV Result is deemed to comply with AV limit.


Note4: For emission above 1GHz that over the limit are fundamental.

Radiated Emission test (below 1 GHz)**For SHENZHEN HUAKESHENG DIGITAL TECHNOLOGY CO.,LTD' power supply:****TR-4-E-009 Radiated Emission Test Result****Test Site** : DDT 3m Chamber 3#

D:\E3 6.111\2022 Report Data\Q22092912-2E\FCC BELOW 1G.EM6

Test Date : 2022-10-14**Tested By** : Bairong**EUT** : In-House Bluetooth Speaker**Model Number** : EDF286001**Power Supply** : AC 120V/60Hz**Test Mode** : Tx Mode**Condition** : Temp:23.8°C,Humi:52.4%,Press:100.3kPa**Antenna/Distance** : 2022 VLUB9163 #3/3m/HORIZONTAL**Memo** : BLE 1M (HUAKESHENG)

Data:3



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	43.20	1.59	12.74	3.63	17.96	40.00	-22.04	QP	HORIZONTAL
2	157.01	17.75	7.80	4.29	29.84	43.50	-13.66	QP	HORIZONTAL
3	187.10	9.67	9.91	4.40	23.98	43.50	-19.52	QP	HORIZONTAL
4	431.03	4.18	15.86	5.26	25.30	46.00	-20.70	QP	HORIZONTAL
5	603.54	3.92	18.70	5.75	28.37	46.00	-17.63	QP	HORIZONTAL
6	872.18	3.62	22.24	6.40	32.26	46.00	-13.74	QP	HORIZONTAL

Note:

- Result Level = Read Level + Antenna Factor + Cable loss.
- If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
- Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 3#

D:\E3 6.111\2022 Report Data\Q22092912-2E\FCC BELOW 1G.EM6

Test Date : 2022-10-14

Tested By : Bairong

EUT : In-House Bluetooth Speaker

Model Number : EDF286001


Power Supply : AC 120V/60Hz

Test Mode : Tx Mode

Condition : Temp:23.8°C,Humi:52.4%,Press:100.3kPa **Antenna/Distance** : 2022 VLUB9163 #3/3m/VERTICAL

Memo : BLE 1M (HUAKESHENG)

Data:4




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	33.21	8.88	10.44	3.57	22.89	40.00	-17.11	QP	VERTICAL
2	58.20	6.53	12.18	3.74	22.45	40.00	-17.55	QP	VERTICAL
3	110.96	8.70	10.31	4.05	23.06	43.50	-20.44	QP	VERTICAL
4	158.67	17.76	7.90	4.29	29.95	43.50	-13.55	QP	VERTICAL
5	319.94	0.49	13.80	4.89	19.18	46.00	-26.82	QP	VERTICAL
6	942.13	2.75	22.60	6.56	31.91	46.00	-14.09	QP	VERTICAL

Note:

1. Result Level = Read Level + Antenna Factor + Cable loss.
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

For LianGang Optoelectronic Technology Co.,Ltd.' power supply: TR-4-E-009 Radiated Emission Test Result

Test Date: 2022-11-28
Tested By: James Gan
EUT: In-House Bluetooth Speaker
Model Number: EDF286001
Test Mode: TX Mode
Power Supply: AC 120V/60Hz
Condition: Temp:23.4°C;Humi:58.6%;Press:100.3kPa
Test Site: DDT 3# Chamber
File Path: d:\ts\2022 report data\Q22092912-2E EDF286001\FCC BELOW 1G\20221128-204915_H
Memo: BLE (LianGang)




Final Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	41.86	31.28	-19.18	12.10	40.00	27.90	QP	Horizontal
2	71.97	37.32	-23.50	13.82	40.00	26.18	QP	Horizontal
3	176.95	50.11	-21.85	28.26	43.50	15.24	QP	Horizontal
4	275.04	36.32	-17.71	18.61	46.00	27.39	QP	Horizontal
5	335.40	34.69	-16.14	18.55	46.00	27.45	QP	Horizontal
6	980.56	25.51	-4.68	20.83	54.00	33.17	QP	Horizontal

Note:

1. Result Level = Read Level + Factor
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2022-11-28
Tested By: James Gan
EUT: In-House Bluetooth Speaker
Model Number: EDF286001
Test Mode: TX Mode
Power Supply: AC 120V/60Hz
Condition: Temp:23.4°C;Humi:58.6%;Press:100.3kPa
Test Site: DDT 3# Chamber
File Path: d:\ts\2022 report data\Q22092912-2E EDF286001\FCC BELOW 1G\20221128-204959_V
Memo: BLE (LianGang)



Final Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	35.95	40.45	-20.54	19.91	40.00	20.09	QP	Vertical
2	72.58	41.13	-23.68	17.45	40.00	22.55	QP	Vertical
3	113.92	48	-21.20	26.80	43.50	16.70	QP	Vertical
4	161.99	52.94	-22.78	30.16	43.50	13.34	QP	Vertical
5	327.73	31.34	-16.34	15.00	46.00	31.00	QP	Vertical
6	978.50	25.66	-4.74	20.92	54.00	33.08	QP	Vertical

Note:

1. Result Level = Read Level + Factor
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

Radiated Emission test (above 1GHz)

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 3#

D:\E3 6.111\2022 Report Data\Q22092912-2E\FCC ABOVE
1G .EM6

Test Date : 2022-10-17

Tested By : Bairong

EUT : In-House Bluetooth Speaker

Model Number : EDF286001

Power Supply : AC 120V/60Hz


Test Mode : Tx Mode

Condition : Temp:23.7°C,Humi:63.1%,Press:100.3kPa

Antenna/Distance : 2021 BBHA 9120D 3#/3m/HORIZONTAL

Memo : BLE 1M 2402

Data: 14



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Filter Factor (dB)	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	1028.00	51.19	25.49	37.94	1.12	0.51	40.37	74.00	-33.63	Peak	HORIZONTAL
2	1212.00	50.50	25.46	38.22	1.22	0.54	39.50	74.00	-34.50	Peak	HORIZONTAL
3	1598.00	53.94	25.65	38.80	1.42	0.61	42.82	74.00	-31.18	Peak	HORIZONTAL
4	2292.00	51.55	27.23	39.55	1.68	0.71	41.62	74.00	-32.38	Peak	HORIZONTAL
5	2454.00	53.38	27.52	39.63	1.73	0.73	43.73	74.00	-30.27	Peak	HORIZONTAL
6	2914.00	50.37	29.17	39.86	1.85	0.78	42.31	74.00	-31.69	Peak	HORIZONTAL

Note:

1. Result Level = Read Level + Antenna Factor + Cable loss + Filter Factor - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. For emission above 1GHz that over the limit are fundamental.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 3#

D:\E3 6.111\2022 Report Data\Q22092912-2E\FCC ABOVE
1G .EM6

Test Date : 2022-10-17

Tested By : Bairong

EUT : In-House Bluetooth Speaker

Model Number : EDF286001

Power Supply : AC 120V/60Hz


Test Mode : Tx Mode

Condition : Temp:23.7°C,Humi:63.1%,Press:100.3kPa

Antenna/Distance : 2021 BBHA 9120D 3#/3m/VERTICAL

Memo : BLE 1M 2402

Data: 15



Note:

1. Result Level = Read Level + Antenna Factor + Cable loss + Filter Factor - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. For emission above 1GHz that over the limit are fundamental.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 3#

D:\E3 6.111\2022 Report Data\Q22092912-2E\FCC ABOVE 1G .EM6

Test Date : 2022-10-17

Tested By : Bairong

EUT : In-House Bluetooth Speaker

Model Number : EDF286001

Power Supply : AC 120V/60Hz


Test Mode : Tx Mode

Condition : Temp:23.7°C,Humi:63.1%,Press:100.3kPa

Antenna/Distance : 2021 BBHA 9120D 3#/3m/HORIZONTAL

Memo : BLE 1M 2402

Data: 16



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Filter Factor (dB)	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	4935.00	47.07	32.89	40.39	2.52	2.18	44.27	74.00	-29.73	Peak	HORIZONTAL
2	8100.00	45.47	37.16	39.81	3.20	2.27	48.29	74.00	-25.71	Peak	HORIZONTAL
3	9840.00	46.59	38.50	40.49	3.65	2.43	50.68	74.00	-23.32	Peak	HORIZONTAL
4	12165.00	45.11	39.13	40.15	3.94	2.49	50.52	74.00	-23.48	Peak	HORIZONTAL
5	14535.00	44.02	39.87	39.65	4.36	2.75	51.35	74.00	-22.65	Peak	HORIZONTAL
6	17970.00	39.72	42.31	40.68	4.95	3.78	50.08	74.00	-23.92	Peak	HORIZONTAL

Note:

1. Result Level = Read Level + Antenna Factor + Cable loss + Filter Factor - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. For emission above 1GHz that over the limit are fundamental.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 3#

D:\E3 6.111\2022 Report Data\Q22092912-2E\FCC ABOVE
1G .EM6

Test Date : 2022-10-17

Tested By : Bairong

EUT : In-House Bluetooth Speaker

Model Number : EDF286001

Power Supply : AC 120V/60Hz


Test Mode : Tx Mode

Condition : Temp:23.7°C,Humi:63.1%,Press:100.3kPa

Antenna/Distance : 2021 BBHA 9120D 3#/3m/VERTICAL

Memo : BLE 1M 2402

Data: 17



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Filter Factor (dB)	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	4785.00	48.63	32.41	40.36	2.46	2.16	45.30	74.00	-28.70	Peak	VERTICAL
2	7725.00	46.94	36.67	39.77	3.16	2.27	49.27	74.00	-24.73	Peak	VERTICAL
3	10500.00	45.82	39.00	40.40	3.67	2.43	50.52	74.00	-23.48	Peak	VERTICAL
4	11700.00	45.20	39.08	40.13	4.00	2.39	50.54	74.00	-23.46	Peak	VERTICAL
5	14520.00	42.92	39.88	39.65	4.35	2.75	50.25	74.00	-23.75	Peak	VERTICAL
6	17955.00	39.68	42.22	40.67	4.95	3.78	49.96	74.00	-24.04	Peak	VERTICAL

Note:

1. Result Level = Read Level + Antenna Factor + Cable loss + Filter Factor - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. For emission above 1GHz that over the limit are fundamental.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 3#

D:\E3 6.111\2022 Report Data\Q22092912-2E\FCC ABOVE 1G .EM6

Test Date : 2022-10-17

Tested By : Bairong

EUT : In-House Bluetooth Speaker

Model Number : EDF286001

Power Supply : AC 120V/60Hz


Test Mode : Tx Mode

Condition : Temp:23.7°C,Humi:63.1%,Press:100.3kPa

Antenna/Distance : 2021 BBHA 9120D 3#/3m/HORIZONTAL

Memo : BLE 1M 2440

Data: 20



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Filter Factor (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	1140.00	50.60	25.47	38.11	1.18	0.53	39.67	74.00	-34.33	Peak	HORIZONTAL
2	1598.00	53.84	25.65	38.80	1.42	0.61	42.72	74.00	-31.28	Peak	HORIZONTAL
3	2300.00	52.55	27.24	39.55	1.68	0.71	42.63	74.00	-31.37	Peak	HORIZONTAL
4	2396.00	58.75	27.41	39.60	1.71	0.72	48.99	74.00	-25.01	Peak	HORIZONTAL
5	2602.00	50.14	27.99	39.70	1.77	0.75	40.95	74.00	-33.05	Peak	HORIZONTAL
6	2934.00	50.09	29.25	39.87	1.85	0.78	42.10	74.00	-31.90	Peak	HORIZONTAL

Note:

1. Result Level = Read Level + Antenna Factor + Cable loss + Filter Factor - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. For emission above 1GHz that over the limit are fundamental.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 3#

D:\E3 6.111\2022 Report Data\Q22092912-2E\FCC ABOVE
1G .EM6

Test Date : 2022-10-17

Tested By : Bairong

EUT : In-House Bluetooth Speaker

Model Number : EDF286001

Power Supply : AC 120V/60Hz


Test Mode : Tx Mode

Condition : Temp:23.7°C,Humi:63.1%,Press:100.3kPa

Antenna/Distance : 2021 BBHA 9120D 3#/3m/VERTICAL

Memo : BLE 1M 2440

Data: 21



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Filter Factor (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	1084.00	50.91	25.48	38.03	1.15	0.52	40.03	74.00	-33.97	Peak	VERTICAL
2	1408.00	51.59	25.42	38.51	1.33	0.57	40.40	74.00	-33.60	Peak	VERTICAL
3	1598.00	56.84	25.65	38.80	1.42	0.61	45.72	74.00	-28.28	Peak	VERTICAL
4	2316.00	55.09	27.27	39.56	1.69	0.71	45.20	74.00	-28.80	Peak	VERTICAL
5	2730.00	51.28	28.47	39.77	1.80	0.76	42.54	74.00	-31.46	Peak	VERTICAL
6	2934.00	50.66	29.25	39.87	1.85	0.78	42.67	74.00	-31.33	Peak	VERTICAL

Note:

- Result Level = Read Level + Antenna Factor + Cable loss + Filter Factor - PRM Factor.
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
- For emission above 1GHz that over the limit are fundamental.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 3#

D:\E3 6.111\2022 Report Data\Q22092912-2E\FCC ABOVE 1G .EM6

Test Date : 2022-10-17

Tested By : Bairong

EUT : In-House Bluetooth Speaker

Model Number : EDF286001

Power Supply : AC 120V/60Hz


Test Mode : Tx Mode

Condition : Temp:23.7°C,Humi:63.1%,Press:100.3kPa

Antenna/Distance : 2021 BBHA 9120D 3#/3m/HORIZONTAL

Memo : BLE 1M 2440

Data: 22



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Filter Factor (dB)	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	4470.00	47.84	31.48	40.29	2.34	2.11	43.48	74.00	-30.52	Peak	HORIZONTAL
2	6345.00	44.85	34.83	40.22	3.20	2.61	45.27	74.00	-28.73	Peak	HORIZONTAL
3	9840.00	45.93	38.50	40.49	3.65	2.43	50.02	74.00	-23.98	Peak	HORIZONTAL
4	13560.00	44.01	39.99	40.01	4.05	2.93	50.97	74.00	-23.03	Peak	HORIZONTAL
5	16185.00	42.44	37.90	39.94	4.65	3.19	48.24	74.00	-25.76	Peak	HORIZONTAL
6	17955.00	39.54	42.22	40.67	4.95	3.78	49.82	74.00	-24.18	Peak	HORIZONTAL

Note:

1. Result Level = Read Level + Antenna Factor + Cable loss + Filter Factor - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. For emission above 1GHz that over the limit are fundamental.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 3#

D:\E3 6.111\2022 Report Data\Q22092912-2E\FCC ABOVE 1G .EM6

Test Date : 2022-10-17

Tested By : Bairong

EUT : In-House Bluetooth Speaker

Model Number : EDF286001

Power Supply : AC 120V/60Hz


Test Mode : Tx Mode

Condition : Temp:23.7°C,Humi:63.1%,Press:100.3kPa

Antenna/Distance : 2021 BBHA 9120D 3#/3m/VERTICAL

Memo : BLE 1M 2440

Data: 23



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Filter Factor (dB)	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	4770.00	49.43	32.36	40.35	2.46	2.16	46.06	74.00	-27.94	Peak	VERTICAL
2	7515.00	45.68	36.42	39.75	3.14	2.27	47.76	74.00	-26.24	Peak	VERTICAL
3	12015.00	45.05	39.19	40.10	4.04	2.41	50.59	74.00	-23.41	Peak	VERTICAL
4	13965.00	42.29	39.91	39.72	4.49	2.90	49.87	74.00	-24.13	Peak	VERTICAL
5	16170.00	42.75	37.90	39.93	4.64	3.19	48.55	74.00	-25.45	Peak	VERTICAL
6	17940.00	39.64	42.13	40.66	4.94	3.77	49.82	74.00	-24.18	Peak	VERTICAL


Note:

1. Result Level = Read Level + Antenna Factor + Cable loss + Filter Factor - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. For emission above 1GHz that over the limit are fundamental.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 3#D:\E3 6.111\2022 Report Data\Q22092912-2E\FCC ABOVE
1G .EM6**Test Date** : 2022-10-17**Tested By** : Bairong**EUT** : In-House Bluetooth Speaker**Model Number** : EDF286001**Power Supply** : AC 120V/60Hz**Test Mode** : Tx Mode**Condition** : Temp:23.7°C,Humi:63.1%,Press:100.3kPa**Antenna/Distance** : 2021 BBHA 9120D 3#/3m/HORIZONTAL**Memo** : BLE 1M 2480

Data: 24



Note:

1. Result Level = Read Level + Antenna Factor + Cable loss + Filter Factor - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. For emission above 1GHz that over the limit are fundamental.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 3#

D:\E3 6.111\2022 Report Data\Q22092912-2E\FCC ABOVE
1G .EM6

Test Date : 2022-10-17

Tested By : Bairong

EUT : In-House Bluetooth Speaker

Model Number : EDF286001

Power Supply : AC 120V/60Hz


Test Mode : Tx Mode

Condition : Temp:23.7°C,Humi:63.1%,Press:100.3kPa

Antenna/Distance : 2021 BBHA 9120D 3#/3m/VERTICAL

Memo : BLE 1M 2480

Data: 25



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Filter Factor (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	1086.00	50.95	25.48	38.03	1.15	0.52	40.07	74.00	-33.93	Peak	VERTICAL
2	1592.00	54.41	25.64	38.79	1.42	0.61	43.29	74.00	-30.71	Peak	VERTICAL
3	2250.00	54.62	27.15	39.53	1.67	0.71	44.62	74.00	-29.38	Peak	VERTICAL
4	2374.00	56.17	27.37	39.59	1.70	0.72	46.37	74.00	-27.63	Peak	VERTICAL
5	2746.00	53.03	28.53	39.77	1.80	0.76	44.35	74.00	-29.65	Peak	VERTICAL
6	2996.00	51.68	29.48	39.90	1.87	0.79	43.92	74.00	-30.08	Peak	VERTICAL

Note:

1. Result Level = Read Level + Antenna Factor + Cable loss + Filter Factor - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. For emission above 1GHz that over the limit are fundamental.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 3#

D:\E3 6.111\2022 Report Data\Q22092912-2E\FCC ABOVE
1G .EM6

Test Date : 2022-10-17

Tested By : Bairong

EUT : In-House Bluetooth Speaker

Model Number : EDF286001

Power Supply : AC 120V/60Hz


Test Mode : Tx Mode

Condition : Temp:23.7°C,Humi:63.1%,Press:100.3kPa

Antenna/Distance : 2021 BBHA 9120D 3#/3m/HORIZONTAL

Memo : BLE 1M 2480

Data: 26



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Filter Factor (dB)	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	4740.00	48.26	32.27	40.35	2.45	2.15	44.78	74.00	-29.22	Peak	HORIZONTAL
2	6900.00	46.35	35.84	39.78	3.07	2.31	47.79	74.00	-26.21	Peak	HORIZONTAL
3	10065.00	44.84	38.48	40.57	3.67	2.47	48.89	74.00	-25.11	Peak	HORIZONTAL
4	13500.00	43.56	40.00	40.05	3.99	2.93	50.43	74.00	-23.57	Peak	HORIZONTAL
5	15645.00	41.97	38.54	39.79	4.57	2.94	48.23	74.00	-25.77	Peak	HORIZONTAL
6	17985.00	40.07	42.41	40.69	4.96	3.79	50.54	74.00	-23.46	Peak	HORIZONTAL

Note:

1. Result Level = Read Level + Antenna Factor + Cable loss + Filter Factor - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. For emission above 1GHz that over the limit are fundamental.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 3#

D:\E3 6.111\2022 Report Data\Q22092912-2E\FCC ABOVE
1G .EM6

Test Date : 2022-10-17

Tested By : Bairong

EUT : In-House Bluetooth Speaker

Model Number : EDF286001

Power Supply : AC 120V/60Hz


Test Mode : Tx Mode

Condition : Temp:23.7°C,Humi:63.1%,Press:100.3kPa

Antenna/Distance : 2021 BBHA 9120D 3#/3m/VERTICAL

Memo : BLE 1M 2480

Data: 27



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Filter Factor (dB)	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	4200.00	48.34	31.26	40.24	2.21	2.07	43.64	74.00	-30.36	Peak	VERTICAL
2	6180.00	46.14	34.43	40.36	3.12	2.70	46.03	74.00	-27.97	Peak	VERTICAL
3	8940.00	44.25	38.24	39.89	3.32	2.19	48.11	74.00	-25.89	Peak	VERTICAL
4	12000.00	44.61	39.20	40.10	4.05	2.40	50.16	74.00	-23.84	Peak	VERTICAL
5	14295.00	42.65	39.90	39.67	4.42	2.82	50.12	74.00	-23.88	Peak	VERTICAL
6	17940.00	38.63	42.13	40.66	4.94	3.77	48.81	74.00	-25.19	Peak	VERTICAL

Note:

1. Result Level = Read Level + Antenna Factor + Cable loss + Filter Factor - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. For emission above 1GHz that over the limit are fundamental.

9. RF Conducted Spurious Emissions

9.1. Block diagram of test setup

Same as section 4.1

9.2. Limits

In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

9.3. Test procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

Center frequency	Test frequency
RBW:	100 kHz
VBW:	300 kHz
Span	Wide enough to capture the peak level of the in-band emission
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.

(4) Set the spectrum analyzer as follows:

RBW:	100 kHz
VBW:	300 kHz
Span	Encompass frequency range to be measured
Number of measurement points	$\geq \text{span}/\text{RBW}$
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band.


Note:

- 1.The attenuator loss was inputted into spectrum analyzer as amplitude offset.
- 2.The pathloss of external cable: 0.5dB (According to the manufacturer's claims).


9.4. Test result

Mode	Freq. (MHz)	Verdict
BLE_1M	2402	Pass
	2440	Pass
	2480	Pass


9.5. Original test data




BLE 1M Ant1_2402_1000~26500




BLE 1M Ant1_2440_0~Reference




BLE 1M Ant1_2440_30~1000





10. Emissions in Restricted Frequency Bands

10.1. Block diagram of test setup



10.2. Limit

All restriction band should comply with 15.209, other emission should be at least 20dB below the fundamental.

10.3. Test procedure

- Same with clause 8.3 except change investigated frequency range from 2310 MHz to 2410 MHz and 2475 MHz to 2500 MHz.

Remark: All restriction band have been tested, and only the worst case is shown in report.


10.4. Test result

Pass. (See below detailed test result)

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 3#D:\E3 6.111\2022 Report Data\Q22092912-2E\FCC ABOVE
1G .EM6**Test Date** : 2022-10-17**Tested By** : Bairong**EUT** : In-House Bluetooth Speaker**Model Number** : EDF286001**Power Supply** : AC 120V/60Hz**Test Mode** : Tx Mode**Condition** : Temp:23.7°C,Humi:63.1%,Press:100.3kPa**Antenna/Distance** : 2021 BBHA 9120D 3#/3m/HORIZONTAL**Memo** : BLE 1M 2402

Data: 18



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Filter Factor (dB)	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	2333.80	50.25	27.30	39.57	1.69	0.72	40.39	74.00	-33.61	Peak	HORIZONTAL
2	2390.00	50.40	27.40	39.60	1.71	0.72	40.63	74.00	-33.37	Peak	HORIZONTAL

Note:

1. Result Level = Read Level + Antenna Factor + Cable loss + Filter Factor - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. For emission above 1GHz that over the limit are fundamental.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 3#

D:\E3 6.111\2022 Report Data\Q22092912-2E\FCC ABOVE
1G .EM6

Test Date : 2022-10-17

Tested By : Bairong

EUT : In-House Bluetooth Speaker

Model Number : EDF286001

Power Supply : AC 120V/60Hz


Test Mode : Tx Mode

Condition : Temp:23.7°C,Humi:63.1%,Press:100.3kPa

Antenna/Distance : 2021 BBHA 9120D 3#/3m/VERTICAL

Memo : BLE 1M 2402

Data: 19



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Filter Factor (dB)	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	2389.70	57.67	27.40	39.59	1.71	0.72	47.91	74.00	-26.09	Peak	VERTICAL
2	2390.00	54.00	27.40	39.60	1.71	0.72	44.23	74.00	-29.77	Peak	VERTICAL

Note:

1. Result Level = Read Level + Antenna Factor + Cable loss + Filter Factor - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. For emission above 1GHz that over the limit are fundamental.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 3#

D:\E3 6.111\2022 Report Data\Q22092912-2E\FCC ABOVE
1G .EM6

Test Date : 2022-10-17

Tested By : Bairong

EUT : In-House Bluetooth Speaker

Model Number : EDF286001

Power Supply : AC 120V/60Hz


Test Mode : Tx Mode

Condition : Temp:23.7°C,Humi:63.1%,Press:100.3kPa

Antenna/Distance : 2021 BBHA 9120D 3#/3m/HORIZONTAL

Memo : BLE 1M 2480

Data: 28



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Filter Factor (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	50.63	27.57	39.64	1.74	0.73	41.03	74.00	-32.97	Peak	HORIZONTAL
2	2483.88	52.63	27.57	39.64	1.74	0.73	43.03	74.00	-30.97	Peak	HORIZONTAL

Note:

1. Result Level = Read Level + Antenna Factor + Cable loss + Filter Factor - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. For emission above 1GHz that over the limit are fundamental.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 3#

D:\E3 6.111\2022 Report Data\Q22092912-2E\FCC ABOVE
1G .EM6

Test Date : 2022-10-17

Tested By : Bairong

EUT : In-House Bluetooth Speaker

Model Number : EDF286001

Power Supply : AC 120V/60Hz


Test Mode : Tx Mode

Condition : Temp:23.7°C,Humi:63.1%,Press:100.3kPa

Antenna/Distance : 2021 BBHA 9120D 3#/3m/VERTICAL

Memo : BLE 1M 2480

Data: 29




Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Filter Factor (dB)	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	49.09	27.57	39.64	1.74	0.73	39.49	74.00	-34.51	Peak	VERTICAL
2	2483.83	49.72	27.57	39.64	1.74	0.73	40.12	74.00	-33.88	Peak	VERTICAL

Note:

1. Result Level = Read Level + Antenna Factor + Cable loss + Filter Factor - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. For emission above 1GHz that over the limit are fundamental.

11. Power Line Conducted Emission

11.1. Block diagram of test setup



11.2. Power line conducted emission limits

Frequency	Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150 kHz ~ 500 kHz	66 ~ 56*	56 ~ 46*
500 kHz ~ 5 MHz	56	46
5 MHz ~ 30 MHz	60	50

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

11.3. Test procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

Configuration EUT to simulate typical usage as described in clause 2.4 and test setup as described in clause 11.1 of this report.

All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

11.4. Test result

Pass. (See below detailed test result)

Note1: All emissions not reported below are too low against the prescribed limits.

Note2: “---” means Peak detection; “---” means Average detection

Note3: Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/60Hz, recorded worse case.

For SHENZHEN HUAKESHENG DIGITAL TECHNOLOGY CO.,LTD' power supply: TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room

D:\2022 CE report date\Q22092912-2E\FCC.EM6

Test Date : 2022-10-18

Tested By : Bairong

EUT : In-House Bluetooth Speaker

Model Number : EDF286001

Power Supply : AC 120V/60Hz


Test Mode : TX

Condition : TEMP:24.3°C, RH:53.0%, BP:101.0kPa

LISN : 2021 1# ENV216/LINE

Memo : BLE 1M (HUAKESHENG)

Data: 6



Item	Freq.	Read Level	LISN Factor	Cable Loss	Pulse Limiter Factor	Result Level	Limit Line	Over Limit	Detector	Phase
(Mark)	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV)	(dBuV)	(dB)		
1	0.40	11.39	9.65	0.02	9.91	30.97	57.77	-26.80	QP	LINE
2	0.40	10.60	9.65	0.02	9.91	30.18	47.77	-17.59	Average	LINE
3	0.81	11.49	9.54	0.03	9.90	30.96	56.00	-25.04	QP	LINE
4	0.81	9.52	9.54	0.03	9.90	28.99	46.00	-17.01	Average	LINE
5	0.85	15.05	9.56	0.03	9.90	34.54	56.00	-21.46	QP	LINE
6	0.85	-2.05	9.56	0.03	9.90	17.44	46.00	-28.56	Average	LINE
7	1.22	8.00	9.57	0.03	9.89	27.49	56.00	-28.51	QP	LINE
8	1.22	6.50	9.57	0.03	9.89	25.99	46.00	-20.01	Average	LINE
9	2.02	-0.51	9.50	0.04	9.89	18.92	56.00	-37.08	QP	LINE
10	2.02	-6.12	9.50	0.04	9.89	13.31	46.00	-32.69	Average	LINE
11	28.76	-1.74	9.69	0.20	10.00	18.15	60.00	-41.85	QP	LINE
12	28.76	-7.39	9.69	0.20	10.00	12.50	50.00	-37.50	Average	LINE

Note:

1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room

D:\2022 CE report date\Q22092912-2EIFCC.EM6

Test Date : 2022-10-18

Tested By : Bairong

EUT : In-House Bluetooth Speaker

Model Number : EDF286001

Power Supply : AC 120V/60Hz


Test Mode : TX

Condition : TEMP:24.3°C, RH:53.0%, BP:101.0kPa

LISN : 2021 1# ENV216/NEUTRAL

Memo : BLE 1M (HUAKESHENG)

Data: 8



Item	Freq.	Read Level	LISN Factor	Cable Loss	Pulse Limiter Factor	Result Level	Limit Line	Over Limit	Detector	Phase
(Mark)	(MHz)	(dBμV)	(dB)	(dB)	(dB)	(dBμV)	(dBμV)	(dB)		
1	0.40	11.27	9.57	0.02	9.91	30.77	57.77	-27.00	QP	NEUTRAL
2	0.40	10.62	9.57	0.02	9.91	30.12	47.77	-17.65	Average	NEUTRAL
3	0.81	11.18	9.76	0.03	9.90	30.87	56.00	-25.13	QP	NEUTRAL
4	0.81	9.64	9.76	0.03	9.90	29.33	46.00	-16.67	Average	NEUTRAL
5	0.85	13.96	9.75	0.03	9.90	33.64	56.00	-22.36	QP	NEUTRAL
6	0.85	-3.55	9.75	0.03	9.90	16.13	46.00	-29.87	Average	NEUTRAL
7	1.22	7.78	9.67	0.03	9.89	27.37	56.00	-28.63	QP	NEUTRAL
8	1.22	6.21	9.67	0.03	9.89	25.80	46.00	-20.20	Average	NEUTRAL
9	2.02	0.14	9.60	0.04	9.89	19.67	56.00	-36.33	QP	NEUTRAL
10	2.02	-4.22	9.60	0.04	9.89	15.31	46.00	-30.69	Average	NEUTRAL
11	28.15	-0.65	9.88	0.20	9.99	19.42	60.00	-40.58	QP	NEUTRAL
12	28.15	-6.41	9.88	0.20	9.99	13.66	50.00	-36.34	Average	NEUTRAL

Note:

1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

For LianGang Optoelectronic Technology Co.,Ltd.' power supply: TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room

D:\2022 CE report

date\Q22092912-2E-EDF100063\FCC2.EM6

Test Date : 2022-11-28

Tested By : James Gan

EUT : In-House Bluetooth Speaker

Model Number : EDF286001

Power Supply : AC 120V/60Hz


Test Mode : TX

Condition : TEMP:21.2°C, RH:53.3%, BP:100.2kPa

LISN : 2021 1# ENV216/NEUTRAL

Memo : BLE 1M (LianGang)

Data: 4



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBμV)	Limit Line (dBμV)	Over Limit (dB)	Detector	Phase
1	0.39	11.78	9.58	0.02	9.91	31.29	58.03	-26.74	QP	NEUTRAL
2	0.39	9.10	9.58	0.02	9.91	28.61	48.03	-19.42	Average	NEUTRAL
3	0.63	2.44	9.70	0.02	9.91	22.07	56.00	-33.93	QP	NEUTRAL
4	0.63	-8.36	9.70	0.02	9.91	11.27	46.00	-34.73	Average	NEUTRAL
5	1.17	0.30	9.68	0.03	9.89	19.90	56.00	-36.10	QP	NEUTRAL
6	1.17	-2.31	9.68	0.03	9.89	17.29	46.00	-28.71	Average	NEUTRAL
7	3.90	-1.33	9.79	0.06	9.92	18.44	56.00	-37.56	QP	NEUTRAL
8	3.90	-6.61	9.79	0.06	9.92	13.16	46.00	-32.84	Average	NEUTRAL
9	7.69	2.94	9.65	0.09	9.94	22.62	60.00	-37.38	QP	NEUTRAL
10	7.69	-2.47	9.65	0.09	9.94	17.21	50.00	-32.79	Average	NEUTRAL
11	28.15	-1.16	9.88	0.20	9.99	18.91	60.00	-41.09	QP	NEUTRAL
12	28.15	-6.50	9.88	0.20	9.99	13.57	50.00	-36.43	Average	NEUTRAL

Note:

1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room

D:\2022 CE report

date\Q22092912-2E-EDF100063\FCC2.EM6

Test Date : 2022-11-28

Tested By : James Gan

EUT : In-House Bluetooth Speaker

Model Number : EDF286001

Power Supply : AC 120V/60Hz


Test Mode : TX

Condition : TEMP:21.2°C, RH:53.3%, BP:100.2kPa

LISN : 2021 1# ENV216/LINE

Memo : BLE 1M (LianGang)

Data: 8



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBμV)	Limit Line (dBμV)	Over Limit (dB)	Detector	Phase
1	0.39	11.55	9.65	0.02	9.91	31.13	58.03	-26.90	QP	LINE
2	0.39	8.83	9.65	0.02	9.91	28.41	48.03	-19.62	Average	LINE
3	0.63	0.33	9.53	0.02	9.91	19.79	56.00	-36.21	QP	LINE
4	0.63	-6.56	9.53	0.02	9.91	12.90	46.00	-33.10	Average	LINE
5	1.54	6.95	9.54	0.04	9.89	26.42	56.00	-29.58	QP	LINE
6	1.54	4.60	9.54	0.04	9.89	24.07	46.00	-21.93	Average	LINE
7	3.53	-0.73	9.58	0.05	9.91	18.81	56.00	-37.19	QP	LINE
8	3.53	-9.20	9.58	0.05	9.91	10.34	46.00	-35.66	Average	LINE
9	7.77	-0.65	9.50	0.09	9.94	18.88	60.00	-41.12	QP	LINE
10	7.77	-5.70	9.50	0.09	9.94	13.83	50.00	-36.17	Average	LINE
11	28.00	-0.14	9.68	0.20	9.99	19.73	60.00	-40.27	QP	LINE
12	28.00	-5.35	9.68	0.20	9.99	14.52	50.00	-35.48	Average	LINE

Note:

1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

12. Antenna Requirements

12.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

For intentional device, according to RSS-Gen issue 5 section 6.8.

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

12.2. Result

The antenna used for this product is PCB antenna and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is -0.29 dBi.

14. Photos of the EUT

Please refer to Appendix I: Photos of the EUT.

END OF REPORT