



## RF EXPOSURE REPORT

<b>Applicant</b>	:	Edifier International Limited
<b>Address of Applicant</b>	:	P.O. Box 6264 General Post Office, Hong Kong
<b>Manufacturer</b>	:	Beijing Edifier Technology Co., Ltd.
<b>Address of Manufacturer</b>	:	815, Floor 8, Shuangqiao Building, No.68, North Fourth Ring West Road, Haidian District, 100080 Beijing, P.R. China
<b>Equipment under Test</b>	:	Tabletop Wireless Speaker
<b>Model No.</b>	:	EDF286006
<b>FCC ID</b>	:	Z9G-EDF253
<b>Test Standard(s)</b>	:	KDB447498 D01 General RF Exposure Guidance v06
<b>Report No.</b>	:	DDT-RE24062510-1E05
<b>Issue Date</b>	:	2024/08/22
<b>Issue By</b>	:	Guangdong Dongdian Testing Service Co., Ltd. Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

# REPORT

## Table of Contents

1.	General Test Information.....	5
1.1.	Description of EUT.....	5
1.2.	Accessories of EUT .....	5
1.3.	Test laboratory .....	5
2.	RF Exposure evaluation for FCC.....	6
2.1.	Assessment procedure .....	6
2.2.	Assess result.....	7
3.	Photos of the EUT .....	8

## Test Report Declare

<b>Applicant</b>	:	Edifier International Limited
<b>Address of Applicant</b>	:	P.O. Box 6264 General Post Office, Hong Kong
<b>Equipment under Test</b>	:	Tabletop Wireless Speaker
<b>Model No.</b>	:	EDF286006
<b>Manufacturer</b>	:	Beijing Edifier Technology Co., Ltd.
<b>Address of Manufacturer</b>	:	815, Floor 8, Shuangqiao Building, No.68, North Fourth Ring West Road, Haidian District, 100080 Beijing, P.R. China

**Test Standard Used:**

KDB447498 D01 General RF Exposure Guidance v06

**We Declare:**

The equipment described above is tested by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

<b>Report No.:</b>	DDT-RE24062510-1E05		
<b>Date of Receipt:</b>	2024/06/28	<b>Date of Test:</b>	2024/07/09~2024/08/21

**Prepared By:**

  
\_\_\_\_\_  
Jacky Huang/Engineer

**Approved By:**

  
\_\_\_\_\_  
Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

## Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	2024/08/22	

## 1. General Test Information

### 1.1. Description of EUT

EUT Name	:	Tabletop Wireless Speaker
Model Number	:	EDF286006
EUT Function Description	:	Please reference user manual of this device
Power Supply	:	100-240V~ 50/60Hz 600mA, DC 7.4V is powered by a built-in lithium battery.
Radio Specification	:	Bluetooth (BDR/EDR/LE), 2.4G WLAN: IEEE 802.11g/n20, 5G WLAN: IEEE 802.11 n HT20
Operation Frequency	:	Bluetooth: 2402 MHz-2480 MHz 2.4G WLAN: 2412 MHz-2462 MHz 5G WLAN: 5180MHz-5240MHz, 5260MHz-5320MHz, 5500MHz-5720MHz, 5745MHz-5825MHz
Modulation	:	Bluetooth: GFSK, $\pi/4$ -DQPSK, 8DPSK IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna information		
Antenna Type	:	FPC Antenna
Max Antenna Gain (dBi)	:	Bluetooth: 1.2 2.4G WLAN: 2.1 5G WLAN: 2.0

Note: The above EUT information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications or User's Manual. The above Antenna information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

### 1.2. Accessories of EUT

Accessories	Manufacturer	Model number	Description
/	/	/	/

### 1.3. Test laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: [ddt@dgddt.com](mailto:ddt@dgddt.com).

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

## 2. RF Exposure evaluation for FCC

### 2.1. Assessment procedure

#### Requirement:

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100000			1.0	30

Note: f= frequency in MHz; \*Plane-wave equivalent power density

#### Calculation method

$$E(V/m) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } S(mW/cm^2) = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = Peak RF output power (mW)

**G** = EUT Antenna numeric gain (numeric)=

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

We can change the formula to:

$$S = \frac{30 \times P \times G}{377 \times d^2} \quad \text{or, } d = \sqrt{\frac{30 \times P \times G}{377 \times S}}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2 m, as well as the gain of the used antenna, the RF power density can be obtained.

## 2.2. Assess result

Mode	Output power (dBm)	Output power (mW)	tune up power (dBm)	tune up power (mW)	Antenna Gain (dBi)	Antenna Gain (linear)	MPE Values (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
BDR/EDR	10.85	12.16	12	15.85	1.2	1.32	0.004	1
BLE	7.96	6.25	9	7.94	1.2	1.32	0.002	1
2.4G WIFI	14.32	27.04	15	31.62	2.1	1.62	0.010	1
5G WIFI	14.07	25.53	15	31.62	2.0	1.58	0.010	1

Simultaneous transmit evaluation result (worst case):  $0.004/1+0.01/1=0.014<1$ .

Note 1: The estimation distance is 20 cm

Note 2: EUT does not support 2.4G WIFI and 5 G WIFI simultaneous transmit.

Conclusion: MPE evaluation required since transmitter power is below FCC threshold

### 3. Photos of the EUT

Please refer to DDT-Q24062510-2E appendix I

-----End Report-----