



RF EXPOSURE REPORT

Applicant	:	Edifier International Limited
Address of Applicant	:	P.O. Box 6264 General Post Office, Hong Kong
Manufacturer	:	Beijing Edifier Technology Co., Ltd.
Address of Manufacturer	:	815, Floor 8, Shuangqiao Building, No.68, North Fourth Ring West Road, Haidian District, 100080 Beijing, P.R. China
Equipment under Test	:	Portable Bluetooth Speaker
Model No.	:	EDF100094
FCC ID	:	Z9G-EDF285
Test Standard(s)	:	KDB447498 D01 General RF Exposure Guidance v06
Report No.	:	DDT-RE25030323-1E03
Issue Date	:	2025/04/02
Issue By	:	Guangdong Dongdian Testing Service Co., Ltd. Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

REPORT

Table of Contents

1. General Test Information.....5

1.1. Description of EUT.....5

1.2. Accessories of EUT5

1.3. Test laboratory5

2. RF Exposure evaluation for FCC.....6

2.1. Assessment procedure6

2.2. Assess result.....7

Test Report Declare

Applicant	:	Edifier International Limited
Address of Applicant	:	P.O. Box 6264 General Post Office, Hong Kong
Equipment under Test	:	Portable Bluetooth Speaker
Model No.	:	EDF100094
Manufacturer	:	Beijing Edifier Technology Co., Ltd.
Address of Manufacturer	:	815, Floor 8, Shuangqiao Building, No.68, North Fourth Ring West Road, Haidian District, 100080 Beijing, P.R. China

Test Standard Used:

KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is tested by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

Report No.:	DDT-RE25030323-1E03		
Date of Receipt:	2025/03/05	Date of Test:	2025/03/05~2025/03/31

Created: Zoe Peng	Reviewed: Ella Gong	Approved: Damon Hu
		
2025/04/02	2025/04/02	2025/04/02

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

Version	Revision Content	Issue Date	Approved
---	Initial issue	2025/04/02	

1. General Test Information

1.1. Description of EUT

EUT Name	: Portable Bluetooth Speaker
Model Number	: EDF100094
EUT Function Description	: Please reference user manual of this device
Power Supply	: DC 5V is powered by type-C port, or DC 7.4V is powered by a built-in lithium battery
Radio Specification	: Bluetooth BR/EDR/LE
Operation Frequency	: 2402 MHz to 2480 MHz
Modulation	: GFSK, $\pi/4$ -DQPSK
Antenna Type	: PCB antenna
Max Antenna Gain (dBi)	: 2.59

Note: The above EUT information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications or User's Manual.

1.2. Accessories of EUT

Accessories	Manufacturer	Model number	Description
/	/	/	/

1.3. Test laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20240, G-20118

2. RF Exposure evaluation for FCC

2.1. Assessment procedure

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances $\leq$ 50 mm are determined by:

$$\left[\frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where:}$$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

2.2. Assess result

BR/EDR

Mode	Antenna	Frequency [MHz]	Target (dBm)	Tolerance ±(dB)
GFSK (Peak)	Ant1	2402	-0.97	1.5
		2441	-0.99	1.5
		2480	-1.43	1.5
π/4DQPSK (Peak)	Ant1	2402	-0.47	1.5
		2441	-0.62	1.5
		2480	-0.73	1.5

BLE

Mode	Antenna	Frequency [MHz]	Target (dBm)	Tolerance ±(dB)
BLE_1M (Peak)	Ant1	2402	1.43	1.5
		2440	1.57	1.5
		2480	1.28	1.5
BLE_2M (Peak)	Ant1	2404	1.60	1.5
		2440	1.62	1.5
		2478	1.42	1.5

Manufacturing Tolerance:

Estimation Result:

Worse case is as below: [2440 MHz, 3.12 dBm, (2.051 mW) output power]

$(2.051/5) \cdot [\sqrt{2.440(\text{GHz})}] = 0.641 < 3.0$ for 1-g SAR

Then SAR evaluation is not required.

-----End Report-----