

EDIFIER

Active Speaker system
B8 Soundbar

HDMI

The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. in the United States and other countries. This sentence may be translated into local languages upon approval by HDMI Licensing Administrator, Inc.

-2 , 0 , +2
-4 +4
-6 +6
Bass
Pair
Status indicator

The soundbar has been paired with the subwoofer before leaving the factory. Hence the wireless connection will resume automatically when both soundbar and subwoofer are powered on and the red indicator is lit. If the wireless connection fails to resume, please follow the steps below to re-pair.

1. Power on the subwoofer, the red indicator should blink in a breathing pattern, which means no active wireless connection.
2. Use paper clip or the similar tool to press and hold the "Pair" button on back panel of the subwoofer for 2 seconds to put it into pairing mode. The red indicator will blink rapidly.
3. Press and hold the "Pair" button on back panel of soundbar to put it into pairing mode.
4. Wait until the red indicator on subwoofer is lit constantly. Then the pairing is complete and wireless connection is made.

FCC statement:
"This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation."
IC statement:
CAN ICES-3(B)/NMB-3(B).
Contains FCC ID: Z9G-EDF54
Contains IC: 10004A-EDF54

ON
OFF

100-240V~
50/60Hz
450mA



Edifier International Limited
Made in China

丝印PAN 425C
底面喷黑色沙纹漆

A1: 增加北美认证

物料名称	物料编码	版本
B8后面板出口	MP-001-B00080-01	V1.1

文件编号	EDF/JS-TSY-	版次 A1
文件名称	B8后面板出口	
绘 制		
审 核		
批 准		