



1) How does this device operate?

Input Through the audio and Powered from AC adapter

2) Provide information on the device and antenna?

The transmitters antenna is External antenna, this is fixed by reversed thread connector and meets the requirements of this section.

3) How is it installed?

Power by DC 12V via AC adapter.

4) What test procedure was used?

Operating condition is according to ANSI C63.4-2003.

5) Was the tuning range properly verified?

The test lab should indicate in the report that the tuning controls were manually adjusted to verify maximum tuning range. EUT was adjusted to work at selected channels: 88.1MHz, 98.0MHz, and 107.9MHz. The EUT will not allow operation below 88.1MHz and will not allow operation above 107.9MHz.

6) Was the bandwidth properly tested with maximum audio input?

Emissions from the intentional radiator shall be confined within a band 200 kHz wide centered on the operation frequency. The 200 kHz band shall lie wholly within the frequency range of 88-108 MHz .Setup the EUT and simulators as shown in the report. Enable RF signal and confirm EUT active. Modulate output capacity of EUT up to specifications.

7) Provide the test report.

Test Report Submitted.

Signature: 

Name: Ronnie.Liu

Title: Project Manager

Telephone: +86-0755-26648642

Email: Ronnie.Liu@estcl.com

Date: Jan. 05, 2012