

Modular approval Declaration letter

We, 8devices apply single modular approval for

Product Name: Komikan

Model: **Komikan** FCC ID: **Z9W-KOM**

According to 996369 D01 Module Equip Auth Guide v01r04 and 15.212 requirements:

1) The radio elements must have the radio frequency circuitry shielded. Physical components and tuning capacitor(s) may be located external to the shield, but must be on the module assembly;

Answer: Yes, the radio elements shielded by cover. The cover is metal.

- 2) The module must have buffered modulation/data inputs to ensure that the device will comply with Part 15 requirements with any type of input signal;

 Answer: Yes, all inputs to the modules are buffered through logic or microprocessor inputs.
- 3) The modular transmitter must have its own power supply regulation. *Answer: Yes, A low drop out regulator is used for modular power supply regulation.*
- 4) The module must contain a permanently attached antenna, or contain a unique antenna connector, and be marketed and operated only with specific antenna(s), per Sections 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b); Answer: Yes, Device has permanently attached ceramic chip antenna, version without antenna has unique HSC connector.
- 5) The module must demonstrate compliance in a stand-alone configuration; Answer: Yes, the module demonstrates compliance in a stand-alone configuration.
- 6) The module must be labelled with its permanently affixed FCC ID label, or use an electronic display (See KDB Publication 784748 about labelling requirements); Answer: Yes, the module has a permanent fixed label, and below statement was listed in the User's Manual. The host device must be labelled to display the FCCID of the module Contains Z9W-JLP
- 7) The module must comply with all specific rules applicable to the transmitter including all the conditions provided in the integration instructions by the grantee; Answer: Yes, the module complies with all specific rules applicable to the transmitter including all the conditions provided in the integration instructions by the grantee, refer to test report and user manual.



8) The module must comply with RF exposure requirements Answer: Yes, Transmitter meets MPE calculation of 47 CFR 1.1307. Refer to MPE Reports and Refer to modular installation manual

Dated:	2020-05-12	
Ву:	M	Jonas Sabaliauskas
	✓ Signature	Printed
Title: D	irector	
On beha	If of: 8devices	
Telephor	ne: +37061444116	