

Model version	B.7
---------------	-----

1		2		3		4	
Remarks & Symbols + S CTS dimension (Critical to Safety) = Process capability (Cpk) ≥ 1,67 + Q CTQ dimension (Critical to Quality) = Process capability (Cpk) ≥ 1,33				A			
				B			
				C			
TEXT 1 FONT: ARIAL HEIGHT: 1mm COLOR: BLACK TEXT 2 FONT: ARIAL HEIGHT: 1mm COLOR: BLACK 'CE' PICTOGRAM ±7x5mm COLOR: BLACK TEXT 3 FONT: ARIAL HEIGHT: 1mm COLOR: BLACK 'WEEE' PICTOGRAM ±4.3x6mm COLOR: BLACK UKCA PICTOGRAM 5.0x5.0mm COLOR: BLACK 'RCM' PICTOGRAM ±6.7x5mm COLOR: BLACK 'MIC' PICTOGRAM ±7.5x5mm COLOR: BLACK TEXT 1: TK Home Solutions BV van Utrechtweg 99 2921 LN Krimpen a/d IJssel NL TEXT 2: M/N: 1122596 Rating: 24VDC 50mA FCC ID:ZAH-1122596 IC: 27285-1122596 TEXT 3: 202-XXXXXX NOTE: - MATERIAL: POLYESTER CLEAR GLOSS, SELF ADHESIVE B432 (SEE SPECIFICATION D04435)				D			
E							
General edge acc. to ISO 13715 Tolerancing acc. to N.A. Geom. tol. acc. to N.A. Dim tol. acc. to N.A. Scale 1:1 Units: mm Format A4 Created by Christiaan Beij Creation date 22-Apr-22 Modified by Dennis Willard Modified date 23-Aug-22 04:07:48 PM CE LABEL CALL DEVICE Drawing number 1161456 Drw revision B Sheet 1 of 1 Lifecycle state Tooling Iteration 6				F			