

Shenzhen Certification Technology Service Co., Ltd. 2F, Building B, East Area of Nanchang Second Industrial Zone, Gushu 2nd Road, Bao'an District, Shenzhen 518126, P.R. China

TEST REPORT

FCC ID: ZAY-Z-B50

Applicant: SHENZHEN ZONOKI DIGITAL TECHNOLOGY CO., LTD

Address: 1-3 Floor, Building B, NO.49, Shangxia Road, Henggang Street,

Shenzhen, Guangdong, China

Equipment Under Test (EUT):

Name : Stereo Bluetooth Headset

Model : Z-B50

In Accordance with: FCC 15.247

Report No : STE120614760

Date of Test : June 20-29, 2012

Date of Issue : June 29,2012

Test Result: PASS

In the configuration tested, the EUT complied with the standards specified above

Authorized Signature

(Mark Zhu)

General Manager

The manufacture should ensure that all the products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of Shenzhen Certification Technology Service Co., Ltd. Or test done by Shenzhen Certification Technology Service Co., Ltd. Approvals in connection with, distribution or use of the product described in this report must be approved by Shenzhen Certification Technology Service Co., Ltd. Approvals in writing.

FCC ID: ZAY-Z-B50 Page 1 of 62

Contents

1.	Gen	eral Informationeral	4
	1.1.	Description of Device (EUT)	4
	1.2.	Accessories of device (EUT)	4
	1.3.	Test Lab information	4
2.	Sum	mary of test	5
	2.1.	Summary of test result	5
	2.2.	Assistant equipment used for test	5
	2.3.	Block Diagram	5
	2.4.	Test mode	6
	2.5.	Test Conditions	6
	2.6.	Measurement Uncertainty (95% confidence levels, k=2)	6
		Test Equipment	
3.	Max	ximum Peak Output power	8
	3.1.	Limit	8
		Test Procedure	
	3.3.	Test Result	8
4.		B bandwidth	
		Limit	
		Test Procedure	
		Test Result	
5.		rier Frequency Separation	
		Limit	
		Test Procedure	
		Test Result	
6.		nber Of Hopping Channel	
		Limit	
		Test Procedure	
		Test Result	
7.	Dwe	ell Time	
	7.1.	2 0 0 111111	
	7.2.	Test Procedure	17
		Test Results	
8.		iated emissions	
	8.1.	Limit	
	8.2.	Block Diagram of Test setup	
		Test Procedure	
		Test Result	
9.		d Edge Compliance	
		Block Diagram of Test Setup	
		Limit	
		Test Procedure	
		Test Result	
10.	Pow	er Line Conducted Emissions	50

Report No.: STE120614760

	10.1. Block Diagram of Test Setup	50
	10.2. Limit	
	10.3. Test Procedure	
	10.4. Test Result	
11.	Antenna Requirements	53
	11.1. Limit	
	11.2. Result.	53
12.	Test setup photo	54
	Photos of EUT	

Report No.: STE120614760

1. General Information

1.1. Description of Device (EUT)

EUT : Stereo Bluetooth Headset

Model No. : Z-B50

Power supply : DC 3.7V From battery

DC 5V From PC With AC 120V/60Hz

Radio : Bluetooth 2.1+ EDR

Technology

FCC Operation: 2402MHz -2480MHz

frequency

Modulation : GFSK, $\pi/4$ DQPSK, 8-DPSK

Antenna Type : Patch antenna, Gain: 3dBi

Applicant : SHENZHEN ZONOKI DIGITAL TECHNOLOGY CO., LTD

Address : 1-3 Floor, Building B, NO.49, Shangxia Road, Henggang

Street, Shenzhen, Guangdong, China

Manufacturer : SHENZHEN ZONOKI DIGITAL TECHNOLOGY CO., LTD

Address : 1-3 Floor, Building B, NO.49, Shangxia Road, Henggang

Street, Shenzhen, Guangdong, China

1.2. Accessories of device (EUT)

Accessories 1 : Audio cable M/N : 1m, unshield

Accessories 2 : USB cable

Type : 1m, unshield

1.3. Test Lab information

Shenzhen Certification Technology Service Co., Ltd. 2F, Building B, East Area of Nanchang Second Industrial Zone, Gushu 2nd Road, Bao'an District, Shenzhen 518126, P.R. China FCC Registered No.:197647

FCC ID: ZAY-Z-B50 Page 4 of 62

2. Summary of test

2.1. Summary of test result

Description of Test Item	Standard	Results
Maximum Peak Output Power	FCC Part 15: 15.247(b)(1) ANSI C63.10 :2009	PASS
20dB Bandwidth	FCC Part 15: 15.215 ANSI C63.10 :2009	PASS
Carrier Frequency Separation	FCC Part 15: 15.247(a)(1) ANSI C63.10 :2009	PASS
Number Of Hopping Channel	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10 :2009	PASS
Dwell Time	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10 :2009	PASS
Radiated Emission	FCC Part 15: 15.209 FCC Part 15: 15.247(d) ANSI C63.10 :2009	PASS
Band Edge Compliance	FCC Part 15: 15.247(d) ANSI C63.10 :2009	PASS
Power Line Conducted Emissions	FCC Part 15: 15.207 ANSI C63.10 :2009	PASS
Antenna requirement	FCC Part 15: 15.203	PASS
MPE ESTIMATION	FCC Part 2: 2.1093	PASS


2.2. Assistant equipment used for test

Description : Test PC 1

Manufacturer : Dell Model No. : D430

2.3. Block Diagram

1, For radiated emissions test: EUT was placed on a turn table, which is 0.8 meter high above ground. EUT was be set into BT test mode by Bluesuite software before test.



FCC ID: ZAY-Z-B50 Page 5 of 62

2, For Power Line Conducted Emissions Test: EUT was connected to power adapter by 1m USB line



2.4. Test mode

The test software "Bluesuite" was used to control EUT work in Continuous TX mode, and select test channel, wireless mode

Tested mode, channel, and data rate information				
Mode	Channel	Frequency		
		(MHz)		
	Low:CH1	2402		
BDR:GFSK	Middle: CH40	2441		
	High: CH79	2480		
	Low:CH1	2402		
EDR:π/4 QPSK	Middle: CH40	2441		
	High: CH79	2480		
	Low:CH1	2402		
EDR:8-DPSK	Middle: CH40	2441		
	High: CH79	2480		

Note: For $\pi/4$ QPSK its same modulation type with 8-DPSK, and based exploratory test, there is no significant difference of that two types test result, so except output power, all other items final test were only performed with 8-DPSK and GFSK.

2.5. Test Conditions

Temperature range	21-25℃
Humidity range	40-75%
Pressure range	86-106kPa

2.6. Measurement Uncertainty (95% confidence levels, k=2)

Item	MU	Remark
Uncertainty for Power point Conducted Emissions Test	2.42dB	
Uncertainty for Radiation Emission test in 3m	3.54dB	Polarize: V
chamber (30MHz to 1GHz)	4.1dB	Polarize: H
Uncertainty for Radiation Emission test in 3m	2.08dB	Polarize: H
chamber (1GHz to 25GHz)	2.56dB	Polarize: V

FCC ID: ZAY-Z-B50

Uncertainty for radio frequency	1×10-9	
Uncertainty for conducted RF Power	0.65dB	
Uncertainty for temperature	0.2℃	
Uncertainty for humidity	1%	
Uncertainty for DC and low frequency voltages	0.06%	

2.7. Test Equipment

Equipment	Manufacture	Model No.	Serial No.	Last cal.	Cal Interval
3m Semi-Anechoic	ETS-LINDGR EN	N/A	SEL0017	05.08, 2012	1Year
Spectrum analyzer	Agilent	E4443A	MY46185649	05.08, 2012	1Year
Receiver	R&S	ESCI	100492	05.08, 2012	1Year
Receiver	R&S	ESCI	101202	05.08, 2012	1Year
Bilog Antenna	Sunol	ЈВ3	A121206	12.15, 2011	1Year
Horn Antenna	EMCO	3115	640201028-06	12.15, 2011	1Year
Power Meter	Anritsu	ML2487A	6K00001491	05.08, 2012	1Year
ETS Horn Antenna	ETS	3160	SEL0076	05.08, 2012	1Year
Active Loop Antenna	Beijing Daze	ZN30900A	SEL0097	12.15, 2011	1Year
Cable	Resenberger	N/A	No.1	05.08, 2012	1Year
Cable	SCHWARZBE CK	N/A	No.2	05.08, 2012	1Year
Cable	SCHWARZBE CK	N/A	No.3	05.08, 2012	1Year
Pre-amplifier	R&S	AFS42-0010 1 800-25-S-42	SEL0081	05.08, 2012	1Year
Pre-amplifier	R&S	AFS33-1800 2650-30-8P- 44	SEL0080	05.08, 2012	1Year
Base station	Agilent	E5515C	GB44300243	05.08, 2012	1 Year
Temperature controller	Terchy	MHQ	120	05.08, 2012	1Year
Power divider	Anritsu	K240C	020346	05.08, 2012	1 Year
Signal Generator	HP	83732B	VS3449051	05.08, 2012	1 Year
Attenuator	Agilent	8491B	MY39262165	05.08, 2012	1 Year

FCC ID: ZAY-Z-B50

Report No.: STE120614760

3. Maximum Peak Output power

3.1. Limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts, the e.i.r.p shall not exceed 4W

3.2. Test Procedure

- (1). The EUT was placed on a 0.8m high table in the chamber and turned on in continuously transmitting mode.
- (2). The maximum fundamental emission (E) at 3m distance was measured and recorded with receive antenna in both vertical and horizontal by rotating the turntable and by moved up and down antenna, the test Spectrum Analyzer was set as below

RBW: 2MHz (>20dB bandwidth of signal)

VBW: 3MHz Detector: Peak

(3). Calculate the transmitter's peak power using the following equation:

$$P = [(E*D)^2]/(30G)$$

 \boldsymbol{E} is the measured maximum fundamental field strength in $\boldsymbol{V}/\boldsymbol{m}$

G is the numeric gain of the transmitting antenna with reference to an isotropic radiator.

D is the distance in meters from which the field strength was measured.

P is the power in watts

3.3. Test Result

EUT: Stereo Bluetooth Headset M/N:Z-B50						
Test date: 20	12-06-25	Test site: RF site	Tested b	y: TaTa jiang	<u> </u>	
Mode	Freq (MHz)	Maximum fundamental emission (E) at 3m (dBuV/m)	Result (dBm)	Limit (dBm)	Margin (dB)	
	2402	98.75	2.33	30	27.67	
GFSK	2441	98.94	2.45	30	27.55	
	2480	98.61	2.09	30	27.91	
	2402	98.28	1.82	30	28.18	
π/4 QPSK	2441	98.44	1.58	30	28.42	
	2480	98.62	2.06	30	27.94	
	2402	98.47	1.76	30	28.24	
8-DPSK	2441	98.43	1.91	30	28.09	
	2480	98.54	1.95	30	28.05	
Conclusion: I	Conclusion: PASS					

FCC ID: ZAY-Z-B50 Page 8 of 62

4. 20dB bandwidth

4.1. Limit

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

4.2. Test Procedure


The transmitter output was coupled to a spectrum analyzer via a antenna. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30kHz RBW and 100kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.


4.3. Test Result


EUT: Stereo Bluetooth Headset M/N:Z-B50					
Test date: 20	12-06-25	Test site: RF site	Tested by: TaTa jian	g	
Mode Freq (MHz)		20dB Bandwidth (MHz)	Limit (kHz)	Conclusion	
	2402	0.835	/	PASS	
GFSK	2441	0.845	/	PASS	
	2480	0.835	/	PASS	
	2402	1.330	/	PASS	
8-DPSK	2441	1.325	/	PASS	
	2480	1.305	/	PASS	


FCC ID: ZAY-Z-B50 Page 9 of 62

Orginal Test data For 20dB bandwidth GFSK









5. Carrier Frequency Separation

5.1. Limit


Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW


5.2. Test Procedure

The transmitter output was coupled to a spectrum analyzer via a antenna. The carrier frequency was measured by spectrum analyzer with 30kHz RBW and 100kHz VBW.

5.3. Test Result

EUT: Stereo Bluetooth Headset M/N:Z-B50					
Test date: 20	12-06-28	Test site: RF site	Tested by: TaTa jiang		
Mode	Channel separation (MHz)	20dB Bandwidth (MHz)	Limit (MHz) 2/3 20dB bandwidth	Conclusion	
GFSK	1.0	0.845	0.563	PASS	
8-DPSK	1.0	1.330	0.887	PASS	





Report No.: STE120614760

6. Number Of Hopping Channel

6.1. Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels


6.2. Test Procedure


The transmitter output was coupled to a spectrum analyzer via a antenna. The number of hopping channel was measured by spectrum analyzer with 300kHz RBW and 1MHz VBW.

6.3. Test Result

EUT: Stereo Bluetooth Headset M/N:Z-B50					
Test date: 2012-06-28 Test site: RF site Tested by: TaTa jiang					
Mode	Number of hopping channel	Limit	Conclusion		
GFSK	79	>15	PASS		
8-DPSK	79	>15	PASS		

Original test data for hopping channel number GFSK:





7. Dwell Time

7.1. Test limit

Please refer section 15.247

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz. The average time of occupancy on any frequency shall not greater than 0.4 s within period of 0.4 sec- onds multiplied by the number of hopping channel employed.

7.2. Test Procedure

- 7.2.1. Place the EUT on the table and set it in transmitting mode.
- 7.2.2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 7.2.3. Set center frequency of spectrum analyzer = operating frequency.
- 7.2.4. Set the spectrum analyzer as RBW, VBW=1MHz, Span = 0Hz, Sweep = auto.
- 7.2.5. Repeat above procedures until all frequency measured were complete.

7.3. Test Results

PASS.

A period time = 0.4 (s) * 79 = 31.6(s)

```
CH Low: DH1 time slot = 0.396 (ms) * (1600/(1*79)) * 31.6 = 253.4 (ms)

DH3 time slot = 1.630 (ms) * (1600/(3*79)) * 31.6 = 347.7 (ms)

DH5 time slot = 2.898 (ms) * (1600/(5*79)) * 31.6 = 370.9 (ms)

3-DH1 time slot = 0.404 (ms) * (1600/(1*79)) * 31.6 = 258.6(ms)
```

3-DH3 time slot =
$$1.658$$
 (ms) * $(1600/(3*79))$ * $31.6 = 353.7$ (ms)

3-DH5 time slot = 2.898 (ms) * (1600/(5*79)) * 31.6 = 370.9 (ms)

CH Mid: DH1 time slot =
$$0.396$$
 (ms) * $(1600/(1*79))$ * $31.6 = 253.4$ (ms)

DH3 time slot =
$$1.658 \text{ (ms)} * (1600/(3*79)) * 31.6 = 353.7 \text{ (ms)}$$

DH5 time slot =
$$2.898 \text{ (ms)} * (1600/(5*79)) * 31.6 = 370.9 \text{ (ms)}$$

3-DH1 time slot =
$$0.404$$
 (ms) * $(1600/(1*79))$ * $31.6 = 258.6$ (ms)

3-DH3 time slot =
$$1.658$$
 (ms) * $(1600/(3*79))$ * $31.6 = 353.7$ (ms)

3-DH5 time slot =
$$2.898 \text{ (ms)} * (1600/(5*79)) * 31.6 = 370.9 \text{ (ms)}$$

CH High: DH1 time slot =
$$0.390 \text{ (ms)} * (1600/(1*79)) * 31.6 = 249.6 \text{ (ms)}$$

DH3 time slot =
$$1.644$$
 (ms) * $(1600/(3*79))$ * $31.6 = 350.7$ (ms)

DH5 time slot =
$$2.898 \text{ (ms)} * (1600/(5*79)) * 31.6 = 370.9 \text{ (ms)}$$


3-DH1 time slot =
$$0.404$$
 (ms) * $(1600/(1*79))$ * $31.6 = 258.6$ (ms)

```
3-DH3 time slot = 1.658 (ms) * (1600/(3*79)) * 31.6 = 353.7 (ms)
```


3-DH5 time slot =
$$2.912$$
 (ms) * $(1600/(5*79))$ * $31.6 = 372.7$ (ms)

Detailed information please see the following page.


DH1: CH Low




DH1: CH Mid




DH1: CH High




DH3: CH Low:




DH3: CH Mid




DH3 CH High




DH5 CH Low




DH5 CH Mid




DH5 CH High




3-DH1: CH Low




3-DH1: CH Mid




3-DH1: CH High




3-DH3: CH Low




3-DH3: CH Mid




3-DH3: CH High




3-DH5: CH Low



3-DH5: CH Mid



3-DH5: CH High



8. Radiated emissions

8.1. Limit

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band


MHz	MHz MHz		GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

15.209 Limit


FREQUENCY		DISTANCE	FIELD STREN	NGTHS LIMIT	
MHz		Meters	μV/m	$dB(\mu V)/m$	
30 ~ 88		3	100	40.0	
88 ~ 216		3	150	43.5	
216 ~	960	3	200	46.0	
960 ~	1000	3	500	54.0	
Above	1000	3	74.0 dB(µV)/m (Peak)		
Hoove	1000	3	54.0 dB(μV)/m (Average)		

8.2. Block Diagram of Test setup

8.2.1. In 3m Anechoic Chamber Test Setup Diagram for below 1GHz



8.2.2. In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



Note: For harmonic emissions test a appropriate high pass filter was inserted in the input port of AMP.

8.3. Test Procedure

(1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber.

- (2) Setup EUT and simulator as shown in section 1.4 and 6.1
- (3) Test antenna was located 3m from the EUT on an adjustable mast. Below pre-scan procedure was first performed in order to find prominent radiated emissions.
- (a) Change work frequency or channel of device if practicable.
- (b) Change modulation type of device if practicable.
- (c) Change power supply range from 85% to 115% of the rated supply voltage for AC power supply.
- (d) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions
- (4) Spectrum frequency from 9KHz to 25GHz (tenth harmonic of fundamental frequency) was investigated
- (5) For final emissions measurements at each frequency of interest, the EUT were rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10 2009 on Radiated Emission test.
- (6) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RBW is set at 1MHz, VBW is set at 10Hz for Average measure.

8.4. Test Result

We have scanned the 5th harmonic from 9KHz to the EUT.

Detailed information please see the following page.

From 9KHz to 30MHz: Conclusion: PASS


Note: The amplitude of spurious emissions which are attenuated by more than 20d B below the permissible value has no need to be reported.

Page 30 of 62

FCC ID: ZAY-Z-B50



Shenzhen Certification Technology Service Co., Ltd 2F, Building B, East Area of Nanchang Second Industrial Zone Gushu 2nd Road, Bao'an District, Shenzhen 518126, P.R. China Tel: 4006786199 FAX: +86-755-26736857 Website: http://www.cessz.com/Email: Service@cessz.com/



Condition : FCC PART 15 B 3m POL: HORIZONTAL

EUI : Stereo Bluetooth Headset


Model No. : Z-B50
Test Mode : Tx Mode
Power : DC 3.7V
Test Engineer : Simple

Remark :

Item	Freq	Read Level	Antenna Factor	Preamp Factor	Cable Lose	Level	Limit	Margin	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dBuV	
1	143.49	48.05	13.64	28.90	1.10	33.89	43.50	-9.61	QP
2	282.20	56.56	12.41	29.15	1.84	41.66	46.00	-4.34	QP
3	421.88	53.32	15.28	29.45	2.58	41.73	46.00	-4.27	QP
4	568.35	49.79	17.70	29.75	3.14	40.88	46.00	-5.12	QP
5	635.28	47.23	18.92	29.80	3.27	39.62	46.00	-6.38	QP
6	804.06	44.95	20.73	29,65	3.61	39.64	46.00	-6.36	QP



Shenzhen Certification Technology Service Co., Ltd 2F, Building B, East Area of Nanchang Second Industrial Zone Gushu 2nd Road, Bao'an District, Shenzhen 518126, P.R. China Tel: 4006786199 FAX: +86-755-26736857 Website: http://www.cessz.com/Email: Service@cessz.com/



Condition : FCC PART 15 B 3m POL: VERTICAL

EUI : Stereo Bluetooth Headset


Model No. : Z-B50
Test Mode : Tx Mode
Power : DC 3.7V
Test Engineer : Simple

Remark :

Item	Freq	Read Level	Antenna Factor	Preamp Factor	Cable Lose	Level	Limit	Margin	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dBuV	
1	143.49	48.29	13.64	28.90	1.10	34.13	43.50	-9.37	QP
2	351.07	53.46	13.83	29.27	2.20	40.22	46.00	-5.78	QP
3	425.76	51.46	15.38	29.46	2.60	39.98	46.00	-6.02	QP
4	567.38	50.46	17.67	29.75	3.13	41.51	46.00	-4.49	QP
5	675.05	46.24	19.40	29.77	3.35	39.22	46.00	-6.78	QP
6	806.00	47.79	20.74	29.66	3.61	42.48	46.00	-3.52	QP



Shenzhen Certification Technology Service Co., Ltd. 2F, Building B, East Area of Nanchang Second Industrial Zone. Gushu 2nd Road, Bao'an District, Shenzhen 518126, P.R. China Tel: 4006786199 FAX: +86-755-26736857 Website http://www.cessz.com Email Service@cessz.com



: FCC PART 15 B Condition POL: HORIZONTAL 3m

EUT : Stereo Bluetooth Headset

Model No. : Z-B50 Test Mode

: Charge : DC 5V From PC With AC 120V/60Hz Power


Test Engineer : Simple

Remark

Item	Freq	Read Level	Antenna Factor	Preamp Factor	Cable Lose	Level	Limit	Margin	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dBuV	
1	212.36	51.97	10.18	29.03	1.46	34.58	43.50	-8.92	QP
2	284.14	54.62	12.45	29.16	1.85	39.76	46.00	-6.24	QP
3	351.07	51.41	13.83	29.27	2.20	38.17	46.00	-7.83	QP
4	426.73	52.00	15.38	29.46	2,61	40.53	46.00	-5.47	QP
5	568.35	47.06	17.70	29.75	3.14	38.15	46.00	-7.85	QP
6	729.37	44 90	20.02	29.71	3 46	38,67	46.00	-7 33	OP



Shenzhen Certification Technology Service Co., Ltd. 2F, Building B, East Area of Nanchang Second Industrial Zone. Gushu 2nd Road, Bao'an District, Shenzhen 518126, P.R. China Tel: 4006786199 FAX: +86-755-26736857 Website http://www.cessz.com Email Service@cessz.com



: FCC PART 15 B Condition POL: VERTICAL 3m

EUT : Stereo Bluetooth Headset

Model No. : Z-B50 Test Mode

: Charge : DC 5V From PC With AC 120V/60Hz Power

Test Engineer : Simple

Remark

Item	Freq	Read Level	Antenna Factor	Preamp Factor	Cable Lose	Level	Limit	Margin	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dBuV	
1	132.82	47.83	12.93	28.89	1.04	32.91	43.50	-10.59	QP
2	213.33	52.67	10.30	29.04	1.47	35.40	43.50	-8.10	QP
3	283.17	52.27	12.45	29.16	1.84	37.40	46.00	-8.60	QP
4	424.79	52.59	15.33	29.45	2,60	41.07	46.00	-4.93	QP
5	568.35	49.58	17.70	29.75	3.14	40.67	46.00	-5.33	QP
6	809.88	46.17	20.77	29.66	3.62	40.90	46.00	-5.10	QP

1GHz—25GHz Radiated emissison Test result											
EUT: Stereo Bluetooth Headset M/N:Z-B50											
Power: DC 3.7V											
Test	Test date: 2012-06-26 Test site: 3m Chamber Tested by: TaTa jiang										
Test	Test mode: GFSK Tx CH1 2402MHz										
Ante	enna pola	rity: Vertica	al								
No	Freq (MHz)	Read Level (dBuV/m)	Antenna Factor (dB/m)	Cable loss(d B)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/ m)	Margin (dB)	Remark		
1	2402	86.28	28.43	6.84	36.11	85.44	/	/	PK		
2	4804	42.14	34.25	10.56	35.34	51.61	74.00	22.39	PK		
3	4804	29.35	34.25	10.56	35.34	38.82	54.00	15.18	AV		
4	7206	/									
5	9608	/									
6	12010	/									
Ante	enna Pola	rity: Horizo	ontal								
1	2402	99.41	28.43	6.84	36.11	98.57	/	/	PK		
2	4804	42.28	34.25	10.56	35.34	51.75	74.00	22.25	PK		
3	4804	30.93	34.25	10.56	35.34	40.40	54.00	13.60	AV		
4	7206	/									
5	9608	/									
6	12010	/									
Note	j.										

Note:

- 1, Measuring frequency from 1GHz to 25GHz
- 2, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK
- 2, Spectrum Set for AV measure: RBW=1MHz, VBW=10Hz, Sweep time=Auto, Detector: PK
- 3, Result = Read level + Antenna factor + cable loss-Amp factor
- 4, All the other emissions not reported were too low to read and deemed to comply with FCC limit.

1GHz—25GHz Radiated emissison Test result										
EUT: Stereo Bluetooth Headset M/N:Z-B50										
Powe	r: DC 3.7	V								
Test date: 2012-06-26 Test site: 3m Chamber Tested by: TaTa jiang										
Test r	Test mode: GFSK Tx CH40 2441MHz									
Anter	na polari	ty: Vertical								
No	Freq (MHz)	Read Level (dBuV/m)	Antenna Factor (dB/m)	Cable loss(d B)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	
1	2441	86.97	28.53	6.86	36.18	86.18	/	/	PK	
2	4882	41.46	34.32	10.59	35.39	50.98	74.00	23.02	PK	
3	4882	29.13	34.32	10.59	35.39	38.65	54.00	15.35	AV	
4	7323	/								
5	9764	/								
6	12205	/								
Anten	nna Polari	ty: Horizon	tal							
1	2441	99.15	28.53	6.86	36.18	98.36	/	/	PK	
2	4882	42.56	34.32	10.59	35.39	52.08	74.00	21.92	PK	
3	4882	30.73	34.32	10.59	35.39	40.25	54.00	13.75	AV	
4	7323	/								
5	9764	/								
6	12205	/								

Note:

- 1, Measuring frequency from 1GHz to 25GHz
- 2, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK
- 2, Spectrum Set for AV measure: RBW=1MHz, VBW=10Hz, Sweep time=Auto, Detector: PK
- 3, Result = Read level + Antenna factor + cable loss-Amp factor
- 4, All the other emissions not reported were too low to read and deemed to comply with FCC limit.

	1GHz—25GHz Radiated emissison Test result										
EU'	Γ: Stereo	Bluetooth I	Headset	M/N	:Z-B50						
Pow	ver: DC 3	5.7V									
Tes	t date: 20	12-06-26	Test site	e: 3m C	hamber	Tested by	y: TaTa ji	ang			
Tes	t mode: C	GFSK Tx Cl	H79 2480	MHz							
Ant	enna pola	arity: Vertic	al								
No	Freq (MHz)	Read Level (dBuV/m)	Antenna Factor (dB/m)	Cable loss(d B)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remar k		
1	2480	87.38	28.59	6.89	35.21	87.65	/	/	PK		
2	4960	42.14	35.37	10.62	35.42	52.71	74.00	21.29	PK		
3	4960	30.92	35.37	10.62	35.42	41.49	54.00	12.51	AV		
4	7440	/									
5	9920	/									
6	12400	/									
Ant	enna Pol	arity: Horiz	ontal								
1	2480	99.15	28.59	6.89	35.21	99.42	/	/	PK		
2	4960	43.57	35.37	10.62	35.42	54.14	74.00	19.86	PK		
3	4960	30.86	35.37	10.62	35.42	41.43	54.00	12.57	AV		
4	7440	/									
5	9920	/									
6	12400	/									
NTak											

Note:

- 1, Measuring frequency from 1GHz to 25GHz
- 2, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK
- 2, Spectrum Set for AV measure: RBW=1MHz, VBW=10Hz, Sweep time=Auto, Detector: PK
- 3, Result = Read level + Antenna factor + cable loss-Amp factor
- 4, All the other emissions not reported were too low to read and deemed to comply with

FCC limit.

		1GH	Iz—25GH	Iz Radi	ated em	issison Test	t result		
EU'	Γ: Stereo	Bluetooth I	Headset	M/N	:Z-B50				
Pov	er: DC 3	.7V							
Tes	t date: 20	12-06-26	Test site	e: 3m C	hamber	Tested by	y: TaTa ji	ang	
Tes	t mode: 8	-DPSK Tx	CH1 240	2MHz			-		
Ant	enna pola	arity: Vertic	al						
No	Freq (MHz)	Read Level (dBuV/m)	Antenna Factor (dB/m)	Cable loss(d B)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/ m)	Margin (dB)	Remar k
1	2402	88.47	28.45	6.74	36.03	87.63	/	/	PK
2	4804	42.38	34.35	10.54	35.38	51.89	74.00	22.11	PK
3	4804	30.72	34.35	10.54	35.38	40.23	54.00	13.77	AV
4	7206	/							
5	9608	/							
6	12010	/							
Ant	enna Pola	arity: Horiz	ontal						
1	2402	99.62	28.45	6.74	36.03	98.78	/	/	PK
2	4804	43.36	34.35	10.54	35.38	52.87	74.00	21.13	PK
3	4804	30.79	34.35	10.54	35.38	40.30	54.00	13.70	AV
4	7206	/							
5	9608	/							
6	12010	/							
Not	e:								
1,M	easuring	frequency f	from 1GH	Iz to 25	GHz				
$2,S_1$	pectrum	Set for PK	measure	e: RBW	V=1MH:	z, VBW=1	MHz, Sv	veep time	e=Auto
Det	ector: PK								
$2,S_1$	pectrum	Set for AV	/ measur	e: RBV	V=1MF	Iz, VBW=	10Hz, Sv	veep time	e=Auto
Det	ector: PK								
1									

3,Result = Read level + Antenna factor + cable loss-Amp factor

4,All the other emissions not reported were too low to read and deemed to comply

with FCC limit.

	1GHz—25GHz Radiated emissison Test result									
EU'	EUT: Stereo Bluetooth Headset M/N:Z-B50									
Pow	Power: DC 3.7V									
Tes	Test date: 2012-06-26 Test site: 3m Chamber Tested by: TaTa jiang									
Tes	Test mode: 8-DPSK Tx CH40 2441MHz									
Ant	Antenna polarity: Vertical									
No	Freq (MHz)	Read Level (dBuV/m)	Antenna Factor (dB/m)	Cable loss(d B)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/ m)	Margin (dB)	Remar k	
1	2441	87.24	28.47	6.81	36.06	86.46	/	/	PK	
2	4882	41.71	34.48	10.60	35.40	51.39	74.00	22.61	PK	
3	4882	30.55	34.48	10.60	35.40	40.23	54.00	13.77	AV	
4	7323	/								
5	9764	/								
6	12205	/								
Ant	enna Pola	arity: Horize	ontal							
1	2441	99.77	28.47	6.81	36.06	98.99	/	/	PK	
2	4882	42.12	34.48	10.60	35.40	51.80	74.00	22.20	PK	
3	4882	30.59	34.48	10.60	35.40	40.27	54.00	13.73	AV	
4	7323	/								
5	9764	/								
6	12205	/								
Not	۵٠									

Note:

- 1, Measuring frequency from 1GHz to 25GHz
- 2, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK
- 2, Spectrum Set for AV measure: RBW=1MHz, VBW=10Hz, Sweep time=Auto, Detector: PK
- 3, Result = Read level + Antenna factor + cable loss-Amp factor
- 4, All the other emissions not reported were too low to read and deemed to comply with

FCC limit.


	1GHz—25GHz Radiated emissison Test result									
EUT:	EUT: Stereo Bluetooth Headset M/N:Z-B50									
Powe	Power: DC 3.7V									
Test c	Test date: 2012-06-26 Test site: 3m Chamber Tested by: TaTa jiang									
Test r	Test mode: 8-DPSK Tx CH79 2480MHz									
Anter	na polari	ty: Vertical								
No	Freq (MHz)	Read Level (dBuV/m)	Antenna Factor (dB/m)	Cable loss(d B)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/ m)	Margin (dB)	Remark	
1	2480	88.35	28.53	6.88	36.11	87.65	/	/	PK	
2	4960	42.07	35.07	10.64	35.44	52.34	74.00	21.66	PK	
3	4960	30.52	35.07	10.64	35.44	40.79	54.00	13.21	AV	
4	7440	/								
5	9920	/								
6	12400	/								
Anten	nna Polari	ty: Horizon	tal							
1	2480	99.84	28.53	6.88	36.11	99.14	/	/	PK	
2	4960	42.76	35.07	10.64	35.44	53.03	74.00	20.97	PK	
3	4960	30.31	35.07	10.64	35.44	40.58	54.00	13.42	AV	
4	7440	/								
5	9920	/								
6	12400	/								
Moto.										

Note:

- 1, Measuring frequency from 1GHz to 25GHz
- 2, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK
- 2, Spectrum Set for AV measure: RBW=1MHz, VBW=10Hz, Sweep time=Auto, Detector: PK
- 3, Result = Read level + Antenna factor + cable loss-Amp factor
- 4, All the other emissions not reported were too low to read and deemed to comply with FCC limit.

9. Band Edge Compliance

9.1. Block Diagram of Test Setup



9.2. Limit

All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz and 5725MHz to 5850MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

9.3. Test Procedure


Same with clause 6.3 except change investigated frequency range from 2310MHz to 2415MHz, 2475MHz to 2500MHz and 5725MHz to 5850MHz

9.4. Test Result

PASS. (See below detailed test data)


GFSK

CH LOW:




Detector mode: Average


Polarity: Horizontal



#Res BW 1 MHz





#VBW 1 MHz




Sweep 1 ms (601 pts)

CH LOW:







Detector mode: Average Polarity: Vertical ★ Agilent R T Mkr1 2.483 50 GHz Ref 120 dB μV #Atten 30 dB 46.53 dB μV #Avg Log 10 dB/ 10 dB/ 10 dB/ 10 dB/ DI 54.0 54.0 10 dB/ 10 dB/


dB**µ**V PAva

W1 S2 S3 FC

£(f): FTun

8-DPSK

CH LOW:





#VBW 10 Hz

FCC ID: ZAY-Z-B50


Start 2.310 0 GHz #Res BW 1 MHz Stop 2.420 0 GHz


Sweep 27.12 s (601 pts)






CH LOW:








Detector mode: Average Polarity: Vertical R T 🔆 Agilent Mkr1 2.483 50 GHz Ref 120 dBpV #Atten 30 dB 46.41 dB**µ**V #Avg Log 10 dB/ DI 54.0 ďB**µ**V PAvg W1 S2 S3 FC £(f): FTun Swp Start 2.450 00 GHz Stop 2.500 00 GHz #Res BW 1 MHz **#VBW 10 Hz** Sweep 12.33 s (601 pts)

10. Power Line Conducted Emissions

10.1.Block Diagram of Test Setup



10.2.Limit

	Maximum RF Line Voltage					
Frequency	Quasi-Peak Level	Average Level				
	$dB(\mu V)$	$dB(\mu V)$				
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*				
500kHz ~ 5MHz	56	46				
5MHz ~ 30MHz	60	50				

Notes: 1. * Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

10.3. Test Procedure

- (1) The EUT was placed on a non-metallic table, 80cm above the ground plane.
- (2) Setup the EUT and simulator as shown in 10.1
- (3) The EUT Power connected to the power mains through a power adapter and a line impedance stabilization network (L.I.S.N1). The other peripheral devices power cord connected to the power mains through a line impedance stabilization network (L.I.S.N1), this provided a 50-ohm coupling impedance for the EUT (Please refer to the block diagram of the test setup and photographs). Both sides of power line were checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.4 2009 and ANSI C64.10:2009 on conducted Emission test.
- (4) The bandwidth of test receiver is set at 10KHz.
- (5) The frequency range from 150 KHz to 30MHz is checked.

10.4. Test Result


PASS. (See below detailed test data)

FCC ID: ZAY-Z-B50

From 30MHz to 1GHz



Shenzhen Certification Technology Service Co., Ltd. 2F, Building B, East Area of Nanchang Second Industrial Zone, Gushu 2nd Road, Bao'an District, Shenzhen 518126, P.R. China Tel: 4006786199 Fax: +86-755-26736857 Website: http://www.cessz.com Email;Service@cessz.com



POL: LINE : FCC PART 15 B QP Condition

EUT : Stereo Bluetooth Headset

Model No. : Z-B50 Test Mode : Normal


Power : DC 5V From PC With AC 120V/60Hz

Test Engineer: Simple Remark

Ite	m Freq	Read	LISN Factor	Preamp Factor	Cable Lose	Level	Limit	Margin	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dBuV	
1	0.186	39.29	0.03	-9.72	0.10	49.14	64.20	-15.06	QP
2	0.186	13,29	0.03	-9.72	0.10	23.14	64.20	-41.06	Average
3	0.984	31.92	0.04	-9.71	0.10	41.77	56.00	-14.23	QP
4	0.984	4.92	0.04	-9.71	0.10	14.77	56.00	-41.23	Average
5	2.448	37.79	0.06	-9.70	0.11	47.66	56.00	-8.34	QP
6	2.448	13.79	0.06	-9.70	0.11	23,66	56.00	-32.34	Average
7	5.993	36.75	0.11	-9.61	0.14	46.61	60.00	-13.39	QP
8	5.993	19.75	0.11	-9.61	0.14	29.61	60.00	-30.39	Average
9	10.072	40.66	0.19	-9.52	0.21	50.58	60.00	-9.42	QP
10	10,072	24,66	0.19	-9.52	0,21	34.58	60.00	-25.42	Average
11	23.636	30.65	0.44	-9.56	0.44	41.09	60.00	-18.91	QP
12	23.636	16.65	0.44	-9.56	0.44	27.09	60.00	-32.91	Average



Shenzhen Certification Technology Service Co., Ltd.
2F, Building B, East Area of Nanchang Second Industrial Zone,
Gushu 2nd Road, Bao'an District, Shenzhen 518126, P.R. China
Tel: 4006786199 Fax: +86-755-26736857
Website: http://www.cessz.com Email:Service@cessz.com



Condition : FCC PARI 15 B QP POL: NEUTRAL

EUT : Stereo Bluetooth Headset

Model No. : Z-B50

Test Mode : Normal

Power : DC 5V From PC With AC 120V/60Hz

Test Engineer: Simple

Remark :

Item	Freq	Read	LISN Factor	Preamp Factor	Cable Lose	Level	Limit	Margin	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dBuV	
1	0.197	37.74	0.03	-9.72	0.10	47.59	63.76	-16.17	QP
2	0.197	18.74	0.03	-9.72	0.10	28,59	63.76	-35.17	Average
3	1.054	21.01	0.04	-9.71	0.10	30.86	56.00	-25.14	QP
4	1.054	-0.99	0.04	-9.71	0.10	8.86	56.00	-47.14	Average
5	2.384	27.80	0.06	-9.70	0.11	37.67	56.00	-18.33	QP
6	2.384	3.80	0.06	-9.70	0.11	13.67	56.00	-42.33	Average
7	6.186	29.41	0.11	-9.60	0.14	39.26	60.00	-20.74	QP
8	6.186	9.41	0.11	-9.60	0.14	19.26	60.00	-40.74	Average
9	10.125	31.96	0.19	-9.52	0.21	41.88	60.00	-18.12	QP
10	10.125	15.96	0.19	-9.52	0.21	25.88	60.00	-34.12	Average
11	11.438	30.13	0.24	-9.48	0.22	40.07	60.00	-19.93	QP
12	11.438	13.13	0.24	-9.48	0.22	23.07	60.00	-36.93	Average

-5-

Note: 1. Result Level = Read Level +LISN Factor + Cable loss

2. If QP Result comply with AV limit, AV Result is deemed to comply with AV limit

11. Antenna Requirements

11.1.Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.


11.2.Result

The antennas used for this product are integral Patch Antenna and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is only 0dBi.

FCC ID: ZAY-Z-B50 Page 53 of 62

12. Test setup photo







13. Photos of EUT



































END OF THE REPORT