

FCC PART 15B
MEASUREMENT AND TEST REPORT
FOR

Shenzhen Mobidata Communication Technology Co., Ltd

Room 108, 1/F, R&D Complex Building, Tsinghua Hi-Tech Park, Hi-Tech Industrial Park(North), Nanshan District, Shenzhen, China

FCC ID: ZBF88888

Report Concerns: Original Report	Equipment Type: HSUPA WIRELESS MODEM
Model:	<u>MBD-220HU</u>
Report No.:	<u>STR11028094I-2</u>
Test Date:	<u>2011-02-25 to 2011-03-10</u>
Issue Date:	<u>2011-03-11</u>
Tested By:	<u>Seven Song</u>
Reviewed By:	<u>Lahm Peng</u>
Approved & Authorized By:	<u>Jandy so</u>
Prepared By:	SEM.Test Compliance Service Co., Ltd 3/F, Jinbao Commerce Building, Xin'an Fanshen Road, Bao'an District, Shenzhen, P.R.C. (518101) Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permission by SEM.Test Compliance Service Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS.....	3
1.3 TEST METHODOLOGY.....	3
1.4 TEST FACILITY	4
1.5 EUT EXERCISE SOFTWARE	4
1.6 ACCESSORIES EQUIPMENT LIST AND DETAILS	4
1.7 EUT CABLE LIST AND DETAILS	4
2. SUMMARY OF TEST RESULTS	5
3. §15.107 (A)- CONDUCTED EMISSION	6
3.1 MEASUREMENT UNCERTAINTY	6
3.2 TEST EQUIPMENT LIST AND DETAILS	6
3.3 TEST PROCEDURE.....	6
3.4 BASIC TEST SETUP BLOCK DIAGRAM.....	6
3.5 ENVIRONMENTAL CONDITIONS	7
3.6 TEST RECEIVER SETUP	7
3.7 SUMMARY OF TEST RESULTS/PLOTS	7
3.8 CONDUCTED EMISSIONS TEST DATA.....	7
4. §15.109(A)- RADIATED EMISSION	10
4.1 MEASUREMENT UNCERTAINTY	10
4.2 TEST EQUIPMENT LIST AND DETAILS	10
4.3 TEST PROCEDURE.....	10
4.4 TEST RECEIVER SETUP	11
4.5 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	11
4.6 ENVIRONMENTAL CONDITIONS	11
4.7 SUMMARY OF TEST RESULTS/PLOTS	11

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Shenzhen Mobidata Communication Technology Co., Ltd
Address of applicant: Room 108, 1/F, R&D Complex Building, Tsinghua Hi-Tech Park, Hi-Tech Industrial Park(North), Nanshan District, Shenzhen China

Manufacturer: Shenzhen Mobidata Communication Technology Co., Ltd
Address of manufacturer: Room 108, 1/F, R&D Complex Building, Tsinghua Hi-Tech Park, Hi-Tech Industrial Park(North), Nanshan District, Shenzhen China

General Description of E.U.T

Items	Description
EUT Description:	HSUPA WIRELESS MODEM
Trade Name:	MOBIDATA
Model No.:	MBD-220HU
Rated Voltage:	DC 5V USB
Rated Current:	/
Size:	7.1X4.9X2.0cm

For more information refer to the circuit diagram form and the user's manual.

The test data is gathered from a production sample, provided by the manufacturer.

1.2 Test Standards

The following report is prepared on behalf of the Shenzhen Mobidata Communication Technology Co., Ltd in accordance with Part 2, Subpart J, and Part 15, Subparts A and B of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15.107, and 15.109 rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which results in lowering the emission/immunity, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

The equipment under test (EUT) was configured to measure its highest possible susceptibility against the tested phenomena. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Test Facility

- **FCC – Registration No.: 994117**

SEM.Test Compliance Services Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 994117.

- **Industry Canada (IC) Registration No.: 7673A**

The 3m Semi-anechoic chamber of SEM.Test Compliance Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 7673A.

- **CNAS Registration No.: L4062**

Shenzhen SEM.Test Electronics Service Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 3/F, Jinbao Commerce Building, Xin'an Fanshen Road, Bao'an District, Shenzhen, P.R.C (518101)

1.5 EUT Exercise Software

The EUT exercise program used during radiated and conducted testing was designed to exercise the system components. The test software, provided by the customer, is started while the EUT is on to simulate the normal work. under the Windows XP terminal.

1.6 Accessories Equipment List and Details

Description	Manufacturer	Model	Serial Number
Notebook	ASUS	X81	N/A

1.7 EUT Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
USB Cable	0.8	Shielded	Without Core
Antenna Cable	3.0	Shielded	Without Core

2. SUMMARY OF TEST RESULTS

Description of Test	Result
§15.107 (a) Conducted Emission	Compliant
§15.109(a) Radiated Emission	Compliant

3. §15.107 (a)- CONDUCTED EMISSION

3.1 Measurement Uncertainty

Base on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement is ± 2.88 dB.

3.2 Test Equipment List and Details


Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2010-12-20	2011-12-19
L.I.S.N	Schwarz beck	NSLK8126	8126-224	2010-12-20	2011-12-19
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2010-12-20	2011-12-19

3.3 Test Procedure

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.107 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

3.4 Basic Test Setup Block Diagram



3.5 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

3.6 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:


Start Frequency 150 kHz
Stop Frequency..... 30 MHz
Sweep Speed Auto
IF Bandwidth..... 10 kHz
Quasi-Peak Adapter Bandwidth 9 kHz
Quasi-Peak Adapter Mode Normal

3.7 Summary of Test Results/Plots


According to the data in section 3.8, the EUT complied with the FCC 15B Conducted margin for a Class B device, with the *worst* margin reading of:

-4.50 dB μ V at 0.338 MHz in the Line mode, Average detector, 0.15-30MHz

3.8 Conducted Emissions Test Data

Plot of Conducted Emissions Test Data*Conducted Disturbance**EUT: HSUPA WIRELESS MODEM**M/N: MBD-220HU**Operating Condition: Running with Program**Test Specification: N**Comment: AC 120V/60Hz connect to PC, USB 5V*

EDIT PEAK LIST (Please see Results)				
Trace1:	-QB			
Trace2:	-AV			
Trace3:	---			
TRACE	FRQUENCY	LEVEL dBpV	DELTA	LIMIT dB
1 Max Peak	3.38 kHz	47.79	-11.46	
2 Average	3.38 kHz	44.55	-4.70	
2 Average	4.34 kHz	31.83	-15.33	
1 Max Peak	6.26 kHz	39.27	-16.72	
2 Average	4.112 MHz	27.97	-18.02	
1 Max Peak	4.122 MHz	37.64	-18.33	
1 Max Peak	8.754 MHz	40.10	-19.89	
2 Average	11.994 MHz	32.36	-17.63	
1 Max Peak	13.612 MHz	41.79	-18.20	
2 Average	23.986 MHz	33.62	-16.38	

Plot of Conducted Emissions Test Data*Conducted Disturbance**EUT: HSUPA WIRELESS MODEM**M/N: MBD-220HU**Operating Condition: Running with Program**Test Specification: L**Comment: AC 120V/60Hz connect to PC, USB 5V*

EDIT PEAK LIST (Please see Results)				
Trace1:	-QB			
Trace2:	-AV			
Trace3:	---			
TRACE	FRQUENCY	LEVEL dBpV	DELTA	LIMIT dB
1 Max Peak	3.38 kHz	47.16	-12.08	
2 Average	3.38 kHz	44.74	-4.50	
2 Average	4.34 kHz	32.25	-14.91	
1 Max Peak	6.34 kHz	38.20	-17.79	
1 Max Peak	4.154 MHz	37.88	-18.11	
2 Average	4.154 MHz	27.77	-18.22	
1 Max Peak	8.274 MHz	40.67	-19.32	
2 Average	11.994 MHz	34.06	-15.93	
1 Max Peak	13.154 MHz	42.56	-17.43	
2 Average	30 MHz	31.51	-18.48	

4. §15.109(a)- RADIATED EMISSION

4.1 Measurement Uncertainty

Base on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any radiation emissions measurement is ± 5.10 dB.

4.2 Test Equipment List and Details


Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	R&S	FSP	836079/035	2010-12-20	2011-12-19
EMI Test Receiver	R&S	ESVB	825471/005	2010-12-20	2011-12-19
Positioning Controller	C&C	CC-C-1F	N/A	2010-12-20	2011-12-19
RF Switch	EM	EMSW18	SW060023	2010-12-20	2011-12-19
Pre-amplifier	Agilent	8447F	3113A06717	2010-12-20	2011-12-19
Pre-amplifier	Compliance Direction	PAP-0118	24002	2010-12-20	2011-12-19
Trilog Broadband Antenna	SCHWARZBECK	VULB9163	9163-333	2011-01-09	2012-01-08
Horn Antenna	ETS	3117	00086197	2011-01-09	2012-01-08

4.3 Test Procedure

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.205 and FCC Part 15.109 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.



4.4 Test Receiver Setup

During the radiated emission test, the test receiver was set with the following configurations:

Start Frequency 30 MHz
Stop Frequency 1000 MHz
Sweep Speed Auto
IF Bandwidth 100 kHz
Quasi-Peak Adapter Bandwidth 120 kHz
Quasi-Peak Adapter Mode Normal

4.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} - \text{Corr. Factor}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15B Limit}$$


4.6 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

4.7 Summary of Test Results/Plots


According to the data, the EUT complied with the FCC 15B Class B standards, and had the worst margin of:

-1.95 dB μ V at 137.4202 MHz in the Vertical polarization, 30 MHz to 1 GHz, 3Meters

Plot of Radiation Emissions Test Data*Radiated Disturbance**EUT: HSUPA WIRELESS MODEM**M/N: MBD-220HU**Operating Condition: Running with Program**Test Specification: Horizontal & Vertical**Comment: AC 120V/60Hz connect to PC, USB 5V**Horizontal*

No.	Frequency (MHz)	Reading (dBuV)	Correct dB	Result (dBuV)	Limit (dBuV)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	61.3463	30.97	7.00	37.97	40.00	-2.03	360	100	peak
2	113.7143	33.37	6.98	40.35	43.50	-3.15	360	100	peak
3	147.4036	36.61	4.05	40.66	43.50	-2.84	360	100	peak
4	183.2005	33.57	5.93	39.50	43.50	-4.00	360	100	peak
5	258.3264	24.94	8.91	33.85	46.00	-12.15	360	100	peak

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Correct dB	Result (dBuV)	Limit (dBuV)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	62.2128	30.61	6.67	37.28	40.00	-2.72	360	100	peak
2	114.5146	34.18	6.85	41.03	43.50	-2.47	360	100	peak
3	137.4202	37.44	4.11	41.55	43.50	-1.95	360	100	peak
4	148.4410	36.40	4.07	40.47	43.50	-3.03	360	100	peak

***** END OF REPORT *****