



STC Test Report

Date : 2011-03-23

Page 36 of 41

No. : MH184983

RF Exposure

Test Requirement: FCC 47CFR 15.247(b)(5)

Test Date: 2011-3-03

Mode of Operation: Tx mode

Test Method:

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines.

Test Results:

The EUT complied with the requirement(s) of this section.

EUT meets the requirements of these sections as proven through MPE calculation

The MPE calculation for EUT @ 20cm

Based on the highest P =43.4 mW

$$\begin{aligned} P_d &= PG / 4\pi * R^2 = (43.4 \times 1.584) / 12.566 * (20)^2 \\ &= (68.746) / 12.566 \times 400 = 68.746 / 5026.4 \\ &= 0.014 \text{ mW/cm}^2 \end{aligned}$$

where:

*Pd = power density in mW/cm²

* G = Antenna numeric gain (1.584); Log G = g/10 (g = 2dBi).

* P = Conducted RF power to antenna (43.4 mW).

* R = Minimum allowable distance.(20 cm)

*The power density Pd = 0.014 mW/cm² is less than 1 mW/cm² (listed MPE limit)

*The SAR evaluation is not needed (this is a desk top device, R> 20 cm)

* The EUT(antenna) must be 0.2 meters away from the General Population.

The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org