

FCC SAR Test Report

Report No. : SA190325W006-1

Applicant : Corporativo Lanix S.A. de C.V.

Address : Carretera Internacional Hermosillo-Nogales Km 8.5, Hermosillo Sonora,
Mexico

Product : smartphone

FCC ID : ZC4ALPHA1S

Brand : LANIX

Model No. : Ilium Alpha 1s

Standards : FCC 47 CFR Part 2 (2.1093) / IEEE C95.1:1992 / IEEE 1528:2013
KDB 865664 D01 v01r04 / KDB 865664 D02 v01r02
KDB 248227 D01 v02r02 / KDB 447498 D01 v06 / KDB 648474 D04 v01r03
/ KDB 941225 D01 v03r01 / KDB 941225 D05 v02r05 / KDB 941225 D06 v02r01

Sample Received Date : Mar. 25, 2019


Date of Testing : Mar. 26, 2019 ~ Apr. 02, 2019

CERTIFICATION: The above equipment have been tested by **BV 7LAYERS COMMUNICATIONS TECHNOLOGY (SHENZHEN) CO. LTD.**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's SAR characteristics under the conditions specified in this report. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by A2LA or any government agencies.

Prepared By :


Wiky Zhang / Engineer

Approved By :


Luke Lu / Manager



This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	3
1. Summary of Maximum SAR Value	4
2. Description of Equipment Under Test	5
3. SAR Measurement System	6
3.1 Definition of Specific Absorption Rate (SAR)	6
3.2 COMOSAR System.....	6
3.2.1 Measurement System Diagram	6
3.2.2 Robot.....	7
3.2.3 E-Field Probes	8
3.2.4 Phantoms	9
3.2.5 Device Holder.....	10
3.2.6 System Validation Dipoles.....	11
3.2.7 Tissue Simulating Liquids.....	11
3.3 SAR System Verification	14
3.4 SAR Measurement Procedure	15
3.4.1 Area & Zoom Scan Procedure	15
3.4.2 Volume Scan Procedure.....	15
3.4.3 Power Drift Monitoring.....	16
3.4.4 Spatial Peak SAR Evaluation	16
3.4.5 SAR Averaged Methods	16
4. SAR Measurement Evaluation	17
4.1 EUT Configuration and Setting.....	17
4.2 EUT Testing Position	21
4.2.1 Head Exposure Conditions.....	21
4.2.2 Body-worn Accessory Exposure Conditions.....	23
4.2.3 Hotspot Mode Exposure Conditions	24
4.2.4 Extremity Exposure Conditions	25
4.2.5 SAR Test Exclusion Evaluations	25
4.2.6 Simultaneous Transmission Possibilities.....	26
4.3 Tissue Verification	27
4.4 System Validation.....	27
4.5 System Verification.....	28
4.6 Maximum Output Power.....	29
4.6.1 Maximum Conducted Power	29
4.6.2 Measured Conducted Power Result.....	30
4.7 SAR Testing Results	40
4.7.1 SAR Test Reduction Considerations	40
4.7.2 SAR Results for Head Exposure Condition	42
4.7.3 SAR Results for Body-worn Exposure Condition (Separation Distance is 1.0 cm Gap).....	43
4.7.4 SAR Results for Hotspot Exposure Condition (Separation Distance is 1.0 cm Gap).....	45
4.7.5 SAR Measurement Variability.....	47
4.7.6 Simultaneous Multi-band Transmission Evaluation	47
5. Calibration of Test Equipment.....	54
6. Measurement Uncertainty.....	55
7. Information on the Testing Laboratories.....	56
Appendix A. SAR Plots of System Verification	
Appendix B. SAR Plots of SAR Measurement	
Appendix C. Calibration Certificate for Probe and Dipole	
Appendix D. Photographs of EUT and Setup	

Release Control Record

Report No.	Reason for Change	Date Issued
SA190325W006-1	Initial release	Apr. 12, 2019

FCC SAR Test Report

1. Summary of Maximum SAR Value

Equipment Class	Mode	Highest Reported Head SAR _{1g} (W/kg)	Highest Reported Body-worn SAR _{1g} (1.0 cm Gap) (W/kg)	Highest Reported Hotspot SAR _{1g} (1.0 cm Gap) (W/kg)
PCE	GSM850	0.17	0.25	0.25
	GSM1900	0.16	0.27	0.27
	WCDMA II	0.28	0.39	0.39
	WCDMA IV	0.39	0.25	0.25
	WCDMA V	0.12	0.18	0.18
	LTE 2	0.28	0.39	0.39
	LTE 4	0.31	0.25	0.25
	LTE 5	0.27	0.15	0.15
	LTE 7	0.16	0.85	0.85
	LTE 12	0.18	0.17	0.17
	LTE 66	0.32	0.26	0.26
DTS	2.4G WLAN	0.75	0.28	0.28
DSS	Bluetooth	N/A	N/A	N/A
Highest Simultaneous Transmission SAR		Head (W/kg)	Body-worn (W/kg)	Hotspot (W/kg)
PCE + DTS		1.14	1.13	1.13
PCE + DSS		N/A	0.98	N/A

Note:

- The SAR limit (**Head & Body: SAR_{1g} 1.6 W/kg**) for general population / uncontrolled exposure is specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992

FCC SAR Test Report

2. Description of Equipment Under Test

EUT Type	smartphone
FCC ID	ZC4ALPHA1S
Brand Name	LANIX
Model Name	Ilium Alpha 1s
IMEI Code	863408025534448
HW Version	V1.0
SW Version	Ilium Alpha 1s_SW_01_V01
Tx Frequency Bands (Unit: MHz)	GSM850 : 824.2 ~ 848.8 GSM1900 : 1850.2 ~ 1909.8 WCDMA Band II : 1852.4 ~ 1907.6 WCDMA Band IV : 1712.4 ~ 1752.6 WCDMA Band V : 826.4 ~ 846.6 LTE Band 2 : 1850.7 ~ 1909.3 (1.4M), 1851.5 ~ 1908.5 (3M), 1852.5 ~ 1907.5 (5M), 1855 ~ 1905 (10M), 1857.5 ~ 1902.5 (15M), 1860 ~ 1900 (20M) LTE Band 4 : 1710.7 ~ 1754.3 (1.4M), 1711.5 ~ 1753.5 (3M), 1712.5 ~ 1752.5 (5M), 1715 ~ 1750 (10M), 1717.5 ~ 1747.5 (15M), 1720 ~ 1745 (20M) LTE Band 5 : 824.7 ~ 848.3 (1.4M), 825.5 ~ 847.5 (3M), 826.5 ~ 846.5 (5M), 829 ~ 844 (10M) LTE Band 7 : 2502.5 ~ 2567.5 (5M), 2505 ~ 2565 (10M), 2507.5 ~ 2562.5 (15M), 2510 ~ 2560 (20M) LTE Band 12 : 699.7 ~ 715.3 (1.4M), 700.5 ~ 714.5 (3M), 701.5 ~ 713.5 (5M), 704 ~ 711 (10M) LTE Band 66 : 1710.7 ~ 1779.3 (1.4M), 1711.5 ~ 1778.5 (3M), 1712.5 ~ 1777.5 (5M), 1715 ~ 1775 (10M), 1717.5 ~ 1772.5 (15M), 1720 ~ 1770 (20M) WLAN : 2412 ~ 2462 Bluetooth : 2402 ~ 2480
Uplink Modulations	GSM & GPRS & EDGE : GMSK, 8PSK WCDMA : BPSK, QPSK LTE : QPSK, 16QAM 802.11b : DSSS 802.11g/n : OFDM Bluetooth : GFSK, $\pi/4$ -DQPSK, 8-DPSK, LE
Maximum Tune-up Conducted Power (Unit: dBm)	Please refer to section 4.6.1 of this report.
Antenna Type	WLAN: PIFA Antenna WWAN: Fixed Internal Antenna
EUT Stage	Identical Prototype

Note:

- The above EUT information is declared by manufacturer and for more detailed features description please refers to the manufacturer's specifications or User's Manual.

List of Accessory:

Battery	Brand Name	lanix
	Model Name	Ilium Alpha 1s-BAT
	Power Rating	3.85Vdc, 4000mAh
	Type	Li-ion
Earphone	Brand Name	lanix
	Model Name	Alpha 1s
	Signal Line Type	1.2 meter non-shielded cable without ferrite core

3. SAR Measurement System

3.1 Definition of Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)


SAR measurement can be related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

3.2 COMOSAR System

3.2.1 Measurement System Diagram



These measurements were performed with the automated near-field scanning system COMOSAR from SATIMO. The system is based on a high precision robot (working range: 850 mm), which positions the probes with a positional repeatability of better than ± 0.02 mm. Special E- and H-field probes have been developed for measurements close to material discontinuity, the sensors of which are directly loaded with a Schottky diode and connected via highly resistive lines to the data acquisition unit.

FCC SAR Test Report

The SAR measurements were conducted with dosimetric probe (manufactured by SATIMO), designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe has been calibrated according to the procedure described in SAR standard with accuracy of better than $\pm 10\%$. The spherical isotropy was evaluated with the procedure described in SAR standard and found to be better than ± 0.25 dB. The phantom used was the SAM Phantom as described in FCC supplement C, IEEE P1528.

3.2.2 Robot

The COMOSAR system uses the high precision robots from KUKA. For the 6-axis controller system, the robot controller version (KUKA-KRC2sr) from KUKA is used. The KUKA robot series have many features that are important for our application:

- High precision (repeatability ± 0.02 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)



FCC SAR Test Report

3.2.3 E-Field Probes


The SAR measurement is conducted with the dosimetric probe. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency.



Device Type	COMOSAR DOSIMETRIC E FIELD PROBE
Model	SSE2
Frequency	100 MHz to 6 GHz
Directivity	± 0.25 dB in brain tissue (rotation around probe axis) ± 0.5 dB in brain tissue (rotation normal probe axis)
Dynamic Range	0.001W/kg to > 100W/kg
Probe Linearity	± 0.25 dB
Dimensions	Overall length: 330 mm Tip diameter: 2.5 mm Distance from probe tip to dipole centers: <1.5 mm

E-Field Probe Calibration Process

Probe calibration is realized, in compliance with EN/IEC 62209-1/-2 and IEEE 1528 std, with CALISAR, SATIMO proprietary calibration system. The calibration is performed with the technique using reference waveguide.



FCC SAR Test Report

$$SAR = \frac{4(P_{fw} - P_{bw})}{ab\sigma} \cos^2 \left(\pi \frac{y}{a} \right) e^{-(2\pi/\sigma)t}$$

Where :

- P_{fw} = Forward Power
- P_{bw} = Backward Power
- a and b = Waveguide Dimensions
- t = Skin Depth

Keithley configuration

Rate=Medium; Filter=ON; RDGS=10; FILTER TYPE=MOVING AVERAGE; RANGE AUTO

After each calibration, a SAR measurement performed on a validation dipole and compared with a NPL calibrated probe, to verify it.

The Calibration factors, CF(N), for the 3 sensors corresponding to dipole 1, dipole 2 and dipole 3 are:

$$CF(N) = SAR(N)/V_{lin}(N) \quad (N=1,2,3)$$

The linearized output voltage V_{lin}(N) is obtained from the displayed output voltage V(N) using

$$V_{lin}(N) = V(N) * (1 + V(N)/DCP(N)) \quad N=1,2,3$$

Where the DCP is the dipole compression point in mV

3.2.4 Phantoms

The phantom developed by SATIMO is produced in accordance with the specified in the standards. It has been designed to fit the COMOSAR phantom tables and is delivered with a plastic cover to prevent liquid evaporation.

Model	SAM Phantom	
Construction	The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching reference points with the robot.	
Material	The material is resistant to Glycol and offers high rigidity composite material based on fiberglass).	
Shell Thickness	2 ± 0.2 mm (6 ± 0.2 mm at ear point)	
Dimensions	Length: 1000 mm Width: 500 mm Height: 200 mm	
Filling Volume	approx. 27 liters	

FCC SAR Test Report

Model	Elliptic Phantom	
Construction	Elliptic Phantom for compliance testing of handheld and body-mounted wireless devices. Elliptic Phantom is fully compatible with the IEC/EN 62209-2 standard and all known tissue simulating liquids. Elliptic Phantom has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching reference points.	
Material	The material is resistant to Glycol and offers high rigidity composite material based on fiberglass).	
Shell Thickness	2.0 ± 0.2 mm (bottom plate)	
Dimensions	Length: 600 mm Width: 400 mm Height: 200 mm	
Filling Volume	approx. 25 liters	

3.2.5 Device Holder


The positioning system is made of an extremely stable material, which ensures easy handling and reproducible positioning. It also allows correct positioning of the dipoles referenced by the IEEE, ANSI and IEC.

Model	Handset Positioning System	
Material properties	The positioning system is made of PETP. This material offers a low permittivity of 3.2 and low loss, with a loss tangent of 0.005 to minimize the influence of the DUT on measurement results.	
Mechanical properties	The positioning system developed by SATIMO allows a positioning resolution better than 1 mm. The system is fixed on a bottom rail "x axis" so that the positioning system can be quickly moved from the right to the left part of the phantom. In addition, it can be moved on a perpendicular "y axis" and the height can be adapted. The system is also composed of three rotation points for accurate positioning of the device's acoustical output.	
Accuracy and precision	A curved rail on the top part allows the fast switch from the cheek to the tilt position. The required 15° angle for the tilt position can be easily checked thanks to a printed scale on the curved rail with a tolerance of ± 1°	

Model	Device Positioning System	
Material properties	The positioning system is made of PETP. This material offers a low permittivity of 3.2 and low loss, with a loss tangent of 0.005 to minimize the influence of the DUT on measurement results.	
Mechanical properties	2 rows of rail to cover easily the surface of the phantom. The fixing plate is perfectly adapted to larger devices, such as a PC which can be positioned in all configurations.	
Accuracy and precision	Graduated scale available on each axis. The DUT is fixed with a specific adaptable grip.	



FCC SAR Test Report

3.2.6 System Validation Dipoles

Model	D-Serial	
Construction	Symmetrical dipole with $\lambda/4$ ablaun. Enables measurement of feed point impedance with NWA. Matched for use near flat phantoms filled with tissue simulating solutions.	
Frequency	300 MHz to 6000 MHz	
Return Loss	> 20 dB	
Adaptation	S11 < -20 dB in specified validation Position	

3.2.7 Tissue Simulating Liquids

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5% are listed in Table-3.1.

	
Photo of Liquid Height for Head Position	Photo of Liquid Height for Body Position

The dielectric properties of the head tissue simulating liquids are defined in IEEE 1528, and KDB 865664 D01 Appendix A. For the body tissue simulating liquids, the dielectric properties are defined in KDB 865664 D01 Appendix A. The dielectric properties of the tissue simulating liquids were verified prior to the SAR evaluation using a dielectric assessment kit and a network analyzer.

FCC SAR Test Report

Table-3.1 Targets of Tissue Simulating Liquid

Frequency (MHz)	Target Permittivity	Range of $\pm 5\%$	Target Conductivity	Range of $\pm 5\%$
For Head				
750	41.9	39.8 ~ 44.0	0.89	0.85 ~ 0.93
835	41.5	39.4 ~ 43.6	0.90	0.86 ~ 0.95
900	41.5	39.4 ~ 43.6	0.97	0.92 ~ 1.02
1450	40.5	38.5 ~ 42.5	1.20	1.14 ~ 1.26
1640	40.3	38.3 ~ 42.3	1.29	1.23 ~ 1.35
1750	40.1	38.1 ~ 42.1	1.37	1.30 ~ 1.44
1800	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
1900	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
2000	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
2300	39.5	37.5 ~ 41.5	1.67	1.59 ~ 1.75
2450	39.2	37.2 ~ 41.2	1.80	1.71 ~ 1.89
2600	39.0	37.1 ~ 41.0	1.96	1.86 ~ 2.06
3500	37.9	36.0 ~ 39.8	2.91	2.76 ~ 3.06
5200	36.0	34.2 ~ 37.8	4.66	4.43 ~ 4.89
5300	35.9	34.1 ~ 37.7	4.76	4.52 ~ 5.00
5500	35.6	33.8 ~ 37.4	4.96	4.71 ~ 5.21
5600	35.5	33.7 ~ 37.3	5.07	4.82 ~ 5.32
5800	35.3	33.5 ~ 37.1	5.27	5.01 ~ 5.53
For Body				
750	55.5	52.7 ~ 58.3	0.96	0.91 ~ 1.01
835	55.2	52.4 ~ 58.0	0.97	0.92 ~ 1.02
900	55.0	52.3 ~ 57.8	1.05	1.00 ~ 1.10
1450	54.0	51.3 ~ 56.7	1.30	1.24 ~ 1.37
1640	53.8	51.1 ~ 56.5	1.40	1.33 ~ 1.47
1750	53.4	50.7 ~ 56.1	1.49	1.42 ~ 1.56
1800	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60
1900	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60
2000	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60
2300	52.9	50.3 ~ 55.5	1.81	1.72 ~ 1.90
2450	52.7	50.1 ~ 55.3	1.95	1.85 ~ 2.05
2600	52.5	49.9 ~ 55.1	2.16	2.05 ~ 2.27
3500	51.3	48.7 ~ 53.9	3.31	3.14 ~ 3.48
5200	49.0	46.6 ~ 51.5	5.30	5.04 ~ 5.57
5300	48.9	46.5 ~ 51.3	5.42	5.15 ~ 5.69
5500	48.6	46.2 ~ 51.0	5.65	5.37 ~ 5.93
5600	48.5	46.1 ~ 50.9	5.77	5.48 ~ 6.06
5800	48.2	45.8 ~ 50.6	6.00	5.70 ~ 6.30

FCC SAR Test Report

The following table gives the recipes for tissue simulating liquids.

Table-3.2 Recipes of Tissue Simulating Liquid

Tissue Type	Bactericide	DGBE	HEC	NaCl	Sucrose	Triton X-100	Water	Diethylene Glycol Mono-hexylether
H750	0.2	-	0.2	1.5	56.0	-	42.1	-
H835	0.2	-	0.2	1.5	57.0	-	41.1	-
H900	0.2	-	0.2	1.4	58.0	-	40.2	-
H1450	-	43.3	-	0.6	-	-	56.1	-
H1640	-	45.8	-	0.5	-	-	53.7	-
H1750	-	47.0	-	0.4	-	-	52.6	-
H1800	-	44.5	-	0.3	-	-	55.2	-
H1900	-	44.5	-	0.2	-	-	55.3	-
H2000	-	44.5	-	0.1	-	-	55.4	-
H2300	-	44.9	-	0.1	-	-	55.0	-
H2450	-	45.0	-	0.1	-	-	54.9	-
H2600	-	45.1	-	0.1	-	-	54.8	-
H3500	-	8.0	-	0.2	-	20.0	71.8	-
H5G	-	-	-	-	-	17.2	65.5	17.3
B750	0.2	-	0.2	0.8	48.8	-	50.0	-
B835	0.2	-	0.2	0.9	48.5	-	50.2	-
B900	0.2	-	0.2	0.9	48.2	-	50.5	-
B1450	-	34.0	-	0.3	-	-	65.7	-
B1640	-	32.5	-	0.3	-	-	67.2	-
B1750	-	31.0	-	0.2	-	-	68.8	-
B1800	-	29.5	-	0.4	-	-	70.1	-
B1900	-	29.5	-	0.3	-	-	70.2	-
B2000	-	30.0	-	0.2	-	-	69.8	-
B2300	-	31.0	-	0.1	-	-	68.9	-
B2450	-	31.4	-	0.1	-	-	68.5	-
B2600	-	31.8	-	0.1	-	-	68.1	-
B3500	-	28.8	-	0.1	-	-	71.1	-
B5G	-	-	-	-	-	10.7	78.6	10.7

3.3 SAR System Verification

The system check verifies that the system operates within its specifications. It is performed daily or before every SAR measurement. The system check uses normal SAR measurements in the flat section of the phantom with a matched dipole at a specified distance. The system verification setup is shown as below.




Fig-3.3 System Verification Setup

The validation dipole is placed beneath the flat phantom with the specific spacer in place. The distance spacer is touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The spectrum analyzer measures the forward power at the location of the system check dipole connector. The signal generator is adjusted for the desired forward power at the dipole connector and the power meter is read at that level. After connecting the cable to the dipole, the signal generator is readjusted for the same reading at power meter.

After system check testing, the SAR result will be normalized to 1W forward input power and compared with the reference SAR value derived from validation dipole certificate report. The deviation of system check should be within 10 %.

FCC SAR Test Report

3.4 SAR Measurement Procedure

According to the SAR test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- Power reference measurement
- Area scan
- Zoom scan
- Power drift measurement

The SAR measurement procedures for each of test conditions are as follows:

- Make EUT to transmit maximum output power
- Measure conducted output power through RF cable
- Place the EUT in the specific position of phantom
- Perform SAR testing steps on the COMOSAR system
- Record the SAR value

3.4.1 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. According to KDB 865664 D01, the resolution for Area and Zoom scan is specified in the table below.

Items	<= 2 GHz	2-3 GHz	3-4 GHz	4-5 GHz	5-6 GHz
Area Scan ($\Delta x, \Delta y$)	<= 15 mm	<= 12 mm	<= 12 mm	<= 10 mm	<= 10 mm
Zoom Scan ($\Delta x, \Delta y$)	<= 8 mm	<= 5 mm	<= 5 mm	<= 4 mm	<= 4 mm
Zoom Scan (Δz)	<= 5 mm	<= 5 mm	<= 4 mm	<= 3 mm	<= 2 mm
Zoom Scan Volume	>= 30 mm	>= 30 mm	>= 28 mm	>= 25 mm	>= 22 mm

Note:

When zoom scan is required and report SAR is <= 1.4 W/kg, the zoom scan resolution of $\Delta x / \Delta y$ (2-3GHz: <= 8 mm, 3-4GHz: <= 7 mm, 4-6GHz: <= 5 mm) may be applied.

3.4.2 Volume Scan Procedure

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software can combine and subsequently superpose these measurement data to calculating the multiband SAR.

3.4.3 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In COMOSAR measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. If the power drift more than 5%, the SAR will be retested.

3.4.4 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The OPENSAR software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine. The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

3.4.5 SAR Averaged Methods

In COMOSAR System, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.

4. SAR Measurement Evaluation

4.1 EUT Configuration and Setting

<Connections between EUT and System Simulator>

For WWAN SAR testing, the EUT was linked and controlled by base station emulator (Agilent E5515C is used for GSM/WCDMA, and Anritsu MT8820C is used for LTE). Communication between the EUT and the emulator was established by air link. The distance between the EUT and the communicating antenna of the emulator is larger than 50 cm and the output power radiated from the emulator antenna is at least 30 dB smaller than the output power of EUT. The EUT was set from the emulator to radiate maximum output power during SAR testing.

<Considerations Related to GSM / GPRS / EDGE for Setup and Testing>

The maximum multi-slot capability supported by this device is as below.

1. This EUT is class B device
2. This EUT supports GPRS multi-slot class 33 (max. uplink: 4, max. downlink: 5, total timeslots: 6)
3. This EUT supports EDGE multi-slot class 33 (max. uplink: 4, max. downlink: 5, total timeslots: 6)

For GSM850 frequency band, the power control level is set to 5 for GSM mode and GPRS (GMSK: CS1), and set to 8 for EDGE (GMSK: MCS1, 8PSK: MCS9). For GSM1900 frequency band, the power control level is set to 0 for GSM mode and GPRS (GMSK: CS1), and set to 2 for EDGE (GMSK: MCS1, 8PSK: MCS9).

SAR test reduction for GPRS and EDGE modes is determined by the source-based time-averaged output power specified for production units, including tune-up tolerance. The data mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested.

<Considerations Related to WCDMA for Setup and Testing>

WCDMA Handsets Head SAR

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all "1's". The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode.

WCDMA Handsets Body-worn SAR

SAR for body-worn configurations is measured using a 12.2 kbps RMC with TPC bits configured to all "1's". The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCH_n configurations supported by the handset with 12.2 kbps RMC as the primary mode.

Handsets with Release 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body-worn configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for HSDPA using the HSDPA body SAR procedures in the "Release 5 HSDPA Data Devices", for the highest reported SAR body-worn exposure configuration in 12.2 kbps RMC. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

Handsets with Release 6 HSUPA

FCC SAR Test Report

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body-worn configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for HSPA using the HSPA body SAR procedures in the "Release 6 HSPA Data Devices", for the highest reported body-worn exposure SAR configuration in 12.2 kbps RMC. When VOIP is applicable for next to the ear head exposure in HSPA, the 3G SAR test reduction procedure is applied to HSPA with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body-worn measurements is tested for next to the ear head exposure.

Release 5 HSDPA Data Devices

The 3G SAR test reduction procedure is applied to body SAR with 12.2 kbps RMC as the primary mode. Otherwise, body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, for the highest reported SAR configuration in 12.2 kbps RMC without HSDPA. HSDPA is configured according to the applicable UE category of a test device. The number of HS-DSCH / HS-PDSCHs, HARQ processes, minimum inter-TTI interval, transport block sizes and RV coding sequence are defined by the H-set. To maintain a consistent test configuration and stable transmission conditions, QPSK is used in the H-set for SAR testing. HS-DPCCH should be configured with a CQI feedback cycle of 4 ms and a CQI repetition factor of 2 to maintain a constant rate of active CQI slots. DPCCH and DPDCH gain factors (β_c , β_d), and HS-DPCCH power offset parameters (Δ_{ACK} , Δ_{NACK} , Δ_{CQI}) are set according to values indicated in below. The CQI value is determined by the UE category, transport block size, number of HS-PDSCHs and modulation used in the H-set.

Sub-test	β_c	β_d	β_d (SF)	β_c / β_d	$\beta_{hs}^{(1)}$	CM (dB) ⁽²⁾	MPR
1	2 / 15	15 / 15	64	2 / 15	4 / 15	0.0	0
2	12 / 15 ⁽³⁾	15 / 15 ⁽³⁾	64	12 / 15 ⁽³⁾	24 / 15	1.0	0
3	15 / 15	8 / 15	64	15 / 8	30 / 15	1.5	0.5
4	15 / 15	4 / 15	64	15 / 4	30 / 15	1.5	0.5

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs} / \beta_c = 30 / 15 \Leftrightarrow \beta_{hs} = 30 / 15 * \beta_c$.
Note 2: CM = 1 for $\beta_c / \beta_d = 12 / 15$, $\beta_{hs} / \beta_c = 24 / 15$.
Note 3: For subtest 2 the β_c / β_d ratio of 12 / 15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11 / 15$ and $\beta_d = 15 / 15$.

Release 6 HSUPA Data Devices

The 3G SAR test reduction procedure is applied to body SAR with 12.2 kbps RMC as the primary mode. Otherwise, body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA. When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode. Otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing. Due to inner loop power control requirements in HSPA, a communication test set is required for output power and SAR tests. The 12.2 kbps RMC, FRC H-set 1 and E-DCH configurations for HSPA are configured according to the β values indicated in below.

Sub-test	β_c	β_d	β_d (SF)	β_c / β_d	$\beta_{hs}^{(1)}$	β_{ec}	β_{ed}	β_{ed} (SF)	β_{ed} (codes)	CM ⁽²⁾ (dB)	MPR (dB)	AG ⁽⁴⁾ Index	E-TFCI
1	11 / 15 ⁽³⁾	15 / 15 ⁽³⁾	64	11 / 15 ⁽³⁾	22 / 15	209 / 225	1039 / 225	4	1	1.0	0.0	20	75
2	6 / 15	15 / 15	64	6 / 15	12 / 15	12 / 15	94 / 75	4	1	3.0	2.0	12	67
3	15 / 15	9 / 15	64	15 / 9	30 / 15	30 / 15	$\beta_{ed1}: 47/15$ $\beta_{ed2}: 47/15$	4	2	2.0	1.0	15	92

FCC SAR Test Report

4	2 / 15	15 / 15	64	2 / 15	4 / 15	2 / 15	56 / 75	4	1	3.0	2.0	17	71
5	15 / 15 ⁽⁴⁾	15 / 15 ⁽⁴⁾	64	15 / 15 ⁽⁴⁾	30 / 15	24 / 15	134 / 15	4	1	1.0	0.0	21	81

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 8 \Leftrightarrow A_{HS} = \beta_{HS} / \beta_C = 30 / 15 \Leftrightarrow \beta_{HS} = 30 / 15 * \beta_C$.

Note 2: CM = 1 for $\beta_C / \beta_d = 12 / 15$, $\beta_{HS} / \beta_C = 24 / 15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_C / β_d ratio of 11 / 15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_C = 10 / 15$ and $\beta_d = 15 / 15$.

Note 4: For subtest 5 the β_C / β_d ratio of 15 / 15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_C = 14 / 15$ and $\beta_d = 15 / 15$.

Note 5: Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Table 5.1g.

Note 6: β_{ed} cannot be set directly; it is set by Absolute Grant Value.

<Considerations Related to LTE for Setup and Testing>

This device contains LTE transmitter which follows 3GPP standards, is category 3, supports both QPSK and 16QAM modulations, and supported LTE band and channel bandwidth is listed in below. The output power was tested per 3GPP TS 36.521-1 maximum transmit procedures for both QPSK and 16QAM modulation. The results please refer to section 4.6 of this report.

EUT Supported LTE Band and Channel Bandwidth						
LTE Band	BW 1.4 MHz	BW 3 MHz	BW 5 MHz	BW 10 MHz	BW 15 MHz	BW 20 MHz
2	V	V	V	V	V	V
4	V	V	V	V	V	V
5	V	V	V	V		
7			V	V	V	V
12	V	V	V	V		
66	V	V	V	V	V	V

The LTE maximum power reduction (MPR) in accordance with 3GPP TS 36.101 is active all times during LTE operation. The allowed MPR for the maximum output power is specified in below.

Modulation	Channel Bandwidth / RB Configurations						LTE MPR Setting (dB)
	BW 1.4 MHz	BW 3 MHz	BW 5 MHz	BW 10 MHz	BW 15 MHz	BW 20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	1
16QAM	<= 5	<= 4	<= 8	<= 12	<= 16	<= 18	1
16QAM	> 5	> 4	> 8	> 12	> 16	> 18	2

Note: MPR is according to the standard and implemented in the circuit (mandatory).

In addition, the device is compliant with additional maximum power reduction (A-MPR) requirements defined in 3GPP TS 36.101 section 6.2.4 that was disabled for all FCC compliance testing.

During LTE SAR testing, the related parameters of operating band, channel bandwidth, uplink channel number, modulation type, and RB was set in base station simulator. When the EUT has registered and communicated to base station simulator, the simulator set to make EUT transmitting the maximum radiated power.

<Considerations Related to WLAN for Setup and Testing>

In general, various vendor specific external test software and chipset based internal test modes are typically used for SAR measurement. These chipset based test mode utilities are generally hardware and manufacturer dependent, and often include substantial flexibility to reconfigure or reprogram a device. A Wi-Fi device must be configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest

FCC SAR Test Report

transmission duty factor supported by the test mode tools for SAR measurement. The test frequencies established using test mode must correspond to the actual channel frequencies. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. In addition, a periodic transmission duty factor is required for current generation SAR systems to measure SAR correctly. The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

According to KDB 248227 D01, this device has installed WLAN engineering testing software which can provide continuous transmitting RF signal. During WLAN SAR testing, this device was operated to transmit continuously at the maximum transmission duty with specified transmission mode, operating frequency, lowest data rate, and maximum output power.

Initial Test Configuration

An initial test configuration is determined for OFDM transmission modes in 2.4 GHz and 5 GHz bands according to the channel bandwidth, modulation and data rate combination(s) with the highest maximum output power specified for production units in each standalone and aggregated frequency band. When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel in the initial test configuration, for each frequency band.

Subsequent Test Configuration

SAR measurement requirements for the remaining 802.11 transmission mode configurations that have not been tested in the initial test configuration are determined separately for each standalone and aggregated frequency band, in each exposure condition, according to the maximum output power specified for production units. Additional power measurements may be required to determine if SAR measurements are required for subsequent highest output power channels in a subsequent test configuration. When the highest reported SAR for the initial test configuration according to the initial test position or fixed exposure position requirements, is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for that subsequent test configuration.

SAR Test Configuration and Channel Selection

When multiple channel bandwidth configurations in a frequency band have the same specified maximum output power, the initial test configuration is using largest channel bandwidth, lowest order modulation, lowest data rate, and lowest order 802.11 mode (i.e., 802.11a is chosen over 802.11n then 802.11ac or 802.11g is chosen over 802.11n). After an initial test configuration is determined, if multiple test channels have the same measured maximum output power, the channel chosen for SAR measurement is determined according to the following.

- 1) The channel closest to mid-band frequency is selected for SAR measurement.
- 2) For channels with equal separation from mid-band frequency; for example, high and low channels or two mid-band channels, the higher frequency (number) channel is selected for SAR measurement.

4.2 EUT Testing Position

According to KDB 648474 D04, handsets are tested for SAR compliance in head, body-worn accessory and other use configurations described in the following subsections.

4.2.1 Head Exposure Conditions

Head exposure is limited to next to the ear voice mode operations. Head SAR compliance is tested according to the test positions defined in IEEE Std 1528-2013 using the SAM phantom illustrated as below.

1. Define two imaginary lines on the handset
 - (a) The vertical centerline passes through two points on the front side of the handset - the midpoint of the width w_t of the handset at the level of the acoustic output, and the midpoint of the width w_b of the bottom of the handset.
 - (b) The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
 - (c) The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.




Fig-4.1 Illustration for Handset Vertical and Horizontal Reference Lines

FCC SAR Test Report

2. Cheek Position

- To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the three ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.
- To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with the ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost (see Fig-4.2).




Fig-4.2 Illustration for Cheek Position

3. Tilted Position

- To position the device in the "cheek" position described above.
- While maintaining the device the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until contact with the ear is lost (see Fig-4.3).




Fig-4.3 Illustration for Tilted Position

4.2.2 Body-worn Accessory Exposure Conditions

Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in KDB 447498 are used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is $> 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.

Body-worn accessories that do not contain metallic or conductive components may be tested according to worst-case exposure configurations, typically according to the smallest test separation distance required for the group of body-worn accessories with similar operating and exposure characteristics. All body-worn accessories containing metallic components are tested in conjunction with the host device.

Body-worn accessory SAR compliance is based on a single minimum test separation distance for all wireless and operating modes applicable to each body-worn accessory used by the host, and according to the relevant voice and/or data mode transmissions and operations. If a body-worn accessory supports voice only operations in its normal and expected use conditions, testing of data mode for body-worn compliance is not required.

A conservative minimum test separation distance for supporting off-the-shelf body-worn accessories that may be acquired by users of consumer handsets is used to test for body-worn accessory SAR compliance. This distance is determined by the handset manufacturer, according to the requirements of Supplement C 01-01. Devices that are designed to operate on the body of users using lanyards and straps, or without requiring additional body-worn accessories, will be tested using a conservative minimum test separation distance $\leq 5 \text{ mm}$ to support compliance.





Fig-4.4 Illustration for Body Worn Position

4.2.3 Hotspot Mode Exposure Conditions

For handsets that support hotspot mode operations, with wireless router capabilities and various web browsing functions, the relevant hand and body exposure conditions are tested according to the hotspot SAR procedures in KDB 941225 D06. A test separation distance of 10 mm is required between the phantom and all surfaces and edges with a transmitting antenna located within 25 mm from that surface or edge. When the form factor of a handset is smaller than 9 cm x 5 cm, a test separation distance of 5 mm (instead of 10 mm) is required for testing hotspot mode. When the separation distance required for body-worn accessory testing is larger than or equal to that tested for hotspot mode, in the same wireless mode and for the same surface of the phone, the hotspot mode SAR data may be used to support body-worn accessory SAR compliance for that particular configuration (surface).



Based on the antenna location shown on appendix D of this report, the SAR testing required for hotspot mode is listed as below.

Antenna	Front Face	Rear Face	Left Side	Right Side	Top Side	Bottom Side
WWAN Ant-0	V	V	V	V		V
WLAN / BT	V	V	V	V	V	

4.2.4 Extremity Exposure Conditions

For smart phones with a display diagonal dimension > 15 cm or an overall diagonal dimension > 16 cm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, the following phablet procedures should be applied to evaluate SAR compliance for each applicable wireless modes and frequency band. Devices marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance.

1. The normally required head and body-worn accessory SAR test procedures for handsets, including hotspot mode, must be applied.
2. The UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna located at ≤ 25 mm from that surface or edge, in direct contact with a flat phantom, for 10-g extremity SAR according to the body-equivalent tissue dielectric parameters in KDB 865664 to address interactive hand use exposure conditions. The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g SAR > 1.2 W/kg. The normal tablet procedures in KDB 616217 are required when the over diagonal dimension of the device is > 20 cm. Hotspot mode SAR is not required when normal tablet procedures are applied. Extremity 10-g SAR is also not required for the front (top) surface of large form factor full size tablets. The more conservative tablet SAR results can be used to support the 10-g extremity SAR for phablet mode.
3. The simultaneous transmission operating configurations applicable to voice and data transmissions for both phone and mini-tablet modes must be taken into consideration separately for 1-g and 10-g SAR to determine the simultaneous transmission SAR test exclusion and measurement requirements for the relevant wireless modes and exposure conditions.

4.2.5 SAR Test Exclusion Evaluations

According to KDB 447498 D01, the SAR test exclusion condition is based on source-based time-averaged maximum conducted output power, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions. The SAR exclusion threshold is determined by the following formula.

$$\frac{\text{Max. Tune up Power}_{(\text{mW})}}{\text{Min. Test Separation Distance}_{(\text{mm})}} \times \sqrt{f_{(\text{GHz})}} \leq 3.0 \text{ for SAR-1g, } \leq 7.5 \text{ for SAR-10g}$$

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Mode	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	Body-Worn		
			Ant. to Surface (mm)	Calculated Result	Require SAR Testing?
BT (2.48 GHz)	8.0	6.31	10	1.0	No

Note:

1. When separation distance ≤ 50 mm and the calculated result shown in above table is ≤ 3.0 for SAR-1g exposure condition, or ≤ 7.5 for SAR-10g exposure condition, the SAR testing exclusion is applied.

FCC SAR Test Report

4.2.6 Simultaneous Transmission Possibilities

The simultaneous transmission possibilities for this device are listed as below.

Simultaneous TX Combination	Capable Transmit Configurations	Head (Voice / VoIP)	Body-worn (Voice / VoIP)	Hotspot (Data)
1	GSM850 (Voice / Data) + WLAN (Data)	Yes	Yes	Yes
2	GSM1900 (Voice / Data) + WLAN (Data)	Yes	Yes	Yes
3	WCDMA II (Voice / Data) + WLAN (Data)	Yes	Yes	Yes
4	WCDMA IV (Voice / Data) + WLAN (Data)	Yes	Yes	Yes
5	WCDMA V (Voice / Data) + WLAN (Data)	Yes	Yes	Yes
6	LTE 2 (Data) + WLAN (Data)	Yes	Yes	Yes
7	LTE 4 (Data) + WLAN (Data)	Yes	Yes	Yes
8	LTE 5 (Data) + WLAN (Data)	Yes	Yes	Yes
9	LTE 7 (Data) + WLAN (Data)	Yes	Yes	Yes
10	LTE 12 (Data) + WLAN (Data)	Yes	Yes	Yes
11	LTE 66 (Data) + WLAN (Data)	Yes	Yes	Yes
12	GSM850 (Voice / Data) + BT (Data)	No	Yes	No
13	GSM1900 (Voice / Data) + BT (Data)	No	Yes	No
14	WCDMA II (Voice / Data) + BT (Data)	No	Yes	No
15	WCDMA IV (Voice / Data) + BT (Data)	No	Yes	No
16	WCDMA V (Voice / Data) + BT (Data)	No	Yes	No
17	LTE 2 (Data) + BT (Data)	No	Yes	No
18	LTE 4 (Data) + BT (Data)	No	Yes	No
19	LTE 5 (Data) + BT (Data)	No	Yes	No
20	LTE 7 (Data) + BT (Data)	No	Yes	No
21	LTE 12 (Data) + BT (Data)	No	Yes	No
22	LTE 66 (Data) + BT (Data)	No	Yes	No

Note : The WLAN and Bluetooth cannot transmit simultaneously, so there is no co-location test requirement for WLAN and Bluetooth.

FCC SAR Test Report

4.3 Tissue Verification

The measuring results for tissue simulating liquid are shown as below.

Test Date	Tissue Type	Frequency (MHz)	Liquid Temp. (°C)	Measured Conductivity (σ)	Measured Permittivity (ϵ_r)	Target Conductivity (σ)	Target Permittivity (ϵ_r)	Conductivity Deviation (%)	Permittivity Deviation (%)
Mar. 26, 2019	HL750	750	22.1	0.88	41.87	0.89	41.90	-1.12	-0.07
Mar. 27, 2019	HL850	835	21.8	0.92	41.37	0.90	41.50	2.22	-0.31
Mar. 28, 2019	HL1800	1800	22.2	1.38	40.07	1.40	40.00	-1.43	0.18
Mar. 29, 2019	HL1900	1900	21.9	1.39	39.93	1.40	40.00	-0.71	-0.18
Mar. 30, 2019	HL2450	2450	22.1	1.79	39.16	1.80	39.20	-0.56	-0.10
Mar. 31, 2019	HL2600	2600	21.6	1.93	38.91	1.96	39.00	-1.53	-0.23
Mar. 26, 2019	BL750	750	21.9	0.97	56.62	1.00	56.80	-3.00	-0.32
Mar. 27, 2019	BL850	835	21.8	0.95	55.08	0.97	55.20	-2.06	-0.22
Mar. 28, 2019	BL1800	1800	21.9	1.49	52.40	1.52	53.30	-1.97	-1.69
Mar. 29, 2019	BL1900	1900	21.7	1.50	52.85	1.52	53.30	-1.32	-0.84
Mar. 30, 2019	BL2450	2450	21.6	1.91	52.41	1.95	52.70	-2.05	-0.55
Mar. 31, 2019	BL2600	2600	21.5	2.11	51.93	2.16	52.50	-2.31	-1.09

Note:

1. The dielectric properties of the tissue simulating liquid must be measured within 24 hours before the SAR testing and within $\pm 5\%$ of the target values. Liquid temperature during the SAR testing must be within $\pm 2^\circ\text{C}$.
2. Since the maximum deviation of dielectric properties of the tissue simulating liquid is within 5%, SAR correction is evaluated in the measurement uncertainty shown on section 6 of this report.

4.4 System Validation

The SAR measurement system was validated according to procedures in KDB 865664 D01. The validation status in tabulated summary is as below.

Test Date	Probe S/N	Calibration Point		Measured Conductivity (σ)	Measured Permittivity (ϵ_r)	Validation for CW			Validation for Modulation		
						Sensitivity Range	Probe Linearity	Probe Isotropy	Modulation Type	Duty Factor	PAR
Mar. 26, 2019	SN 27/15 EPGO262	Head	750	0.88	41.87	Pass	Pass	Pass	N/A	N/A	N/A
Mar. 27, 2019	SN 27/15 EPGO262	Head	835	0.92	41.37	Pass	Pass	Pass	GMSK	Pass	N/A
Mar. 28, 2019	SN 27/15 EPGO262	Head	1800	1.38	40.07	Pass	Pass	Pass	N/A	N/A	N/A
Mar. 29, 2019	SN 27/15 EPGO262	Head	1900	1.39	39.93	Pass	Pass	Pass	GMSK	Pass	N/A
Mar. 30, 2019	SN 27/15 EPGO262	Head	2450	1.79	39.16	Pass	Pass	Pass	OFDM	N/A	Pass
Mar. 31, 2019	SN 27/15 EPGO262	Head	2600	1.93	38.91	Pass	Pass	Pass	N/A	N/A	N/A
Mar. 26, 2019	SN 27/15 EPGO262	Body	750	0.97	56.62	Pass	Pass	Pass	N/A	N/A	N/A
Mar. 27, 2019	SN 27/15 EPGO262	Body	835	0.95	55.08	Pass	Pass	Pass	GMSK	Pass	N/A
Mar. 28, 2019	SN 27/15 EPGO262	Body	1800	1.49	52.40	Pass	Pass	Pass	N/A	N/A	N/A
Mar. 29, 2019	SN 27/15 EPGO262	Body	1900	1.50	52.85	Pass	Pass	Pass	GMSK	Pass	N/A
Mar. 30, 2019	SN 27/15 EPGO262	Body	2450	1.91	52.41	Pass	Pass	Pass	OFDM	N/A	Pass
Mar. 31, 2019	SN 27/15 EPGO262	Body	2600	2.11	51.93	Pass	Pass	Pass	N/A	N/A	N/A

FCC SAR Test Report

4.5 System Verification

The measuring result for system verification is tabulated as below.

Test Date	Mode	Frequency (MHz)	1W Target SAR-1g (W/kg)	Measured SAR-1g (W/kg)	Normalized to 1W SAR-1g (W/kg)	Deviation (%)	Dipole S/N	Probe S/N	DAE S/N
Mar. 26, 2019	Head	750	8.55	0.84	8.44	-1.29	SN 26/14 DIP0G750-325	SN 27/15 EPGO262	
Mar. 27, 2019	Head	835	9.64	0.93	9.30	-3.53	SN 18/11 DIPC150	SN 27/15 EPGO262	1331865
Mar. 28, 2019	Head	1800	37.99	3.69	36.87	-2.95	SN 18/11 DIPF152	SN 27/15 EPGO262	1331865
Mar. 29, 2019	Head	1900	39.88	3.86	38.61	-3.18	SN 18/11 DIPG153	SN 27/15 EPGO262	1331865
Mar. 30, 2019	Head	2450	53.18	5.21	52.10	-2.03	SN 18/11 DIPJ155	SN 27/15 EPGO262	1331865
Mar. 31, 2019	Head	2600	54.89	5.43	54.30	-1.07	SN 26/14 DIP2G600-326	SN 27/15 EPGO262	1331865
Mar. 26, 2019	Body	750	8.75	0.85	8.50	-2.86	SN 26/14 DIP0G750-325	SN 27/15 EPGO262	
Mar. 27, 2019	Body	835	9.96	0.97	9.70	-2.61	SN 18/11 DIPC150	SN 27/15 EPGO262	1331865
Mar. 28, 2019	Body	1800	39.62	3.92	39.20	-1.06	SN 18/11 DIPF152	SN 27/15 EPGO262	1331865
Mar. 29, 2019	Body	1900	40.38	3.98	39.80	-1.44	SN 18/11 DIPG153	SN 27/15 EPGO262	1331865
Mar. 30, 2019	Body	2450	52.73	5.15	51.50	-2.33	SN 18/11 DIPJ155	SN 27/15 EPGO262	1331865
Mar. 31, 2019	Body	2600	54.23	5.37	53.70	-0.98	SN 26/14 DIP2G600-326	SN 27/15 EPGO262	1331865

Note:

Comparing to the reference SAR value provided by MVG, the validation data should be within its specification of 10 %. The result indicates the system check can meet the variation criterion and the plots can be referred to Appendix A of this report.

FCC SAR Test Report

4.6 Maximum Output Power

4.6.1 Maximum Conducted Power

The maximum conducted average power (Unit: dBm) including tune-up tolerance is shown as below.

Mode	GSM850	GSM1900
GSM (GMSK, 1Tx-slot)	33.0	30.5
GPRS (GMSK, 1Tx-slot)	33.0	30.5
GPRS (GMSK, 2Tx-slot)	31.0	28.5
GPRS (GMSK, 3Tx-slot)	29.0	27.5
GPRS (GMSK, 4Tx-slot)	27.0	25.5
EDGE (8PSK, 1Tx-slot)	26.5	25.5
EDGE (8PSK, 2Tx-slot)	25.0	24.0
EDGE (8PSK, 3Tx-slot)	22.5	21.5
EDGE (8PSK, 4Tx-slot)	20.0	19.0

Mode	WCDMA Band II	WCDMA Band IV	WCDMA Band V
RMC 12.2K	23.0	23.0	23.0
HSDPA	22.0	22.0	22.0
HSUPA	22.0	22.0	22.0

Mode	LTE 2	LTE 4	LTE 5
QPSK / 16QAM	23.0 / 22.0	23.0 / 22.0	22.5 / 21.5

Mode	LTE 7	LTE 12	LTE 66
QPSK / 16QAM	23.5 / 22.5	23.0 / 22.0	23.0 / 22.0

Mode	2.4G WLAN
802.11b	17.0
802.11g	CH1-6: 13.5 CH7-11: 12.5
802.11n HT20	12.5

Mode	2.4G Bluetooth
GFSK	8.0
$\pi/4$ -DQPSK	5.5
8-DPSK	5.5
LE	CH0-19: 3.0 CH20-39: 5.0

FCC SAR Test Report

4.6.2 Measured Conducted Power Result

The measuring conducted average power (Unit: dBm) is shown as below.

Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency (MHz)	824.2	836.4	848.8	1850.2	1880.0	1909.8
Maximum Burst-Averaged Output Power						
GSM (GMSK, 1Tx-slot)	32.56	32.52	32.62	30.28	30.11	29.91
GPRS (GMSK, 1Tx-slot)	32.55	32.51	32.59	30.26	30.12	29.88
GPRS (GMSK, 2Tx-slot)	30.49	30.46	30.50	28.25	28.05	27.87
GPRS (GMSK, 3Tx-slot)	28.63	28.05	28.66	26.79	26.60	26.44
GPRS (GMSK, 4Tx-slot)	26.58	26.62	26.63	24.88	24.72	24.58
EDGE (8PSK, 1Tx-slot)	25.57	25.66	25.57	24.84	25.34	25.20
EDGE (8PSK, 2Tx-slot)	24.41	24.51	24.40	23.37	23.88	23.65
EDGE (8PSK, 3Tx-slot)	22.07	22.16	22.05	20.84	21.34	20.91
EDGE (8PSK, 4Tx-slot)	19.36	19.53	19.36	18.03	18.61	18.32
Maximum Frame-Averaged Output Power						
GSM (GMSK, 1Tx-slot)	23.56	23.52	23.62	21.28	21.11	20.91
GPRS (GMSK, 1Tx-slot)	23.55	23.51	23.59	21.26	21.12	20.88
GPRS (GMSK, 2Tx-slot)	24.49	24.46	24.50	22.25	22.05	21.87
GPRS (GMSK, 3Tx-slot)	24.37	23.79	24.40	22.53	22.34	22.18
GPRS (GMSK, 4Tx-slot)	23.58	23.62	23.63	21.88	21.72	21.58
EDGE (8PSK, 1Tx-slot)	16.57	16.66	16.57	15.84	16.34	16.20
EDGE (8PSK, 2Tx-slot)	18.41	18.51	18.40	17.37	17.88	17.65
EDGE (8PSK, 3Tx-slot)	17.81	17.90	17.79	16.58	17.08	16.65
EDGE (8PSK, 4Tx-slot)	16.36	16.53	16.36	15.03	15.61	15.32

Note:

- SAR testing was performed on the maximum frame-averaged power mode.
- The frame-averaged power is linearly proportion to the slot number configured and it is linearly scaled the maximum burst-averaged power based on time slots. The calculated method is shown as below:
Frame-averaged power = 10 x log (Burst-averaged power mW x Slot used / 8)
- The configuration of time-slot for GSM has transmitting signal in one time-slot during one frame (8 time-slots).

Band	WCDMA Band II			WCDMA Band IV			WCDMA Band V			3GPP MPR (dB)
Channel	9262	9400	9538	1312	1413	1513	4132	4182	4233	
Frequency (MHz)	1852.4	1880.0	1907.6	1712.4	1732.6	1752.6	826.4	836.4	846.6	
RMC 12.2K	22.52	22.58	22.53	22.46	22.42	22.33	22.74	22.72	22.76	-
HSDPA Subtest-1	21.46	21.52	21.41	21.35	21.48	21.39	21.62	21.70	21.69	0
HSDPA Subtest-2	21.34	21.29	21.38	21.28	21.41	21.35	21.58	21.67	21.54	0
HSDPA Subtest-3	20.95	20.79	20.93	20.81	20.96	20.82	21.13	21.19	21.17	0.5
HSDPA Subtest-4	20.83	20.78	20.86	20.86	20.93	20.87	20.07	21.13	21.04	0.5
HSUPA Subtest-1	21.41	21.49	21.38	21.25	21.43	21.36	21.57	21.66	21.61	0
HSUPA Subtest-2	19.46	19.34	19.31	19.13	19.45	19.32	19.59	19.57	19.62	2
HSUPA Subtest-3	20.37	20.19	20.42	20.11	20.29	20.34	20.61	20.76	20.51	1
HSUPA Subtest-4	19.34	19.51	19.42	19.08	19.39	19.26	19.62	19.45	19.71	2
HSUPA Subtest-5	21.31	21.37	21.32	21.21	21.36	21.25	21.52	21.59	21.56	0

FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 18607	Mid CH 18900	High CH 19193		Low CH 18607	Mid CH 18900	High CH 19193	
			1850.7 MHz	1880.0 MHz	1909.3 MHz		1850.7 MHz	1880.0 MHz	1909.3 MHz	
2 / 1.4M	1	0	22.26	22.32	22.08	0	21.12	21.18	20.94	1
	1	2	22.10	22.16	21.92	0	20.98	21.04	20.80	1
	1	5	22.03	22.09	21.85	0	20.94	21.00	20.76	1
	3	0	21.18	21.24	21.00	0	20.23	20.29	20.05	1
	3	1	21.11	21.17	20.93	0	20.13	20.19	19.95	1
	3	3	21.12	21.18	20.94	0	20.21	20.27	20.03	1
	6	0	21.09	21.15	20.91	1	20.30	20.36	20.12	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 18615	Mid CH 18900	High CH 19185		Low CH 18615	Mid CH 18900	High CH 19185	
			1851.5 MHz	1880.0 MHz	1908.5 MHz		1851.5 MHz	1880.0 MHz	1908.5 MHz	
2 / 3M	1	0	22.29	22.35	22.11	0	21.15	21.21	20.97	1
	1	7	22.13	22.19	21.95	0	21.01	21.07	20.83	1
	1	14	22.06	22.12	21.88	0	20.97	21.03	20.79	1
	8	0	21.19	21.25	21.01	1	20.25	20.31	20.07	2
	8	3	21.12	21.18	20.94	1	20.15	20.21	19.97	2
	8	7	21.13	21.19	20.95	1	20.23	20.29	20.05	2
	15	0	21.10	21.16	20.92	1	20.32	20.38	20.14	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 18625	Mid CH 18900	High CH 19175		Low CH 18625	Mid CH 18900	High CH 19175	
			1852.5 MHz	1880.0 MHz	1907.5 MHz		1852.5 MHz	1880.0 MHz	1907.5 MHz	
2 / 5M	1	0	22.32	22.38	22.14	0	21.18	21.24	21.00	1
	1	12	22.16	22.22	21.98	0	21.04	21.10	20.86	1
	1	24	22.09	22.15	21.91	0	21.00	21.06	20.82	1
	12	0	21.22	21.28	21.04	1	20.28	20.34	20.10	2
	12	6	21.15	21.21	20.97	1	20.18	20.24	20.00	2
	12	13	21.16	21.22	20.98	1	20.26	20.32	20.08	2
	25	0	21.13	21.19	20.95	1	20.35	20.41	20.17	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 18650	Mid CH 18900	High CH 19150		Low CH 18650	Mid CH 18900	High CH 19150	
			1855.0 MHz	1880.0 MHz	1905.0 MHz		1855.0 MHz	1880.0 MHz	1905.0 MHz	
2 / 10M	1	0	22.34	22.40	22.16	0	21.20	21.26	21.02	1
	1	24	22.18	22.24	22.00	0	21.06	21.12	20.88	1
	1	49	22.11	22.17	21.93	0	21.02	21.08	20.84	1
	25	0	21.24	21.30	21.06	1	20.30	20.36	20.12	2
	25	12	21.17	21.23	20.99	1	20.20	20.26	20.02	2
	25	25	21.18	21.24	21.00	1	20.28	20.34	20.10	2
	50	0	21.15	21.21	20.97	1	20.37	20.43	20.19	2

FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 18675	Mid CH 18900	High CH 19125		Low CH 18675	Mid CH 18900	High CH 19125	
			1857.5 MHz	1880.0 MHz	1902.5 MHz		1857.5 MHz	1880.0 MHz	1902.5 MHz	
2 / 15M	1	0	22.37	22.43	22.19	0	21.23	21.29	21.05	1
	1	37	22.21	22.27	22.03	0	21.09	21.15	20.91	1
	1	74	22.14	22.20	21.96	0	21.05	21.11	20.87	1
	36	0	21.27	21.33	21.09	1	20.33	20.39	20.15	2
	36	19	21.20	21.26	21.02	1	20.23	20.29	20.05	2
	36	39	21.21	21.27	21.03	1	20.31	20.37	20.13	2
	75	0	21.18	21.24	21.00	1	20.40	20.46	20.22	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 18700	Mid CH 18900	High CH 19100		Low CH 18700	Mid CH 18900	High CH 19100	
			1860.0 MHz	1880.0 MHz	1900.0 MHz		1860.0 MHz	1880.0 MHz	1900.0 MHz	
2 / 20M	1	0	22.42	22.48	22.24	0	21.28	21.34	21.10	1
	1	50	22.26	22.32	22.08	0	21.14	21.20	20.96	1
	1	99	22.19	22.25	22.01	0	21.10	21.16	20.92	1
	50	0	21.32	21.38	21.14	1	20.38	20.44	20.20	2
	50	25	21.25	21.31	21.07	1	20.28	20.34	20.10	2
	50	50	21.26	21.32	21.08	1	20.36	20.42	20.18	2
	100	0	21.23	21.29	21.05	1	20.45	20.51	20.27	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 19957	Mid CH 20175	High CH 20393		Low CH 19957	Mid CH 20175	High CH 20393	
			1710.7 MHz	1732.5 MHz	1754.3 MHz		1710.7 MHz	1732.5 MHz	1754.3 MHz	
4 / 1.4M	1	0	22.29	22.22	22.12	0	21.67	21.60	21.50	1
	1	2	22.21	22.14	22.04	0	21.49	21.42	21.32	1
	1	5	22.11	22.04	21.94	0	21.46	21.39	21.29	1
	3	0	21.29	21.22	21.12	0	20.37	20.30	20.20	1
	3	1	21.10	21.03	20.93	0	20.28	20.21	20.11	1
	3	3	21.21	21.14	21.04	0	20.30	20.23	20.13	1
	6	0	21.17	21.10	21.00	1	20.23	20.16	20.06	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 19965	Mid CH 20175	High CH 20385		Low CH 19965	Mid CH 20175	High CH 20385	
			1711.5 MHz	1732.5 MHz	1753.5 MHz		1711.5 MHz	1732.5 MHz	1753.5 MHz	
4 / 3M	1	0	22.30	22.23	22.13	0	21.68	21.61	21.51	1
	1	7	22.22	22.15	22.05	0	21.50	21.43	21.33	1
	1	14	22.12	22.05	21.95	0	21.47	21.40	21.30	1
	8	0	21.31	21.24	21.14	1	20.38	20.31	20.21	2
	8	3	21.12	21.05	20.95	1	20.29	20.22	20.12	2
	8	7	21.23	21.16	21.06	1	20.31	20.24	20.14	2
	15	0	21.19	21.12	21.02	1	20.24	20.17	20.07	2

FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 19975	Mid CH 20175	High CH 20375		Low CH 19975	Mid CH 20175	High CH 20375	
			1712.5 MHz	1732.5 MHz	1752.5 MHz		1712.5 MHz	1732.5 MHz	1752.5 MHz	
4 / 5M	1	0	22.33	22.26	22.16	0	21.71	21.64	21.54	1
	1	12	22.25	22.18	22.08	0	21.53	21.46	21.36	1
	1	24	22.15	22.08	21.98	0	21.50	21.43	21.33	1
	12	0	21.34	21.27	21.17	1	20.41	20.34	20.24	2
	12	6	21.15	21.08	20.98	1	20.32	20.25	20.15	2
	12	13	21.26	21.19	21.09	1	20.34	20.27	20.17	2
	25	0	21.22	21.15	21.05	1	20.27	20.20	20.10	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20000	Mid CH 20175	High CH 20350		Low CH 20000	Mid CH 20175	High CH 20350	
			1715.0 MHz	1732.5 MHz	1750.0 MHz		1715.0 MHz	1732.5 MHz	1750.0 MHz	
4 / 10M	1	0	22.37	22.30	22.20	0	21.75	21.68	21.58	1
	1	24	22.29	22.22	22.12	0	21.57	21.50	21.40	1
	1	49	22.19	22.12	22.02	0	21.54	21.47	21.37	1
	25	0	21.38	21.31	21.21	1	20.45	20.38	20.28	2
	25	12	21.19	21.12	21.02	1	20.36	20.29	20.19	2
	25	25	21.30	21.23	21.13	1	20.38	20.31	20.21	2
	50	0	21.26	21.19	21.09	1	20.31	20.24	20.14	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20025	Mid CH 20175	High CH 20325		Low CH 20025	Mid CH 20175	High CH 20325	
			1717.5 MHz	1732.5 MHz	1747.5 MHz		1717.5 MHz	1732.5 MHz	1747.5 MHz	
4 / 15M	1	0	22.43	22.36	22.26	0	21.81	21.74	21.64	1
	1	37	22.35	22.28	22.18	0	21.63	21.56	21.46	1
	1	74	22.25	22.18	22.08	0	21.60	21.53	21.43	1
	36	0	21.44	21.37	21.27	1	20.51	20.44	20.34	2
	36	19	21.25	21.18	21.08	1	20.42	20.35	20.25	2
	36	39	21.36	21.29	21.19	1	20.44	20.37	20.27	2
	75	0	21.32	21.25	21.15	1	20.37	20.30	20.20	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20050	Mid CH 20175	High CH 20300		Low CH 20050	Mid CH 20175	High CH 20300	
			1720.0 MHz	1732.5 MHz	1745.0 MHz		1720.0 MHz	1732.5 MHz	1745.0 MHz	
4 / 20M	1	0	22.46	22.39	22.29	0	21.84	21.77	21.67	1
	1	50	22.38	22.31	22.21	0	21.66	21.59	21.49	1
	1	99	22.28	22.21	22.11	0	21.63	21.56	21.46	1
	50	0	21.47	21.40	21.30	1	20.54	20.47	20.37	2
	50	25	21.28	21.21	21.11	1	20.45	20.38	20.28	2
	50	50	21.39	21.32	21.22	1	20.47	20.40	20.30	2
	100	0	21.35	21.28	21.18	1	20.40	20.33	20.23	2

FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20407	Mid CH 20525	High CH 20643		Low CH 20407	Mid CH 20525	High CH 20643	
			824.7 MHz	836.5 MHz	848.3 MHz		824.7 MHz	836.5 MHz	848.3 MHz	
5 / 1.4M	1	0	21.99	22.05	22.02	0	21.19	21.25	21.22	1
	1	2	21.92	21.98	21.95	0	21.02	21.08	21.05	1
	1	5	21.87	21.93	21.90	0	21.12	21.18	21.15	1
	3	0	21.09	21.15	21.12	0	20.26	20.32	20.29	1
	3	1	20.96	21.02	20.99	0	20.22	20.28	20.25	1
	3	3	20.90	20.96	20.93	0	20.20	20.26	20.23	1
	6	0	20.94	21.00	20.97	1	20.19	20.25	20.22	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20415	Mid CH 20525	High CH 20635		Low CH 20415	Mid CH 20525	High CH 20635	
			825.5 MHz	836.5 MHz	847.5 MHz		825.5 MHz	836.5 MHz	847.5 MHz	
5 / 3M	1	0	22.03	22.09	22.06	0	21.23	21.29	21.26	1
	1	7	21.96	22.02	21.99	0	21.06	21.12	21.09	1
	1	14	21.91	21.97	21.94	0	21.16	21.22	21.19	1
	8	0	21.11	21.17	21.14	1	20.27	20.33	20.30	2
	8	3	20.98	21.04	21.01	1	20.23	20.29	20.26	2
	8	7	20.92	20.98	20.95	1	20.21	20.27	20.24	2
	15	0	20.96	21.02	20.99	1	20.20	20.26	20.23	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20425	Mid CH 20525	High CH 20625		Low CH 20425	Mid CH 20525	High CH 20625	
			826.5 MHz	836.5 MHz	846.5 MHz		826.5 MHz	836.5 MHz	846.5 MHz	
5 / 5M	1	0	22.09	22.15	22.12	0	21.29	21.35	21.32	1
	1	12	22.02	22.08	22.05	0	21.12	21.18	21.15	1
	1	24	21.97	22.03	22.00	0	21.22	21.28	21.25	1
	12	0	21.17	21.23	21.20	1	20.33	20.39	20.36	2
	12	6	21.04	21.10	21.07	1	20.29	20.35	20.32	2
	12	13	20.98	21.04	21.01	1	20.27	20.33	20.30	2
	25	0	21.02	21.08	21.05	1	20.26	20.32	20.29	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20450	Mid CH 20525	High CH 20600		Low CH 20450	Mid CH 20525	High CH 20600	
			829.0 MHz	836.5 MHz	844.0 MHz		829.0 MHz	836.5 MHz	844.0 MHz	
5 / 10M	1	0	22.12	22.18	22.15	0	21.32	21.38	21.35	1
	1	24	22.05	22.11	22.08	0	21.15	21.21	21.18	1
	1	49	22.00	22.06	22.03	0	21.25	21.31	21.28	1
	25	0	21.20	21.26	21.23	1	20.36	20.42	20.39	2
	25	12	21.07	21.13	21.10	1	20.32	20.38	20.35	2
	25	25	21.01	21.07	21.04	1	20.30	20.36	20.33	2
	50	0	21.05	21.11	21.08	1	20.29	20.35	20.32	2

FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20775	Mid CH 21100	High CH 21425		Low CH 20775	Mid CH 21100	High CH 21425	
			2502.5 MHz	2535.0 MHz	2567.5 MHz		2502.5 MHz	2535.0 MHz	2567.5 MHz	
7 / 5M	1	0	22.61	22.69	22.43	0	21.67	21.75	21.49	1
	1	12	22.53	22.61	22.35	0	21.76	21.84	21.58	1
	1	24	22.50	22.58	22.32	0	21.80	21.88	21.62	1
	12	0	21.66	21.74	21.48	1	20.70	20.78	20.52	2
	12	6	21.62	21.70	21.44	1	20.66	20.74	20.48	2
	12	13	21.56	21.64	21.38	1	20.74	20.82	20.56	2
	25	0	21.63	21.71	21.45	1	20.72	20.80	20.54	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20800	Mid CH 21100	High CH 21400		Low CH 20800	Mid CH 21100	High CH 21400	
			2505.0 MHz	2535.0 MHz	2565.0 MHz		2505.0 MHz	2535.0 MHz	2565.0 MHz	
7 / 10M	1	0	22.65	22.73	22.47	0	21.71	21.79	21.53	1
	1	24	22.57	22.65	22.39	0	21.80	21.88	21.62	1
	1	49	22.54	22.62	22.36	0	21.84	21.92	21.66	1
	25	0	21.70	21.78	21.52	1	20.74	20.82	20.56	2
	25	12	21.66	21.74	21.48	1	20.70	20.78	20.52	2
	25	25	21.60	21.68	21.42	1	20.78	20.86	20.60	2
	50	0	21.67	21.75	21.49	1	20.76	20.84	20.58	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20825	Mid CH 21100	High CH 21375		Low CH 20825	Mid CH 21100	High CH 21375	
			2507.5 MHz	2535.0 MHz	2562.5 MHz		2507.5 MHz	2535.0 MHz	2562.5 MHz	
7 / 15M	1	0	22.71	22.79	22.53	0	21.77	21.85	21.59	1
	1	37	22.63	22.71	22.45	0	21.86	21.94	21.68	1
	1	74	22.60	22.68	22.42	0	21.90	21.98	21.72	1
	36	0	21.76	21.84	21.58	1	20.80	20.88	20.62	2
	36	19	21.72	21.80	21.54	1	20.76	20.84	20.58	2
	36	39	21.66	21.74	21.48	1	20.84	20.92	20.66	2
	75	0	21.73	21.81	21.55	1	20.82	20.90	20.64	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20850	Mid CH 21100	High CH 21350		Low CH 20850	Mid CH 21100	High CH 21350	
			2510.0 MHz	2535.0 MHz	2560.0 MHz		2510.0 MHz	2535.0 MHz	2560.0 MHz	
7 / 20M	1	0	22.74	22.82	22.56	0	21.80	21.88	21.62	1
	1	50	22.66	22.74	22.48	0	21.89	21.97	21.71	1
	1	99	22.63	22.71	22.45	0	21.93	22.01	21.75	1
	50	0	21.79	21.87	21.61	1	20.83	20.91	20.65	2
	50	25	21.75	21.83	21.57	1	20.79	20.87	20.61	2
	50	50	21.69	21.77	21.51	1	20.87	20.95	20.69	2
	100	0	21.76	21.84	21.58	1	20.85	20.93	20.67	2

FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 23017	Mid CH 23095	High CH 23173		Low CH 23017	Mid CH 23095	High CH 23173	
			699.7 MHz	707.5 MHz	715.3 MHz		699.7 MHz	707.5 MHz	715.3 MHz	
12 / 1.4M	1	0	22.30	22.34	22.25	0	21.30	21.34	21.25	1
	1	2	22.14	22.18	22.09	0	21.18	21.22	21.13	1
	1	5	22.11	22.15	22.06	0	21.26	21.30	21.21	1
	3	0	22.28	22.32	22.23	0	21.29	21.33	21.24	1
	3	1	22.12	22.16	22.07	0	21.17	21.21	21.12	1
	3	3	22.09	22.13	22.04	0	21.25	21.29	21.20	1
	6	0	21.09	21.13	21.04	1	20.25	20.29	20.20	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 23025	Mid CH 23095	High CH 23165		Low CH 23025	Mid CH 23095	High CH 23165	
			700.5 MHz	707.5 MHz	714.5 MHz		700.5 MHz	707.5 MHz	714.5 MHz	
12 / 3M	1	0	22.34	22.38	22.29	0	21.34	21.38	21.29	1
	1	7	22.18	22.22	22.13	0	21.22	21.26	21.17	1
	1	14	22.15	22.19	22.10	0	21.30	21.34	21.25	1
	8	0	21.32	21.36	21.27	1	20.56	20.60	20.51	2
	8	3	21.25	21.29	21.20	1	20.51	20.55	20.46	2
	8	7	21.24	21.28	21.19	1	20.43	20.47	20.38	2
	15	0	21.13	21.17	21.08	1	20.29	20.33	20.24	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 23035	Mid CH 23095	High CH 23155		Low CH 23035	Mid CH 23095	High CH 23155	
			701.5 MHz	707.5 MHz	713.5 MHz		701.5 MHz	707.5 MHz	713.5 MHz	
12 / 5M	1	0	22.40	22.44	22.35	0	21.40	21.44	21.35	1
	1	12	22.24	22.28	22.19	0	21.28	21.32	21.23	1
	1	24	22.21	22.25	22.16	0	21.36	21.40	21.31	1
	12	0	21.38	21.42	21.33	1	20.62	20.66	20.57	2
	12	6	21.31	21.35	21.26	1	20.57	20.61	20.52	2
	12	13	21.30	21.34	21.25	1	20.49	20.53	20.44	2
	25	0	21.19	21.23	21.14	1	20.35	20.39	20.30	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 23060	Mid CH 23095	High CH 23130		Low CH 23060	Mid CH 23095	High CH 23130	
			704.0 MHz	707.5 MHz	711.0 MHz		704.0 MHz	707.5 MHz	711.0 MHz	
12 / 10M	1	0	22.43	22.47	22.38	0	21.43	21.47	21.38	1
	1	24	22.27	22.31	22.22	0	21.31	21.35	21.26	1
	1	49	22.24	22.28	22.19	0	21.39	21.43	21.34	1
	25	0	21.41	21.45	21.36	1	20.65	20.69	20.60	2
	25	12	21.34	21.38	21.29	1	20.60	20.64	20.55	2
	25	25	21.33	21.37	21.28	1	20.52	20.56	20.47	2
	50	0	21.22	21.26	21.17	1	20.38	20.42	20.33	2

FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 131979	Mid CH 132322	High CH 132665		Low CH 131979	Mid CH 132322	High CH 132665	
			1710.7 MHz	1745.0 MHz	1779.3 MHz		1710.7 MHz	1745.0 MHz	1779.3 MHz	
66 / 1.4M	1	0	22.56	22.35	22.21	0	21.51	21.30	21.16	1
	1	2	22.38	22.17	22.03	0	21.42	21.21	21.07	1
	1	5	22.20	21.99	21.85	0	21.36	21.15	21.01	1
	3	0	22.55	22.34	22.20	0	21.49	21.28	21.14	1
	3	1	22.37	22.16	22.02	0	21.40	21.19	21.05	1
	3	3	22.19	21.98	21.84	0	21.34	21.13	20.99	1
	6	0	21.47	21.26	21.12	1	20.47	20.26	20.12	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 131987	Mid CH 132322	High CH 132657		Low CH 131987	Mid CH 132322	High CH 132657	
			1711.5 MHz	1745.0 MHz	1778.5 MHz		1711.5 MHz	1745.0 MHz	1778.5 MHz	
66 / 3M	1	0	22.59	22.38	22.24	0	21.54	21.33	21.19	1
	1	7	22.41	22.20	22.06	0	21.45	21.24	21.10	1
	1	14	22.23	22.02	21.88	0	21.39	21.18	21.04	1
	8	0	21.59	21.38	21.24	1	20.58	20.37	20.23	2
	8	3	21.49	21.28	21.14	1	20.53	20.32	20.18	2
	8	7	21.46	21.25	21.11	1	20.42	20.21	20.07	2
	15	0	21.50	21.29	21.15	1	20.50	20.29	20.15	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 131997	Mid CH 132322	High CH 132647		Low CH 131997	Mid CH 132322	High CH 132647	
			1712.5 MHz	1745.0 MHz	1777.5 MHz		1712.5 MHz	1745.0 MHz	1777.5 MHz	
66 / 5M	1	0	22.62	22.41	22.27	0	21.57	21.36	21.22	1
	1	12	22.44	22.23	22.09	0	21.48	21.27	21.13	1
	1	24	22.26	22.05	21.91	0	21.42	21.21	21.07	1
	12	0	21.62	21.41	21.27	1	20.61	20.40	20.26	2
	12	6	21.52	21.31	21.17	1	20.56	20.35	20.21	2
	12	13	21.49	21.28	21.14	1	20.45	20.24	20.10	2
	25	0	21.53	21.32	21.18	1	20.53	20.32	20.18	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 132022	Mid CH 132322	High CH 132622		Low CH 132022	Mid CH 132322	High CH 132622	
			1715.0 MHz	1745.0 MHz	1775.0 MHz		1715.0 MHz	1745.0 MHz	1775.0 MHz	
66 / 10M	1	0	22.64	22.43	22.29	0	21.59	21.38	21.24	1
	1	24	22.46	22.25	22.11	0	21.50	21.29	21.15	1
	1	49	22.28	22.07	21.93	0	21.44	21.23	21.09	1
	25	0	21.64	21.43	21.29	1	20.63	20.42	20.28	2
	25	12	21.54	21.33	21.19	1	20.58	20.37	20.23	2
	25	25	21.51	21.30	21.16	1	20.47	20.26	20.12	2
	50	0	21.55	21.34	21.20	1	20.55	20.34	20.20	2

FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 132047	Mid CH 132322	High CH 132597		Low CH 132047	Mid CH 132322	High CH 132597	
			1717.5 MHz	1745.0 MHz	1772.5 MHz		1717.5 MHz	1745.0 MHz	1772.5 MHz	
66 / 15M	1	0	22.67	22.46	22.32	0	21.62	21.41	21.27	1
	1	37	22.49	22.28	22.14	0	21.53	21.32	21.18	1
	1	74	22.31	22.10	21.96	0	21.47	21.26	21.12	1
	36	0	21.67	21.46	21.32	1	20.66	20.45	20.31	2
	36	19	21.57	21.36	21.22	1	20.61	20.40	20.26	2
	36	39	21.54	21.33	21.19	1	20.50	20.29	20.15	2
	75	0	21.58	21.37	21.23	1	20.58	20.37	20.23	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 132072	Mid CH 132322	High CH 132572		Low CH 132072	Mid CH 132322	High CH 132572	
			1720.0 MHz	1745.0 MHz	1770.0 MHz		1720.0 MHz	1745.0 MHz	1770.0 MHz	
66 / 20M	1	0	22.72	22.51	22.37	0	21.67	21.46	21.32	1
	1	50	22.54	22.33	22.19	0	21.58	21.37	21.23	1
	1	99	22.36	22.15	22.01	0	21.52	21.31	21.17	1
	50	0	21.72	21.51	21.37	1	20.71	20.50	20.36	2
	50	25	21.62	21.41	21.27	1	20.66	20.45	20.31	2
	50	50	21.59	21.38	21.24	1	20.55	20.34	20.20	2
	100	0	21.63	21.42	21.28	1	20.63	20.42	20.28	2

FCC SAR Test Report

<WLAN 2.4G>

Mode	802.11b		
Channel / Frequency (MHz)	1 (2412)	6 (2437)	11 (2462)
Average Power	16.88	16.70	15.14
Mode	802.11g		
Channel / Frequency (MHz)	1 (2412)	6 (2437)	11 (2462)
Average Power	12.82	12.93	11.36
Mode	802.11n (HT20)		
Channel / Frequency (MHz)	1 (2412)	6 (2437)	11 (2462)
Average Power	12.05	12.22	10.72

<Bluetooth>

Mode	Bluetooth GFSK		
Channel / Frequency (MHz)	0 (2402)	39 (2441)	78 (2480)
Average Power	7.39	6.99	7.16
Mode	Bluetooth $\pi/4$ -DQPSK		
Channel / Frequency (MHz)	0 (2402)	39 (2441)	78 (2480)
Average Power	4.32	5.12	4.92
Mode	Bluetooth 8-DPSK		
Channel / Frequency (MHz)	0 (2402)	39 (2441)	78 (2480)
Average Power	4.30	5.08	4.89
Mode	Bluetooth LE		
Channel / Frequency (MHz)	0 (2402)	19 (2440)	39 (2480)
Average Power	2.43	1.95	4.39

4.7 SAR Testing Results

4.7.1 SAR Test Reduction Considerations

<KDB 447498 D01, General RF Exposure Guidance>

Testing of other required channels within the operating mode of a frequency band is not required when the reported SAR for the mid-band or highest output power channel is:

- (1) ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
- (2) ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
- (3) ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz

<KDB 941225 D01, 3G SAR Measurement Procedures>

The mode tested for SAR is referred to as the primary mode. The equivalent modes considered for SAR test reduction are denoted as secondary modes. Both primary and secondary modes must be in the same frequency band. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq 1/4$ dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode.

<KDB 941225 D05, SAR Evaluation Considerations for LTE Devices>

(1) QPSK with 1 RB and 50% RB allocation

Start with the largest channel bandwidth and measure SAR, using the RB offset and required test channel combination with the highest maximum output power among RB offsets at the upper edge, middle and lower edge of each required test channel. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel. When the reported SAR of a required test channel is > 1.45 W/kg, SAR is required for all three RB offset configurations for that required test channel.

(2) QPSK with 100% RB allocation

SAR is not required when the highest maximum output power for 100% RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.

(3) Higher order modulations

SAR is required only when the highest maximum output power for the configuration in the higher order modulation is $> 1/2$ dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is > 1.45 W/kg.

(4) Other channel bandwidth

SAR is required when the highest maximum output power of the smaller channel bandwidth is $> 1/2$ dB higher than the equivalent channel configurations in the largest channel bandwidth configuration or the reported SAR of a configuration for the largest channel bandwidth is > 1.45 W/kg.

<KDB 248227 D01, SAR Guidance for Wi-Fi Transmitters>

- (1) For handsets operating next to ear, hotspot mode or mini-tablet configurations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When the reported SAR of initial test position is ≤ 0.4 W/kg, SAR testing for remaining test positions is not required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.
- (2) For WLAN 2.4 GHz, the highest measured maximum output power channel for DSSS was selected for SAR measurement. When the reported SAR is ≤ 0.8 W/kg, no further SAR testing is required. Otherwise, SAR is evaluated at the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel. For OFDM modes (802.11g/n), SAR is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and it is ≤ 1.2 W/kg.

FCC SAR Test Report

4.7.2 SAR Results for Head Exposure Condition

Plot No.	Band	Mode	Test Position	Ch.	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaling Factor	Scaled SAR-1g (W/kg)
	GSM850	GPRS10	Right Cheek	251	31.0	30.50	0.44	0.147	1.12	0.16
	GSM850	GPRS10	Right Tilted	251	31.0	30.50	-2.06	0.123	1.12	0.14
1#	GSM850	GPRS10	Left Cheek	251	31.0	30.50	0.02	0.152	1.12	0.17
	GSM850	GPRS10	Left Tilted	251	31.0	30.50	0.38	0.141	1.12	0.16
2#	GSM1900	GPRS11	Right Cheek	512	27.5	26.79	-4.73	0.094	1.18	0.11
	GSM1900	GPRS11	Right Tilted	512	27.5	26.79	2.91	0.072	1.18	0.08
	GSM1900	GPRS11	Left Cheek	512	27.5	26.79	-1.67	0.134	1.18	0.16
	GSM1900	GPRS11	Left Tilted	512	27.5	26.79	-1.05	0.12	1.18	0.14
	WCDMA II	RMC12.2K	Right Cheek	9400	23.0	22.58	-3.95	0.149	1.10	0.16
	WCDMA II	RMC12.2K	Right Tilted	9400	23.0	22.58	1.94	0.104	1.10	0.11
3#	WCDMA II	RMC12.2K	Left Cheek	9400	23.0	22.58	-3.14	0.25	1.10	0.28
	WCDMA II	RMC12.2K	Left Tilted	9400	23.0	22.58	-2.41	0.185	1.10	0.20
4#	WCDMA IV	RMC12.2K	Right Cheek	1312	23.0	22.46	-2.63	0.346	1.13	0.39
	WCDMA IV	RMC12.2K	Right Tilted	1312	23.0	22.46	0.95	0.09	1.13	0.10
	WCDMA IV	RMC12.2K	Left Cheek	1312	23.0	22.46	-0.94	0.191	1.13	0.22
	WCDMA IV	RMC12.2K	Left Tilted	1312	23.0	22.46	-0.89	0.127	1.13	0.14
5#	WCDMA V	RMC12.2K	Right Cheek	4233	23.0	22.76	0.17	0.115	1.06	0.12
	WCDMA V	RMC12.2K	Right Tilted	4233	23.0	22.76	0.24	0.094	1.06	0.10
	WCDMA V	RMC12.2K	Left Cheek	4233	23.0	22.76	0.73	0.107	1.06	0.11
	WCDMA V	RMC12.2K	Left Tilted	4233	23.0	22.76	0.44	0.076	1.06	0.08

Plot No.	Band	Mode	Test Position	Ch.	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaling Factor	Scaled SAR-1g (W/kg)
	LTE 2	QPSK20M	Right Cheek	18900	1	0	23.0	22.48	-1.36	0.167	1.13	0.19
	LTE 2	QPSK20M	Right Tilted	18900	1	0	23.0	22.48	4.69	0.098	1.13	0.11
6#	LTE 2	QPSK20M	Left Cheek	18900	1	0	23.0	22.48	-0.54	0.244	1.13	0.28
	LTE 2	QPSK20M	Left Tilted	18900	1	0	23.0	22.48	-3.37	0.155	1.13	0.17
	LTE 2	QPSK20M	Right Cheek	18900	50	0	22.0	21.38	-1.92	0.135	1.15	0.16
	LTE 2	QPSK20M	Right Tilted	18900	50	0	22.0	21.38	-0.31	0.072	1.15	0.08
	LTE 2	QPSK20M	Left Cheek	18900	50	0	22.0	21.38	-0.7	0.194	1.15	0.22
	LTE 2	QPSK20M	Left Tilted	18900	50	0	22.0	21.38	0.15	0.112	1.15	0.13
	LTE 4	QPSK20M	Right Cheek	20050	1	0	23.0	22.46	-0.84	0.225	1.13	0.25
	LTE 4	QPSK20M	Right Tilted	20050	1	0	23.0	22.46	3.59	0.095	1.13	0.11
7#	LTE 4	QPSK20M	Left Cheek	20050	1	0	23.0	22.46	-0.58	0.271	1.13	0.31
	LTE 4	QPSK20M	Left Tilted	20050	1	0	23.0	22.46	-0.96	0.117	1.13	0.13
	LTE 4	QPSK20M	Right Cheek	20050	50	0	22.0	21.47	0.72	0.181	1.13	0.20
	LTE 4	QPSK20M	Right Tilted	20050	50	0	22.0	21.47	-0.38	0.072	1.13	0.08
	LTE 4	QPSK20M	Left Cheek	20050	50	0	22.0	21.47	2.19	0.224	1.13	0.25
	LTE 4	QPSK20M	Left Tilted	20050	50	0	22.0	21.47	-2.57	0.108	1.13	0.12
	LTE 5	QPSK10M	Right Cheek	20525	1	0	22.5	22.18	-0.22	0.132	1.08	0.14
	LTE 5	QPSK10M	Right Tilted	20525	1	0	22.5	22.18	-1.31	0.127	1.08	0.14
8#	LTE 5	QPSK10M	Left Cheek	20525	1	0	22.5	22.18	-1.31	0.249	1.08	0.27
	LTE 5	QPSK10M	Left Tilted	20525	1	0	22.5	22.18	0.43	0.132	1.08	0.14
	LTE 5	QPSK10M	Right Cheek	20525	25	0	21.5	21.26	-0.46	0.108	1.06	0.11
	LTE 5	QPSK10M	Right Tilted	20525	25	0	21.5	21.26	2.35	0.095	1.06	0.10
	LTE 5	QPSK10M	Left Cheek	20525	25	0	21.5	21.26	-0.07	0.206	1.06	0.22
	LTE 5	QPSK10M	Left Tilted	20525	25	0	21.5	21.26	-2.55	0.112	1.06	0.12

FCC SAR Test Report

Plot No.	Band	Mode	Test Position	Ch.	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaling Factor	Scaled SAR-1g (W/kg)
	LTE 7	QPSK20M	Right Cheek	21100	1	0	23.5	22.82	0.24	0.082	1.17	0.10
	LTE 7	QPSK20M	Right Tilted	21100	1	0	23.5	22.82	-0.02	0.066	1.17	0.08
9#	LTE 7	QPSK20M	Left Cheek	21100	1	0	23.5	22.82	0.38	0.133	1.17	0.16
	LTE 7	QPSK20M	Left Tilted	21100	1	0	23.5	22.82	1.78	0.104	1.17	0.12
	LTE 7	QPSK20M	Right Cheek	21100	50	0	22.5	21.87	0.15	0.071	1.16	0.08
	LTE 7	QPSK20M	Right Tilted	21100	50	0	22.5	21.87	2.19	0.061	1.16	0.07
	LTE 7	QPSK20M	Left Cheek	21100	50	0	22.5	21.87	-0.66	0.114	1.16	0.13
	LTE 7	QPSK20M	Left Tilted	21100	50	0	22.5	21.87	2.12	0.087	1.16	0.10
	LTE 12	QPSK10M	Right Cheek	23095	1	0	23.0	22.47	0.15	0.094	1.13	0.11
	LTE 12	QPSK10M	Right Tilted	23095	1	0	23.0	22.47	-2.23	0.135	1.13	0.15
10#	LTE 12	QPSK10M	Left Cheek	23095	1	0	23.0	22.47	-3.1	0.161	1.13	0.18
	LTE 12	QPSK10M	Left Tilted	23095	1	0	23.0	22.47	-0.2	0.123	1.13	0.14
	LTE 12	QPSK10M	Right Cheek	23095	25	0	22.0	21.45	-0.34	0.083	1.14	0.09
	LTE 12	QPSK10M	Right Tilted	23095	25	0	22.0	21.45	1.37	0.077	1.14	0.09
	LTE 12	QPSK10M	Left Cheek	23095	25	0	22.0	21.45	-0.92	0.142	1.14	0.16
	LTE 12	QPSK10M	Left Tilted	23095	25	0	22.0	21.45	1.45	0.105	1.14	0.12
	LTE 66	QPSK20M	Right Cheek	132072	1	0	23.0	22.72	0.6	0.248	1.07	0.26
	LTE 66	QPSK20M	Right Tilted	132072	1	0	23.0	22.72	-0.45	0.105	1.07	0.11
11#	LTE 66	QPSK20M	Left Cheek	132072	1	0	23.0	22.72	0.59	0.299	1.07	0.32
	LTE 66	QPSK20M	Left Tilted	132072	1	0	23.0	22.72	-0.61	0.123	1.07	0.13
	LTE 66	QPSK20M	Right Cheek	132072	50	0	22.0	21.72	2.26	0.197	1.07	0.21
	LTE 66	QPSK20M	Right Tilted	132072	50	0	22.0	21.72	1.15	0.084	1.07	0.09
	LTE 66	QPSK20M	Left Cheek	132072	50	0	22.0	21.72	-2.01	0.185	1.07	0.20
	LTE 66	QPSK20M	Left Tilted	132072	50	0	22.0	21.72	1.42	0.106	1.07	0.11

Plot No.	Band	Mode	Test Position	Ch.	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaling Factor	Scaled SAR-1g (W/kg)
12#	802.11b	-	Right Cheek	1	17.0	16.88	-2.86	0.733	1.03	0.75
	802.11b	-	Right Tilted	1	17.0	16.88	-1.83	0.691	1.03	0.71
	802.11b	-	Left Cheek	1	17.0	16.88	-1.11	0.527	1.03	0.54
	802.11b	-	Left Tilted	1	17.0	16.88	-1.45	0.504	1.03	0.52

4.7.3 SAR Results for Body-worn Exposure Condition (Separation Distance is 1.0 cm Gap)

Plot No.	Band	Mode	Test Position	Ch.	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaling Factor	Scaled SAR-1g (W/kg)
	GSM850	GPRS10	Front Face	251	31.0	30.50	-3.03	0.159	1.12	0.18
13#	GSM850	GPRS10	Rear Face	251	31.0	30.50	-0.64	0.226	1.12	0.25
	GSM1900	GPRS11	Front Face	512	27.5	26.79	0.54	0.142	1.18	0.17
14#	GSM1900	GPRS11	Rear Face	512	27.5	26.79	0.21	0.23	1.18	0.27
	WCDMA II	RMC12.2K	Front Face	9400	23.0	22.58	0.08	0.116	1.10	0.13
15#	WCDMA II	RMC12.2K	Rear Face	9400	23.0	22.58	-0.85	0.35	1.10	0.39
	WCDMA IV	RMC12.2K	Front Face	1312	23.0	22.46	0.20	0.198	1.13	0.22
16#	WCDMA IV	RMC12.2K	Rear Face	1312	23.0	22.46	0.30	0.218	1.13	0.25
	WCDMA V	RMC12.2K	Front Face	4233	23.0	22.76	-4.7	0.111	1.06	0.12
17#	WCDMA V	RMC12.2K	Rear Face	4233	23.0	22.76	-0.36	0.169	1.06	0.18

FCC SAR Test Report

Plot No.	Band	Mode	Test Position	Ch.	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaling Factor	Scaled SAR-1g (W/kg)
18#	LTE 2	QPSK20M	Front Face	18900	1	0	23.0	22.48	-1.2	0.308	1.13	0.35
	LTE 2	QPSK20M	Rear Face	18900	1	0	23.0	22.48	-2.24	0.347	1.13	0.39
	LTE 2	QPSK20M	Front Face	18900	50	0	22.0	21.38	-2.4	0.277	1.15	0.32
	LTE 2	QPSK20M	Rear Face	18900	50	0	22.0	21.38	-0.24	0.29	1.15	0.33
19#	LTE 4	QPSK20M	Front Face	20050	1	0	23.0	22.46	-4.53	0.177	1.13	0.20
	LTE 4	QPSK20M	Rear Face	20050	1	0	23.0	22.46	-3.15	0.22	1.13	0.25
	LTE 4	QPSK20M	Front Face	20050	50	0	22.0	21.47	-3.31	0.143	1.13	0.16
	LTE 4	QPSK20M	Rear Face	20050	50	0	22.0	21.47	-0.83	0.172	1.13	0.19
20#	LTE 5	QPSK10M	Front Face	20525	1	0	22.5	22.18	1.24	0.102	1.08	0.11
	LTE 5	QPSK10M	Rear Face	20525	1	0	22.5	22.18	-2.5	0.139	1.08	0.15
	LTE 5	QPSK10M	Front Face	20525	25	0	21.5	21.26	-2.3	0.08	1.06	0.08
	LTE 5	QPSK10M	Rear Face	20525	25	0	21.5	21.26	-2.56	0.117	1.06	0.12
21#	LTE 7	QPSK20M	Front Face	21100	1	0	23.5	22.82	0.09	0.252	1.17	0.29
	LTE 7	QPSK20M	Rear Face	21100	1	0	23.5	22.82	0.93	0.713	1.17	0.83
	LTE 7	QPSK20M	Front Face	21100	50	0	22.5	21.87	0.12	0.209	1.16	0.24
	LTE 7	QPSK20M	Rear Face	21100	50	0	22.5	21.87	-2.47	0.574	1.16	0.66
22#	LTE 7	QPSK20M	Rear Face	20850	1	0	23.5	22.74	-2.22	0.715	1.19	0.85
	LTE 7	QPSK20M	Rear Face	21350	1	0	23.5	22.56	-0.86	0.677	1.24	0.84
	LTE 12	QPSK10M	Front Face	23095	1	0	23.0	22.47	-0.31	0.098	1.13	0.11
	LTE 12	QPSK10M	Rear Face	23095	1	0	23.0	22.47	-3.51	0.154	1.13	0.17
23#	LTE 12	QPSK10M	Front Face	23095	25	0	22.0	21.45	-0.1	0.084	1.14	0.10
	LTE 12	QPSK10M	Rear Face	23095	25	0	22.0	21.45	-4.93	0.126	1.14	0.14
	LTE 66	QPSK20M	Front Face	132072	1	0	23.0	22.72	-1.04	0.19	1.07	0.20
	LTE 66	QPSK20M	Rear Face	132072	1	0	23.0	22.72	-3.05	0.241	1.07	0.26
24#	LTE 66	QPSK20M	Front Face	132072	50	0	22.0	21.72	-1.49	0.156	1.07	0.17
	LTE 66	QPSK20M	Rear Face	132072	50	0	22.0	21.72	-2.55	0.22	1.07	0.23

Plot No.	Band	Mode	Test Position	Ch.	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaling Factor	Scaled SAR-1g (W/kg)
24#	802.11b	-	Front Face	1	17.0	16.88	0.13	0.149	1.03	0.15
	802.11b	-	Rear Face	1	17.0	16.88	0.81	0.268	1.03	0.28

FCC SAR Test Report

4.7.4 SAR Results for Hotspot Exposure Condition (Separation Distance is 1.0 cm Gap)

Plot No.	Band	Mode	Test Position	Ch.	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaling Factor	Scaled SAR-1g (W/kg)
13#	GSM850	GPRS10	Front Face	251	31.0	30.50	-3.03	0.159	1.12	0.18
	GSM850	GPRS10	Rear Face	251	31.0	30.50	-0.64	0.226	1.12	0.25
	GSM850	GPRS10	Left Side	251	31.0	30.50	0.7	0.085	1.12	0.10
	GSM850	GPRS10	Right Side	251	31.0	30.50	0.28	0.11	1.12	0.12
	GSM850	GPRS10	Bottom Side	251	31.0	30.50	0.2	0.117	1.12	0.13
14#	GSM1900	GPRS11	Front Face	512	27.5	26.79	0.54	0.142	1.18	0.17
	GSM1900	GPRS11	Rear Face	512	27.5	26.79	0.21	0.23	1.18	0.27
	GSM1900	GPRS11	Left Side	512	27.5	26.79	1.05	0.077	1.18	0.09
	GSM1900	GPRS11	Right Side	512	27.5	26.79	1.06	0.104	1.18	0.12
	GSM1900	GPRS11	Bottom Side	512	27.5	26.79	2.05	0.112	1.18	0.13
15#	WCDMA II	RMC12.2K	Front Face	9400	23.0	22.58	0.08	0.116	1.10	0.13
	WCDMA II	RMC12.2K	Rear Face	9400	23.0	22.58	-0.85	0.35	1.10	0.39
	WCDMA II	RMC12.2K	Left Side	9400	23.0	22.58	0.29	0.3	1.10	0.33
	WCDMA II	RMC12.2K	Right Side	9400	23.0	22.58	0.27	0.102	1.10	0.11
	WCDMA II	RMC12.2K	Bottom Side	9400	23.0	22.58	0.54	0.213	1.10	0.23
16#	WCDMA IV	RMC12.2K	Front Face	1312	23.0	22.46	0.20	0.198	1.13	0.22
	WCDMA IV	RMC12.2K	Rear Face	1312	23.0	22.46	0.30	0.218	1.13	0.25
	WCDMA IV	RMC12.2K	Left Side	1312	23.0	22.46	0.84	0.068	1.13	0.08
	WCDMA IV	RMC12.2K	Right Side	1312	23.0	22.46	1.23	0.097	1.13	0.11
	WCDMA IV	RMC12.2K	Bottom Side	1312	23.0	22.46	0.02	0.107	1.13	0.12
17#	WCDMA V	RMC12.2K	Front Face	4233	23.0	22.76	-4.7	0.111	1.06	0.12
	WCDMA V	RMC12.2K	Rear Face	4233	23.0	22.76	-0.36	0.169	1.06	0.18
	WCDMA V	RMC12.2K	Left Side	4233	23.0	22.76	-2.72	0.052	1.06	0.05
	WCDMA V	RMC12.2K	Right Side	4233	23.0	22.76	-1.21	0.071	1.06	0.08
	WCDMA V	RMC12.2K	Bottom Side	4233	23.0	22.76	-0.03	0.083	1.06	0.09

Plot No.	Band	Mode	Test Position	Ch.	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaling Factor	Scaled SAR-1g (W/kg)
18#	LTE 2	QPSK20M	Front Face	18900	1	0	23.0	22.48	-1.2	0.308	1.13	0.35
	LTE 2	QPSK20M	Rear Face	18900	1	0	23.0	22.48	-2.24	0.347	1.13	0.39
	LTE 2	QPSK20M	Left Side	18900	1	0	23.0	22.48	-2.78	0.239	1.13	0.27
	LTE 2	QPSK20M	Right Side	18900	1	0	23.0	22.48	-0.91	0.091	1.13	0.10
	LTE 2	QPSK20M	Bottom Side	18900	1	0	23.0	22.48	-0.61	0.146	1.13	0.16
	LTE 2	QPSK20M	Front Face	18900	50	0	22.0	21.38	-2.4	0.277	1.15	0.32
	LTE 2	QPSK20M	Rear Face	18900	50	0	22.0	21.38	-0.24	0.29	1.15	0.33
	LTE 2	QPSK20M	Left Side	18900	50	0	22.0	21.38	-3.37	0.189	1.15	0.22
	LTE 2	QPSK20M	Right Side	18900	50	0	22.0	21.38	-3.52	0.072	1.15	0.08
	LTE 2	QPSK20M	Bottom Side	18900	50	0	22.0	21.38	-3.2	0.117	1.15	0.13
19#	LTE 4	QPSK20M	Front Face	20050	1	0	23.0	22.46	-4.53	0.177	1.13	0.20
	LTE 4	QPSK20M	Rear Face	20050	1	0	23.0	22.46	-3.15	0.22	1.13	0.25
	LTE 4	QPSK20M	Left Side	20050	1	0	23.0	22.46	-4.56	0.111	1.13	0.13
	LTE 4	QPSK20M	Right Side	20050	1	0	23.0	22.46	-3.46	0.04	1.13	0.05
	LTE 4	QPSK20M	Bottom Side	20050	1	0	23.0	22.46	0.96	0.095	1.13	0.11
	LTE 4	QPSK20M	Front Face	20050	50	0	22.0	21.47	-3.31	0.143	1.13	0.16
	LTE 4	QPSK20M	Rear Face	20050	50	0	22.0	21.47	-0.83	0.172	1.13	0.19
	LTE 4	QPSK20M	Left Side	20050	50	0	22.0	21.47	-2.53	0.086	1.13	0.10
	LTE 4	QPSK20M	Right Side	20050	50	0	22.0	21.47	1.03	0.029	1.13	0.03
	LTE 4	QPSK20M	Bottom Side	20050	50	0	22.0	21.47	-0.4	0.058	1.13	0.07

FCC SAR Test Report

Plot No.	Band	Mode	Test Position	Ch.	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaling Factor	Scaled SAR-1g (W/kg)
20#	LTE 5	QPSK10M	Front Face	20525	1	0	22.5	22.18	1.24	0.102	1.08	0.11
	LTE 5	QPSK10M	Rear Face	20525	1	0	22.5	22.18	-2.5	0.139	1.08	0.15
	LTE 5	QPSK10M	Left Side	20525	1	0	22.5	22.18	-2.76	0.07	1.08	0.08
	LTE 5	QPSK10M	Right Side	20525	1	0	22.5	22.18	-1.69	0.084	1.08	0.09
	LTE 5	QPSK10M	Bottom Side	20525	1	0	22.5	22.18	-0.89	0.07	1.08	0.08
	LTE 5	QPSK10M	Front Face	20525	25	0	21.5	21.26	-2.3	0.08	1.06	0.08
	LTE 5	QPSK10M	Rear Face	20525	25	0	21.5	21.26	-2.56	0.117	1.06	0.12
	LTE 5	QPSK10M	Left Side	20525	25	0	21.5	21.26	-4.12	0.057	1.06	0.06
	LTE 5	QPSK10M	Right Side	20525	25	0	21.5	21.26	-0.01	0.063	1.06	0.07
	LTE 5	QPSK10M	Bottom Side	20525	25	0	21.5	21.26	1.24	0.061	1.06	0.06
	LTE 7	QPSK20M	Front Face	21100	1	0	23.5	22.82	0.09	0.252	1.17	0.29
	LTE 7	QPSK20M	Rear Face	21100	1	0	23.5	22.82	0.93	0.713	1.17	0.83
	LTE 7	QPSK20M	Left Side	21100	1	0	23.5	22.82	-2.04	0.168	1.17	0.20
	LTE 7	QPSK20M	Right Side	21100	1	0	23.5	22.82	0.36	0.131	1.17	0.15
	LTE 7	QPSK20M	Bottom Side	21100	1	0	23.5	22.82	-0.81	0.639	1.17	0.75
	LTE 7	QPSK20M	Front Face	21100	50	0	22.5	21.87	0.12	0.209	1.16	0.24
	LTE 7	QPSK20M	Rear Face	21100	50	0	22.5	21.87	-2.47	0.574	1.16	0.66
	LTE 7	QPSK20M	Left Side	21100	50	0	22.5	21.87	1.17	0.125	1.16	0.14
	LTE 7	QPSK20M	Right Side	21100	50	0	22.5	21.87	-0.33	0.104	1.16	0.12
	LTE 7	QPSK20M	Bottom Side	21100	50	0	22.5	21.87	0.37	0.515	1.16	0.60
21#	LTE 7	QPSK20M	Rear Face	20850	1	0	23.5	22.74	-2.22	0.715	1.19	0.85
	LTE 7	QPSK20M	Rear Face	21350	1	0	23.5	22.56	-0.86	0.677	1.24	0.84
22#	LTE 12	QPSK10M	Front Face	23095	1	0	23.0	22.47	-0.31	0.098	1.13	0.11
	LTE 12	QPSK10M	Rear Face	23095	1	0	23.0	22.47	-3.51	0.154	1.13	0.17
	LTE 12	QPSK10M	Left Side	23095	1	0	23.0	22.47	-1.32	0.121	1.13	0.14
	LTE 12	QPSK10M	Right Side	23095	1	0	23.0	22.47	0.41	0.089	1.13	0.10
	LTE 12	QPSK10M	Bottom Side	23095	1	0	23.0	22.47	-0.83	0.035	1.13	0.04
	LTE 12	QPSK10M	Front Face	23095	25	0	22.0	21.45	-0.1	0.084	1.14	0.10
	LTE 12	QPSK10M	Rear Face	23095	25	0	22.0	21.45	-4.93	0.126	1.14	0.14
	LTE 12	QPSK10M	Left Side	23095	25	0	22.0	21.45	0.63	0.103	1.14	0.12
	LTE 12	QPSK10M	Right Side	23095	25	0	22.0	21.45	-2.35	0.08	1.14	0.09
	LTE 12	QPSK10M	Bottom Side	23095	25	0	22.0	21.45	-0.46	0.03	1.14	0.03
23#	LTE 66	QPSK20M	Front Face	132072	1	0	23.0	22.72	-1.04	0.19	1.07	0.20
	LTE 66	QPSK20M	Rear Face	132072	1	0	23.0	22.72	-3.05	0.241	1.07	0.26
	LTE 66	QPSK20M	Left Side	132072	1	0	23.0	22.72	-3.07	0.118	1.07	0.13
	LTE 66	QPSK20M	Right Side	132072	1	0	23.0	22.72	-3.06	0.04	1.07	0.04
	LTE 66	QPSK20M	Bottom Side	132072	1	0	23.0	22.72	-1.44	0.081	1.07	0.09
	LTE 66	QPSK20M	Front Face	132072	50	0	22.0	21.72	-1.49	0.156	1.07	0.17
	LTE 66	QPSK20M	Rear Face	132072	50	0	22.0	21.72	-2.55	0.22	1.07	0.23
	LTE 66	QPSK20M	Left Side	132072	50	0	22.0	21.72	-3.59	0.093	1.07	0.10
	LTE 66	QPSK20M	Right Side	132072	50	0	22.0	21.72	-0.63	0.033	1.07	0.04
	LTE 66	QPSK20M	Bottom Side	132072	50	0	22.0	21.72	-3.09	0.064	1.07	0.07

Plot No.	Band	Mode	Test Position	Ch.	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaling Factor	Scaled SAR-1g (W/kg)
24#	802.11b	-	Front Face	1	17.0	16.88	0.13	0.149	1.03	0.15
	802.11b	-	Rear Face	1	17.0	16.88	0.81	0.268	1.03	0.28
	802.11b	-	Left Side	1	17.0	16.88	0.63	0.162	1.03	0.17
	802.11b	-	Right Side	1	17.0	16.88	0.72	0.035	1.03	0.04
	802.11b	-	Top Side	1	17.0	16.88	0.71	0.173	1.03	0.18

4.7.5 SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are ≤ 1.45 W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is ≤ 1.10 , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

Since all the measured SAR are less than 0.8 W/kg, the repeated measurement is not required.

4.7.6 Simultaneous Multi-band Transmission Evaluation

<Estimated SAR Calculation>

According to KDB 447498 D01, when standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR was estimated according to following formula to result in substantially conservative SAR values of ≤ 0.4 W/kg to determine simultaneous transmission SAR test exclusion.

$$\text{Estimated SAR} = \frac{\text{Max. Tune up Power}_{(\text{mW})}}{\text{Min. Test Separation Distance}_{(\text{mm})}} \times \frac{\sqrt{f_{(\text{GHz})}}}{7.5}$$

If the minimum test separation distance is < 5 mm, a distance of 5 mm is used for estimated SAR calculation. When the test separation distance is > 50 mm, the 0.4 W/kg is used for SAR-1g.

Mode / Band	Frequency (GHz)	Max. Tune-up Power (dBm)	Test Position	Separation Distance (mm)	Estimated SAR (W/kg)
BT (DSS)	2.48	8.0	Body-worn	10	0.13

Note:

1. The separation distance is determined from the outer housing of the tablet to the user.
2. When standalone SAR testing is not required, an estimated SAR can be applied to determine simultaneous transmission SAR test exclusion.

FCC SAR Test Report

<SAR Summation Analysis>

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of SAR_{1g} of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR_{1g} 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR_{1g} is greater than the SAR limit (SAR_{1g} 1.6 W/kg), SAR test exclusion is determined by the SPLSR.

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
1	GSM850 + WLAN (DTS)	Head	Right Cheek	0.16	0.75	0.91	Σ SAR < 1.6, Not required
			Right Tilted	0.14	0.71	0.85	Σ SAR < 1.6, Not required
			Left Cheek	0.17	0.54	0.71	Σ SAR < 1.6, Not required
			Left Tilted	0.16	0.52	0.68	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.18	0.15	0.33	Σ SAR < 1.6, Not required
			Rear Face	0.25	0.28	0.53	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.18	0.15	0.33	Σ SAR < 1.6, Not required
			Rear Face	0.25	0.28	0.53	Σ SAR < 1.6, Not required
			Left Side	0.10	0.17	0.27	Σ SAR < 1.6, Not required
			Right Side	0.12	0.04	0.16	Σ SAR < 1.6, Not required
			Top Side	0.00	0.18	0.18	Σ SAR < 1.6, Not required
			Bottom Side	0.13	0.00	0.13	Σ SAR < 1.6, Not required
2	GSM850 + BT (DSS)	Body-Worn	Front Face	0.18	0.13	0.31	Σ SAR < 1.6, Not required
			Rear Face	0.25	0.13	0.38	Σ SAR < 1.6, Not required

FCC SAR Test Report

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
3	GSM1900 + WLAN (DTS)	Head	Right Cheek	0.11	0.75	0.86	Σ SAR < 1.6, Not required
			Right Tilted	0.08	0.71	0.79	Σ SAR < 1.6, Not required
			Left Cheek	0.16	0.54	0.70	Σ SAR < 1.6, Not required
			Left Tilted	0.14	0.52	0.66	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.17	0.15	0.32	Σ SAR < 1.6, Not required
			Rear Face	0.27	0.28	0.55	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.17	0.15	0.32	Σ SAR < 1.6, Not required
			Rear Face	0.27	0.28	0.55	Σ SAR < 1.6, Not required
			Left Side	0.09	0.17	0.26	Σ SAR < 1.6, Not required
			Right Side	0.12	0.04	0.16	Σ SAR < 1.6, Not required
			Top Side	0.00	0.18	0.18	Σ SAR < 1.6, Not required
			Bottom Side	0.13	0.00	0.13	Σ SAR < 1.6, Not required
4	GSM1900 + BT (DSS)	Body-Worn	Front Face	0.17	0.13	0.30	Σ SAR < 1.6, Not required
			Rear Face	0.27	0.13	0.40	Σ SAR < 1.6, Not required

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
5	WCDMA II + WLAN (DTS)	Head	Right Cheek	0.16	0.75	0.91	Σ SAR < 1.6, Not required
			Right Tilted	0.11	0.71	0.82	Σ SAR < 1.6, Not required
			Left Cheek	0.28	0.54	0.82	Σ SAR < 1.6, Not required
			Left Tilted	0.20	0.52	0.72	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.13	0.15	0.28	Σ SAR < 1.6, Not required
			Rear Face	0.39	0.28	0.67	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.13	0.15	0.28	Σ SAR < 1.6, Not required
			Rear Face	0.39	0.28	0.67	Σ SAR < 1.6, Not required
			Left Side	0.33	0.17	0.50	Σ SAR < 1.6, Not required
			Right Side	0.11	0.04	0.15	Σ SAR < 1.6, Not required
			Top Side	0.00	0.18	0.18	Σ SAR < 1.6, Not required
			Bottom Side	0.23	0.00	0.23	Σ SAR < 1.6, Not required
6	WCDMA II + BT (DSS)	Body-Worn	Front Face	0.13	0.13	0.26	Σ SAR < 1.6, Not required
			Rear Face	0.39	0.13	0.52	Σ SAR < 1.6, Not required

FCC SAR Test Report

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
7	WCDMA IV + WLAN (DTS)	Head	Right Cheek	0.39	0.75	1.14	Σ SAR < 1.6, Not required
			Right Tilted	0.10	0.71	0.81	Σ SAR < 1.6, Not required
			Left Cheek	0.22	0.54	0.76	Σ SAR < 1.6, Not required
			Left Tilted	0.14	0.52	0.66	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.22	0.15	0.37	Σ SAR < 1.6, Not required
			Rear Face	0.25	0.28	0.53	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.22	0.15	0.37	Σ SAR < 1.6, Not required
			Rear Face	0.25	0.28	0.53	Σ SAR < 1.6, Not required
			Left Side	0.08	0.17	0.25	Σ SAR < 1.6, Not required
			Right Side	0.11	0.04	0.15	Σ SAR < 1.6, Not required
			Top Side	0.00	0.18	0.18	Σ SAR < 1.6, Not required
			Bottom Side	0.12	0.00	0.12	Σ SAR < 1.6, Not required
8	WCDMA IV + BT (DSS)	Body-Worn	Front Face	0.22	0.13	0.35	Σ SAR < 1.6, Not required
			Rear Face	0.25	0.13	0.38	Σ SAR < 1.6, Not required

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
9	WCDMA V + WLAN (DTS)	Head	Right Cheek	0.12	0.75	0.87	Σ SAR < 1.6, Not required
			Right Tilted	0.10	0.71	0.81	Σ SAR < 1.6, Not required
			Left Cheek	0.11	0.54	0.65	Σ SAR < 1.6, Not required
			Left Tilted	0.08	0.52	0.60	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.12	0.15	0.27	Σ SAR < 1.6, Not required
			Rear Face	0.18	0.28	0.46	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.12	0.15	0.27	Σ SAR < 1.6, Not required
			Rear Face	0.18	0.28	0.46	Σ SAR < 1.6, Not required
			Left Side	0.05	0.17	0.22	Σ SAR < 1.6, Not required
			Right Side	0.08	0.04	0.12	Σ SAR < 1.6, Not required
			Top Side	0.00	0.18	0.18	Σ SAR < 1.6, Not required
			Bottom Side	0.09	0.00	0.09	Σ SAR < 1.6, Not required
10	WCDMA V + BT (DSS)	Body-Worn	Front Face	0.12	0.13	0.25	Σ SAR < 1.6, Not required
			Rear Face	0.18	0.13	0.31	Σ SAR < 1.6, Not required

FCC SAR Test Report

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
11	LTE 2 + WLAN (DTS)	Head	Right Cheek	0.19	0.75	0.94	Σ SAR < 1.6, Not required
			Right Tilted	0.11	0.71	0.82	Σ SAR < 1.6, Not required
			Left Cheek	0.28	0.54	0.82	Σ SAR < 1.6, Not required
			Left Tilted	0.17	0.52	0.69	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.35	0.15	0.50	Σ SAR < 1.6, Not required
			Rear Face	0.39	0.28	0.67	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.35	0.15	0.50	Σ SAR < 1.6, Not required
			Rear Face	0.39	0.28	0.67	Σ SAR < 1.6, Not required
			Left Side	0.27	0.17	0.44	Σ SAR < 1.6, Not required
			Right Side	0.10	0.04	0.14	Σ SAR < 1.6, Not required
			Top Side	0.00	0.18	0.18	Σ SAR < 1.6, Not required
			Bottom Side	0.16	0.00	0.16	Σ SAR < 1.6, Not required
12	LTE 2 + BT (DSS)	Body-Worn	Front Face	0.35	0.13	0.48	Σ SAR < 1.6, Not required
			Rear Face	0.39	0.13	0.52	Σ SAR < 1.6, Not required

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
13	LTE 4 + WLAN (DTS)	Head	Right Cheek	0.25	0.75	1.00	Σ SAR < 1.6, Not required
			Right Tilted	0.11	0.71	0.82	Σ SAR < 1.6, Not required
			Left Cheek	0.31	0.54	0.85	Σ SAR < 1.6, Not required
			Left Tilted	0.13	0.52	0.65	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.20	0.15	0.35	Σ SAR < 1.6, Not required
			Rear Face	0.25	0.28	0.53	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.20	0.15	0.35	Σ SAR < 1.6, Not required
			Rear Face	0.25	0.28	0.53	Σ SAR < 1.6, Not required
			Left Side	0.13	0.17	0.30	Σ SAR < 1.6, Not required
			Right Side	0.05	0.04	0.09	Σ SAR < 1.6, Not required
			Top Side	0.00	0.18	0.18	Σ SAR < 1.6, Not required
			Bottom Side	0.11	0.00	0.11	Σ SAR < 1.6, Not required
14	LTE 4 + BT (DSS)	Body-Worn	Front Face	0.20	0.13	0.33	Σ SAR < 1.6, Not required
			Rear Face	0.25	0.13	0.38	Σ SAR < 1.6, Not required

FCC SAR Test Report

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
15	LTE 5 + WLAN (DTS)	Head	Right Cheek	0.14	0.75	0.89	Σ SAR < 1.6, Not required
			Right Tilted	0.14	0.71	0.85	Σ SAR < 1.6, Not required
			Left Cheek	0.27	0.54	0.81	Σ SAR < 1.6, Not required
			Left Tilted	0.14	0.52	0.66	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.11	0.15	0.26	Σ SAR < 1.6, Not required
			Rear Face	0.15	0.28	0.43	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.11	0.15	0.26	Σ SAR < 1.6, Not required
			Rear Face	0.15	0.28	0.43	Σ SAR < 1.6, Not required
			Left Side	0.08	0.17	0.25	Σ SAR < 1.6, Not required
			Right Side	0.09	0.04	0.13	Σ SAR < 1.6, Not required
			Top Side	0.00	0.18	0.18	Σ SAR < 1.6, Not required
			Bottom Side	0.08	0.00	0.08	Σ SAR < 1.6, Not required
16	LTE 5 + BT (DSS)	Body-Worn	Front Face	0.11	0.13	0.24	Σ SAR < 1.6, Not required
			Rear Face	0.15	0.13	0.28	Σ SAR < 1.6, Not required

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
17	LTE 7 + WLAN (DTS)	Head	Right Cheek	0.10	0.75	0.85	Σ SAR < 1.6, Not required
			Right Tilted	0.08	0.71	0.79	Σ SAR < 1.6, Not required
			Left Cheek	0.16	0.54	0.70	Σ SAR < 1.6, Not required
			Left Tilted	0.12	0.52	0.64	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.29	0.15	0.44	Σ SAR < 1.6, Not required
			Rear Face	0.85	0.28	1.13	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.29	0.15	0.44	Σ SAR < 1.6, Not required
			Rear Face	0.85	0.28	1.13	Σ SAR < 1.6, Not required
			Left Side	0.20	0.17	0.37	Σ SAR < 1.6, Not required
			Right Side	0.15	0.04	0.19	Σ SAR < 1.6, Not required
			Top Side	0.00	0.18	0.18	Σ SAR < 1.6, Not required
			Bottom Side	0.75	0.00	0.75	Σ SAR < 1.6, Not required
18	LTE 7 + BT (DSS)	Body-Worn	Front Face	0.29	0.13	0.42	Σ SAR < 1.6, Not required
			Rear Face	0.85	0.13	0.98	Σ SAR < 1.6, Not required

FCC SAR Test Report

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
19	LTE 12 + WLAN (DTS)	Head	Right Cheek	0.11	0.75	0.86	Σ SAR < 1.6, Not required
			Right Tilted	0.15	0.71	0.86	Σ SAR < 1.6, Not required
			Left Cheek	0.18	0.54	0.72	Σ SAR < 1.6, Not required
			Left Tilted	0.14	0.52	0.66	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.11	0.15	0.26	Σ SAR < 1.6, Not required
			Rear Face	0.17	0.28	0.45	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.11	0.15	0.26	Σ SAR < 1.6, Not required
			Rear Face	0.17	0.28	0.45	Σ SAR < 1.6, Not required
			Left Side	0.14	0.17	0.31	Σ SAR < 1.6, Not required
			Right Side	0.10	0.04	0.14	Σ SAR < 1.6, Not required
			Top Side	0.00	0.18	0.18	Σ SAR < 1.6, Not required
			Bottom Side	0.04	0.00	0.04	Σ SAR < 1.6, Not required
20	LTE 12 + BT (DSS)	Body-Worn	Front Face	0.11	0.13	0.24	Σ SAR < 1.6, Not required
			Rear Face	0.17	0.13	0.30	Σ SAR < 1.6, Not required

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
21	LTE 66 + WLAN (DTS)	Head	Right Cheek	0.26	0.75	1.01	Σ SAR < 1.6, Not required
			Right Tilted	0.11	0.71	0.82	Σ SAR < 1.6, Not required
			Left Cheek	0.32	0.54	0.86	Σ SAR < 1.6, Not required
			Left Tilted	0.13	0.52	0.65	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.20	0.15	0.35	Σ SAR < 1.6, Not required
			Rear Face	0.26	0.28	0.54	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.20	0.15	0.35	Σ SAR < 1.6, Not required
			Rear Face	0.26	0.28	0.54	Σ SAR < 1.6, Not required
			Left Side	0.13	0.17	0.30	Σ SAR < 1.6, Not required
			Right Side	0.04	0.04	0.08	Σ SAR < 1.6, Not required
			Top Side	0.00	0.18	0.18	Σ SAR < 1.6, Not required
			Bottom Side	0.09	0.00	0.09	Σ SAR < 1.6, Not required
22	LTE 66 + BT (DSS)	Body-Worn	Front Face	0.20	0.13	0.33	Σ SAR < 1.6, Not required
			Rear Face	0.26	0.13	0.39	Σ SAR < 1.6, Not required

Test Engineer : Wiky Zhang

FCC SAR Test Report

5. Calibration of Test Equipment

Equipment	Manufacturer	Model	SN	Cal. Date	Cal. Interval
System Validation Dipole	SATIMO	SID750	SN 26/14 DIP0G750-325	Jun. 08, 2017	2 Years
System Validation Dipole	SATIMO	SID835	SN 18/11 DIPC 150	Jun. 08, 2017	2 Years
System Validation Dipole	SATIMO	SID1800	SN 18/11 DIPF 152	Jun. 08, 2017	2 Years
System Validation Dipole	SATIMO	SID1900	SN 18/11 DIPG 153	Jun. 08, 2017	2 Years
System Validation Dipole	SATIMO	SID2450	SN 18/11 DIPJ155	Jun. 08, 2017	2 Years
System Validation Dipole	SATIMO	SID2600	SN 26/14 DIP2G600-326	Jun. 08, 2017	2 Years
E-Field Probe	MVG	SSE2	SN 27/15 EPO262	Jun. 07, 2018	1 Year
MultiMeter	Keithley	Multimate 2000	1331865	Feb. 26, 2019	1 Year
Radio Communication Analyzer	ANRITSU	MT8820C	6201300717	Jul. 09, 2018	1 Year
Wireless Communication Test Set	Agilent	E5515C	MY48360324	Feb. 26, 2019	1 Year
ENA Series Network Analyzer	Agilent	E5071C	MY46214638	Jul. 09, 2018	1 Year
Spectrum Analyzer	KEYSIGHT	N9010A	MY54510322	Feb. 26, 2019	1 Year
MXG Analog Signal Generator	KEYSIGHT	N5183A	MY50143024	Mar. 14, 2019	1 Year
Power Meter	Agilent	N1914A	MY52180044	Oct. 10, 2018	2 Years
Power Sensor	Agilent	E9304A H18	MY52050011	Jan. 21, 2019	1 Year
Temp. & Humi. Recorder	HUATO	A2000-TH	HE20107712	Jul. 11, 2018	1 Year
Electronic Thermometer	YONGFA	YF-160A	120100323	Sep. 22, 2018	1 Year
Coupler	Woken	0110A056020-10	COM27RW1A3	Sep. 20, 2018	1 Year

FCC SAR Test Report

6. Measurement Uncertainty

Source of Uncertainty	Tolerance (± %)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty (1g)	Standard Uncertainty (10g)	Vi Veff
Measurement System								
Probe Calibration	6.0	N	1	1	1	6.0	6.0	∞
Axial Isotropy	5.9	R	1.732	0.7	0.7	2.4	2.4	∞
Hemispherical Isotropy	12.2	R	1.732	0.7	0.7	4.9	4.9	∞
Boundary Effects	1.0	R	1.732	1	1	0.6	0.6	∞
Linearity	5.9	R	1.732	1	1	3.4	3.4	∞
System Detection Limits	1.0	R	1.732	1	1	0.6	0.6	∞
Readout Electronics	1.0	N	1	1	1	1.0	1.0	∞
Response Time	0.0	R	1.732	1	1	0.0	0.0	∞
Integration Time	2.6	R	1.732	1	1	1.5	1.5	∞
RF Ambient Noise	3.0	R	1.732	1	1	1.7	1.7	∞
RF Ambient Reflections	3.0	R	1.732	1	1	1.7	1.7	∞
Probe Positioner	1.4	R	1.732	1	1	0.8	0.8	∞
Probe Positioning	1.4	R	1.732	1	1	0.8	0.8	∞
Max. SAR Eval.	2.3	R	1.732	1	1	1.3	1.3	∞
Test Sample Related								
Device Positioning	2.3	N	1	1	1	2.3	2.3	35
Device Holder	2.7	N	1	1	1	2.7	2.7	12
Power Drift	5.0	R	1.732	1	1	2.9	2.9	∞
Power Scaling	0.0	R	1.732	1	1	0.0	0.0	∞
Phantom and Setup								
Phantom Uncertainty	4.0	R	1.732	1	1	2.3	2.3	∞
SAR correction	1.2	R	1.732	1	0.84	0.7	0.6	∞
Liquid Conductivity (target)	5.0	R	1.732	0.78	0.71	2.3	2.0	∞
Liquid Conductivity (mea.)	4.1	R	1.732	0.78	0.71	1.8	1.7	∞
Temp. unc. - Conductivity	3.4	R	1.732	0.78	0.71	1.5	1.4	∞
Liquid Permittivity (target)	5.0	R	1.732	0.23	0.26	0.7	0.8	∞
Liquid Permittivity (mea.)	5.0	R	1.732	0.23	0.26	0.7	0.8	∞
Temp. unc. - Permittivity	0.83	R	1.732	0.23	0.26	0.1	0.1	∞
Combined Standard Uncertainty (K = 1)						± 11.4 %	± 11.3 %	2923
Expanded Uncertainty (K = 2)						± 22.7 %	± 22.6 %	

7. Information on the Testing Laboratories

We, BV 7LAYERS COMMUNICATIONS TECHNOLOGY (SHENZHEN) CO. LTD., were founded in 2015 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Add: No. B102, Dazu Chuangxin Mansion, North of Beihuan Avenue, North Area, Hi-Tech Industry Park, Nanshan District, Shenzhen, Guangdong, China

Tel: 86-755-8869-6566

Fax: 86-755-8869-6577

Email: customerservice.dg@cn.bureauveritas.com

Web Site: www.bureauveritas.com

The road map of all our labs can be found in our web site also.

---END---

Appendix A. SAR Plots of System Verification

The plots for system verification with largest deviation for each SAR system combination are shown as follows.



System Verification Plots


Product Description: Dipole

Model: SID750

Test Date: Mar 26, 2019

Ambient Temperature: 23.2°C; Liquid Temperature: 22.1°C

Medium(liquid type)	HL750
Frequency (MHz)	750.0
Relative permittivity (real part)	41.87
Conductivity (S/m)	0.88
Input power	100mW
E-Field Probe	SN 27/15 EPGO262
Crest factor	1.0
Conversion Factor	1.71
Sensor-surface	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	-1.350000
SAR 10g (W/Kg)	0.537062
SAR 1g (W/Kg)	0.827214
 	






Product Description: Dipole

Model: SID750

Test Date: Mar 26, 2019

Ambient Temperature: 23.1°C; Liquid Temperature: 21.9°C

Medium(liquid type)	BL750
Frequency (MHz)	750.0
Relative permittivity (real part)	56.62
Conductivity (S/m)	0.97
Input power	100mW
E-Field Probe	SN 27/15 EPGO262
Crest factor	1.0
Conversion Factor	1.76
Sensor-surface	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	1.670000
SAR 10g (W/Kg)	0.608317
SAR 1g (W/Kg)	0.901241






Product Description: Dipole

Model: SID835

Test Date: Mar 27, 2019

Ambient Temperature: 22.9°C; Liquid Temperature: 21.8°C

Medium(liquid type)	HL835
Frequency (MHz)	835.0
Relative permittivity (real part)	41.37
Conductivity (S/m)	0.92
Input power	100mW
E-Field Probe	SN 27/15 EPG0262
Crest factor	1.0
Conversion Factor	1.79
Sensor-surface	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	-1.060000
SAR 10g (W/Kg)	0.596023
SAR 1g (W/Kg)	0.985123






Product Description: Dipole

Model: SID835

Test Date: Mar 27, 2019

Ambient Temperature: 22.7°C; Liquid Temperature: 21.8°C

Medium(liquid type)	BL835
Frequency (MHz)	835.0
Relative permittivity (real part)	55.08
Conductivity (S/m)	0.95
Input power	100mW
E-Field Probe	SN 27/15 EPGO262
Crest factor	1.0
Conversion Factor	1.86
Sensor-surface	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	0.350000
SAR 10g (W/Kg)	0.621384
SAR 1g (W/Kg)	0.993507






Product Description: Dipole

Model: SID1800

Test Date: Mar 28, 2019

Ambient Temperature: 23.1°C; Liquid Temperature: 22.2°C

Medium(liquid type)	HL1800
Frequency (MHz)	1800.0
Relative permittivity (real part)	40.07
Conductivity (S/m)	1.38
Input power	100mW
E-Field Probe	SN 27/15 EPG0262
Crest factor	1.0
Conversion Factor	1.88
Sensor-Surface	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	1.290000
SAR 10g (W/Kg)	1.860452
SAR 1g (W/Kg)	3.861275






Product Description: Dipole

Model: SID1800

Test Date: Mar 28, 2019

Ambient Temperature: 22.9°C; Liquid Temperature: 21.9°C

Medium(liquid type)	BL1800
Frequency (MHz)	1800.0
Relative permittivity (real part)	52.40
Conductivity (S/m)	1.49
Input power	100mW
E-Field Probe	SN 27/15 EPGO262
Crest factor	1.0
Conversion Factor	1.95
Sensor-Surface	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	1.270000
SAR 10g (W/Kg)	2.085394
SAR 1g (W/Kg)	4.165078






Product Description: Dipole

Model: SID1900

Test Date: Mar 29, 2019

Ambient Temperature: 22.8°C; Liquid Temperature: 21.9°C

Medium(liquid type)	HL1900
Frequency (MHz)	1900.0
Relative permittivity (real part)	39.93
Conductivity (S/m)	1.39
Input power	100mW
E-Field Probe	SN 27/15 EPG0262
Crest factor	1.0
Conversion Factor	2.14
Sensor-Surface	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	-1.580000
SAR 10g (W/Kg)	1.880632
SAR 1g (W/Kg)	3.860527






Product Description: Dipole

Model: SID1900

Test Date: Mar 29, 2019

Ambient Temperature: 22.9°C; Liquid Temperature: 21.7°C

Medium(liquid type)	BL1900
Frequency (MHz)	1900.0
Relative permittivity (real part)	52.85
Conductivity (S/m)	1.50
Input power	100mW
E-Field Probe	SN 27/15 EPGO262
Crest factor	1.0
Conversion Factor	2.20
Sensor-Surface	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	0.310000
SAR 10g (W/Kg)	2.072416
SAR 1g (W/Kg)	4.250462





Product Description: Dipole

Model: SID2450

Test Date: Mar 30, 2019

Ambient Temperature: 23.1°C; Liquid Temperature: 22.1°C

Medium(liquid type)	HL_2450
Frequency (MHz)	2450.0
Relative permittivity (real part)	39.16
Conductivity (S/m)	1.79
Input power	100mW
Crest factor	1.0
E-Field Probe	SN 27/15 EPGO262
Conversion Factor	2.25
Area Scan	dx=8mm dy=8mm
Zoom Scan	7x7x7,dx=5mm dy=5mm dz=5mm
Variation (%)	1.040000
SAR 10g (W/Kg)	2.481332
SAR 1g (W/Kg)	5.460213





Product Description: Dipole

Model: SID2450

Test Date: Mar 30, 2019

Ambient Temperature: 22.8°C; Liquid Temperature: 21.6°C

Medium(liquid type)	BL_2450
Frequency (MHz)	2450.0
Relative permittivity (real part)	52.41
Conductivity (S/m)	1.91
Input power	100mW
Crest factor	1.0
E-Field Probe	SN 27/15 EPGO262
Conversion Factor	2.31
Area Scan	dx=8mm dy=8mm
Zoom Scan	7x7x7,dx=5mm dy=5mm dz=5mm
Variation (%)	-0.760000
SAR 10g (W/Kg)	2.291685
SAR 1g (W/Kg)	5.251074






Product Description: Dipole

Model: SID2600

Test Date: Mar 31, 2019

Ambient Temperature: 22.7°C; Liquid Temperature: 21.6°C

Medium(liquid type)	HSL_2600
Frequency (MHz)	2600.0
Relative permittivity (real part)	38.91
Conductivity (S/m)	1.93
Input power	100mW
E-Field Probe	SN 27/15 EPG0262
Crest factor	1.0
Conversion Factor	2.16
Sensor-Surface	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	7x7x7,dx=5mm dy=5mm dz=5mm
Variation (%)	0.620000
SAR 10g (W/Kg)	2.283122
SAR 1g (W/Kg)	5.286041






Product Description: Dipole

Model: SID2600

Test Date: Mar 31, 2019

Ambient Temperature: 22.6°C; Liquid Temperature: 21.5°C

Medium(liquid type)	MSL_2600
Frequency (MHz)	2600.0
Relative permittivity (real part)	51.93
Conductivity (S/m)	2.11
Input power	100mW
E-Field Probe	SN 27/15 EPGO262
Crest factor	1.0
Conversion Factor	2.21
Sensor-Surface	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	7x7x7,dx=5mm dy=5mm dz=5mm
Variation (%)	-1.240000
SAR 10g (W/Kg)	2.463251
SAR 1g (W/Kg)	5.572413



Appendix B. SAR Plots of SAR Measurement

The SAR plots for highest measured SAR in each exposure configuration, wireless mode and frequency band combination, and measured SAR > 1.5 W/kg are shown as follows.

Maximum SAR measurement Plots




1# GSM850_GPRS 10_Left Cheek_Ch251

DUT: 190325W006

Test Date: Mar 27, 2019

Ambient Temperature: 22.9°C; Liquid Temperature: 21.8°C

Medium(liquid type)	HL835
Frequency (MHz)	848.8
Relative permittivity (real part)	41.37
Conductivity (S/m)	0.92
E-Field Probe	SN 27/15 EPGO262
Crest factor	4.0
Conversion Factor	1.79
Sensor-Surface	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	0.020000
SAR 10g (W/Kg)	0.121306
SAR 1g (W/Kg)	0.151903
SURFACE SAR	VOLUME SAR






2# GSM1900_GPRS11_Left Cheek_Ch512

DUT: 190325W006

Test Date: Mar 29, 2019

Ambient Temperature: 22.8°C; Liquid Temperature: 21.9°C

Medium(liquid type)	HL1900
Frequency (MHz)	1850.2
Relative permittivity (real part)	39.93
Conductivity (S/m)	1.39
E-Field Probe	SN 27/15 EPGO262
Crest factor	2.66
Conversion Factor	2.14
Sensor-Surface	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	-1.670000
SAR 10g (W/Kg)	0.082992
SAR 1g (W/Kg)	0.133588
SURFACE SAR	VOLUME SAR






3# WCDMA Band II _ RMC12.2K _ Left Cheek _ Ch9400

DUT: 190325W006

Test Date: Mar 29, 2019

Ambient Temperature: 22.8°C; Liquid Temperature: 21.9°C

Medium(liquid type)	HL1900
Frequency (MHz)	1880.0
Relative permittivity (real part)	39.93
Conductivity (S/m)	1.39
E-Field Probe	SN 27/15 EPGO262
Crest factor	1.0
Conversion Factor	2.01
Sensor-Surface	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	-3.140000
SAR 10g (W/Kg)	0.155798
SAR 1g (W/Kg)	0.249641
SURFACE SAR	VOLUME SAR






4# WCDMA Band IV_RMC12.2K_Right Cheek_Ch1312

DUT: 190325W006

Test Date: Mar 28, 2019

Ambient Temperature: 23.1°C; Liquid Temperature: 22.2°C

Medium(liquid type)	HL1800
Frequency (MHz)	1712.4
Relative permittivity (real part)	40.07
Conductivity (S/m)	1.38
E-Field Probe	SN 27/15 EPGO262
Crest factor	1.0
Conversion Factor	1.88
Sensor-Surface	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	-2.630000
SAR 10g (W/Kg)	0.228077
SAR 1g (W/Kg)	0.345900
SURFACE SAR	VOLUME SAR






5# WCDMA Band V _ RMC12.2K _ Right Cheek _ Ch4233

DUT: 190325W006

Test Date: Mar 27, 2019

Ambient Temperature: 22.9°C; Liquid Temperature: 21.8°C

Medium(liquid type)	HL835
Frequency (MHz)	846.6
Relative permittivity (real part)	41.37
Conductivity (S/m)	0.92
E-Field Probe	SN 27/15 EPG0262
Crest factor	1.0
Conversion Factor	1.79
Sensor-Surface	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	0.170000
SAR 10g (W/Kg)	0.086901
SAR 1g (W/Kg)	0.114732
SURFACE SAR	VOLUME SAR



6# LTE BAND 2_QPSK20M_Left Cheek_Ch18900_1RB_OS0

DUT: 190325W006




Test Date: Mar 29, 2019

Ambient Temperature: 22.8°C; Liquid Temperature: 21.9°C

Medium(liquid type)	HSL_1900
Frequency (MHz)	1880.0
Relative permittivity (real part)	39.93
Conductivity (S/m)	1.39
E-Field Probe	SN 27/15 EPGO262
Crest factor	1.0
Conversion Factor	2.14
Sensor-Surface	4mm
Bandwidth(MHz)	20
RB Allocation	1
RB Offset	0
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	-0.540000
SAR 10g (W/Kg)	0.162271
SAR 1g (W/Kg)	0.244464

SURFACE SAR

VOLUME SAR



7# LTE BAND 4_QPSK20M_Left Cheek_Ch20050_1RB_OS0


DUT: 190325W006

Test Date: Mar 28, 2019



Ambient Temperature: 23.1°C; Liquid Temperature: 22.2°C

Medium(liquid type)	HSL_1800
Frequency (MHz)	1720.0
Relative permittivity (real part)	40.07
Conductivity (S/m)	1.38
E-Field Probe	SN 27/15 EPG0262
Crest factor	1.0
Conversion Factor	1.88
Sensor-Surface	4mm
Bandwidth(MHz)	20
RB Allocation	1
RB Offset	0
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	-0.580000
SAR 10g (W/Kg)	0.173485
SAR 1g (W/Kg)	0.271310

SURFACE SAR



VOLUME SAR



8# LTE BAND 5_QPSK10M_ Left Cheek_Ch20525_1RB_OS0


DUT: 190325W006

Test Date: Mar 27, 2019



Ambient Temperature: 22.9°C; Liquid Temperature: 21.8°C

Medium(liquid type)	HSL_835
Frequency (MHz)	836.5
Relative permittivity (real part)	41.37
Conductivity (S/m)	0.92
E-Field Probe	SN 27/15 EPGO262
Crest factor	1.0
Conversion Factor	1.79
Sensor-Surface	4mm
Bandwidth(MHz)	10
RB Allocation	1
RB Offset	0
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	-1.310000
SAR 10g (W/Kg)	0.164030
SAR 1g (W/Kg)	0.248836

SURFACE SAR



VOLUME SAR



9# LTE BAND 7_QPSK20M_Left Cheek_Ch21100_1RB_OS0

DUT: 190325W006




Test Date: Mar 31, 2019

Ambient Temperature: 22.7°C; Liquid Temperature: 21.6°C

Medium(liquid type)	HSL_2600
Frequency (MHz)	2535.0
Relative permittivity (real part)	38.91
Conductivity (S/m)	1.93
E-Field Probe	SN 27/15 EPGO262
Crest factor	1.0
Conversion Factor	2.16
Sensor-Surface	4mm
Bandwidth(MHz)	20
RB Allocation	1
RB Offset	0
Area Scan	dx=8mm dy=8mm
Zoom Scan	7x7x7,dx=5mm dy=5mm dz=5mm
Variation (%)	0.380000
SAR 10g (W/Kg)	0.075643
SAR 1g (W/Kg)	0.132754

SURFACE SAR

VOLUME SAR



10# LTE BAND 12_QPSK10M_Left Cheek_Ch23095_1RB_OS0

DUT: 190325W006




Test Date: Mar 26, 2019

Ambient Temperature: 23.2°C; Liquid Temperature: 22.1°C

Medium(liquid type)	HSL_750
Frequency (MHz)	707.5
Relative permittivity (real part)	41.87
Conductivity (S/m)	0.88
E-Field Probe	SN 27/15 EPGO262
Crest factor	1.0
Conversion Factor	1.71
Sensor-Surface	4mm
Bandwidth(MHz)	10
RB Allocation	1
RB Offset	0
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	-3.100000
SAR 10g (W/Kg)	0.114770
SAR 1g (W/Kg)	0.160618

SURFACE SAR

VOLUME SAR



11# LTE BAND 66_QPSK20M_Left Cheek_Ch132072_1RB_OS0


DUT: 190325W006

Test Date: Mar 28, 2019



Ambient Temperature: 23.1°C; Liquid Temperature: 22.2°C

Medium(liquid type)	HSL_1800
Frequency (MHz)	1720.0
Relative permittivity (real part)	40.07
Conductivity (S/m)	1.38
E-Field Probe	SN 27/15 EPG0262
Crest factor	1.0
Conversion Factor	1.88
Sensor-Surface	4mm
Bandwidth(MHz)	20
RB Allocation	1
RB Offset	0
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	0.590000
SAR 10g (W/Kg)	0.189320
SAR 1g (W/Kg)	0.298658

SURFACE SAR



VOLUME SAR






12# 802.11b_Right Cheek Ch 1

DUT: 190325W006

Test Date: Mar 30, 2019

Ambient Temperature: 23.1°C; Liquid Temperature: 22.1°C

Medium(liquid type)	HL_2450
Frequency (MHz)	2412.0
Relative permittivity (real part)	39.16
Conductivity (S/m)	1.79
Crest factor	1.0
E-Field Probe	SN 27/15 EPGO262
Conversion Factor	2.25
Area Scan	dx=8mm dy=8mm
Zoom Scan	7x7x7,dx=5mm dy=5mm dz=5mm
Variation (%)	-2.860000
SAR 10g (W/Kg)	0.353180
SAR 1g (W/Kg)	0.732853






13# GSM850_GPRS10_Rear Face_1.0cm_Ch251

DUT: 190325W006

Test Date: Mar 27, 2019

Ambient Temperature: 22.7°C; Liquid Temperature: 21.8°C

Medium(liquid type)	BL835
Frequency (MHz)	848.8
Relative permittivity (real part)	55.08
Conductivity (S/m)	0.95
E-Field Probe	SN 27/15 EPGO262
Crest factor	2.0
Conversion Factor	1.86
Sensor-Surface	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	-0.640000
SAR 10g (W/Kg)	0.149309
SAR 1g (W/Kg)	0.226364
SURFACE SAR	VOLUME SAR






14# GSM1900_GPRS11_Rear Face_1.0cm_Ch512

DUT: 190325W006

Test Date: Mar 29, 2019

Ambient Temperature: 22.9°C; Liquid Temperature: 21.7°C

Medium(liquid type)	BL1900
Frequency (MHz)	1850.2
Relative permittivity (real part)	52.85
Conductivity (S/m)	1.50
E-Field Probe	SN 27/15 EPG0262
Crest factor	2.0
Conversion Factor	2.20
Sensor-Surface	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	0.210000
SAR 10g (W/Kg)	0.151415
SAR 1g (W/Kg)	0.230354
SURFACE SAR	VOLUME SAR






15# WCDMA Band II _RMC12.2K_Rear Face_1.0cm_Ch9400

DUT: 190325W006

Test Date: Mar 29, 2019

Ambient Temperature: 22.9°C; Liquid Temperature: 21.7°C

Medium(liquid type)	BL1900
Frequency (MHz)	1880.0
Relative permittivity (real part)	52.85
Conductivity (S/m)	1.50
E-Field Probe	SN 27/15 EPG0262
Crest factor	1.0
Conversion Factor	2.20
Sensor-Surface	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	-0.850000
SAR 10g (W/Kg)	0.205901
SAR 1g (W/Kg)	0.349512
SURFACE SAR	VOLUME SAR






16# WCDMA Band IV_RMC12.2K_Rear Face_1.0cm_Ch1312

DUT: 190325W006

Test Date: Mar 28, 2019

Ambient Temperature: 22.9°C; Liquid Temperature: 21.9°C

Medium(liquid type)	BL1800
Frequency (MHz)	1712.4
Relative permittivity (real part)	52.40
Conductivity (S/m)	1.49
E-Field Probe	SN 27/15 EPGO262
Crest factor	1.0
Conversion Factor	1.95
Sensor-Surface	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	0.300000
SAR 10g (W/Kg)	0.146263
SAR 1g (W/Kg)	0.217726
SURFACE SAR	VOLUME SAR






17# WCDMA Band V _RMC12.2K_Rear Face_1.0cm_Ch4233

DUT: 190325W006

Test Date: Mar 27, 2019

Ambient Temperature: 22.7°C; Liquid Temperature: 21.8°C

Medium(liquid type)	BL835
Frequency (MHz)	846.6
Relative permittivity (real part)	55.08
Conductivity (S/m)	0.95
E-Field Probe	SN 27/15 EPGO262
Crest factor	1.0
Conversion Factor	1.86
Sensor-Surface	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	-0.360000
SAR 10g (W/Kg)	0.111420
SAR 1g (W/Kg)	0.169257
SURFACE SAR	VOLUME SAR



18# LTE BAND 2_QPSK20M_Rear Face_1cm_Ch18900_1RB_OS0


DUT: 190325W006

Test Date: Mar 29, 2019



Ambient Temperature: 22.9°C; Liquid Temperature: 21.7°C

Medium(liquid type)	MSL_1900
Frequency (MHz)	1880.0
Relative permittivity (real part)	52.85
Conductivity (S/m)	1.50
E-Field Probe	SN 27/15 EPGO262
Crest factor	1.0
Conversion Factor	2.20
Sensor-Surface	4mm
Bandwidth(MHz)	20
RB Allocation	1
RB Offset	0
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	-2.240000
SAR 10g (W/Kg)	0.205841
SAR 1g (W/Kg)	0.347270

SURFACE SAR



VOLUME SAR



19# LTE BAND 4_QPSK20M_Rear Face_1cm_Ch20050_1RB_OS0


DUT: 190325W006

Test Date: Mar 28, 2019



Ambient Temperature: 22.9°C; Liquid Temperature: 21.9°C

Medium(liquid type)	MSL_1800
Frequency (MHz)	1720.0
Relative permittivity (real part)	52.40
Conductivity (S/m)	1.49
E-Field Probe	SN 27/15 EPGO262
Crest factor	1.0
Conversion Factor	1.95
Sensor-Surface	4mm
Bandwidth(MHz)	20
RB Allocation	1
RB Offset	0
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	-3.150000
SAR 10g (W/Kg)	0.156696
SAR 1g (W/Kg)	0.220301

SURFACE SAR



VOLUME SAR



20# LTE BAND 5_QPSK10M_Rear Face_1cm_Ch20525_1RB_OS0

DUT: 190325W006




Test Date: Mar 27, 2019

Ambient Temperature: 22.7°C; Liquid Temperature: 21.8°C

Medium(liquid type)	MSL_835
Frequency (MHz)	836.5
Relative permittivity (real part)	55.08
Conductivity (S/m)	0.95
E-Field Probe	SN 27/15 EPGO262
Crest factor	1.0
Conversion Factor	1.86
Sensor-Surface	4mm
Bandwidth(MHz)	10
RB Allocation	1
RB Offset	0
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	-2.500000
SAR 10g (W/Kg)	0.089184
SAR 1g (W/Kg)	0.138641

SURFACE SAR

VOLUME SAR



21# LTE BAND 7_QPSK20M_Rear Face_1cm_Ch20850_1RB_OS0


DUT: 190325W006

Test Date: Mar 30, 2019



Ambient Temperature: 22.8°C; Liquid Temperature: 21.6°C

Medium(liquid type)	MSL_2600
Frequency (MHz)	2510.0
Relative permittivity (real part)	52.41
Conductivity (S/m)	1.91
E-Field Probe	SN 27/15 EPGO262
Crest factor	1.0
Conversion Factor	2.21
Sensor-Surface	4mm
Bandwidth(MHz)	20
RB Allocation	1
RB Offset	0
Area Scan	dx=8mm dy=8mm
Zoom Scan	7x7x7,dx=5mm dy=5mm dz=5mm
Variation (%)	-2.220000
SAR 10g (W/Kg)	0.328722
SAR 1g (W/Kg)	0.714792

SURFACE SAR



VOLUME SAR



22# LTE BAND 12_QPSK10M_Rear Face_1cm_Ch23095_1RB_OS0


DUT: 190325W006

Test Date: Mar 26, 2019



Ambient Temperature: 23.1°C; Liquid Temperature: 21.9°C

Medium(liquid type)	MSL_750
Frequency (MHz)	707.5
Relative permittivity (real part)	56.62
Conductivity (S/m)	0.97
E-Field Probe	SN 27/15 EPGO262
Crest factor	1.0
Conversion Factor	1.76
Sensor-Surface	4mm
Bandwidth(MHz)	10
RB Allocation	1
RB Offset	0
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	-3.510000
SAR 10g (W/Kg)	0.118629
SAR 1g (W/Kg)	0.154199

SURFACE SAR



VOLUME SAR



23# LTE BAND 66_QPSK20M_Rear Face_1cm_Ch132072_1RB_OS0

DUT: 190325W006




Test Date: Mar 28, 2019

Ambient Temperature: 22.9°C; Liquid Temperature: 21.9°C

Medium(liquid type)	MSL_1800
Frequency (MHz)	1720.0
Relative permittivity (real part)	52.40
Conductivity (S/m)	1.49
E-Field Probe	SN 27/15 EPGO262
Crest factor	1.0
Conversion Factor	1.95
Sensor-Surface	4mm
Bandwidth(MHz)	20
RB Allocation	1
RB Offset	0
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	-3.050000
SAR 10g (W/Kg)	0.168175
SAR 1g (W/Kg)	0.240698

SURFACE SAR

VOLUME SAR






24# 802.11b_Rear Face_1cm_Ch 1

DUT: 190325W006

Test Date: Mar 30, 2019

Ambient Temperature: 22.8°C; Liquid Temperature: 21.6°C

Medium(liquid type)	BL_2450
Frequency (MHz)	2412
Relative permittivity (real part)	52.41
Conductivity (S/m)	1.91
Crest factor	1.0
E-Field Probe	SN 27/15 EPG0262
Conversion Factor	2.31
Area Scan	dx=8mm dy=8mm
Zoom Scan	7x7x7,dx=5mm dy=5mm dz=5mm
Variation (%)	0.810000
SAR 10g (W/Kg)	0.134657
SAR 1g (W/Kg)	0.267978



Appendix C. Calibration Certificate for Probe and Dipole

The MVG calibration certificates are shown as follows.



COMOSAR E-Field Probe Calibration Report

Ref : ACR.158.1.18.SATU.A

**BV 7LAYERS COMMUNICATIONS
TECHNOLOGY (SHENZHEN) CO. LTD**
NO.B102, DAZU CHUANGXIN MANSION,NORTH OF
BEIHUAN AVENUE,NORTH AREA,
HI-TECH INDUSTRIAL PARK,NANSHAN
DISTRICT,SHENZHEN, CHINA
MVG COMOSAR DOSIMETRIC E-FIELD PROBE
SERIAL NO.: SN 27/15 EPG0262

Calibrated at MVG US
2105 Barrett Park Dr. - Kennesaw, GA 30144



Calibration Date: 06/07/2018

Summary:

This document presents the method and results from an accredited COMOSAR Dosimetric E-Field Probe calibration performed in MVG USA using the CALISAR / CALIBAIR test bench, for use with a COMOSAR system only. All calibration results are traceable to national metrology institutions.



	<i>Name</i>	<i>Function</i>	<i>Date</i>	<i>Signature</i>
<i>Prepared by :</i>	Jérôme LUC	Product Manager	6/7/2018	<i>JS</i>
<i>Checked by :</i>	Jérôme LUC	Product Manager	6/7/2018	<i>JS</i>
<i>Approved by :</i>	Kim RUTKOWSKI	Quality Manager	6/7/2018	<i>Kim Rutkowski</i>

	<i>Customer Name</i>
<i>Distribution :</i>	BV 7Layers Communications Technology (Shenzhen) Co. Ltd

<i>Issue</i>	<i>Date</i>	<i>Modifications</i>
A	6/7/2018	Initial release



TABLE OF CONTENTS

1	Device Under Test	4
2	Product Description	4
2.1	General Information	4
3	Measurement Method	4
3.1	Linearity	4
3.2	Sensitivity	5
3.3	Lower Detection Limit	5
3.4	Isotropy	5
3.5	Boundary Effect	5
4	Measurement Uncertainty	5
5	Calibration Measurement Results	6
5.1	Sensitivity in air	6
5.2	Linearity	7
5.3	Sensitivity in liquid	7
5.4	Isotropy	8
6	List of Equipment	10

1 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR DOSIMETRIC E FIELD PROBE
Manufacturer	MVG
Model	SSE2
Serial Number	SN 27/15 EPGO262
Product Condition (new / used)	Used
Frequency Range of Probe	0.7 GHz-6GHz
Resistance of Three Dipoles at Connector	Dipole 1: R1=0.222 MΩ Dipole 2: R2=0.200 MΩ Dipole 3: R3=0.200 MΩ

A yearly calibration interval is recommended.

2 PRODUCT DESCRIPTION

2.1 GENERAL INFORMATION

MVG's COMOSAR E field Probes are built in accordance to the IEEE 1528, OET 65 Bulletin C and CEI/IEC 62209 standards.



Figure 1 – MVG COMOSAR Dosimetric E field Dipole

Probe Length	330 mm
Length of Individual Dipoles	2 mm
Maximum external diameter	8 mm
Probe Tip External Diameter	2.5 mm
Distance between dipoles / probe extremity	1 mm

3 MEASUREMENT METHOD

The IEEE 1528, OET 65 Bulletin C, CENELEC EN50361 and CEI/IEC 62209 standards provide recommended practices for the probe calibrations, including the performance characteristics of interest and methods by which to assess their affect. All calibrations / measurements performed meet the fore mentioned standards.

3.1 LINEARITY

The evaluation of the linearity was done in free space using the waveguide, performing a power sweep to cover the SAR range 0.01W/kg to 100W/kg.

Page: 4/10

*This document shall not be reproduced, except in full or in part, without the written approval of MVG.
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.*

3.2 SENSITIVITY

The sensitivity factors of the three dipoles were determined using a two step calibration method (air and tissue simulating liquid) using waveguides as outlined in the standards.

3.3 LOWER DETECTION LIMIT

The lower detection limit was assessed using the same measurement set up as used for the linearity measurement. The required lower detection limit is 10 mW/kg.

3.4 ISOTROPY

The axial isotropy was evaluated by exposing the probe to a reference wave from a standard dipole with the dipole mounted under the flat phantom in the test configuration suggested for system validations and checks. The probe was rotated along its main axis from 0 - 360 degrees in 15 degree steps. The hemispherical isotropy is determined by inserting the probe in a thin plastic box filled with tissue-equivalent liquid, with the plastic box illuminated with the fields from a half wave dipole. The dipole is rotated about its axis (0°–180°) in 15° increments. At each step the probe is rotated about its axis (0°–360°).

3.5 BOUNDARY EFFECT

The boundary effect is defined as the deviation between the SAR measured data and the expected exponential decay in the liquid when the probe is oriented normal to the interface. To evaluate this effect, the liquid filled flat phantom is exposed to fields from either a reference dipole or waveguide. With the probe normal to the phantom surface, the peak spatial average SAR is measured and compared to the analytical value at the surface.

4 MEASUREMENT UNCERTAINTY

The guidelines outlined in the IEEE 1528, OET 65 Bulletin C, CENELEC EN50361 and CEI/IEC 62209 standards were followed to generate the measurement uncertainty associated with an E-field probe calibration using the waveguide technique. All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

Uncertainty analysis of the probe calibration in waveguide					
ERROR SOURCES	Uncertainty value (%)	Probability Distribution	Divisor	ci	Standard Uncertainty (%)
Incident or forward power	3.00%	Rectangular	$\sqrt{3}$	1	1.732%
Reflected power	3.00%	Rectangular	$\sqrt{3}$	1	1.732%
Liquid conductivity	5.00%	Rectangular	$\sqrt{3}$	1	2.887%
Liquid permittivity	4.00%	Rectangular	$\sqrt{3}$	1	2.309%
Field homogeneity	3.00%	Rectangular	$\sqrt{3}$	1	1.732%
Field probe positioning	5.00%	Rectangular	$\sqrt{3}$	1	2.887%