



Report No.: SZ11090038W01



FCC TEST REPORT

Issued to

CORPORATIVO LANIX S.A. DE C.V.

For

GSM mobile phone

Model Name: LX5
Brand Name: LANIX
Trade Name: LANIX
FCC ID: ZC4LX5
Standard: 47 CFR Part 2
47 CFR Part 22 Subpart H
47 CFR Part 24 Subpart E
Test date: September 09, 2011- September 15, 2011
Issue date: April 24, 2012

Shenzhen Morlab Communications Technology Co., Ltd.



Tested by Zhang Yan

Zhang Yan

Date 2012. 4. 24

Approved by Wu Xuewen

Wu Xuewen

Date 2012. 04. 24

Review by

Peng Huarui

Peng Huarui

Date 2012. 4. 24

CTIA Authorized Test Lab
LAB CODE 20081223-00

IEEE 1725 OTA

OFTA
電訊管理局



GCF
Official Observer of
Global Certification Forum

Bluetooth
BQTF

FCC
Reg. No.
741109

The report refers only to the sample tested and does not apply to the bulk. This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen MORLAB Communication Technology Co., Ltd. It may not be reproduced either in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it or a certified copy thereof prepared by the Shenzhen MORLAB Telecommunication Co., Ltd to his customer. Supplier or others persons directly concerned. Shenzhen MORLAB Telecommunication Co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report. In the event of the improper use of the report, Shenzhen MORLAB Telecommunication Co., Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

TABLE OF CONTENTS

1.	GENERAL INFORMATION	3
1.1	EUT Description	3
1.2	Test Standards and Results	4
1.3	Facilities and Accreditations	5
2.	47 CFR PART 2, PART 22H & 24E REQUIREMENTS	6
2.1	Conducted RF Output Power	6
2.2	99% Occupied Bandwidth	17
2.3	Frequency Stability	21
2.4	Conducted Out of Band Emissions	23
2.5	Band Edge	30
2.6	Transmitter Radiated Power (EIRP/ERP)	33
2.7	Radiated Out of Band Emissions	39

Change History		
Issue	Date	Reason for change
1.0	April 24, 2012	First edition

1. GENERAL INFORMATION

1.1 EUT Description

EUT Type: GSM mobile phone
Serial No.....: (n.a, marked #1 by test site)
Hardware Version: V1.0
Software Version: ZV268A_45A0_V1_0_6
Applicant: CORPORATIVO LANIX S.A. DE C.V.
CARRETERA INTERNACIONAL A NOGALES KM 8.5 C.P.
83160 HERMOSILLO SONORA, MEXICO
Manufacturer: Shanghai Huaqin Telecom Technology Co., Ltd.
NO.1 Building,399 Keyuan Road, Zhangjiang Hi-Tech Park,
Pudong New Area, Shanghai, China 201203
Frequency Range: GSM 850MHz:
Tx: 824.20 - 848.80MHz (at intervals of 200kHz);
Rx: 869.20 - 893.80MHz (at intervals of 200kHz)
GSM 1900MHz:
Tx: 1850.20 - 1909.80MHz (at intervals of 200kHz);
Rx: 1930.20 - 1989.80MHz (at intervals of 200kHz)
Multislot Class.....: Multislot Class 10
Antenna Type.....: PIFA
Modulation Type.....: GMSK
Emission Designators: 300KGXW

Note 1: The transmitter (Tx) frequency arrangement of the Cellular 850MHz band used by the EUT can be represented with the formula $F(n)=824.2+0.2*(n-128)$, $128 \leq n \leq 251$; the lowest, middle, highest channel numbers (ARFCHs) used and tested in this report are separately 128 (824.2MHz), 190 (836.6MHz) and 251 (848.8MHz).

Note 2: The transmitter (Tx) frequency arrangement of the PCS 1900MHz band used by the EUT can be represented with the formula $F(n)=1850.2+0.2*(n-512)$, $512 \leq n \leq 810$; the lowest, middle and highest channel numbers (ARFCHs) used and tested in this report are separately 512 (1850.2MHz), 661 (1880.0MHz) and 810 (1909.8MHz).

Note 3: The GPRS was tested under 4 time-slots mode.

Note 4: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

1.2 Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 2, Part 22 and Part 24 for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 2 (10-1-09 Edition)	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
2	47 CFR Part 22 (10-1-09 Edition)	Public Mobile Services
3	47 CFR Part 24 (10-1-09 Edition)	Personal Communications Services

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Result
1	2.1046	Conducted RF Output Power	PASS
2	2.1049	20dB Occupied Bandwidth	PASS
3	2.1055 22.355 24.235	Frequency Stability	PASS
4	2.1051 2.1057 22.917 24.238	Conducted Out of Band Emissions	PASS
5	2.1051 2.1057 22.917 24.238	Band Edge	PASS
6	22.913 24.232	Transmitter Radiated Power (EIPR/ERP)	PASS
7	2.1053 2.1057 22.917 24.238	Radiated Out of Band Emissions	PASS

NOTE: Measurement method according to ANSI/TIA-603-D 2010.

1.3 Facilities and Accreditations

1.3.1 Facilities

Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L3572.

All measurement facilities used to collect the measurement data are located at 3/F, Electronic Testing Building, Shahe Road, Xili, Nanshan District, Shenzhen, 518055 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22; the FCC registration number is 741109.

1.3.2 Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 - 35
Relative Humidity (%):	30 -60
Atmospheric Pressure (kPa):	86-106

2. 47 CFR PART 2, PART 22H & 24E REQUIREMENTS


2.1 Conducted RF Output Power

2.1.1 Requirement

According to FCC section 2.1046(a), for transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, power output shall be measured at the RF output terminals when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in FCC section 2.1033(c)(8).

2.1.2 Test Description

1. Test Setup:



The EUT, which is powered by the Battery, is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the SS.

2. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date
System Simulator	Agilent	E5515C	GB43130131	2011.05
Spectrum Analyzer	Agilent	E7405A	US44210471	2011.05
Power Splitter	Weinschel	1506A	NW521	(n.a.)
Attenuator 1	Resnet	20dB	(n.a.)	(n.a.)
Attenuator 2	Resnet	3dB	(n.a.)	(n.a.)

2.1.3 Test Result

Here the lowest, middle and highest channels are selected to perform testing to verify the conducted RF output power of the EUT. For the GSM 850MHz operates at PCL=5 (where Power Class is 4), the


rated conducted RF output power is 33dBm, and For the GSM 1900MHz operates at PCL=0 (where Power Class is 1), the rated conducted RF output power is 30dBm.

1. Test Verdict:


Band	Channel	Frequency (MHz)	Measured Output Power		Limit dBm	Verdict
			dBm	Refer to Plot		
GSM 850MHz	128	824.1	34.06	Plot A1 to A3	35	PASS
	190	836.6	34.00			PASS
	251	848.7	33.95			PASS
GSM 1900MHz	512	1850.1	30.09	Plot B1 to B3	32	PASS
	661	1879.9	30.04			PASS
	810	1909.8	29.55			PASS
GPRS 850MHz	128	824.1	33.43	Plot G1 to G3 3down link 2up link	35	PASS
	190	836.5	33.14			PASS
	251	848.7	33.15			PASS
GPRS 1900MHz	512	1850.2	29.45	Plot H1 to H3 3down link 2up link	32	PASS
	661	1879.9	29.54			PASS
	810	1909.8	29.65			PASS
GPRS 850MHz	128	824.2	32.23	Plot I1 to I3 4down link 1up link	35	PASS
	190	836.5	33.88			PASS
	251	848.7	33.88			PASS
GPRS 1900MHz	512	1850.0	30.08	Plot J1 to J3 4down link 1up link	32	PASS
	661	1879.9	30.12			PASS
	810	1909.7	30.45			PASS

2. Test Plot


Plot A1: GSM 850MHz Channel = 128




Plot A2: GSM 850MHz Channel = 190




Plot A3: GSM 850MHz Channel = 251




Plot B1: GSM 1900MHz Channel = 512




Plot B2: GSM 1900MHz Channel = 661




Plot B3: GSM 1900MHz Channel = 810




Plot G1: GPRS850MHz Channel = 128-3down link 2up link




Plot G2: GPRS 850MHz Channel = 190-3down link 2up link




Plot G3: GPRS 850MHz Channel = 251-3down link 2up link




Plot H1: GPRS 1900MHz Channel = 512-3down link 2up link




Plot H2: GPRS 1900MHz Channel = 661-3down link 2up link




Plot H3: GPRS 1900MHz Channel = 810-3down link 2up link




Plot I1: GPRS 850MHz Channel = 128 -4down link 1up link




Plot I2: GPRS 850MHz Channel = 190-4down link 1up link




Plot I3: GPRS 850MHz Channel = 251-4down link 1up link




Plot J1: GPRS 1900MHz Channel = 512-4down link 1up link



Plot J2: GPRS 1900MHz Channel = 661-4down link 1up link



Plot J3: GSM1900MHz Channel = 810-4down link 1up link



2.2 99% Occupied Bandwidth

2.2.1 Definition

According to FCC section 2.1049, the occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission.

Occupied bandwidth is also known as the 99% emission bandwidth.

2.2.2 Test Description

See section 2.1.2 of this report.


2.2.3 Test Verdict

Here the lowest, middle and highest channels are tested to record the 99% occupied bandwidth


Test Verdict:

Band	Channel	Frequency (MHz)	Measured 99% Occupied Bandwidth (kHz)	Refer to Plot
GSM 850MHz	128	824.1	247.7259	Plot A
	190	836.5	248.2947	Plot B
	251	848.7	245.2808	Plot C
GSM 1900MHz	512	1850.2	243.3654	Plot D
	661	1880.0	251.0824	Plot E
	810	1909.7	245.5848	Plot F


3. Test Plots:




(Plot A: GSM 850MHz Channel = 128)




(Plot B: GSM 850MHz Channel = 190)




(Plot C: GSM 850MHz Channel = 251)



(Plot D: GSM 1900MHz Channel = 512)



(Plot E: GSM 1900MHz Channel = 661)



(Plot F: GSM 1900MHz Channel = 810)

2.3 Frequency Stability


2.3.1 Requirement

According to FCC section 22.355 and FCC section 24.235, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. According to FCC section 2.1055, the test conditions are:

- (a) The temperature is varied from -30°C to +50°C at intervals of not more than 10°C.
- (b) For hand carried battery powered equipment, the primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer. The supply voltage shall be measured at the input to the cable normally provided with the equipment, or at the power supply terminals if cables are not normally provided.

2.3.2 Test Description

1. Test Setup:



The EUT, which is powered by the DC Power Supply directly, is located in the Temperature Chamber. The EUT is commanded by the System Simulator (SS) to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the SS via a Common Antenna.

2. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date
System Simulator	Agilent	E5515C	GB43130131	2011.05
DC Power Supply	Good Will	GPS-3030DD	EF920938	2011.05
Temperature Chamber	YinHe Experimental Equip.	HL4003T	(n.a.)	2011.05

2.3.3 Test Verdict

The nominal, highest and lowest extreme voltages are separately 3.7VDC, 4.2VDC and 3.5VDC, which are specified by the applicant; the normal temperature here used is 25°C. The frequency

deviation limit of GSM 850MHz band is ± 2.5 ppm, and GSM 1900MHz is ± 1 ppm

Band	Test Conditions		Frequency Deviation						Verdict	
	Power (VDC)	Temperature (°C)	Channel = 128 (824.2MHz)		Channel = 190 (836.6MHz)		Channel = 251 (848.8MHz)			
			Hz	Limits	Hz	Limits	Hz	Limits		
GSM 850MHz	3.8	-30	27.12	± 2060.5	27.82	± 2091.5	25.74	± 2122	PASS	
		-20	26.83		29.70		25.74			
		-10	23.28		28.12		31.14			
		0	25.11		21.06		25.17			
		+10	-23.13		13.07		25.47			
		+20	-10.39		-12.76		-7.61			
		+30	17.75		-2.05		6.09			
		+40	5.31		-33.77		15.49			
		+50	-12.19		5.39		10.19			
		4.2	+25		19.65		8.71			
		3.6	+25		-26.96		-25.27			
GSM 1900MHz	3.8	Test Conditions		Frequency Deviation						
		Power (VDC)	Temperature (°C)	Channel = 512 (1850.2MHz)		Channel = 661 (1880.0MHz)		Channel = 810 (1909.8MHz)		Verdict
				Hz	Limits	Hz	Limits	Hz	Limits	
		-30	29.30	± 1850.2	27.82	± 1880.0	29.47	± 1909.8	PASS	
		-20	29.22		29.45		29.30			
		-10	25.19		28.17		27.12			
		0	29.37		-3.20		11.82			
		+10	13.97		20.04		19.77			
		+20	22.42		-14.29		-22.73			
		+30	18.57		-27.62		-22.22			
		+40	-19.93		-17.97		22.21			
		+50	23.76		-18.23		-22.22			
		4.2	+25		27.16		22.63			
		3.6	+25		-15.31		-15.15			

2.4 Conducted Out of Band Emissions

2.4.1 Requirement

According to FCC section 22.917(a) and FCC section 24.238(a), the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43+10*\log(P)$ dB. This calculated to be -13dBm.

2.4.2 Test Description

See section 2.1.2 of this report.

2.4.3 Test Result


The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the out of band emissions.

1. Test Verdict:


Band	Channel	Frequency (MHz)	Measured Max. Spurious Emission (dBm)	Refer to Plot	Limit (dBm)	Verdict
GSM 850MHz	128	824.2	-30.00	Plot A	-13	PASS
	190	836.6	-30.09	Plot B		PASS
	251	848.8	-30.74	Plot C		PASS
GSM 1900MHz	512	1850.2	-32.76	Plot D	-13	PASS
	661	1880.0	-32.20	Plot E		PASS
	810	1909.8	-33.07	Plot F		PASS

2. Test Plots for the Whole Measurement Frequency Range:


Note: the power of the EUT transmitting frequency should be ignored.




(Plot A: GSM 850MHz Channel = 128,30Hz to 1GHz)




(Plot A: GSM 850MHz Channel = 128, 1GHz to 9GHz)




(Plot B: GSM 850MHz Channel = 190, 30MHz to 1GHz)




(Plot B: GSM 850MHz Channel = 190, 1GHz to 9GHz)




(Plot C: GSM 850 MHz Channel = 251, 30MHz to 1GHz)




(Plot C: GSM 850MHz Channel = 251, 1GHz to 9GHz)




(Plot D: GSM 1900MHz Channel = 512, 30MHz to 1GHz)




(Plot D: GSM 1900MHz Channel = 512, 1GHz to 20GHz)




(Plot E: GSM 1900MHz Channel = 661, 30MHz to 1GHz)



(Plot E: GSM 1900MHz Channel = 661, 1GHz to 20GHz)



(Plot F: GSM 1900MHz Channel = 810, 30MHz to 1GHz)



(Plot F: GSM 1900MHz Channel = 810, 1GHz to 20GHz)

2.5 Band Edge

2.5.1 Requirement

According to FCC section 22.917(b) and FCC section 24.238(b), in the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth (26dB emission bandwidth) of the fundamental emission of the transmitter may be employed.

2.5.2 Test Description

See section 2.1.2 of this report.


2.5.3 Test Result

The lowest and highest channels are tested to verify the band edge emissions.


1. Test Verdict:

Band	Channel	Frequency (MHz)	Measured Max. Band Edge Emission (dBm)	Refer to Plot	Limit (dBm)	Verdict
GSM 850MHz	128	823.9	-13.14	Plot A	-13	PASS
	251	848.8	-13.76	Plot B		PASS
GSM 1900MHz	512	1850.2	-18.10	Plot C	-13	PASS
	810	1909.8	-17.50	Plot D		PASS


2. Test Plots:




(Plot A: Channel = 128)



(Plot B: Channel = 251)



(Plot C: Channel = 512)



(Plot D: Channel = 810)


2.6 Transmitter Radiated Power (EIRP/ERP)

2.6.1 Requirement

According to FCC section 22.913, the Effective Radiated Power (ERP) of mobile transmitters and auxiliary test transmitters must not exceed 7Watts, and FCC section 24.232, the broadband PCS mobile station is limited to 2Watts e.i.r.p. peak power.

2.6.2 Test Description

1. Test Setup:



The EUT, which is powered by the Battery charged with the AC Adapter, is located in a 3m Full-Anechoic Chamber; the cable loss, air loss and so on of the site as factors are pre-calibrated using the "Substitution" method, and calculated to correct the reading.

A call is established between the EUT and the SS via a Common Antenna. The EUT is commanded by the SS to operate at the maximum and minimum output power (i.e. GSM850MHz band Power Control Level (PCL) = 5/19 and Power Class = 4, GSM1900MHz band Power Control Level (PCL) = 0/15 and Power Class = 1), and only the test result of the maximum output power was recorded.

-Maximum RF output power: GSM850 31.82dBm, GSM 1900 29.26dBm, Please refer to section 2.1.3 of this report.

- Step size (dB): 3dB

- Minimum RF power: GSM850 -4.2dBm, GSM 1900 -10.16dBm

The Test Antenna is a Bi-Log one (used for 30MHz to 1GHz) or a Horn one (used for above 3GHz), and it's located at the same height as the EUT. The Filters consists of Notch Filters and High Pass Filter.

2. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date
System Simulator	Agilent	E5515C	GB43130131	2011.05
Spectrum Analyzer	Agilent	E7405A	US44210471	2011.05
Full-Anechoic Chamber	Albatross	9m*6m*6m	(n.a.)	2011.05
Test Antenna - Bi-Log	Schwarzbeck	VULB 9163	9163-274	2011.05
Test Antenna - Horn	Schwarzbeck	BBHA 9120C	9120C-384	2011.05

2.6.3 Test Result

The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. The lowest, middle and highest channels are tested.

The substitution corrections are obtained as described below:

$$A_{SUBST} = P_{SUBST_TX} - P_{SUBST_RX} - L_{SUBST_CABLES} + G_{SUBST_TX_ANT}$$

$$A_{TOT} = L_{CABLES} + A_{SUBST}$$

Where A_{SUBST} is the final substitution correction including receive antenna gain.

P_{SUBST_TX} is signal generator level,

P_{SUBST_RX} is receiver level,

L_{SUBST_CABLES} is cable losses including TX cable,

$G_{SUBST_TX_ANT}$ is substitution antenna gain.

A_{TOT} is total correction factor including cable loss and substitution correction

During the test, the data of A_{TOT} was added in the Test Spectrum Analyze, so Spectrum Analyze reading is the final values which contain the data of A_{TOT} .

1. Test Verdict:


Test result of ERP:

Band	Channel	Frequency (MHz)	PCL	Measured ERP			Limit		Verdict
				dBm	W	Refer to Plot	dBm	W	
GSM 850MHz	128	824.20	5	29.9	0.977237	Plot A	38.45	7	PASS
	190	836.60	5	30.73	1.183042				PASS
	251	848.80	5	30.1	1.023293				PASS
GPRS 850MHz	128	824.20	5	29.5	0.891251	Plot D 3down link 2up link	38.45	7	PASS
	190	836.60	5	30.53	1.129796				PASS
	251	848.80	5	30.09	1.020939				PASS
GPRS 850MHz	128	824.20	5	29.09	0.810961	Plot C 4down link 1up link	38.45	7	PASS
	190	836.60	5	30.4	1.096478				PASS
	251	848.80	5	30.07	1.016249				PASS


Test result of EIRP:

Band	Channel	Frequency (MHz)	PCL	Measured EIRP			Limit		Verdict
				dBm	W	Refer to Plot	dBm	W	
GSM 1900MHz	512	1850.2	0	29.74	0.941890	Plot D	33	2	PASS
	661	1880.0	0	29.2	0.831764				PASS
	810	1909.8	0	28.78	0.755092				PASS
GPRS 1900MHz	512	1850.2	0	28.04	0.636796	Plot E 3down link 2up link	33	2	PASS
	661	1880.0	0	28.25	0.668344				PASS
	810	1909.8	0	28.64	0.731139				PASS
GPRS 1900MHz	512	1850.2	0	29.72	0.937562	Plot F 4down link 1up link	33	2	PASS
	661	1880.0	0	29.22	0.835603				PASS
	810	1909.8	0	29.54	0.899498				PASS


2. Test Plots:




(Plot A: GSM 850MHz Channel = 128,190,251)




(Plot B: GPRS 850MHz Channel = 128,190,251-3down link 2up link)




(Plot C: GPRS 850MHz Channel = 128,190,251-4down link 1up link)



(Plot D: GSM 1900MHz Channel = 512, 661, 810)



(Plot E: GPRS 1900MHz Channel = 512, 661, 810-3down link 2up link)



(Plot F: GPRS 1900MHz Channel = 512,661,810-2down link 3up link)

2.7 Radiated Out of Band Emissions

2.7.1 Requirement

According to FCC section 22.917(a) and section 24.238(a), the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43+10*\log(P)$ dB. This calculated to be -13dBm.

2.7.2 Test Description

See section 2.6.2 of this report.

Note: when doing measurements above 1GHz, the EUT has been within the 3dB cone width of the horn antenna during horizontal antenna.

2.7.3 Test Result


The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360° , and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. The lowest, middle and highest channels are tested to verify the out of band emissions.

1. Test Verdict:


Band	Channe l	Frequenc y (MHz)	Measured Max. Spurious Emission (dBm)		Refer to Plot	Limit (dBm)	Verdict
			Test Antenna Horizontal	Test Antenna Vertical			
GSM 850MHz	128	824.2	-36.33	-36.37	Plot A.1/A.2	-13	PASS
	190	836.6	-35.97	-48.03	Plot B.1/B.2		PASS
	251	848.8	-35.98	-35.69	Plot C.1/C.2		PASS
GSM 1900MHz	512	1850.2	22.21	-17.49	Plot D.1/D.2	-13	PASS
	661	1880.0	-20.23	-16.64	Plot E.1/E.2		PASS
	810	1909.8	-20.42	-14.29	Plot F.1/F.2		PASS

2. Test Plots for the Whole Measurement Frequency Range:


Note: the power of the EUT transmitting frequency should be ignored.




(Plot A.1: GSM 850MHz Channel = 128, Test Antenna Horizontal)




(Plot A.2: GSM 850MHz Channel = 128, Test Antenna Vertical)




(Plot B.1: GSM 850MHz Channel = 190, Test Antenna Horizontal)




(Plot B.2: GSM 850MHz Channel = 190, Test Antenna Vertical)




(Plot C.1: GSM 850MHz Channel = 251, Test Antenna Horizontal)



(Plot C.2: GSM 850MHz Channel = 251, Test Antenna Vertical)



(Plot D.1: GSM 1900MHz Channel = 512, Test Antenna Horizontal)



(Plot D.2: GSM 1900MHz Channel = 512, Test Antenna Vertical)




(Plot E.1: GSM 1900MHz Channel = 661, Test Antenna Horizontal)



(Plot E.2: GSM 1900MHz Channel = 661, Test Antenna Vertical)



(Plot F.1: GSM 1900MHz Channel = 810, Test Antenna Horizontal)



(Plot F.2: GSM 1900MHz Channel = 810, Test Antenna Vertical)

** END OF REPORT **