



SAR TEST REPORT

No. I19Z62374-SEM09

For

SAMSUNG Electronics Co., Ltd.

Multi-band GSM/WCDMA/LTE phone with Bluetooth, WLAN

Model name: SM-A215U1

With

Hardware Version: REV1.0

Software Version: A215U1.001

FCC ID: ZCASMA215U

Issued Date: 2020-3-21

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

Test Laboratory:

CTTL, Telecommunication Technology Labs, CAICT

No. 51, Xueyuan Road, Haidian District, Beijing, P. R. China 100191.

Tel: +86(0)10-62304633-2512, Fax: +86(0)10-62304633-2504

Email: ctl_terminals@caict.ac.cn, website: www.caict.ac.cn



No.I19Z62374-SEM09

REPORT HISTORY

Report Number	Revision	Issue Date	Description
I19Z62374-SEM09	Rev.0	2020-3-21	Initial creation of test report

TABLE OF CONTENT

1 TEST LABORATORY	5
1.1 TESTING LOCATION.....	5
1.2 TESTING ENVIRONMENT.....	5
1.3 PROJECT DATA	5
1.4 SIGNATURE.....	5
2 STATEMENT OF COMPLIANCE	6
3 CLIENT INFORMATION	8
3.1 APPLICANT INFORMATION	8
3.2 MANUFACTURER INFORMATION	8
4 EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	9
4.1 ABOUT EUT	9
4.2 INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	9
4.3 INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	10
5 TEST METHODOLOGY	11
5.1 APPLICABLE LIMIT REGULATIONS	11
5.2 APPLICABLE MEASUREMENT STANDARDS	11
6 SPECIFIC ABSORPTION RATE (SAR).....	12
6.1 INTRODUCTION.....	12
6.2 SAR DEFINITION.....	12
7 TISSUE SIMULATING LIQUIDS	13
7.1 TARGETS FOR TISSUE SIMULATING LIQUID.....	13
7.2 DIELECTRIC PERFORMANCE	13
8 SYSTEM VERIFICATION	18
8.1 SYSTEM SETUP.....	18
8.2 SYSTEM VERIFICATION.....	19
9 MEASUREMENT PROCEDURES	20
9.1 TESTS TO BE PERFORMED	20
9.2 GENERAL MEASUREMENT PROCEDURE.....	22
9.3 WCDMA MEASUREMENT PROCEDURES FOR SAR	23
9.4 SAR MEASUREMENT FOR LTE.....	24
9.5 BLUETOOTH & WI-FI MEASUREMENT PROCEDURES FOR SAR	26
9.6 POWER DRIFT	26
10 AREA SCAN BASED 1-G SAR.....	27
10.1 REQUIREMENT OF KDB.....	27
10.2 FAST SAR ALGORITHMS	27

11 CONDUCTED OUTPUT POWER.....	28
11.1 GSM MEASUREMENT RESULT	28
11.2 WCDMA MEASUREMENT RESULT	30
11.3 CDMA MEASUREMENT RESULT	32
11.3 LTE MEASUREMENT RESULT	33
11.4 Wi-Fi AND BT MEASUREMENT RESULT	76
12 SIMULTANEOUS TX SAR CONSIDERATIONS.....	79
12.1 INTRODUCTION.....	79
12.2 TRANSMIT ANTENNA SEPARATION DISTANCES.....	79
12.3 SAR MEASUREMENT POSITIONS	79
12.4 STANDALONE SAR TEST EXCLUSION CONSIDERATIONS	80
13 EVALUATION OF SIMULTANEOUS.....	81
14 SAR TEST RESULT	83
14.1 SAR RESULTS FOR FAST SAR	84
14.2 SAR RESULTS FOR STANDARD PROCEDURE	99
14.3 WLAN EVALUATION FOR 2.4G	107
14.4 WLAN EVALUATION FOR 5G.....	110
15 SAR MEASUREMENT VARIABILITY.....	116
16 MEASUREMENT UNCERTAINTY	117
16.1 MEASUREMENT UNCERTAINTY FOR NORMAL SAR TESTS (300MHz~3GHz).....	117
16.2 MEASUREMENT UNCERTAINTY FOR NORMAL SAR TESTS (3~6GHz)	118
16.3 MEASUREMENT UNCERTAINTY FOR FAST SAR TESTS (300MHz~3GHz).....	119
16.4 MEASUREMENT UNCERTAINTY FOR FAST SAR TESTS (3~6GHz)	120
17 MAIN TEST INSTRUMENTS.....	121
ANNEX A GRAPH RESULTS.....	122
ANNEX B SYSTEM VERIFICATION RESULTS	173
ANNEX C SAR MEASUREMENT SETUP	183
ANNEX D POSITION OF THE WIRELESS DEVICE IN RELATION TO THE PHANTOM	189
ANNEX E EQUIVALENT MEDIA RECIPES	192
ANNEX F SYSTEM VALIDATION	193
ANNEX G PROBE CALIBRATION CERTIFICATE.....	194
ANNEX H DIPOLE CALIBRATION CERTIFICATE	222
ANNEX I SENSOR TRIGGERING DATA SUMMARY.....	317
ANNEX J ACCREDITATION CERTIFICATE.....	323

1 Test Laboratory

1.1 Testing Location

Company Name:	CTTL(Shouxiang)
Address:	No. 51 Shouxiang Science Building, Xueyuan Road, Haidian District, Beijing, P. R. China100191

1.2 Testing Environment

Temperature:	18°C~25°C,
Relative humidity:	30%~ 70%
Ground system resistance:	< 0.5 Ω
Ambient noise & Reflection:	< 0.012 W/kg


1.3 Project Data

Project Leader:	Qi Dianyuan
Test Engineer:	Lin Xiaojun
Testing Start Date:	January 13, 2020
Testing End Date:	January 21, 2020


1.4 Signature



Lin Xiaojun
(Prepared this test report)



Qi Dianyuan
(Reviewed this test report)



Lu Bingsong
Deputy Director of the laboratory
(Approved this test report)

2 Statement of Compliance

The maximum results of SAR found during testing for SAMSUNG Electronics Co., Ltd. Multi-band GSM/WCDMA/LTE phone with Bluetooth, WLAN SM-A215U1 are as follows:

Table 2.1: Highest Reported SAR (1g)

Exposure Configuration	Technology Band	Highest Reported SAR 1g(W/kg)	Equipment Class
Head	GSM 850	0.38	PCE
	PCS 1900	0.18	
	UMTS FDD 2	0.23	
	UMTS FDD 4	0.17	
	UMTS FDD 5	0.42	
	CDMA BC0	0.32	
	CDMA BC1	0.10	
	CDMA BC10	0.28	
	LTE Band 7	0.20	
	LTE Band 12	0.25	
	LTE Band 13	0.36	
	LTE Band 25	0.30	
	LTE Band 26	0.42	
	LTE Band 41(Power Class 3)	0.19	
	LTE Band 41(Power Class 2)	0.12	
	LTE Band 66	0.15	
	LTE Band 71	0.26	
	WLAN 2.4 GHz	0.57	DTS
	WLAN 5 GHz	0.60	UNII
Hotspot	GSM 850	0.45	PCE
	PCS 1900	1.27	
	UMTS FDD 2	0.76	
	UMTS FDD 4	0.90	
	UMTS FDD 5	0.51	
	CDMA BC0	0.62	
	CDMA BC1	0.60	
	CDMA BC10	0.46	
	LTE Band 7	0.38	
	LTE Band 12	0.47	
	LTE Band 13	0.48	
	LTE Band 25	0.75	
	LTE Band 26	0.47	
	LTE Band 41(Power Class 3)	0.22	
	LTE Band 41(Power Class 2)	0.24	
	LTE Band 66	0.72	
	LTE Band 71	0.45	
	WLAN 2.4 GHz	0.54	DTS
	WLAN 5 GHz	0.40	UNII

The SAR values found for the Mobile Phone are below the maximum recommended levels of 1.6 W/kg as averaged over any 1g tissue according to the ANSI C95.1-1992.

For body operation, this device has been tested and meets FCC RF exposure guidelines when used with any accessory that contains no metal and which provides a minimum separation distance of 10 mm between this device and the body of the user. Use of other accessories may not ensure compliance with FCC RF exposure guidelines.

The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power output.

The measurement together with the test system set-up is described in annex C of this test report. A detailed description of the equipment under test can be found in chapter 4 of this test report. The highest reported SAR value is obtained at the case of **(Table 2.1)**, and the values are: **1.27 W/kg(1g)**.

Table 2.2: The sum of reported SAR values for main antenna and WiFi2.4G

	Position	Main antenna	WiFi	Sum
Highest reported SAR value for Head	Left hand, Tilt	0.26	0.57	0.83
Highest reported SAR value for Body	Bottom 10mm	1.27	/	1.27

Table 2.3: The sum of reported SAR values for main antenna and WiFi5G

	Position	Main antenna	WiFi	Sum
Highest reported SAR value for Head	Left hand, Touch cheek	0.37	0.55	0.92
Highest reported SAR value for Body	Bottom 10mm	1.27	/	1.27

Table 2.4: The sum of reported SAR values for main antenna and BT

	Position	Main antenna	BT	Sum
Maximum reported SAR value for Head	Right hand, Touch cheek	0.42	0.33 ^[1]	0.75
Maximum reported SAR value for Body	Bottom 10mm	1.27	/	1.27

[1] - Estimated SAR for Bluetooth (see the table 13.3)

According to the above tables, the highest sum of reported SAR values is **1.27 W/kg (1g)**. The detail for simultaneous transmission consideration is described in chapter 13.

3 Client Information

3.1 Applicant Information

Company Name:	SAMSUNG Electronics Co., Ltd.
Address/Post:	19 Chapin Rd.,Building D Pine Brook ,NJ 07058
Contact Person:	Jenni Chun
Contact Email:	j1.chun@samsung.com
Telephone:	1-973-808-6375
Fax	NA

3.2 Manufacturer Information

Company Name:	SAMSUNG Electronics Co., Ltd.
Address/Post:	Samsung R5, Maetan dong 129, Samsung ro Youngtong gu, Suwon city 443 742, Korea
Contact Person:	JP KIM
Contact Email:	jp426.kim@samsung.com
Telephone:	NA
Fax	NA

4 Equipment Under Test (EUT) and Ancillary Equipment (AE)

4.1 About EUT

Description:	Multi-band GSM/WCDMA/LTE phone with Bluetooth, WLAN
Model name:	SM-A215U1
Operating mode(s):	GSM 850/900/1800/1900, UMTS FDD 1/2/4/5/8, CDMA BC0/1/10,BT, Wi-Fi, LTE Band 1/2/3/4/5/7/8/12/13/17/20/25/26/28/38/39/40/41/66/71
Tested Tx Frequency:	824 – 849 MHz (GSM 850)
	1850 – 1910 MHz (GSM 1900)
	824–849 MHz (WCDMA 850 Band V)
	1710 – 1755 MHz (WCDMA 1700 Band IV)
	1850–1910 MHz (WCDMA1900 Band II)
	824.7 - 848.31 MHz (CDMA BC0)
	1851.25 - 1908.75 MHz (CDMA BC1)
	817.9 - 823.1 MHz (CDMA BC10)
	2502.5 – 2567.5 MHz(LTE Band 7)
	699.7 – 715.3 MHz (LTE Band 12)
	779.5 –784.5 MHz (LTE Band 13)
	1850.7 – 1914.3 MHz (LTE Band 25)
	814.7 – 848.3 MHz (LTE Band 26)
	2498.5 – 2687.5 MHz (LTE Band 41)
	1710.7 – 1779.3 MHz (LTE Band 66)
	665.5 – 695.5 MHz (LTE Band 71)
	2412 – 2462 MHz (Wi-Fi 2.4G)
	5.15 – 5.825 GHz(Wi-Fi 5G)
GPRS/EGPRS Multislot Class:	12
GPRS capability Class:	B
Test device Production information:	Production unit
Device type:	Portable device
Antenna type:	Integrated antenna
Hotspot mode:	Support

4.2 Internal Identification of EUT used during the test

EUT ID*	IMEI	HW	SW Version
EUT1	354230110026528	REV1.0	A215U1.001
EUT2	354230110026544	REV1.0	A215U1.001
EUT3	354230110026718	REV1.0	A215U1.001
EUT4	354230110026700	REV1.0	A215U1.001
EUT5	354230110026494	REV1.0	A215U1.001
EUT6	354230110026486	REV1.0	A215U1.001
EUT7	354230110026569	REV1.0	A215U1.001

*EUT ID: is used to identify the test sample in the lab internally.

Note: It is performed to test SAR with the EUT1~4 and conducted power with the EUT5~7.

4.3 Internal Identification of AE used during the test

AE ID*	Description	Model	SN	Manufacturer
AE1	Battery	WT240	/	Jiade Energy Technology (Zhuhai) Co., Ltd
AE2	Headset	GH59-15054A	/	Yuenchang
AE3	Headset	GH59-15054A	/	Almusglobal
AE4	Headset	GH59-15054A	/	ESTEC

*AE ID: is used to identify the test sample in the lab internally.

5 TEST METHODOLOGY

5.1 Applicable Limit Regulations

ANSI C95.1–1992:IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

It specifies the maximum exposure limit of **1.6 W/kg** as averaged over any 1 gram of tissue for portable devices being used within 20 cm of the user in the uncontrolled environment.

5.2 Applicable Measurement Standards

IEEE 1528–2013: Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.

KDB447498 D01: General RF Exposure Guidance v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

KDB648474 D04 Handset SAR v01r03: SAR Evaluation Considerations for Wireless Handsets.

KDB941225 D01 SAR test for 3G devices v03r01: SAR Measurement Procedures for 3G Devices

KDB941225 D05 SAR for LTE Devices v02r05: SAR Evaluation Considerations for LTE Devices

KDB941225 D06 Hotspot Mode SAR v02r01: SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities

KDB248227 D01 802.11 Wi-Fi SAR v02r02: SAR GUIDANCE FOR IEEE 802.11 (Wi-Fi) TRANSMITTERS

KDB865664 D01SAR measurement 100 MHz to 6 GHz v01r04: SAR Measurement Requirements for 100 MHz to 6 GHz.

KDB865664 D02RF Exposure Reporting v01r02: RF Exposure Compliance Reporting and Documentation Considerations

6 Specific Absorption Rate (SAR)

6.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

6.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by

$$SAR = c \left(\frac{\delta T}{\delta t} \right)$$

Where: C is the specific heat capacity, δT is the temperature rise and δt is the exposure duration, or related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of tissue and E is the RMS electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

7 Tissue Simulating Liquids

7.1 Targets for tissue simulating liquid

Table 7.1: Targets for tissue simulating liquid


Frequency(MHz)	Liquid Type	Conductivity(σ)	$\pm 5\%$ Range	Permittivity(ϵ)	$\pm 5\%$ Range
750	Head	0.89	0.85~0.93	41.94	39.8~44.0
835	Head	0.90	0.86~0.95	41.5	39.4~43.6
1750	Head	1.37	1.30~1.44	40.08	38.1~42.1
1900	Head	1.40	1.33~1.47	40.0	38.0~42.0
2450	Head	1.80	1.71~1.89	39.2	37.2~41.2
2600	Head	1.96	1.86~2.06	39.01	37.1~41.0
5250	Head	4.71	4.47~4.95	35.93	34.13~ 37.73
5600	Head	5.07	4.82~5.32	35.53	33.8~37.3
5750	Head	5.22	4.96~5.48	35.36	33.59~ 37.13

7.2 Dielectric Performance


Table 7.2: Dielectric Performance of Tissue Simulating Liquid

Measurement Date (yyyy-mm-dd)	Type	Frequency	Permittivity ϵ	Drift (%)	Conductivity σ (S/m)	Drift (%)
2020-1-13	Head	750 MHz	42.5	1.34	0.89	0.00
2020-1-14	Head	835 MHz	55.24	-0.47	0.97	1.04
2020-1-15	Head	1750 MHz	40.69	-1.95	0.888	-1.33
2020-1-16	Head	1900 MHz	54.43	-1.39	0.955	-1.55
2020-1-17	Head	2450 MHz	40.2	0.30	1.354	-1.17
2020-1-18	Head	2600 MHz	53.07	-0.62	1.482	-0.54
2020-1-19	Head	5250 MHz	39.38	-1.55	1.411	0.79
2020-1-20	Head	5600 MHz	52.85	-0.84	1.496	-1.58
2020-1-21	Head	5750 MHz	39.83	1.61	1.818	1.00

Note: The liquid temperature is 22.0°C



Picture 7-1 Liquid depth in the Head Phantom (750MHz)




Picture 7-2 Liquid depth in the Head Phantom (835 MHz)



Picture 7-3 Liquid depth in the Head Phantom (1750 MHz)



Picture 7-4 Liquid depth in the Head Phantom (1900 MHz)



Picture 7-5 Liquid depth in the Head Phantom (2450MHz)



Picture 7-6 Liquid depth in the Head Phantom (2600 MHz)




Picture 7-7 Liquid depth in the Head Phantom (5GHz)

8 System verification

8.1 System Setup

In the simplified setup for system evaluation, the DUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:



Picture 8.1 System Setup for System Evaluation



Picture 8.2 Photo of Dipole Setup

8.2 System Verification

SAR system verification is required to confirm measurement accuracy, according to the tissue dielectric media, probe calibration points and other system operating parameters required for measuring the SAR of a test device. The system verification must be performed for each frequency band and within the valid range of each probe calibration point required for testing the device.

The system verification results are required that the area scan estimated 1-g SAR is within 3% of the zoom scan 1-g SAR. The details are presented in annex B.

Table 8.1: System Verification of Head

Measurement Date (yyyy-mm-dd)	Frequency	Target value (W/kg)		Measured value(W/kg)		Deviation	
		10 g Average	1 g Average	10 g Average	1 g Average	10 g Average	1 g Average
2020/1/13	750 MHz	5.57	8.57	5.44	8.72	-2.33%	1.75%
2020/1/14	835 MHz	6.29	9.70	6.24	9.8	-0.79%	1.03%
2020/1/15	1750 MHz	19.3	36.6	19.68	36.48	1.97%	-0.33%
2020/1/16	1900 MHz	20.8	39.7	20.72	40.04	-0.38%	0.86%
2020/1/17	2450 MHz	24.2	51.6	24.48	51.12	1.16%	-0.93%
2020/1/18	2600 MHz	25.1	55.8	25.16	55.64	0.24%	-0.29%
2020/1/19	5250 MHz	23.2	80.4	23.5	79.9	1.21%	-0.60%
2020-1-20	5600 MHz	24.1	84.5	24.0	84.7	-0.41%	0.26%
2020-1-21	5750 MHz	23.0	80.4	23.3	79.6	1.22%	-1.00%

9 Measurement Procedures

9.1 Tests to be performed

In order to determine the highest value of the peak spatial-average SAR of a handset, all device positions, configurations and operational modes shall be tested for each frequency band according to steps 1 to 3 below. A flowchart of the test process is shown in picture 9.1.


Step 1: The tests described in 9.2 shall be performed at the channel that is closest to the centre of the transmit frequency band (f_c) for:

- a) all device positions (cheek and tilt, for both left and right sides of the SAM phantom, as described in annex D),
- b) all configurations for each device position in a), e.g., antenna extended and retracted, and
- c) all operational modes, e.g., analogue and digital, for each device position in a) and configuration in b) in each frequency band.

If more than three frequencies need to be tested according to 11.1 (i.e., $N_c > 3$), then all frequencies, configurations and modes shall be tested for all of the above test conditions.

Step 2: For the condition providing highest peak spatial-average SAR determined in Step 1, perform all tests described in 9.2 at all other test frequencies, i.e., lowest and highest frequencies. In addition, for all other conditions (device position, configuration and operational mode) where the peak spatial-average SAR value determined in Step 1 is within 3 dB of the applicable SAR limit, it is recommended that all other test frequencies shall be tested as well.

Step 3: Examine all data to determine the highest value of the peak spatial-average SAR found in Steps 1 to 2.



Picture 9.1Block diagram of the tests to be performed

9.2 General Measurement Procedure

The area and zoom scan resolutions specified in the table below must be applied to the SAR measurements and fully documented in SAR reports to qualify for TCB approval. Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1-g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std 1528-2003. The results should be documented as part of the system validation records and may be requested to support test results when all the measurement parameters in the following table are not satisfied.

			≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: Δx_{Zoom} , Δy_{Zoom}			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{Zoom}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{Zoom}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <u>reported</u> SAR from the area scan based 1-g SAR estimation procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

9.3 WCDMA Measurement Procedures for SAR

The following procedures are applicable to WCDMA handsets operating under 3GPP Release99, Release 5 and Release 6. The default test configuration is to measure SAR with an established radio link between the DUT and a communication test set using a 12.2kbps RMC (reference measurement channel) configured in Test Loop Mode 1. SAR is selectively confirmed for other physical channel configurations (DPCCH & DPDCH_n), HSDPA and HSPA (HSUPA/HSDPA) modes according to output power, exposure conditions and device operating capabilities. Both uplink and downlink should be configured with the same RMC or AMR, when required. SAR for Release 5 HSDPA and Release 6 HSPA are measured using the applicable FRC (fixed reference channel) and E-DCH reference channel configurations. Maximum output power is verified according to applicable versions of 3GPP TS 34.121 and SAR must be measured according to these maximum output conditions. When Maximum Power Reduction (MPR) is not implemented according to Cubic Metric (CM) requirements for Release 6 HSPA, the following procedures do not apply.

For Release 5 HSDPA Data Devices:

Sub-test	β_c	β_d	β_d (SF)	β_c / β_d	β_{hs}	CM/dB
1	2/15	15/15	64	2/15	4/15	0.0
2	12/15	15/15	64	12/15	24/25	1.0
3	15/15	8/15	64	15/8	30/15	1.5
4	15/15	4/15	64	15/4	30/15	1.5

For Release 6 HSPA Data Devices

Sub-test	β_c	β_d	β_d (SF)	β_c / β_d	β_{hs}	β_{ec}	β_{ed}	β_{ed} (SF)	β_{ed} (codes)	CM (dB)	MPR (dB)	AG Index	E-TFCI
1	11/15	15/15	64	11/15	22/15	209/225	1039/225	4	1	1.5	1.5	20	75
2	6/15	15/15	64	6/15	12/15	12/15	12/15	4	1	1.5	1.5	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{ed1}:47/15$ $\beta_{ed2}:47/15$	4	2	1.5	1.5	15	92
4	2/15	15/15	64	2/15	4/15	4/15	56/75	4	1	1.5	1.5	17	71
5	15/15	15/15	64	15/15	24/15	30/15	134/15	4	1	1.5	1.5	21	81

Rel.8 DC-HSDPA (Cat 24)

SAR test exclusion for Rel.8 DC-HSDPA must satisfy the SAR test exclusion requirements of Rel.5 HSDPA. SAR test exclusion for DC-HSDPA devices is determined by power measurements according to the H-Set 12, Fixed Reference Channel (FRC) configuration in Table C.8.1.12 of 3GPP TS 34.121-1. A primary and a secondary serving HS-DSCH Cell are required to perform the power measurement and for the results to qualify for SAR test exclusion.

9.4 SAR Measurement for LTE

SAR tests for LTE are performed with a base station simulator, Rohde & Schwarz CMW500. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. All powers were measured with the CMW 500.

It is performed for conducted power and SAR based on the KDB941225 D05.

SAR is evaluated separately according to the following procedures for the different test positions in each exposure condition – head, body, body-worn accessories and other use conditions. The procedures in the following subsections are applied separately to test each LTE frequency band.

1) QPSK with 1 RB allocation

Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power among RB offsets at the upper edge, middle and lower edge of each required test channel. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required for 1 RB allocation; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel. When the reported SAR of a required test channel is > 1.45 W/kg, SAR is required for all three RB offset configurations for that required test channel.

2) QPSK with 50% RB allocation

The procedures required for 1 RB allocation in 1) are applied to measure the SAR for QPSK with 50% RB allocation.

3) QPSK with 100% RB allocation

For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation in 1) and 2) are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.

TDD test:

TDD testing is performed using guidance from FCC KDB 941225 D05 v02r05 and the SAR test guidance provided in April 2013 TCB works hop notes. TDD is tested at the highest duty factor using UL-DL configuration 0 with special subframe configuration 6 and applying the FDD LTE procedures in KDB 941225 D05 v02r05. SAR testing is performed using the extended cyclic prefix listed in 3GPP TS 36.211.




Figure 9.2: Frame structure type 2 (for 5 ms switch-point periodicity)

Table 9.1: Configuration of special subframe (lengths of DwPTS/GP/UpPTS)

Special subframe configuration	Normal cyclic prefix in downlink			Extended cyclic prefix in downlink		
	DwPTS	UpPTS		DwPTS	UpPTS	
		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
0	$6592 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$	$7680 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$
1	$19760 \cdot T_s$			$20480 \cdot T_s$		
2	$21952 \cdot T_s$			$23040 \cdot T_s$		
3	$24144 \cdot T_s$			$25600 \cdot T_s$		
4	$26336 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$	$7680 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$
5	$6592 \cdot T_s$			$20480 \cdot T_s$		
6	$19760 \cdot T_s$			$23040 \cdot T_s$		
7	$21952 \cdot T_s$			$12800 \cdot T_s$		
8	$24144 \cdot T_s$			-	-	-
9	$13168 \cdot T_s$			-	-	-

Table 9.2: Uplink-downlink configurations

Uplink-downlink configuration	Downlink-to-Uplink Switch-point periodicity	Subframe number									
		0	1	2	3	4	5	6	7	8	9
0	5 ms	D	S	U	U	U	D	S	U	U	U
1	5 ms	D	S	U	U	D	D	S	U	U	D
2	5 ms	D	S	U	D	D	D	S	U	D	D
3	10 ms	D	S	U	U	U	D	D	D	D	D
4	10 ms	D	S	U	U	D	D	D	D	D	D
5	10 ms	D	S	U	D	D	D	D	D	D	D
6	5 ms	D	S	U	U	U	D	S	U	U	D

Duty factor is calculated by:

$$\begin{aligned}
 \text{Duty factor} &= \text{uplink frame} \cdot 6 + \text{UpPTS} \cdot 2 / \text{one frame length} \\
 &= (30720 \cdot T_s \cdot 6 + 5120 \cdot T_s \cdot 2) / 307200 \cdot T_s \\
 &= 0.633
 \end{aligned}$$

According to the KDB 447498 D01, SAR should be evaluated at more than 3 frequencies for devices supporting transmit bands wider than 100MHz. Oct.2014 FCC-TCB conference notes (Dec. 2014 rev.) specifies the 5 test channels to use for 3GPP band 41 SAR evaluation.

9.5 Bluetooth & Wi-Fi Measurement Procedures for SAR

Normal network operating configurations are not suitable for measuring the SAR of 802.11 transmitters in general. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure that the results are consistent and reliable.

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in a test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters. The test frequencies should correspond to actual channel frequencies defined for domestic use. SAR for devices with switched diversity should be measured with only one antenna transmitting at a time during each SAR measurement, according to a fixed modulation and data rate. The same data pattern should be used for all measurements.

9.6 Power Drift

To control the output power stability during the SAR test, DASY4 system calculates the power drift by measuring the E-field at the same location at the beginning and at the end of the measurement for each test position. These drift values can be found in section14 labeled as: (Power Drift [dB]). This ensures that the power drift during one measurement is within 5%.

10 Area Scan Based 1-g SAR

10.1 Requirement of KDB

According to the KDB447498 D01 v05, when the implementation is based the specific polynomial fit

algorithm as presented at the 29th Bioelectromagnetics Society meeting (2007) and the estimated 1-gSAR is ≤ 1.2 W/kg, a zoom scan measurement is not required provided it is also not needed for any other purpose; for example, if the peak SAR location required for simultaneous transmission SAR test exclusion can be determined accurately by the SAR system or manually to discriminate between distinctive peaks and scattered noisy SAR distributions from area scans.

There must not be any warning or alert messages due to various measurement concerns identified by the SAR system; for example, noise in measurements, peaks too close to scan boundary, peaks are too sharp, spatial resolution and uncertainty issues etc. The SAR system verification must also demonstrate that the area scan estimated 1-g SAR is within 3% of the zoom scan 1-g SAR (See Annex B). When all the SAR results for each exposure condition in a frequency band and wireless mode are based on estimated 1-g SAR, the 1-g SAR for the highest SAR configuration must be determined by a zoom scan.

10.2 Fast SAR Algorithms

The approach is based on the area scan measurement applying a frequency dependent attenuation parameter. This attenuation parameter was empirically determined by analyzing a large number of phones. The MOTOROLA FAST SAR was developed and validated by the MOTOROLA Research Group in Ft. Lauderdale.

In the initial study, an approximation algorithm based on Linear fit was developed. The accuracy of the algorithm has been demonstrated across a broad frequency range (136-2450 MHz) and for both 1- and 10-g averaged SAR using a sample of 264 SAR measurements from 55 wireless handsets. For the sample size studied, the root-mean-squared errors of the algorithm are 1.2% and 5.8% for 1- and 10-g averaged SAR, respectively. The paper describing the algorithm in detail is expected to be published in August 2004 within the Special Issue of Transactions on MTT.

In the second step, the same research group optimized the fitting algorithm to an Polynomial fit whereby the frequency validity was extended to cover the range 30-6000MHz. Details of this study can be found in the BEMS 2007 Proceedings.

Both algorithms are implemented in DASY software.

11 Conducted Output Power

For Main antenna, there are two sets of tune-up power, Normal power and Low power, used for different use cases for PCS1900/WCDMA1700/ WCDMA1900/CDMA BC1 and LTE Band7/25/41(PC2)/41(PC3)/66. Normal power status is applied for head test and body worn test of above bands. Low power status is applied for sensor test of above bands. For other bands, Normal power status is applied for both head and body test.

11.1 GSM Measurement result

During the process of testing, the EUT was controlled via Agilent Digital Radio Communication tester (E5515C) to ensure the maximum power transmission and proper modulation. This result contains conducted output power for the EUT. In all cases, the measured peak output power should be greater and within 5% than EMI measurement.

Normal Power

Table 11.1-1: The conducted power measurement results for GSM, GPRS and EGPRS

GSM 850 Speech (GMSK)	Measured Power (dBm)			Tune up	calculation	Averaged Power (dBm)		
	251	190	128			251	190	128
1 Txslot	32.50	32.50	32.52	33.50	/	/	/	/
GSM 850 GPRS (GMSK)	Measured Power (dBm)				calculation	Averaged Power (dBm)		
	251	190	128			251	190	128
1 Txslot	32.54	32.52	32.54	33.50	-9.03	23.51	23.49	23.51
2 Txslots	31.84	31.81	31.84	33.00	-6.02	25.82	25.79	25.82
3Txslots	30.08	30.08	30.15	31.00	-4.26	25.82	25.82	25.89
4 Txslots	28.99	29.00	29.07	30.00	-3.01	25.98	25.99	26.06
GSM 850 EGPRS (GMSK)	Measured Power (dBm)				calculation	Averaged Power (dBm)		
	251	190	128			251	190	128
1 Txslot	32.50	32.50	32.52	33.50	-9.03	23.47	23.47	23.49
2 Txslots	31.81	31.79	31.81	33.00	-6.02	25.79	25.77	25.79
3Txslots	30.05	30.06	30.12	31.00	-4.26	25.79	25.80	25.86
4 Txslots	28.96	28.98	29.04	30.00	-3.01	25.95	25.97	26.03
GSM 850 EGPRS (8PSK)	Measured Power (dBm)				calculation	Averaged Power (dBm)		
	251	190	128			251	190	128
1 Txslot	26.97	26.92	26.76	28.50	-9.03	17.94	17.89	17.73
2 Txslots	25.91	25.76	25.67	27.00	-6.02	19.89	19.74	19.65
3Txslots	23.81	23.77	25.76	25.00	-4.26	19.55	19.51	21.50
4 Txslots	22.28	22.29	22.09	24.00	-3.01	19.27	19.28	19.08
PCS1900 Speech (GMSK)	Measured Power (dBm)			Tune up	calculation	Averaged Power (dBm)		
	810	661	512			810	661	512
1 Txslot	29.51	29.53	29.51	31.00	/	/	/	/
PCS1900 GPRS (GMSK)	Measured Power (dBm)				calculation	Averaged Power (dBm)		
	810	661	512			810	661	512

1 Txslot	29.54	29.53	29.51	31.00	-9.03	20.51	20.50	20.48
2 Txslots	28.83	28.87	28.89	30.00	-6.02	22.81	22.85	22.87
3Txslots	27.10	27.17	27.26	28.50	-4.26	22.84	22.91	23.00
4 Txslots	26.02	26.08	26.16	27.50	-3.01	23.01	23.07	23.15
PCS1900 EGPRS (GMSK)	Measured Power (dBm)				calculation	Averaged Power (dBm)		
	810	661	512			810	661	512
1 Txslot	29.50	29.51	29.49	31.00	-9.03	20.47	20.48	20.46
2 Txslots	28.81	28.84	28.87	30.00	-6.02	22.79	22.82	22.85
3Txslots	27.08	27.15	27.24	28.50	-4.26	22.82	22.89	22.98
4 Txslots	26.00	26.05	26.15	27.50	-3.01	22.99	23.04	23.14
PCS1900 EGPRS (8PSK)	Measured Power (dBm)				calculation	Averaged Power (dBm)		
	810	661	512			810	661	512
1 Txslot	26.15	26.12	26.19	26.50	-9.03	17.12	17.09	17.16
2 Txslots	25.11	25.07	25.15	26.00	-6.02	19.09	19.05	19.13
3Txslots	22.84	22.83	22.88	24.00	-4.26	18.58	18.57	18.62
4 Txslots	21.57	21.57	21.64	23.00	-3.01	18.56	18.56	18.63

NOTES:

1) Division Factors

To average the power, the division factor is as follows:

1TX-slot = 1 transmit time slot out of 8 time slots=> conducted power divided by (8/1) => -9.03dB

2TX-slots = 2 transmit time slots out of 8 time slots=> conducted power divided by (8/2) => -6.02dB

3TX-slots = 3 transmit time slots out of 8 time slots=> conducted power divided by (8/3) => -4.26dB

4TX-slots = 4 transmit time slots out of 8 time slots=> conducted power divided by (8/4) => -3.01dB

According to the conducted power as above, the body measurements are performed with 4Txslots for GSM850 and GSM1900.

Low Power

PCS1900 GPRS (GMSK)	Measured Power (dBm)				calculation	Averaged Power (dBm)		
	810	661	512			810	661	512
1 Txslot	27.74	27.72	27.76	29.00	-9.03	18.71	18.69	18.73
2 Txslots	25.10	25.09	25.14	26.00	-6.02	19.08	19.07	19.12
3Txslots	23.14	23.08	23.11	24.30	-4.26	18.88	18.82	18.85
4 Txslots	22.08	22.06	22.01	23.00	-3.01	19.07	19.05	19.00
PCS1900 EGPRS (GMSK)	Measured Power (dBm)				calculation	Averaged Power (dBm)		
	810	661	512			810	661	512
1 Txslot	27.73	27.73	27.74	29.00	-9.03	18.70	18.70	18.71
2 Txslots	25.09	25.09	25.12	26.00	-6.02	19.07	19.07	19.10
3Txslots	23.13	23.09	23.10	24.30	-4.26	18.87	18.83	18.84
4 Txslots	22.06	22.06	22.00	23.00	-3.01	19.05	19.05	18.99

NOTES:

1) Division Factors

To average the power, the division factor is as follows:

1TX-slot = 1 transmit time slot out of 8 time slots=> conducted power divided by (8/1) => -9.03dB

2TX-slots = 2 transmit time slots out of 8 time slots=> conducted power divided by (8/2) => -6.02dB

3TX-slots = 3 transmit time slots out of 8 time slots=> conducted power divided by (8/3) => -4.26dB

4TX-slots = 4 transmit time slots out of 8 time slots=> conducted power divided by (8/4) => -3.01dB

According to the conducted power as above, the body measurements are performed with 2Txslots for GSM1900.

11.2 WCDMA Measurement result

Normal power

Table 11.2-1: The conducted Power for WCDMA

Item	band	FDDV result			
	ARFCN	4233 (846.6MHz)	4182 (836.4MHz)	4132 (826.4MHz)	Tune up
WCDMA	1	23.41	23.45	23.45	25.00
HSUPA	1	20.32	20.34	20.36	21.50
	2	20.35	20.36	20.37	21.50
	3	21.3	21.31	21.35	22.50
	4	19.82	19.85	19.85	21.00
	5	21.29	21.30	21.34	22.50
DC-HSDPA	1	21.47	21.52	21.48	22.50
	2	21.31	21.40	21.36	22.50
	3	20.98	21.01	20.90	22.50
	4	20.93	20.97	20.91	22.50
Item	band	FDDIV result			
	ARFCN	1513 (1752.6MHz)	1412 (1732.4MHz)	1312 (1712.4MHz)	
WCDMA	1	23.04	23.02	23.05	24.50
HSUPA	1	19.96	19.93	19.98	21.00
	2	19.98	19.94	19.99	21.00
	3	20.96	20.93	20.97	22.00
	4	19.45	19.42	19.48	20.50
	5	20.93	20.94	20.99	22.00
DC-HSDPA	1	21.11	21.06	21.18	22.00
	2	20.92	21.02	21.11	22.00
	3	20.61	20.57	20.65	21.50
	4	20.54	20.53	20.62	21.50
Item	band	FDDII result			
	ARFCN	9538 (1907.6MHz)	9400 (1880MHz)	9262 (1852.4MHz)	Tune up
WCDMA	1	22.95	22.94	22.97	24.50
HSUPA	1	19.9	19.85	19.92	21.00
	2	19.87	19.86	19.89	21.00

	3	20.87	20.84	20.88	22.00
	4	19.39	19.35	19.41	20.50
	5	20.84	20.82	20.91	22.00
DC-HSDPA	1	20.99	21.01	21.02	22.00
	2	20.92	20.98	21.01	22.00
	3	20.46	20.49	20.52	21.50
	4	20.45	20.46	20.48	21.50

Low power

Table 11.2-2: The conducted Power for WCDMA

Item	band	FDDIV result			
	ARFCN	1513 (1752.6MHz)	1412(1732.4MHz)	1312 (1712.4MHz)	Tune up
WCDMA	1	18.48	18.58	18.51	20.00
HSUPA	1	15.49	15.45	15.51	17.00
	2	15.48	15.47	15.54	17.00
	3	16.43	16.40	16.48	18.00
	4	14.94	14.96	14.99	16.50
	5	16.39	16.36	16.42	18.00
DC-HSDPA	1	17.45	17.41	17.47	18.00
	2	17.42	17.39	17.46	18.00
	3	16.94	16.92	16.99	18.00
	4	16.91	16.91	16.98	18.00
Item	band	FDDII result			
	ARFCN	9538 (1907.6MHz)	9400 (1880MHz)	9262 (1852.4MHz)	Tune up
WCDMA	1	18.67	18.64	18.66	20.00
HSUPA	1	15.69	15.65	15.66	17.50
	2	15.67	15.61	15.62	17.50
	3	16.62	16.57	16.58	18.00
	4	15.13	15.12	15.10	17.00
	5	16.6	16.52	16.53	17.50
DC-HSDPA	1	17.58	17.59	17.56	18.00
	2	17.51	17.50	17.55	18.00
	3	17.07	17.08	17.06	18.00
	4	17.05	17.07	17.04	18.00

11.3 CDMA Measurement result

Normal power

Table 11.3-1: The conducted Power for CDMA

Mode	CDMA BC0			
	777 (848.31MHz)	384 (836.52MHz)	1013 (824.7MHz)	Tune up
SO55/RC3	23.92	24.02	23.90	25.00
SO55/RC1	23.91	24.01	23.89	25.00
SO32/RC3(FCH only)	23.84	23.95	23.81	25.00
SO32/RC3(FCH+SCH _n)	23.81	23.92	23.76	25.00
EVDO Rev.0	24.36	24.46	24.14	25.00
EVDO Rev.A	24.24	24.47	24.15	25.00
Mode	CDMA BC1			
	1175 (1908.75MHz)	600 (1880MHz)	25 (1851.25MHz)	Tune up
SO55/RC3	23.95	23.97	24.05	25.00
SO55/RC1	23.93	23.96	24.03	25.00
SO32/RC3(FCH only)	23.86	23.84	23.96	25.00
SO32/RC3(FCH+SCH _n)	23.79	23.80	23.91	25.00
EVDO Rev.0	24.01	23.96	23.90	25.00
EVDO Rev.A	24.21	24.02	24.00	25.00
Mode	CDMA BC10			
	684 (823.1MHz)	580 (820.5MHz)	476(817.9MHz)	Tune up
SO55/RC3	24.39	24.45	24.34	25.00
SO55/RC1	24.37	24.44	24.33	25.00
SO32/RC3(FCH only)	24.21	24.40	24.30	25.00
SO32/RC3(FCH+SCH _n)	24.13	24.28	24.19	25.00
EVDO Rev.0	24.22	24.25	24.25	25.00
EVDO Rev.A	24.21	24.22	24.24	25.00

Low power

Table 11.3-1: The conducted Power for CDMA

Mode	CDMA BC1			
	1175 (1908.75MHz)	600 (1880MHz)	25 (1851.25MHz)	Tune up
SO55/RC3	17.39	17.41	17.52	18.00
SO55/RC1	17.15	17.18	17.28	18.00
SO32/RC3(FCH only)	17.10	17.16	17.22	18.00
SO32/RC3(FCH+SCH _n)	17.06	17.14	17.20	18.00
EVDO Rev.0	17.02	17.05	17.12	18.00
EVDO Rev.A	17.00	17.09	17.22	18.00

11.3 LTE Measurement result

Table 13.3-1: Maximum Power Reduction (MPR) for LTE

Modulation	Channel bandwidth / Transmission bandwidth configuration [RB]						MPR (dB)
	1.4 MHz	3 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	1
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	2

Table 13.3-2: The tune up for LTE – Normal Power

Band	Tune up
LTE Band 7	24.5
LTE Band 12	24
LTE Band 13	24
LTE Band 25	24
LTE Band 26	24
LTE Band 41(PC3)	24
LTE Band 41(PC2)	27
LTE Band 66	24
LTE Band 71	24.5

Table 13.3-3: The tune up for LTE – Low Power

Band	Tune up
LTE Band 7	21
LTE Band 25	20
LTE Band 41(PC3)	22
LTE Band 41(PC2)	24.5
LTE Band 66	19

Normal power

Table 11.3-4: The conducted Power for LTE

Band 7					
Bandwidth (MHz)	RB allocation	Frequency (MHz)	QPSK	16QAM	64QAM
	RB offset (Start RB)		Actual output power (dBm)	Actual output power (dBm)	Actual output power (dBm)
5 MHz	1RB High (24)	2567.5	22.68	21.51	20.82
		2535	22.72	21.79	21.10
		2502.5	22.69	22.12	21.43
	1RB Middle (12)	2567.5	22.93	21.69	21.00
		2535	23.01	22.03	21.34
		2502.5	22.94	22.38	21.69
	1RB Low (0)	2567.5	22.65	21.61	20.92
		2535	22.73	21.80	21.11
		2502.5	22.66	22.11	21.42
	12RB High (13)	2567.5	21.73	20.75	20.06
		2535	21.73	20.75	20.06
		2502.5	21.78	20.91	20.22
	12RB Middle (6)	2567.5	21.78	20.80	20.11
		2535	21.82	20.87	20.18
		2502.5	21.86	20.95	20.26
	12RB Low (0)	2567.5	21.76	20.78	20.09
		2535	21.75	20.81	20.12
		2502.5	21.75	20.86	20.17
	25RB (0)	2567.5	21.72	20.70	20.01
		2535	21.75	20.80	20.11
		2502.5	21.80	20.83	20.14
10 MHz	1RB High (49)	2565	22.67	21.67	20.98
		2535	22.70	21.67	20.98
		2505	22.78	22.09	21.40
	1RB Middle (24)	2565	22.81	21.77	21.08
		2535	22.80	21.78	21.09
		2505	22.95	22.25	21.56
	1RB Low (0)	2565	22.65	21.64	20.95
		2535	22.71	21.61	20.92
		2505	22.78	22.04	21.35
	25RB High (25)	2565	21.73	20.85	20.16
		2535	21.82	20.87	20.18
		2505	21.84	20.87	20.18
	25RB Middle (12)	2565	21.80	20.89	20.20
		2535	21.85	20.90	20.21
		2505	21.89	20.94	20.25
	25RB Low (0)	2565	21.81	20.88	20.19
		2535	21.85	20.86	20.17
		2505	21.85	20.88	20.19
	50RB	2565	21.79	20.86	20.17

	(0)	2535	21.84	20.86	20.17
		2505	21.86	20.89	20.20
15 MHz	1RB High (74)	2562.5	22.69	21.90	21.21
		2535	22.68	21.57	20.88
		2507.5	22.68	22.01	21.32
	1RB Middle (37)	2562.5	22.79	22.14	21.45
		2535	22.79	21.66	20.97
		2507.5	22.80	22.10	21.41
	1RB Low (0)	2562.5	22.67	22.01	21.32
		2535	22.69	21.58	20.89
		2507.5	22.70	21.98	21.29
	36RB High (38)	2562.5	21.85	20.70	20.01
		2535	21.83	20.77	20.08
		2507.5	21.86	20.85	20.16
	36RB Middle (19)	2562.5	21.84	20.78	20.09
		2535	21.89	20.80	20.11
		2507.5	21.85	20.84	20.15
	36RB Low (0)	2562.5	21.80	20.71	20.02
		2535	21.80	20.80	20.11
		2507.5	21.83	20.79	20.10
	75RB (0)	2562.5	21.83	20.78	20.09
		2535	21.87	20.81	20.12
		2507.5	21.88	20.81	20.12
20 MHz	1RB High (99)	2560	22.75	22.07	21.38
		2535	22.76	22.15	21.46
		2510	22.73	22.24	21.55
	1RB Middle (50)	2560	23.04	22.40	21.71
		2535	23.31	22.41	21.72
		2510	23.06	22.54	21.85
	1RB Low (0)	2560	22.75	22.18	21.49
		2535	22.75	22.09	21.40
		2510	22.76	22.21	21.52
	50RB High (50)	2560	21.77	20.82	20.13
		2535	21.87	20.82	20.13
		2510	21.89	20.94	20.25
	50RB Middle (25)	2560	21.93	20.96	20.27
		2535	21.97	20.96	20.27
		2510	21.90	20.96	20.27
	50RB Low (0)	2560	21.87	20.89	20.20
		2535	21.91	20.96	20.27
		2510	21.86	20.92	20.23
	100RB (0)	2560	21.82	20.85	20.16
		2535	21.90	20.93	20.24
		2510	21.90	20.92	20.23

Band 12					
Bandwidth (MHz)	RB allocation	Frequency (MHz)	QPSK	16QAM	64QAM
	RB offset (Start RB)		Actual output power (dBm)	Actual output power (dBm)	Actual output power (dBm)
1.4 MHz	1RB High (5)	715.3	22.11	21.22	20.37
		707.5	22.10	21.25	20.40
		699.7	22.17	21.53	20.68
	1RB Middle (3)	715.3	22.27	21.38	20.53
		707.5	22.30	21.44	20.59
		699.7	22.35	21.80	20.95
	1RB Low (0)	715.3	22.03	21.23	20.38
		707.5	22.13	21.25	20.40
		699.7	22.15	21.50	20.65
	3RB High (3)	715.3	22.29	21.47	20.62
		707.5	22.22	21.28	20.43
		699.7	22.31	21.44	20.59
	3RB Middle (1)	715.3	22.32	21.51	20.66
		707.5	22.30	21.34	20.49
		699.7	22.38	21.46	20.61
	3RB Low (0)	715.3	22.27	21.45	20.60
		707.5	22.23	21.30	20.45
		699.7	22.31	21.45	20.60
	6RB (0)	715.3	21.19	20.40	19.55
		707.5	21.15	20.36	19.51
		699.7	21.15	20.12	19.27
3 MHz	1RB High (14)	714.5	22.10	21.17	20.32
		707.5	22.07	21.07	20.22
		700.5	22.22	21.55	20.70
	1RB Middle (7)	714.5	22.26	21.37	20.52
		707.5	22.22	21.23	20.38
		700.5	22.39	21.75	20.90
	1RB Low (0)	714.5	22.11	21.21	20.36
		707.5	22.08	21.09	20.24
		700.5	22.18	21.55	20.70
	8RB High (7)	714.5	21.14	20.22	19.37
		707.5	21.11	20.26	19.41
		700.5	21.16	20.29	19.44
	8RB Middle (4)	714.5	21.18	20.27	19.42
		707.5	21.15	20.31	19.46
		700.5	21.24	20.36	19.51
	8RB Low (0)	714.5	21.17	20.22	19.37
		707.5	21.12	20.30	19.45
		700.5	21.15	20.26	19.41
	15RB (0)	714.5	21.19	20.14	19.29
		707.5	21.16	20.22	19.37

		700.5	21.18	20.23	19.38
5 MHz	1RB High (24)	713.5	22.62	21.24	20.39
		707.5	22.07	21.58	20.73
		701.5	22.08	21.20	20.35
		701.5	22.08	21.20	20.35
	1RB Middle (12)	713.5	22.61	21.52	20.67
		707.5	22.31	21.84	20.99
		701.5	22.40	21.47	20.62
	1RB Low (0)	713.5	22.06	21.25	20.40
		707.5	22.04	21.61	20.76
		701.5	22.11	21.19	20.34
	12RB High (13)	713.5	21.06	20.17	19.32
		707.5	21.14	20.34	19.49
		701.5	21.15	20.24	19.39
	12RB Middle (6)	713.5	21.21	20.33	19.48
		707.5	21.17	20.35	19.50
		701.5	21.25	20.29	19.44
	12RB Low (0)	713.5	21.19	20.28	19.43
		707.5	21.19	20.35	19.50
		701.5	21.16	20.21	19.36
	25RB (0)	713.5	21.14	20.19	19.34
		707.5	21.17	20.27	19.42
		701.5	21.18	20.14	19.29
10 MHz	1RB High (49)	711	22.60	21.61	20.76
		707.5	22.65	21.94	21.09
		704	22.54	21.57	20.72
	1RB Middle (24)	711	22.65	21.68	20.83
		707.5	22.74	22.08	21.23
		704	22.68	21.71	20.86
	1RB Low (0)	711	22.53	21.53	20.68
		707.5	22.59	21.96	21.11
		704	22.56	21.59	20.74
	25RB High (25)	711	21.61	20.66	19.81
		707.5	21.67	20.76	19.91
		704	21.62	20.70	19.85
	25RB Middle (12)	711	21.70	20.74	19.89
		707.5	21.71	20.77	19.92
		704	21.74	20.79	19.94
	25RB Low (0)	711	21.69	20.74	19.89
		707.5	21.72	20.74	19.89
		704	21.66	20.75	19.90
	50RB (0)	711	21.63	20.67	19.82
		707.5	21.70	20.73	19.88
		704	21.67	20.70	19.85

Band 13					
Bandwidth (MHz)	RB allocation	Frequency (MHz)	QPSK	16QAM	64QAM
	RB offset (Start RB)		Actual output power (dBm)	Actual output power (dBm)	Actual output power (dBm)
5 MHz	1RB High (24)	784.4	22.38	21.95	21.48
		782	22.42	21.49	21.02
		799.5	22.44	21.53	21.06
	1RB Middle (12)	784.4	22.59	22.13	21.66
		782	22.65	21.70	21.23
		799.5	22.73	21.80	21.33
	1RB Low (0)	784.4	22.35	21.88	21.41
		782	22.42	21.51	21.04
		799.5	22.47	21.51	21.04
	12RB High (13)	784.4	21.41	20.58	20.11
		782	21.47	20.49	20.02
		799.5	21.52	20.62	20.15
	12RB Middle (6)	784.4	21.53	20.67	20.20
		782	21.52	20.57	20.10
		799.5	21.55	20.64	20.17
	12RB Low (0)	784.4	21.52	20.66	20.19
		782	21.44	20.48	20.01
		799.5	21.41	20.49	20.02
	25RB (0)	784.4	21.49	20.57	20.10
		782	21.45	20.38	20.01
		799.5	21.52	20.55	20.08
10 MHz	1RB High (49)	782	22.91	22.04	21.57
	1RB Middle (24)	782	23.03	22.05	21.58
	1RB Low (0)	782	22.95	21.89	21.42
	25RB High (25)	782	21.97	21.05	20.58
	25RB Middle (12)	782	22.04	21.09	20.62
	25RB Low (0)	782	21.96	21.02	20.55
	50RB (0)	782	21.92	20.98	20.51

Band 25					
Bandwidth (MHz)	RB allocation	Frequency (MHz)	QPSK	16QAM	64QAM
	RB offset (Start RB)		Actual output power (dBm)	Actual output power (dBm)	Actual output power (dBm)
1.4 MHz	1RB High (5)	1914.3	22.87	21.30	20.66
		1882.5	22.80	21.73	21.09
		1850.7	22.40	21.79	21.15
	1RB Middle (3)	1914.3	23.07	21.44	20.80
		1882.5	22.84	21.82	21.18
		1850.7	22.53	21.97	21.33
	1RB Low (0)	1914.3	22.90	21.25	20.61
		1882.5	22.38	21.54	20.90
		1850.7	22.41	21.75	21.11
	3RB High (3)	1914.3	22.87	21.44	20.80
		1882.5	22.44	21.53	20.89
		1850.7	22.52	21.70	21.06
	3RB Middle (1)	1914.3	22.92	21.53	20.89
		1882.5	22.51	21.57	20.93
		1850.7	22.57	21.70	21.06
	3RB Low (0)	1914.3	22.89	21.60	20.96
		1882.5	22.50	21.58	20.94
		1850.7	22.53	21.66	21.02
	6RB (0)	1914.3	22.09	20.74	20.10
		1882.5	21.35	20.63	19.99
		1850.7	21.47	20.40	19.76
3 MHz	1RB High (14)	1913.5	22.96	21.32	20.68
		1882.5	22.88	21.83	21.19
		1851.5	22.63	22.12	21.48
	1RB Middle (7)	1913.5	23.03	21.52	20.88
		1882.5	23.00	21.97	21.33
		1851.5	22.68	22.14	21.50
	1RB Low (0)	1913.5	22.95	21.49	20.85
		1882.5	22.84	21.61	20.97
		1851.5	22.49	22.02	21.38
	8RB High (7)	1913.5	21.94	20.75	20.11
		1882.5	21.63	20.80	20.16
		1851.5	21.45	20.91	20.27
	8RB Middle (4)	1913.5	21.99	21.02	20.38
		1882.5	21.61	21.05	20.41
		1851.5	21.46	21.08	20.44
	8RB Low (0)	1913.5	21.97	21.01	20.37
		1882.5	21.60	20.93	20.29
		1851.5	21.48	21.02	20.38

	15RB (0)	1913.5	21.89	20.89	20.25
		1882.5	21.49	20.85	20.21
		1851.5	21.48	20.90	20.26
5 MHz	1RB High (24)	1912.5	22.87	21.49	20.85
		1882.5	22.89	22.00	21.36
		1852.5	22.74	22.22	21.58
	1RB Middle (12)	1912.5	23.08	21.64	21.00
		1882.5	23.12	22.26	21.62
		1852.5	22.91	22.44	21.80
	1RB Low (0)	1912.5	22.84	21.74	21.10
		1882.5	22.90	21.84	21.20
		1852.5	22.40	22.06	21.42
	12RB High (13)	1912.5	21.83	20.82	20.18
		1882.5	21.91	20.78	20.14
		1852.5	21.48	20.86	20.22
	12RB Middle (6)	1912.5	21.94	21.01	20.37
		1882.5	21.90	21.03	20.39
		1852.5	21.67	21.14	20.50
	12RB Low (0)	1912.5	21.88	20.97	20.33
		1882.5	21.93	20.84	20.20
		1852.5	21.68	21.07	20.43
	25RB (0)	1912.5	21.82	20.84	20.20
		1882.5	21.73	20.98	20.34
		1852.5	21.57	20.92	20.28
10 MHz	1RB High (49)	1910	22.86	21.58	20.94
		1882.5	22.81	21.80	21.16
		1855	22.85	22.22	21.58
	1RB Middle (24)	1910	23.05	22.00	21.36
		1882.5	23.00	21.93	21.29
		1855	23.04	22.41	21.77
	1RB Low (0)	1910	22.86	21.92	21.28
		1882.5	22.81	21.84	21.20
		1855	22.86	22.17	21.53
	25RB High (25)	1910	21.84	20.99	20.35
		1882.5	21.99	21.11	20.47
		1855	21.95	21.09	20.45
	25RB Middle (12)	1910	21.94	21.10	20.46
		1882.5	21.98	21.10	20.46
		1855	21.93	21.06	20.42
	25RB Low (0)	1910	21.96	21.15	20.51
		1882.5	21.93	21.09	20.45
		1855	21.93	21.08	20.44
	50RB (0)	1910	21.90	21.03	20.39
		1882.5	22.01	21.08	20.44
		1855	21.94	21.03	20.39
15 MHz	1RB High (74)	1907.5	22.94	22.04	21.40
		1882.5	22.79	21.77	21.13
		1857.5	22.88	22.19	21.55

	1RB Middle (37)	1907.5	22.97	22.33	21.69
		1882.5	22.89	21.92	21.28
		1857.5	22.92	22.30	21.66
	1RB Low (0)	1907.5	22.89	22.25	21.61
		1882.5	22.78	21.82	21.18
		1857.5	22.87	22.19	21.55
	36RB High (38)	1907.5	22.02	21.00	20.36
		1882.5	21.95	21.00	20.36
		1857.5	21.97	21.05	20.41
	36RB Middle (19)	1907.5	22.08	21.03	20.39
		1882.5	21.98	21.00	20.36
		1857.5	21.93	21.02	20.38
	36RB Low (0)	1907.5	22.05	21.03	20.39
		1882.5	22.01	21.03	20.39
		1857.5	21.94	21.02	20.38
	75RB (0)	1907.5	22.10	21.09	20.45
		1882.5	21.99	21.06	20.42
		1857.5	21.92	21.04	20.40
20 MHz	1RB High (99)	1905	22.76	21.99	21.35
		1882.5	22.69	22.13	21.49
		1860	22.72	22.27	21.63
	1RB Middle (50)	1905	23.04	22.45	21.81
		1882.5	23.04	22.44	21.80
		1860	22.98	22.52	21.88
	1RB Low (0)	1905	22.71	22.20	21.56
		1882.5	22.70	22.14	21.50
		1860	22.72	22.23	21.59
	50RB High (50)	1905	21.88	20.96	20.32
		1882.5	21.93	21.01	20.37
		1860	21.88	21.01	20.37
	50RB Middle (25)	1905	21.94	21.02	20.38
		1882.5	21.93	20.98	20.34
		1860	21.90	21.00	20.36
	50RB Low (0)	1905	21.94	21.04	20.40
		1882.5	21.96	20.97	20.33
		1860	21.79	20.95	20.31
	100RB (0)	1905	21.89	20.99	20.35
		1882.5	21.96	21.01	20.37
		1860	21.84	20.98	20.34

Band 26					
Bandwidth (MHz)	RB allocation	Frequency (MHz)	QPSK	16QAM	64QAM
	RB offset (Start RB)		Actual output power (dBm)	Actual output power (dBm)	Actual output power (dBm)
1.4 MHz	1RB High (5)	848.3	22.89	21.91	20.97
		831.5	23.04	21.95	21.01
		814.7	23.01	22.37	21.43
	1RB Middle (3)	848.3	23.13	22.00	21.06
		831.5	23.26	22.12	21.18
		814.7	23.19	22.44	21.50
	1RB Low (0)	848.3	22.94	21.90	20.96
		831.5	23.05	21.95	21.01
		814.7	23.01	22.36	21.42
	3RB High (3)	848.3	23.05	22.17	21.23
		831.5	23.01	21.96	21.02
		814.7	23.09	22.26	21.32
	3RB Middle (1)	848.3	23.10	22.19	21.25
		831.5	23.07	22.02	21.08
		814.7	23.12	22.31	21.37
	3RB Low (0)	848.3	23.00	22.16	21.22
		831.5	23.03	21.99	21.05
		814.7	22.88	22.25	21.31
	6RB (0)	848.3	22.08	21.20	20.26
		831.5	22.05	21.16	20.22
		814.7	21.90	20.97	20.03
3 MHz	1RB High (14)	847.5	22.93	22.28	21.34
		831.5	23.09	21.87	20.93
		815.5	23.12	21.87	20.93
	1RB Middle (7)	847.5	23.09	22.49	21.55
		831.5	23.18	22.08	21.14
		815.5	23.24	22.06	21.12
	1RB Low (0)	847.5	22.97	22.32	21.38
		831.5	22.97	21.98	21.04
		815.5	22.99	21.96	21.02
	8RB High (7)	847.5	21.99	21.05	20.11
		831.5	22.05	21.06	20.12
		815.5	22.06	21.05	20.11
	8RB Middle (4)	847.5	22.06	21.13	20.19
		831.5	22.05	21.09	20.15
		815.5	22.07	21.11	20.17
	8RB Low (0)	847.5	22.04	21.12	20.18
		831.5	22.03	21.04	20.10

	15RB (0)	815.5	22.04	21.05	20.11
		847.5	22.02	21.06	20.12
		831.5	22.03	20.98	20.04
		815.5	22.04	20.98	20.04
5 MHz	1RB High (24)	846.5	22.92	21.97	21.03
		831.5	23.03	21.98	21.04
		816.5	22.92	22.40	21.46
	1RB Middle (12)	846.5	23.20	22.24	21.30
		831.5	23.26	22.26	21.32
		816.5	23.16	22.65	21.71
	1RB Low (0)	846.5	22.92	21.99	21.05
		831.5	22.94	21.99	21.05
		816.5	22.91	22.40	21.46
	12RB High (13)	846.5	21.91	20.98	20.04
		831.5	21.99	21.00	20.06
		816.5	22.06	21.17	20.23
	12RB Middle (6)	846.5	22.04	21.11	20.17
		831.5	22.02	21.08	20.14
		816.5	22.05	21.20	20.26
	12RB Low (0)	846.5	22.04	21.08	20.14
		831.5	21.97	21.04	20.10
		816.5	22.01	21.13	20.19
	25RB (0)	846.5	22.00	20.95	20.01
		831.5	21.97	21.02	20.08
		816.5	22.01	21.15	20.21
10 MHz	1RB High (49)	844	22.99	21.86	20.92
		831.5	23.01	22.21	21.27
		820	22.95	22.01	21.07
	1RB Middle (24)	844	23.05	22.00	21.06
		831.5	23.14	22.35	21.41
		820	23.08	22.07	21.13
	1RB Low (0)	844	22.95	21.87	20.93
		831.5	22.98	22.35	21.41
		820	22.97	21.96	21.02
	25RB High (25)	844	21.90	20.94	20.00
		831.5	22.01	21.05	20.11
		820	21.99	21.11	20.17
	25RB Middle (12)	844	22.04	21.04	20.10
		831.5	22.00	21.09	20.15
		820	22.02	21.16	20.22
	25RB Low (0)	844	22.08	21.12	20.18
		831.5	22.10	21.14	20.20
		820	21.94	21.11	20.17
	50RB (0)	844	21.99	20.99	20.05
		831.5	22.05	21.10	20.16
		820	22.03	21.07	20.13
15 MHz	1RB High (74)	841.5	22.93	22.18	21.24
		831.5	22.95	22.18	21.24

		822.5	22.89	21.74	20.80
	1RB Middle (37)	1907.5	23.05	22.31	21.37
		1882.5	22.99	22.23	21.29
		1857.5	23.01	21.91	20.97
	1RB Low (0)	1907.5	22.96	22.14	21.20
		1882.5	22.91	22.30	21.36
		1857.5	22.95	21.78	20.84
	36RB High (38)	1907.5	21.97	20.97	20.03
		1882.5	22.10	20.96	20.02
		1857.5	22.03	20.94	20.00
	36RB Middle (19)	1907.5	22.03	21.02	20.08
		1882.5	22.08	20.97	20.03
		1857.5	22.04	21.00	20.06
	36RB Low (0)	1907.5	22.04	21.00	20.06
		1882.5	22.11	21.03	20.09
		1857.5	22.03	20.95	20.01
	75RB (0)	1907.5	22.00	20.96	20.02
		1882.5	22.13	21.04	20.10
		1857.5	22.01	21.00	20.06

Band 41 – PC2					
Bandwidth (MHz)	RB allocation	Frequency (MHz)	QPSK	16QAM	64QAM
	RB offset (Start RB)		Actual output power (dBm)	Actual output power (dBm)	Actual output power (dBm)
5 MHz	1RB High (24)	2687.5	25.63	24.90	23.63
		2640.3	25.78	25.05	23.78
		2593	25.76	24.88	23.61
		2545.8	25.77	24.99	23.72
		2498.5	25.74	25.03	23.76
	1RB Middle (12)	2687.5	26.01	25.20	23.93
		2640.3	26.11	25.38	24.11
		2593	26.12	25.22	23.95
		2545.8	26.11	25.29	24.02
		2498.5	26.08	25.32	24.05
	1RB Low (0)	2687.5	25.70	24.89	23.62
		2640.3	25.78	25.06	23.79
		2593	25.80	24.92	23.65
		2545.8	25.77	24.99	23.72
		2498.5	25.72	25.00	23.73
	12RB High (13)	2687.5	24.75	23.71	22.44
		2640.3	24.89	23.94	22.67
		2593	24.85	23.82	22.55
		2545.8	24.85	23.79	22.52
		2498.5	24.77	23.80	22.53
	12RB Middle (6)	2687.5	24.81	23.76	22.49
		2640.3	24.91	23.97	22.70
		2593	24.89	23.87	22.60
		2545.8	24.91	23.81	22.54
		2498.5	24.88	23.87	22.60
	12RB Low (0)	2687.5	24.79	23.73	22.46
		2640.3	24.82	23.91	22.64
		2593	24.89	23.84	22.57
		2545.8	24.86	23.79	22.52
		2498.5	24.81	23.84	22.57
	25RB (0)	2687.5	24.76	23.78	22.51
		2640.3	24.87	23.87	22.60
		2593	24.85	23.80	22.53
		2545.8	24.84	23.85	22.58
		2498.5	24.78	23.82	22.55
10 MHz	1RB	2685	25.75	25.10	23.83

	High (49)	2639	25.81	25.16	23.89
		2593	25.94	25.04	23.77
		2547	25.88	25.18	23.91
		2501	25.79	25.12	23.85
	1RB Middle (24)	2685	25.84	25.17	23.90
		2639	25.89	25.20	23.93
		2593	26.00	25.07	23.80
		2547	25.94	25.26	23.99
	1RB Low (0)	2501	25.87	25.21	23.94
		2685	25.73	25.05	23.78
		2639	25.82	25.15	23.88
		2593	25.92	25.03	23.76
	25RB High (25)	2547	25.86	25.15	23.88
		2501	25.73	25.08	23.81
		2685	24.77	23.78	22.51
		2639	24.90	23.92	22.65
	25RB Middle (12)	2593	24.92	23.89	22.62
		2547	24.92	23.89	22.62
		2501	24.81	23.81	22.54
		2685	24.79	23.83	22.56
	25RB Low (0)	2639	24.90	23.93	22.66
		2593	24.86	23.85	22.58
		2547	24.88	23.84	22.57
		2501	24.82	23.80	22.53
	50RB (0)	2685	24.82	23.79	22.52
		2639	24.90	23.91	22.64
		2593	24.89	23.87	22.60
		2547	24.90	23.81	22.54
	15 MHz	2501	24.86	23.88	22.61
	1RB High (74)	2685	24.76	23.77	22.50
		2639	24.89	23.92	22.65
		2593	24.88	23.85	22.58
	1RB Middle	2547	24.86	23.86	22.59
		2501	24.79	23.84	22.57
		2682.5	25.69	25.04	23.77
		2637.8	25.71	25.03	23.76
	1RB High (74)	2593	25.82	24.91	23.64
		2548.3	25.80	25.12	23.85
		2503.5	25.70	25.00	23.73
		2682.5	25.77	25.13	23.86
	1RB Middle	2637.8	25.85	25.13	23.86

	(37)	2593	25.96	25.04	23.77
		2548.3	25.94	25.22	23.95
		2503.5	25.84	25.10	23.83
	1RB Low (0)	2682.5	25.72	25.02	23.75
		2637.8	25.73	25.02	23.75
		2593	25.91	24.97	23.70
		2548.3	25.83	25.12	23.85
		2503.5	25.67	24.99	23.72
	36RB High (38)	2682.5	24.82	23.76	22.49
		2637.8	24.99	23.92	22.65
		2593	24.97	23.84	22.57
		2548.3	24.96	23.83	22.56
		2503.5	24.90	23.80	22.53
	36RB Middle (19)	2682.5	24.89	23.79	22.52
		2637.8	25.04	23.94	22.67
		2593	24.96	23.83	22.56
		2548.3	24.99	23.87	22.60
		2503.5	24.93	23.87	22.60
	36RB Low (0)	2682.5	24.83	23.74	22.47
		2637.8	25.02	23.87	22.60
		2593	24.97	23.83	22.56
		2548.3	24.94	23.82	22.55
		2503.5	24.91	23.84	22.57
	75RB (0)	2682.5	24.87	23.80	22.53
		2637.8	24.98	23.92	22.65
		2593	24.95	23.88	22.61
		2548.3	24.94	23.87	22.60
		2503.5	24.90	23.83	22.56
20 MHz	1RB High (99)	2680	25.64	24.99	23.72
		2636.5	25.78	24.93	23.66
		2593	25.83	24.82	23.55
		2549.5	25.73	25.04	23.77
		2506	25.80	24.94	23.67
	1RB Middle (50)	2680	26.00	25.33	24.06
		2636.5	26.17	25.34	24.07
		2593	26.21	25.17	23.90
		2549.5	26.12	25.40	24.13
		2506	26.14	25.29	24.02
	1RB Low (0)	2680	25.62	24.98	23.71
		2636.5	25.79	24.94	23.67
		2593	25.85	24.84	23.57

		2549.5	25.73	25.03	23.76
		2506	25.72	24.89	23.62
	50RB High (50)	2680	24.69	23.74	22.47
		2636.5	24.81	23.82	22.55
		2593	24.82	23.84	22.57
		2549.5	24.83	23.88	22.61
		2506	24.77	23.72	22.45
	50RB Middle (25)	2680	24.76	23.84	22.57
		2636.5	24.90	23.89	22.62
		2593	24.84	23.86	22.59
		2549.5	24.85	23.87	22.60
		2506	24.84	23.79	22.52
	50RB Low (0)	2680	24.70	23.78	22.51
		2636.5	24.82	23.84	22.57
		2593	24.80	23.81	22.54
		2549.5	24.76	23.79	22.52
		2506	24.82	23.78	22.51
	100RB (0)	2680	24.71	23.74	22.47
		2636.5	24.83	23.84	22.57
		2593	24.80	23.81	22.54
		2549.5	24.79	23.78	22.51
		2506	24.79	23.77	22.50

Band 41 – PC3					
Bandwidth (MHz)	RB allocation	Frequency (MHz)	QPSK	16QAM	64QAM
	RB offset (Start RB)		Actual output power (dBm)	Actual output power (dBm)	Actual output power (dBm)
5 MHz	1RB High (24)	2687.5	22.27	21.37	20.20
		2640.3	22.43	21.64	20.47
		2593	22.56	21.34	20.17
		2545.8	22.47	21.43	20.26
		2498.5	22.42	21.49	20.32
	1RB Middle (12)	2687.5	22.34	21.41	20.24
		2640.3	22.43	21.60	20.43
		2593	22.55	21.41	20.24
		2545.8	22.49	21.46	20.29
		2498.5	22.41	21.56	20.39
	1RB Low (0)	2687.5	22.31	21.39	20.22
		2640.3	22.38	21.63	20.46
		2593	22.50	21.41	20.24
		2545.8	22.42	21.41	20.24
		2498.5	22.38	21.45	20.28
	12RB High (13)	2687.5	21.50	20.45	19.28
		2640.3	21.58	20.60	19.43
		2593	21.56	20.56	19.39
		2545.8	21.58	20.44	19.27
		2498.5	21.44	20.42	19.25
	12RB Middle (6)	2687.5	21.64	20.55	19.11
		2640.3	21.70	20.72	19.55
		2593	21.65	20.65	19.48
		2545.8	21.65	20.55	19.38
		2498.5	21.56	20.60	19.43
	12RB Low (0)	2687.5	21.55	20.46	19.29
		2640.3	21.54	20.58	19.41
		2593	21.54	20.54	19.37
		2545.8	21.53	20.44	19.27
		2498.5	21.50	20.56	19.39
	25RB (0)	2687.5	21.51	20.58	19.41
		2640.3	21.60	20.59	19.42
		2593	21.58	20.59	19.42
		2545.8	21.60	20.57	19.40

		2498.5	21.56	20.51	19.34
10 MHz	1RB High (49)	2685	22.36	21.44	20.27
		2639	22.48	21.70	20.53
		2593	22.62	21.51	20.34
		2547	22.50	21.58	20.41
		2501	22.47	21.58	20.41
	1RB Middle (24)	2685	22.65	21.72	20.55
		2639	22.75	21.94	20.77
		2593	22.92	21.77	20.60
		2547	22.80	21.78	20.61
		2501	22.78	21.91	20.74
	1RB Low (0)	2685	22.28	21.45	20.28
		2639	22.46	21.70	20.53
		2593	22.62	21.51	20.34
		2547	22.43	21.45	20.28
		2501	22.41	21.59	20.42
	25RB High (25)	2685	21.46	20.48	19.31
		2639	21.63	20.64	19.47
		2593	21.62	20.64	19.47
		2547	21.63	20.58	19.41
		2501	21.54	20.48	19.31
	25RB Middle (12)	2685	21.49	20.51	19.34
		2639	21.70	20.71	19.54
		2593	21.59	20.63	19.46
		2547	21.59	20.54	19.37
		2501	21.48	20.49	19.32
	25RB Low (0)	2685	21.53	20.53	19.36
		2639	21.63	20.62	19.45
		2593	21.62	20.60	19.43
		2547	21.59	20.57	19.40
		2501	21.56	20.57	19.40
	50RB (0)	2685	21.48	20.51	19.34
		2639	21.66	20.68	19.51
		2593	21.59	20.59	19.42
		2547	21.56	20.56	19.39
		2501	21.52	20.53	19.36
15 MHz	1RB High (74)	2682.5	22.81	21.38	20.21
		2637.8	22.34	21.56	20.39
		2593	22.49	21.39	20.22
		2548.3	22.43	21.43	20.26
		2503.5	22.40	21.47	20.30

	1RB Middle (37)	2682.5	22.93	21.48	20.31
		2637.8	22.52	21.67	20.50
		2593	22.62	21.55	20.38
		2548.3	22.60	21.56	20.39
		2503.5	22.47	21.57	20.40
	1RB Low (0)	2682.5	22.64	21.37	20.20
		2637.8	22.43	21.59	20.42
		2593	22.63	21.51	20.34
		2548.3	22.48	21.42	20.25
		2503.5	22.40	21.44	20.27
	36RB High (38)	2682.5	21.94	20.36	19.19
		2637.8	21.58	20.56	19.39
		2593	21.54	20.50	19.33
		2548.3	21.53	20.45	19.28
		2503.5	21.47	20.45	19.28
	36RB Middle (19)	2682.5	21.94	20.42	19.25
		2637.8	21.61	20.59	19.42
		2593	21.52	20.46	19.29
		2548.3	21.58	20.48	19.31
		2503.5	21.54	20.46	19.29
	36RB Low (0)	2682.5	21.80	20.38	19.21
		2637.8	21.55	20.54	19.37
		2593	21.51	20.45	19.28
		2548.3	21.50	20.43	19.26
		2503.5	21.49	20.43	19.26
	75RB (0)	2682.5	21.51	20.41	19.24
		2637.8	21.57	20.55	19.38
		2593	21.50	20.48	19.31
		2548.3	21.49	20.47	19.30
		2503.5	21.49	20.48	19.31
20 MHz	1RB High (99)	2680	22.80	21.82	20.65
		2636.5	22.95	21.84	20.67
		2593	22.98	22.11	20.94
		2549.5	22.93	21.95	20.78
		2506	22.95	21.85	20.68
	1RB Middle (50)	2680	23.08	22.06	20.89
		2636.5	23.20	22.10	20.93
		2593	23.19	22.36	21.19
		2549.5	23.23	22.24	21.07
		2506	23.26	22.08	20.91
	1RB Low (0)	2680	22.78	21.81	20.64
		2636.5	22.95	21.87	20.70

		2593	22.95	22.08	20.91
		2549.5	22.91	21.91	20.74
		2506	22.97	21.81	20.64
	50RB High (50)	2680	21.92	20.91	19.74
		2636.5	22.08	21.10	19.93
		2593	22.09	21.13	19.96
		2549.5	22.11	21.08	19.91
		2506	22.04	21.02	19.85
	50RB Middle (25)	2680	22.03	21.01	19.84
		2636.5	22.18	21.18	20.01
		2593	22.14	21.17	20.00
		2549.5	22.13	21.12	19.95
		2506	22.10	21.08	19.91
	50RB Low (0)	2680	21.95	20.93	19.76
		2636.5	22.07	21.08	19.91
		2593	22.08	21.13	19.96
		2549.5	22.04	21.02	19.85
		2506	22.07	21.08	19.91
	100RB (0)	2680	21.98	20.94	19.77
		2636.5	22.10	21.12	19.95
		2593	22.05	21.03	19.86
		2549.5	22.08	21.07	19.90
		2506	22.07	21.04	19.87

Band 66					
Bandwidth (MHz)	RB allocation	Frequency (MHz)	QPSK	16QAM	64QAM
	RB offset (Start RB)		Actual output power (dBm)	Actual output power (dBm)	Actual output power (dBm)
1.4 MHz	1RB High (5)	1779.3	22.83	21.55	20.84
		1745	22.60	22.09	21.38
		1710.7	22.46	21.91	21.20
	1RB Middle (3)	1779.3	23.02	21.78	21.07
		1745	22.75	22.42	21.71
		1710.7	22.50	22.04	21.33
	1RB Low (0)	1779.3	22.82	21.59	20.88
		1745	22.55	22.25	21.54
		1710.7	22.32	21.71	21.00
	3RB High (3)	1779.3	22.59	21.50	20.79
		1745	22.77	22.07	21.36
		1710.7	22.48	21.98	21.27
	3RB Middle (1)	1779.3	22.59	21.66	20.95
		1745	22.78	22.21	21.50
		1710.7	22.48	21.96	21.25
	3RB Low (0)	1779.3	22.50	21.59	20.88
		1745	22.57	22.14	21.43
		1710.7	22.44	21.92	21.21
	6RB (0)	1779.3	21.58	20.98	20.27
		1745	21.63	21.01	20.30
		1710.7	21.43	20.99	20.28
3 MHz	1RB High (14)	1778.5	22.86	21.74	21.03
		1745	22.74	22.19	21.48
		1711.5	22.66	21.89	21.18
	1RB Middle (7)	1778.5	22.99	21.93	21.22
		1745	22.64	22.45	21.74
		1711.5	22.55	22.07	21.36
	1RB Low (0)	1778.5	22.66	21.66	20.95
		1745	22.53	22.29	21.58
		1711.5	22.36	21.92	21.21
	8RB High (7)	1778.5	21.87	21.01	20.30
		1745	21.61	21.03	20.32
		1711.5	21.49	20.98	20.27
	8RB Middle (4)	1778.5	21.90	21.11	20.40
		1745	22.03	21.14	20.43
		1711.5	21.69	21.05	20.34
	8RB Low (0)	1778.5	21.86	21.08	20.37
		1745	21.93	21.10	20.39
		1711.5	21.73	20.98	20.27

	15RB (0)	1778.5	21.84	21.00	20.29
		1745	21.91	21.03	20.32
		1711.5	21.81	20.93	20.22
5 MHz	1RB High (24)	1777.5	22.79	21.57	20.86
		1745	22.59	22.23	21.52
		1712.5	22.60	21.94	21.23
	1RB Middle (12)	1777.5	23.13	21.89	21.18
		1745	22.89	22.48	21.77
		1712.5	22.76	22.16	21.45
	1RB Low (0)	1777.5	22.68	21.75	21.04
		1745	22.47	22.15	21.44
		1712.5	22.38	21.89	21.18
	12RB High (13)	1777.5	21.84	20.82	20.11
		1745	21.66	20.99	20.28
		1712.5	21.47	20.91	20.20
	12RB Middle (6)	1777.5	21.87	20.95	20.24
		1745	21.79	21.14	20.43
		1712.5	21.53	21.06	20.35
	12RB Low (0)	1777.5	21.51	21.03	20.32
		1745	21.66	21.15	20.44
		1712.5	21.66	20.97	20.26
	25RB (0)	1777.5	21.71	20.96	20.25
		1745	21.68	21.07	20.36
		1712.5	21.55	20.94	20.23
10 MHz	1RB High (49)	1775	22.78	21.30	20.59
		1745	22.68	22.07	21.36
		1715	22.36	21.92	21.21
	1RB Middle (24)	1775	22.98	21.71	21.00
		1745	22.82	22.39	21.68
		1715	22.65	22.06	21.35
	1RB Low (0)	1775	22.80	21.47	20.76
		1745	22.68	22.20	21.49
		1715	22.31	21.80	21.09
	25RB High (25)	1775	21.93	20.73	20.02
		1745	21.77	21.08	20.37
		1715	21.72	21.05	20.34
	25RB Middle (12)	1775	21.94	20.91	20.20
		1745	21.63	21.09	20.38
		1715	21.66	21.14	20.43
	25RB Low (0)	1775	21.96	20.80	20.09
		1745	21.71	21.06	20.35
		1715	21.56	20.95	20.24
	50RB (0)	1775	21.86	20.94	20.23
		1745	21.86	21.06	20.35
		1715	21.73	21.07	20.36
15 MHz	1RB High (74)	1772.5	22.70	21.56	20.85
		1745	22.84	22.13	21.42
		1717.5	22.79	22.22	21.51

	1RB Middle (37)	1772.5	22.88	21.84	21.13
		1745	22.94	22.29	21.58
		1717.5	22.92	22.35	21.64
	1RB Low (0)	1772.5	22.74	21.72	21.01
		1745	22.84	22.17	21.46
		1717.5	22.74	22.17	21.46
	36RB High (38)	1772.5	21.93	20.96	20.25
		1745	21.97	21.04	20.33
		1717.5	21.93	21.03	20.32
	36RB Middle (19)	1772.5	21.99	20.97	20.26
		1745	21.97	21.03	20.32
		1717.5	21.97	20.97	20.26
	36RB Low (0)	1772.5	21.94	20.98	20.27
		1745	21.94	20.98	20.27
		1717.5	21.90	20.91	20.20
	75RB (0)	1772.5	21.97	21.00	20.29
		1745	21.94	20.99	20.28
		1717.5	21.86	21.02	20.31
20 MHz	1RB High (99)	1770	22.59	22.11	21.40
		1745	22.65	22.14	21.43
		1720	22.72	22.27	21.56
	1RB Middle (50)	1770	22.96	22.43	21.72
		1745	22.94	22.43	21.72
		1720	22.97	22.52	21.81
	1RB Low (0)	1770	22.65	22.13	21.42
		1745	22.67	22.08	21.37
		1720	22.63	22.21	21.50
	50RB High (50)	1770	21.80	20.95	20.24
		1745	21.88	20.95	20.24
		1720	21.90	21.02	20.31
	50RB Middle (25)	1770	21.87	20.98	20.27
		1745	21.89	20.97	20.26
		1720	21.93	20.98	20.27
	50RB Low (0)	1770	21.86	20.97	20.26
		1745	21.86	20.92	20.21
		1720	21.77	20.91	20.20
	100RB (0)	1770	21.83	20.92	20.21
		1745	21.89	20.95	20.24
		1720	21.80	20.92	20.21

Band 71					
Bandwidth (MHz)	RB allocation	Frequency (MHz)	QPSK	16QAM	64QAM
	RB offset (Start RB)		Actual output power (dBm)	Actual output power (dBm)	Actual output power (dBm)
5 MHz	1RB High (24)	695.5	23.01	22.11	21.50
		680.5	23.10	22.19	21.58
		665.5	23.03	22.52	21.91
	1RB Middle (12)	695.5	23.25	22.32	21.71
		680.5	23.36	22.43	21.82
		665.5	23.27	22.73	22.12
	1RB Low (0)	695.5	23.00	22.12	21.51
		680.5	23.12	22.24	21.63
		665.5	23.04	22.53	21.92
	12RB High (13)	695.5	22.12	21.12	20.51
		680.5	22.06	21.20	20.59
		665.5	22.14	21.30	20.69
	12RB Middle (6)	695.5	22.12	21.17	20.56
		680.5	22.14	21.25	20.64
		665.5	22.15	21.29	20.68
	12RB Low (0)	695.5	22.09	21.14	20.53
		680.5	22.05	21.16	20.55
		665.5	22.06	21.18	20.57
	25RB (0)	695.5	22.10	21.07	20.46
		680.5	22.12	21.14	20.53
		665.5	22.11	21.22	20.61
10 MHz	1RB High (49)	693	22.98	22.08	21.47
		680.5	23.04	21.98	21.37
		668	23.09	22.50	21.89
	1RB Middle (24)	693	23.20	22.20	21.59
		680.5	23.18	22.14	21.53
		668	23.23	22.59	21.98
	1RB Low (0)	693	22.95	22.02	21.41
		680.5	22.97	22.02	21.41
		668	23.11	22.38	21.77
	25RB High (25)	693	22.16	21.26	20.65
		680.5	22.18	21.21	20.60
		668	22.17	21.21	20.60
	25RB Middle (12)	693	22.14	21.28	20.67
		680.5	22.21	21.21	20.60
		668	22.17	21.20	20.59
	25RB Low (0)	693	22.20	21.31	20.70
		680.5	22.11	21.17	20.56
		668	22.06	21.10	20.49
	50RB (0)	693	22.18	21.22	20.61
		680.5	22.17	21.17	20.56
		668	22.13	21.17	20.56

15 MHz	1RB High (74)	690.5	23.03	22.36	21.75
		680.5	23.01	22.41	21.80
		670.5	23.02	22.01	21.40
	1RB Middle (37)	690.5	23.12	22.49	21.88
		680.5	23.15	22.56	21.95
		670.5	23.10	22.08	21.47
	1RB Low (0)	690.5	23.03	22.40	21.79
		680.5	23.01	22.42	21.81
		670.5	23.05	21.94	21.33
	36RB High (38)	690.5	22.16	21.20	20.59
		680.5	22.15	21.09	20.48
		670.5	22.16	21.09	20.48
	36RB Middle (19)	690.5	22.15	21.21	20.60
		680.5	22.16	21.12	20.51
		670.5	22.19	21.12	20.51
	36RB Low (0)	690.5	22.19	21.18	20.57
		680.5	22.11	21.05	20.44
		670.5	22.03	21.01	20.40
	75RB (0)	690.5	22.19	21.23	20.62
		680.5	22.15	21.12	20.51
		670.5	22.11	21.11	20.50
20 MHz	1RB High (99)	688	22.61	22.18	21.57
		683	22.60	22.14	21.53
		673	22.66	22.08	21.47
	1RB Middle (50)	688	22.84	22.44	21.83
		683	22.89	22.37	21.76
		673	22.90	22.33	21.72
	1RB Low (0)	688	22.61	22.22	21.61
		683	22.56	22.11	21.50
		673	22.65	22.01	21.40
	50RB High (50)	688	21.74	20.82	20.21
		683	21.65	20.67	20.06
		673	21.82	20.84	20.23
	50RB Middle (25)	688	21.78	20.85	20.24
		683	21.83	20.86	20.25
		673	21.84	20.84	20.23
	50RB Low (0)	688	21.74	20.85	20.24
		683	21.72	20.75	20.14
		673	21.66	20.63	20.02
	100RB (0)	688	21.71	20.82	20.21
		683	21.66	20.70	20.09
		673	21.78	20.77	20.16

Low power

Table 11.3-5: The conducted Power for LTE

Band 7					
Bandwidth (MHz)	RB allocation	Frequency (MHz)	QPSK	16QAM	64QAM
	RB offset (Start RB)		Actual output power (dBm)	Actual output power (dBm)	Actual output power (dBm)
5 MHz	1RB High (24)	2567.5	19.46	19.57	19.27
		2535	19.41	19.55	20.21
		2502.5	19.32	19.81	20.30
	1RB Middle (12)	2567.5	19.70	19.82	20.56
		2535	19.68	19.80	20.43
		2502.5	19.62	20.08	20.49
	1RB Low (0)	2567.5	19.45	19.55	20.31
		2535	19.44	19.53	20.26
		2502.5	19.33	19.80	20.30
	12RB High (13)	2567.5	19.46	19.52	20.28
		2535	19.45	19.49	20.15
		2502.5	19.40	19.54	20.25
	12RB Middle (6)	2567.5	19.58	19.63	20.40
		2535	19.49	19.56	20.21
		2502.5	19.46	19.58	20.34
	12RB Low (0)	2567.5	19.51	19.58	20.34
		2535	19.43	19.51	20.16
		2502.5	19.39	19.52	20.31
	25RB (0)	2567.5	19.52	19.48	20.36
		2535	19.43	19.48	20.15
		2502.5	19.40	19.48	20.26
10 MHz	1RB High (49)	2565	19.51	19.58	20.53
		2535	19.47	19.41	20.31
		2505	19.50	19.78	20.42
	1RB Middle (24)	2565	19.63	19.65	20.60
		2535	19.54	19.52	20.44
		2505	19.55	19.89	20.60
	1RB Low (0)	2565	19.47	19.50	20.45
		2535	19.43	19.43	20.37
		2505	19.43	19.77	20.41
	25RB High (25)	2565	19.55	19.63	20.35
		2535	19.50	19.56	20.19
		2505	19.51	19.55	19.74
	25RB Middle (12)	2565	19.57	19.65	20.37
		2535	19.51	19.55	20.21
		2505	19.44	19.48	20.30
	25RB Low (0)	2565	19.55	19.65	20.36
		2535	19.51	19.56	20.27
		2505	19.46	19.53	20.35
	50RB	2565	19.58	19.61	20.37

	(0)	2535	19.55	19.52	20.22
		2505	19.49	19.56	20.34
15 MHz	1RB High (74)	2562.5	19.39	19.35	20.46
		2535	19.39	19.73	20.21
		2507.5	19.36	19.78	20.35
	1RB Middle (37)	2562.5	19.49	19.50	20.42
		2535	19.53	19.87	20.37
		2507.5	19.45	19.96	20.42
	1RB Low (0)	2562.5	19.37	19.35	20.40
		2535	19.45	19.78	20.20
		2507.5	19.34	19.77	20.40
	36RB High (38)	2562.5	19.52	19.52	20.34
		2535	19.46	19.51	20.15
		2507.5	19.51	19.44	20.28
	36RB Middle (19)	2562.5	19.56	19.54	20.30
		2535	19.56	19.59	20.22
		2507.5	19.47	19.45	20.32
	36RB Low (0)	2562.5	19.51	19.51	20.31
		2535	19.55	19.54	20.23
		2507.5	19.46	19.37	20.30
	75RB (0)	2562.5	19.53	19.48	20.28
		2535	19.52	19.54	20.20
		2507.5	19.46	19.46	20.26
20 MHz	1RB High (99)	2560	19.84	20.33	20.28
		2535	19.80	20.36	20.19
		2510	19.71	20.16	20.18
	1RB Middle (50)	2560	19.89	20.60	20.49
		2535	19.84	20.60	20.40
		2510	19.83	20.50	20.48
	1RB Low (0)	2560	19.81	20.32	20.27
		2535	19.74	20.28	20.31
		2510	19.73	20.11	20.26
	50RB High (50)	2560	19.88	19.92	20.27
		2535	19.84	19.89	20.09
		2510	19.87	19.88	20.26
	50RB Middle (25)	2560	19.99	20.02	20.35
		2535	19.98	19.99	20.23
		2510	19.89	19.89	20.29
	50RB Low (0)	2560	19.91	19.97	20.27
		2535	19.96	20.00	20.24
		2510	19.85	19.86	20.28
	100RB (0)	2560	19.90	19.95	20.24
		2535	19.93	19.97	20.18
		2510	19.89	19.89	20.22

Band 25					
Bandwidth (MHz)	RB allocation	Frequency (MHz)	QPSK	16QAM	64QAM
	RB offset (Start RB)		Actual output power (dBm)	Actual output power (dBm)	Actual output power (dBm)
1.4 MHz	1RB High (5)	1914.3	18.42	18.12	18.93
		1882.5	18.05	18.28	19.00
		1850.7	18.13	18.50	19.24
	1RB Middle (3)	1914.3	18.39	18.29	18.99
		1882.5	18.23	18.45	19.15
		1850.7	18.34	18.69	19.25
	1RB Low (0)	1914.3	18.03	18.13	18.96
		1882.5	18.11	18.27	19.05
		1850.7	18.11	18.51	19.18
	3RB High (3)	1914.3	18.11	18.31	18.92
		1882.5	18.15	18.23	19.06
		1850.7	18.19	18.43	19.10
	3RB Middle (1)	1914.3	18.19	18.34	19.02
		1882.5	18.20	18.29	19.09
		1850.7	18.25	18.45	19.19
	3RB Low (0)	1914.3	18.13	18.27	18.93
		1882.5	18.17	18.25	19.04
		1850.7	18.20	18.40	19.17
	6RB (0)	1914.3	18.14	18.29	18.83
		1882.5	18.14	18.32	18.96
		1850.7	18.15	18.09	19.05
3 MHz	1RB High (14)	1913.5	18.55	18.14	19.03
		1882.5	18.12	18.16	19.15
		1851.5	18.14	18.57	19.23
	1RB Middle (7)	1913.5	18.47	18.29	19.18
		1882.5	18.23	18.26	19.33
		1851.5	18.32	18.70	19.39
	1RB Low (0)	1913.5	18.22	18.22	19.02
		1882.5	18.10	18.16	19.20
		1851.5	18.19	18.53	19.24
	8RB High (7)	1913.5	18.07	18.12	18.82
		1882.5	18.10	18.24	18.96
		1851.5	18.08	18.24	19.04
	8RB Middle (4)	1913.5	18.11	18.17	18.87
		1882.5	18.19	18.35	19.02
		1851.5	18.15	18.27	19.10
	8RB Low (0)	1913.5	18.12	18.15	18.89
		1882.5	18.14	18.28	19.00
		1851.5	18.11	18.28	19.07
	15RB (0)	1913.5	18.12	18.08	18.83
		1882.5	18.15	18.20	18.93

5 MHz	1RB High (24)	1851.5	18.10	18.19	19.00
		1912.5	18.55	18.16	18.81
		1882.5	18.07	18.29	19.06
		1852.5	18.08	18.57	19.13
	1RB Middle (12)	1912.5	18.81	18.42	19.14
		1882.5	18.36	18.53	19.41
		1852.5	18.32	18.85	19.32
	1RB Low (0)	1912.5	18.41	18.20	18.97
		1882.5	18.07	18.27	18.98
		1852.5	18.05	18.58	19.16
	12RB High (13)	1912.5	18.13	18.06	18.85
		1882.5	18.09	18.27	18.95
		1852.5	18.13	18.28	19.02
	12RB Middle (6)	1912.5	18.18	18.21	18.93
		1882.5	18.16	18.27	19.00
		1852.5	18.17	18.33	19.08
	12RB Low (0)	1912.5	18.12	18.17	18.88
		1882.5	18.07	18.26	18.94
		1852.5	18.20	18.31	19.03
	25RB (0)	1912.5	18.11	18.07	18.86
		1882.5	18.14	18.18	18.94
		1852.5	18.10	18.25	19.01
10 MHz	1RB High (49)	1910	18.49	18.10	18.95
		1882.5	18.09	18.09	19.08
		1855	18.10	18.47	19.17
	1RB Middle (24)	1910	18.74	18.29	19.18
		1882.5	18.20	18.25	19.28
		1855	18.25	18.68	19.35
	1RB Low (0)	1910	18.54	18.16	19.09
		1882.5	18.05	18.11	19.11
		1855	18.13	18.50	19.18
	25RB High (25)	1910	18.33	18.20	18.91
		1882.5	18.20	18.29	19.01
		1855	18.18	18.24	19.02
	25RB Middle (12)	1910	18.29	18.28	18.94
		1882.5	18.16	18.25	18.98
		1855	18.18	18.24	19.01
	25RB Low (0)	1910	18.25	18.30	18.97
		1882.5	18.19	18.23	18.99
		1855	18.18	18.24	19.06
	50RB (0)	1910	18.14	18.21	18.96
		1882.5	18.20	18.25	18.97
		1855	18.21	18.23	19.02
15 MHz	1RB High (74)	1907.5	18.07	18.12	18.93
		1882.5	18.08	18.42	19.06
		1857.5	18.01	18.54	19.06
	1RB Middle	1907.5	18.14	18.16	19.05
		1882.5	18.24	18.57	19.20

	(37)	1857.5	18.12	18.69	19.28
	1RB Low (0)	1907.5	18.08	18.08	18.99
		1882.5	18.08	18.46	19.03
		1857.5	18.07	18.57	19.14
	36RB High (38)	1907.5	18.18	18.16	18.91
		1882.5	18.20	18.24	18.96
		1857.5	18.14	18.10	19.01
	36RB Middle (19)	1907.5	18.24	18.20	18.97
		1882.5	18.17	18.24	18.99
		1857.5	18.13	18.11	19.02
	36RB Low (0)	1907.5	18.23	18.19	18.99
		1882.5	18.14	18.26	19.02
		1857.5	18.14	18.12	19.05
	75RB (0)	1907.5	18.19	18.20	18.96
		1882.5	18.14	18.19	18.97
		1857.5	18.09	18.11	18.98
20 MHz	1RB High (99)	1905	18.39	18.89	18.84
		1882.5	18.39	19.00	18.93
		1860	18.40	18.85	18.95
	1RB Middle (50)	1905	18.72	19.28	19.16
		1882.5	18.71	19.37	19.23
		1860	18.63	19.18	19.33
	1RB Low (0)	1905	18.49	18.97	19.02
		1882.5	18.41	19.02	19.06
		1860	18.45	18.96	19.15
	50RB High (50)	1905	18.54	18.64	18.93
		1882.5	18.67	18.73	18.97
		1860	18.57	18.61	18.93
	50RB Middle (25)	1905	18.63	18.71	18.93
		1882.5	18.64	18.69	18.98
		1860	18.58	18.62	19.00
	50RB Low (0)	1905	18.68	18.72	19.01
		1882.5	18.67	18.76	19.03
		1860	18.52	18.56	18.97
	100RB (0)	1905	18.64	18.71	18.92
		1882.5	18.69	18.74	19.00
		1860	18.54	18.59	18.93

Band 41 – PC2					
Bandwidth (MHz)	RB allocation	Frequency (MHz)	QPSK	16QAM	64QAM
	RB offset (Start RB)		Actual output power (dBm)	Actual output power (dBm)	Actual output power (dBm)
5 MHz	1RB High (24)	2687.5	23.56	23.45	23.90
		2640.3	23.37	24.01	23.85
		2593	23.21	23.74	24.00
		2545.8	23.26	23.49	23.75
		2498.5	23.02	23.52	23.94
	1RB Middle (12)	2687.5	23.78	23.91	24.02
		2640.3	23.66	24.28	23.87
		2593	23.47	23.94	24.06
		2545.8	23.32	23.73	23.84
		2498.5	23.29	23.85	23.94
	1RB Low (0)	2687.5	23.56	23.68	23.93
		2640.3	23.23	23.86	23.90
		2593	23.16	23.52	24.07
		2545.8	23.09	23.40	23.77
		2498.5	23.00	23.59	23.93
	12RB High (13)	2687.5	23.69	23.38	24.05
		2640.3	23.32	23.74	24.09
		2593	23.26	23.38	24.16
		2545.8	23.22	23.15	23.93
		2498.5	23.10	23.26	24.03
	12RB Middle (6)	2687.5	23.68	23.35	24.13
		2640.3	23.54	23.70	24.14
		2593	23.28	23.57	24.30
		2545.8	23.23	23.22	23.94
		2498.5	23.22	23.39	24.14
	12RB Low (0)	2687.5	23.73	23.42	24.08
		2640.3	23.24	23.67	24.09
		2593	23.24	23.45	24.21
		2545.8	23.21	23.18	23.92
		2498.5	23.24	23.38	24.12
	25RB (0)	2687.5	23.71	23.64	24.11
		2640.3	23.28	23.63	24.07
		2593	23.30	23.31	24.22
		2545.8	23.20	23.26	23.94

		2498.5	23.27	23.39	24.04
10 MHz	1RB High (49)	2685	23.62	23.62	23.96
		2639	23.73	23.75	23.86
		2593	23.88	23.64	24.05
		2547	23.29	23.64	23.86
		2501	23.09	23.55	23.94
	1RB Middle (24)	2685	23.75	23.70	24.13
		2639	23.83	23.82	24.06
		2593	23.80	23.56	24.24
		2547	23.21	23.74	23.93
		2501	23.19	23.65	24.11
	1RB Low (0)	2685	23.68	23.65	24.05
		2639	23.71	23.65	23.93
		2593	23.67	23.51	24.20
		2547	23.14	23.59	23.83
		2501	23.09	23.52	24.03
	25RB High (25)	2685	23.73	23.24	24.15
		2639	23.82	23.38	24.10
		2593	23.51	23.37	24.30
		2547	23.31	23.31	24.00
		2501	23.21	23.24	24.12
	25RB Middle (12)	2685	23.77	23.28	24.24
		2639	23.73	23.40	24.11
		2593	23.39	23.35	24.30
		2547	23.27	23.28	24.03
		2501	23.20	23.25	24.15
	25RB Low (0)	2685	23.80	23.29	24.22
		2639	23.84	23.38	24.15
		2593	23.51	23.37	24.33
		2547	23.25	23.28	24.00
		2501	23.25	23.27	24.20
	50RB (0)	2685	23.74	23.79	24.18
		2639	23.86	23.64	24.07
		2593	23.81	23.72	24.25
		2547	23.45	23.27	23.95
		2501	23.49	23.34	24.10
15 MHz	1RB High (74)	2682.5	23.57	23.51	23.83
		2637.8	23.61	23.88	23.84
		2593	23.74	23.60	23.96
		2548.3	23.67	23.72	23.77
		2503.5	23.34	23.40	23.77

	1RB Middle (37)	2682.5	23.73	23.70	24.07
		2637.8	23.75	23.94	23.96
		2593	23.90	23.85	24.12
		2548.3	23.74	23.71	23.87
		2503.5	23.35	23.51	23.97
	1RB Low (0)	2682.5	23.63	23.60	24.03
		2637.8	23.66	23.64	23.93
		2593	23.79	23.70	24.10
		2548.3	23.38	23.56	23.75
		2503.5	23.24	23.39	23.94
	36RB High (38)	2682.5	23.72	23.71	24.06
		2637.8	23.88	23.86	24.00
		2593	23.84	23.78	24.13
		2548.3	23.78	23.49	23.88
		2503.5	23.70	23.50	23.91
	36RB Middle (19)	2682.5	23.77	23.76	24.09
		2637.8	23.89	23.88	24.01
		2593	23.86	23.79	24.18
		2548.3	23.80	23.71	23.88
		2503.5	23.73	23.62	24.00
	36RB Low (0)	2682.5	23.76	23.74	24.09
		2637.8	23.86	23.83	24.05
		2593	23.83	23.77	24.19
		2548.3	23.76	23.56	23.85
		2503.5	23.70	23.67	24.01
	75RB (0)	2682.5	23.75	23.77	24.09
		2637.8	23.86	23.92	24.01
		2593	23.83	23.80	24.17
		2548.3	23.76	23.55	23.87
		2503.5	23.74	23.72	24.00
20 MHz	1RB High (99)	2680	23.52	23.75	23.82
		2636.5	23.61	24.03	23.76
		2593	23.65	23.89	23.88
		2549.5	23.62	23.76	23.72
		2506	23.54	23.87	23.69
	1RB Middle (50)	2680	23.91	24.11	24.11
		2636.5	23.94	24.38	24.01
		2593	24.02	24.27	24.20
		2549.5	24.01	24.11	23.90
		2506	23.87	24.25	23.93
	1RB Low (0)	2680	23.62	23.75	23.96
		2636.5	23.59	24.03	23.94

		2593	23.66	23.92	24.03
		2549.5	23.60	23.73	23.72
		2506	23.49	23.85	23.89
	50RB High (50)	2680	23.65	23.68	24.03
		2636.5	23.73	23.80	23.97
		2593	23.74	23.75	24.13
		2549.5	23.73	23.76	23.94
		2506	23.64	23.70	23.87
	50RB Middle (25)	2680	23.69	23.73	24.13
		2636.5	23.77	23.85	24.06
		2593	23.71	23.77	24.19
		2549.5	23.71	23.74	23.90
		2506	23.69	23.74	24.00
	50RB Low (0)	2680	23.68	23.76	24.13
		2636.5	23.71	23.79	24.06
		2593	23.74	23.72	24.19
		2549.5	23.66	23.69	23.85
		2506	23.66	23.72	24.04
	100RB (0)	2680	23.68	23.69	24.11
		2636.5	23.74	23.76	24.05
		2593	23.74	23.75	24.18
		2549.5	23.69	23.71	23.92
		2506	23.65	23.69	23.99

Band 41 – PC3					
Bandwidth (MHz)	RB allocation	Frequency (MHz)	QPSK	16QAM	64QAM
	RB offset (Start RB)		Actual output power (dBm)	Actual output power (dBm)	Actual output power (dBm)
5 MHz	1RB High (24)	2687.5	20.19	20.18	20.01
		2640.3	20.31	20.40	20.23
		2593	20.35	20.26	20.09
		2545.8	20.24	20.27	20.10
		2498.5	20.16	20.32	20.15
	1RB Middle (12)	2687.5	20.20	20.25	20.08
		2640.3	20.30	20.41	20.24
		2593	20.41	20.28	20.11
		2545.8	20.23	20.31	20.14
		2498.5	20.18	20.33	20.16
	1RB Low (0)	2687.5	20.22	20.20	20.03
		2640.3	20.32	20.44	20.27
		2593	20.44	20.24	20.07
		2545.8	20.24	20.23	20.06
		2498.5	20.11	20.31	20.14
	12RB High (13)	2687.5	20.31	20.25	20.08
		2640.3	20.52	20.48	20.31
		2593	20.39	20.41	20.24
		2545.8	20.35	20.36	20.19
		2498.5	20.24	20.35	20.18
	12RB Middle (6)	2687.5	20.42	20.37	20.20
		2640.3	20.59	20.59	20.42
		2593	20.48	20.49	20.32
		2545.8	20.45	20.47	20.30
		2498.5	20.33	20.41	20.24
	12RB Low (0)	2687.5	20.34	20.27	20.10
		2640.3	20.51	20.48	20.31
		2593	20.41	20.42	20.25
		2545.8	20.35	20.30	20.13
		2498.5	20.26	20.34	20.17
	25RB (0)	2687.5	20.36	20.38	20.21
		2640.3	20.53	20.47	20.30
		2593	20.44	20.48	20.31
		2545.8	20.37	20.44	20.27
		2498.5	20.31	20.34	20.17

10 MHz	1RB High (49)	2685	20.22	20.30	20.13
		2639	20.39	20.57	20.40
		2593	20.52	20.43	20.26
		2547	20.31	20.43	20.26
		2501	20.23	20.42	20.25
	1RB Middle (24)	2685	20.54	20.63	20.46
		2639	20.69	20.91	20.74
		2593	20.78	20.71	20.54
		2547	20.61	20.67	20.50
		2501	20.55	20.74	20.57
	1RB Low (0)	2685	20.29	20.35	20.18
		2639	20.38	20.58	20.41
		2593	20.52	20.41	20.24
		2547	20.23	20.38	20.21
		2501	20.24	20.41	20.24
	25RB High (25)	2685	20.32	20.39	20.22
		2639	20.47	20.56	20.39
		2593	20.49	20.53	20.36
		2547	20.43	20.48	20.31
		2501	20.32	20.41	20.24
	25RB Middle (12)	2685	20.41	20.44	20.27
		2639	20.49	20.58	20.41
		2593	20.48	20.56	20.39
		2547	20.43	20.47	20.30
		2501	20.30	20.39	20.22
	25RB Low (0)	2685	20.46	20.49	20.32
		2639	20.54	20.61	20.44
		2593	20.52	20.55	20.38
		2547	20.44	20.49	20.32
		2501	20.37	20.43	20.26
	50RB (0)	2685	20.39	20.45	20.28
		2639	20.54	20.60	20.43
		2593	20.46	20.51	20.34
		2547	20.41	20.47	20.30
		2501	20.30	20.41	20.24
15 MHz	1RB High (74)	2682.5	20.63	20.38	20.21
		2637.8	20.73	20.44	20.27
		2593	20.91	20.36	20.19
		2548.3	20.76	20.29	20.12
		2503.5	20.66	20.28	20.11
	1RB	2682.5	20.78	20.37	20.20

	Middle (37)	2637.8	20.88	20.52	20.35
		2593	21.02	20.43	20.26
		2548.3	20.88	20.38	20.21
		2503.5	20.81	20.40	20.23
		2682.5	20.73	20.28	20.11
	1RB Low (0)	2637.8	20.76	20.41	20.24
		2593	20.95	20.36	20.19
		2548.3	20.75	20.27	20.10
		2503.5	20.62	20.27	20.10
		2682.5	20.76	20.79	20.62
	36RB High (38)	2637.8	20.91	20.46	20.29
		2593	20.88	20.39	20.22
		2548.3	20.86	20.34	20.17
		2503.5	20.78	20.28	20.11
		2682.5	20.81	20.84	20.67
	36RB Middle (19)	2637.8	20.91	20.62	20.45
		2593	20.89	20.36	20.19
		2548.3	20.86	20.34	20.17
		2503.5	20.79	20.32	20.15
		2682.5	20.79	20.82	20.65
	36RB Low (0)	2637.8	20.89	20.49	20.32
		2593	20.87	20.38	20.21
		2548.3	20.80	20.30	20.13
		2503.5	20.75	20.26	20.09
		2682.5	20.79	20.86	20.69
	75RB (0)	2637.8	20.89	20.49	20.32
		2593	20.86	20.41	20.24
		2548.3	20.81	20.34	20.17
		2503.5	20.78	20.28	20.11
		2680	20.72	20.86	20.69
20 MHz	1RB High (99)	2636.5	20.86	20.86	20.69
		2593	20.91	20.75	20.58
		2549.5	20.85	20.95	20.78
		2506	20.80	20.80	20.63
		2680	21.04	21.12	20.95
	1RB Middle (50)	2636.5	21.14	21.07	20.90
		2593	21.14	21.05	20.88
		2549.5	21.08	21.21	21.04
		2506	20.99	21.01	20.84
		2680	20.81	20.92	20.75
	1RB Low (0)	2636.5	20.86	20.90	20.73
		2593	20.92	20.80	20.63

		2549.5	20.85	20.94	20.77
		2506	20.80	20.76	20.59
	50RB High (50)	2680	20.82	20.92	20.75
		2636.5	20.94	20.97	20.80
		2593	20.98	21.05	20.88
		2549.5	20.93	21.06	20.89
		2506	20.85	20.88	20.71
	50RB Middle (25)	2680	20.91	20.99	20.82
		2636.5	21.03	21.04	20.87
		2593	21.02	21.07	20.90
		2549.5	21.00	21.07	20.90
		2506	20.92	20.93	20.76
	50RB Low (0)	2680	20.88	20.99	20.82
		2636.5	20.96	20.99	20.82
		2593	20.99	21.03	20.86
		2549.5	20.92	21.02	20.85
		2506	20.90	20.96	20.79
	100RB (0)	2680	20.86	20.92	20.75
		2636.5	20.98	21.00	20.83
		2593	20.98	21.04	20.87
		2549.5	20.97	20.98	20.81
		2506	20.86	20.91	20.74

Band 66					
Bandwidth (MHz)	RB allocation	Frequency (MHz)	QPSK	16QAM	64QAM
	RB offset (Start RB)		Actual output power (dBm)	Actual output power (dBm)	Actual output power (dBm)
1.4 MHz	1RB High (5)	1779.3	17.87	18.00	18.79
		1745	17.95	18.25	18.73
		1710.7	17.89	18.03	18.92
	1RB Middle (3)	1779.3	18.08	18.19	18.80
		1745	18.13	18.38	18.86
		1710.7	18.11	18.19	18.98
	1RB Low (0)	1779.3	17.87	18.05	18.77
		1745	18.00	18.30	18.82
		1710.7	17.89	18.00	18.90
	3RB High (3)	1779.3	17.90	18.00	18.69
		1745	17.91	18.13	18.82
		1710.7	18.04	18.18	18.87
	3RB Middle (1)	1779.3	17.90	18.02	18.80
		1745	17.99	18.17	18.84
		1710.7	18.08	18.26	18.90
	3RB Low (0)	1779.3	17.94	18.03	18.69
		1745	17.95	18.14	18.79
		1710.7	18.00	18.17	18.88
	6RB (0)	1779.3	17.94	18.14	18.63
		1745	17.98	17.91	18.67
		1710.7	18.06	18.22	18.75
3 MHz	1RB High (14)	1778.5	17.93	17.89	18.86
		1745	18.04	18.37	18.91
		1711.5	18.01	18.05	18.95
	1RB Middle (7)	1778.5	18.03	18.07	18.96
		1745	18.14	18.48	18.93
		1711.5	18.13	18.23	18.91
	1RB Low (0)	1778.5	17.89	17.95	18.87
		1745	18.01	18.35	18.81
		1711.5	18.06	18.15	18.83
	8RB High (7)	1778.5	17.91	18.02	18.69
		1745	17.90	18.03	18.73
		1711.5	17.99	18.04	18.78
	8RB Middle (4)	1778.5	17.96	18.08	18.73
		1745	17.98	18.12	18.75
		1711.5	18.06	18.12	18.82
	8RB Low (0)	1778.5	17.92	18.04	18.72
		1745	17.96	18.07	18.73
		1711.5	18.03	18.06	18.83
	15RB	1778.5	17.93	17.97	18.61

	(0)	1745	17.94	18.00	18.64
		1711.5	17.97	17.95	18.74
5 MHz	1RB High (24)	1777.5	17.91	18.08	18.75
		1745	17.92	18.43	18.73
		1712.5	17.98	18.08	18.91
	1RB Middle (12)	1777.5	18.12	18.32	18.95
		1745	18.14	18.62	18.94
		1712.5	18.19	18.30	18.96
	1RB Low (0)	1777.5	17.93	18.09	18.79
		1745	17.93	18.42	18.80
		1712.5	18.04	18.15	18.91
	12RB High (13)	1777.5	17.94	18.00	18.70
		1745	18.02	18.11	18.69
		1712.5	17.98	18.07	18.75
	12RB Middle (6)	1777.5	17.95	18.05	18.70
		1745	18.04	18.14	18.72
		1712.5	18.07	18.11	18.79
	12RB Low (0)	1777.5	17.93	17.99	18.68
		1745	17.97	18.09	18.69
		1712.5	18.01	18.00	18.75
	25RB (0)	1777.5	17.91	17.95	18.66
		1745	17.95	18.02	18.71
		1712.5	17.98	17.98	18.73
10 MHz	1RB High (49)	1775	17.90	17.91	18.76
		1745	18.01	18.36	18.90
		1715	17.95	18.04	18.87
	1RB Middle (24)	1775	18.09	18.04	18.99
		1745	18.13	18.44	18.91
		1715	18.05	18.14	18.93
	1RB Low (0)	1775	17.91	17.97	18.83
		1745	18.04	18.33	18.92
		1715	17.96	18.07	18.99
	25RB High (25)	1775	18.00	18.04	18.74
		1745	18.02	18.07	18.76
		1715	18.06	18.16	18.81
	25RB Middle (12)	1775	17.98	18.07	18.71
		1745	18.04	18.08	18.73
		1715	18.07	18.16	18.76
	25RB Low (0)	1775	18.01	18.02	18.76
		1745	18.00	18.05	18.74
		1715	18.03	18.13	18.79
	50RB (0)	1775	18.01	17.99	18.71
		1745	18.05	18.05	18.76
		1715	18.06	18.12	18.80
15 MHz	1RB High (74)	1772.5	17.83	17.82	18.76
		1745	17.93	18.27	18.77
		1717.5	17.91	18.35	18.74
	1RB	1772.5	17.91	17.97	18.82

	Middle (37)	1745	18.05	18.36	18.87
		1717.5	18.06	18.51	18.96
	1RB Low (0)	1772.5	17.91	17.93	18.81
		1745	17.98	18.31	18.83
	36RB High (38)	1717.5	17.99	18.49	18.87
		1772.5	18.00	17.94	18.69
		1745	18.01	18.05	18.68
	36RB Middle (19)	1717.5	18.07	18.05	18.78
		1772.5	18.02	18.00	18.74
		1745	18.05	18.09	18.73
	36RB Low (0)	1717.5	18.03	18.00	18.73
		1772.5	18.04	18.03	18.70
		1745	17.99	18.04	18.70
	75RB (0)	1717.5	18.03	18.01	18.76
		1772.5	18.03	18.01	18.70
		1745	17.99	18.05	18.71
20 MHz	1RB High (99)	1717.5	18.06	18.01	18.71
		1770	18.19	18.69	18.62
		1745	18.23	18.81	18.70
	1RB Middle (50)	1720	18.26	18.70	18.65
		1770	18.55	18.97	19.00
		1745	18.55	18.93	18.97
	1RB Low (0)	1720	18.58	18.95	19.00
		1770	18.21	18.70	18.69
		1745	18.29	18.83	18.79
	50RB High (50)	1720	18.31	18.81	18.89
		1770	18.40	18.41	18.70
		1745	18.38	18.42	18.68
	50RB Middle (25)	1720	18.42	18.44	18.76
		1770	18.38	18.44	18.72
		1745	18.45	18.49	18.74
	50RB Low (0)	1720	18.45	18.44	18.71
		1770	18.37	18.45	18.72
		1745	18.38	18.42	18.69
	100RB (0)	1720	18.37	18.37	18.72
		1770	18.39	18.41	18.67
		1745	18.41	18.44	18.70
		1720	18.40	18.41	18.71

The conducted power measurement results of uplink LTE CA Condued Power are as below)-Normal Power:

DL LTE CA Class	PCC								SCC			Power	
	PC C Band	PCC Band width (MHz)	PCC UL RB size	PCC UL RB offset	PCC DL RB size	PCC DL RB offset	PCC UL Channel	PCC DL Channel	SCC Band	SCC Band width (MHz)	SCC DL Channel	Rel 8 LTETx Power(dB m)	Rel 10 DL LTE CA Tx Power(dB m)
41C	41	20	50	25	100	0	39750	39750	41	20	39948	24.84	21.15

The conducted power measurement results of downlink LTE CA Condued Power are as below (2CA)-Normal Power:

L LTE CA Class	PCC								SCC			Power	
	PC C Band	PCC Band width (MHz)	PCC UL RB size	PCC UL RB offset	PCC DL RB size	PCC DL RB offset	PCC UL Channel	PCC DL Channel	SCC Band	SCC Band width (MHz)	SCC DL Channel	Rel 8 LTETx Power(dB m)	Rel 10 DL LTE CA Tx Power(dBm)
5A-5A	5	5	1	12	25	0	20625	2625	5	3	2586	22.31	22.94
5A-2A	5	5	1	12	25	0	20625	2625	2	20	900	22.31	22.17
5A-4A	5	5	1	12	25	0	20625	2625	4	20	2175	22.31	22.15
5B	5	5	1	12	25	0	20625	2625	5	3	2586	22.31	22.37
5A-7A	5	5	1	12	25	0	20625	2625	7	20	3100	22.31	22.30
5A-66A	5	5	1	12	25	0	20625	2625	66	20	66786	22.31	22.12
7A-7A	7	20	1	50	100	0	21100	3100	7	15	3400	23.31	23.17
7A-5A	7	20	1	50	100	0	21100	3100	5	10	2525	23.31	23.16
7A-12A	7	20	1	50	100	0	21100	3100	12	10	5095	23.31	23.24
12B	12	10	1	24	50	0	23130	5130	12	5	5058	22.65	22.51
12A-2A	12	5	1	12	25	0	23035	5035	2	20	900	22.40	22.38
12A-4A	12	5	1	12	25	0	23035	5035	4	20	2175	22.40	22.29
12A-7A	12	5	1	12	25	0	23035	5035	7	20	3100	22.40	22.34
12A-66A	12	5	1	12	25	0	23035	5035	66	20	66786	22.40	22.21
13A-2A	13	10	1	24	50	0	23230	5230	2	20	900	23.03	22.93
13A-4A	13	10	1	24	50	0	23230	5230	4	20	2175	23.03	22.71
13A-66A	13	10	1	24	50	0	23230	5230	66	20	66786	23.03	22.59
25A-25A	25	20	1	50	100	0	26590	8590	25	20	8365	23.04	22.83
25A-26A	25	20	1	50	100	0	26590	8590	26	15	8865	23.04	22.71
26A-25A	26	15	1	37	75	0	26965	8965	25	20	8365	23.05	22.95
A-41APC2	41	20	1	50	100	0	39750	39750	41	20	41490	26.14	26.04
41C PC2	41	20	1	50	100	0	39750	39750	41	20	39948	26.14	25.97
A-41APC3	41	20	1	50	100	0	39750	39750	41	20	41490	23.26	23.11
41C PC2	41	20	1	50	100	0	39750	39750	41	20	39948	23.26	23.08
66A-66A	66	5	1	12	25	0	132647	67111	66	20	66536	23.13	22.93
66B	66	5	1	12	25	0	132647	67111	66	15	67204	23.13	22.85
66C	66	5	1	12	25	0	132647	67111	66	20	67228	23.13	22.94

66A-2A	66	5	1	12	25	0	132647	67111	2	20	900	23.13	23.01
66A-5A	66	5	1	12	25	0	132647	67111	5	10	2525	23.13	23.11
66A-12A	66	5	1	12	25	0	132647	67111	12	10	5095	23.13	23.10
66A-13A	66	5	1	12	25	0	132647	67111	13	10	5230	23.13	23.02
66A-71A	66	5	1	12	25	0	132647	67111	71	20	68786	23.13	22.96
71A-2A	71	5	1	12	25	0	133297	68761	2	20	900	23.36	22.89
71A-4A	71	5	1	12	25	0	133297	68761	4	20	2175	23.36	23.11
71A-66A	71	5	1	12	25	0	133297	68761	66	20	66786	23.36	23.04

The conducted power measurement results of downlink LTE CA Conducted Power are as below
(2CA)-Low Power:

LTE CA Class	PCC								SCC			Power	
	PCC Band	PCC Band width (MHz)	PCC UL RB size	PCC UL RB offset	PCC DL RB size	PCC DL RB offset	PCC UL Channel	PCC DL Channel	SCC Band	SCC Band width (MHz)	SCC DL Channel	Rel 8 LTE Tx Power(dBm)	Rel 10 DL LTE CA Tx Power(dBm)
7A-7A	7	20	1	50	100	0	21350	3350	7	20	2850	19.89	19.72
7A-5A	7	20	1	50	100	0	21350	3350	5	10	2525	19.89	19.67
7A-12A	7	20	1	50	100	0	21350	3350	12	10	5095	19.89	19.83
25A-25A	25	20	1	50	100	0	26590	8590	25	20	8365	18.72	18.69
25A-26A	25	20	1	50	100	0	26590	8590	26	15	8865	18.72	18.53
A-41APC2	41	20	1	50	100	0	39750	39750	41	20	41490	23.87	23.71
41C PC2	41	20	1	50	100	0	39750	39750	41	20	39948	23.87	23.66
A-41APC3	41	20	1	50	100	0	39750	39750	41	20	41490	20.99	20.83
41C PC2	41	20	1	50	100	0	39750	39750	41	20	39948	20.99	20.81
66A-66A	66	20	1	50	100	0	132072	66536	66	20	66786	18.58	18.37
66B	66	5	1	12	25	0	131997	66461	66	5	66509	18.19	18.10
66C	66	20	1	50	100	0	132072	66536	66	20	66734	18.58	18.47
66A-2A	66	20	1	50	100	0	132072	66536	2	20	900	18.58	18.43
66A-5A	66	20	1	50	100	0	132072	66536	5	10	2525	18.58	18.32
66A-12A	66	20	1	50	100	0	132072	66536	12	10	5095	18.58	18.42
66A-13A	66	20	1	50	100	0	132072	66536	13	10	5230	18.58	18.52
66A-71A	66	20	1	50	100	0	132072	66536	71	20	68786	18.58	18.57

11.4 Wi-Fi and BT Measurement result

The maximum output power of BT is 8.77dBm.

The maximum tune up of BT is 9dBm.

For Wifi antenna, there are three sets of tune-up power, Normal power and Low power (Receiver on / Sensor)

Table: Summary of Receiver detection mechanism

Normal power	Low Power-Receiver on	Low Power-Sensor
Power Level A	Power Level B	Power Level C

The average conducted power for Wi-Fi is as following:

Power Level A

FCC									
802.11b(dBm)									
Channel\data rate	1Mbps	2Mbps	5.5Mbps	11Mbps					
11(2462MHz)	22.27	/	/	/					
6(2437MHz)	22.69	22.47	22.54	22.37					
1(2412MHz)	22.20	/	/	/					
Tune up	24.00	24.00	24.00	24.00					
802.11g(dBm)									
Channel\data rate	6Mbps	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps	
11(2462MHz)	19.01	/	/	/	/	/	/	/	
6(2437MHz)	19.72	19.22	19.19	18.69	18.39	17.77	16.82	16.42	
1(2412MHz)	19.61	/	/	/	/	/	/	/	
Tune up	21.00	20.50	20.50	20.00	19.50	19.00	18.50	18.00	
802.11n(dBm)-20MHz									
Channel\data rate	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	
11(2462MHz)	19.14	/	/	/	/	/	/	/	
6(2437MHz)	19.52	18.93	18.87	18.63	18.13	17.25	16.71	16.25	
1(2412MHz)	19.27	/	/	/	/	/	/	/	
Tune up	21.00	20.50	20.50	20.00	19.50	19.00	18.50	18.00	

5GHz									
802.11a(dBm)									
Channel\data rate	6Mbps	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps	
36(5180 MHz)	18.74								
40(5200 MHz)	18.36								
44(5220 MHz)	18.24								
48(5240 MHz)	18.75	17.92	18.00	17.62	17.23	16.69	15.85	15.22	
52(5260 MHz)	18.04								
56(5280 MHz)	18.06								
60(5300 MHz)	18.55								
64(5320 MHz)	18.91	18.42	18.59	18.33	17.79	17.26	16.37	15.82	
100(5500 MHz)	18.79								
104(5520 MHz)	18.04								
108(5540 MHz)	18.31								
112(5560 MHz)	18.26								
116(5580 MHz)	19.61	18.78	18.86	18.48	18.09	17.55	16.71	16.08	
120(5600 MHz)	18.80								
124(5620 MHz)	19.11								
128(5640 MHz)	19.09								
132(5660 MHz)	18.18								
136(5680 MHz)	18.30								
140(5700 MHz)	18.75								
144(5720 MHz)	18.55								
149(5745 MHz)	19.93	19.41	19.50	19.06	18.70	18.23	17.50	16.95	
153(5765 MHz)	19.86								
157(5785 MHz)	18.96								
161(5805 MHz)	18.91								
165(5825 MHz)	18.88								
Tune up	20.00	19.50	19.50	19.50	19.00	18.50	17.50	17.00	

Power Level B

FCC									
802.11b(dBm)									
Channel\data rate	1Mbps	2Mbps	5.5Mbps	11Mbps					
11(2462MHz)	13.22	/	/	/					
6(2437MHz)	13.53	13.49	13.51	13.46					
1(2412MHz)	13.39	/	/	/					
Tune up	14.00	14.00	14.00	14.00					
802.11g(dBm)									
Channel\data rate	6Mbps	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps	
11(2462MHz)	13.18	/	/	/	/	/	/	/	
6(2437MHz)	13.64	13.58	13.52	13.51	13.50	13.48	13.16	13.13	
1(2412MHz)	13.31	/	/	/	/	/	/	/	
Tune up	14.00	14.00	14.00	14.00	14.00	14.00	14.00	14.00	
802.11n(dBm)-20MHz									
Channel\data rate	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	
11(2462MHz)	13.02	/	/	/	/	/	/	/	
6(2437MHz)	13.43	13.42	13.35	13.40	13.38	13.07	13.03	13.07	
1(2412MHz)	13.13	/	/	/	/	/	/	/	
Tune up	14.00	14.00	14.00	14.00	14.00	14.00	14.00	14.00	

5GHz										
802.11ac(dBm)-80MHz										
Channel\data rate	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9
42(5210 MHz)	12.12	12.04	12.18	12.08	12.13	11.73	11.70	11.61	11.69	11.52
58(5290 MHz)	11.18	11.47	11.61	11.51	11.56	11.16	11.13	11.04	11.12	1.03
106(5530 MHz)	11.47	/	11.82	/	/	/	/	/	/	/
122(5610 MHz)	12.61	12.49	12.63	12.53	12.58	12.18	12.15	12.06	12.14	11.97
138(5690 MHz)	12.00	/	12.13	/	/	/	/	/	/	/
Tune up	13.00	13.00	13.50	13.50	13.50	13.00	13.00	13.00	13.00	13.00
155(5775 MHz)	12.69	13.00	13.14	13.04	13.09	12.69	12.66	12.57	12.65	12.48
Tune up	13.50	13.50	13.50	13.50	13.50	13.00	13.00	13.00	13.00	13.00

Power Level C

FCC								
802.11b(dBm)								
Channel\data rate	1Mbps	2Mbps	5.5Mbps	11Mbps				
11(2462MHz)	16.02	/	/	/				
6(2437MHz)	16.34	16.29	16.31	16.26				
1(2412MHz)	16.28	/	/	/				
Tune up	17.00	17.00	17.00	17.00				
802.11g(dBm)								
Channel\data rate	6Mbps	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
11(2462MHz)	16.22	/	/	/	/	/	/	/
6(2437MHz)	16.91	16.84	16.76	16.75	16.74	16.71	16.32	16.28
1(2412MHz)	16.47	/	/	/	/	/	/	/
Tune up	17.00	17.00	17.00	17.00	17.00	17.00	17.00	17.00
802.11n(dBm)-20MHz								
Channel\data rate	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
11(2462MHz)	16.09	/	/	/	/	/	/	/
6(2437MHz)	16.64	16.63	16.54	16.60	16.58	16.19	16.15	16.19
1(2412MHz)	16.31	/	/	/	/	/	/	/
Tune up	17.00	17.00	17.00	17.00	17.00	17.00	17.00	17.00


5GHz										
802.11ac(dBm)-80MHz										
Channel\data rate	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9
42(5210 MHz)	16.10	15.80	15.62	15.32	14.85	13.90	13.92	13.29	12.89	12.39
58(5290 MHz)	16.70	16.40	16.38	15.92	15.45	14.50	14.52	13.89	13.49	12.99
Tune up	18	17.00	17.00	17.00	16.50	15.00	15.00	15.00	14.00	14.00
106(5530 MHz)	16.55	/	/	/	/	/	/	/	/	/
122(5610 MHz)	17.01	16.71	16.69	16.23	15.76	14.81	14.83	14.20	13.80	13.30
138(5690 MHz)	16.25	/	/	/	/	/	/	/	/	/
Tune up	18	17.00	17.00	17.00	16.50	16.00	16.00	15.00	14.00	14.00
155(5775 MHz)	17.42	17.12	17.10	16.64	16.17	15.22	15.24	14.61	14.21	13.71
Tune up	18	18	18	18	17	16	16	15	15	14

12 Simultaneous TX SAR Considerations

12.1 Introduction

The following procedures adopted from “FCC SAR Considerations for Cell Phones with Multiple Transmitters” are applicable to handsets with built-in unlicensed transmitters such as 802.11 a/b/g and Bluetooth devices which may simultaneously transmit with the licensed transmitter. For this device, the BT and Wi-Fi can transmit simultaneous with other transmitters.

12.2 Transmit Antenna Separation Distances



Antenna	Mode	Band
1# (ANT1) TX/RX	GSM	2, 3, 5, 8
	CDMA	BC0/BC1/BC10
	WCDMA	1, 2, 4, 5, 8
	LTE	1, 2, 3, 4, 5, 7, 8, 12, 13, 17, 20, 25, 26, 28, 38, 39, 40, 41, 66, 71
2# (ANT2) RX	GSM	2, 3, 5, 8
	CDMA	BC0/BC1/BC10
	WCDMA	1, 2, 4, 5, 8
	LTE	1, 2, 3, 4, 5, 7, 8, 12, 13, 17, 20, 25, 26, 28, 38, 39, 40, 41, 66, 71
3#	WIFI 2.4G	2.4G
	GPS	GPS
	BT	BT
4#	WIFI 5G	5G

Picture 12.1 Antenna Locations

12.3 SAR Measurement Positions

According to the KDB941225 D06 Hot Spot SAR v01, the edges with less than 2.5 cm distance to the antennas need to be tested for SAR.

SAR measurement positions						
Mode	Front	Rear	Left edge	Right edge	Top edge	Bottom edge
Main antenna	Yes	Yes	Yes	Yes	No	Yes
WLAN	Yes	Yes	No	Yes	Yes	No

12.4 Standalone SAR Test Exclusion Considerations

Standalone 1-g head or body SAR evaluation by measurement or numerical simulation is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied. The 1-g SAR test exclusion threshold for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \right] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR, where}$$

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Table 12.1: Standalone SAR test exclusion considerations

Band/Mode	F(GHz)	Position	SAR test exclusion threshold(mW)	RF output power		SAR test exclusion
				dBm	mW	
Bluetooth	2.441	Head	9.60	9	7.9	Yes
		Body	19.20	9	7.9	Yes
2.4GHz WLAN	2.45	Head	9.58	24	251.19	No
		Body	19.17	24	251.19	No
5GHz WLAN	5.2	Head	6.58	20	100	No
		Body	13.16	20	100	No
	5.3	Head	6.52	20	100	No
		Body	13.03	20	100	No
	5.6	Head	6.34	20	100	No
		Body	12.68	20	100	No
	5.8	Head	6.23	20	100	No
		Body	12.46	20	100	No

13 Evaluation of Simultaneous

Table 13.1: The sum of reported SAR values for main antenna and WiFi2.4G

	Position	Main antenna	WiFi	Sum
Highest reported SAR value for Head	Left hand, Tilt	0.26	0.57	0.83
Highest reported SAR value for Body	Bottom 10mm	1.27	/	1.27

Table 13.2: The sum of reported SAR values for main antenna and WiFi5G

	Position	Main antenna	WiFi	Sum
Highest reported SAR value for Head	Left hand, Touch cheek	0.37	0.55	0.92
Highest reported SAR value for Body	Bottom 10mm	1.27	/	1.27

Table 13.3: The sum of reported SAR values for main antenna and BT

	Position	Main antenna	BT	Sum
Maximum reported SAR value for Head	Right hand, Touch cheek	0.42	0.33 ^[1]	0.75
Maximum reported SAR value for Body	Bottom 10mm	1.27	/	1.27

[1] - Estimated SAR for Bluetooth (see the table 13.3)

Table 13.4: Estimated SAR for Bluetooth

Mode/Band	F (GHz)	Position	Distance (mm)	Upper limit of power *		Estimated _{1g} (W/kg)
				dBm	mW	
Bluetooth	2.441	Head	5	9	7.9	0.33
Bluetooth	2.441	Body	10	9	7.9	0.17

* - Maximum possible output power declared by manufacturer

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance,mm)]·[√f(GHz)/x] W/kg for test separation distances ≤ 50 mm;

where x = 7.5 for 1-g SAR.

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine



No.I19Z62374-SEM09

SAR test exclusion

Conclusion:

According to the above tables, the sum of reported SAR values is $<1.6\text{W/kg}$. So the simultaneous transmission SAR with volume scans is not required.

14 SAR Test Result

It is determined by user manual for the distance between the EUT and the phantom bottom. The distance is 10 mm or 15mm and just applied to the condition of body worn accessory.

It is performed for all SAR measurements with area scan based 1-g SAR estimation (Fast SAR). A zoom scan measurement is added when the estimated 1-gSAR is the highest measured SAR in each exposure configuration, wireless mode and frequency band combination or more than 1.2W/kg.

The calculated SAR is obtained by the following formula:

$$\text{Reported SAR} = \text{Measured SAR} \times 10^{(P_{\text{Target}} - P_{\text{Measured}})/10}$$

Where P_{Target} is the power of manufacturing upper limit;

P_{Measured} is the measured power in chapter 11.

Table 14.1: Duty Cycle

Mode	Duty Cycle
Speech for GSM850/1900	1:2
GPRS&EGPRS for GSM850/1900- Normal Power	1:2
GPRS&EGPRS for GSM1900-Low Power	1:4
WCDMA<E FDD	1:1
LTE B41 PC2	1:2.309
LTE B41 PC3	1:1.58

Note;

H1: the headset of GH59-15054A by Yuenchang

H2: the headset of GH59-15054A by Almusglobal

H3: the headset of GH59-15054A by ESTEC

14.1 SAR results for Fast SAR

Table 14.1-1: SAR Values (GSM 850 MHz Band - Head)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C					
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
190	836.6	Left	Touch	/	29.00	30.00	0.197	0.25	0.241	0.30	-0.03
190	836.6	Left	Tilt	/	29.00	30.00	0.164	0.21	0.210	0.26	0.10
251	848.8	Right	Touch	Fig.1	28.99	30.00	0.230	0.29	0.303	0.38	0.00
190	836.6	Right	Touch	/	29.00	30.00	0.215	0.27	0.286	0.36	-0.10
128	824.2	Right	Touch	/	29.07	30.00	0.212	0.26	0.282	0.35	-0.12
190	836.6	Right	Tilt	/	29.00	30.00	0.133	0.17	0.168	0.21	0.12

Note: the head SAR of GSM850 is tested with GPRS (4Txslots) mode because of VoIP.

Table 14.1-2: SAR Values (GSM 850 MHz Band - Body)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C					
Frequency		Mode (number of timeslots)	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
190	836.6	GPRS (4)	Front	/	29.00	30.00	0.230	0.29	0.310	0.39	-0.13
251	848.8	GPRS (4)	Rear		28.99	30.00	0.230	0.29	0.300	0.38	-0.07
190	836.6	GPRS (4)	Rear	Fig.2	29.00	30.00	0.270	0.34	0.360	0.45	-0.03
128	824.2	GPRS (4)	Rear	/	29.07	30.00	0.263	0.33	0.349	0.43	0.13
190	836.6	GPRS (4)	Left	/	29.00	30.00	0.255	0.32	0.317	0.40	0.04
190	836.6	GPRS (4)	Right	/	29.00	30.00	0.174	0.22	0.219	0.28	-0.10
190	836.6	GPRS (4)	Bottom	/	29.00	30.00	0.192	0.24	0.329	0.41	-0.07
190	836.6	EGPRS (4)	Rear	/	28.98	30.00	0.258	0.33	0.344	0.44	0.01

Note: The distance between the EUT and the phantom bottom is 10mm.

Table 14.1-3: SAR Values (GSM 1900 MHz Band - Head)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5 °C					
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
810	1909.8	Left	Touch	Fig.3	26.02	27.50	0.079	0.11	0.131	0.18	0.10
661	1880	Left	Touch	/	26.08	27.50	0.069	0.10	0.112	0.16	-0.06
512	1850.2	Left	Touch	/	26.16	27.50	0.053	0.07	0.089	0.12	0.09
661	1880	Left	Tilt	/	26.08	27.50	0.035	0.05	0.048	0.07	-0.03
661	1880	Right	Touch	/	26.08	27.50	0.039	0.05	0.058	0.08	0.03
661	1880	Right	Tilt	/	26.08	27.50	0.029	0.04	0.044	0.06	0.09

Note: the head SAR of GSM1900 is tested with GPRS (4Txslots) mode because of VoIP.

Table 14.1-4: SAR Values (GSM 1900 MHz Band - Body)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5 °C					
Frequency		Mode (number of timeslots)	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
661	1880	GPRS (2)	Front	/	25.09	26.00	0.282	0.35	0.481	0.59	0.13
810	1909.8	GPRS (2)	Rear	/	25.10	26.00	0.509	0.63	0.948	1.17	-0.02
661	1880	GPRS (2)	Rear	/	25.09	26.00	0.506	0.62	0.921	1.14	-0.13
512	1850.2	GPRS (2)	Rear	/	25.14	26.00	0.329	0.40	0.527	0.64	0.05
810	1909.8	GPRS (2)	Bottom	Fig.4	25.10	26.00	0.562	0.69	1.03	1.27	-0.11
661	1880	GPRS (2)	Bottom	/	25.09	26.00	0.513	0.63	0.962	1.19	-0.03
512	1850.2	GPRS (2)	Bottom	/	25.14	26.00	0.338	0.41	0.610	0.74	-0.01
661	1880	GPRS (4)	Front	Note2	26.08	27.50	0.219	0.30	0.366	0.51	-0.02
661	1880	GPRS (4)	Rear	Note3	26.08	27.50	0.136	0.19	0.216	0.30	-0.11
661	1880	GPRS (4)	Left	/	26.08	27.50	0.086	0.12	0.137	0.19	0.06
661	1880	GPRS (4)	Right	/	26.08	27.50	0.109	0.15	0.193	0.27	-0.13
661	1880	GPRS (4)	Bottom	Note3	26.08	27.50	0.284	0.39	0.470	0.65	0.03
810	1909.8	EGPRS (2)	Bottom	/	25.09	26.00	0.536	0.66	1.01	1.25	0.06
810	1909.8	GPRS (2)	Bottom	H1	25.10	26.00	0.391	0.48	0.722	0.89	0.05
810	1909.8	GPRS (2)	Bottom	H2	25.10	26.00	0.376	0.46	0.701	0.86	0.08
810	1909.8	GPRS (2)	Bottom	H3	25.10	26.00	0.388	0.48	0.716	0.88	0.01

Note1: The distance between the EUT and the phantom bottom is 10mm

Note2: The distance between the EUT and the phantom bottom is 15mm by sensor (See detail in annex I).

Note3: The distance between the EUT and the phantom bottom is 21mm by sensor (See detail in annex I).

Note4: As the headset port is located at the bottom side and the device cannot be positioned at the distance of 10mm for bottom side with headset by design, so the bottom side with headset is positioned directly against the flat phantom. The distance between the EUT and the phantom bottom is 18mm.

Table 14.1-5: SAR Values (WCDMA 1900 MHz Band - Head)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C					
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
9938	1907.6	Left	Touch	/	22.95	24.50	0.095	0.14	0.155	0.22	0.11
9800	1880	Left	Touch	/	22.94	24.50	0.072	0.10	0.118	0.17	0.03
9662	1852.4	Left	Touch	Fig.5	22.97	24.50	0.101	0.14	0.164	0.23	-0.01
9800	1880	Left	Tilt	/	22.94	24.50	0.039	0.06	0.065	0.09	0.07
9800	1880	Right	Touch	/	22.94	24.50	0.050	0.07	0.074	0.11	-0.12
9800	1880	Right	Tilt	/	22.94	24.50	0.049	0.07	0.078	0.11	-0.05

Table 14.1-6: SAR Values (WCDMA 1900 MHz Band - Body)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5 °C				
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz									
9800	1880	Front	/	18.64	20.00	0.104	0.14	0.172	0.24	-0.06
9800	1880	Rear	/	18.64	20.00	0.164	0.22	0.285	0.39	-0.06
9800	1880	Bottom	/	18.64	20.00	0.178	0.24	0.316	0.43	-0.12
9800	1880	Front	Note2	22.94	24.50	0.222	0.32	0.350	0.50	0.10
9800	1880	Rear	Note3	22.94	24.50	0.228	0.33	0.359	0.51	0.12
9800	1880	Left	/	22.94	24.50	0.111	0.16	0.189	0.27	-0.03
9800	1880	Right	/	22.94	24.50	0.069	0.10	0.107	0.15	-0.04
9938	1907.6	Bottom	Note3 Fig.6	22.95	24.50	0.323	0.46	0.530	0.76	0.09
9800	1880	Bottom	Note3	22.94	24.50	0.291	0.42	0.478	0.68	-0.08
9662	1852.4	Bottom	Note3	22.97	24.50	0.302	0.43	0.506	0.72	-0.04

Note1: The distance between the EUT and the phantom bottom is 10mm

Note2: The distance between the EUT and the phantom bottom is 15mm by sensor (See detail in annex I).

Note3: The distance between the EUT and the phantom bottom is 21mm by sensor (See detail in annex I).

Table 14.1-7: SAR Values (WCDMA 1700 MHz Band - Head)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C					
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
1513	1752.6	Left	Touch	Fig.7	23.04	24.50	0.080	0.11	0.124	0.17	0.12
1412	1732.4	Left	Touch	/	23.02	24.50	0.077	0.11	0.113	0.16	-0.01
1312	1712.4	Left	Touch	/	23.05	24.50	0.067	0.09	0.102	0.14	-0.08
1412	1732.4	Left	Tilt	/	23.02	24.50	0.039	0.05	0.059	0.08	0.06

1412	1732.4	Right	Touch	/	23.02	24.50	0.051	0.07	0.071	0.10	-0.06
1412	1732.4	Right	Tilt	/	23.02	24.50	0.030	0.04	0.043	0.06	-0.01

Table 14.1-8: SAR Values (WCDMA 1700 MHz Band - Body)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C				
Frequency		Test Position	Figure No.	Conduc ted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz									
1412	1732.5	Front	/	18.58	20.00	0.118	0.16	0.204	0.28	0.00
1412	1732.5	Rear	/	18.58	20.00	0.231	0.32	0.419	0.58	0.03
1412	1732.5	Bottom	/	18.58	20.00	0.252	0.35	0.451	0.63	0.08
1412	1732.5	Front	Note2	23.02	24.50	0.270	0.38	0.444	0.62	0.06
1412	1732.5	Rear	Note3	23.02	24.50	0.289	0.41	0.458	0.64	-0.12
1412	1732.5	Left	/	23.02	24.50	0.119	0.17	0.206	0.29	-0.10
1412	1732.5	Right	/	23.02	24.50	0.075	0.11	0.130	0.18	-0.12
1513	1752.6	Bottom	Note3 Fig.8	23.04	24.50	0.397	0.56	0.645	0.90	-0.02
1412	1732.5	Bottom	Note3	23.02	24.50	0.373	0.52	0.604	0.85	-0.12
1312	1712.4	Bottom	Note3	23.05	24.50	0.331	0.46	0.532	0.74	0.05

Note1: The distance between the EUT and the phantom bottom is 10mm

Note2: The distance between the EUT and the phantom bottom is 15mm by sensor (See detail in annex I).

Note3: The distance between the EUT and the phantom bottom is 21mm by sensor (See detail in annex I).

Table 14.1-9: SAR Values (WCDMA 850 MHz Band - Head)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C					
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
4182	836.4	Left	Touch	/	23.45	25.00	0.191	0.27	0.251	0.36	-0.04
4182	836.4	Left	Tilt	/	23.45	25.00	0.141	0.20	0.180	0.26	0.08
4233	846.6	Right	Touch	Fig.9	23.41	25.00	0.217	0.31	0.288	0.42	0.05
4182	836.4	Right	Touch	/	23.45	25.00	0.210	0.30	0.285	0.41	-0.08
4132	826.4	Right	Touch	/	23.45	25.00	0.191	0.27	0.252	0.36	-0.11
4182	836.4	Right	Tilt	/	23.45	25.00	0.115	0.16	0.147	0.21	0.13

Table 14.1-10: SAR Values (WCDMA 850 MHz Band - Body)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C				
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz									
4182	836.4	Front	/	23.45	25.00	0.135	0.19	0.206	0.29	0.11
4233	846.6	Rear	Fig.10	23.41	25.00	0.214	0.31	0.355	0.51	0.00
4182	836.4	Rear	/	23.45	25.00	0.174	0.25	0.270	0.39	-0.05
4132	826.4	Rear	/	23.45	25.00	0.108	0.15	0.281	0.40	0.11
4182	836.4	Left	/	23.45	25.00	0.146	0.21	0.220	0.31	0.09
4182	836.4	Right	/	23.45	25.00	0.100	0.14	0.144	0.21	-0.01
4182	836.4	Bottom	/	23.45	25.00	0.127	0.18	0.227	0.32	-0.07

Note: The distance between the EUT and the phantom bottom is 10mm.

Table 14.1-11: SAR Values (CDMA BC0 - Head)

Ambient Temperature: 22.9 °C					Liquid Temperature: 22.5°C						
Frequency		Side	Test Position	Figure No.	Conduct ed Power (dBm)	Max. tune-up Power (dBm)	Measure d SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reporte d SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
384	836.52	Left	Touch	/	24.02	25.00	0.101	0.13	0.109	0.14	-0.06
384	836.52	Left	Tilt	/	24.02	25.00	0.061	0.08	0.071	0.09	0.10
777	848.31	Right	Touch	/	23.92	25.00	0.140	0.18	0.195	0.25	0.09
384	836.52	Right	Touch	Fig.11	24.02	25.00	0.197	0.25	0.256	0.32	0.02
1013	824.7	Right	Touch	/	23.90	25.00	0.132	0.17	0.168	0.22	0.04
384	836.52	Right	Tilt	/	24.02	25.00	0.132	0.17	0.191	0.24	0.01

Table 14.1-12: SAR Values (CDMA BC0 - Body)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C				
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz									
384	836.52	Front	/	23.95	25.00	0.217	0.28	0.355	0.45	-0.07
777	848.31	Rear	/	23.84	25.00	0.223	0.29	0.375	0.49	0.11
384	836.52	Rear	Fig.12	23.95	25.00	0.291	0.37	0.488	0.62	0.07
1013	824.7	Rear	/	23.81	25.00	0.269	0.35	0.461	0.61	-0.05
384	836.52	Left	/	23.95	25.00	0.193	0.25	0.303	0.39	0.03
384	836.52	Right	/	23.95	25.00	0.081	0.10	0.123	0.16	0.03
384	836.52	Bottom	/	23.95	25.00	0.209	0.27	0.394	0.50	-0.05

Note1: The distance between the EUT and the phantom bottom is 10mm

Table 14.1-13: SAR Values (CDMA BC1 - Head)

Ambient Temperature: 22.9 °C Liquid Temperature: 22.5°C											
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
600	1880	Left	Touch	/	23.97	25.00	0.022	0.03	0.029	0.04	0.05
600	1880	Left	Tilt	/	23.97	25.00	0.032	0.04	0.044	0.06	-0.07
1175	1908.75	Right	Touch	/	23.95	25.00	0.035	0.04	0.051	0.06	-0.02
600	1880	Right	Touch	Fig.13	23.97	25.00	0.050	0.06	0.078	0.10	0.13
25	1851.25	Right	Touch	/	24.05	25.00	0.035	0.04	0.050	0.06	0.01
600	1880	Right	Tilt	/	23.97	25.00	0.041	0.05	0.063	0.08	-0.12

Table 14.1-14: SAR Values (CDMA BC1 - Body)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C				
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz									
600	1880	Front	/	17.16	18	0.078	0.09	0.133	0.16	0.07
600	1880	Rear	/	17.16	18	0.122	0.15	0.22	0.27	-0.06
600	1880	Bottom	/	17.16	18	0.126	0.15	0.227	0.28	-0.02
600	1880	Front	Note2	23.84	25	0.228	0.30	0.379	0.50	-0.08
600	1880	Rear	/	23.84	25	0.23	0.30	0.379	0.50	0.08
600	1880	Left	/	23.84	25	0.107	0.14	0.179	0.23	-0.04
600	1880	Right	/	23.84	25	0.114	0.15	0.21	0.27	-0.10
1175	1908.75	Bottom	Note3	23.86	25	0.259	0.34	0.432	0.56	0.08
600	1880	Bottom	Note3 Fig.14	23.84	25	0.279	0.36	0.46	0.60	0.02
25	1851.25	Bottom	Note3	23.96	25	0.229	0.29	0.391	0.50	0.06

Note1: The distance between the EUT and the phantom bottom is 10mm

Note2: The distance between the EUT and the phantom bottom is 15mm by sensor (See detail in annex I).

Note3: The distance between the EUT and the phantom bottom is 21mm by sensor (See detail in annex I).

Table 14.1-15: SAR Values (CDMA BC10 - Head)

Ambient Temperature: 22.9 °C Liquid Temperature: 22.5°C											
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
580	820.5	Left	Touch	/	24.45	25.00	0.156	0.18	0.191	0.22	0.06
580	820.5	Left	Tilt	/	24.45	25.00	0.180	0.20	0.233	0.26	0.11
684	823.1	Right	Touch	/	24.39	25.00	0.159	0.18	0.210	0.24	-0.10

580	820.5	Right	Touch	Fig.15	24.45	25.00	0.190	0.22	0.246	0.28	0.09
476	817.9	Right	Touch	/	24.34	25.00	0.173	0.20	0.225	0.26	0.05
580	820.5	Right	Tilt	/	24.45	25.00	0.097	0.11	0.138	0.16	-0.05

Table 14.1-16: SAR Values (CDMA BC10 - Body)

Ambient Temperature: 22.9℃						Liquid Temperature: 22.5℃				
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz									
580	820.5	Front	/	23.95	25.00	0.217	0.28	0.355	0.45	-0.07
684	823.1	Rear	/	23.84	25.00	0.223	0.29	0.375	0.49	0.11
580	820.5	Rear	Fig.16	23.95	25.00	0.291	0.37	0.488	0.62	0.07
476	817.9	Rear	/	23.81	25.00	0.269	0.35	0.461	0.61	-0.05
580	820.5	Left	/	23.95	25.00	0.193	0.25	0.303	0.39	0.03
580	820.5	Right	/	23.95	25.00	0.081	0.10	0.123	0.16	0.03
580	820.5	Bottom	/	23.95	25.00	0.209	0.27	0.394	0.50	-0.05

Note1: The distance between the EUT and the phantom bottom is 10mm

Table 14.1-17: SAR Values (LTE Band7 - Head)

Ambient Temperature: 22.9 °C							Liquid Temperature: 22.5 °C					
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz											
21100	2535	1RB_Mid	Left	Touch	Fig.17	23.10	24.50	0.086	0.12	0.148	0.20	-0.10
21100	2535	1RB_Mid	Left	Tilt	/	23.10	24.50	0.036	0.05	0.058	0.08	0.12
21100	2535	1RB_Mid	Right	Touch	/	23.10	24.50	0.057	0.08	0.087	0.12	0.06
21100	2535	1RB_Mid	Right	Tilt	/	23.10	24.50	0.056	0.08	0.102	0.14	0.09
21100	2535	50RB_Mid	Left	Touch	/	21.97	23.50	0.066	0.09	0.114	0.16	-0.01
21100	2535	50RB_Mid	Left	Tilt	/	21.97	23.50	0.031	0.04	0.049	0.07	0.06
21100	2535	50RB_Mid	Right	Touch	/	21.97	23.50	0.044	0.06	0.068	0.10	0.09
21100	2535	50RB_Mid	Right	Tilt	/	21.97	23.50	0.044	0.06	0.084	0.12	-0.13

Note1: The LTE mode is QPSK_20MHz.

Table 14.1-18: SAR Values (LTE Band7 - Body)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5 °C					
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
21325	2560	1RB_Mid	Front	/	19.89	21.00	0.094	0.12	0.178	0.23	0.07

21325	2560	1RB_Mid	Rear	Fig.18	19.89	21.00	0.156	0.20	0.291	0.38	0.05
21325	2560	1RB_Mid	Bottom	/	19.89	21.00	0.104	0.13	0.229	0.30	-0.12
21100	2535	1RB_Mid	Front	Note2	23.31	24.50	0.145	0.19	0.282	0.37	0.08
21100	2535	1RB_Mid	Rear	Note3	23.31	24.50	0.152	0.20	0.276	0.36	0.09
21100	2535	1RB_Mid	Left	/	23.31	24.50	0.152	0.20	0.283	0.37	0.11
21100	2535	1RB_Mid	Right	/	23.31	24.50	0.086	0.11	0.156	0.21	0.00
21100	2535	1RB_Mid	Bottom	Note3	23.31	24.50	0.144	0.19	0.260	0.34	-0.01
21325	2560	50RB_Mid	Front	/	19.99	21.00	0.093	0.12	0.175	0.22	0.12
21325	2560	50RB_Mid	Rear	/	19.99	21.00	0.154	0.19	0.288	0.36	-0.02
21325	2560	50RB_Mid	Bottom	/	19.99	21.00	0.102	0.13	0.224	0.28	-0.02
21100	2535	50RB_Mid	Front	Note2	21.97	23.50	0.124	0.18	0.227	0.32	-0.08
21100	2535	50RB_Mid	Rear	Note3	21.97	23.50	0.116	0.16	0.205	0.29	0.01
21100	2535	50RB_Mid	Left	/	21.97	23.50	0.114	0.16	0.210	0.30	0.03
21100	2535	50RB_Mid	Right	/	21.97	23.50	0.065	0.09	0.118	0.17	0.03
21100	2535	50RB_Mid	Bottom	Note3	21.97	23.50	0.109	0.16	0.198	0.28	-0.09

Note1: The distance between the EUT and the phantom bottom is 10mm

Note2: The distance between the EUT and the phantom bottom is 15mm by sensor (See detail in annex I).

Note3: The distance between the EUT and the phantom bottom is 21mm by sensor (See detail in annex I).

Table 14.1-19: SAR Values (LTE Band12 - Head)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C						
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz											
23095	707.5	1RB_Mid	Left	Touch	Fig.19	22.74	24.00	0.148	0.20	0.187	0.25	-0.08
23095	707.5	1RB_Mid	Left	Tilt	/	22.74	24.00	0.088	0.12	0.109	0.15	-0.01
23095	707.5	1RB_Mid	Right	Touch	/	22.74	24.00	0.119	0.16	0.152	0.20	-0.11
23095	707.5	1RB_Mid	Right	Tilt	/	22.74	24.00	0.068	0.09	0.083	0.11	0.07
23060	704	25RB_Mid	Left	Touch	/	21.74	23.00	0.134	0.18	0.172	0.23	0.08
23060	704	25RB_Mid	Left	Tilt	/	21.74	23.00	0.073	0.10	0.090	0.12	0.06
23060	704	25RB_Mid	Right	Touch	/	21.74	23.00	0.100	0.13	0.129	0.17	-0.06
23060	704	25RB_Mid	Right	Tilt	/	21.74	23.00	0.061	0.08	0.076	0.10	0.02

Note1: The LTE mode is QPSK_10MHz.

Table 14.1-20: SAR Values (LTE Band12 - Body)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C					
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
23095	707.5	1RB_Mid	Front	/	22.74	24.00	0.207	0.28	0.262	0.35	0.09
23095	707.5	1RB_Mid	Rear	Fig.20	22.74	24.00	0.274	0.37	0.354	0.47	0.04
23095	707.5	1RB_Mid	Left	/	22.74	24.00	0.252	0.34	0.347	0.46	0.08
23095	707.5	1RB_Mid	Right	/	22.74	24.00	0.170	0.23	0.231	0.31	0.10
23095	707.5	1RB_Mid	Bottom	/	22.74	24.00	0.100	0.13	0.175	0.23	0.01
23060	704	25RB_Mid	Front	/	21.74	23.00	0.171	0.23	0.217	0.29	0.09
23060	704	25RB_Mid	Rear	/	21.74	23.00	0.239	0.32	0.303	0.40	0.09
23060	704	25RB_Mid	Left	/	21.74	23.00	0.202	0.27	0.278	0.37	-0.04
23060	704	25RB_Mid	Right	/	21.74	23.00	0.144	0.19	0.194	0.26	0.11
23060	704	25RB_Mid	Bottom	/	21.74	23.00	0.093	0.12	0.164	0.22	0.06

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: The LTE mode is QPSK_10MHz.

Table 14.1-21: SAR Values (LTE Band13 - Head)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C						
Frequency		Mode	Side	Test Position	Figure No.	Conduct ed Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g)(W/kg)	Measure d SAR(1g) (W/kg)	Reporte d SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz											
23230	782	1RB_Mid	Left	Touch	Fig.21	23.03	24.00	0.218	0.27	0.285	0.36	0.02
23230	782	1RB_Mid	Left	Tilt	/	23.03	24.00	0.115	0.14	0.150	0.19	-0.07
23230	782	1RB_Mid	Right	Touch	/	23.03	24.00	0.178	0.22	0.239	0.30	-0.01
23230	782	1RB_Mid	Right	Tilt	/	23.03	24.00	0.148	0.19	0.191	0.24	-0.07
23230	782	25RB_Mid	Left	Touch	/	22.04	23.00	0.164	0.20	0.215	0.27	0.03
23230	782	25RB_Mid	Left	Tilt	/	22.04	23.00	0.087	0.11	0.113	0.14	0.08
23230	782	25RB_Mid	Right	Touch	/	22.04	23.00	0.132	0.16	0.176	0.22	-0.11
23230	782	25RB_Mid	Right	Tilt	/	22.04	23.00	0.106	0.13	0.135	0.17	0.13

Note1: The LTE mode is QPSK_10MHz.

Table 14.1-22: SAR Values (LTE Band13 - Body)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C					
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
23230	782	1RB_Mid	Front	/	23.03	24.00	0.250	0.31	0.265	0.33	-0.13
23230	782	1RB_Mid	Rear	Fig.22	23.03	24.00	0.290	0.36	0.381	0.48	0.08

23230	782	1RB_Mid	Left	/	23.03	24.00	0.320	0.40	0.369	0.46	0.09
23230	782	1RB_Mid	Right	/	23.03	24.00	0.226	0.28	0.264	0.33	-0.10
23230	782	1RB_Mid	Bottom	/	23.03	24.00	0.206	0.26	0.320	0.40	0.00
23230	782	25RB_Mid	Front	/	22.04	23.00	0.173	0.22	0.215	0.27	0.12
23230	782	25RB_Mid	Rear	/	22.04	23.00	0.270	0.34	0.285	0.36	-0.06
23230	782	25RB_Mid	Left	/	22.04	23.00	0.223	0.28	0.258	0.32	-0.05
23230	782	25RB_Mid	Right	/	22.04	23.00	0.171	0.21	0.200	0.25	-0.01
23230	782	25RB_Mid	Bottom	/	22.04	23.00	0.155	0.19	0.240	0.30	0.01

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: The LTE mode is QPSK_10MHz.

Table 14.1-23: SAR Values (LTE Band25 - Head)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C						
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz											
26590	1905	1RB_Mid	Left	Touch	Fig.23	23.04	24.00	0.145	0.18	0.243	0.30	0.02
26590	1905	1RB_Mid	Left	Tilt	/	23.04	24.00	0.048	0.06	0.079	0.10	0.11
26590	1905	1RB_Mid	Right	Touch	/	23.04	24.00	0.081	0.10	0.121	0.15	0.07
26590	1905	1RB_Mid	Right	Tilt	/	23.04	24.00	0.072	0.09	0.118	0.15	-0.04
26365	1882.5	50RB_Low	Left	Touch	/	21.96	23.00	0.133	0.17	0.223	0.28	0.01
26365	1882.5	50RB_Low	Left	Tilt	/	21.96	23.00	0.041	0.05	0.080	0.10	0.07
26365	1882.5	50RB_Low	Right	Touch	/	21.96	23.00	0.099	0.13	0.149	0.19	0.10
26365	1882.5	50RB_Low	Right	Tilt	/	21.96	23.00	0.074	0.09	0.124	0.16	-0.02

Note1: The LTE mode is QPSK_20MHz.

Table 14.1-24: SAR Values (LTE Band25 - Body)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C					
Frequency		Mode	Test Position	Figure No.	Conduc ted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
26590	1905	1RB_Mid	Front	/	18.72	20.00	0.120	0.16	0.200	0.27	-0.06
26590	1905	1RB_Mid	Rear	/	18.72	20.00	0.205	0.28	0.357	0.48	0.03
26590	1905	1RB_Mid	Bottom	/	18.72	20.00	0.227	0.30	0.407	0.55	0.11
26590	1905	1RB_Mid	Front	Note2	23.04	24.00	0.303	0.38	0.491	0.61	0.10
26590	1905	1RB_Mid	Rear	Note3	23.04	24.00	0.305	0.38	0.492	0.61	-0.05
26590	1905	1RB_Mid	Left	/	23.04	24.00	0.118	0.15	0.191	0.24	-0.13
26590	1905	1RB_Mid	Right	/	23.04	24.00	0.129	0.16	0.229	0.29	0.09
26590	1905	1RB_Mid	Bottom	Note3 Fig.24	23.04	24.00	0.363	0.45	0.598	0.75	-0.02

26590	1905	50RB_Mid	Front	/	18.68	20.00	0.116	0.16	0.194	0.26	0.03
26590	1905	50RB_Mid	Rear	/	18.68	20.00	0.199	0.27	0.347	0.47	-0.03
26590	1905	50RB_Mid	Bottom	/	18.68	20.00	0.217	0.29	0.389	0.53	0.02
26365	1882.5	50RB_Mid	Front	Note2	21.96	23.00	0.302	0.38	0.489	0.62	-0.02
26365	1882.5	50RB_Mid	Rear	Note3	21.96	23.00	0.312	0.40	0.505	0.64	-0.02
26365	1882.5	50RB_Mid	Left	/	21.96	23.00	0.125	0.16	0.122	0.16	0.00
26365	1882.5	50RB_Mid	Right	/	21.96	23.00	0.133	0.17	0.236	0.30	-0.08
26365	1882.5	50RB_Mid	Bottom	Note3	21.96	23.00	0.351	0.45	0.585	0.74	0.08

Note1: The distance between the EUT and the phantom bottom is 10mm

Note2: The distance between the EUT and the phantom bottom is 15mm by sensor (See detail in annex I).

Note3: The distance between the EUT and the phantom bottom is 21mm by sensor (See detail in annex I).

Table 14.1-25: SAR Values (LTE Band26 - Head)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5 °C						
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz											
26965	841.5	1RB_Mid	Left	Touch	/	23.05	24.50	0.163	0.23	0.267	0.37	-0.11
26965	841.5	1RB_Mid	Left	Tilt	/	23.05	24.50	0.101	0.14	0.165	0.23	-0.03
26965	841.5	1RB_Mid	Right	Touch	Fig.25	23.05	24.50	0.177	0.25	0.299	0.42	-0.12
26965	841.5	1RB_Mid	Right	Tilt	/	23.05	24.50	0.108	0.15	0.173	0.24	-0.09
26865	831.5	36RB_Low	Left	Touch	/	22.11	23.50	0.142	0.20	0.233	0.32	-0.11
26865	831.5	36RB_Low	Left	Tilt	/	22.11	23.50	0.098	0.13	0.158	0.22	0.11
26865	831.5	36RB_Low	Right	Touch	/	22.11	23.50	0.135	0.19	0.227	0.31	0.05
26865	831.5	36RB_Low	Right	Tilt	/	22.11	23.50	0.093	0.13	0.149	0.21	-0.02

Note1: The LTE mode is QPSK_15MHz.

Table 14.1-26: SAR Values (LTE Band26 - Body)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5 °C					
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
26965	841.5	1RB_Mid	Front	/	23.05	24.50	0.152	0.21	0.250	0.35	0.03
26965	841.5	1RB_Mid	Rear	Fig.26	23.05	24.50	0.204	0.28	0.337	0.47	-0.07
26965	841.5	1RB_Mid	Left	/	23.05	24.50	0.147	0.21	0.221	0.31	0.03
26965	841.5	1RB_Mid	Right	/	23.05	24.50	0.090	0.13	0.136	0.19	0.05
26965	841.5	1RB_Mid	Bottom	/	23.05	24.50	0.146	0.20	0.276	0.39	-0.09
26865	831.5	36RB_Low	Front	/	22.11	23.50	0.113	0.16	0.185	0.25	-0.05
26865	831.5	36RB_Low	Rear	/	22.11	23.50	0.149	0.21	0.244	0.34	-0.06
26865	831.5	36RB_Low	Left	/	22.11	23.50	0.111	0.15	0.168	0.23	-0.07

26865	831.5	36RB_Low	Right	/	22.11	23.50	0.072	0.10	0.109	0.15	-0.11
26865	831.5	36RB_Low	Bottom	/	22.11	23.50	0.098	0.13	0.197	0.27	0.00

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: The LTE mode is QPSK_15MHz.

Table 14.1-27: SAR Values (LTE Band41 PC2 - Head)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C						
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz											
40620	2593	1RB_Mid	Left	Touch	/	26.21	27.00	0.029	0.03	0.050	0.06	0.11
40620	2593	1RB_Mid	Left	Tilt	/	26.21	27.00	0.022	0.03	0.041	0.05	0.08
40620	2593	1RB_Mid	Right	Touch	/	26.21	27.00	0.036	0.04	0.064	0.08	-0.03
40620	2593	1RB_Mid	Right	Tilt	/	26.21	27.00	0.035	0.04	0.072	0.09	0.01
41055	2636.5	50RB_Mid	Left	Touch	/	24.90	26.00	0.040	0.05	0.072	0.09	0.12
41055	2636.5	50RB_Mid	Left	Tilt	/	24.90	26.00	0.022	0.03	0.043	0.06	-0.01
41055	2636.5	50RB_Mid	Right	Touch	Fig.27	24.90	26.00	0.053	0.07	0.095	0.12	-0.13
41055	2636.5	50RB_Mid	Right	Tilt	/	24.90	26.00	0.039	0.05	0.076	0.10	0.04
39750	2506	50RB_Mid	Right	Touch	ULCA	21.15	22.50	0.047	0.06	0.088	0.12	-0.03

Note1: The LTE mode is QPSK_20MHz.

Table 14.1-28: SAR Values (LTE Band41 PC2 - Body)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C					
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
40620	2593	1RB_Mid	Front	/	24.02	24.50	0.038	0.04	0.084	0.09	0.02
40620	2593	1RB_Mid	Rear	/	24.02	24.50	0.061	0.07	0.125	0.14	-0.02
40620	2593	1RB_Mid	Bottom	/	24.02	24.50	0.039	0.04	0.100	0.11	0.10
40620	2593	1RB_Mid	Front	Note2	26.21	27.00	0.090	0.11	0.177	0.21	0.02
40620	2593	1RB_Mid	Rear	Note3	26.21	27.00	0.044	0.05	0.086	0.10	-0.01
40620	2593	1RB_Mid	Left	/	26.21	27.00	0.078	0.09	0.164	0.20	0.03
40620	2593	1RB_Mid	Right	/	26.21	27.00	0.013	0.02	0.026	0.03	-0.01
40620	2593	1RB_Mid	Bottom	Note3	26.21	27.00	0.055	0.07	0.113	0.14	0.11
41055	2636.5	50RB_Low	Front	/	23.77	24.50	0.040	0.05	0.089	0.11	0.04
41055	2636.5	50RB_Low	Rear	/	23.77	24.50	0.061	0.07	0.130	0.15	0.07
41055	2636.5	50RB_Low	Bottom	/	23.77	24.50	0.044	0.05	0.113	0.13	-0.08
41055	2636.5	50RB_Mid	Front	Note2 Fig.28	24.90	26.00	0.096	0.12	0.187	0.24	-0.06
41055	2636.5	50RB_Mid	Rear	Note3	24.90	26.00	0.050	0.06	0.105	0.14	0.08

41055	2636.5	50RB_Mid	Left	/	24.90	26.00	0.083	0.11	0.174	0.22	0.07
41055	2636.5	50RB_Mid	Right	/	24.90	26.00	0.015	0.02	0.032	0.04	-0.06
41055	2636.5	50RB_Mid	Bottom	Note3	24.90	26.00	0.066	0.09	0.135	0.17	-0.07
39750	2506	50RB_Mid	Front	ULCA	21.15	22.50	0.066	0.09	0.120	0.16	0.06

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: The distance between the EUT and the phantom bottom is 15mm by sensor (See detail in annex I).

Note3: The distance between the EUT and the phantom bottom is 21mm by sensor (See detail in annex I).

Note4: The LTE mode is QPSK_20MHz.

Table 14.1-29: SAR Values (LTE Band41 PC3 - Head)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5 °C						
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	tune-up Power (dBm)	Measured SAR(10g)	Reported SAR(10g)	Measured SAR(1g)	Reported SAR(1g)	Power Drift (dB)
Ch.	MHz							(W/kg)	(W/kg)	(W/kg)	(W/kg)	
39750	2506	1RB_Mid	Left	Touch	/	23.26	24.00	0.052	0.06	0.098	0.12	0.11
39750	2506	1RB_Mid	Left	Tilt	/	23.26	24.00	0.047	0.06	0.090	0.11	0.01
39750	2506	1RB_Mid	Right	Touch	/	23.26	24.00	0.050	0.06	0.087	0.10	-0.11
39750	2506	1RB_Mid	Right	Tilt	/	23.26	24.00	0.064	0.08	0.129	0.15	0.07
41055	2636.5	50RB_Mid	Left	Touch	Fig.29	22.18	23.00	0.083	0.10	0.157	0.19	0.11
41055	2636.5	50RB_Mid	Left	Tilt	/	22.18	23.00	0.049	0.06	0.092	0.11	-0.06
41055	2636.5	50RB_Mid	Right	Touch	/	22.18	23.00	0.053	0.06	0.090	0.11	0.06
41055	2636.5	50RB_Mid	Right	Tilt	/	22.18	23.00	0.056	0.07	0.109	0.13	-0.06

Note1: The LTE mode is QPSK_20MHz.

Table 14.1-30: SAR Values (LTE Band41 PC3 - Body)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5 °C					
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
41055	2636.5	1RB_Mid	Front	/	21.14	22.00	0.085	0.10	0.167	0.20	0.00
41055	2636.5	1RB_Mid	Rear	Fig.30	21.14	22.00	0.095	0.12	0.177	0.22	0.09
41055	2636.5	1RB_Mid	Bottom	/	21.14	22.00	0.054	0.07	0.075	0.09	0.13
40620	2593	1RB_Mid	Front	Note2	23.26	24.00	0.019	0.02	0.034	0.04	-0.11
40620	2593	1RB_Mid	Rear	Note3	23.26	24.00	0.023	0.03	0.039	0.05	-0.09
40620	2593	1RB_Mid	Left	/	23.26	24.00	0.066	0.08	0.114	0.14	0.08
40620	2593	1RB_Mid	Right	/	23.26	24.00	0.033	0.04	0.056	0.07	-0.01
40620	2593	1RB_Mid	Bottom	Note3	23.26	24.00	0.051	0.06	0.084	0.10	0.06
41055	2636.5	50RB_Low	Front		21.03	22.00	0.084	0.11	0.166	0.21	0.05

41055	2636.5	50RB_Low	Rear	/	21.03	22.00	0.084	0.11	0.164	0.21	0.12
41055	2636.5	50RB_Low	Bottom	/	21.03	22.00	0.049	0.06	0.068	0.09	-0.03
41055	2636.5	50RB_Mid	Front	Note2	22.18	23.00	0.075	0.09	0.134	0.16	0.11
41055	2636.5	50RB_Mid	Rear	Note3	22.18	23.00	0.061	0.07	0.105	0.13	-0.10
41055	2636.5	50RB_Mid	Left	/	22.18	23.00	0.090	0.11	0.153	0.18	-0.03
41055	2636.5	50RB_Mid	Right	/	22.18	23.00	0.024	0.03	0.039	0.05	0.12
41055	2636.5	50RB_Mid	Bottom	Note3	22.18	23.00	0.064	0.08	0.117	0.14	-0.11

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: The distance between the EUT and the phantom bottom is 15mm by sensor (See detail in annex I).

Note3: The distance between the EUT and the phantom bottom is 21mm by sensor (See detail in annex I).

Note4: The LTE mode is QPSK_20MHz.

Table 14.1-31: SAR Values (LTE Band66 - Head)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5 °C						
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz											
132072	1720	1RB_Mid	Left	Touch	Fig.31	22.97	24.00	0.075	0.10	0.116	0.15	-0.10
132072	1720	1RB_Mid	Left	Tilt	/	22.97	24.00	0.031	0.04	0.046	0.06	-0.08
132072	1720	1RB_Mid	Right	Touch	/	22.97	24.00	0.054	0.07	0.078	0.10	0.00
132072	1720	1RB_Mid	Right	Tilt	/	22.97	24.00	0.048	0.06	0.078	0.10	0.00
132072	1720	50RB_Mid	Left	Touch	/	21.90	23.00	0.066	0.09	0.103	0.13	-0.12
132072	1720	50RB_Mid	Left	Tilt	/	21.90	23.00	0.028	0.04	0.042	0.05	0.05
132072	1720	50RB_Mid	Right	Touch	/	21.90	23.00	0.046	0.06	0.065	0.08	0.09
132072	1720	50RB_Mid	Right	Tilt	/	21.90	23.00	0.040	0.05	0.065	0.08	-0.12

Note1: The LTE mode is QPSK_20MHz.

Table 14.1-32: SAR Values (LTE Band66 - Body)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C					
Frequency		Mode	Test Position	Figure No.	Conduct ed Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
132072	1720	1RB_Mid	Front	/	18.58	19.00	0.087	0.10	0.148	0.16	-0.05
132072	1720	1RB_Mid	Rear	/	18.58	19.00	0.191	0.21	0.339	0.37	-0.04
132072	1720	1RB_Mid	Bottom		18.58	19.00	0.198	0.22	0.346	0.38	-0.13
132072	1720	1RB_Mid	Front	Note2	22.97	24.00	0.257	0.33	0.419	0.53	-0.08
132072	1720	1RB_Mid	Rear	Note3	22.97	24.00	0.257	0.33	0.409	0.52	-0.02

132072	1720	1RB_Mid	Left	/	22.97	24.00	0.079	0.10	0.120	0.15	-0.06
132072	1720	1RB_Mid	Right	/	22.97	24.00	0.062	0.08	0.104	0.13	0.12
132072	1720	1RB_Mid	Bottom	Note3 Fig.32	22.97	24.00	0.358	0.45	0.566	0.72	-0.01
132072	1720	50RB_Mid	Front	/	18.45	19.00	0.084	0.10	0.142	0.16	-0.03
132072	1720	50RB_Mid	Rear	/	18.45	19.00	0.185	0.21	0.328	0.37	0.11
132072	1720	50RB_Mid	Bottom	/	18.45	19.00	0.185	0.21	0.325	0.37	-0.05
132072	1720	50RB_Mid	Front	Note2	21.90	23.00	0.222	0.29	0.361	0.47	0.05
132072	1720	50RB_Mid	Rear	Note3	21.90	23.00	0.232	0.30	0.369	0.48	-0.04
132072	1720	50RB_Mid	Left	/	21.90	23.00	0.071	0.09	0.109	0.14	-0.11
132072	1720	50RB_Mid	Right	/	21.90	23.00	0.057	0.07	0.095	0.12	-0.09
132072	1720	50RB_Mid	Bottom	Note3	21.90	23.00	0.277	0.36	0.437	0.56	-0.08

Note1: The distance between the EUT and the phantom bottom is 10mm

Note2: The distance between the EUT and the phantom bottom is 15mm by sensor (See detail in annex I).

Note3: The distance between the EUT and the phantom bottom is 21mm by sensor (See detail in annex I).

Note4: The LTE mode is QPSK_20MHz.

Table 14.1-33: SAR Values (LTE Band71 - Head)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C						
Frequency		Mode	Side	Test Position	Figure No.	Conduct ed Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g)(W/kg)	Measure d SAR(1g) (W/kg)	Reporte d SAR(1g) (W/kg)	Powe r Drift (dB)
Ch.	MH z											
133222	673	1RB_Mid	Left	Touch	Fig.33	22.90	24.50	0.142	0.21	0.180	0.26	-0.06
133222	673	1RB_Mid	Left	Tilt	/	22.90	24.50	0.056	0.08	0.086	0.12	0.00
133222	673	1RB_Mid	Right	Touch	/	22.90	24.50	0.108	0.16	0.135	0.20	0.09
133222	673	1RB_Mid	Right	Tilt	/	22.90	24.50	0.071	0.10	0.087	0.13	-0.13
133222	673	50RB_Mid	Left	Touch	/	21.84	23.50	0.143	0.21	0.183	0.27	0.10
133222	673	50RB_Mid	Left	Tilt	/	21.84	23.50	0.050	0.07	0.079	0.12	-0.07
133222	673	50RB_Mid	Right	Touch	/	21.84	23.50	0.109	0.16	0.138	0.20	0.07
133222	673	50RB_Mid	Right	Tilt	/	21.84	23.50	0.071	0.10	0.087	0.13	-0.11

Note1: The LTE mode is QPSK_20MHz.

Table 14.1-34: SAR Values (LTE Band71 - Body)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C					
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
133222	673	1RB_Mid	Front	/	22.90	24.50	0.210	0.30	0.272	0.39	-0.02
133222	673	1RB_Mid	Rear	Fig.34	22.90	24.50	0.243	0.35	0.313	0.45	-0.13
133222	673	1RB_Mid	Left	/	22.90	24.50	0.217	0.31	0.303	0.44	-0.03
133222	673	1RB_Mid	Right	/	22.90	24.50	0.143	0.21	0.199	0.29	-0.11

133222	673	1RB_Mid	Bottom	/	22.90	24.50	0.082	0.12	0.141	0.20	0.02
133222	673	50RB_Mid	Front	/	21.84	23.50	0.189	0.28	0.244	0.36	0.03
133222	673	50RB_Mid	Rear	/	21.84	23.50	0.225	0.33	0.291	0.43	0.03
133222	673	50RB_Mid	Left	/	21.84	23.50	0.201	0.29	0.281	0.41	0.03
133222	673	50RB_Mid	Right	/	21.84	23.50	0.138	0.20	0.192	0.28	-0.02
133222	673	50RB_Mid	Bottom	/	21.84	23.50	0.082	0.12	0.140	0.21	-0.03

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: The LTE mode is QPSK_20MHz.

14.2 SAR results for Standard procedure

There is zoom scan measurement to be added for the highest measured SAR in each exposure configuration/band.

Table 14.2-1: SAR Values (GSM 850 MHz Band - Head)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C					
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
251	848.8	Right	Touch	Fig.1	28.99	30.00	0.230	0.29	0.303	0.38	0.00

Note: the head SAR of GSM850 is tested with GPRS (4Txslots) mode because of VoIP.

Table 14.2-2: SAR Values (GSM 850 MHz Band - Body)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C					
Frequency		Mode (number of timeslots)	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
190	836.6	GPRS (4)	Rear	Fig.2	29.00	30.00	0.270	0.34	0.360	0.45	-0.03

Note: The distance between the EUT and the phantom bottom is 10mm.

Table 14.2-3: SAR Values (GSM 1900 MHz Band - Head)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C					
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
810	1909.8	Left	Touch	Fig.3	26.02	27.50	0.079	0.11	0.131	0.18	0.10

Note: the head SAR of GSM1900 is tested with GPRS (4Txslots) mode because of VoIP.

Table 14.2-4: SAR Values (GSM 1900 MHz Band - Body)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C					
Frequency		Mode (number of timeslots)	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
810	1909.8	GPRS (2)	Bottom	Fig.4	25.10	26.00	0.562	0.69	1.03	1.27	-0.11

Note1: The distance between the EUT and the phantom bottom is 10mm

Table 14.2-5: SAR Values (WCDMA 1900 MHz Band - Head)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C					
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measure d SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measure d SAR(1g) (W/kg)	Reporte d SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
9662	1852.4	Left	Touch	Fig.5	22.97	24.50	0.101	0.14	0.164	0.23	-0.01

Table 14.2-6: SAR Values (WCDMA 1900 MHz Band - Body)

Ambient Temperature: 22.9°C						Liquid Temperature: 22.5°C				
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz									
9938	1907.6	Bottom	Note3 Fig.6	22.95	24.50	0.323	0.46	0.530	0.76	0.09

Note3: The distance between the EUT and the phantom bottom is 21mm by sensor (See detail in annex I).

Table 14.2-7: SAR Values (WCDMA 1700 MHz Band - Head)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C					
Frequency		Side	Test Position	Figure No.	Conducte d Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measure d SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
1513	1752.6	Left	Touch	Fig.7	23.04	24.50	0.080	0.11	0.124	0.17	0.12

Table 14.2-8: SAR Values (WCDMA 1700 MHz Band - Body)

Ambient Temperature: 22.9 °C					Liquid Temperature: 22.5°C					
Frequency		Test Position	Figure No.	Conduc ted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz									
1513	1752.6	Bottom	Note3 Fig.8	23.04	24.50	0.397	0.56	0.645	0.90	-0.02

Note3: The distance between the EUT and the phantom bottom is 21mm by sensor (See detail in annex I).

Table 14.2-9: SAR Values (WCDMA 850 MHz Band - Head)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C					
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
4233	846.6	Right	Touch	Fig.9	23.41	25.00	0.217	0.31	0.288	0.42	0.05

Table 14.2-10: SAR Values (WCDMA 850 MHz Band - Body)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C				
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz									
4233	846.6	Rear	Fig.10	23.41	25.00	0.214	0.31	0.355	0.51	0.00

Note: The distance between the EUT and the phantom bottom is 10mm.

Table 14.2-11: SAR Values (CDMA BC0 - Head)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C					
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
384	836.52	Right	Touch	Fig.11	24.02	25.00	0.197	0.25	0.256	0.32	0.02

Table 14.2-12: SAR Values (CDMA BC0 - Body)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C				
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz									
384	836.52	Rear	Fig.12	23.95	25.00	0.291	0.37	0.488	0.62	0.07

Note1: The distance between the EUT and the phantom bottom is 10mm

Table 14.2-13: SAR Values (CDMA BC1 - Head)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C					
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
600	1880	Right	Touch	Fig.13	23.97	25.00	0.050	0.06	0.078	0.10	0.13

Table 14.2-14: SAR Values (CDMA BC1 - Body)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C				
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz									
600	1880	Bottom	Note3 Fig.14	23.84	25	0.279	0.36	0.46	0.60	0.02

Note3: The distance between the EUT and the phantom bottom is 21mm by sensor (See detail in annex I).

Table 14.2-15: SAR Values (CDMA BC10 - Head)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C					
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
580	820.5	Right	Touch	Fig.15	24.45	25.00	0.190	0.22	0.246	0.28	0.09

Table 14.2-16: SAR Values (CDMA BC10 - Body)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C				
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz									
580	820.5	Rear	Fig.16	23.95	25.00	0.291	0.37	0.488	0.62	0.07

Note1: The distance between the EUT and the phantom bottom is 10mm

Table 14.2-17: SAR Values (LTE Band7 - Head)

Ambient Temperature: 22.9 °C							Liquid Temperature: 22.5°C					
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz											
21100	2535	1RB_Mid	Left	Touch	Fig.17	23.10	24.50	0.086	0.12	0.148	0.20	-0.10

Note1: The LTE mode is QPSK_20MHz.

Table 14.2-18: SAR Values (LTE Band7 - Body)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C					
Frequency		Mode	Test Position	Figure No.	Conduct ed Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
21325	2560	1RB_Mid	Rear	Fig.18	19.89	21.00	0.156	0.20	0.291	0.38	0.05

Note1: The distance between the EUT and the phantom bottom is 10mm

Table 14.2-19: SAR Values (LTE Band12 - Head)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C						
Frequency		Mode	Side	Test Position	Figure No.	Conduct ed Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g)(W/kg)	Measure d SAR(1g) (W/kg)	Reporte d SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz											
23095	707.5	1RB_Mid	Left	Touch	Fig.19	22.74	24.00	0.148	0.20	0.187	0.25	-0.08

Note1: The LTE mode is QPSK_10MHz.

Table 14.2-20: SAR Values (LTE Band12 - Body)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C					
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
23095	707.5	1RB_Mid	Rear	Fig.20	22.74	24.00	0.274	0.37	0.354	0.47	0.04

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: The LTE mode is QPSK_10MHz.

Table 14.2-21: SAR Values (LTE Band13 - Head)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C						
Frequency		Mode	Side	Test Position	Figure No.	Conduct ed Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g)(W/kg)	Measure d SAR(1g) (W/kg)	Reporte d SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz											
23230	782	1RB_Mid	Left	Touch	Fig.21	23.03	24.00	0.218	0.27	0.285	0.36	0.02

Note1: The LTE mode is QPSK_10MHz.

Table 14.2-22: SAR Values (LTE Band13 - Body)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C					
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
23230	782	1RB_Mid	Rear	Fig.22	23.03	24.00	0.290	0.36	0.381	0.48	0.08

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: The LTE mode is QPSK_10MHz.

Table 14.2-23: SAR Values (LTE Band25 - Head)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C						
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz											
26590	1905	1RB_Mid	Left	Touch	Fig.23	23.04	24.00	0.145	0.18	0.243	0.30	0.02

Note1: The LTE mode is QPSK_20MHz.

Table 14.2-24: SAR Values (LTE Band25 - Body)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C					
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
26590	1905	1RB_Mid	Bottom	Note3 Fig.24	23.04	24.00	0.363	0.45	0.598	0.75	-0.02

Note3: The distance between the EUT and the phantom bottom is 21mm by sensor (See detail in annex I).

Table 14.2-25: SAR Values (LTE Band26 - Head)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C						
Frequency		Mode	Side	Test Position	Figure No.	Conduct ed Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g)(W/kg)	Measure d SAR(1g) (W/kg)	Reporte d SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz											
26965	841.5	1RB_Mid	Right	Touch	Fig.25	23.05	24.50	0.177	0.25	0.299	0.42	-0.12

Note1: The LTE mode is QPSK_15MHz.

Table 14.2-26: SAR Values (LTE Band26 - Body)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C					
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
26965	841.5	1RB_Mid	Rear	Fig.26	23.05	24.50	0.204	0.28	0.337	0.47	-0.07

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: The LTE mode is QPSK_15MHz.

Table 14.2-27: SAR Values (LTE Band41 PC2 - Head)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C						
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz											
41055	2636.5	50RB_Mid	Right	Touch	Fig.27	24.90	26.00	0.053	0.07	0.095	0.12	-0.13

Note1: The LTE mode is QPSK_20MHz.

Table 14.2-28: SAR Values (LTE Band41 PC2 - Body)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C					
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
41055	2636.5	50RB_Mid	Front	Note2 Fig.28	24.90	26.00	0.096	0.12	0.187	0.24	-0.06

Note3: The distance between the EUT and the phantom bottom is 21mm by sensor (See detail in annex I).

Note4: The LTE mode is QPSK_20MHz.

Table 14.2-29: SAR Values (LTE Band41 PC3 - Head)

Ambient Temperature: 22.9°C													Liquid Temperature: 22.5°C		
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)			
Ch.	MHz														
41055	2636.5	50RB_Mid	Left	Touch	Fig.29	22.18	23.00	0.083	0.10	0.157	0.19	0.11			

Note1: The LTE mode is QPSK_20MHz.

Table 14.2-30: SAR Values (LTE Band41 PC3 - Body)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C					
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
41055	2636.5	1RB_Mid	Rear	Fig.30	21.14	22.00	0.095	0.12	0.177	0.22	0.09

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note4: The LTE mode is QPSK_20MHz.

Table 14.2-31: SAR Values (LTE Band66 - Head)

Ambient Temperature: 22.9 °C							Liquid Temperature: 22.5°C					
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz											
132072	1720	1RB_Mid	Left	Touch	Fig.31	22.97	24.00	0.075	0.10	0.116	0.15	-0.10

Note1: The LTE mode is QPSK_20MHz.

Table 14.2-32: SAR Values (LTE Band66 - Body)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C					
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
132072	1720	1RB_Mid	Bottom	Note3 Fig.32	22.97	24.00	0.358	0.45	0.566	0.72	-0.01

Note3: The distance between the EUT and the phantom bottom is 21mm by sensor (See detail in annex I).

Note4: The LTE mode is QPSK_20MHz.

Table 14.2-33: SAR Values (LTE Band71 - Head)

Ambient Temperature: 22.9 °C Liquid Temperature: 22.5°C												
Frequency		Mode	Side	Test Position	Figure No.	Conduct ed Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g)(W/kg)	Measure d SAR(1g) (W/kg)	Reporte d SAR(1g) (W/kg)	Powe r Drift (dB)
Ch.	MH z											
133222	673	1RB_Mid	Left	Touch	Fig.33	22.90	24.50	0.142	0.21	0.180	0.26	-0.06

Note1: The LTE mode is QPSK_20MHz.

Table 14.2-34: SAR Values (LTE Band71 - Body)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C					
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
133222	673	1RB_Mid	Rear	Fig.34	22.90	24.50	0.243	0.35	0.313	0.45	-0.13

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: The LTE mode is QPSK_20MHz.

14.3 WLAN Evaluation for 2.4G

According to the KDB248227 D01, SAR is measured for 2.4GHz 802.11b DSSS using the initial test position procedure.

Head Evaluation

Table 14.3-1: SAR Values (WLAN - Head)– 802.11b (Fast SAR)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C					
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
2437	6	Left	Touch	/	13.53	14.00	0.153	0.17	0.362	0.40	-0.04
2437	6	Left	Tilt	/	13.53	14.00	0.216	0.24	0.527	0.59	0.07
2437	6	Right	Touch	/	13.53	14.00	0.082	0.09	0.175	0.20	0.11
2437	6	Right	Tilt	/	13.53	14.00	0.095	0.11	0.231	0.26	-0.12

As shown above table, the initial test position for head is “Left Tilt”. So the head SAR of WLAN is presented as below:

Table 14.3-2: SAR Values (WLAN - Head)– 802.11b (Full SAR)

Ambient Temperature: 22.9 °C						Liquid Temperature: 22.5°C					
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
2437	6	Left	Touch	/	13.53	14.00	0.135	0.15	0.349	0.39	0.08
2437	6	Left	Tilt	Fig.35	13.53	14.00	0.188	0.21	0.509	0.57	-0.11

Note1: When the reported SAR of the initial test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position using subsequent highest estimated 1-g SAR conditions determined by area scans, on the highest maximum output power channel, until the reported SAR is ≤ 0.8 W/kg.

Note2: For all positions/configurations tested using the initial test position and subsequent test positions, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.

According to the KDB248227 D01, The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit. The scaled reported SAR is presented as below.

Table 14.3-3: SAR Values (WLAN - Head) – 802.11b (Scaled Reported SAR)

Ambient Temperature: 22.9 °C				Liquid Temperature: 22.5 °C			
Frequency		Side	Test Position	Actual duty factor	maximum duty factor	Reported SAR (1g)(W/kg)	Scaled reported SAR (1g)(W/kg)
MHz	Ch.						
2437	6	Left	Tilt	100%	100%	0.57	0.57

SAR is not required for OFDM because the 802.11b adjusted SAR ≤ 1.2 W/kg.

Body Evaluation

Table 14.3-4: SAR Values (WLAN - Body)– 802.11b (Fast SAR)

Ambient Temperature: 22.9℃						Liquid Temperature: 22.5℃				
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g)(W/kg)	Power Drift (dB)
MHz	Ch.									
2437	6	Front		16.34	17.00	0.063	0.07	0.131	0.15	0.08
2437	6	Rear		16.34	17.00	0.083	0.10	0.173	0.20	-0.08
2437	6	Top		16.34	17.00	0.123	0.14	0.267	0.31	0.06
2437	6	Front	Note3	22.69	24.00	0.085	0.11	0.171	0.23	0.01
2437	6	Rear	Note4	22.69	24.00	0.114	0.15	0.213	0.29	0.05
2437	6	Right	/	22.69	24.00	0.087	0.12	0.172	0.23	-0.11
2437	6	Top	Note5	22.69	24.00	0.204	0.28	0.408	0.55	0.10

As shown above table, the initial test position for body is “Top”. So the body SAR of WLAN is presented as below:

Table 14.3-5: SAR Values (WLAN - Body)– 802.11b (Full SAR)

Ambient Temperature: 22.9°C					Liquid Temperature: 22.5°C					
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g)(W/kg)	Power Drift (dB)
MHz	Ch.									
2437	6	Top	Fig.36	22.69	24.00	0.196	0.27	0.401	0.54	0.10
2437	6	Top	Note5	16.34	17.00	0.121	0.14	0.278	0.32	0.06

Note1: When the reported SAR of the initial test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position using subsequent highest estimated 1-g SAR conditions determined by area scans, on the highest maximum output power channel, until the reported SAR is ≤ 0.8 W/kg.

Note2: For all positions/configurations tested using the initial test position and subsequent test positions, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.

Note3: The distance between the EUT and the phantom bottom is 13mm.

Note4: The distance between the EUT and the phantom bottom is 17mm.


Note5: The distance between the EUT and the phantom bottom is 15mm.

According to the KDB248227 D01, The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit. The scaled reported SAR is presented as below.

Table 14.3-6: SAR Values (WLAN - Body) – 802.11b (Scaled Reported SAR)

Ambient Temperature: 22.9 °C			Liquid Temperature: 22.5 °C			
Frequency		Test Position	Actual duty factor	maximum duty factor	Reported SAR (1g)(W/kg)	Scaled reported SAR (1g)(W/kg)
MHz	Ch.					
2437	6	Top	100%	100%	0.54	0.54

SAR is not required for OFDM because the 802.11b adjusted SAR ≤ 1.2 W/kg.



Picture 14.1 Duty factor plot

14.4 WLAN Evaluation For 5G

Table 14.4-1: OFDM mode specified maximum output power of WLAN antenna

802.11 mode	a	g	n		ac			
Ch. BW(MHz)	20	20	20	40	20	40	80	160
U-NII-1	X		X	X	X	X	X	
U-NII-2A	X		X	X	X	X	X	
U-NII-2C	X		X	X	X	X	X	
U-NII-3	X		X	X	X	X	X	
§ 15.247 (5.8/ GHz)								

X: maximum(conducted) output power(mW), including tolerance, specified for production units

Table 14.4-2: Maximum output power specified of WLAN antenna-Head

802.11 mode	a	g	n		ac			
Ch. BW(MHz)	20	20	20	40	20	40	80	160
U-NII-1	22		22	22	22	22	22	
U-NII-2A	22		22	22	22	22	22	
U-NII-2C	22		22	22	22	22	22	
U-NII-3	22		22	22	22	22	22	
§ 15.247 (5.8 GHz)								

- The maximum output power specified for production units is the same for all channels, modulations and data rates in each channel bandwidth configuration of the 802.11a/g/n/ac modes.
- The **blue highlighted** cells represent highest output configurations in each standalone or aggregated frequency band, with tune-up tolerance included.

Table 14.4-3: Maximum output power specified of WLAN antenna-Body Normal Power

802.11 mode	a	g	n		ac			
Ch. BW(MHz)	20	20	20	40	20	40	80	160
U-NII-1	100		100	79	100	79	63	
U-NII-2A	100		100	79	100	79	63	
U-NII-2C	100		100	79	100	79	63	
U-NII-3	100		100	79	100	79	63	
§ 15.247 (5.8 GHz)								

- The maximum output power specified for production units is the same for all channels, modulations and data rates in each channel bandwidth configuration of the 802.11a/g/n/ac modes.
- The **blue highlighted** cells represent highest output configurations in each standalone or aggregated frequency band, with tune-up tolerance included.

Table 14.4-4: Maximum output power specified of WLAN antenna-Body Sensor

802.11 mode	a	g	n		ac			
Ch. BW(MHz)	20	20	20	40	20	40	80	160
U-NII-1	63		63	63	63	63	63	
U-NII-2A	63		63	63	63	63	63	
U-NII-2C	63		63	63	63	63	63	
U-NII-3	63		63	63	63	63	63	
§ 15.247 (5.8 GHz)								
- The maximum output power specified for production units is the same for all channels, modulations and data rates in each channel bandwidth configuration of the 802.11a/g/n/ac modes. - The blue highlighted cells represent highest output configurations in each standalone or aggregated frequency band, with tune-up tolerance included.								

Table 14.4-5: Maximum output power measured of WLAN antenna, for the applicable OFDM configurations according to the default power measurement procedures for selection initial test configurations - Body Normal Power

802.11 mode	a	n		ac		
BW(MHz)	20	20	40	20	40	80
U-NII-1	36/40/44/48 75/69/67/75	36/40/44/48 Lower power	38/46 Lower power	36/40/44/48 Lower power	38/46 Lower power	42 Lower power
U-NII-2A	52/56/60/64 64/64/72/78	52/56/60/64 Lower power	54/62 Lower power	52/56/60/64 Lower power	54/62 Lower power	58 Lower power
U-NII-2C	100/104/108/116 120/12 4/128/132/136/140/144 76/64/68/67/91 /76/81/81/66/68/75/72	100/104/108/116 12 116/132/136/140 Lower power	102/110/118/126/134/142 Lower power	100/104/108/112 116/132/136/140 Lower power	102/110/134 Lower power	106/122/138 Lower power
U-NII-3	149/153/157/161/165 98/97/79/78/77	149/153/157/161/165 Lower power	151/159 Lower power	149/153/157/161/165 Lower power	151/159 Lower power	155 Lower power
- The bold numbers is the maximum output measured power (mW). - Channels with measured maximum power within 0.25dB are considered to have the same measured output. - Channels selected for initial test configuration are highlighted in yellow.						

Table 14.4-6: Maximum output power measured of WLAN antenna, for the applicable OFDM configurations according to the default power measurement procedures for selection initial test configurations - Body Sensor

802.11 mode	a	n		ac		
BW(MHz)	20	20	40	20	40	80
U-NII-1	36/40/44/48 Lower power	36/40/44/48 Lower power	38/46 Lower power	36/40/44/48 Lower power	38/46 Lower power	42 41
U-NII-2A	52/56/60/64 Lower power	52/56/60/64 Lower power	54/62 Lower power	52/56/60/64 Lower power	54/62 Lower power	58 47
U-NII-2C	100/104/108/112/116/120/124/128/132/136/140/144 Lower power	100/104/108/112/116/132/136/140 Lower power	102/110/118/126/134/142 Lower power	100/104/108/112/116/132/136/140 Lower power	102/110/134 Lower power	106/ 122 /138 45/50/42
U-NII-3	149/153/157/161/165 Lower power	149/153/157/161/165 Lower power	151/159 Lower power	149/153/157/161/165 Lower power	151/159 Lower power	155 55
- The bold numbers is the maximum output measured power (mW). - Channels with measured maximum power within 0.25dB are considered to have the same measured output. - Channels selected for initial test configuration are highlighted in yellow.						

Table 14.4-7: Reported SAR of initial test configuration for Head

802.11 mode	a	n		ac		
BW(MHz)	20	20	40	20	40	80
U-NII-2A	52/56/60/64	52/56/60/64	54/62	52/56/60/64	54/62	58 0.60
U-NII-2C	100/104/108/112/116/120/124/128/132/136/140/144	100/104/108/112/116/132/136/140	102/110/118/126/134/142	100/104/108/112/116/132/136/140	102/110/134	106/ 122 /138 0.36
U-NII-3	149/153/157/161/165	149/153/157/161/165	151/159	149/153/157/161/165	151/159	155 0.36
Highest measured output power channel tested initially are in yellow highlight .						

Table 14.4-8: Reported SAR of initial test configuration for Body – 10mm

802.11 mode	a	n		ac		
BW(MHz)	20	20	40	20	40	80
U-NII-2A	52/56/60/64	52/56/60/64	54/62	52/56/60/64	54/62	58 0.38
U-NII-2C	100/104/108/112 116/120/124/128 132/136/140/144	100/104/108/112 116/132/136/140	102/110/118/1 26/134/142	100/104/108/1 12 116/132/136/1 40	102/110/134	106/ 122 /138 0.36
U-NII-3	149/153/157/161/ 165	149/153/157/161 /165	151/159	149/153/157/1 61/165	151/159	155 0.40

Highest measured output power channel tested initially are in **yellow highlight**.

Table 14.4-7: SAR Values (WLAN 5G - Head)

Frequency		Side	Test Position	Figure No.	Conducte d Power (dBm)	Max. tune- up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
58	5290	Left	Touch	/	11.61	13.50	0.117	0.18	0.359	0.55	0.06
58	5290	Left	Tilt	Fig.37	11.61	13.50	0.128	0.20	0.390	0.60	0.10
58	5290	Right	Touch	/	11.61	13.50	0.086	0.13	0.219	0.34	0.08
58	5290	Right	Tilt	/	11.61	13.50	0.111	0.17	0.307	0.47	0.12
122	5610	Left	Touch	/	12.63	13.50	0.091	0.11	0.268	0.33	-0.13
122	5610	Left	Tilt	/	12.63	13.50	0.100	0.12	0.287	0.35	0.12
122	5610	Right	Touch	/	12.63	13.50	0.075	0.09	0.212	0.26	0.10
122	5610	Right	Tilt	/	12.63	13.50	0.104	0.13	0.296	0.36	0.11
155	5775	Left	Touch	/	13.14	13.50	0.102	0.11	0.281	0.31	0.01
155	5775	Left	Tilt	/	13.14	13.50	0.117	0.13	0.329	0.36	0.02
155	5775	Right	Touch	/	13.14	13.50	0.096	0.10	0.265	0.29	0.11
155	5775	Right	Tilt	/	13.14	13.50	0.113	0.12	0.323	0.35	0.00

Table 14.4-8: SAR Values (WLAN 5G - Body)

Frequency		Test Position	Figure No.	Conducte d Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz									
58	5290	Front		16.70	18.00	0.070	0.09	0.170	0.23	-0.06
58	5290	Rear		16.70	18.00	0.099	0.13	0.239	0.32	0.01
58	5290	Top		16.70	18.00	0.115	0.16	0.283	0.38	-0.10
64	5320	Front	Note2	18.91	20.00	0.083	0.11	0.195	0.25	-0.07
64	5320	Rear	Note3	18.91	20.00	0.102	0.13	0.240	0.31	-0.06
64	5320	Left	/	18.91	20.00	0.111	0.14	0.275	0.35	0.12

64	5320	Top	Note4	18.91	20.00	0.100	0.13	0.244	0.31	0.00
122	5610	Front	/	17.01	18.00	0.054	0.07	0.132	0.17	-0.02
122	5610	Rear	/	17.01	18.00	0.080	0.10	0.202	0.25	-0.04
122	5610	Top		17.01	18.00	0.104	0.13	0.285	0.36	-0.11
116	5580	Front	Note2	19.61	20.00	0.075	0.08	0.183	0.20	0.09
116	5580	Rear	Note3	19.61	20.00	0.100	0.11	0.234	0.26	0.12
116	5580	Left	/	19.61	20.00	0.089	0.10	0.213	0.23	-0.13
116	5580	Top	Note4	19.61	20.00	0.100	0.11	0.249	0.27	-0.04
155	5775	Front		17.42	18.00	0.068	0.08	0.171	0.20	0.12
155	5775	Rear		17.42	18.00	0.111	0.13	0.285	0.33	0.06
155	5775	Top	Fig.38	17.42	18.00	0.129	0.15	0.351	0.40	0.08
149	5745	Front	Note2	19.93	20.00	0.078	0.08	0.201	0.20	0.06
149	5745	Rear	Note3	19.93	20.00	0.128	0.13	0.294	0.30	-0.11
149	5745	Left	/	19.93	20.00	0.110	0.11	0.251	0.26	0.00
149	5745	Top	Note4	19.93	20.00	0.138	0.14	0.325	0.33	-0.04

Note: The distance between the EUT and the phantom bottom is 10mm.

Note2: The distance between the EUT and the phantom bottom is 13mm.

Note3: The distance between the EUT and the phantom bottom is 17mm.

Note4: The distance between the EUT and the phantom bottom is 15mm.


According to the KDB248227 D01, The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit. The scaled reported SAR is presented as below.

Table 14.4-9: SAR Values (WLAN 5G - Head) (Scaled Reported SAR)


Frequency		Side	Test Position	Actual duty factor	maximum duty factor	Reported SAR (1g) (W/kg)	Scaled reported SAR (1g) (W/kg)
Ch.	MHz						
58	5290	Left	Tilt	100%	100%	0.60	0.60

Table 14.4-10 SAR Values (WLAN 5G - Body) (Scaled Reported SAR)

Frequency		Test Position	D (mm)	Actual duty factor	maximum duty factor	Reported SAR (1g) (W/kg)	Scaled reported SAR (1g) (W/kg)
Ch.	MHz						
155	5775	Top	10	100%	100%	0.40	0.40



Picture 14.2 The plot of duty factor for Head



Picture 14.3The plot of duty factor for Body

15 SAR Measurement Variability

SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium.

The following procedures are applied to determine if repeated measurements are required.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

Table 15.1: SAR Measurement Variability for Body GSM1900 (1g)

Frequency		Test Position	Spacing (mm)	Original SAR (W/kg)	First Repeated SAR (W/kg)	The Ratio	Second Repeated SAR (W/kg)
Ch.	MHz						
810	1909.8	Bottom	10	1.03	0.977	1.05	/

16 Measurement Uncertainty

16.1 Measurement Uncertainty for Normal SAR Tests (300MHz~3GHz)

No.	Error Description	Type	Uncertainty value	Probably Distribution	Div.	(Ci) 1g	(Ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)	Degree of freedom
Measurement system										
1	Probe calibration	B	6.0	N	1	1	1	6.0	6.0	∞
2	Isotropy	B	4.7	R	$\sqrt{3}$	0.7	0.7	1.9	1.9	∞
3	Boundary effect	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
4	Linearity	B	4.7	R	$\sqrt{3}$	1	1	2.7	2.7	∞
5	Detection limit	B	1.0	N	1	1	1	0.6	0.6	∞
6	Readout electronics	B	0.3	R	$\sqrt{3}$	1	1	0.3	0.3	∞
7	Response time	B	0.8	R	$\sqrt{3}$	1	1	0.5	0.5	∞
8	Integration time	B	2.6	R	$\sqrt{3}$	1	1	1.5	1.5	∞
9	RF ambient conditions-noise	B	0	R	$\sqrt{3}$	1	1	0	0	∞
10	RF ambient conditions-reflection	B	0	R	$\sqrt{3}$	1	1	0	0	∞
11	Probe positioned mech. restrictions	B	0.4	R	$\sqrt{3}$	1	1	0.2	0.2	∞
12	Probe positioning with respect to phantom shell	B	2.9	R	$\sqrt{3}$	1	1	1.7	1.7	∞
13	Post-processing	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
Test sample related										
14	Test sample positioning	A	3.3	N	1	1	1	3.3	3.3	71
15	Device holder uncertainty	A	3.4	N	1	1	1	3.4	3.4	5
16	Drift of output power	B	5.0	R	$\sqrt{3}$	1	1	2.9	2.9	∞
Phantom and set-up										
17	Phantom uncertainty	B	4.0	R	$\sqrt{3}$	1	1	2.3	2.3	∞
18	Liquid conductivity (target)	B	5.0	R	$\sqrt{3}$	0.64	0.43	1.8	1.2	∞
19	Liquid conductivity (meas.)	A	2.06	N	1	0.64	0.43	1.32	0.89	43
20	Liquid permittivity (target)	B	5.0	R	$\sqrt{3}$	0.6	0.49	1.7	1.4	∞
21	Liquid permittivity (meas.)	A	1.6	N	1	0.6	0.49	1.0	0.8	521

Combined standard uncertainty	$u_c = \sqrt{\sum_{i=1}^{21} c_i^2 u_i^2}$					9.55	9.43	257
Expanded uncertainty (confidence interval of 95 %)	$u_e = 2u_c$					19.1	18.9	

16.2 Measurement Uncertainty for Normal SAR Tests (3~6GHz)

No.	Error Description	Type	Uncertainty value	Probably Distribution	Div.	(Ci) 1g	(Ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)	Degree of freedom
Measurement system										
1	Probe calibration	B	6.55	N	1	1	1	6.55	6.55	∞
2	Isotropy	B	4.7	R	$\sqrt{3}$	0.7	0.7	1.9	1.9	∞
3	Boundary effect	B	2.0	R	$\sqrt{3}$	1	1	1.2	1.2	∞
4	Linearity	B	4.7	R	$\sqrt{3}$	1	1	2.7	2.7	∞
5	Detection limit	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
6	Readout electronics	B	0.3	R	$\sqrt{3}$	1	1	0.3	0.3	∞
7	Response time	B	0.8	R	$\sqrt{3}$	1	1	0.5	0.5	∞
8	Integration time	B	2.6	R	$\sqrt{3}$	1	1	1.5	1.5	∞
9	RF ambient conditions-noise	B	0	R	$\sqrt{3}$	1	1	0	0	∞
10	RF ambient conditions-reflection	B	0	R	$\sqrt{3}$	1	1	0	0	∞
11	Probe positioned mech. restrictions	B	0.8	R	$\sqrt{3}$	1	1	0.5	0.5	∞
12	Probe positioning with respect to phantom shell	B	6.7	R	$\sqrt{3}$	1	1	3.9	3.9	∞
13	Post-processing	B	4.0	R	$\sqrt{3}$	1	1	2.3	2.3	∞
Test sample related										
14	Test sample positioning	A	3.3	N	1	1	1	3.3	3.3	71
15	Device holder uncertainty	A	3.4	N	1	1	1	3.4	3.4	5
16	Drift of output power	B	5.0	R	$\sqrt{3}$	1	1	2.9	2.9	∞
Phantom and set-up										
17	Phantom uncertainty	B	4.0	R	$\sqrt{3}$	1	1	2.3	2.3	∞
18	Liquid conductivity (target)	B	5.0	R	$\sqrt{3}$	0.64	0.43	1.8	1.2	∞
19	Liquid conductivity (meas.)	A	2.06	N	1	0.64	0.43	1.32	0.89	43
20	Liquid permittivity	B	5.0	R	$\sqrt{3}$	0.6	0.49	1.7	1.4	∞

	(target)									
21	Liquid permittivity (meas.)	A	1.6	N	1	0.6	0.49	1.0	0.8	521
Combined standard uncertainty		$u_c = \sqrt{\sum_{i=1}^{21} c_i^2 u_i^2}$						10.7	10.6	257
Expanded uncertainty (confidence interval of 95 %)		$u_e = 2u_c$						21.4	21.1	

16.3 Measurement Uncertainty for Fast SAR Tests (300MHz~3GHz)

No.	Error Description	Type	Uncertainty value	Probably Distribution	Div.	(Ci) 1g	(Ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)	Degree of freedom
Measurement system										
1	Probe calibration	B	6.0	N	1	1	1	6.0	6.0	∞
2	Isotropy	B	4.7	R	$\sqrt{3}$	0.7	0.7	1.9	1.9	∞
3	Boundary effect	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
4	Linearity	B	4.7	R	$\sqrt{3}$	1	1	2.7	2.7	∞
5	Detection limit	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
6	Readout electronics	B	0.3	R	$\sqrt{3}$	1	1	0.3	0.3	∞
7	Response time	B	0.8	R	$\sqrt{3}$	1	1	0.5	0.5	∞
8	Integration time	B	2.6	R	$\sqrt{3}$	1	1	1.5	1.5	∞
9	RF ambient conditions-noise	B	0	R	$\sqrt{3}$	1	1	0	0	∞
10	RF ambient conditions-reflection	B	0	R	$\sqrt{3}$	1	1	0	0	∞
11	Probe positioned mech. Restrictions	B	0.4	R	$\sqrt{3}$	1	1	0.2	0.2	∞
12	Probe positioning with respect to phantom shell	B	2.9	R	$\sqrt{3}$	1	1	1.7	1.7	∞
13	Post-processing	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
14	Fast SAR z-Approximation	B	7.0	R	$\sqrt{3}$	1	1	4.0	4.0	∞
Test sample related										
15	Test sample positioning	A	3.3	N	1	1	1	3.3	3.3	71
16	Device holder uncertainty	A	3.4	N	1	1	1	3.4	3.4	5
17	Drift of output power	B	5.0	R	$\sqrt{3}$	1	1	2.9	2.9	∞
Phantom and set-up										
18	Phantom uncertainty	B	4.0	R	$\sqrt{3}$	1	1	2.3	2.3	∞

19	Liquid conductivity (target)	B	5.0	R	$\sqrt{3}$	0.64	0.43	1.8	1.2	∞
20	Liquid conductivity (meas.)	A	2.06	N	1	0.64	0.43	1.32	0.89	43
21	Liquid permittivity (target)	B	5.0	R	$\sqrt{3}$	0.6	0.49	1.7	1.4	∞
22	Liquid permittivity (meas.)	A	1.6	N	1	0.6	0.49	1.0	0.8	521
Combined standard uncertainty		$u_c' = \sqrt{\sum_{i=1}^{22} c_i^2 u_i^2}$						10.4	10.3	257
Expanded uncertainty (confidence interval of 95 %)		$u_e = 2u_c$						20.8	20.6	

16.4 Measurement Uncertainty for Fast SAR Tests (3~6GHz)

No.	Error Description	Type	Uncertainty value	Probably Distribution	Div.	(Ci) 1g	(Ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)	Degree of freedom
Measurement system										
1	Probe calibration	B	6.55	N	1	1	1	6.55	6.55	∞
2	Isotropy	B	4.7	R	$\sqrt{3}$	0.7	0.7	1.9	1.9	∞
3	Boundary effect	B	2.0	R	$\sqrt{3}$	1	1	1.2	1.2	∞
4	Linearity	B	4.7	R	$\sqrt{3}$	1	1	2.7	2.7	∞
5	Detection limit	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
6	Readout electronics	B	0.3	R	$\sqrt{3}$	1	1	0.3	0.3	∞
7	Response time	B	0.8	R	$\sqrt{3}$	1	1	0.5	0.5	∞
8	Integration time	B	2.6	R	$\sqrt{3}$	1	1	1.5	1.5	∞
9	RF ambient conditions-noise	B	0	R	$\sqrt{3}$	1	1	0	0	∞
10	RF ambient conditions-reflection	B	0	R	$\sqrt{3}$	1	1	0	0	∞
11	Probe positioned mech. Restrictions	B	0.8	R	$\sqrt{3}$	1	1	0.5	0.5	∞
12	Probe positioning with respect to phantom shell	B	6.7	R	$\sqrt{3}$	1	1	3.9	3.9	∞
13	Post-processing	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
14	Fast SAR z-Approximation	B	14.0	R	$\sqrt{3}$	1	1	8.1	8.1	∞
Test sample related										
15	Test sample	A	3.3	N	1	1	1	3.3	3.3	71

	positioning									
16	Device holder uncertainty	A	3.4	N	1	1	1	3.4	3.4	5
17	Drift of output power	B	5.0	R	$\sqrt{3}$	1	1	2.9	2.9	∞
Phantom and set-up										
18	Phantom uncertainty	B	4.0	R	$\sqrt{3}$	1	1	2.3	2.3	∞
19	Liquid conductivity (target)	B	5.0	R	$\sqrt{3}$	0.64	0.43	1.8	1.2	∞
20	Liquid conductivity (meas.)	A	2.06	N	1	0.64	0.43	1.32	0.89	43
21	Liquid permittivity (target)	B	5.0	R	$\sqrt{3}$	0.6	0.49	1.7	1.4	∞
22	Liquid permittivity (meas.)	A	1.6	N	1	0.6	0.49	1.0	0.8	521
Combined standard uncertainty		$u_c' = \sqrt{\sum_{i=1}^{22} c_i^2 u_i^2}$						13.5	13.4	257
Expanded uncertainty (confidence interval of 95 %)		$u_e = 2u_c$						27.0	26.8	

17 MAIN TEST INSTRUMENTS

Table 17.1: List of Main Instruments

No.	Name	Type	Serial Number	Calibration Date	Valid Period
01	Network analyzer	E5071C	MY46110673	January 24, 2019	One year
02	Power meter	NRP2	106277	September 4, 2019	One year
03	Power sensor	NRP8S	104291		
04	Signal Generator	E4438C	MY49070393	January 4, 2019	One Year
05	Amplifier	60S1G4	0331848	No Calibration Requested	
06	BTS	CMW500	166370	June 27, 2019	One year
07	E-field Probe	SPEAG EX3DV4	3617	January 31, 2019	One year
08	DAE	SPEAG DAE4	1289	April 11,2019	One year
09	Dipole Validation Kit	SPEAG D750V3	1017	July 18,2019	One year
10	Dipole Validation Kit	SPEAG D835V2	4d069	July 18,2019	One year
11	Dipole Validation Kit	SPEAG D1750V2	1003	July 16,2019	One year
12	Dipole Validation Kit	SPEAG D1900V2	5d101	July 17,2019	One year
13	Dipole Validation Kit	SPEAG D2450V2	853	July 17,2019	One year
14	Dipole Validation Kit	SPEAG D2600V2	1012	July 17,2019	One year
15	Dipole Validation Kit	SPEAG D5GHZV2	1060	July 22, 2019	One year

END OF REPORT BODY

ANNEX A Graph Results

GSM850_CH251 Right Cheek

Date: 2020/1/14

Electronics: DAE4 Sn1289

Medium: head 835 MHz

Medium parameters used: $f = 848.8$; $\sigma = 0.901$ mho/m; $\epsilon_r = 40.67$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.5°C, Liquid Temperature: 22.3°C

Communication System: GSM850 848.8 Duty Cycle: 1: 2

Probe: EX3DV4 – SN3617 ConvF(9.75,9.75,9.75)

Area Scan (71x121x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.342 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 4.988 V/m; Power Drift = 0 dB

Peak SAR (extrapolated) = 0.387 W/kg

SAR(1 g) = 0.303 W/kg; SAR(10 g) = 0.23 W/kg

Maximum value of SAR (measured) = 0.35 W/kg




Fig A.1

GSM850_CH190 Rear

Date: 2020/1/14

Electronics: DAE4 Sn1289

Medium: head 835 MHz

Medium parameters used: $f = 836.6$; $\sigma = 0.89$ mho/m; $\epsilon_r = 40.69$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.5°C, Liquid Temperature: 22.3°C

Communication System: GSM850 836.6 Duty Cycle: 1: 2

Probe: EX3DV4 – SN3617 ConvF(9.75,9.75,9.75)

Area Scan (71x121x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.428 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 19.59 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.482 W/kg

SAR(1 g) = 0.36 W/kg; SAR(10 g) = 0.27 W/kg

Maximum value of SAR (measured) = 0.431 W/kg




Fig A.2

PCS1900_CH810 Left Cheek

Date: 2020/1/16

Electronics: DAE4 Sn1289

Medium: head 1900 MHz

Medium parameters used: $f = 1909.8$; $\sigma = 1.42$ mho/m; $\epsilon_r = 39.37$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.5°C, Liquid Temperature: 22.3°C

Communication System: PCS1900 1909.8 Duty Cycle: 1: 2

Probe: EX3DV4 – SN3617 ConvF(8.14,8.14,8.14)

Area Scan (71x121x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.18 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 3.645 V/m; Power Drift = 0.1 dB

Peak SAR (extrapolated) = 0.207 W/kg

SAR(1 g) = 0.131 W/kg; SAR(10 g) = 0.079 W/kg

Maximum value of SAR (measured) = 0.158 W/kg




Fig A.3

PCS1900_CH810 Bottom

Date: 2020/1/16

Electronics: DAE4 Sn1289

Medium: head 1900 MHz

Medium parameters used: $f = 1909.8$; $\sigma = 1.42$ mho/m; $\epsilon_r = 39.37$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.5°C, Liquid Temperature: 22.3°C

Communication System: PCS1900 1909.8 Duty Cycle: 1: 4

Probe: EX3DV4 – SN3617 ConvF(8.14,8.14,8.14)

Area Scan (61x91x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 1.63 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 20.40 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 1.88 W/kg

SAR(1 g) = 1.03 W/kg; SAR(10 g) = 0.562 W/kg

Maximum value of SAR (measured) = 1.55 W/kg




Fig A.4

WCDMA1900-BII_CH9262 Left Cheek

Date: 2020/1/16

Electronics: DAE4 Sn1289

Medium: head 1900 MHz

Medium parameters used: $f = 1852.4$; $\sigma = 1.365$ mho/m; $\epsilon_r = 39.44$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.5°C, Liquid Temperature: 22.3°C

Communication System: WCDMA1900-BII 1852.4 Duty Cycle: 1: 1

Probe: EX3DV4 – SN3617 ConvF(8.14,8.14,8.14)

Area Scan (71x121x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.22 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 5.959 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.252 W/kg

SAR(1 g) = 0.164 W/kg; SAR(10 g) = 0.101 W/kg

Maximum value of SAR (measured) = 0.193 W/kg




Fig A.5

WCDMA1900-BII_CH9538 Bottom

Date: 2020/1/16

Electronics: DAE4 Sn1289

Medium: head 1900 MHz

Medium parameters used: $f = 1907.6$; $\sigma = 1.419$ mho/m; $\epsilon_r = 39.37$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.5°C, Liquid Temperature: 22.3°C

Communication System: WCDMA1900-BII 1907.6 Duty Cycle: 1: 1

Probe: EX3DV4 – SN3617 ConvF(8.14,8.14,8.14)

Area Scan (71x121x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.696 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 19.6 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.839 W/kg

SAR(1 g) = 0.53 W/kg; SAR(10 g) = 0.323 W/kg

Maximum value of SAR (measured) = 0.693 W/kg




Fig A.6

WCDMA1700-BIV_CH1513 Left Cheek

Date: 2020/1/15

Electronics: DAE4 Sn1289

Medium: head 1750 MHz

Medium parameters used: $f = 1752.6$; $\sigma = 1.357$ mho/m; $\epsilon_r = 40.2$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.5°C, Liquid Temperature: 22.3°C

Communication System: WCDMA1700-BIV 1752.6 Duty Cycle: 1: 1

Probe: EX3DV4 – SN3617 ConvF(8.38,8.38,8.38)

Area Scan (71x121x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.16 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 5.943 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 0.179 W/kg

SAR(1 g) = 0.124 W/kg; SAR(10 g) = 0.08 W/kg

Maximum value of SAR (measured) = 0.143 W/kg




Fig A.7

WCDMA1700-BIV_CH1513 Bottom

Date: 2020/1/15

Electronics: DAE4 Sn1289

Medium: head 1750 MHz

Medium parameters used: $f = 1752.6$; $\sigma = 1.357$ mho/m; $\epsilon_r = 40.2$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.5°C, Liquid Temperature: 22.3°C

Communication System: WCDMA1700-BIV 1752.6 Duty Cycle: 1: 1

Probe: EX3DV4 – SN3617 ConvF(8.38,8.38,8.38)

Area Scan (71x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.838 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 22.32 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.989 W/kg

SAR(1 g) = 0.645 W/kg; SAR(10 g) = 0.397 W/kg

Maximum value of SAR (measured) = 0.833 W/kg




Fig A.8

WCDMA850-BV_CH4233 Right Cheek

Date: 2020/1/14

Electronics: DAE4 Sn1289

Medium: head 835 MHz

Medium parameters used: $f = 846.6$; $\sigma = 0.899$ mho/m; $\epsilon_r = 40.68$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.5°C, Liquid Temperature: 22.3°C

Communication System: WCDMA850-BV 846.6 Duty Cycle: 1: 1

Probe: EX3DV4 – SN3617 ConvF(9.75,9.75,9.75)

Area Scan (71x121x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.329 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 6.107 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.374 W/kg

SAR(1 g) = 0.288 W/kg; SAR(10 g) = 0.217 W/kg

Maximum value of SAR (measured) = 0.338 W/kg




Fig A.9

WCDMA850-BV_CH4233 Rear

Date: 2020/1/14

Electronics: DAE4 Sn1289

Medium: head 835 MHz

Medium parameters used: $f = 846.6$; $\sigma = 0.899$ mho/m; $\epsilon_r = 40.68$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.5°C, Liquid Temperature: 22.3°C

Communication System: WCDMA850-BV 846.6 Duty Cycle: 1: 1

Probe: EX3DV4 – SN3617 ConvF(9.75,9.75,9.75)

Area Scan (71x121x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.464 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 18.71 V/m; Power Drift = 0 dB

Peak SAR (extrapolated) = 0.593 W/kg

SAR(1 g) = 0.355 W/kg; SAR(10 g) = 0.214 W/kg

Maximum value of SAR (measured) = 0.475 W/kg




Fig A.10

CDMA800-BC0_CH384 Right Cheek

Date: 2020/1/14

Electronics: DAE4 Sn1289

Medium: head 835 MHz

Medium parameters used: $f = 836.52$; $\sigma = 0.89$ mho/m; $\epsilon_r = 40.69$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.5°C, Liquid Temperature: 22.3°C

Communication System: CDMA800-BC0 836.52 Duty Cycle: 1: 1

Probe: EX3DV4 – SN3617 ConvF(9.75,9.75,9.75)

Area Scan (71x121x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.329 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 6.946 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.317 W/kg

SAR(1 g) = 0.256 W/kg; SAR(10 g) = 0.197 W/kg

Maximum value of SAR (measured) = 0.266 W/kg




Fig A.11

CDMA800-BC0_CH384 Rear

Date: 2020/1/14

Electronics: DAE4 Sn1289

Medium: head 835 MHz

Medium parameters used: $f = 836.52$; $\sigma = 0.89$ mho/m; $\epsilon_r = 40.69$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.5°C, Liquid Temperature: 22.3°C

Communication System: CDMA800-BC0 836.52 Duty Cycle: 1: 1

Probe: EX3DV4 – SN3617 ConvF(9.75,9.75,9.75)

Area Scan (71x121x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.641 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 21.23 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.826 W/kg

SAR(1 g) = 0.488 W/kg; SAR(10 g) = 0.291 W/kg

Maximum value of SAR (measured) = 0.654 W/kg




Fig A.12

CDMA1900-BC1_CH600 Right Cheek

Date: 2020/1/16

Electronics: DAE4 Sn1289

Medium: head 1900 MHz

Medium parameters used: $f = 1880$; $\sigma = 1.392$ mho/m; $\epsilon_r = 39.4$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.5°C, Liquid Temperature: 22.3°C

Communication System: CDMA1900-BC1 1880 Duty Cycle: 1: 1

Probe: EX3DV4 – SN3617 ConvF(8.14,8.14,8.14)

Area Scan (71x121x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.098 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 2.637 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 0.114 W/kg

SAR(1 g) = 0.078 W/kg; SAR(10 g) = 0.05 W/kg

Maximum value of SAR (measured) = 0.0981 W/kg




Fig A.13

CDMA1900-BC1_CH600 Bottom

Date: 2020/1/16

Electronics: DAE4 Sn1289

Medium: head 1900 MHz

Medium parameters used: $f = 1880$; $\sigma = 1.392$ mho/m; $\epsilon_r = 39.4$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.5°C, Liquid Temperature: 22.3°C

Communication System: CDMA1900-BC1 1880 Duty Cycle: 1: 1

Probe: EX3DV4 – SN3617 ConvF(8.14,8.14,8.14)

Area Scan (71x121x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.598 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 9.369 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.729 W/kg

SAR(1 g) = 0.46 W/kg; SAR(10 g) = 0.279 W/kg

Maximum value of SAR (measured) = 0.604 W/kg




Fig A.14

CDMA800-BC10_CH580 Right Cheek

Date: 2020/1/14

Electronics: DAE4 Sn1289

Medium: head 835 MHz

Medium parameters used: $f = 820.5$; $\sigma = 0.874$ mho/m; $\epsilon_r = 40.71$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.5°C, Liquid Temperature: 22.3°C

Communication System: CDMA800-BC10 820.5 Duty Cycle: 1: 1

Probe: EX3DV4 – SN3617 ConvF(9.75,9.75,9.75)

Area Scan (71x121x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.292 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 7.061 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.303 W/kg

SAR(1 g) = 0.246 W/kg; SAR(10 g) = 0.19 W/kg

Maximum value of SAR (measured) = 0.255 W/kg




Fig A.15

CDMA800-BC10_CH684 Rear

Date: 2020/1/14

Electronics: DAE4 Sn1289

Medium: head 835 MHz

Medium parameters used: $f = 823.1$; $\sigma = 0.877$ mho/m; $\epsilon_r = 40.7$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.5°C, Liquid Temperature: 22.3°C

Communication System: CDMA800-BC10 823.1 Duty Cycle: 1: 1

Probe: EX3DV4 – SN3617 ConvF(9.75,9.75,9.75)

Area Scan (71x121x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.484 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 19.91 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.517 W/kg

SAR(1 g) = 0.402 W/kg; SAR(10 g) = 0.304 W/kg

Maximum value of SAR (measured) = 0.466 W/kg




Fig A.16

LTE2500-FDD7_CH21100 Left Cheek

Date: 2020/1/18

Electronics: DAE4 Sn1289

Medium: head 2600 MHz

Medium parameters used: $f = 2535$ MHz; $\sigma = 1.894$ mho/m; $\epsilon_r = 39.09$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.5°C, Liquid Temperature: 22.3°C

Communication System: LTE2500-FDD7 2535 MHz Duty Cycle: 1: 1

Probe: EX3DV4 – SN3617 ConvF(7.19,7.19,7.19)

Area Scan (91x151x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.220 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 5.636 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 0.270 W/kg

SAR(1 g) = 0.148 W/kg; SAR(10 g) = 0.086 W/kg

Maximum value of SAR (measured) = 0.193 W/kg




Fig A.17

LTE2500-FDD7_CH21350 Rear

Date: 2020/1/18

Electronics: DAE4 Sn1289

Medium: head 2600 MHz

Medium parameters used: $f = 2560$ MHz; $\sigma = 1.918$ mho/m; $\epsilon_r = 39.06$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.5°C, Liquid Temperature: 22.3°C

Communication System: LTE2500-FDD7 2560 MHz Duty Cycle: 1: 1

Probe: EX3DV4 – SN3617 ConvF(7.19,7.19,7.19)

Area Scan (71x121x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.425 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 3.461 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.566 W/kg

SAR(1 g) = 0.291 W/kg; SAR(10 g) = 0.156 W/kg

Maximum value of SAR (measured) = 0.418 W/kg




Fig A.18

LTE700-FDD12_CH23095 Left Cheek

Date: 2020/1/13

Electronics: DAE4 Sn1289

Medium: head 750 MHz

Medium parameters used: $f = 707.5$ MHz; $\sigma = 0.85$ mho/m; $\epsilon_r = 42.55$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.5°C, Liquid Temperature: 22.3°C

Communication System: LTE700-FDD12 707.5 MHz Duty Cycle: 1: 1

Probe: EX3DV4 – SN3617 ConvF(10.03,10.03,10.03)

Area Scan (71x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.209 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.378 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 0.23 W/kg

SAR(1 g) = 0.187 W/kg; SAR(10 g) = 0.148 W/kg

Maximum value of SAR (measured) = 0.203 W/kg




Fig A.19

LTE700-FDD12_CH23095 Rear

Date: 2020/1/13

Electronics: DAE4 Sn1289

Medium: head 750 MHz

Medium parameters used: $f = 707.5$ MHz; $\sigma = 0.85$ mho/m; $\epsilon_r = 42.55$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.5°C, Liquid Temperature: 22.3°C

Communication System: LTE700-FDD12 707.5 MHz Duty Cycle: 1: 1

Probe: EX3DV4 – SN3617 ConvF(10.03,10.03,10.03)

Area Scan (71x121x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.419 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 21.33 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.45 W/kg

SAR(1 g) = 0.354 W/kg; SAR(10 g) = 0.274 W/kg

Maximum value of SAR (measured) = 0.407 W/kg




Fig A.20

LTE750-FDD13_CH23230 Left Cheek

Date: 2020/1/13

Electronics: DAE4 Sn1289

Medium: head 750 MHz

Medium parameters used: $f = 782 \text{ MHz}$; $\sigma = 0.92 \text{ mho/m}$; $\epsilon_r = 42.46$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 22.5°C , Liquid Temperature: 22.3°C

Communication System: LTE750-FDD13 782 MHz Duty Cycle: 1: 1

Probe: EX3DV4 – SN3617 ConvF(10.03,10.03,10.03)

Area Scan (71x121x1): Interpolated grid: $dx=1.000 \text{ mm}$, $dy=1.000 \text{ mm}$

Maximum value of SAR (interpolated) = 0.334 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 5.939 V/m ; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.358 W/kg

SAR(1 g) = 0.285 W/kg ; SAR(10 g) = 0.218 W/kg

Maximum value of SAR (measured) = 0.313 W/kg




Fig A.21

LTE750-FDD13_CH23230 Rear

Date: 2020/1/13

Electronics: DAE4 Sn1289

Medium: head 750 MHz

Medium parameters used: $f = 782 \text{ MHz}$; $\sigma = 0.92 \text{ mho/m}$; $\epsilon_r = 42.46$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 22.5°C , Liquid Temperature: 22.3°C

Communication System: LTE750-FDD13 782 MHz Duty Cycle: 1: 1

Probe: EX3DV4 – SN3617 ConvF(10.03,10.03,10.03)

Area Scan (71x121x1): Interpolated grid: $dx=1.000 \text{ mm}$, $dy=1.000 \text{ mm}$

Maximum value of SAR (interpolated) = 0.443 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 20.93 V/m ; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 0.489 W/kg

SAR(1 g) = 0.381 W/kg ; SAR(10 g) = 0.29 W/kg

Maximum value of SAR (measured) = 0.44 W/kg




Fig A.22

LTE1900-FDD25_CH26590 Left Cheek

Date: 2020/1/16

Electronics: DAE4 Sn1289

Medium: head 1900 MHz

Medium parameters used: $f = 1905 \text{ MHz}$; $\sigma = 1.416 \text{ mho/m}$; $\epsilon_r = 39.37$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 22.5°C , Liquid Temperature: 22.3°C

Communication System: LTE1900-FDD25 1905 MHz Duty Cycle: 1: 1

Probe: EX3DV4 – SN3617 ConvF(8.14,8.14,8.14)

Area Scan (71x121x1): Interpolated grid: $dx=1.000 \text{ mm}$, $dy=1.000 \text{ mm}$

Maximum value of SAR (interpolated) = 0.348 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 3.969 V/m ; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.379 W/kg

SAR(1 g) = 0.243 W/kg ; SAR(10 g) = 0.145 W/kg

Maximum value of SAR (measured) = 0.291 W/kg




Fig A.23

LTE1900-FDD25_CH26590 Bottom

Date: 2020/1/16

Electronics: DAE4 Sn1289

Medium: head 1900 MHz

Medium parameters used: $f = 1905 \text{ MHz}$; $\sigma = 1.416 \text{ mho/m}$; $\epsilon_r = 39.37$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 22.5°C , Liquid Temperature: 22.3°C

Communication System: LTE1900-FDD25 1905 MHz Duty Cycle: 1: 1

Probe: EX3DV4 – SN3617 ConvF(8.14,8.14,8.14)

Area Scan (71x121x1): Interpolated grid: $dx=1.000 \text{ mm}$, $dy=1.000 \text{ mm}$

Maximum value of SAR (interpolated) = 0.79 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 18.52 V/m ; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.946 W/kg

SAR(1 g) = 0.598 W/kg ; SAR(10 g) = 0.363 W/kg

Maximum value of SAR (measured) = 0.783 W/kg




Fig A.24

LTE850-FDD26_CH26965 Right Cheek

Date: 2020/1/14

Electronics: DAE4 Sn1289

Medium: head 835 MHz

Medium parameters used: $f = 841.5$ MHz; $\sigma = 0.895$ mho/m; $\epsilon_r = 40.68$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.5°C, Liquid Temperature: 22.3°C

Communication System: LTE850-FDD26 841.5 MHz Duty Cycle: 1: 1

Probe: EX3DV4 – SN3617 ConvF(9.75,9.75,9.75)

Area Scan (71x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.348 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.41 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 0.377 W/kg

SAR(1 g) = 0.299 W/kg; SAR(10 g) = 0.177 W/kg

Maximum value of SAR (measured) = 0.342 W/kg




Fig A.25

LTE850-FDD26_CH26965 Rear

Date: 2020/1/14

Electronics: DAE4 Sn1289

Medium: head 835 MHz

Medium parameters used: $f = 841.5$ MHz; $\sigma = 0.895$ mho/m; $\epsilon_r = 40.68$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.5°C, Liquid Temperature: 22.3°C

Communication System: LTE850-FDD26 841.5 MHz Duty Cycle: 1: 1

Probe: EX3DV4 – SN3617 ConvF(9.75,9.75,9.75)

Area Scan (71x121x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.435 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 19.08 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.561 W/kg

SAR(1 g) = 0.337 W/kg; SAR(10 g) = 0.204 W/kg

Maximum value of SAR (measured) = 0.45 W/kg




Fig A.26

LTE2600-TDD41 PC3_CH41055 Left Cheek

Date: 2020/1/18

Electronics: DAE4 Sn1289

Medium: head 2600 MHz

Medium parameters used: $f = 2636.5$; $\sigma = 1.992$ mho/m; $\epsilon_r = 38.97$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.5°C, Liquid Temperature: 22.3°C

Communication System: LTE2600-TDD41 2636.5 Duty Cycle: 1: 1.58

Probe: EX3DV4 – SN3617 ConvF(7.19,7.19,7.19)

Area Scan (71x121x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.213 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 2.138 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.287 W/kg

SAR(1 g) = 0.157 W/kg; SAR(10 g) = 0.083 W/kg

Maximum value of SAR (measured) = 0.22 W/kg




Fig A.27

LTE2600-TDD41 PC3_CH41055 Rear

Date: 2020/1/18

Electronics: DAE4 Sn1289

Medium: head 2600 MHz

Medium parameters used: $f = 2636.5$; $\sigma = 1.992$ mho/m; $\epsilon_r = 38.97$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.5°C, Liquid Temperature: 22.3°C

Communication System: LTE2600-TDD41 2636.5 Duty Cycle: 1: 1.58

Probe: EX3DV4 – SN3617 ConvF(7.19,7.19,7.19)

Area Scan (71x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.234 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 1.082 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.356 W/kg

SAR(1 g) = 0.177 W/kg; SAR(10 g) = 0.095 W/kg

Maximum value of SAR (measured) = 0.256 W/kg




Fig A.28

LTE2600-TDD41 PC2_CH41055 Right Cheek

Date: 2020/1/18

Electronics: DAE4 Sn1289

Medium: head 2600 MHz

Medium parameters used: $f = 2636.5$; $\sigma = 1.992$ mho/m; $\epsilon_r = 38.97$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.5°C, Liquid Temperature: 22.3°C

Communication System: LTE2600-TDD41 2636.5 Duty Cycle: 1: 2.309

Probe: EX3DV4 – SN3617 ConvF(7.19,7.19,7.19)

Area Scan (71x131x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.156 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 1.526 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.166 W/kg

SAR(1 g) = 0.095 W/kg; SAR(10 g) = 0.053 W/kg

Maximum value of SAR (measured) = 0.132 W/kg




Fig A.29

LTE2600-TDD41 PC2_CH41055 Front

Date: 2020/1/18

Electronics: DAE4 Sn1289

Medium: head 2600 MHz

Medium parameters used: $f = 2636.5$; $\sigma = 1.992$ mho/m; $\epsilon_r = 38.97$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.5°C, Liquid Temperature: 22.3°C

Communication System: LTE2600-TDD41 2636.5 Duty Cycle: 1: 2.309

Probe: EX3DV4 – SN3617 ConvF(7.19,7.19,7.19)

Area Scan (71x131x1): Interpolated grid: $dx=1.000$ mm, $dy=1.500$ mm

Maximum value of SAR (interpolated) = 0.281 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 2.957 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 0.367 W/kg

SAR(1 g) = 0.187 W/kg; SAR(10 g) = 0.096 W/kg

Maximum value of SAR (measured) = 0.274 W/kg




Fig A.30

LTE1700-FDD66_CH132072 Left Cheek

Date: 2020/1/15

Electronics: DAE4 Sn1289

Medium: head 1750 MHz

Medium parameters used: $f = 2636.5$; $\sigma = 2.196$ mho/m; $\epsilon_r = 39.14$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.5°C, Liquid Temperature: 22.3°C

Communication System: LTE1700-FDD66 2636.5 Duty Cycle: 1: 1

Probe: EX3DV4 – SN3617 ConvF(8.38,8.38,8.38)

Area Scan (71x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.161 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.256 V/m; Power Drift = -0.1 dB

Peak SAR (extrapolated) = 0.169 W/kg

SAR(1 g) = 0.116 W/kg; SAR(10 g) = 0.075 W/kg

Maximum value of SAR (measured) = 0.135 W/kg




Fig A.31

LTE1700-FDD66_CH132072 Bottom

Date: 2020/1/15

Electronics: DAE4 Sn1289

Medium: head 1750 MHz

Medium parameters used: $f = 2636.5$; $\sigma = 2.196$ mho/m; $\epsilon_r = 39.14$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.5°C, Liquid Temperature: 22.3°C

Communication System: LTE1700-FDD66 2636.5 Duty Cycle: 1: 1

Probe: EX3DV4 – SN3617 ConvF(8.38,8.38,8.38)

Area Scan (71x121x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.734 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 18.31 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.864 W/kg

SAR(1 g) = 0.566 W/kg; SAR(10 g) = 0.358 W/kg

Maximum value of SAR (measured) = 0.731 W/kg




Fig A.32

LTE700-FDD71_CH133222 Left Cheek

Date: 2020/1/13

Electronics: DAE4 Sn1289

Medium: head 750 MHz

Medium parameters used: $f = 2636.5$; $\sigma = 2.682$ mho/m; $\epsilon_r = 40.24$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.5°C, Liquid Temperature: 22.3°C

Communication System: LTE700-FDD71 2636.5 Duty Cycle: 1: 1

Probe: EX3DV4 – SN3617 ConvF(10.03,10.03,10.03)

Area Scan (71x121x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.201 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 3.407 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 0.219 W/kg

SAR(1 g) = 0.18 W/kg; SAR(10 g) = 0.142 W/kg

Maximum value of SAR (measured) = 0.195 W/kg




Fig A.33

LTE700-FDD71_CH133222 Rear

Date: 2020/1/13

Electronics: DAE4 Sn1289

Medium: head 750 MHz

Medium parameters used: $f = 2636.5$; $\sigma = 2.682$ mho/m; $\epsilon_r = 40.24$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.5°C, Liquid Temperature: 22.3°C

Communication System: LTE700-FDD71 2636.5 Duty Cycle: 1: 1

Probe: EX3DV4 – SN3617 ConvF(10.03,10.03,10.03)

Area Scan (71x121x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.366 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 20.7 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.396 W/kg

SAR(1 g) = 0.313 W/kg; SAR(10 g) = 0.243 W/kg

Maximum value of SAR (measured) = 0.359 W/kg




Fig A.34

WLAN2450_CH6 Left Tilt

Date: 2020/1/17

Electronics: DAE4 Sn1289

Medium: head 2450 MHz

Medium parameters used: $f = 2437$; $\sigma = 1.806$ mho/m; $\epsilon_r = 39.85$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.5°C, Liquid Temperature: 22.3°C

Communication System: WLAN2450 2437 Duty Cycle: 1: 1

Probe: EX3DV4 – SN3617 ConvF(7.62,7.62,7.62)

Area Scan (71x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.947 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.81 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 1.34 W/kg

SAR(1 g) = 0.509 W/kg; SAR(10 g) = 0.188 W/kg

Maximum value of SAR (measured) = 0.604 W/kg




Fig A.35

WLAN2450_CH6 Top

Date: 2020/1/17

Electronics: DAE4 Sn1289

Medium: head 2450 MHz

Medium parameters used: $f = 2437$; $\sigma = 1.806$ mho/m; $\epsilon_r = 39.85$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.5°C, Liquid Temperature: 22.3°C

Communication System: WLAN2450 2437 Duty Cycle: 1: 1

Probe: EX3DV4 – SN3617 ConvF(7.62,7.62,7.62)

Area Scan (71x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.659 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.98 V/m; Power Drift = 0.1 dB

Peak SAR (extrapolated) = 0.788 W/kg

SAR(1 g) = 0.401 W/kg; SAR(10 g) = 0.196 W/kg

Maximum value of SAR (measured) = 0.451 W/kg




Fig A.36

WLAN5G_CH58 Left Tilt

Date: 2020/1/19

Electronics: DAE4 Sn1289

Medium: head 5 GHz

Medium parameters used: $f = 5290$; $\sigma = 4.769$ mho/m; $\epsilon_r = 36.03$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.5°C, Liquid Temperature: 22.3°C

Communication System: WLAN5G 5290 Duty Cycle: 1: 1

Probe: EX3DV4 – SN3617 ConvF(5.39,5.39,5.39)

Area Scan (71x121x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.954 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 8.915 V/m; Power Drift = 0.1 dB

Peak SAR (extrapolated) = 1.76 W/kg

SAR(1 g) = 0.39 W/kg; SAR(10 g) = 0.128 W/kg

Maximum value of SAR (measured) = 0.992 W/kg




Fig A.37

WLAN5G_CH155 Top

Date: 2020/1/21

Electronics: DAE4 Sn1289

Medium: head 5 GHz

Medium parameters used: $f = 5775$; $\sigma = 5.221$ mho/m; $\epsilon_r = 35.71$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.5°C, Liquid Temperature: 22.3°C

Communication System: WLAN5G 5775 Duty Cycle: 1: 1

Probe: EX3DV4 – SN3617 ConvF(5.07,5.07,5.07)

Area Scan (71x121x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.849 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 11.16 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 1.56 W/kg

SAR(1 g) = 0.351 W/kg; SAR(10 g) = 0.129 W/kg

Maximum value of SAR (measured) = 0.862 W/kg




Fig A.38



Fig. 1-1 Z-Scan at power reference point (GSM850)




Fig. 1-2 Z-Scan at power reference point (GSM850)




Fig. 1-3 Z-Scan at power reference point (PCS1900)




Fig. 1-4 Z-Scan at power reference point (PCS1900)




Fig. 1-5 Z-Scan at power reference point (WCDMA1900)




Fig. 1-6 Z-Scan at power reference point (WCDMA1900)




Fig. 1-7 Z-Scan at power reference point (WCDMA1700)




Fig. 1-8 Z-Scan at power reference point (WCDMA1700)




Fig. 1-9 Z-Scan at power reference point (WCDMA850)




Fig. 1-10 Z-Scan at power reference point (WCDMA850)




Fig. 1-11 Z-Scan at power reference point (CDMA BC0)




Fig. 1-12 Z-Scan at power reference point (CDMA BC0)




Fig. 1-13 Z-Scan at power reference point (CDMA BC1)




Fig. 1-14 Z-Scan at power reference point (CDMA BC1)




Fig. 1-15 Z-Scan at power reference point (CDMA BC10)




Fig. 1-16 Z-Scan at power reference point (CDMA BC10)




Fig. 1-17 Z-Scan at power reference point (LTE Band 7)




Fig. 1-18 Z-Scan at power reference point (LTE Band 7)



Fig. 1-19 Z-Scan at power reference point (LTE Band12)



Fig. 1-20 Z-Scan at power reference point (LTE Band12)




Fig. 1-21 Z-Scan at power reference point (LTE Band13)



Fig. 1-22 Z-Scan at power reference point (LTE Band13)




Fig. 1-23 Z-Scan at power reference point (LTE Band25)




Fig. 1-24 Z-Scan at power reference point (LTE Band25)




Fig. 1-25 Z-Scan at power reference point (LTE Band26)




Fig. 1-26 Z-Scan at power reference point (LTE Band26)




Fig. 1-27 Z-Scan at power reference point (LTE Band41-PC3)




Fig. 1-28 Z-Scan at power reference point (LTE Band41-PC3)




Fig. 1-29 Z-Scan at power reference point (LTE Band41-PC2)




Fig. 1-30 Z-Scan at power reference point (LTE Band41-PC2)




Fig. 1-31 Z-Scan at power reference point (LTE Band66)




Fig. 1-32 Z-Scan at power reference point (LTE Band66)




Fig. 1-33 Z-Scan at power reference point (LTE Band71)




Fig. 1-34 Z-Scan at power reference point (LTE Band71)




Fig. 1-35 Z-Scan at power reference point (2450 MHz)




Fig. 1-36 Z-Scan at power reference point (2450 MHz)




Fig. 1-37 Z-Scan at power reference point (5 GHz)




Fig. 1-38 Z-Scan at power reference point (5 GHz)

ANNEX B System Verification Results

750 MHz

Date: 1/13/2020

Electronics: DAE4 Sn1289

Medium: Head 750 MHz

Medium parameters used: $f = 750 \text{ MHz}$; $\sigma = 0.89 \text{ mho/m}$; $\epsilon_r = 42.5$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 22.5°C Liquid Temperature: 22.3°C

Communication System: CW Frequency: 750 MHz Duty Cycle: 1:1

Probe: EX3DV4 – SN3617 ConvF(10.03,10.03,10.03)

System Validation /Area Scan (81x191x1): Interpolated grid: $dx=1.000 \text{ mm}$, $dy=1.000 \text{ mm}$

Reference Value = 58.99 V/m ; Power Drift = -0.02

Fast SAR: SAR(1 g) = 2.12 W/kg ; SAR(10 g) = 1.39 W/kg

Maximum value of SAR (interpolated) = 2.82 W/kg


System Validation /Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 58.99 V/m ; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 3.23 W/kg

SAR(1 g) = 2.18 W/kg ; SAR(10 g) = 1.36 W/kg

Maximum value of SAR (measured) = 2.82 W/kg



$0 \text{ dB} = 2.82 \text{ W/kg} = 4.5 \text{ dB W/kg}$

Fig.B.1 validation 750 MHz 250mW

835 MHz

Date: 1/14/2020

Electronics: DAE4 Sn1289

Medium: Head 835 MHz

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.888 \text{ mho/m}$; $\epsilon_r = 40.69$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 22.5°C Liquid Temperature: 22.3°C

Communication System: CW Frequency: 835 MHz Duty Cycle: 1:1

Probe: EX3DV4 – SN3617 ConvF(9.75,9.75,9.75)

System Validation /Area Scan (81x191x1): Interpolated grid: $dx=1.000 \text{ mm}$, $dy=1.000 \text{ mm}$

Reference Value = 63.17 V/m; Power Drift = 0.1

Fast SAR: SAR(1 g) = 2.39 W/kg; SAR(10 g) = 1.54 W/kg

Maximum value of SAR (interpolated) = 3.11 W/kg


System Validation /Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value =63.17 V/m; Power Drift = 0.1 dB

Peak SAR (extrapolated) = 3.59 W/kg

SAR(1 g) = 2.45 W/kg; SAR(10 g) = 1.56 W/kg

Maximum value of SAR (measured) = 3.23 W/kg



0 dB = 3.23 W/kg = 5.09 dB W/kg

Fig.B.3 validation 835 MHz 250mW

1750 MHz

Date: 1/15/2020

Electronics: DAE4 Sn1289

Medium: Head 1750 MHz

Medium parameters used: $f = 1750$ MHz; $\sigma = 1.354$ mho/m; $\epsilon_r = 40.2$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.5°C Liquid Temperature: 22.3°C

Communication System: CW Frequency: 1750 MHz Duty Cycle: 1:1

Probe: EX3DV4 – SN3617 ConvF(8.38,8.38,8.38)

System Validation /Area Scan (81x191x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Reference Value = 106.22 V/m; Power Drift = 0.01

Fast SAR: SAR(1 g) = 9.32 W/kg; SAR(10 g) = 4.92 W/kg

Maximum value of SAR (interpolated) = 13.82 W/kg


System Validation /Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value =106.22 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 16.63 W/kg

SAR(1 g) = 9.12 W/kg; SAR(10 g) = 4.92 W/kg

Maximum value of SAR (measured) = 13.72 W/kg



0 dB = 13.72 W/kg = 11.37 dB W/kg

Fig.B.5 validation 1750 MHz 250mW