




Fig.48. Conducted spurious emission: 8DPSK, Channel 39, 2441MHz




Fig.49. Conducted spurious emission: 8DPSK, Channel 39, 30MHz - 1GHz




Fig.50. Conducted spurious emission: 8DPSK, Channel 39, 1GHz - 3GHz




Fig.51. Conducted spurious emission: 8DPSK, Channel 39, 3GHz - 10GHz




Fig.52. Conducted spurious emission: 8DPSK, Channel 39, 10GHz – 26GHz




Fig.53. Conducted spurious emission: 8DPSK, Channel 78, 2480MHz




Fig.54. Conducted spurious emission: 8DPSK, Channel 78, 30MHz - 1GHz




Fig.55. Conducted spurious emission: 8DPSK, Channel 78, 1GHz - 3GHz




Fig.56. Conducted spurious emission: 8DPSK, Channel 78, 3GHz - 10GHz




Fig.57. Conducted spurious emission: 8DPSK, Channel 78, 10GHz - 26GHz

A.5. Transmitter Spurious Emission - Radiated

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247, 15.205, 15.209	20dB below peak output power

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

The measurement is made according to ANSI C63.10

Limit in restricted band:

Frequency of emission (MHz)	Field strength(uV/m)	Field strength(dBuV/m)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

Test Condition

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	100KHz/300KHz	5
1000-4000	1MHz/3MHz	15
4000-18000	1MHz/3MHz	40
18000-26500	1MHz/3MHz	20

Measurement Results:

Result= $P_{Mea} + ARPL$

For GFSK

Channel	Frequency Range	Test Results	Conclusion
Power	2.31GHz~2.4GHz---L	Fig.58	P
Power	2.45GHz~2.5GHz---H	Fig.59	P

For $\pi/4$ DQPSK

Channel	Frequency Range	Test Results	Conclusion
Power	2.31GHz~2.4GHz---L	Fig.60	P
Power	2.45GHz~2.5GHz---H	Fig.61	P

For 8DPSK

Channel	Frequency Range	Test Results	Conclusion
Power	2.31GHz~2.4GHz---L	Fig.62	P
Power	2.45GHz~2.5GHz---H	Fig.63	P

GFSK Ch 0 - Average

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)	Antenna Height (cm)	Turntable angle (deg)
2383.800	46.16	2.9	32.0	11.29	54.0	7.8	H	155	48
2389.100	46.22	2.9	32.0	11.33	54.0	7.8	H	155	70
4804.500	29.96	-35.0	34.1	30.84	54.0	24.0	H	155	92
7206.000	33.62	-32.4	35.7	30.27	54.0	20.4	H	155	112
9607.500	46.71	-29.7	36.7	39.66	54.0	7.3	H	155	136
12010.500	37.64	-30.5	38.9	29.24	54.0	16.4	H	155	156

GFSK Ch 39 - Average

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)	Antenna Height (cm)	Turntable angle (deg)
2437.100	46.22	2.9	32.1	11.22	54.0	7.8	H	155	180
2445.300	46.27	2.9	32.1	11.25	54.0	7.7	H	155	204
4882.500	30.56	-35.5	34.2	31.93	54.0	23.4	H	155	222
7323.000	34.98	-31.3	35.8	30.53	54.0	19.0	H	155	245
9763.500	43.15	-31.4	36.9	37.63	54.0	10.9	H	155	72
12205.500	37.42	-28.9	38.9	27.34	54.0	16.6	H	155	94

GFSK Ch 78 - Average

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)	Antenna Height (cm)	Turntable angle (deg)
2483.500	51.05	2.9	32.2	15.94	54.0	3.0	H	155	28
2483.600	49.26	2.9	32.2	14.15	54.0	4.7	H	155	74
4960.500	30.82	-34.9	34.2	31.51	54.0	23.2	H	155	140
7440.000	35.20	-32.2	35.8	31.59	54.0	18.8	H	155	8
9919.500	42.49	-29.6	37.1	35.04	54.0	11.5	H	155	80
12400.500	38.62	-30.0	39.0	29.66	54.0	15.4	H	155	243

$\pi/4$ DQPSK Ch 0 - Average

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)	Antenna Height (cm)	Turntable angle (deg)
2386.700	46.11	2.9	32.0	11.24	54.0	7.9	H	155	24
2388.300	46.09	2.9	32.0	11.20	54.0	7.9	H	155	336
4804.500	30.08	-35.0	34.1	30.96	54.0	23.9	H	155	248
7206.000	33.72	-32.4	35.7	30.37	54.0	20.3	H	155	268
9607.500	46.98	-29.7	36.7	39.93	54.0	7.0	H	155	290
12010.500	37.64	-30.5	38.9	29.23	54.0	16.4	H	155	300

$\pi/4$ DQPSK Ch 39 - Average

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)	Antenna Height (cm)	Turntable angle (deg)
2437.200	48.17	2.9	32.1	13.17	54.0	5.8	H	155	268
2445.312	48.84	2.9	32.1	13.83	54.0	5.2	H	155	290
4882.500	30.66	-35.5	34.2	32.03	54.0	23.3	H	155	312
7323.000	35.21	-31.3	35.8	30.76	54.0	18.8	H	155	46
9763.500	43.08	-31.4	36.9	37.57	54.0	10.9	H	155	70
12205.500	37.43	-28.9	38.9	27.34	54.0	16.6	H	155	92

$\pi/4$ DQPSK Ch 78 - Average

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)	Antenna Height (cm)	Turntable angle (deg)
2483.500	51.62	2.9	32.2	16.51	54.0	2.4	H	155	92
2483.650	51.42	2.9	32.2	16.31	54.0	2.6	H	155	115
4960.500	31.11	-34.9	34.2	31.81	54.0	22.9	H	155	135
7440.000	35.56	-32.2	35.8	31.95	54.0	18.4	H	155	156
9919.500	43.77	-29.6	37.1	36.31	54.0	10.2	H	155	180
12400.500	38.91	-30.0	39.0	29.96	54.0	15.1	H	155	204

8DPSK Ch 0 - Average

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)	Antenna Height (cm)	Turntable angle (deg)
2383.890	46.46	2.9	32.0	11.59	54.0	7.5	H	155	8
2388.760	46.47	2.9	32.0	11.59	54.0	7.5	H	155	26
4804.500	30.12	-35.0	34.1	31.00	54.0	23.9	H	155	72
7206.000	33.80	-32.4	35.7	30.45	54.0	20.2	H	155	136
9607.500	46.33	-29.7	36.7	39.27	54.0	7.7	H	155	94
12010.500	37.61	-30.5	38.9	29.21	54.0	16.4	H	155	48

8DPSK Ch 39 - Average

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)	Antenna Height (cm)	Turntable angle (deg)
2437.020	47.63	2.9	32.1	12.64	54.0	6.4	H	155	4
2449.200	47.69	2.9	32.1	12.66	54.0	6.3	H	155	32
4882.500	30.61	-35.5	34.2	31.98	54.0	23.4	H	155	72
7323.000	35.13	-31.3	35.8	30.68	54.0	18.9	H	155	90
9763.500	43.65	-31.4	36.9	38.14	54.0	10.3	H	155	46
12205.500	37.44	-28.9	38.9	27.36	54.0	16.6	H	155	16

8DPSK Ch 78 - Average

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)	Antenna Height (cm)	Turntable angle (deg)
2483.500	53.07	2.9	32.2	17.97	54.0	0.9	H	155	98
2483.890	51.50	2.9	32.2	16.40	54.0	2.5	H	155	135
4960.500	30.48	-34.9	34.2	31.17	54.0	23.5	H	155	4
7440.000	35.08	-32.2	35.8	31.46	54.0	18.9	H	155	74
9919.500	42.33	-29.6	37.1	34.87	54.0	11.7	H	155	48
12400.500	38.57	-30.0	39.0	29.62	54.0	15.4	H	155	246

GFSK Ch 0 – Peak

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)	Antenna Height (cm)	Turntable angle (deg)
2333.450	59.94	2.8	31.9	25.19	74.0	14.1	H	155	44
2356.130	60.11	2.8	32.0	25.31	74.0	13.9	H	155	66
4804.000	40.27	-35.0	34.1	41.15	74.0	33.7	H	155	88
7206.000	43.93	-32.4	35.7	40.58	74.0	30.1	H	155	110
9608.000	49.76	-29.7	36.7	42.69	74.0	24.2	H	155	132
12010.000	48.00	-30.5	38.9	39.59	74.0	26.0	H	155	154

GFSK Ch 39 - Peak

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)	Antenna Height (cm)	Turntable angle (deg)
2315.600	48.12	-27.8	31.9	44.00	74.0	25.9	H	155	176
2907.620	49.78	-25.4	32.5	42.63	74.0	24.2	H	155	198
4882.000	41.63	-35.5	34.2	43.00	74.0	32.4	H	155	220
7323.000	45.60	-31.3	35.8	41.14	74.0	28.4	V	155	242
9764.000	51.28	-31.4	36.9	45.77	74.0	22.7	H	155	66
12205.000	47.50	-28.8	38.9	37.40	74.0	26.5	H	155	88

GFSK Ch 78 - Peak

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)	Antenna Height (cm)	Turntable angle (deg)
2485.705	60.46	2.9	32.2	25.34	74.0	13.5	H	155	22
2488.705	60.52	2.9	32.2	25.41	74.0	13.5	H	155	66
4960.000	41.35	-34.9	34.2	42.05	74.0	32.6	V	155	132
7440.000	45.94	-32.2	35.8	42.33	74.0	28.1	H	155	0
9919.500	50.67	-29.6	37.1	43.21	74.0	23.3	V	155	88
12400.000	48.49	-30.0	39.0	39.55	74.0	25.5	V	155	242

$\pi/4$ DQPSK Ch 0 - Peak

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)	Antenna Height (cm)	Turntable angle (deg)
2375.380	59.93	2.9	32.0	25.08	74.0	14.1	H	155	22
2389.688	60.05	2.9	32.0	25.17	74.0	13.9	H	155	330
4804.000	40.21	-35.0	34.1	41.08	74.0	33.8	H	155	242
7206.000	44.20	-32.4	35.7	40.85	74.0	29.8	V	155	264
9608.000	49.82	-29.7	36.7	42.75	74.0	24.2	V	155	286
12010.000	46.99	-30.5	38.9	38.58	74.0	27.0	V	155	308

$\pi/4$ DQPSK Ch 39 - Peak

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)	Antenna Height (cm)	Turntable angle (deg)
2303.650	47.60	-27.8	31.9	43.55	74.0	26.4	H	155	264
2662.380	48.84	-26.7	32.3	43.23	74.0	25.2	H	155	286
4882.000	40.83	-35.5	34.2	42.20	74.0	33.2	V	155	308
7323.000	45.02	-31.3	35.8	40.57	74.0	29.0	H	155	44
9764.000	50.91	-31.4	36.9	45.40	74.0	23.1	H	155	66
12205.000	46.81	-28.8	38.9	36.71	74.0	27.2	V	155	88

$\pi/4$ DQPSK Ch 78 - Peak

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)	Antenna Height (cm)	Turntable angle (deg)
2483.475	61.31	2.9	32.2	26.20	74.0	12.7	H	155	88
2483.690	60.76	2.9	32.2	25.66	74.0	13.2	H	155	110
4960.000	40.94	-34.9	34.2	41.63	74.0	33.1	H	155	132
7440.000	44.57	-32.2	35.8	40.95	74.0	29.4	V	155	154
9919.500	51.52	-29.6	37.1	44.06	74.0	22.5	V	155	176
12400.000	48.94	-30.0	39.0	39.99	74.0	25.1	H	155	198

8DPSK Ch 0 - Peak

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)	Antenna Height (cm)	Turntable angle (deg)
2365.740	60.92	2.8	32.0	26.09	74.0	13.1	H	155	0
2387.924	60.53	2.9	32.0	25.65	74.0	13.5	H	155	22
4804.000	41.02	-35.0	34.1	41.90	74.0	33.0	H	155	66
7206.000	44.91	-32.4	35.7	41.55	74.0	29.1	V	155	132
9608.000	54.61	-29.7	36.7	47.54	74.0	19.4	H	155	88
12010.000	48.23	-30.5	38.9	39.82	74.0	25.8	V	155	44

8DPSK Ch 39 - Peak

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)	Antenna Height (cm)	Turntable angle (deg)
2124.000	47.77	-28.6	31.5	44.83	74.0	26.2	H	155	0
2965.600	50.52	-28.1	32.6	46.07	74.0	23.5	H	155	22
4882.000	40.44	-35.5	34.2	41.81	74.0	33.6	V	155	66
7323.000	44.89	-31.3	35.8	40.43	74.0	29.1	V	155	88
9764.000	52.89	-31.4	36.9	47.38	74.0	21.1	V	155	44
12205.000	47.25	-28.8	38.9	37.15	74.0	26.8	H	155	22

8DPSK Ch 78 - Peak

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)	Antenna Height (cm)	Turntable angle (deg)
2403.545	61.52	2.9	32.0	26.60	74.0	12.5	H	155	88
2489.960	60.53	2.9	32.2	25.41	74.0	13.5	H	155	132
4960.000	41.11	-34.9	34.2	41.80	74.0	32.9	H	155	0
7440.000	46.26	-32.2	35.8	42.65	74.0	27.7	V	155	66
9920.000	51.11	-29.7	37.1	43.67	74.0	22.9	V	155	44
12400.000	48.29	-30.0	39.0	39.34	74.0	25.7	H	155	242

Conclusion: PASS

Test graphs as below:




Fig.58. Radiated emission (Power): GFSK, low channel




Fig.59. Radiated emission (Power) GFSK, high channel

RE - Power-2.31GHz-2.45GHz




Fig.60. Radiated emission (Power): $\pi/4$ DQPSK, low channel

RE - Power-2.45GHz-2.5GHz




Fig.61. Radiated emission (Power): $\pi/4$ DQPSK, high channel




Fig.62. Radiated emission (Power): 8DPSK, low channel




Fig.63. Radiated emission (Power): 8DPSK, high channel

A.6. Time of Occupancy (Dwell Time)

Method of Measurement: See ANSI C63.10-clause 7.8.4

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- Span = zero span, centered on a hopping channel
- RBW = 1 MHz
- VBW $\geq$ RBW
- Sweep = as necessary to capture the entire dwell time per hopping channel
- Detector function = peak
- Trace = max hold

Measure a pulse time in time domain at middle frequency and then count the hopping number in 31.6s(which equals with 0.4 multiply 79) of middle frequency ,then multiply the pulse time and hopping number and record them.

Measurement Limit:

Standard	Limit (ms)
FCC 47 CFR Part 15.247(a) (1)(iii)	< 400

Measurement Result:

For GFSK

Channel	Packet	Pulse time (ms)		Number of Transmissions		Dwell Time (ms)	Conclusion
39	DH1	Fig.64	0.38	Fig.65	318	120.84	P
	DH3	Fig.66	1.64	Fig.67	99	162.36	P
	DH5	Fig.68	2.89	Fig.69	71	205.19	P

For $\pi/4$ DQPSK

Channel	Packet	Pulse time (ms)		Number of Transmissions		Dwell Time (ms)	Conclusion
39	2DH1	Fig.70	0.39	Fig.71	320	124.8	P
	2DH3	Fig.72	1.64	Fig.73	108	177.12	P
	2DH5	Fig.74	2.89	Fig.75	69	199.41	P

For 8DPSK

Channel	Packet	Pulse time (ms)		Number of Transmissions		Dwell Time (ms)	Conclusion
39	3DH1	Fig.76	0.39	Fig.77	319	124.41	P
	3DH3	Fig.78	1.64	Fig.79	106	173.84	P
	3DH5	Fig.80	2.89	Fig.81	67	193.63	P

Conclusion: PASS

Test graphs as below:




Fig.64. Time of occupancy (Dwell Time): Channel 39, Packet DH1




Fig.65. Number of Transmissions Measurement: Channel 39,Packet DH1




Fig.66. Time of occupancy (Dwell Time): Channel 39, Packet DH3




Fig.67. Number of Transmissions Measurement: Channel 39,Packet DH3



Fig.68. Time of occupancy (Dwell Time): Channel 39, Packet DH5




Fig.69. Number of Transmissions Measurement: Channel 39,Packet DH5




Fig.70. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH1




Fig.71. Number of Transmissions Measurement: Channel 39,Packet 2-DH1




Fig.72. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH3




Fig.73. Number of Transmissions Measurement: Channel 39,Packet 2-DH3




Fig.74. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH5




Fig.75. Number of Transmissions Measurement: Channel 39,Packet 2-DH5




Fig.76. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH1




Fig.77. Number of Transmissions Measurement: Channel 39,Packet 3-DH1




Fig.78. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH3




Fig.79. Number of Transmissions Measurement: Channel 39,Packet 3-DH3




Fig.80. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH5




Fig.81. Number of Transmissions Measurement: Channel 39,Packet 3-DH5

A.7. 20dB Bandwidth

Method of Measurement: See ANSI C63.10-clause 6.9.2

Measurement Procedure - Unwanted Emissions

1. Set RBW = 30kHz.
2. Set VBW = 100 kHz.
3. Set span to 3MHz
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.
7. Allow the trace to stabilize (this may take some time, depending on the extent of the span).

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247(a)(1)	NA *

Use NdB Down function of the SA to measure the 20dB Bandwidth

* Comment: This test case is not required according to the latest FCC 47 CFR Part 15.247. But the test results are necessary for “carrier frequency separation” test case, in Annex A.8.

Measurement Results:

For GFSK

Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.82	940.50	NA
39	Fig.83	942.75	NA
78	Fig.84	939.75	NA

For $\pi/4$ DQPSK

Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.85	1293.75	NA
39	Fig.86	1295.25	NA
78	Fig.87	1298.25	NA

For 8DPSK

Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.88	1277.25	NA
39	Fig.89	1280.25	NA
78	Fig.90	1279.50	NA

Conclusion: NA

Test graphs as below:




Fig.82. 20dB Bandwidth: GFSK, Channel 0




Fig.83. 20dB Bandwidth: GFSK, Channel 39




Fig.84. 20dB Bandwidth: GFSK, Channel 78




Fig.85. 20dB Bandwidth: $\pi/4$ DQPSK, Channel 0




Fig.86. 20dB Bandwidth: $\pi/4$ DQPSK, Channel 39




Fig.87. 20dB Bandwidth: $\pi/4$ DQPSK, Channel 78




Fig.88. 20dB Bandwidth: 8DPSK, Channel 0




Fig.89. 20dB Bandwidth: 8DPSK, Channel 39




Fig.90. 20dB Bandwidth: 8DPSK, Channel 78

A.8. Carrier Frequency Separation

Method of Measurement: See ANSI C63.10-clause 7.8.2

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- Span = 3MHz
- RBW=300kHz
- VBW=300kHz
- Sweep = auto
- Detector function = peak
- Trace = max hold
- Allow the trace to stabilize

Search the peak marks of the middle frequency and adjacent channel, then record the separation between them.

* Comment: This limit should be over 25 kHz or $(2/3) * 20\text{dB}$ bandwidth, whichever is greater.

Measurement Limit:

Standard	Limit(kHz)
FCC 47 CFR Part 15.247(a)(1)	over 25 kHz or $(2/3) * 20\text{dB}$ bandwidth

Measurement Result:

For GFSK

Channel	Carrier frequency separation (kHz)		Conclusion
39	Fig.91	990.75	P

For $\pi/4$ DQPSK

Channel	Carrier frequency separation (kHz)		Conclusion
39	Fig.92	982.50	P

For 8DPSK

Channel	Carrier frequency separation (kHz)		Conclusion
39	Fig.93	978.00	P

Conclusion: PASS

Test graphs as below:




Fig.91. Carrier frequency separation measurement: GFSK, Channel 39




Fig.92. Carrier frequency separation measurement: $\pi/4$ DQPSK, Channel 39




Fig.93. Carrier frequency separation measurement: 8DPSK, Channel 39

A.9. Number of Hopping Channels

Method of Measurement: See ANSI C63.10-clause 7.8.3

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- Span = the frequency band of operation
- RBW = 500kHz
- VBW = 500kHz
- Sweep = auto
- Detector function = peak
- Trace = max hold
- Allow the trace to stabilize

It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies. Compliance of an EUT with the appropriate regulatory limit shall be determined for the number of hopping channels. A plot of the data shall be included in the test report.

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247(a) (1)(iii)	At least 15 non-overlapping channels

Measurement Result:

For GFSK

Channel	Number of hopping channels		Conclusion
0~39	Fig.94	79	P
40~78	Fig.95		

For $\pi/4$ DQPSK

Channel	Number of hopping channels		Conclusion
0~39	Fig.96	79	P
40~78	Fig.97		

For 8DPSK

Channel	Number of hopping channels		Conclusion
0~39	Fig.98	79	P
40~78	Fig.99		

Conclusion: PASS

Test graphs as below:




Fig.94. Number of hopping frequencies: GFSK, Channel 0 - 39




Fig.95. Number of hopping frequencies: GFSK, Channel 40 - 78




Fig.96. Number of hopping frequencies: $\pi/4$ DQPSK, Channel 0 - 39




Fig.97. Number of hopping frequencies: $\pi/4$ DQPSK, Channel 40 - 78




Fig.98. Number of hopping frequencies: 8DPSK, Channel 0 - 39




Fig.99. Number of hopping frequencies: 8DPSK, Channel 40 - 78

A.10. AC Powerline Conducted Emission

Method of Measurement: See ANSI C63.10-clause 6.2

1. the one EUT cable configuration and arrangement and mode of operation that produced the emission with the highest amplitude relative to the limit is selected for the final measurement, while applying the appropriate modulating signal to the EUT.
2. If the EUT is relocated from an exploratory test site to a final test site, the highest emissions shall be remaximized at the final test location before final ac power-line conducted emission measurements are performed.
3. The final test on all current-carrying conductors of all of the power cords to the equipment that comprises the EUT (but not the cords associated with other non-EUT equipment in the system) is then performed for the full frequency range for which the EUT is being tested for compliance without further variation of the EUT arrangement, cable positions, or EUT mode of operation.
4. If the EUT is comprised of equipment units that have their own separate ac power connections, e.g., floor-standing equipment with independent power cords for each shelf that are able to connect directly to the ac power network, each current-carrying conductor of one unit is measured while the other units are connected to a second (or more) LISN(s). All units shall be separately measured. If a power strip is provided by the manufacturer, to supply all of the units making up the EUT, only the conductors in the power cord of the power strip shall be measured.
5. If the EUT uses a detachable antenna, these measurements shall be made with a suitable dummy load connected to the antenna output terminals; otherwise, the tests shall be made with the antenna connected and, if adjustable, fully extended. When measuring the ac conducted emissions from a device that operates between 150 kHz and 30 MHz a non-detachable antenna may be replaced with a dummy load for the measurements within the fundamental emission band of the transmitter, but only for those measurements.³⁶ Record the six highest EUT emissions relative to the limit of each of the current-carrying conductors of the power cords of the equipment that comprises the EUT over the frequency range specified by the procuring or regulatory agency. Diagram or photograph the test setup that was used. See Clause 8 for full reporting requirements.

Test Condition

Voltage (V)	Frequency (Hz)
120	60

Measurement Result and limit:

Bluetooth (Quasi-peak Limit)

Frequency range (MHz)	Quasi-peak Limit (dB μ V)	Conclusion
0.15 to 0.5	66 to 56	P
0.5 to 5	56	
5 to 30	60	

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

Bluetooth (Average Limit)


Frequency range (MHz)	Average Limit (dBμV)	Conclusion
0.15 to 0.5	56 to 46	P
0.5 to 5	46	
5 to 30	50	
NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.		

The measurement is made according to ANSI C63.10

Conclusion: PASS

Test graphs as below:

Traffic (With AE3):



Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.


Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.159000	48.0	10000.0	9.000	On	L1	27.1	17.5	65.5
0.321000	31.1	10000.0	9.000	On	L1	20.0	28.6	59.7
0.559500	25.4	10000.0	9.000	On	L1	20.0	30.6	56.0
1.284000	8.7	10000.0	9.000	On	L1	19.8	47.3	56.0
4.807500	41.6	10000.0	9.000	On	L1	19.8	14.4	56.0
9.595500	44.1	10000.0	9.000	On	L1	19.9	15.9	60.0

Final Result 2

Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.159000	32.5	10000.0	9.000	On	L1	27.1	23.0	55.5
0.321000	20.4	10000.0	9.000	On	L1	20.0	29.3	49.7
0.559500	17.4	10000.0	9.000	On	L1	20.0	28.6	46.0
1.288500	5.2	10000.0	9.000	On	L1	19.8	40.8	46.0
4.726500	28.6	10000.0	9.000	On	L1	19.8	17.4	46.0
9.658500	28.1	10000.0	9.000	On	L1	19.9	21.9	50.0

Idle (With AE3):



Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.




Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.235500	37.2	10000.0	9.000	On	L1	20.0	25.1	62.3
0.393000	32.4	10000.0	9.000	On	L1	20.0	25.6	58.0
0.708000	20.6	10000.0	9.000	On	L1	20.0	35.4	56.0
1.725000	20.5	10000.0	9.000	On	L1	19.8	35.5	56.0
4.137000	42.1	10000.0	9.000	On	N	19.8	13.9	56.0
12.583500	52.2	10000.0	9.000	On	L1	20.0	7.8	60.0

Final Result 2

Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.235500	26.4	10000.0	9.000	On	L1	20.0	25.9	52.3
0.393000	26.7	10000.0	9.000	On	L1	20.0	21.3	48.0
0.703500	26.7	10000.0	9.000	On	L1	20.0	19.3	46.0
1.725000	5.9	10000.0	9.000	On	L1	19.8	40.1	46.0
4.222500	26.3	10000.0	9.000	On	L1	19.8	19.7	46.0
12.826500	31.1	10000.0	9.000	On	N	20.0	18.9	50.0

ANNEX B: Accreditation Certificate

United States Department of Commerce National Institute of Standards and Technology NVLAP[®] Certificate of Accreditation to ISO/IEC 17025:2005 NVLAP LAB CODE: 600118-0 Telecommunication Technology Labs, CAICT Beijing China <i>is accredited by the National Voluntary Laboratory Accreditation Program for specific services, listed on the Scope of Accreditation, for:</i> Electromagnetic Compatibility & Telecommunications <i>This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated January 2009).</i> <table><tr><td> 2019-09-26 through 2020-09-30 <i>Effective Dates</i> </td><td></td><td>  <i>For the National Voluntary Laboratory Accreditation Program</i> </td></tr></table>		2019-09-26 through 2020-09-30 <i>Effective Dates</i>		 <i>For the National Voluntary Laboratory Accreditation Program</i>
2019-09-26 through 2020-09-30 <i>Effective Dates</i>		 <i>For the National Voluntary Laboratory Accreditation Program</i>		

*****END OF REPORT*****