



FCC PART 15E TEST REPORT No.25T04Z200152-006

for

Samsung Electronics Co., Ltd.

Tablet with Bluetooth, WLAN

SM-X133

FCC ID: ZCASM133

with

Hardware Version: REV1.0

Software Version: X133.001

Issued Date: 2025-07-21

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

Test Laboratory:

CTTL-Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: cttl_terminals@caict.ac.cn, website: www.caict.ac.cn

REPORT HISTORY

Report Number	Revision	Description	Issue Date
25T04Z200152-006	Rev.0	1st edition	2025-07-21

Note: the latest revision of the test report supersedes all previous version.

CONTENTS

1. TEST LABORATORY	5
1.1. INTRODUCTION & ACCREDITATION	5
1.2. TESTING LOCATION	5
1.3. TESTING ENVIRONMENT	5
1.4. PROJECT DATE	5
1.5. SIGNATURE	5
2. CLIENT INFORMATION	6
2.1. APPLICANT INFORMATION	6
2.2. MANUFACTURER INFORMATION	6
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	7
3.1. ABOUT EUT	7
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	7
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	7
3.4. GENERAL DESCRIPTION	7
4. REFERENCE DOCUMENTS	8
4.1. DOCUMENTS SUPPLIED BY APPLICANT	8
4.2. REFERENCE DOCUMENTS FOR TESTING	8
5. LABORATORY ENVIRONMENT	8
6. TEST RESULTS	9
6.1. SUMMARY OF TEST RESULTS	9
6.2. STATEMENTS	9
6.3. TEST CONDITIONS	9
7. TEST FACILITIES UTILIZED	10
8. MEASUREMENT UNCERTAINTY	11
8.1. TRANSMITTER OUTPUT POWER	11
8.2. PEAK POWER SPECTRAL DENSITY	11
8.3. 6dB EMISSION BANDWIDTH	11
8.4. BAND EDGES COMPLIANCE	11
8.5. SPURIOUS EMISSIONS	11
8.6. RADIATED UNWANTED EMISSION	11
8.7. AC POWER-LINE CONDUCTED EMISSION	11
ANNEX A: MEASUREMENT RESULTS	12
A.1. MEASUREMENT METHOD	12
A.2. MAXIMUM PEAK OUTPUT POWER	13
A.2.1 ANTENNA GAIN	13
A.2.2. MAXIMUM AVERAGE OUTPUT POWER-CONDUCTED	13



No.25T04Z200152-006

A.3. PEAK POWER SPECTRAL DENSITY	17
A.4. 6dB EMISSION BANDWIDTH	19
A.5. RADIATED UNWANTED EMISSION	24
A.6. AC POWERLINE CONDUCTED EMISSION	44
A.7. ANTENNA REQUIREMENT	48
ANNEX B: EUT PARAMETERS.....	48
ANNEX C: ACCREDITATION CERTIFICATE.....	49

1. Test Laboratory

1.1. Introduction & Accreditation

Telecommunication Technology Labs, CAICT is an ISO/IEC 17025:2017 accredited test laboratory under American Association for Laboratory Accreditation (A2LA) with lab code 7049.01, and is also an FCC accredited test laboratory (CN1349), and ISED accredited test laboratory (CAB identifier:CN0066). The detail accreditation scope can be found on A2LA website.

1.2. Testing Location

Conducted testing Location:CTTL(Gaolizhang Road)

Address: Cuihu Cloud Center, No.1, Gaolizhang Road, Wenquan,
Haidian District, Beijing, China

Radiated testing Location: CTTL (BDA)

Address: No.18A, Kangding Street, Beijing Economic-Technology
Development Area, Beijing, P. R. China 100176

1.3. Testing Environment

Normal Temperature: 15-35°C

Relative Humidity: 20-75%

1.4. Project date

Testing Start Date: 2025-06-06


Testing End Date: 2025-07-21

1.5. Signature



Yao Xingyu

(Prepared this test report)



Zheng Wei

(Reviewed this test report)



Pang Shuai

(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name: Samsung Electronics Co., Ltd.
Address: 19 Chapin Rd., Building D Pine Brook, NJ 07058
Contact: Jenni Chun
Email: j1.chun@samsung.com
Telephone: +1-201-937-4203
Fax: /

2.2. Manufacturer Information

Company Name: Samsung Electronics Co., Ltd.
Address: 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, Republic of Korea
Contact: Kobe Cho
Email: ggobi.cho@samsung.com
Telephone: +82 - 10 - 2722 - 4159
Fax: /

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	Tablet with Bluetooth, WLAN
Model name	SM-X133
FCC ID	ZCASM133
WLAN Frequency Band	ISM Band: 5725MHz~5850MHz
Type of modulation	OFDM
Normal Voltage	3.82V
Extreme High Voltage	4.4V
Extreme Low Voltage	3.45V

3.2. Internal Identification of EUT used during the test

EUT ID*	IMEI	HW Version	SW Version	Date of receipt
UT08a	2504200152UT08a	REV1.0	X133.001	2025-06-20
UT04a	2504200152UT04a	REV1.0	X133.001	2025-06-06

*EUT ID: is used to identify the test sample in the lab internally.

UT08a is used for Conduction test, UT04a is used for Radiation test.

3.3. Internal Identification of AE used during the test

AE ID*	Name	Model	Manufacturer
AE1-1	Battery	HQ-3565S	SCUD(Fujian) Electronics Co., Ltd.
AE1-2	Battery	HQ-6739SDS	SCUD(Fujian) Electronics Co., Ltd.
AE2*	Adapter	EP-T1510	DongYang
AE3-1	Date Cable C-C	EP-DN980BWE	Cresyn
AE3-2	Date Cable C-C	EP-DN980BWE	Luxshare

*AE ID: is used to identify the test sample in the lab internally.

*AE2 is not the AE for EUT, provided by the client for relevant tests.

3.4. General Description

Equipment Under Test (EUT) is a model of Tablet with Bluetooth, WLAN with integrated antenna.

It consists of normal options: Battery and Charger.

Manual and specifications of the EUT were provided to fulfil the test.

Samples undergoing test were selected by the Client.

4. Reference Documents

4.1. Documents supplied by applicant

EUT feature information is supplied by the applicant or manufacturer, which is the basis of testing.

4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

FCC Part15	FCC CFR 47, Part 15, Subpart C and E:	
	15.205 Restricted bands of operation;	
	15.207 Conducted limits;	2021
	15.209 Radiated emission limits, general requirements;	
ANSI C63.10	15.407 General technical requirements.	
	Methods of Measurement of Radio-Noise Emissions from	
	Low-Voltage Electrical and Electronic Equipment in the	2013
	Range of 9 kHz to 40 GHz	
UNII: KDB 789033	General U-NII Test Procedures New Rules v02r01	2017-12
D02		

Note:UNII: KDB 789033 D02 is not in the scope of ISO/IEC 17025 accreditation by A2LA.

5. Laboratory Environment

Conducted RF performance testing is performed in shielding room.

EMC performance testing is performed in Semi-anechoic chamber.

6. Test Results

6.1. Summary of Test Results

SUMMARY OF MEASUREMENT RESULTS	Sub-clause of Part15C/E	Sub-clause of IC	Verdict
Maximum Peak Output Power	15.407 (a)	/	P
Peak Power Spectral Density	15.407 (a)	/	P
6dB Emission Bandwidth	15.407 (e)	/	P
Radiated Unwanted Emission	15.407, 15.205, 15.209	/	P
AC Powerline Conducted Emission	15.207	/	P

Please refer to **ANNEX A** for detail.

Terms used in Verdict column

P	Pass, The EUT complies with the essential requirements in the standard.
NM	Not measured, The test was not measured by CTTL
NA	Not Applicable, The test was not applicable
F	Fail, The EUT does not comply with the essential requirements in the standard

6.2. Statements

CTTL has evaluated the test cases as listed in section 6.1 of this report for the EUT specified in section 3 according to the standards or reference documents listed in section 4.

This report only deals with the WLAN function among the features described in section 3.

6.3. Test Conditions

For this report, all the test cases are tested under normal temperature and normal voltage, and also under norm humidity, the specific condition is shown as follows:

Temperature	26°C
Voltage	3.82V
Humidity	44%

7. Test Facilities Utilized

Conducted test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Vector Signal Analyzer	FSW67	104051	Rohde & Schwarz	1 year	2026-06-09
2	Attenuator	10dB/2W	/	Rosenberger	/	/
3	Shielding Room	S81	/	ETS-Lindgren	/	/

Radiated emission test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Test Receiver	ESU26	100376	R&S	1 year	2026-06-20
2	Test Receiver	FSV40	101047	R&S	1 year	2025-07-28
3	Loop Antenna	HFH2-Z2	829324/007	R&S	2 years	2026-01-04
4	EMI Antenna	VULB9163	01177	Schwarzbeck	1 year	2025-11-19
5	EMI Antenna	3117	00119021	ETS-Lindgren	1 year	2025-09-18
6	EMI Antenna	LB-180400 -25-C-KF	J211060826	A-INFO	1 year	2025-08-29

AC Power Line Conducted Emission

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	LISN	ENV216	101459	R&S	1 year	2026-05-07
2	Test Receiver	ESCI7	100948	R&S	1 year	2025-12-10

8. Measurement Uncertainty

8.1. Transmitter Output Power

Measurement Uncertainty: 0.387dB,k=1.96

8.2. Peak Power Spectral Density

Measurement Uncertainty: 0.705dB,k=1.96

8.3. 6dB Emission Bandwidth

Measurement Uncertainty: 60.80Hz,k=1.96

8.4. Band Edges Compliance

Measurement Uncertainty : 0.62dB,k=1.96

8.5. Spurious Emissions

Conducted (k=1.96)

Frequency Range	Uncertainty(dB)
$30\text{MHz} \leq f \leq 2\text{GHz}$	1.22
$2\text{GHz} \leq f \leq 3.6\text{GHz}$	1.22
$3.6\text{GHz} \leq f \leq 8\text{GHz}$	1.22
$8\text{GHz} \leq f \leq 12.75\text{GHz}$	1.51
$12.75\text{GHz} \leq f \leq 26\text{GHz}$	1.51
$26\text{GHz} \leq f \leq 40\text{GHz}$	1.59

8.6. Radiated Unwanted Emission

Frequency Range	Uncertainty(dB)
9kHz-30MHz	3.96
$30\text{MHz} \leq f \leq 1\text{GHz}$	5.73
$1\text{GHz} \leq f \leq 18\text{GHz}$	5.58
$18\text{GHz} \leq f \leq 40\text{GHz}$	3.37

8.7. AC Power-line Conducted Emission


Measurement Uncertainty: 3.10dB, k=2

ANNEX A: MEASUREMENT RESULTS

A.1. Measurement Method

A.1.1. Conducted Measurements

- 1). Connect the EUT to the test system correctly.
- 2). Set the EUT to the required work mode.
- 3). Set the EUT to the required channel.
- 4). Set the spectrum analyzer to start measurement.
- 5). Record the values. Vector Signal Analyzer



A.1.2. Radiated Emission Measurements

Measurement performed according to Clause 6.4, 6.5, 6.6 in ANSI C63.10 and II.G.4, II.G.5, II.G.6 in KDB 789033.

The radiated emission test is performed in semi-anechoic chamber. The EUT was placed on a non-conductive table with 80cm above the ground plane for measurement below 1GHz and 1.5m above the ground plane for measurement above 1GHz. The measurement antenna was placed at a distance of 3 meters from the EUT. The test is carried out on both vertical and horizontal polarization and only maximization result of both polarizations is kept. During the test, the turntable is rotated from 0° to 360° and the measurement antenna is moved from 1m to 4m to get the maximization result. The maximization process was repeated with the EUT positioned in each of its three orthogonal orientations

A.2. Maximum Peak Output Power

Measurement Limit and Method:

Standard	Limit (dBm)
FCC CRF Part 15.407(a)	< 30

Set span to encompass the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal.

Set RBW = 1 MHz.

Set VBW $\geq$ 3 MHz.

Number of points in sweep $\geq 2 \times \text{span} / \text{RBW}$.

Sweep time = auto.

Detector = power averaging (rms)

Trace average at least 100 traces in power averaging (rms) mode; however, the number of traces to be averaged shall be increased above 100 as needed to ensure that the average accurately represents the true average over the on and off periods of the transmitter.

Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument's band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at 1 MHz intervals extending across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal. Add 10 log (1/x), where x is the duty cycle

A.2.1 Antenna Gain

Antenna gain is -1.1dBi and the value is supplied by the applicant or manufacturer.

A.2.2. Maximum Average Output Power-Conducted

EUT ID: UT08a

Measurement Results:

802.11a mode

Mode	Data Rate (Mbps)	Test Result (dBm)		
		5745MHz (Ch149)	5785MHz (Ch157)	5825MHz (Ch165)
802.11a	6	16.39	16.28	16.20
	9	16.36		
	12	15.87		
	18	15.86		
	24	14.26		
	36	14.18		
	48	13.56		
	54	13.52		

The data rate 6Mbps is selected as worst condition, and the following cases are performed with this condition.

802.11n-HT20 mode

Mode	Data Rate (Index)	Test Result (dBm)		
		5745MHz (Ch149)	5785MHz (Ch157)	5825MHz (Ch165)
802.11n (20MHz)	MCS0	16.26	16.02	16.06
	MCS1	16.25		
	MCS2	15.66		
	MCS3	15.62		
	MCS4	14.09		
	MCS5	14.07		
	MCS6	13.92		
	MCS7	13.86		

The data rate MCS0 is selected as worst condition, and the following cases are performed with this condition.

802.11ac-VHT20 mode

Mode	Data Rate (Index)	Test Result (dBm)		
		5745MHz (Ch149)	5785MHz (Ch157)	5825MHz (Ch165)
802.11ac (20MHz)	MCS0	16.30	16.12	16.15
	MCS1	16.26		
	MCS2	15.69		
	MCS3	15.66		
	MCS4	14.57		
	MCS5	14.52		
	MCS6	13.85		
	MCS7	13.76		
	MCS8	13.34		

The data rate MCS0 is selected as worst condition, and the following cases are performed with this condition.

802.11n-HT40 mode

Mode	Data Rate (Index)	Test Result (dBm)	
		5755MHz (Ch151)	5795MHz (Ch159)
802.11n (40MHz)	MCS0	15.81	15.23
	MCS1	15.80	
	MCS2	14.53	
	MCS3	14.51	
	MCS4	14.52	
	MCS5	14.50	
	MCS6	13.32	
	MCS7	13.26	

The data rate MCS0 is selected as worst condition, and the following cases are performed with this condition.

802.11ac-VHT40 mode

Mode	Data Rate (Index)	Test Result (dBm)	
		5755MHz (Ch151)	5795MHz (Ch159)
802.11ac (40MHz)	MCS0	15.82	15.35
	MCS1	15.78	
	MCS2	14.68	
	MCS3	14.56	
	MCS4	14.52	
	MCS5	14.51	
	MCS6	13.33	
	MCS7	13.25	
	MCS8	12.17	
	MCS9	12.12	


The data rate MCS0 is selected as worst condition, and the following cases are performed with this condition.

802.11ac-VHT80 mode

Mode	Data Rate (Index)	Test Result (dBm)
		5775MHz (Ch155)
802.11ac (80MHz)	MCS0	14.45
	MCS1	14.42
	MCS2	13.15
	MCS3	13.13
	MCS4	13.03
	MCS5	13.01
	MCS6	12.02
	MCS7	12.00
	MCS8	11.06
	MCS9	11.01

The data rate MCS0 is selected as worst condition, and the following cases are performed with this condition.

The duty cycle of all mode are 100%



Maximum output Power: 11a CH149

Conclusion: PASS

A.3. Peak Power Spectral Density

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.407(a)	< 30 dBm/500 kHz

Set span to encompass the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal.

Set RBW = 500 kHz.

Set VBW $\geq$ 3 MHz.

Number of points in sweep $\geq 2 \times \text{span} / \text{RBW}$.

Sweep time = auto.

Detector = power averaging (rms)

Trace average at least 100 traces in power averaging (rms) mode; however, the number of traces to be averaged shall be increased above 100 as needed to ensure that the average accurately represents the true average over the on and off periods of the transmitter. Use the peak search function on the instrument to find the peak of the spectrum and record its value. Add $10 \log (1/x)$, where x is the duty cycle.


Measurement Uncertainty:

Measurement Uncertainty	0.75dB
-------------------------	--------

EUT ID: UT08a

Measurement Results:

TestMode	Frequency[MHz]	Result [dBm/500KHz]	Limit[dBm/500KHz]	Verdict
11A	5745	3.27	≤ 30.00	PASS
	5785	3.26	≤ 30.00	PASS
	5825	3.18	≤ 30.00	PASS
11AC20SISO	5745	3.05	≤ 30.00	PASS
	5785	2.92	≤ 30.00	PASS
	5825	2.88	≤ 30.00	PASS
11AC40SISO	5755	-0.37	≤ 30.00	PASS
	5795	-0.78	≤ 30.00	PASS
11AC80SISO	5775	-5.18	≤ 30.00	PASS



22:33:10 17.07.2025

Peak Power Spectral Density:11a CH149

Conclusion: PASS

A.4. 6dB Emission Bandwidth

Measurement Limit:

Standard	Limit (kHz)
FCC 47 CFR Part 15.407 (e)	≥ 500

Set RBW = 100 kHz.

Set the video bandwidth (VBW) $\geq 3 \times$ RBW.

Detector = Peak.

Trace mode = max hold.

Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Measurement Uncertainty:


Measurement Uncertainty	60.80Hz
-------------------------	---------


EUT ID: UT08a

Measurement Result:

TestMode	Frequency[MHz]	6db EBW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11A	5745	16.32	5736.72	5753.04	0.5	PASS
	5785	16.32	5776.72	5793.04	0.5	PASS
	5825	16.32	5816.72	5833.04	0.5	PASS
11AC20SISO	5745	17.60	5736.08	5753.68	0.5	PASS
	5785	17.60	5776.08	5793.68	0.5	PASS
	5825	17.60	5816.08	5833.68	0.5	PASS
11AC40SISO	5755	36.40	5736.68	5773.08	0.5	PASS
	5795	36.08	5776.76	5812.84	0.5	PASS
11AC80SISO	5775	76.48	5736.60	5813.08	0.5	PASS

Test graphs as below:






22:34:58 17.07.2025

11AC20SISO_5745



22:47:17 17.07.2025

11AC20SISO_5785




22:50:38 17.07.2025

11AC20SISO_5825




22:51:54 17.07.2025

11AC40SISO_5755




22:53:26 17.07.2025

11AC40SISO_5795



22:56:18 17.07.2025

11AC80SISO_5775



22:57:37 17.07.2025

Conclusion: PASS

A.5. Radiated Unwanted Emission

A.5.1 Limits

Unwanted Emissions in the unrestricted bands shall not exceed the limits that shown in 15.407:

Standard	Limit (dBm/MHz)	
FCC 47 CFR Part 15.407	at the band edge	27
	at 5 MHz above or below the band edge	15.6
	at 25 MHz above or below the band edge	10
	at 75 MHz or more above or below the band edge	-27
	Note: Increasing linearly from point to point.	

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c))

Frequency (MHz)	Field strength(μ V/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30

Frequency of emission (MHz)	Field strength (μ V/m)	Field strength (dBuV/m)	Measurement distance (m)
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Note: When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor (as defined in KDB 789033 II.G.2.d).

A.5.2 Test setup




Figure A.5.1. Test Site Diagram (9kHz-30MHz)




Figure A.5.2. Test Site Diagram (30MHz-1GHz)




Figure A.5.3. Test Site Diagram (1GHz-40GHz)

A.5.3 Test Procedures

Radiated unwanted emissions from the EUT were measured according to ANSI C63.10 and KDB 789033.

Test setting

Frequency of emission (MHz)	RBW/VBW
30-1000	100kHz/300kHz
1000-4000	1MHz/3MHz
4000-18000	1MHz/3MHz
18000-26500	1MHz/3MHz
26500-40000	1MHz/3MHz

A.5.4 Calculation

1. The measurement results reported below is calculated by:

Measurement Results (dB μ V/m) = $P_{\text{measurement}}$ (dB μ V) + Cable Loss(dB) + Antenna Factor (dB/m)

Where: $P_{\text{measurement}}$ is the field strength recorded from the instrument

2. Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:

$$E = \text{EIRP} - 20 \log(D) + 104.77$$

Where:

E is the field strength in dB μ V/m

D is the measurement distance in meters

EIRP is the equivalent isotropically radiated power in dBm

Test note

1. The EUT is operating at its maximum duty cycle and its maximum power control level.
2. Investigation has been done on all modes and modulations/data rates. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.
3. Spurious emissions for all channels were investigated and almost the same below 1GHz. According to FCC 47 CFR §15.31, emission levels are not report much lower than the limit by over 20dB
4. Measurement frequencies were performed from 9 kHz to 40GHz.

A.5.5 Measurement Result

Average Results:

Channel 149

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5458.850	45.2	-22.5	34.5	33.23	54.0	8.8	H
5459.600	45.2	-22.5	34.5	33.24	54.0	8.8	H
11490.200	35.7	-28.3	38.1	25.86	54.0	18.3	H
17778.350	40.9	-21.4	40.6	21.78	54.0	13.1	V
17868.000	41.3	-21.3	40.5	22.08	54.0	12.7	V
17956.000	41.2	-20.9	40.6	21.55	54.0	12.8	V

Channel 157

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5455.400	45.2	-22.5	34.5	33.30	54.0	8.8	H
5458.250	45.3	-22.5	34.5	33.29	54.0	8.7	H
11569.950	36.1	-28.6	38.4	26.25	54.0	17.9	V
17788.800	40.9	-21.3	40.6	21.69	54.0	13.1	V
17888.350	41.3	-21.0	40.5	21.80	54.0	12.7	V
17951.600	41.2	-20.8	40.6	21.54	54.0	12.8	V

Channel 165

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5458.100	45.4	-22.5	34.5	33.42	54.0	8.6	H
5459.300	45.4	-22.5	34.5	33.39	54.0	8.6	H
11650.250	36.2	-28.4	38.5	26.15	54.0	17.8	V
17780.000	41.1	-21.3	40.6	21.89	54.0	12.9	V
17865.250	41.2	-21.3	40.5	22.01	54.0	12.8	H
17953.800	41.2	-20.9	40.6	21.48	54.0	12.8	H

802.11n-HT20
Channel 149

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5458.100	45.4	-22.5	34.5	33.45	54.0	8.6	H
5459.450	45.5	-22.5	34.5	33.48	54.0	8.5	H
11490.200	35.6	-28.3	38.1	25.78	54.0	18.4	H
17788.800	40.8	-21.3	40.6	21.58	54.0	13.2	H
17864.150	41.1	-21.3	40.5	21.82	54.0	12.9	H
17952.700	41.0	-20.9	40.6	21.32	54.0	13.0	H

Channel 157

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5459.300	45.4	-22.5	34.5	33.39	54.0	8.6	H
5459.600	45.4	-22.5	34.5	33.42	54.0	8.6	H
11569.950	35.9	-28.6	38.4	26.08	54.0	18.1	H
17778.900	40.8	-21.4	40.6	21.65	54.0	13.2	V
17843.250	40.9	-21.3	40.6	21.59	54.0	13.1	V
17867.450	41.0	-21.3	40.5	21.82	54.0	13.0	H

Channel 165

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5458.550	45.4	-22.5	34.5	33.41	54.0	8.6	H
5459.300	45.4	-22.5	34.5	33.41	54.0	8.6	H
11650.250	36.3	-28.4	38.5	26.23	54.0	17.7	H
17860.850	41.1	-21.3	40.5	21.89	54.0	12.9	V
17888.350	41.2	-21.0	40.5	21.70	54.0	12.8	V
17948.850	41.2	-20.9	40.5	21.59	54.0	12.8	H

802.11n-HT40

Channel 151

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5457.200	45.4	-22.5	34.5	33.48	54.0	8.6	H
5458.700	45.4	-22.5	34.5	33.45	54.0	8.6	H
11510.000	35.2	-28.4	38.1	25.46	54.0	18.8	V
17754.700	39.5	-21.7	40.6	20.69	54.0	14.5	H
17881.750	40.2	-21.0	40.5	20.62	54.0	13.8	V
17961.500	40.0	-21.0	40.6	20.42	54.0	14.0	V

Channel 159

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5459.600	45.4	-22.5	34.5	33.44	54.0	8.6	H
5459.900	45.4	-22.5	34.5	33.44	54.0	8.6	H
11589.750	35.5	-27.7	38.5	24.78	54.0	18.5	V
17782.750	39.7	-21.3	40.6	20.47	54.0	14.3	V
17890.000	40.1	-21.0	40.5	20.60	54.0	13.9	H
17952.700	40.0	-20.9	40.6	20.33	54.0	14.0	V

802.11ac-HT20

Channel 149

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5459.300	45.4	-22.5	34.5	33.43	54.0	8.6	H
5459.900	45.4	-22.5	34.5	33.45	54.0	8.6	H
11490.200	34.6	-28.3	38.1	24.83	54.0	19.4	V
16165.200	39.4	-22.6	41.0	21.07	54.0	14.6	H
17886.150	40.0	-21.0	40.5	20.48	54.0	14.0	V
17949.400	40.0	-20.9	40.5	20.28	54.0	14.0	H

Channel 157

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5412.200	45.4	-22.4	34.3	33.44	54.0	8.6	H
5429.750	45.4	-22.5	34.4	33.51	54.0	8.6	H
11569.950	35.0	-28.6	38.4	25.20	54.0	19.0	V
15972.150	39.2	-23.3	40.8	21.65	54.0	14.8	H
17886.150	40.0	-21.0	40.5	20.49	54.0	14.0	V
17948.850	39.9	-20.9	40.5	20.26	54.0	14.1	V

Channel 165

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5458.250	45.4	-22.5	34.5	33.43	54.0	8.6	H
5458.550	45.4	-22.5	34.5	33.42	54.0	8.6	H
11650.250	35.0	-28.4	38.5	24.95	54.0	19.0	V
15868.200	39.3	-23.2	40.9	21.57	54.0	14.7	H
17881.750	40.0	-21.0	40.5	20.48	54.0	14.0	V
17948.850	39.9	-20.9	40.5	20.26	54.0	14.1	V

802.11ac-HT40

Channel 151

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5457.050	45.5	-22.5	34.5	33.50	54.0	8.5	H
5458.400	45.4	-22.5	34.5	33.39	54.0	8.6	H
11510.000	35.3	-28.4	38.1	25.57	54.0	18.7	V
15863.250	39.4	-23.3	40.9	21.87	54.0	14.6	V
17876.250	40.3	-21.1	40.5	20.83	54.0	13.7	H
17948.850	40.1	-20.9	40.5	20.49	54.0	13.9	H

Channel 159

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5437.250	45.4	-22.5	34.4	33.51	54.0	8.6	H
5440.100	45.4	-22.6	34.5	33.46	54.0	8.6	H
11589.750	35.7	-27.7	38.5	24.98	54.0	18.3	V
15862.700	39.4	-23.3	40.9	21.85	54.0	14.6	V
17886.700	40.3	-21.0	40.5	20.76	54.0	13.7	V
17948.850	40.2	-20.9	40.5	20.51	54.0	13.8	H

802.11ac-HT80

Channel 155

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5455.850	45.5	-22.5	34.4	33.55	54.0	8.5	H
5458.100	45.5	-22.5	34.5	33.52	54.0	8.5	H
11550.150	35.5	-28.2	38.3	25.39	54.0	18.5	H
15859.950	39.4	-23.3	40.9	21.79	54.0	14.6	V
17882.850	40.4	-21.0	40.5	20.86	54.0	13.6	V
17949.400	40.3	-20.9	40.5	20.60	54.0	13.7	H

Peak Results:

802.11a

Channel 149

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5650.213	56.6	-22.5	34.7	44.45	68.4	11.7	H
5650.426	57.0	-22.5	34.7	44.81	68.5	11.5	H
11491.850	48.0	-28.3	38.1	38.28	74.0	26.0	H
16676.700	54.7	-22.5	41.4	35.87	68.2	13.5	V
16885.700	55.0	-22.2	41.4	35.81	68.2	13.2	V
17235.500	51.6	-22.4	40.9	33.07	68.2	16.6	H

Channel 157

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5729.600	58.2	-22.2	34.3	46.12	68.2	10.0	H
5838.600	58.4	-22.1	34.8	45.58	68.3	9.9	H
11568.850	48.7	-28.6	38.4	38.89	74.0	25.3	H
16918.700	54.4	-22.4	41.3	35.43	68.2	13.8	V
17354.850	52.7	-21.9	40.7	33.86	68.2	15.5	V
17362.550	54.2	-21.9	40.7	35.41	68.2	14.0	H

Channel 165

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5924.586	57.2	-22.0	34.8	44.44	68.5	11.3	H
5924.914	55.8	-22.0	34.8	43.06	68.3	12.4	H
11650.250	48.2	-28.4	38.5	38.10	74.0	25.8	V
16721.250	54.7	-22.6	41.4	35.95	68.2	13.5	V
17474.200	53.0	-21.8	40.8	34.09	68.2	15.2	H
17542.950	55.5	-20.9	40.8	35.58	68.2	12.7	H

802.11n-HT20

Channel 149

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5650.173	56.4	-22.5	34.7	44.20	68.3	12.0	H
5650.270	56.5	-22.5	34.7	44.31	68.4	11.9	H
11490.200	47.6	-28.3	38.1	37.79	74.0	26.4	H
16291.700	54.6	-22.1	40.9	35.81	68.2	13.6	H
17236.050	51.4	-22.4	40.9	32.91	68.2	16.8	V
17362.550	54.6	-21.9	40.7	35.80	68.2	13.6	H

Channel 157

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5743.200	56.8	-22.1	34.3	44.51	68.2	11.4	H
5822.200	57.8	-21.9	34.7	44.96	68.2	10.4	H
11569.950	47.6	-28.6	38.4	37.78	74.0	26.4	V
16555.150	54.5	-22.8	41.2	36.06	68.2	13.7	V
16656.900	54.8	-22.5	41.4	35.90	68.2	13.4	H
17353.750	52.6	-21.9	40.7	33.76	68.2	15.6	H

Channel 165

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5924.471	56.9	-22.0	34.8	44.08	68.6	11.7	H
5924.960	56.0	-22.0	34.8	43.24	68.2	12.2	H
11650.250	48.1	-28.4	38.5	37.96	74.0	25.9	V
16390.150	54.3	-22.6	40.9	35.99	68.2	13.9	V
17294.900	54.3	-22.1	40.8	35.64	68.2	13.9	H
17474.750	54.4	-21.8	40.8	35.44	68.2	13.8	H

802.11n-HT40

Channel 151

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5650.075	56.2	-22.5	34.7	44.04	68.3	12.0	H
5650.242	57.1	-22.5	34.7	44.90	68.4	11.3	H
11509.450	48.8	-28.4	38.1	39.04	74.0	25.2	H
16661.300	54.4	-22.4	41.4	35.40	68.2	13.8	H
17265.200	52.2	-22.2	40.8	33.49	68.2	16.0	V
17517.100	54.4	-21.8	40.8	35.42	68.2	13.8	V

Channel 159

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5924.943	56.2	-22.0	34.8	43.46	68.2	12.0	H
5924.994	55.9	-22.0	34.8	43.09	68.2	12.3	H
11589.200	48.0	-27.8	38.5	37.27	74.0	26.0	V
16950.050	54.6	-22.2	41.2	35.57	68.2	13.6	H
17385.100	51.7	-21.9	40.7	32.81	68.2	16.5	V
17681.000	55.4	-21.3	40.5	36.07	68.2	12.9	H

802.11ac-HT20

Channel 149

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5650.155	56.5	-22.5	34.7	44.32	68.3	11.8	H
5650.213	56.6	-22.5	34.7	44.43	68.4	11.7	H
11490.200	46.3	-28.3	38.1	36.53	74.0	27.7	H
16665.700	52.6	-22.4	41.4	33.66	68.2	15.6	V
17234.950	49.7	-22.4	40.9	31.21	68.2	18.5	H
17560.550	52.8	-21.8	40.7	33.87	68.2	15.4	H

Channel 157

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5712.000	57.9	-22.1	34.3	45.70	68.2	10.3	H
5872.600	58.1	-21.8	34.9	45.11	68.2	10.1	H
11569.950	46.8	-28.6	38.4	36.95	74.0	27.2	V
16654.700	53.5	-22.6	41.4	34.73	68.2	14.7	V
17061.700	52.9	-22.4	41.0	34.22	68.2	15.3	H
17354.850	50.2	-21.9	40.7	31.35	68.2	18.0	V

Channel 165

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5924.851	55.6	-22.0	34.8	42.81	68.3	12.7	H
5924.954	55.7	-22.0	34.8	42.94	68.2	12.5	H
11650.250	45.9	-28.4	38.5	35.78	74.0	28.1	V
16468.800	53.2	-22.8	41.0	34.94	68.2	15.0	V
17474.750	50.1	-21.8	40.8	31.12	68.2	18.1	H
17652.400	53.4	-21.3	40.6	34.09	68.2	14.8	V

802.11ac-HT40

Channel 151

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5650.811	57.9	-22.5	34.7	45.76	68.8	10.9	H
5650.920	57.1	-22.5	34.7	44.89	68.9	11.8	H
11510.000	46.1	-28.4	38.1	36.38	74.0	27.9	V
16749.850	53.0	-22.8	41.4	34.44	68.2	15.2	V
16959.950	53.4	-22.2	41.2	34.45	68.2	14.8	H
17265.200	50.7	-22.2	40.8	32.03	68.2	17.5	V

Channel 159

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5924.500	56.8	-22.0	34.8	44.00	68.6	11.8	H
5924.770	56.7	-22.0	34.8	43.93	68.4	11.7	H
11589.750	46.0	-27.7	38.5	35.32	74.0	28.0	V
16661.850	53.6	-22.4	41.4	34.60	68.2	14.6	V
16968.750	53.3	-22.2	41.2	34.25	68.2	14.9	H
17385.100	49.8	-21.9	40.7	30.97	68.2	18.4	H

802.11ac-HT80

Channel 155

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5650.144	60.5	-22.5	34.7	48.33	68.3	7.8	H
5923.741	57.7	-22.2	34.8	45.13	69.1	11.4	H
11550.150	46.4	-28.2	38.3	36.28	74.0	27.6	H
16687.700	53.7	-22.2	41.2	34.65	68.2	14.5	V
17325.150	50.7	-22.1	40.8	32.00	68.2	17.5	H
17555.050	53.4	-21.1	40.8	33.75	68.2	14.8	H

Conclusion: PASS

Note:

1. The spurious emission above 18G is noise only.
2. All emissions below 30MHz are more than 20 dB below the limit

Band edge compliance

Mode	Channel	Test Results	Conclusion
802.11a	5745 MHz	Fig.1	P
	5825 MHz	Fig.2	P
802.11n HT20	5745 MHz	Fig.3	P
	5825 MHz	Fig.4	P
802.11n HT40	5755 MHz	Fig.5	P
	5795 MHz	Fig.6	P
802.11ac HT20	5745 MHz	Fig.7	P
	5825 MHz	Fig.8	P
802.11ac HT40	5755 MHz	Fig.9	P
	5795 MHz	Fig.10	P
802.11ac HT80	5775 MHz	Fig.11 Fig.12	P

Conclusion: PASS

Test graphs as below:




Fig. 1 Band Edges (802.11a Ch149, 5745MHz)




Fig. 2 Band Edges (802.11a Ch165, 5825MHz)




Fig. 3 Band Edges (802.11n-HT20 Ch149, 5745MHz)




Fig. 4 Band Edges (802.11n-HT20 Ch165, 5825MHz)




Fig. 5 Band Edges (802.11n-HT40 Ch151, 5755MHz)




Fig. 6 Band Edges (802.11n-HT40 Ch159, 5795MHz)




Fig. 7 Band Edges (802.11ac-HT20 Ch149, 5745MHz)




Fig. 8 Band Edges (802.11ac-HT20 Ch165, 5825MHz)




Fig. 9 Band Edges (802.11ac-HT40 Ch151, 5755MHz)




Fig. 10 Band Edges (802.11ac-HT40 Ch159, 5795MHz)




Fig. 11 Band Edges (802.11ac-HT80 Ch155, 5775MHz)




Fig. 12 Band Edges (802.11ac-HT80 Ch155, 5775MHz)

A.6. AC Powerline Conducted Emission

A.6.1 Summary

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section

A.6.2 Method of Measurement

See Clause 6.2 of ANSI C63.10 specifically.

See Clause 4 and Clause 5 of ANSI C63.10 generally.

The conducted emissions from the AC port of the EUT are measured in a shielding room. The EUT is connected to a Line Impedance Stabilization Network (LISN). An overview sweep with peak detection was performed. The measurements were performed with a quasi-peak detector and if required, an average detector.

The conducted emission measurements were made with the following detector of the test receiver:
Quasi-Peak / Average Detector.


The measurement bandwidth is:

Frequency of Emission (MHz)	RBW/IF bandwidth
0.15-30	9kHz

A.6.3 Test Condition

Voltage (V)	Frequency (Hz)
120	60

A.6.4 Test setup



A.6.5 Measurement Result and limit

Wi-Fi (Quasi-peak Limit)

Frequency range (MHz)	Quasi-peak Limit (dBμV)	Result (dBμV)		Conclusion
		With charger		
		Wi-Fi	Idle	
0.15 to 0.5	66 to 56	Fig.A.6.1	Fig. A.6.2	P
0.5 to 5	56			
5 to 30	60			

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

Wi-Fi (Average Limit)

Frequency range (MHz)	Average Limit (dBμV)	Result (dBμV)		Conclusion
		With charger		
		Wi-Fi	Idle	
0.15 to 0.5	56 to 46	Fig.A.6.1	Fig. A.6.2	P
0.5 to 5	46			
5 to 30	50			

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

Conclusion: Pass

Test graphs as below:




Fig.A.6.1. AC Powerline Conducted Emission-Iidle

Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.708000	50.0	2000.0	9.000	On	L1	20.2	6.0	56.0
0.757500	51.9	2000.0	9.000	On	L1	20.2	4.1	56.0
0.793500	52.4	2000.0	9.000	On	L1	20.2	3.6	56.0
1.401000	49.1	2000.0	9.000	On	L1	20.2	6.9	56.0
1.995000	48.7	2000.0	9.000	On	L1	20.1	7.3	56.0
19.815000	44.8	2000.0	9.000	On	N	20.4	15.2	60.0

Final Result 2

Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.739500	33.7	2000.0	9.000	On	L1	20.2	12.3	46.0
0.789000	37.5	2000.0	9.000	On	L1	20.2	8.5	46.0
1.482000	34.4	2000.0	9.000	On	L1	20.2	11.6	46.0
1.945500	34.7	2000.0	9.000	On	L1	20.1	11.3	46.0
2.557500	33.5	2000.0	9.000	On	L1	20.2	12.5	46.0
3.030000	33.0	2000.0	9.000	On	L1	20.2	13.0	46.0




Fig.A.6.2. AC Powerline Conducted Emission-Idle

Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.694500	49.6	2000.0	9.000	On	L1	20.2	6.4	56.0
0.753000	51.4	2000.0	9.000	On	L1	20.2	4.6	56.0
0.771000	52.7	2000.0	9.000	On	L1	20.2	3.3	56.0
0.784500	53.5	2000.0	9.000	On	L1	20.2	2.5	56.0
0.807000	51.2	2000.0	9.000	On	L1	20.2	4.8	56.0
19.968000	46.5	2000.0	9.000	On	N	20.4	13.5	60.0

Final Result 2

Frequency (MHz)	Average (dBuV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.753000	32.6	2000.0	9.000	On	L1	20.2	13.4	46.0
0.784500	36.1	2000.0	9.000	On	L1	20.2	9.9	46.0
0.924000	33.2	2000.0	9.000	On	L1	20.2	12.8	46.0
1.482000	33.7	2000.0	9.000	On	L1	20.2	12.3	46.0
1.941000	33.3	2000.0	9.000	On	L1	20.1	12.7	46.0
2.013000	34.1	2000.0	9.000	On	L1	20.1	11.9	46.0

A.7. Antenna Requirement

The antenna of the device is permanently attached. There are no provisions for connection to an external antenna.

The unit complies with the requirement of FCC Part 15.203.

ANNEX B: EUT parameters

Disclaimer: The antenna gain provided by the client may affect the validity of the measurement results in this report, and the client shall bear the impact and consequences arising therefrom.

ANNEX C: Accreditation Certificate



Accredited Laboratory

A2LA has accredited

TELECOMMUNICATION TECHNOLOGY LABS, CAICT

Beijing, People's Republic of China

for technical competence in the field of

Electrical Testing

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 *General requirements for the competence of testing and calibration laboratories*. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).



Presented this 23rd day of July 2024.



Mr. Trace McInturff, Vice President, Accreditation Services
For the Accreditation Council
Certificate Number 7049.01
Valid to July 31, 2026

For the tests to which this accreditation applies, please refer to the laboratory's Electrical Scope of Accreditation.

***** END OF REPORT BODY *****