
FCC Test Report

Report No.: AGC03X110301F1

FCC ID : ZCN-ECG300
PRODUCT DESIGNATION : Cellphone TV
BRAND NAME : Ring
MODEL NAME : ECG300
CLIENT : Starmarket S.A.
DATE OF ISSUE : Mar.14, 2011
STANDARD(S) : FCC Part 15 Rules

Attestation of Global Compliance Co., Ltd.

1. CAUTION: This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.

TABLE OF CONTENTS

1. VERIFICATION OF COMPLIANCE	2
2. PRODUCT INFORMATION	3
3. TEST FACILITY	4
4. SUPPORT EQUIPMENT LIST	5
5. SYSTEM DESCRIPTION	5
6. FCC LINE CONDUCTED EMISSION TEST	6
6.1. TEST EQUIPMENT OF LINE CONDUCTED EMISSION TEST	6
6.2 .LIMITS OF LINE CONDUCTED EMISSION TEST	6
6.3. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST.....	6
6.4. PROCEDURE OF LINE CONDUCTED EMISSION TEST.....	7
6.5 TEST RESULT OF LINE CONDUCTED EMISSION TEST	8
7. FCC RADIATED EMISSION TEST.....	10
7.1. TEST EQUIPMENT OF RADIATED EMISSION	10
7.2. LIMITS OF RADIATED EMISSION TEST	10
7.3 BLOCK DIAGRAM OF RADIATED EMISSION TEST	10
7.4 PROCEDURE OF RADIATED EMISSION TEST	11
7.5 TEST RESULT OF RADIATED EMISSION TEST	12
APPENDIX 1	14
PHOTOGRAPHS OF TEST SETUP	14
APPENDIX 2	15
PHOTOGRAPHS OF EUT	15


1. VERIFICATION OF COMPLIANCE

Product Designation:	Cellphone TV
Brand name:	Ring
Model Name:	ECG300
Applicant:	Starmarket S.A. Av Juan Tanca Marengo Km 4 1/2 CC Saibaba Ic 22
Manufacturer:	Easybuy China LTD. Rm. 1413-1415, 14F, WanDe Building, ShenNan Millde Rd., FuTian Dist., Shen Zhen
FCC ID:	ZCN-ECG300
Measurement Procedure:	ANSI C63.4: 2003
File Number:	AGC03X110301F1
Date of test:	Mar 05, 2011 to Mar.12, 2011
Deviation:	None
Condition of Test Sample:	Normal

The above equipment was tested by Attestation Of Global Compliance Co., Ltd. for compliance with the requirements set forth in the FCC Rules and Regulations Part 15, the measurement procedure according to ANSI C63.4:2003. This said equipment in the configuration described in this report shows the maximum emission levels emanating from equipment are within the compliance requirements.

The test results of this report relate only to the tested sample identified in this report.

Checked By :



Mary Liu

Mar.14, 2011

Authorized By :



Forrest Lei

Mar.14, 2011

2. PRODUCT INFORMATION

Housing Type: Plastic

EUT Rating Voltage: DC 5V supplied by PC

I/O Port Information (Applicable Not Applicable)

I/O Port of EUT			
I/O Port Type	Q'TY	Cable	Tested with
USB/EARPHONE Input Port	1	N/A	1

3. TEST FACILITY

Facility	Attestation of Global Compliance Co., Ltd.
Location:	1F, No.2 Building, Huafeng No.1 Technical, Industrial Park, Sanwei, Xixiang, Baoan District, Shenzhen, China
Description:	The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2003.
Site Filing:	The FCC Registration Number is 259865
Instrument Tolerance:	All measuring equipment is in accord with ANSI C63.4 requirements that meet industry regulatory agency and accreditation agency requirement.

4. SUPPORT EQUIPMENT LIST

Device Type	Manufacturer	Model Name	Serial No.	Data Cable	Power Cable
PC	Apple	Q550S	N/A	N/A	N/A

**Note: All the above equipment/cables were placed in worse case positions to maximize emission signals during emission test.

Grounding: Grounding was in accordance with the manufacturer's requirements and conditions for the intended use.

5. SYSTEM DESCRIPTION

EUT test procedure:

1. Connect EUT and peripheral devices (if need).
2. Power on the EUT, the EUT begins to work.
3. Make sure the EUT operates normally during the test.

6. FCC LINE CONDUCTED EMISSION TEST

6.1. TEST EQUIPMENT OF LINE CONDUCTED EMISSION TEST

Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Spectrum Analyzer	Agilent	E4440A	N/A	06/29/2010	06/28/2011
EMI Test Receiver	H.P.	8546A	N/A	06/29/2010	06/28/2011
LISN	EMCO	3825/2	N/A	06/29/2010	06/28/2011


6.2 .LIMITS OF LINE CONDUCTED EMISSION TEST

Frequency	Maximum RF Line Voltage	
	Q.P.(dBuV)	Average(dBuV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

**Note: 1. The lower limit shall apply at the transition frequency.

2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz

6.3. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST




6.4. PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1) The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2) Support equipment, if needed, was placed as per ANSI C63.4.
- 3) All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4) The EUT received DC 5V power by PC. All support equipments received AC 120V/60Hz power from socket under the turntable, if any.
- 5) The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 6) Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 7) During the above scans, the emissions were maximized by cable manipulation.
- 8) A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions.
- 9) Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less -2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.

The test data of the worst case condition(s) was reported on the Summary Data page.

6.5 TEST RESULT OF LINE CONDUCTED EMISSION TEST


LINE CONDUCTED EMISSION - L



Site: Conduction Phase: L1 Temperature: 26
Limit: FCC Class B Conduction(QP) Power: AC 120V/60Hz Humidity: 60 %

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.2060	38.55		24.62	10.22	48.77		34.84	63.36	53.36	-14.59	-18.52	P	
2	0.6300	38.12		17.30	10.32	48.44		27.62	56.00	46.00	-7.56	-18.38	P	
3	1.3220	36.16		12.54	10.38	46.54		22.92	56.00	46.00	-9.46	-23.08	P	
4	1.9780	36.44		14.56	10.23	46.67		24.79	56.00	46.00	-9.33	-21.21	P	
5	4.5219	36.54		16.78	10.21	46.75		26.99	56.00	46.00	-9.25	-19.01	P	
6	6.7459	36.94		15.51	10.33	47.27		25.84	60.00	50.00	-12.73	-24.16	P	

LINE CONDUCTED EMISSION – N



Site: Conduction Phase: *N* Temperature: 26
Limit: FCC Class B Conduction(QP) Power: AC 120V/60Hz Humidity: 60 %

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.2060	37.76		31.11	10.22	47.98		41.33	63.36	53.36	-15.38	-12.03	P	
2	0.5540	36.09		27.73	10.35	46.44		38.08	56.00	46.00	-9.56	-7.92	P	
3	0.6260	36.81		26.41	10.32	47.13		36.73	56.00	46.00	-8.87	-9.27	P	
4	1.3940	37.33		19.77	10.38	47.71		30.15	56.00	46.00	-8.29	-15.85	P	
5	2.6740	36.00		21.51	10.47	46.47		31.98	56.00	46.00	-9.53	-14.02	P	
6	4.3659	36.26		21.73	10.27	46.53		32.00	56.00	46.00	-9.47	-14.00	P	

7. FCC RADIATED EMISSION TEST

7.1. TEST EQUIPMENT OF RADIATED EMISSION


Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
PSA SERIES SPECTRUM ANALYZER	AGILENT	E4440A	US41421290	06/29/2010	06/28/2011
ANTENNA	A.H.	SAS-521-4	128	06/29/2010	06/28/2011
HORN ANTENNA	EM	EM-AH-10180	N/A	06/29/2010	06/28/2011
AMPLIFIER	EM	EM30180	0607030	06/29/2010	06/28/2011
POSITIONING CONTROLLER	MF	MF-7802	MF780208147	06/29/2010	06/28/2011

7.2. LIMITS OF RADIATED EMISSION TEST

Frequency (MHz)	Distance (m)	Maximum Field Strength Limit (dBuV/m/ Q.P.)
30~88	3	40.0
88~216	3	43.5
216~960	3	46.0
Above 960	3	54.0

**Note: The lower limit shall apply at the transition frequency.

7.3 BLOCK DIAGRAM OF RADIATED EMISSION TEST




7.4 PROCEDURE OF RADIATED EMISSION TEST

- 1) The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden turntable with a height of 0.8 meters is used which is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2) Support equipment, if needed, was placed as per ANSI C63.4.
- 3) All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4) The EUT received DC 5V by PC. All support equipments received AC 120V/60Hz power from socket under the turntable, if any.
- 5) The antenna was placed at 3 meter away from the EUT as stated in FCC Part 15. The antenna connected to the Analyzer via a cable and at times a pre-amplifier would be used.
- 6) The Analyzer / Receiver quickly scanned from 30MHz to 1000MHz. The EUT test program was started. Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- 7) The test mode(s) were scanned during the test:
- 8) Recorded at least the six highest emissions. Emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit and Q.P./Peak reading is presented.

The test data of the worst case condition (s) was reported on the Summary Data page.

7.5 TEST RESULT OF RADIATED EMISSION TEST


Radiated Emission Test –Horizontal -3m



Site: site #1 Polarization: *Horizontal* Temperature: 26
Limit: FCC Class B 3M Radiation Power: DC 5V Humidity: 60 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		104.3667	11.91	15.90	27.81	43.50	-15.69	peak			
2	*	165.8000	15.57	15.09	30.66	43.50	-12.84	peak			
3		238.5500	12.40	16.98	29.38	46.00	-16.62	peak			
4		272.5000	13.17	17.21	30.38	46.00	-15.62	peak			
5		311.3000	14.50	17.74	32.24	46.00	-13.76	peak			
6		621.7000	4.13	25.03	29.16	46.00	-16.84	peak			

Radiated Emission Test –Vertical -3m



Site: site #1

Polarization: *Vertical*

Temperature: 26

Limit: FCC Class B 3M Radiation

Power: DC 5V

Humidity: 60 %


No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		89.8167	13.39	12.09	25.48	43.50	-18.02	peak			
2	*	104.3667	19.52	11.05	30.57	43.50	-12.93	peak			
3		165.8000	14.83	12.87	27.70	43.50	-15.80	peak			
4		235.3167	8.98	16.42	25.40	46.00	-20.60	peak			
5		311.3000	11.53	17.74	29.27	46.00	-16.73	peak			
6		506.9167	7.54	23.07	30.61	46.00	-15.39	peak			

APPENDIX 1 PHOTOGRAPHS OF TEST SETUP

FCC LINE CONDUCTED EMISSION TEST SETUP



FCC RADIATED EMISSION TEST SETUP



APPENDIX 2 PHOTOGRAPHS OF EUT

TOP VIEW OF SAMPLE



BOTTOM VIEW OF SAMPLE



LEFT VIEW OF SAMPLE



RIGHT VIEW OF SAMPLE



FRONT VIEW OF SAMPLE




BACK VEW OF SAMPLE



ALL VIEW OF SAMPLE



OPEN PHOTO OF SAMPLE – 1




OPEN PHOTO OF SAMPLE – 2




OPEN PHOTO OF SAMPLE – 3



INTERNAL PHOTO OF SAMPLE – 1



INTERNAL PHOTO OF SAMPLE – 2



-----END OF REPORT-----