

## FCC Part 15.247

## TEST REPORT

For

### FEITIAN Technologies Co., Ltd.

Floor 17th, Tower B, Huizhi Mansion, No.9 Xueqing Road, Haidian District, Beijing,  
China

**FCC ID: ZD3FTF20SC200RNA**

**Report Type:**  
Original Report

**Product Type:**  
Android POS Terminal

**Report Producer :** Jane Chen

*Jane Chen*

**Report Number :** RXZ210922002RF04

**Report Date :** 2021-11-01

**Reviewed By:** Andy Shih

*Andy Shih*

**Prepared By:** Bay Area Compliance Laboratories Corp.

70, Lane 169, Sec. 2, Datong Road, Xizhi Dist.,  
New Taipei City 22183, Taiwan, R.O.C.

Tel: +886 (2) 2647 6898

Fax: +886 (2) 2647 6895

[www.bacl.com.tw](http://www.bacl.com.tw)

Revision History

| Revision | No.          | Report Number    | Issue Date | Description     | Author/<br>Revised by |
|----------|--------------|------------------|------------|-----------------|-----------------------|
| 0.0      | RXZ210922002 | RXZ210922002RF04 | 2021-11-01 | Original Report | Jane Chen             |

## **TABLE OF CONTENTS**

|                                                                        |           |
|------------------------------------------------------------------------|-----------|
| <b>1. General Information .....</b>                                    | <b>5</b>  |
| 1.1. Product Description for Equipment under Test (EUT) .....          | 5         |
| 1.2. Objective .....                                                   | 6         |
| 1.3. Related Submittal(s)/Grant(s).....                                | 6         |
| 1.4. Test Methodology.....                                             | 6         |
| 1.5. Statement of Compliance .....                                     | 6         |
| 1.6. Measurement Uncertainty .....                                     | 7         |
| 1.7. Environmental Conditions.....                                     | 7         |
| 1.8. Test Facility .....                                               | 7         |
| <b>2. System Test Configuration.....</b>                               | <b>8</b>  |
| 2.1. Description of Test Configuration.....                            | 8         |
| 2.2. Equipment Modifications .....                                     | 8         |
| 2.3. EUT Exercise Software .....                                       | 8         |
| 2.4. Test Mode.....                                                    | 8         |
| 2.5. Support Equipment List and Details.....                           | 9         |
| 2.6. External Cable List and Details .....                             | 9         |
| 2.7. Block Diagram of Test Setup .....                                 | 9         |
| <b>3. Summary of Test Results.....</b>                                 | <b>11</b> |
| <b>4. Test Equipment List and Details .....</b>                        | <b>12</b> |
| <b>5. FCC §15.247(i), §1.1310, § 2.1093 - RF Exposure.....</b>         | <b>14</b> |
| 5.1. Applicable Standard .....                                         | 14        |
| 5.2. RF Exposure Evaluation Result.....                                | 14        |
| <b>6. FCC §15.203 – Antenna Requirements.....</b>                      | <b>15</b> |
| 6.1. Applicable Standard .....                                         | 15        |
| 6.2. Antenna Information .....                                         | 15        |
| <b>7. FCC §15.207(a) – AC Line Conducted Emissions .....</b>           | <b>16</b> |
| 7.1. Applicable Standard .....                                         | 16        |
| 7.2. EUT Setup .....                                                   | 16        |
| 7.3. EMI Test Receiver Setup .....                                     | 17        |
| 7.4. Test Procedure .....                                              | 17        |
| 7.5. Corrected Factor & Margin Calculation.....                        | 17        |
| 7.6. Test Results .....                                                | 18        |
| <b>8. FCC §15.209, §15.205 , §15.247(d) – Spurious Emissions .....</b> | <b>20</b> |
| 8.1. Applicable Standard .....                                         | 20        |
| 8.2. EUT Setup .....                                                   | 21        |
| 8.3. EMI Test Receiver & Spectrum Analyzer Setup.....                  | 22        |
| 8.4. Test Procedure .....                                              | 22        |
| 8.5. Corrected Factor & Margin Calculation.....                        | 22        |
| 8.6. Test Results .....                                                | 23        |
| <b>9. FCC §15.247(a)(1) – 20 dB Emission Bandwidth.....</b>            | <b>38</b> |
| 9.1. Applicable Standard .....                                         | 38        |
| 9.2. Test Procedure .....                                              | 38        |
| 9.3. Test Results .....                                                | 38        |
| <b>10. FCC §15.247(a)(1) – Channel Separation Test.....</b>            | <b>44</b> |

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

|                                                                            |           |
|----------------------------------------------------------------------------|-----------|
| 10.1. Applicable Standard .....                                            | 44        |
| 10.2. Test Procedure .....                                                 | 44        |
| 10.3. Test Results .....                                                   | 44        |
| <b>11. FCC§15.247(a)(1)(iii) –Time of Occupancy (Dwell Time) .....</b>     | <b>50</b> |
| 11.1. Applicable Standard .....                                            | 50        |
| 11.2. Test Procedure .....                                                 | 50        |
| 11.3. Test Results .....                                                   | 51        |
| <b>12. FCC §15.247(a)(1)(iii) –Quantity of hopping channel Test.....</b>   | <b>66</b> |
| 12.1. Applicable Standard .....                                            | 66        |
| 12.2. Test Procedure .....                                                 | 66        |
| 12.3. Test Results .....                                                   | 66        |
| <b>13. FCC §15.247(b)(1) – Maximum Output Power.....</b>                   | <b>69</b> |
| 13.1. Applicable Standard .....                                            | 69        |
| 13.2. Test Procedure .....                                                 | 69        |
| 13.3. Test Results .....                                                   | 69        |
| <b>14. FCC §15.247(d) – 100 kHz Bandwidth of Frequency Band Edge .....</b> | <b>71</b> |
| 14.1. Applicable Standard .....                                            | 71        |
| 14.2. Test Procedure .....                                                 | 71        |
| 14.3. Test Results .....                                                   | 71        |

# 1. General Information

## 1.1. Product Description for Equipment under Test (EUT)

|                                    |                                                                                                                                                                                                                                                                                                                                                                                                    |
|------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Applicant                          | FEITIAN Technologies Co., Ltd.                                                                                                                                                                                                                                                                                                                                                                     |
|                                    | Floor 17th, Tower B, Huizhi Mansion, No.9 Xueqing Road,<br>Haidian District, Beijing, China                                                                                                                                                                                                                                                                                                        |
| Manufacturer                       | FEITIAN Technologies Co., Ltd.                                                                                                                                                                                                                                                                                                                                                                     |
|                                    | Floor 17th, Tower B, Huizhi Mansion, No.9 Xueqing Road,<br>Haidian District, Beijing, China                                                                                                                                                                                                                                                                                                        |
| Brand(Trade) Name                  | N/A                                                                                                                                                                                                                                                                                                                                                                                                |
| Product (Equipment)                | Android POS Terminal                                                                                                                                                                                                                                                                                                                                                                               |
| Main Model Name                    | F20 FP                                                                                                                                                                                                                                                                                                                                                                                             |
| Series Model Name                  | F20                                                                                                                                                                                                                                                                                                                                                                                                |
| Model Discrepancy                  | F20 FP with Touch Function<br>F20 without Touch Function                                                                                                                                                                                                                                                                                                                                           |
| Frequency Range                    | 2402 ~ 2480 MHz                                                                                                                                                                                                                                                                                                                                                                                    |
| Transmit Power                     | BR(GFSK) Mode: 8.64 dBm<br>EDR( $\pi/4$ -DQPSK) Mode: 8.70 dBm<br>EDR(8DPSK) Mode: 9.03 dBm                                                                                                                                                                                                                                                                                                        |
| Modulation Technique               | BR Mode: GFSK<br>EDR Mode: $\pi/4$ -DQPSK, 8DPSK                                                                                                                                                                                                                                                                                                                                                   |
| Transmit Data Rate                 | BR(GFSK) Mode: 1 Mbps<br>EDR( $\pi/4$ -DQPSK) Mode: 2 Mbps<br>EDR(8DPSK) Mode: 3 Mbps                                                                                                                                                                                                                                                                                                              |
| Power Operation<br>(Voltage Range) | <input checked="" type="checkbox"/> AC 120V/60Hz<br><input checked="" type="checkbox"/> Adapter1<br>Brand Name: DEE VAN<br>Model: DSA-10PF06-05 FUS<br>I/P: 100-240Vac, 0.3A<br>O/P: 5Vdc, 2.0A<br>Adapter2<br>Brand Name: TEKA<br>Model: TEKA-UCA20US<br>I/P: 100-240Vac, 0.35A<br>O/P: 5Vdc, 2.0A<br><input type="checkbox"/> By AC Power Cord<br><input type="checkbox"/> PoE                   |
|                                    | <input checked="" type="checkbox"/> DC Type<br><input checked="" type="checkbox"/> Battery: Rechargeable Li-ion Battery<br>Rechargeable Li-polymer Battery<br>Brand Name: ShenZhen Utility Power Source Co., Ltd.<br>Model: D07<br>7.6V dc_2500mAh<br><input type="checkbox"/> DC Power Supply<br><input type="checkbox"/> External from USB Cable<br><input type="checkbox"/> External DC Adapter |

|               |                                      |
|---------------|--------------------------------------|
|               | <input type="checkbox"/> Host System |
| Received Date | Sep. 24, 2021                        |
| Date of Test  | Sep 10, 2018 ~ Nov 05, 2018          |

\*All measurement and test data in this report was gathered from production sample serial number:  
RXZ210922002-01 (Assigned by BACL).

## 1.2. Objective

This report is prepared on behalf of *FEITIAN Technologies Co., Ltd.* in accordance with Part 2, Subpart J, Part 15, Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine the Bluetooth BR and EDR mode of EUT compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

## 1.3. Related Submittal(s)/Grant(s)

FCC Part 15.407 NII submission with FCC ID: ZD3FTF20SC200RNA

FCC Part 15.247 DTS Submittal with FCC ID: ZD3FTF20SC200RNA

FCC Part 15.225 DXX submissions with FCC ID: ZD3FTF20SC200RNA

FCC Part 22H24E27 PCB submissions with FCC ID: ZD3FTF20SC200RNA

FCC Part 90 PCB submissions with FCC ID: ZD3FTF20SC200RNA

## 1.4. Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

## 1.5. Statement of Compliance

Decision Rule: No, (The test results do not include MU judgment)

It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

The determination of the test results does not require consideration of the uncertainty of the measurement, unless the assessment is required by customer agreement, regulation or standard document specification.

Bay Area Compliance Laboratories Corp. is not responsible for the authenticity of the information provided by the applicant that affects the test results.

**1.6. Measurement Uncertainty**

| Parameter                     |               | Uncertainty  |
|-------------------------------|---------------|--------------|
| AC Mains                      |               | +/- 2.36 dB  |
| RF output power, conducted    |               | +/- 0.93 dB  |
| Occupied Bandwidth            |               | +/- 0.35 MHz |
| Unwanted Emissions, conducted |               | +/- 1.69 dBm |
| Emissions, radiated           | 30 MHz~1GHz   | +/- 5.22 dB  |
|                               | 1 GHz~18 GHz  | +/- 6.12 dB  |
|                               | 18 GHz~40 GHz | +/- 4.99 dB  |
| Temperature                   |               | +/- 1.27 °C  |
| Humidity                      |               | +/- 3 %      |

**1.7. Environmental Conditions**

| Test Site                                | Test Data           | Temperature (°C) | Relative Humidity (%) | ATM Pressure (hPa) | Test Engineer |
|------------------------------------------|---------------------|------------------|-----------------------|--------------------|---------------|
| AC Line Conducted Emissions              | 2021/10/12          | 27.2             | 50.5                  | 1010               | Boris Kao     |
| Radiation Spurious Emissions             | 2021/10/1~2021/10/3 | 24.1~26.1        | 56~61                 | 1010               | David Lee     |
| Conducted Spurious Emissions             | 2021/9/30           | 25.2             | 50                    | 1010               | David Lee     |
| 20 dB Emission Bandwidth                 | 2021/9/30           | 25.2             | 50                    | 1010               | David Lee     |
| Channel Separation Test                  | 2021/9/30           | 25.2             | 50                    | 1010               | David Lee     |
| Time of Occupancy                        | 2021/9/30           | 25.2             | 50                    | 1010               | David Lee     |
| Quantity of hopping channel              | 2021/9/30           | 25.2             | 50                    | 1010               | David Lee     |
| Maximum Output Power                     | 2021/9/30           | 25.2             | 50                    | 1010               | David Lee     |
| 100 kHz Bandwidth of Frequency Band Edge | 2021/9/30           | 25.2             | 50                    | 1010               | David Lee     |

**1.8. Test Facility**

The Test site used by Bay Area Compliance Laboratories Corp. to collect test data is located on

☒70, Lane 169, Sec. 2, Datong Road, Xizhi Dist., New Taipei City 22183, Taiwan, R.O.C.

Bay Area Compliance Laboratories Corp. is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 3732) and the FCC designation No.TW3732 under the Mutual Recognition Agreement (MRA) in FCC Test.

## 2. System Test Configuration

### 2.1. Description of Test Configuration

For BT mode, 79 channels are provided to testing:

| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|
| 1       | 2402            | 40      | 2441            |
| 2       | 2403            | --      | --              |
| 3       | 2404            | --      | --              |
| 4       | 2405            | 77      | 2478            |
| --      | --              | 78      | 2479            |
| 39      | 2440            | 79      | 2480            |

For BT Modes were tested with channel 1, 40 and 79.

The system was configured for testing in engineering mode, which was provided by manufacturer.

### 2.2. Equipment Modifications

No modification was made to the EUT.

### 2.3. EUT Exercise Software

The test software was used “QRCT V3.0”

| Test Frequency      |                | 2402MHz | 2441MHz | 2480MHz |
|---------------------|----------------|---------|---------|---------|
| Power Level Setting | GFSK           | 9       | 9       | 9       |
|                     | $\pi/4$ -DQPSK | 9       | 9       | 9       |
|                     | 8DPSK          | 9       | 9       | 9       |

### 2.4. Test Mode

Pre-scan

AC Line Conducted Emissions and Radiated Spurious Emissions

Mode 1: F20 FP + Adapter (Model : DSA-10PF06-05 FSU).

Mode 2: F20 FP + Adapter (Model : TEKA-UCA20US).

Mode 3: F20 + Adapter (Model : DSA-10PF06-05 FSU).

Mode 4: F20 + Adapter (Model : TEKA-UCA20US).

Worst case is the F20 + Adapter (Model : DSA-10PF06-05 FSU).

Full System F20 + Adapter (Model : DSA-10PF06-05 FSU) for all test item.



## 2.5. Support Equipment List and Details

| Description | Manufacturer          | Model Number      | S/N     |
|-------------|-----------------------|-------------------|---------|
| NB          | DELL                  | E6410             | 8N7PXN1 |
| Adapter-1   | DEE VAN<br>ENTERPRISE | DSA-10PF06-05 FSU | N/A     |
| Adapter-2   | TEKA                  | TEKA-UCA20US      | N/A     |
| Dock        | FEITIAN               | F20-1             | N/A     |

## 2.6. External Cable List and Details


| Cable Description | Length (m) | From    | To  |
|-------------------|------------|---------|-----|
| USB Cable         | 1.5        | Adapter | EUT |

## 2.7. Block Diagram of Test Setup


See test photographs attached in annex setup photos for the actual connections between EUT and support equipment.

### Radiation:


Below 1GHz:



Above 1GHz:



**Conduction:**



### 3. Summary of Test Results

| FCC Rules                    | Description of Test                      | Results    |
|------------------------------|------------------------------------------|------------|
| §15.247(i), §1.1310, §2.1093 | RF Exposure                              | Compliance |
| §15.203                      | Antenna Requirement                      | Compliance |
| §15.207(a)                   | AC Line Conducted Emissions              | Compliance |
| §15.205, §15.209, §15.247(d) | Spurious Emissions                       | Compliance |
| §15.247(a)(1)                | 20 dB Emission Bandwidth                 | Compliance |
| §15.247 (a)(1)               | Channel Separation Test                  | Compliance |
| §15.247(a)(1)(iii)           | Time of Occupancy (Dwell Time)           | Compliance |
| §15.247(a)(1)(iii)           | Quantity of hopping channel Test         | Compliance |
| §15.247(b)(1)                | Maximum Peak Output Power                | Compliance |
| §15.247(d)                   | 100 kHz Bandwidth of Frequency Band Edge | Compliance |

#### 4. Test Equipment List and Details

| Description                        | Manufacturer                   | Model                  | Serial Number    | Calibration Date | Calibration Due Date |
|------------------------------------|--------------------------------|------------------------|------------------|------------------|----------------------|
| AC Line Conduction Room (CON-A)    |                                |                        |                  |                  |                      |
| LISN                               | Rohde & Schwarz                | ENV216                 | 101612           | 2020/12/30       | 2021/12/29           |
| EMI Test Receiver                  | Rohde & Schwarz                | ESR7                   | 101419           | 2020/11/12       | 2021/11/11           |
| Pulse Limiter                      | Rohde & Schwarz                | ESH3Z2                 | TXZEM104         | 2021/7/29        | 2022/7/29            |
| RF Cable                           | EMEC                           | EM-CB5D                | 001              | 2021/6/11        | 2022/6/11            |
| Software                           | AUDIX                          | E3                     | V9.150826k       | N.C.R            | N.C.R                |
| Radiated Room (966-A)              |                                |                        |                  |                  |                      |
| Bilog Antenna with 6 dB Attenuator | SUNOL SCIENCES & MINI-CIRCUITS | JB6/UNAT-6+            | A050115/15542_01 | 2021/01/19       | 2022/01/18           |
| Horn Antenna                       | EMCO                           | 3115                   | 9311-4158        | 2021/08/26       | 2022/08/25           |
| Horn Antenna                       | ETS-Lindgren                   | 3116                   | 62638            | 2021/08/11       | 2022/08/10           |
| Preamplifier                       | Sonoma                         | 310N                   | 130602           | 2021/06/08       | 2022/06/07           |
| Preamplifier                       | A.H. system Inc.               | PAM-0118P              | 466              | 2020/11/5        | 2021/11/4            |
| Microwave Preamplifier             | EM Electronics Corporation     | EM18G40G               | 060656           | 2020/12/30       | 2021/12/29           |
| EMI Test Receiver                  | Rohde & Schwarz                | ESR7                   | 101419           | 2020/11/12       | 2021/11/11           |
| Spectrum Analyzer                  | Rohde & Schwarz                | FSV40                  | 101435           | 2021/01/07       | 2022/01/06           |
| Micro flex Cable                   | UTIFLEX                        | UFB197C-1-2362-70U-70U | 225757-001       | 2021/2/1         | 2022/1/31            |
| Coaxial Cable                      | COMMATE                        | PEWC                   | 8Dr              | 2020/12/25       | 2021/12/24           |
| Coaxial Cable                      | UTIFLEX                        | UFB311A-Q-1440-300300  | 220490-006       | 2021/2/1         | 2022/1/31            |
| Coaxial Cable                      | JUNFLON                        | J12J102248-00-B-5      | AUG-07-15-044    | 2020/12/25       | 2021/12/24           |
| Cable                              | EMC                            | EMC105-SM-SM-10000     | 201003           | 2021/2/3         | 2022/2/2             |
| Turn Table                         | Champro                        | TT-2000                | 060772-T         | N.C.R            | N.C.R                |
| Antenna Tower                      | Champro                        | AM-BS-4500-B           | 060772-A         | N.C.R            | N.C.R                |
| Controller                         | Champro                        | EM1000                 | 60772            | N.C.R            | N.C.R                |
| Software                           | Farad                          | EZ_EMC                 | BACL-03A1        | N.C.R            | N.C.R                |

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

| Conducted Room    |                 |           |            |            |            |
|-------------------|-----------------|-----------|------------|------------|------------|
| Spectrum Analyzer | Rohde & Schwarz | FSU26     | 200268     | 2021/7/14  | 2022/7/13  |
| Cable             | UTIFLEX         | UFA210A   | 9435       | 2020/10/08 | 2021/10/07 |
| Attenuator        | MCL             | BW-S10W5+ | 1419       | 2021/01/28 | 2022/01/27 |
| Power Sensor      | KEYSIGHT        | U2021XA   | MY54080018 | 2021/01/28 | 2022/01/27 |

**\*Statement of Traceability:** BACL Corp. attests that all of the calibrations on the equipment items listed above were traceable to the SI System of Units via the R.O.C. Center for Measurement Standards of the Electronics Testing Center, Taiwan (ETC) or to another internationally recognized National Metrology Institute (NMI), and were compliant with the current Taiwan Accreditation Foundation (TAF) requirements

## 5. FCC §15.247(i), §1.1310, § 2.1093 - RF Exposure

### 5.1. Applicable Standard

According to §2.1093 and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

1.  $f(\text{GHz})$  is the RF channel transmit frequency in GHz.
2. Power and distance are rounded to the nearest mW and mm before calculation.
3. The result is rounded to one decimal place for comparison.
4. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test Exclusion.

### 5.2. RF Exposure Evaluation Result

#### RF Exposure evaluation:

| Mode | Frequency | Tunp-up<br>Average Power |      | Evaluation<br>Distance | Calculated<br>Value | Threshold | SAR Test<br>Exclusion |
|------|-----------|--------------------------|------|------------------------|---------------------|-----------|-----------------------|
|      | (MHz)     | (dBm)                    | (mW) | (mm)                   |                     | (1-g SAR) |                       |
| BT   | 2402-2480 | 8                        | 6.31 | 5                      | 2.008               | 3         | Yes                   |

**Result:** SAR test is exempted.

## 6. FCC §15.203 – Antenna Requirements

### 6.1. Applicable Standard

According to § 15.203,

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna does not exceed 6dBi.

### 6.2. Antenna Information

| Manufacturer                      | Model | Type        | Antenna Gain |
|-----------------------------------|-------|-------------|--------------|
| AUDEN TECHNO<br>(KUNSHAN) CO. LTD | F200  | FPC Antenna | 2 dBi        |

**Result: Compliance**

## 7. FCC §15.207(a) – AC Line Conducted Emissions

### 7.1. Applicable Standard

According to §15.207


For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequencies ranges.

| Frequency of Emission<br>(MHz) | Conducted Limit (dBuV)     |                            |
|--------------------------------|----------------------------|----------------------------|
|                                | Quasi-Peak                 | Average                    |
| 0.15-0.5                       | 66 to 56 <sup>Note 1</sup> | 56 to 46 <sup>Note 2</sup> |
| 0.5-5                          | 56                         | 46                         |
| 5-30                           | 60                         | 50                         |

Note 1: Decreases with the logarithm of the frequency.

Note 2: A linear average detector is required

### 7.2. EUT Setup



**Note: 1. Support units were connected to second LISN.  
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.**

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.



### 7.3. EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150kHz to 30MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations

| Frequency Range | IF B/W |
|-----------------|--------|
| 150kHz – 30MHz  | 9kHz   |

### 7.4. Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

### 7.5. Corrected Factor & Margin Calculation

The factor is calculated by adding LISN/ISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss} + \text{Transient Limiter Attenuation}$$


The “Over Limit” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an over limit of -7 dB means the emission is 7 dB below the limit. The equation for Over Limit calculation is as follows:

$$\text{Over Limit} = \text{Level} - \text{Limit Line}$$

## 7.6. Test Results

Test Mode: Transmitting

Main: AC120 V, 60 Hz, Line




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Correct<br>Factor(dB) | Result<br>(dBμV) | Limit<br>(dBμV) | Over limit<br>(dB) | Remark  |
|-----|--------------------|-------------------|-----------------------|------------------|-----------------|--------------------|---------|
| 1   | 0.694              | 13.64             | 19.60                 | 33.24            | 56.00           | -22.76             | QP      |
| 2   | 0.694              | 3.83              | 19.60                 | 23.43            | 46.00           | -22.57             | Average |
| 3   | 1.071              | 4.29              | 19.61                 | 23.90            | 56.00           | -32.10             | QP      |
| 4   | 1.071              | -4.95             | 19.61                 | 14.66            | 46.00           | -31.34             | Average |
| 5   | 1.338              | 4.03              | 19.62                 | 23.65            | 56.00           | -32.35             | QP      |
| 6   | 1.338              | -2.27             | 19.62                 | 17.35            | 46.00           | -28.65             | Average |
| 7   | 1.495              | 5.74              | 19.62                 | 25.36            | 56.00           | -30.64             | QP      |
| 8   | 1.495              | -2.32             | 19.62                 | 17.30            | 46.00           | -28.70             | Average |
| 9   | 3.364              | 6.94              | 19.67                 | 26.61            | 56.00           | -29.39             | QP      |
| 10  | 3.364              | -0.90             | 19.67                 | 18.77            | 46.00           | -27.23             | Average |
| 11  | 3.740              | 8.45              | 19.68                 | 28.13            | 56.00           | -27.87             | QP      |
| 12  | 3.740              | 0.02              | 19.68                 | 19.70            | 46.00           | -26.30             | Average |

Note:

Level = Read Level + Factor

Over Limit = Level – Limit Line

Factor = (LISN, ISN, PLC or current probe) Factor + Cable Loss + Attenuator

**Main: AC120 V, 60 Hz, Neutral**

| No. | Frequency | Reading | Correct    | Result | Limit  | Over limit | Remark  |
|-----|-----------|---------|------------|--------|--------|------------|---------|
|     | (MHz)     | (dBμV)  | Factor(dB) | (dBμV) | (dBμV) | (dB)       |         |
| 1   | 0.598     | 2.50    | 19.59      | 22.09  | 56.00  | -33.91     | QP      |
| 2   | 0.598     | -2.71   | 19.59      | 16.88  | 46.00  | -29.12     | Average |
| 3   | 0.686     | 6.34    | 19.59      | 25.93  | 56.00  | -30.07     | QP      |
| 4   | 0.686     | -1.40   | 19.59      | 18.19  | 46.00  | -27.81     | Average |
| 5   | 0.979     | -1.10   | 19.60      | 18.50  | 56.00  | -37.50     | QP      |
| 6   | 0.979     | -7.55   | 19.60      | 12.05  | 46.00  | -33.95     | Average |
| 7   | 1.374     | -1.02   | 19.61      | 18.59  | 56.00  | -37.41     | QP      |
| 8   | 1.374     | -6.54   | 19.61      | 13.07  | 46.00  | -32.93     | Average |
| 9   | 3.346     | 6.20    | 19.67      | 25.87  | 56.00  | -30.13     | QP      |
| 10  | 3.346     | -2.25   | 19.67      | 17.42  | 46.00  | -28.58     | Average |
| 11  | 3.820     | 6.36    | 19.69      | 26.05  | 56.00  | -29.95     | QP      |
| 12  | 3.820     | -1.09   | 19.69      | 18.60  | 46.00  | -27.40     | Average |

Note:

Level = Read Level + Factor

Over Limit = Level – Limit Line

Factor = (LISN, ISN, PLC or current probe) Factor + Cable Loss + Attenuator

## 8. FCC §15.209, §15.205 , §15.247(d) – Spurious Emissions

### 8.1. Applicable Standard

As per FCC §15.35(d): Unless otherwise specified, on any frequency or frequencies above 1000 MHz, the radiated emission limits are based on the use of measurement instrumentation employing an average detector function. Unless otherwise specified, measurements above 1000 MHz shall be performed using a minimum resolution bandwidth of 1MHz.

As Per FCC §15.205(a) except as show in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

| MHz                 | MHz                   | MHz             | GHz           |
|---------------------|-----------------------|-----------------|---------------|
| 0.090 – 0.110       | 16.42 – 16.423        | 608 – 614       | 4. 5 – 5. 15  |
| 0.495 – 0.505       | 16.69475 – 16.69525   | 960 – 1240      | 5. 35 – 5. 46 |
| 2.1735 – 2.1905     | 16.80425 – 16.80475   | 1300 – 1427     | 7.25 – 7.75   |
| 4.125 – 4.128       | 25.5 – 25.67          | 1435 – 1626.5   | 8.025 – 8.5   |
| 4.17725 – 4.17775   | 37.5 – 38.25          | 1645.5 – 1646.5 | 9.0 – 9.2     |
| 4.20725 – 4.20775   | 73 – 74.6             | 1660 – 1710     | 9.3 – 9.5     |
| 6.215 – 6.218       | 74.8 – 75.2           | 1718.8 – 1722.2 | 10.6 – 12.7   |
| 6.26775 – 6.26825   | 108 – 121.94          | 2200 – 2300     | 13.25 – 13.4  |
| 6.31175 – 6.31225   | 123 – 138             | 2310 – 2390     | 14.47 – 14.5  |
| 8.291 – 8.294       | 149.9 – 150.05        | 2483.5 – 2500   | 15.35 – 16.2  |
| 8.362 – 8.366       | 156.52475 – 156.52525 | 2690 – 2900     | 17.7 – 21.4   |
| 8.37625 – 8.38675   | 156.7 – 156.9         | 3260 – 3267     | 22.01 – 23.12 |
| 8.41425 – 8.41475   | 162.0125 – 167.17     | 3.332 – 3.339   | 23.6 – 24.0   |
| 12.29 – 12.293      | 167.72 – 173.2        | 3 3458 – 3 358  | 31.2 – 31.8   |
| 12.51975 – 12.52025 | 240 – 285             | 3.600 – 4.400   | 36.43 – 36.5  |
| 12.57675 – 12.57725 | 322 – 335.4           |                 | Above 38.6    |
| 13.36 – 13.41       | 399.9 – 410           |                 |               |

As per FCC §15.209(a): Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency (MHz) | Field Strength (micro volts/meter) | Measurement Distance (meters) |
|-----------------|------------------------------------|-------------------------------|
| 0.009 - 0.490   | 2400/F(kHz)                        | 300                           |
| 0.490 - 1.705   | 24000/F(kHz)                       | 30                            |
| 1.705 - 30.0    | 30                                 | 30                            |
| 30 - 88         | 100**                              | 3                             |
| 88 - 216        | 150**                              | 3                             |
| 216 - 960       | 200**                              | 3                             |
| Above 960       | 500                                | 3                             |

\*\* Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.


As per FCC §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.


the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

## 8.2. EUT Setup

Below 1 GHz:



Above 1 GHz:



Radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC Part 15.209 and FCC 15.247 Limits.

### 8.3. EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 26.5 GHz. During the radiated emission test, the EMI test receiver was set with the following configurations measurement method 6.3 in ANSI C63.10.

| Frequency Range | RBW     | VBW   | Measurement method |
|-----------------|---------|-------|--------------------|
| 30-1000 MHz     | 120 kHz | /     | QP                 |
| Above 1 GHz     | 1 MHz   | 3 MHz | PK                 |
|                 | 1 MHz   | 10 Hz | Ave                |

### 8.4. Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in the Quasi-peak detector mode from 30 MHz to 1 GHz and PK and average detector modes for frequencies above 1 GHz.

### 8.5. Corrected Factor & Margin Calculation

The Correct Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Correct Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:


$$\text{Margin} = \text{Result} - \text{Limit}$$

8.6. Test Results


Test Mode: Transmitting (Pre-scan with three orthogonal axis, and worse case as X axis.)

30MHz-1GHz: (worst case is BR (GFSK) mode low channel)

Horizontal




Vertical




**BR (GFSK) Mode**

**Horizontal** (worst case is BR (GFSK) mode low channel)

1GHz-18GHz:




18GHz-26.5GHz:






**Vertical** (worst case is BR (GFSK) mode low channel)

1GHz-18GHz:



18GHz-26.5GHz:



**Below 1GHz****Horizontal**

| Frequency | Reading | Correct      | Result   | Limit    | Margin | Height | Degree | Remark |
|-----------|---------|--------------|----------|----------|--------|--------|--------|--------|
| (MHz)     | (dBμV)  | Factor(dB/m) | (dBμV/m) | (dBμV/m) | (dB)   | (cm)   | ( ° )  |        |
| 87.2300   | 38.21   | -16.80       | 21.41    | 40.00    | -18.59 | 100    | 200    | peak   |
| 101.7800  | 32.74   | -13.57       | 19.17    | 43.50    | -24.33 | 100    | 96     | peak   |
| 124.0900  | 35.18   | -10.35       | 24.83    | 43.50    | -18.67 | 100    | 48     | peak   |
| 147.3700  | 34.52   | -10.87       | 23.65    | 43.50    | -19.85 | 100    | 35     | peak   |
| 183.2600  | 33.74   | -12.98       | 20.76    | 43.50    | -22.74 | 100    | 22     | peak   |
| 427.7000  | 30.39   | -7.06        | 23.33    | 46.00    | -22.67 | 100    | 196    | peak   |

**Vertical**

| Frequency | Reading | Correct      | Result   | Limit    | Margin | Height | Degree | Remark |
|-----------|---------|--------------|----------|----------|--------|--------|--------|--------|
| (MHz)     | (dBμV)  | Factor(dB/m) | (dBμV/m) | (dBμV/m) | (dB)   | (cm)   | ( ° )  |        |
| 34.8500   | 40.51   | -6.65        | 33.86    | 40.00    | -6.14  | 100    | 52     | peak   |
| 46.4900   | 47.64   | -14.62       | 33.02    | 40.00    | -6.98  | 100    | 185    | peak   |
| 65.8900   | 44.27   | -16.75       | 27.52    | 40.00    | -12.48 | 100    | 313    | peak   |
| 88.2000   | 45.80   | -16.73       | 29.07    | 43.50    | -14.43 | 100    | 28     | peak   |
| 121.1800  | 33.73   | -10.21       | 23.52    | 43.50    | -19.98 | 100    | 17     | peak   |
| 176.4700  | 36.98   | -12.75       | 24.23    | 43.50    | -19.27 | 100    | 123    | peak   |

Result = Reading + Correct Factor

Margin = Result – Limit

Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain

Spurious emissions more than 20 dB below the limit were not reported.

**Above 1GHz****Horizontal**

| Frequency                 | Reading | Correct      | Result   | Limit    | Margin | Height | Degree | Remark |
|---------------------------|---------|--------------|----------|----------|--------|--------|--------|--------|
| (MHz)                     | (dBμV)  | Factor(dB/m) | (dBμV/m) | (dBμV/m) | (dB)   | (cm)   | ( ° )  |        |
| BR (GFSK), Low channel    |         |              |          |          |        |        |        |        |
| 2360.700                  | 56.43   | -10.46       | 45.97    | 74.00    | -28.03 | 149    | 168    | peak   |
| 2360.700                  | 42.12   | -10.46       | 31.66    | 54.00    | -22.34 | 149    | 168    | AVG    |
| 2402.200                  | 111.42  | -10.13       | 101.29   | N/A      | N/A    | 149    | 168    | peak   |
| 2402.200                  | 95.96   | -10.13       | 85.83    | N/A      | N/A    | 149    | 168    | AVG    |
| 4804.000                  | 43.64   | -3.28        | 40.36    | 74.00    | -33.64 | 146    | 225    | peak   |
| 4804.000                  | 32.53   | -3.28        | 29.25    | 54.00    | -24.75 | 146    | 225    | AVG    |
| 7206.000                  | 42.46   | 3.10         | 45.56    | 74.00    | -28.44 | 152    | 328    | peak   |
| 7206.000                  | 31.66   | 3.10         | 34.76    | 54.00    | -19.24 | 152    | 328    | AVG    |
| BR (GFSK), Middle channel |         |              |          |          |        |        |        |        |
| 2441.000                  | 110.54  | -9.81        | 100.73   | N/A      | N/A    | 145    | 175    | peak   |
| 2441.000                  | 95.25   | -9.81        | 85.44    | N/A      | N/A    | 145    | 175    | AVG    |
| 4882.000                  | 44.65   | -3.02        | 41.63    | 74.00    | -32.37 | 138    | 254    | peak   |
| 4882.000                  | 33.65   | -3.02        | 30.63    | 54.00    | -23.37 | 138    | 254    | AVG    |
| 7323.000                  | 43.73   | 4.08         | 47.81    | 74.00    | -26.19 | 155    | 136    | peak   |
| 7323.000                  | 32.78   | 4.08         | 36.86    | 54.00    | -17.14 | 155    | 136    | AVG    |
| BR (GFSK), High channel   |         |              |          |          |        |        |        |        |
| 2480.000                  | 108.47  | -9.31        | 99.16    | N/A      | N/A    | 155    | 176    | peak   |
| 2480.000                  | 93.56   | -9.31        | 84.25    | N/A      | N/A    | 155    | 176    | AVG    |
| 2492.058                  | 56.94   | -9.14        | 47.80    | 74.00    | -26.20 | 155    | 176    | peak   |
| 2492.058                  | 44.29   | -9.14        | 35.15    | 54.00    | -18.85 | 155    | 176    | AVG    |
| 4960.000                  | 47.08   | -2.69        | 44.39    | 74.00    | -29.61 | 158    | 155    | peak   |
| 4960.000                  | 33.58   | -2.69        | 30.89    | 54.00    | -23.11 | 158    | 155    | AVG    |
| 7440.000                  | 43.70   | 4.25         | 47.95    | 74.00    | -26.05 | 144    | 254    | peak   |
| 7440.000                  | 32.46   | 4.25         | 36.71    | 54.00    | -17.29 | 144    | 254    | AVG    |

Result = Reading + Correct Factor

Margin = Result – Limit

Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain

Spurious emissions more than 20 dB below the limit were not reported.

**Vertical**

| Frequency                 | Reading | Correct      | Result   | Limit    | Margin | Height | Degree | Remark |
|---------------------------|---------|--------------|----------|----------|--------|--------|--------|--------|
| (MHz)                     | (dBμV)  | Factor(dB/m) | (dBμV/m) | (dBμV/m) | (dB)   | (cm)   | ( ° )  |        |
| BR (GFSK), Low channel    |         |              |          |          |        |        |        |        |
| 2378.900                  | 57.27   | -10.32       | 46.95    | 74.00    | -27.05 | 100    | 263    | peak   |
| 2378.900                  | 42.15   | -10.32       | 31.83    | 54.00    | -22.17 | 100    | 263    | AVG    |
| 2402.100                  | 102.72  | -10.13       | 92.59    | N/A      | N/A    | 100    | 263    | peak   |
| 2402.100                  | 89.23   | -10.13       | 79.10    | N/A      | N/A    | 100    | 263    | AVG    |
| 4804.000                  | 44.24   | -3.28        | 40.96    | 74.00    | -33.04 | 156    | 196    | peak   |
| 4804.000                  | 33.28   | -3.28        | 30.00    | 54.00    | -24.00 | 156    | 196    | AVG    |
| 7206.000                  | 41.73   | 3.10         | 44.83    | 74.00    | -29.17 | 146    | 233    | peak   |
| 7206.000                  | 31.56   | 3.10         | 34.66    | 54.00    | -19.34 | 146    | 233    | AVG    |
| BR (GFSK), Middle channel |         |              |          |          |        |        |        |        |
| 2441.000                  | 94.88   | -9.81        | 85.07    | N/A      | N/A    | 105    | 247    | peak   |
| 2441.000                  | 82.79   | -9.81        | 72.98    | N/A      | N/A    | 105    | 247    | AVG    |
| 4882.000                  | 43.08   | -3.02        | 40.06    | 74.00    | -33.94 | 156    | 233    | peak   |
| 4882.000                  | 32.55   | -3.02        | 29.53    | 54.00    | -24.47 | 156    | 233    | AVG    |
| 7323.000                  | 42.41   | 4.08         | 46.49    | 74.00    | -27.51 | 148    | 328    | peak   |
| 7323.000                  | 31.86   | 4.08         | 35.94    | 54.00    | -18.06 | 148    | 328    | AVG    |
| BR (GFSK), High channel   |         |              |          |          |        |        |        |        |
| 2480.086                  | 94.53   | -9.31        | 85.22    | N/A      | N/A    | 108    | 234    | peak   |
| 2480.086                  | 82.54   | -9.31        | 73.23    | N/A      | N/A    | 108    | 234    | AVG    |
| 2485.000                  | 57.01   | -9.24        | 47.77    | 74.00    | -26.23 | 108    | 234    | peak   |
| 2485.000                  | 43.22   | -9.24        | 33.98    | 54.00    | -20.02 | 108    | 234    | AVG    |
| 4960.000                  | 43.61   | -2.69        | 40.92    | 74.00    | -33.08 | 154    | 283    | peak   |
| 4960.000                  | 33.65   | -2.69        | 30.96    | 54.00    | -23.04 | 154    | 283    | AVG    |
| 7440.000                  | 41.89   | 4.25         | 46.14    | 74.00    | -27.86 | 166    | 328    | peak   |
| 7440.000                  | 32.18   | 4.25         | 36.43    | 54.00    | -17.57 | 166    | 328    | AVG    |

Result = Reading + Correct Factor

Margin = Result – Limit

Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain

Spurious emissions more than 20 dB below the limit were not reported.

**Horizontal**

| Frequency                       | Reading | Correct      | Result   | Limit    | Margin | Height | Degree | Remark |
|---------------------------------|---------|--------------|----------|----------|--------|--------|--------|--------|
| (MHz)                           | (dBμV)  | Factor(dB/m) | (dBμV/m) | (dBμV/m) | (dB)   | (cm)   | ( ° )  |        |
| EDR (π/4-DQPSK), Low channel    |         |              |          |          |        |        |        |        |
| 2387.800                        | 56.38   | -10.25       | 46.13    | 74.00    | -27.87 | 145    | 223    | peak   |
| 2387.800                        | 41.98   | -10.25       | 31.73    | 54.00    | -22.27 | 145    | 223    | AVG    |
| 2402.200                        | 111.28  | -10.13       | 101.15   | N/A      | N/A    | 145    | 223    | peak   |
| 2402.200                        | 90.07   | -10.13       | 79.94    | N/A      | N/A    | 145    | 223    | AVG    |
| 4804.000                        | 42.29   | -3.28        | 39.01    | 74.00    | -34.99 | 159    | 242    | peak   |
| 4804.000                        | 32.56   | -3.28        | 29.28    | 54.00    | -24.72 | 159    | 242    | AVG    |
| 7206.000                        | 41.52   | 3.10         | 44.62    | 74.00    | -29.38 | 146    | 322    | peak   |
| 7206.000                        | 31.28   | 3.10         | 34.38    | 54.00    | -19.62 | 146    | 322    | AVG    |
| EDR (π/4-DQPSK), Middle channel |         |              |          |          |        |        |        |        |
| 2441.000                        | 111.04  | -9.81        | 101.23   | N/A      | N/A    | 145    | 171    | peak   |
| 2441.000                        | 88.16   | -9.81        | 78.35    | N/A      | N/A    | 145    | 171    | AVG    |
| 4882.000                        | 44.13   | -3.02        | 41.11    | 74.00    | -32.89 | 156    | 255    | peak   |
| 4882.000                        | 32.18   | -3.02        | 29.16    | 54.00    | -24.84 | 156    | 255    | AVG    |
| 7323.000                        | 42.10   | 4.08         | 46.18    | 74.00    | -27.82 | 148    | 321    | peak   |
| 7323.000                        | 31.96   | 4.08         | 36.04    | 54.00    | -17.96 | 148    | 321    | AVG    |
| EDR (π/4-DQPSK), High channel   |         |              |          |          |        |        |        |        |
| 2480.086                        | 109.03  | -9.31        | 99.72    | N/A      | N/A    | 166    | 178    | peak   |
| 2480.086                        | 88.34   | -9.31        | 79.03    | N/A      | N/A    | 166    | 178    | AVG    |
| 2487.560                        | 57.37   | -9.20        | 48.17    | 74.00    | -25.83 | 166    | 178    | peak   |
| 2487.560                        | 45.06   | -9.20        | 35.86    | 54.00    | -18.14 | 166    | 178    | AVG    |
| 4960.000                        | 43.43   | -2.69        | 40.74    | 74.00    | -33.26 | 146    | 248    | peak   |
| 4960.000                        | 32.58   | -2.69        | 29.89    | 54.00    | -24.11 | 146    | 248    | AVG    |
| 7440.000                        | 42.02   | 4.25         | 46.27    | 74.00    | -27.73 | 155    | 196    | peak   |
| 7440.000                        | 32.01   | 4.25         | 36.26    | 54.00    | -17.74 | 155    | 196    | AVG    |

Result = Reading + Correct Factor

Margin = Result – Limit

Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain

Spurious emissions more than 20 dB below the limit were not reported.

**Vertical**

| Frequency                       | Reading | Correct      | Result   | Limit    | Margin | Height | Degree | Remark |
|---------------------------------|---------|--------------|----------|----------|--------|--------|--------|--------|
| (MHz)                           | (dBμV)  | Factor(dB/m) | (dBμV/m) | (dBμV/m) | (dB)   | (cm)   | ( ° )  |        |
| EDR (π/4-DQPSK), Low channel    |         |              |          |          |        |        |        |        |
| 2379.900                        | 56.58   | -10.31       | 46.27    | 74.00    | -27.73 | 104    | 238    | peak   |
| 2379.900                        | 42.09   | -10.31       | 31.78    | 54.00    | -22.22 | 104    | 238    | AVG    |
| 2402.200                        | 96.34   | -10.13       | 86.21    | N/A      | N/A    | 104    | 238    | peak   |
| 2402.200                        | 78.66   | -10.13       | 68.53    | N/A      | N/A    | 104    | 238    | AVG    |
| 4804.000                        | 44.02   | -3.28        | 40.74    | 74.00    | -33.26 | 145    | 149    | peak   |
| 4804.000                        | 32.28   | -3.28        | 29.00    | 54.00    | -25.00 | 145    | 149    | AVG    |
| 7206.000                        | 41.98   | 3.10         | 45.08    | 74.00    | -28.92 | 156    | 255    | peak   |
| 7206.000                        | 31.56   | 3.10         | 34.66    | 54.00    | -19.34 | 156    | 255    | AVG    |
| EDR (π/4-DQPSK), Middle channel |         |              |          |          |        |        |        |        |
| 2441.000                        | 95.28   | -9.81        | 85.47    | N/A      | N/A    | 110    | 248    | peak   |
| 2441.000                        | 77.90   | -9.81        | 68.09    | N/A      | N/A    | 110    | 248    | AVG    |
| 4882.000                        | 44.49   | -3.02        | 41.47    | 74.00    | -32.53 | 156    | 155    | peak   |
| 4882.000                        | 32.33   | -3.02        | 29.31    | 54.00    | -24.69 | 156    | 155    | AVG    |
| 7323.000                        | 42.75   | 4.08         | 46.83    | 74.00    | -27.17 | 144    | 238    | peak   |
| 7323.000                        | 31.28   | 4.08         | 35.36    | 54.00    | -18.64 | 144    | 238    | AVG    |
| EDR (π/4-DQPSK), High channel   |         |              |          |          |        |        |        |        |
| 2479.922                        | 95.06   | -9.31        | 85.75    | N/A      | N/A    | 105    | 238    | peak   |
| 2479.922                        | 76.80   | -9.31        | 67.49    | N/A      | N/A    | 105    | 238    | AVG    |
| 2487.690                        | 57.24   | -9.20        | 48.04    | 74.00    | -25.96 | 105    | 238    | peak   |
| 2487.690                        | 43.52   | -9.20        | 34.32    | 54.00    | -19.68 | 105    | 238    | AVG    |
| 4960.000                        | 45.41   | -2.69        | 42.72    | 74.00    | -31.28 | 166    | 238    | peak   |
| 4960.000                        | 33.66   | -2.69        | 30.97    | 54.00    | -23.03 | 166    | 238    | AVG    |
| 7440.000                        | 41.34   | 4.25         | 45.59    | 74.00    | -28.41 | 158    | 135    | peak   |
| 7440.000                        | 32.18   | 4.25         | 36.43    | 54.00    | -17.57 | 158    | 135    | AVG    |

Result = Reading + Correct Factor

Margin = Result – Limit

Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain

Spurious emissions more than 20 dB below the limit were not reported.

**Horizontal**

| Frequency                   | Reading | Correct      | Result   | Limit    | Margin | Height | Degree | Remark |
|-----------------------------|---------|--------------|----------|----------|--------|--------|--------|--------|
| (MHz)                       | (dBμV)  | Factor(dB/m) | (dBμV/m) | (dBμV/m) | (dB)   | (cm)   | ( ° )  |        |
| EDR (8DPSK), Low channel    |         |              |          |          |        |        |        |        |
| 2389.800                    | 56.27   | -10.23       | 46.04    | 74.00    | -27.96 | 155    | 161    | peak   |
| 2389.800                    | 42.35   | -10.23       | 32.12    | 54.00    | -21.88 | 155    | 161    | AVG    |
| 2402.200                    | 112.00  | -10.13       | 101.87   | N/A      | N/A    | 155    | 161    | peak   |
| 2402.200                    | 82.84   | -10.13       | 72.71    | N/A      | N/A    | 155    | 161    | AVG    |
| 4804.000                    | 43.20   | -3.28        | 39.92    | 74.00    | -34.08 | 156    | 233    | peak   |
| 4804.000                    | 32.58   | -3.28        | 29.30    | 54.00    | -24.70 | 156    | 233    | AVG    |
| 7206.000                    | 41.83   | 3.10         | 44.93    | 74.00    | -29.07 | 148    | 138    | peak   |
| 7206.000                    | 31.66   | 3.10         | 34.76    | 54.00    | -19.24 | 148    | 138    | AVG    |
| EDR (8DPSK), Middle channel |         |              |          |          |        |        |        |        |
| 2441.000                    | 111.22  | -9.81        | 101.41   | N/A      | N/A    | 145    | 165    | peak   |
| 2441.000                    | 82.43   | -9.81        | 72.62    | N/A      | N/A    | 145    | 165    | AVG    |
| 4882.000                    | 43.72   | -3.02        | 40.70    | 74.00    | -33.30 | 155    | 158    | peak   |
| 4882.000                    | 32.58   | -3.02        | 29.56    | 54.00    | -24.44 | 155    | 158    | AVG    |
| 7323.000                    | 40.96   | 4.08         | 45.04    | 74.00    | -28.96 | 146    | 232    | peak   |
| 7323.000                    | 31.66   | 4.08         | 35.74    | 54.00    | -18.26 | 146    | 232    | AVG    |
| EDR (8DPSK), High channel   |         |              |          |          |        |        |        |        |
| 2480.168                    | 109.07  | -9.31        | 99.76    | N/A      | N/A    | 145    | 238    | peak   |
| 2480.168                    | 80.86   | -9.31        | 71.55    | N/A      | N/A    | 145    | 238    | AVG    |
| 2489.640                    | 57.71   | -9.17        | 48.54    | 74.00    | -25.46 | 145    | 238    | peak   |
| 2489.640                    | 45.34   | -9.17        | 36.17    | 54.00    | -17.83 | 145    | 238    | AVG    |
| 4960.000                    | 43.49   | -2.69        | 40.80    | 74.00    | -33.20 | 139    | 238    | peak   |
| 4960.000                    | 32.45   | -2.69        | 29.76    | 54.00    | -24.24 | 139    | 238    | AVG    |
| 7440.000                    | 42.96   | 4.25         | 47.21    | 74.00    | -26.79 | 142    | 166    | peak   |
| 7440.000                    | 31.28   | 4.25         | 35.53    | 54.00    | -18.47 | 142    | 166    | AVG    |

Result = Reading + Correct Factor

Margin = Result – Limit

Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain

Spurious emissions more than 20 dB below the limit were not reported.

**Vertical**

| Frequency                   | Reading | Correct      | Result   | Limit    | Margin | Height | Degree | Remark |
|-----------------------------|---------|--------------|----------|----------|--------|--------|--------|--------|
| (MHz)                       | (dBμV)  | Factor(dB/m) | (dBμV/m) | (dBμV/m) | (dB)   | (cm)   | ( ° )  |        |
| EDR (8DPSK), Low channel    |         |              |          |          |        |        |        |        |
| 2374.500                    | 57.08   | -10.35       | 46.73    | 74.00    | -27.27 | 108    | 223    | peak   |
| 2374.500                    | 42.49   | -10.35       | 32.14    | 54.00    | -21.86 | 108    | 223    | AVG    |
| 2402.200                    | 96.89   | -10.13       | 86.76    | N/A      | N/A    | 108    | 223    | peak   |
| 2402.200                    | 73.94   | -10.13       | 63.81    | N/A      | N/A    | 108    | 223    | AVG    |
| 4804.000                    | 43.23   | -3.28        | 39.95    | 74.00    | -34.05 | 165    | 238    | peak   |
| 4804.000                    | 32.28   | -3.28        | 29.00    | 54.00    | -25.00 | 165    | 238    | AVG    |
| 7206.000                    | 41.99   | 3.10         | 45.09    | 74.00    | -28.91 | 144    | 155    | peak   |
| 7206.000                    | 31.56   | 3.10         | 34.66    | 54.00    | -19.34 | 144    | 155    | AVG    |
| EDR (8DPSK), Middle channel |         |              |          |          |        |        |        |        |
| 2440.922                    | 95.39   | -9.81        | 85.58    | N/A      | N/A    | 102    | 238    | peak   |
| 2440.922                    | 71.50   | -9.81        | 61.69    | N/A      | N/A    | 102    | 238    | AVG    |
| 4882.000                    | 43.66   | -3.02        | 40.64    | 74.00    | -33.36 | 146    | 238    | peak   |
| 4882.000                    | 32.33   | -3.02        | 29.31    | 54.00    | -24.69 | 146    | 238    | AVG    |
| 7323.000                    | 42.04   | 4.08         | 46.12    | 74.00    | -27.88 | 155    | 135    | peak   |
| 7323.000                    | 31.56   | 4.08         | 35.64    | 54.00    | -18.36 | 155    | 135    | AVG    |
| EDR (8DPSK), High channel   |         |              |          |          |        |        |        |        |
| 2480.086                    | 94.99   | -9.31        | 85.68    | N/A      | N/A    | 105    | 288    | peak   |
| 2480.086                    | 72.82   | -9.31        | 63.51    | N/A      | N/A    | 105    | 288    | AVG    |
| 2485.330                    | 57.49   | -9.24        | 48.25    | 74.00    | -25.75 | 105    | 288    | peak   |
| 2485.330                    | 43.75   | -9.24        | 34.51    | 54.00    | -19.49 | 105    | 288    | AVG    |
| 4960.000                    | 44.13   | -2.69        | 41.44    | 74.00    | -32.56 | 138    | 221    | peak   |
| 4960.000                    | 33.15   | -2.69        | 30.46    | 54.00    | -23.54 | 138    | 221    | AVG    |
| 7440.000                    | 41.34   | 4.25         | 45.59    | 74.00    | -28.41 | 144    | 138    | peak   |
| 7440.000                    | 32.56   | 4.25         | 36.81    | 54.00    | -17.19 | 144    | 138    | AVG    |

Result = Reading + Correct Factor

Margin = Result – Limit


Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain

Spurious emissions more than 20 dB below the limit were not reported.




**Conducted Spurious Emissions:**

| Channel                     | Frequency (MHz) | Delta Peak to Band Emission (dBc) | Limit (dBc) | Result |
|-----------------------------|-----------------|-----------------------------------|-------------|--------|
| BR Mode (GFSK)              |                 |                                   |             |        |
| Low                         | 2402            | 51.10                             | $\geq 20$   | PASS   |
| Mid                         | 2441            | 49.30                             | $\geq 20$   | PASS   |
| High                        | 2480            | 51.76                             | $\geq 20$   | PASS   |
| EDR Mode ( $\pi/4$ -DQPSK): |                 |                                   |             |        |
| Low                         | 2402            | 45.08                             | $\geq 20$   | PASS   |
| Mid                         | 2441            | 44.46                             | $\geq 20$   | PASS   |
| High                        | 2480            | 46.67                             | $\geq 20$   | PASS   |
| EDR Mode (8DPSK):           |                 |                                   |             |        |
| Low                         | 2402            | 47.62                             | $\geq 20$   | PASS   |
| Mid                         | 2441            | 46.86                             | $\geq 20$   | PASS   |
| High                        | 2480            | 50.03                             | $\geq 20$   | PASS   |

**BR Mode (GFSK)****Low Channel**


Date: 30.SEP.2021 11:05:20

Middle Channel



Date: 30.SEP.2021 12:43:06


High Channel



Date: 30.SEP.2021 12:50:01


EDR Mode ( $\pi/4$ -DQPSK)

Low Channel




Date: 30.SEP.2021 14:25:30

Middle Channel



Date: 30.SEP.2021 14:41:32


## High Channel



Date: 30.SEP.2021 14:54:31


## EDR Mode (8DPSK)

### Low Channel




Date: 30.SEP.2021 15:42:51

## Middle Channel



Date: 30.SEP.2021 15:50:55

## High Channel



Date: 30.SEP.2021 15:56:01

## 9. FCC §15.247(a)(1) – 20 dB Emission Bandwidth

### 9.1. Applicable Standard

According to FCC §15.247(a) (1) the maximum 20 dB bandwidth of the hopping channel shall be presented.

### 9.2. Test Procedure

- (1) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- (2) Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- (3) Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
- (4) Repeat above procedures until all frequencies measured were complete.


### 9.3. Test Results

| Channel                                    | Frequency<br>(MHz) | 20 dBc BW<br>(MHz) |
|--------------------------------------------|--------------------|--------------------|
| <i>BR Mode (GFSK)</i>                      |                    |                    |
| Low                                        | 2402               | 0.96               |
| Middle                                     | 2441               | 0.96               |
| High                                       | 2480               | 0.96               |
| <i>EDR Mode (<math>\pi/4</math>-DQPSK)</i> |                    |                    |
| Low                                        | 2402               | 1.28               |
| Middle                                     | 2441               | 1.28               |
| High                                       | 2480               | 1.29               |
| <i>EDR Mode (8DPSK)</i>                    |                    |                    |
| Low                                        | 2402               | 1.29               |
| Middle                                     | 2441               | 1.29               |
| High                                       | 2480               | 1.29               |

Please refer to the following plots


### BR Mode (GFSK)

#### Low Channel




Date: 30.SEP.2021 11:00:49

#### Middle Channel




Date: 30.SEP.2021 12:38:19

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

**High Channel**


Date: 30.SEP.2021 12:48:43

**EDR Mode ( $\pi/4$ -DQPSK)****Low Channel**

Date: 30.SEP.2021 14:23:29




Middle Channel



Date: 30.SEP.2021 14:38:49


High Channel



Date: 30.SEP.2021 14:53:22


## EDR Mode (8DPSK)

### Low Channel




Date: 30.SEP.2021 15:41:24

### Middle Channel



Date: 30.SEP.2021 15:49:47

High Channel



Date: 30.SEP.2021 15:54:35

## 10. FCC §15.247(a)(1) – Channel Separation Test

### 10.1. Applicable Standard

According to FCC §15.247(a) (1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

### 10.2. Test Procedure


1. Set the EUT in transmitting mode, max hold the channel.
2. Set the adjacent channel of the EUT and max hold another trace.
3. Measure the channel separation.

### 10.3. Test Results

| Channel                    | Channel Separation (MHz) | 20 dBc BW (MHz) | Two-thirds of the 20 dB bandwidth (MHz) | Channel Separation Limit           | Result     |
|----------------------------|--------------------------|-----------------|-----------------------------------------|------------------------------------|------------|
| BR Mode (GFSK)             |                          |                 |                                         |                                    |            |
| Low                        | 0.995                    | 0.96            | 0.637                                   | >two-thirds of the 20 dB bandwidth | Compliance |
| Middle                     | 0.995                    | 0.96            | 0.637                                   | >two-thirds of the 20 dB bandwidth | Compliance |
| High                       | 0.990                    | 0.96            | 0.637                                   | >two-thirds of the 20 dB bandwidth | Compliance |
| EDR Mode ( $\pi/4$ -DQPSK) |                          |                 |                                         |                                    |            |
| Low                        | 1.000                    | 1.28            | 0.853                                   | >two-thirds of the 20 dB bandwidth | Compliance |
| Middle                     | 1.000                    | 1.28            | 0.853                                   | >two-thirds of the 20 dB bandwidth | Compliance |
| High                       | 1.000                    | 1.29            | 0.860                                   | >two-thirds of the 20 dB bandwidth | Compliance |
| EDR Mode (8DPSK)           |                          |                 |                                         |                                    |            |
| Low                        | 1.000                    | 1.29            | 0.862                                   | >two-thirds of the 20 dB bandwidth | Compliance |
| Middle                     | 1.004                    | 1.29            | 0.859                                   | >two-thirds of the 20 dB bandwidth | Compliance |
| High                       | 1.000                    | 1.29            | 0.862                                   | >two-thirds of the 20 dB bandwidth | Compliance |


Please refer to the following plots.

BR Mode (GFSK)  
Low Channel




Date: 30.SEP.2021 11:22:10

Middle Channel



Date: 30.SEP.2021 13:00:57


## High Channel



Date: 30.SEP.2021 13:02:19


## EDR Mode ( $\pi/4$ -DQPSK)

### Low Channel




Date: 30.SEP.2021 14:33:34

Middle Channel




Date: 30.SEP.2021 14:51:57

High Channel




Date: 30.SEP.2021 14:59:06

EDR Mode (8DPSK)  
Low Channel



Date: 30.SEP.2021 15:45:21


Middle Channel



Date: 30.SEP.2021 15:53:09



High Channel



Date: 30.SEP.2021 16:24:13

## **11. FCC§15.247(a)(1)(iii) –Time of Occupancy (Dwell Time)**

### **11.1. Applicable Standard**

According to FCC §15.247(a) (1) (iii).

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

### **11.2. Test Procedure**

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel  $RBW \leq$  channel spacing and where possible RBW should be set  $\gg 1/T$ , where T is the expected dwell time per channel Sweep = as necessary to capture the entire dwell time per hopping channel Detector function = peak Trace = max hold

Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

Repeat the measurement using a longer sweep time to determine the number of hops over the period specified in the requirements. The sweep time shall be equal to, or less than, the period specified in the requirements.

Determine the number of hops over the sweep time and calculate the total number of hops in the period specified in the requirements, using the following equation:

(Number of hops in the period specified in the requirements) = (number of hops on spectrum analyzer) x (period specified in the requirements / analyzer sweep time)

The average time of occupancy is calculated from the transmit time per hop multiplied by the number of hops in the period specified. If the number of hops in a specific time varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation.

**11.3. Test Results**

| <b>Test mode: BR mode / 2402 ~ 2480MHz (GFSK)</b>                      |                            |                           |                            |                                |                       |               |
|------------------------------------------------------------------------|----------------------------|---------------------------|----------------------------|--------------------------------|-----------------------|---------------|
| <b>Mode</b>                                                            | <b>Pulse Time<br/>(ms)</b> | <b>Hopping<br/>Number</b> | <b>Period Time<br/>(s)</b> | <b>Total of Dwell<br/>(ms)</b> | <b>Limit<br/>(ms)</b> | <b>Result</b> |
| DH1                                                                    | 0.384                      | 320                       | 31.6                       | 122.88                         | <400                  | PASS          |
| DH3                                                                    | 1.634                      | 160                       | 31.6                       | 261.44                         | <400                  | PASS          |
| DH5                                                                    | 2.884                      | 100                       | 31.6                       | 288.40                         | <400                  | PASS          |
| <b>Test mode: EDR mode / 2402 ~ 2480MHz (<math>\pi/4</math>-DQPSK)</b> |                            |                           |                            |                                |                       |               |
| <b>Mode</b>                                                            | <b>Pulse Time<br/>(ms)</b> | <b>Hopping<br/>Number</b> | <b>Period Time<br/>(s)</b> | <b>Total of Dwell<br/>(ms)</b> | <b>Limit<br/>(ms)</b> | <b>Result</b> |
| 2DH1                                                                   | 0.384                      | 320                       | 31.6                       | 122.88                         | <400                  | PASS          |
| 2DH3                                                                   | 1.634                      | 150                       | 31.6                       | 245.10                         | <400                  | PASS          |
| 2DH5                                                                   | 2.884                      | 100                       | 31.6                       | 288.40                         | <400                  | PASS          |
| <b>Test mode: EDR mode / 2402 ~ 2480MHz (8DPSK)</b>                    |                            |                           |                            |                                |                       |               |
| <b>Mode</b>                                                            | <b>Pulse Time<br/>(ms)</b> | <b>Hopping<br/>Number</b> | <b>Period Time<br/>(s)</b> | <b>Total of Dwell<br/>(ms)</b> | <b>Limit<br/>(ms)</b> | <b>Result</b> |
| 3DH1                                                                   | 0.384                      | 320                       | 31.6                       | 122.88                         | <400                  | PASS          |
| 3DH3                                                                   | 1.634                      | 150                       | 31.6                       | 245.10                         | <400                  | PASS          |
| 3DH5                                                                   | 2.884                      | 100                       | 31.6                       | 288.40                         | <400                  | PASS          |

Note 1: A period time =  $0.4 \times 79 = 31.6$  (s), Total of Dwell = Pulse Time \* Hopping Number


Note 2: Hopping Number = Hopping Number/10 \* 10

Note 3: Hopping Number/10 = Total of highest signals in 3.16s. (Second high signals were other channel)

Please refer to the following plots


BR Mode (GFSK)

DH1: Pulse Width




Date: 30.SEP.2021 12:25:01


DH1: Hopping Number



Date: 30.SEP.2021 12:26:05


**DH1: Hopping Number /10****(Hopping Number = 32 in 1/10 period of highest signals, Second High signals were other channel)**

Date: 30.SEP.2021 15:36:34

**DH3: Pulse Width**

Date: 30.SEP.2021 12:19:10


DH3: Hopping Number



Date: 30.SEP.2021 12:21:19


DH3: Hopping Number /10

(Hopping Number = 15 in 1/10 period of highest signals, Second High signals were other channel)




Date: 30.SEP.2021 12:21:37

DH5: Pulse Width




Date: 30.SEP.2021 11:37:22


DH5: Hopping Number



Date: 30.SEP.2021 11:42:22

**DH5: Hopping Number /10****(Hopping Number = 10 in 1/10 period of highest signals, Second High signals were other channel)**


Date: 30.SEP.2021 11:46:55

**EDR Mode ( $\pi/4$ -DQPSK)****2DH1: Pulse Width**

Date: 30.SEP.2021 14:31:30




2DH1: Hopping Number



Date: 30.SEP.2021 15:29:21


2DH1: Hopping Number /10

(Hopping Number = 32 in 1/10 period of highest signals, Second High signals were other channel)




Date: 30.SEP.2021 15:21:26

2DH3: Pulse Width



Date: 30.SEP.2021 14:30:54


2DH3: Hopping Number



Date: 30.SEP.2021 15:10:59


## 2DH3: Hopping Number /10

(Hopping Number = 15 in 1/10 period of highest signals, Second High signals were other channel)




Date: 30.SEP.2021 15:14:10


## 2DH5: Pulse Width



Date: 30.SEP.2021 14:29:33

**2DH5: Hopping Number**


Date: 30.SEP.2021 15:09:37

**2DH5: Hopping Number /10****(Hopping Number = 10 in 1/10 period of highest signals, Second High signals were other channel)**

Date: 30.SEP.2021 15:10:04


EDR Mode (8DPSK)

3DH1: Pulse Width



Date: 30.SEP.2021 15:47:44


3DH1: Hopping Number



Date: 30.SEP.2021 16:00:52


### 3DH1: Hopping Number /10

(Hopping Number = 32 in 1/10 period of highest signals, Second High signals were other channel)




Date: 30.SEP.2021 16:04:35

### 3DH3: Pulse Width



Date: 30.SEP.2021 15:47:11


3DH3: Hopping Number



Date: 30.SEP.2021 16:03:17


3DH3: Hopping Number /10

(Hopping Number = 15 in 1/10 period of highest signals, Second High signals were other channel)




Date: 30.SEP.2021 16:16:05

3DH5: Pulse Width



Date: 30.SEP.2021 15:46:33

3DH5: Hopping Number




Date: 30.SEP.2021 16:04:05



3DH5: Hopping Number /10

(Hopping Number = 10 in 1/10 period of highest signals, Second High signals were other channel)



Date: 30.SEP.2021 16:01:59

## 12. FCC §15.247(a)(1)(iii) –Quantity of hopping channel Test

### 12.1. Applicable Standard

According to FCC §15.247(a) (1) (iii).

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.


### 12.2. Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the Max-Hold function record the Quantity of the channel.


### 12.3. Test Results

| Mode           | Frequency Range<br>(MHz) | Number of Hopping Channel<br>(CH) | Limit<br>(CH) | Result     |
|----------------|--------------------------|-----------------------------------|---------------|------------|
| GFSK           | 2402-2480                | 79                                | >15           | Compliance |
| $\pi/4$ -DQPSK | 2402-2480                | 79                                | >15           | Compliance |
| 8DPSK          | 2402-2480                | 79                                | >15           | Compliance |

Please refer to the following plots


**BR Mode (GFSK)**

Date: 30.SEP.2021 11:58:54

**EDR Mode ( $\pi/4$ -DQPSK)**

Date: 30.SEP.2021 15:23:30

EDR Mode (8DPSK)



Date: 30.SEP.2021 16:17:43

### 13. FCC §15.247(b)(1) – Maximum Output Power

#### 13.1. Applicable Standard

According to FCC §15.247(b) (1).

Frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725- 5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

#### 13.2. Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to measuring equipment.

#### 13.3. Test Results

| Channel                    | Frequency<br>(MHz) | Peak Conducted Output Power |       | Limit<br>(W) | Result     |
|----------------------------|--------------------|-----------------------------|-------|--------------|------------|
|                            |                    | (dBm)                       | (W)   |              |            |
| BR Mode (GFSK)             |                    |                             |       |              |            |
| Low                        | 2402               | 8.64                        | 0.007 | 0.125        | Compliance |
| Middle                     | 2441               | 7.74                        | 0.006 | 0.125        | Compliance |
| High                       | 2480               | 8.56                        | 0.007 | 0.125        | Compliance |
| EDR Mode ( $\pi/4$ -DQPSK) |                    |                             |       |              |            |
| Low                        | 2402               | 8.70                        | 0.007 | 0.125        | Compliance |
| Middle                     | 2441               | 7.81                        | 0.006 | 0.125        | Compliance |
| High                       | 2480               | 8.60                        | 0.007 | 0.125        | Compliance |
| EDR Mode (8DPSK)           |                    |                             |       |              |            |
| Low                        | 2402               | 9.03                        | 0.008 | 0.125        | Compliance |
| Middle                     | 2441               | 8.03                        | 0.006 | 0.125        | Compliance |
| High                       | 2480               | 8.90                        | 0.008 | 0.125        | Compliance |

| Channel                    | Frequency<br>(MHz) | Average Conducted Output Power |       | Limit<br>(W) | Result     |
|----------------------------|--------------------|--------------------------------|-------|--------------|------------|
|                            |                    | (dBm)                          | (W)   |              |            |
| BR Mode (GFSK)             |                    |                                |       |              |            |
| Low                        | 2402               | 7.54                           | 0.006 | N/A          | Compliance |
| Middle                     | 2441               | 6.66                           | 0.005 | N/A          | Compliance |
| High                       | 2480               | 7.49                           | 0.006 | N/A          | Compliance |
| EDR Mode ( $\pi/4$ -DQPSK) |                    |                                |       |              |            |
| Low                        | 2402               | 5.62                           | 0.004 | N/A          | Compliance |
| Middle                     | 2441               | 4.77                           | 0.003 | N/A          | Compliance |
| High                       | 2480               | 5.58                           | 0.004 | N/A          | Compliance |
| EDR Mode (8DPSK)           |                    |                                |       |              |            |
| Low                        | 2402               | 5.61                           | 0.004 | N/A          | Compliance |
| Middle                     | 2441               | 4.73                           | 0.003 | N/A          | Compliance |
| High                       | 2480               | 5.53                           | 0.004 | N/A          | Compliance |

## 14. FCC §15.247(d) – 100 kHz Bandwidth of Frequency Band Edge

### 14.1. Applicable Standard

According to FCC §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emissions limits specified in §15.209(a) see §15.205(c).

### 14.2. Test Procedure

Span = wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products which fall outside of the authorized band of operation.

RBW = 100 kHz VBW = 300 kHz

Sweep = coupled


Detector function = peak Trace = max hold

### 14.3. Test Results

| Channel                            | Frequency (MHz) | Delta Peak to Band Emission (dBc) | Limit (dBc) | Result |
|------------------------------------|-----------------|-----------------------------------|-------------|--------|
| BR Mode (GFSK)                     |                 |                                   |             |        |
| Low                                | 2402            | 51.37                             | $\geq 20$   | PASS   |
| High                               | 2480            | 54.52                             | $\geq 20$   | PASS   |
| BR Hopping Mode (GFSK)             |                 |                                   |             |        |
| Low                                | 2402-2480       | 53.49                             | $\geq 20$   | PASS   |
| High                               | 2402-2480       | 53.71                             | $\geq 20$   | PASS   |
| EDR Mode ( $\pi/4$ -DQPSK)         |                 |                                   |             |        |
| Low                                | 2402            | 53.18                             | $\geq 20$   | PASS   |
| High                               | 2480            | 52.89                             | $\geq 20$   | PASS   |
| EDR Hopping Mode ( $\pi/4$ -DQPSK) |                 |                                   |             |        |
| Low                                | 2402-2480       | 52.42                             | $\geq 20$   | PASS   |
| High                               | 2402-2480       | 50.13                             | $\geq 20$   | PASS   |
| EDR Mode (8DPSK)                   |                 |                                   |             |        |
| Low                                | 2402            | 52.50                             | $\geq 20$   | PASS   |
| High                               | 2480            | 52.30                             | $\geq 20$   | PASS   |
| EDR Hopping Mode (8DPSK)           |                 |                                   |             |        |
| Low                                | 2402-2480       | 51.57                             | $\geq 20$   | PASS   |
| High                               | 2402-2480       | 51.64                             | $\geq 20$   | PASS   |

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

**BR Mode (GFSK)**  
**Band Edge, CH Low**




Date: 30.SEP.2021 14:17:54

Page 72 of 77




BR Hopping Mode (GFSK)  
Band Edge, CH Low




Date: 30.SEP.2021 11:52:55

Band Edge, CH High




Date: 30.SEP.2021 14:13:41

EDR Mode ( $\pi/4$ -DQPSK)  
Band Edge, CH Low



Date: 30.SEP.2021 14:28:28


Band Edge, CH High



Date: 30.SEP.2021 14:55:16


EDR Hopping Mode ( $\pi/4$ -DQPSK)

Band Edge, CH Low



Date: 30.SEP.2021 15:07:56


Band Edge, CH High



Date: 30.SEP.2021 15:05:28


EDR Mode (8DPSK)

Band Edge, CH Low




Date: 30.SEP.2021 15:43:36


Band Edge, CH High



Date: 30.SEP.2021 15:56:45

**EDR Hopping Mode (8DPSK)****Band Edge, CH Low**

Date: 30.SEP.2021 15:59:41

**Band Edge, CH High**

Date: 30.SEP.2021 15:58:30

**\*\*\*\*\* END OF REPORT \*\*\*\*\***