

FCC PART 15.225


TEST REPORT

For

Feitian Technologies Co., Ltd.

Floor 17th, Tower B, Huizhi Mansion, No.9 Xueqing Road, Haidian District, Beijing, China

FCC ID: ZD3FTF360

Report Type: Original Report	Product Name: Android POS Terminal
Report Number:	RKSA240319001-00E
Report Date:	2024-11-06
Reviewed By:	Bard Liu 
Approved By:	Kyle Xu 
Prepared By:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu Province, China Tel: +86-512-86175000 Fax: +86-512-88934268 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Kunshan). This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, or any agency of the U.S. Government.

TABLE OF CONTENTS

REPORT REVISION HISTORY.....	4
GENERAL INFORMATION.....	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
OBJECTIVE	5
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY.....	6
TEST FACILITY	6
SYSTEM TEST CONFIGURATION.....	7
JUSTIFICATION	7
EUT EXERCISE SOFTWARE	7
EQUIPMENT MODIFICATIONS	7
SUPPORT EQUIPMENT LIST AND DETAILS	7
EXTERNAL I/O CABLE.....	7
BLOCK DIAGRAM OF TEST SETUP	8
TEST EQUIPMENT LIST	10
SUMMARY OF TEST RESULTS	11
FCC§1.1310 & §2.1093 - RF EXPOSURE.....	12
APPLICABLE STANDARD	12
MEASUREMENT RESULT:	12
FCC§15.203 - ANTENNA REQUIREMENT.....	13
APPLICABLE STANDARD	13
ANTENNA CONNECTED CONSTRUCTION	13
FCC §15.207 (A) – AC LINE CONDUCTED EMISSIONS	14
APPLICABLE STANDARD	14
TEST SYSTEM SETUP.....	14
EMI TEST RECEIVER SETUP.....	14
TEST PROCEDURE	14
TEST RESULTS SUMMARY	15
TEST DATA: SEE EXHIBIT D.....	15
FCC§15.225, §15.205 & §15.209 - RADIATED EMISSIONS TEST	16
APPLICABLE STANDARD	16
TEST SYSTEM SETUP.....	16
EMI TEST RECEIVER SETUP.....	18
TEST RESULTS SUMMARY	18
TEST DATA: SEE APPENDIX	18
FCC§15.225(E) - FREQUENCY STABILITY.....	19
APPLICABLE STANDARD	19
TEST PROCEDURE	19
TEST DATA: SEE APPENDIX	20
§15.215(C) - 20DB EMISSION BANDWIDTH TESTING.....	21
REQUIREMENT	21
TEST PROCEDURE	21
TEST DATA: SEE APPENDIX	21
EUT PHOTOGRAPHS.....	22

TEST SETUP PHOTOGRAPHS23

APPENDIX D - TEST DATA.....24

 AC LINE CONDUCTED EMISSIONS25

 RADIATED EMISSIONS TEST29

 FREQUENCY STABILITY39

 20dB EMISSION BANDWIDTH TESTING.....40

REPORT REVISION HISTORY

Number of Revisions	Report No.	Version	Issue Date	Description
0	RKSA240319001-00E	R1V1	2024-11-06	Initial Release

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant:	Feitian Technologies Co., Ltd.
Tested Model:	F360
Product Name:	Android POS Terminal
Power Supply:	DC 3.7V from battery or DC 5V charging by adapter
RF Function:	NFC
Operating Band/Frequency:	13.56 MHz
Antenna Type:	Coil Antenna

Adapter Information:

Model: TEKA-UCA20EU

Input: 100-240V, 50/60Hz, 0.35A Max

Output: 5.0V, 2.0A

Note: The maximum antenna gain was declared by the manufacturer.

All measurement and test data in this report was gathered from production sample serial number: RKSA240319001-1 (Assigned by the BACL (Kunshan). The EUT supplied by the applicant was received on 2024-03-19.)

Objective

This Type approval report is prepared for *Feitian Technologies Co., Ltd.* in accordance with Part 2-Subpart J, and Part 15-Subparts A and C of the Federal Communication Commission's rules.

The objective is to determine the Compliance of the EUT with FCC rules, sec 15.203, 15.205, 15.207, 15.209 and 15.225.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19 dB
RF conducted test with spectrum		0.9dB
Radiated emission	9kHz~30MHz	3.19dB
	30MHz~1GHz	6.11dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu Province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) is accredited in accordance with ISO/IEC 17025:2017 by NVLAP (Lab code: 600338-0), and the lab has been recognized as the FCC accredited lab under the KDB 974614 D01, the FCC Designation No.: CN5055.

SYSTEM TEST CONFIGURATION

Justification

The system was configured for testing in a typical fashion (as normally used by a typical user).

EUT Exercise Software

The EUT is tested in the engineering mode.

Equipment Modifications

No modification on the EUT.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable


Cable Description	Length (m)	From Port	To
Power Cable	1.0	AC Source/LISN	Adapter
USB Cable	1.5	Adapter	EUT

Block Diagram of Test Setup

For Conducted Emissions:



For Radiated Emissions (Below 1GHz):



TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test& 20dB EMISSION BANDWIDTH					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2024-04-23	2025-04-22
Sunol Sciences	Broadband Antenna	JB3	A090314-1	2023-11-11	2024-11-10
ETS-LINDGREN	Loop Antenna	6512	108100	2023-11-09	2024-11-08
Narda	6dB Attenuator	773-6	10690812-2-1	2023-11-11	2024-11-10
Sonoma Instrument	Pre-amplifier	310N	171205	2024-04-23	2025-04-22
Rohde & Schwarz	Auto Test Software	EMC32	100361	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-8	008	2024-04-23	2025-04-22
MICRO-COAX	Coaxial Cable	Cable-9	009	2024-04-23	2025-04-22
MICRO-COAX	Coaxial Cable	Cable-10	010	2024-04-23	2025-04-22
Frequency Stability					
BACL	Temperature & Humidity Chamber	BTH-150	30023	2024-04-25	2025-04-24
EAST	Regulated DC Power Supply	MCH-303D-II	14070562	2023-10-10	2024-10-09
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2024-04-23	2025-04-22
ETS-LINDGREN	Loop Antenna	6512	108100	2023-11-09	2024-11-08
MICRO-COAX	Coaxial Cable	Cable-10	010	2024-04-23	2025-04-22
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03-101746-zn	2023-07-28	2024-07-27
Rohde & Schwarz	LISN	ENV216	101115	2024-04-23	2025-04-22
Audix	Test Software	e3	V9	N/A	N/A
Rohde & Schwarz	Pulse limiter	ESH3-Z2	100552	2024-05-23	2025-05-22
MICRO-COAX	Coaxial Cable	Cable-15	015	2024-04-23	2025-04-22

Statement of Traceability: Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1310 & §2.1093	RF Exposure	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.225 §15.209 §15.205	Radiated Emission Test	Compliant
§15.225(e)	Frequency Stability	Compliant
§15.215(c)	20dB Emission Bandwidth Testing	Compliant

FCC§1.1310 & §2.1093 - RF Exposure

Applicable Standard

According to KDB447498 D01 General RF Exposure Guidance v06: 4.3. General SAR test exclusion Guidance

c) For frequencies below 100 MHz, the following may be considered for SAR test exclusion (also illustrated in Appendix C):

- 1) For test separation distances > 50 mm and < 200 mm, the power threshold at the corresponding test separation distance at 100 MHz in step b) is multiplied by $[1 + \log(100/f(\text{MHz}))]$
- 2) For test separation distances ≤ 50 mm, the power threshold determined by the equation in c) 1) for 50 mm and 100 MHz is multiplied by $\frac{1}{2}$
- 3) SAR measurement procedures are not established below 100 MHz.

Measurement Result:

For NFC, the power of EUT: E-Field@3m is 79.58 dBuV/m = -15.62 dBm(0.03mW)

Note: $E[\text{dB}\mu\text{V/m}] = \text{EIRP}[\text{dBm}] + 95.2$ for $d = 3$ m.

SAR test exclusion threshold for NFC (13.56MHz) separation distance $< 50\text{mm}$

$$= [474 * (1 + \log(100/f(\text{MHz}))) / 2]$$

$$= 443 \text{ mW}$$

$$> 0.03 \text{ mW}$$

Result: Compliant.

FCC§15.203 - ANTENNA REQUIREMENT

Applicable Standard

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

Antenna Connected Construction

The EUT has a Coil antenna for 13.56 MHz, the antenna was permanently attached, fulfill the requirement of this section, please refer to the EUT photos.


Result: Compliant.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207(a)

Test System Setup



The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	VBW
150 kHz - 30 MHz	9 kHz	30 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

If the maximum peak value of the emissions is below the average limit, the QP value and average value measurement will not need to be performed and only record the maximum peak measured value to meet the requirements.

Level & Over Limit Calculation

The Level is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation from the Meter Reading. The basic equation is as follows:

$$\text{Factor (dB)} = \text{LISN VDF (dB)} + \text{Cable Loss (dB)} + \text{Transient Limiter Attenuation (dB)}$$

$$\text{Level (dB}\mu\text{V)} = \text{Read level (dB}\mu\text{V)} + \text{Factor (dB)}$$

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit of 7 dB means the emission is 7 dB above the limit. The equation for Over Limit calculation is as follows:

$$\text{Over Limit (dB)} = \text{Level (dB}\mu\text{V)} - \text{Limit (dB}\mu\text{V)}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Test Data: See Exhibit D

FCC§15.225, §15.205 & §15.209 - RADIATED EMISSIONS TEST

Applicable Standard

As per FCC Part 15.225

(a) The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.


(b) Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.


(c) Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.

(d) The field strength of any emissions appearing outside of the 13.110–14.010 MHz band shall not exceed the general radiated emission limits in §15.209.

Test System Setup

9k - 30MHz:



30 MHz - 1 GHz:

The radiated emission tests were performed in the 3-meter chamber a test site, using the setup accordance with the ANSI C63.10. The specification used was the FCC Part Subpart C limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

According to FCC Rules, 47 CFR 15.33, the EUT emissions were investigated up to 1000 MHz.

During the radiated emission test, the EMI test Receiver was set with the following configurations:

Frequency Range	RBW	VBW	IF B/W	Measurement
9 kHz – 150 kHz	200 Hz	1 kHz	200 Hz	QP/Average
150 kHz – 30 MHz	9 kHz	30 kHz	9 kHz	QP/ Average
30 MHz – 1000 MHz	100 kHz	300 kHz	/	Peak
	/	/	120 kHz	QP

For 9 kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude (dBμV/m) = Meter Reading (dBμV) + Antenna Factor (dB/m) + Cable Loss (dB) - Amplifier Gain (dB)

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15.209, 15.205, 15.225.

Test Data: See Appendix

FCC§15.225(e) - FREQUENCY STABILITY

Applicable Standard

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency over a temperature variation of -20 degrees to $+50$ degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

Test Procedure

a) Supply the EUT with a nominal ac voltage or install a new or fully charged battery in the EUT. If possible, a dummy load shall be connected to the EUT because an antenna near the metallic walls of an environmental test chamber could affect the output frequency of the EUT. If the EUT is equipped with a permanently attached, adjustable-length antenna, then the EUT shall be placed in the center of the chamber with the antenna adjusted to the shortest length possible. Turn ON the EUT and tune it to one of the number of frequencies shown in 5.6.

b) Couple the unlicensed wireless device output to the measuring instrument by connecting an antenna to the measuring instrument with a suitable length of coaxial cable and placing the measuring antenna near the EUT (e.g., 15 cm away), or by connecting a dummy load to the measuring instrument, through an attenuator if necessary.
NOTE—An instrument that has an adequate level of accuracy as specified by the procuring or regulatory agency is the recommended measuring instrument.

c) Adjust the location of the measurement antenna and the controls on the measurement instrument to obtain a suitable signal level (i.e., a level that will not overload the measurement instrument but is strong enough to allow measurement of the operating or fundamental frequency of the EUT).

d) Turn the EUT OFF and place it inside the environmental temperature chamber. For devices that have oscillator heaters, energize only the heater circuit.

e) Set the temperature control on the chamber to the highest specified in the regulatory requirements for the type of device and allow the oscillator heater and the chamber temperature to stabilize.


f) While maintaining a constant temperature inside the environmental chamber, turn the EUT ON and record the operating frequency at startup, and at 2 minutes, 5 minutes, and 10 minutes after the EUT is energized. Four measurements in total are made.

g) Measure the frequency at each of frequencies specified in 5.6.

h) Switch OFF the EUT but do not switch OFF the oscillator heater.

i) Lower the chamber temperature by not more than 10°C , and allow the temperature inside the chamber to stabilize.

j) Repeat step f) through step i) down to the lowest specified temperature.



Test Data: See Appendix


§15.215(c) - 20dB EMISSION BANDWIDTH TESTING

Requirement

Per 15.215 (c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

Test Procedure

1. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.



Test Data: See Appendix

EUT PHOTOGRAPHS

Please refer to the attachment EXHIBIT A - EUT EXTERNAL PHOTOGRAPHS and EXHIBIT B - EUT INTERNAL PHOTOGRAPHS.

TEST SETUP PHOTOGRAPHS

Please refer to the attachment EXHIBIT G - TEST SETUP PHOTOGRAPHS.


APPENDIX D - TEST DATA

Test Item:	AC LINE CONDUCTED EMISSIONS		RADIATED EMISSIONS	
Test Date:	2024-06-25	2024-06-26	2024-05-25	2024-10-11
Temperature:	24.3 °C	24.3 °C	22.4 °C	22.7 °C
Relative Humidity:	61 %	61 %	46 %	47 %
ATM Pressure:	100.1 kPa	100.1 kPa	101.5 kPa	102.6 kPa
Test Result:	Pass	Pass	Pass	Pass
Test Engineer:	Joe Zhang	Joe Zhang	Leah Li	Richard Wen

Test Item:	FREQUENCY STABILITY	20dB EMISSION BANDWIDTH TESTING
Test Date:	2024-06-25	2024-05-25
Temperature:	24.3 °C	22.5 °C
Relative Humidity:	61 %	45 %
ATM Pressure:	100.1 kPa	101.1kPa
Test Result:	Pass	Pass
Test Engineer:	Joe Zhang	Leah Li


AC LINE CONDUCTED EMISSIONS*EUT operation mode: Transmitting***AC 120V/60 Hz, Line**

Test with Antenna



Site : CE
Condition : FCC Part 15.207
: DET:Peak
Project No. : RKSA240319001
Model : F360
Phase : L
Voltage : 120V/60Hz
Mode : NFC
Test Equipment : ENV216,ESR
Temperature : 24.3℃
Humidity : 61%
Atmospheric pressure: 100.1kPa
Test Engineer : Joe Zhang

		Read			Limit	Over	Remark
	Freq	Level	Factor	Level	Line	Limit	
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.496	13.80	20.14	33.94	46.06	-12.12	Average
2	0.496	23.20	20.14	43.34	56.06	-12.72	QP
3	0.537	13.90	20.12	34.02	46.00	-11.98	Average
4	0.537	25.20	20.12	45.32	56.00	-10.68	QP
5	0.573	12.10	20.10	32.20	46.00	-13.80	Average
6	0.573	24.00	20.10	44.10	56.00	-11.90	QP
7	1.032	7.30	19.74	27.04	46.00	-18.96	Average
8	1.032	21.50	19.74	41.24	56.00	-14.76	QP
9	1.187	6.80	19.83	26.63	46.00	-19.37	Average
10	1.187	20.20	19.83	40.03	56.00	-15.97	QP
11	2.648	6.60	20.20	26.80	46.00	-19.20	Average
12	2.648	23.00	20.20	43.20	56.00	-12.80	QP


Test with Load:

Site : CE
 Condition : FCC Part 15.207
 : DET:Peak
 Project No. : RKSA240319001
 Model : F360
 Phase : L
 Voltage : 120V/60Hz
 Mode : NFC
 Test Equipment : ENV216,ESR
 Temperature : 24.3°C
 Humidity : 61%
 Atmospheric pressure: 100.1kPa
 Test Engineer : Joe Zhang

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV		dB	dBuV	dB	
1	0.436	10.39	20.23	30.62	47.14	-16.52	Average
2	0.436	23.19	20.23	43.42	57.14	-13.72	QP
3	0.522	10.20	20.12	30.32	46.00	-15.68	Average
4	0.522	27.40	20.12	47.52	56.00	-8.48	QP
5	0.562	6.00	20.11	26.11	46.00	-19.89	Average
6	0.562	25.00	20.11	45.11	56.00	-10.89	QP
7	1.085	7.90	19.77	27.67	46.00	-18.33	Average
8	1.085	23.70	19.77	43.47	56.00	-12.53	QP
9	1.311	10.40	19.89	30.29	46.00	-15.71	Average
10	1.311	22.90	19.89	42.79	56.00	-13.21	QP
11	2.635	8.30	20.20	28.50	46.00	-17.50	Average
12	2.635	23.00	20.20	43.20	56.00	-12.80	QP

AC 120V/60 Hz, Neutral

Test with Antenna:




Site : CE
Condition : FCC Part 15.207
: DET:Peak
Project No. : RKSA240319001
Model : F360
Phase : N
Voltage : 120V/60Hz
Mode : NFC
Test Equipment : ENV216,ESR
Temperature : 24.3°C
Humidity : 61%
Atmospheric pressure: 100.1kPa
Test Engineer : Joe Zhang

	Read			Limit	Over	
	Freq	Level	Factor	Level	Line	Limit Remark
	MHz	dBUV	dB	dBUV	dBUV	dB
1	0.499	13.80	20.13	33.93	46.02	-12.09 Average
2	0.499	25.20	20.13	45.33	56.02	-10.69 QP
3	0.532	12.50	20.12	32.62	46.00	-13.38 Average
4	0.532	24.40	20.12	44.52	56.00	-11.48 QP
5	0.562	12.40	20.11	32.51	46.00	-13.49 Average
6	0.562	23.60	20.11	43.71	56.00	-12.29 QP
7	1.344	7.40	19.90	27.30	46.00	-18.70 Average
8	1.344	21.00	19.90	40.90	56.00	-15.10 QP
9	1.463	7.60	19.96	27.56	46.00	-18.44 Average
10	1.463	20.90	19.96	40.86	56.00	-15.14 QP
11	2.661	8.00	20.20	28.20	46.00	-17.80 Average
12	2.661	22.60	20.20	42.80	56.00	-13.20 QP

**AC 120V/60 Hz, Neutral
Teat with Load:**

Date: 2024-06-26



Trace: 1

Site : CE
Condition : FCC Part 15.207
: DET:Peak
Project No. : RKSA240319001
Model : F360
Phase : N
Voltage : 120V/60Hz
Mode : NFC
Test Equipment : ENV216,ESR
Temperature : 24.3℃
Humidity : 61%
Atmospheric pressure: 100.1kPa
Test Engineer : Joe Zhang


	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.489	11.89	20.16	32.05	46.19	-14.14	Average
2	0.489	22.79	20.16	42.95	56.19	-13.24	QP
3	0.527	11.40	20.12	31.52	46.00	-14.48	Average
4	0.527	24.40	20.12	44.52	56.00	-11.48	QP
5	0.568	12.31	20.10	32.41	46.00	-13.59	Average
6	0.568	23.21	20.10	43.31	56.00	-12.69	QP
7	1.112	5.21	19.78	24.99	46.00	-21.01	Average
8	1.112	16.31	19.78	36.09	56.00	-19.91	QP
9	1.331	7.50	19.90	27.40	46.00	-18.60	Average
10	1.331	17.20	19.90	37.10	56.00	-18.90	QP
11	2.583	5.70	20.20	25.90	46.00	-20.10	Average
12	2.583	16.30	20.20	36.50	56.00	-19.50	QP

RADIATED EMISSIONS TEST

Test mode: Transmitting

For Ground-parallel


1) 9 kHz~150 kHz:



Project No.RKSA240319001 Tester:Leah Li
Date: 25.MAY.2024 17:41:44

Frequency (kHz)	Corrected Amplitude (dBμV/m)@3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	FCC Part 15.225/15.209	
				Limit (dBμV/m) @3m	Margin (dB)
34.38	63.88	PK	46.06	116.88	53.00
9.00	66.59	PK	57.00	128.52	61.93
20.28	65.62	PK	49.92	121.46	55.84
15.49	65.64	PK	52.87	123.80	58.16

2) 150 kHz~30 MHz:




Project No.RKSA240319001

Tester:Leah Li

Date: 25.MAY.2024 17:36:15

Frequency (MHz)	Corrected Amplitude (dBμV/m)@3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	FCC Part 15.225/15.209	
				Limit (dBμV/m) @3m	Margin (dB)
14.12	39.25	PK	6.07	64.61	25.36
0.21	49.38	PK	49.30	101.16	51.78
1.40	39.85	PK	5.82	64.68	24.83

3) 13.11 MHz~14.01 MHz:




ProjectNo.:RKSA240319001 Tester:Richard

Date: 11.OCT.2024 08:06:21

Frequency (MHz)	Corrected Amplitude (dBμV/m)@3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	FCC Part 15.225/15.209	
				Limit (dBμV/m)@3m	Margin (dB)
13.70	54.87	PK	6.12	90.47	35.6
13.56	78.05	PK	6.12	124.00	45.95
13.49	55.84	PK	6.12	90.47	34.63
13.64	56.03	PK	6.12	90.47	34.44


For Parallel
1) 9 kHz~150 kHz:



Project No.RKSA240319001 Tester:Leah Li
Date: 25.MAY.2024 17:46:18

Frequency (kHz)	Corrected Amplitude (dBμV/m)@3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	FCC Part 15.225/15.209	
				Limit (dBμV/m) @3m	Margin (dB)
15.49	65.85	PK	52.87	123.80	57.95
20.28	65.89	PK	49.92	121.46	55.57
9.28	64.31	PK	56.82	128.25	63.94
34.66	62.60	PK	45.99	116.81	54.21

2) 150 kHz~30 MHz:




Project No.RKSA240319001

Tester:Leah Li

Date: 25.MAY.2024 18:40:44

Frequency (MHz)	Corrected Amplitude (dBuV/m)@3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	FCC Part 15.225/15.209	
				Limit (dBuV/m) @3m	Margin (dB)
14.18	36.34	PK	6.07	69.54	33.20
0.15	52.34	PK	50.90	104.08	51.74
2.00	38.58	PK	13.73	69.54	30.96

3) 13.11 MHz~14.01 MHz:




ProjectNo.:RKSA240319001 Tester:Richard

Date: 11.OCT.2024 08:07:27

Frequency (MHz)	Corrected Amplitude (dBμV/m)@3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	FCC Part 15.225/15.209	
				Limit (dBμV/m)@3m	Margin (dB)
13.48	54.10	PK	6.12	90.47	36.37
13.56	77.38	PK	6.12	124.00	46.62
13.64	54.96	PK	6.12	90.47	35.51
13.70	54.00	PK	6.12	90.47	36.47


For Perpendicular
1) 9 kHz~150 kHz:



Project No.RKSA240319001 Tester:Leah Li
Date: 25.MAY.2024 17:44:13

Frequency (kHz)	Corrected Amplitude (dBμV/m)@3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	FCC Part 15.225/15.209	
				Limit (dBμV/m) @3m	Margin (dB)
34.38	64.36	PK	46.06	116.88	52.52
9.56	64.73	PK	56.64	128.00	63.27
20.28	65.46	PK	49.92	121.46	56.00
15.48	67.29	PK	52.87	123.81	56.52

2) 150 kHz~30 MHz:




Project No.RKSA240319001

Tester:Leah Li

Date: 25.MAY.2024 17:22:47

Frequency (MHz)	Corrected Amplitude (dBμV/m)@3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	FCC Part 15.225/15.209	
				Limit (dBμV/m)@3m	Margin (dB)
14.12	41.55	PK	6.07	69.54	27.99
0.15	55.10	PK	50.90	104.08	48.98
1.58	38.05	PK	8.94	63.63	25.58

3) 13.11 MHz~14.01 MHz:



ProjectNo.:RKSA240319001 Tester:Richard

Date: 11.OCT.2024 08:08:27

Frequency (MHz)	Corrected Amplitude (dBμV/m)@3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	FCC Part 15.225/15.209	
				Limit (dBμV/m)@3m	Margin (dB)
13.71	55.83	PK	6.12	90.47	34.64
13.56	79.58	PK	6.12	124.00	44.42
13.49	57.14	PK	6.12	90.47	33.33
13.64	57.05	PK	6.12	90.47	33.42

30 MHz ~1 GHz:

Common Information

Project No:

EUT Model:

Test Mode:

Standard:

Test Equipment:

Temperature:

Humidity:

Barometric Pressure:

Test Engineer:

Test Date:

RKSA240319001

F360

NFC

FCC Part15.225 & Part 15.209 & Part 15.205

ESCI, JB3, 310N


21.3℃

48%

101.9kPa

Leah Li

2024/5/17



Critical Freqs

Frequency (MHz)	Corrected Amplitude QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Pol	Corr. (dB/m)
30.485000	27.72	40.00	12.28	V	-4.8
51.218750	23.59	40.00	16.41	V	-16.8
70.376250	27.68	40.00	12.32	V	-16.8
76.317500	28.47	40.00	11.53	V	-17.3
131.486250	27.04	43.50	16.46	V	-11.4
266.680000	35.07	46.00	10.93	H	-11.9

FREQUENCY STABILITY*Test Mode: Transmitting.**Test Result: Compliant*

F₀=13.56MHz				
Power Supply(V_{DC})	Temperature (°C)	Measured Frequency (MHz)	Frequency Error (%)	Part 15.225 Limit
3.70	-20	13.561183	0.00872	±0.01%
	-10	13.561192	0.00879	±0.01%
	0	13.561186	0.00875	±0.01%
	10	13.561184	0.00873	±0.01%
	20	13.56119	0.00878	±0.01%
	30	13.561182	0.00872	±0.01%
	40	13.561175	0.00867	±0.01%
	50	13.561163	0.00858	±0.01%
3.33	20	13.561184	0.00873	±0.01%
4.07	20	13.561194	0.00881	±0.01%


20dB EMISSION BANDWIDTH TESTING

Test Mode: Transmitting

Test Result: Compliant

Frequency (MHz)	20 dB Bandwidth (kHz)
13.56	0.44

20 dB Emission Bandwidth-13.56MHz



Project No.RKSA240319001 Tester:Leah Li
Date: 25.MAY.2024 17:28:40

Declarations

1. The laboratory is not responsible for the authenticity of any information provided by the applicant. Information from the applicant that may affect test results is marked with “★”.
2. The test data was only valid for the test sample(s).
3. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.
4. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.
5. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor $k=2$ with the 95.45% confidence interval.

******* END OF REPORT *******