



Report No.: AGC00006140602FE03

Page 1 of 39

FCC Test Report

Report No.: AGC00006140602FE03

FCC ID : ZDB-BRK5200

APPLICATION PURPOSE : Class II Permissive Change

PRODUCT DESIGNATION : Classic Case with Bluetooth® Keyboard for 7" Tablets

BRAND NAME : N/A

MODEL NAME : 8020576, 8020579, 8020580, ITIP-7700UM, BRK5200B

CLIENT : Tianyu Technology Co., Ltd

DATE OF ISSUE : Jun.16, 2014

STANDARD(S) : FCC Part 15 Rules

REPORT VERSION : V 1.0


Attestation of Global Compliance (Shenzhen) Co., Ltd

CAUTION:

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Jun.16, 2014	Valid	Class II Permissive Change

Product Change Record

This is a variant report based on model BRK5200.
Two Models all the same except for the appearance.
The original report can be referred to AGC02Y130301-1F2.
Only Radiated Emission, Band Edges were verified for the differences based on the original product.

TABLE OF CONTENTS

1. VERIFICATION OF COMPLIANCE	5
2. GENERAL INFORMATION	6
2.1 PRODUCT DESCRIPTION.....	6
2.2 TABLE OF CARRIER FREQUENCIES.....	6
2.3 RECEIVER INPUT BANDWIDTH.....	7
2.4 EXAMPLE OF A HOPPING SEQUENCE IN DATA MODE.....	8
2.5 EQUALLY AVERAGE USE OF FREQUENCIES AND BEHAVIOUR.....	8
2.6 RELATED SUBMITTAL(S) / GRANT (S)	8
2.7 TEST METHODOLOGY	8
2.8 MEASUREMENT UNCERTAINTY	8
2.9 TEST FACILITY	9
2.10 SPECIAL ACCESSORIES	9
2.11 EQUIPMENT MODIFICATIONS.....	9
3. SYSTEM TEST CONFIGURATION.....	10
3.1 CONFIGURATION OF TESTED SYSTEM.....	10
3.2 EQUIPMENT USED IN EUT SYSTEM	10
3.3. TEST FACILITY	11
4. SUMMARY OF TEST RESULTS.....	13
5. DESCRIPTION OF TEST MODES.....	13
6. RADIATED EMISSION.....	14
6.1 MEASUREMENT PROCEDURE	14
6.2 TEST SETUP	15
6.3 TEST RESULT (WORST MODULATION: GFSK).....	17
7. BAND EDGES EMISSION	29
7.1 MEASUREMENT PROCEDURE	29
7.2 TEST SET-UP	29
7.3 TEST RESULT	29
APPENDIX A.....	34
PHOTOGRAPHS OF THE TEST SETUP	34
APPENDIX B: PHOTOGRAPHS OF EUT	35

1. VERIFICATION OF COMPLIANCE

Applicant	Tianyu Technology Co., Ltd
Address	No 5, 3rd Beian Road, HuangJiang Town, Dongguan City, China
Manufacturer	Tianyu Technology Co., Ltd
Address	No 5, 3rd Beian Road, HuangJiang Town, Dongguan City, China
Product Designation	Classic Case with Bluetooth® Keyboard for 7" Tablets
Brand Name	N/A
Test Model	8020576
Series Model	8020579, 8020580, ITIP-7700UM, BRK5200B
Difference description	All the same except for the model name.
Date of test	Jun.11, 2014 to Jun.13, 2014
Deviation	None
Condition of Test Sample	Normal

WE HEREBY CERTIFY THAT:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2003) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC Rules Part 15.247.

Prepared By

Water Huang

Water Huang Jun.16, 2014

Checked By

Forrest Lei

Forrest Lei Jun.16, 2014

Authorized By

Solger Zhang

Solger Zhang Jun.16, 2014

2. GENERAL INFORMATION

2.1 PRODUCT DESCRIPTION

The EUT is "Classic Case with Bluetooth® Keyboard for 7" Tablets" designed as a "Communication Device". It is designed by way of utilizing the FHSS technology to achieve the system operation.

A major technical description of EUT is described as following:

Operation Frequency	2.402 GHz to 2.480GHz
Bluetooth Version	V3.0
Modulation	GFSK, $\pi/4$ -DQPSK, 8DPSK
Number of channels	79
Antenna Designation	Integrated Antenna
Antenna Gain	0.8dBi
Hardware Version	N/A
Software Version	N/A
Power Supply	DC 3.7V by Built-in Li-ion Battery

2.2 TABLE OF CARRIER FREQUENCYS

Frequency Band	Channel Number	Frequency
2400~2483.5MHZ	0	2402MHZ
	1	2403MHZ
	:	:
	38	2440 MHZ
	39	2441 MHZ
	40	2442 MHZ
	:	:
	77	2479 MHZ
	78	2480 MHZ

2.3 RECEIVER INPUT BANDWIDTH

The input bandwidth of the receiver is 1.3 MHz. In every connection one Bluetooth device is the master and the other one is slave. The master determines the hopping sequence. The slave follows this sequence. Both devices shift between RX and TX time slot according to the clock of the master. Additionally the type of connection (e.g. single or multisport (packet) is set up at the beginning of the connection. The master adapts its hopping frequency and its TX/RX timing according to the packet type of the connection. Also the slave of the connection will use these settings.

Repeating of a packet has no influence on the hopping sequence. The hopping sequence generated by the master of the connection will be followed in any case. That means, a repeated packet will not be send on the same frequency, it is send on the next frequency of the hopping sequence.

2.4 EXAMPLE OF A HOPPING SEQUENCE IN DATA MODE

Example of a 79 hopping sequence in data mode:

40,21,44,23,42,53,46,55,48,33,52,35,50,65,54,67
56,37,60,39,58,69,62,71,64,25,68,27,66,57,70,59
72,29,76,31,74,61,78,63,01,41,05,43,03,73,07,75
09,45,13,47,11,77,15,00,64,49,66,53,68,02,70,06
01, 51,03,55,05,04

2.5 EQUIALLY AVERAGE USE OF FREQUENCIES AND BEHAVIOUR

The generation of the hopping sequence in connection mode depends essentially on two input values:
1 LAP/UAP of the master of the connection

2 Internal master clock

The LAP(lower address part) are the 24 LSB's of the 48 BD_ADDRESS. The BD_ADDRESS is an unambiguous number of every Bluetooth unit. The UAP(upper address part) are the 24MSB's of the 48BD_ADDRESS

The internal clock of a Bluetooth unit is derived from a free running clock which is never adjusted and is never turned off. For synchronization with other units only offset are used. It has no relation to the time of the day. Its resolution is at least half the RX/TX slot length of 312.5us. The clock has a cycle of about One day(23h30). In most case it is implemented as 28 bit counter. For the deriving of the hopping sequence the entire.

LAP(24 bits),4LSB's(4bits)(Input 1) and the 27MSB's of the clock(Input 2) are used. With this input values different mathematical procedures(permutations, additions, XOR-operations)are performed to generate the Sequence. This will be done at the beginning of every new transmission.

Regarding short transmissions the Bluetooth system has the following behavior:

The first connection between the two devices is established, a hopping sequence was generated. For Transmitting the wanted data the complete hopping sequence was not used. The connection ended.

The second connection will be established. A new hopping sequence is generated. Due to the fact the Bluetooth clock has a different value, because the period between the two transmission is longer(and it Cannot be shorter)than the minimum resolution of the clock(312.5us).The hopping sequence will always Differ from the first one.

2.6 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID: ZDB-BRK5200**, filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

2.7 TEST METHODOLOGY

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4 (2003). Radiated testing was performed at an antenna to EUT distance 3 meters.

2.8 MEASUREMENT UNCERTAINTY

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

- Uncertainty of Conducted Emission, $U_c = \pm 2.75\text{dB}$
- Uncertainty of Radiated Emission, $U_c = \pm 3.2\text{dB}$

2.9 TEST FACILITY

All measurement facilities used to collect the measurement data are located at
Attestation of Global Compliance(Shenzhen) Co., Ltd.
2/F., Building 2, No.1-No.4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang, Bao'an District, Shenzhen,
Guangdong, China
The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4: 2003.
FCC register No.: 259865

2.10 SPECIAL ACCESSORIES

Refer to section 2.2.


2.11 EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.


3. SYSTEM TEST CONFIGURATION

3.1 CONFIGURATION OF TESTED SYSTEM

Configuration 1: (Normal Hopping)



Configuration 2: (Control continuous TX)



3.2 EQUIPMENT USED IN EUT SYSTEM

Item	Equipment	Mfr/Brand	Model/Type No.	Remark
1	Classic Case with Bluetooth® Keyboard for 7" Tablets	N/A	8020576	EUT
2	PC	Dell	INSPIRON	A.E

3.3. TEST FACILITY

Site	Attestation of Global Compliance (Shenzhen) Co., Ltd
Location	2/F., Building 2, No.1-No.4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang, Bao'an District, Shenzhen, Guangdong, China
Description	The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2003.

ALL TEST EQUIPMENT LIST

(For original test equipment list)

Description	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Power Meter	R&S	NRP-Z23	100323	07/18/2012	07/17/2013
RF attenuator	N/A	RFA20db	68	N/A	N/A
Spectrum Analyzer	Agilent	E4440A	US41421290	07/18/2012	07/17/2013
Amplifier	EM	EM30180	0607030	02/28/2013	02/27/2014
Horn Antenna	EM	EM-AH-10180	67	04/21/2012	04/20/2014
Horn Antenna	A.H. Systems Inc.	SAS-574	--	07/18/2012	07/17/2013
EMI Test Receiver	Rohde & Schwarz	ESCI	100694	07/18/2012	07/17/2013
Biological Antenna	A.H. Systems Inc.	SAS-521-4	26	06/08/2012	06/07/2013
Loop Antenna	Daze	ZN30900N	SEL0097	07/18/2012	07/17/2013
Isolation Transformer	LETEAC	LTBK	--	07/18/2012	07/17/2013

(For new test equipment list)

Description	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Power Probe	R&S	NRP-Z23	100323	07/17/2013	07/16/2014
RF attenuator	N/A	RFA20db	68	N/A	N/A
Spectrum Analyzer	Agilent	E4440A	US41421290	07/17/2013	07/16/2014
Amplifier	EM	EM30180	0607030	02/27/2014	02/26/2015
Horn Antenna	EM	EM-AH-10180	67	04/20/2014	04/19/2015
Horn Antenna	A.H. Systems Inc.	SAS-574	--	06/06/2014	06/06/2015
EMI Test Receiver	Rohde & Schwarz	ESCI	100694	07/17/2013	07/16/2014
Biological Antenna	A.H. Systems Inc.	SAS-521-4	26	06/06/2014	06/06/2015
Loop Antenna	Daze	ZN30900N	SEL0097	07/17/2013	07/16/2014
Isolation Transformer	LETEAC	LTBK	--	07/17/2013	07/16/2014

4. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.209	Radiated Emission	Compliant
§15.247	Band Edges	Compliant

5. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
1	Low channel TX
2	Middle channel TX
3	High channel TX
4	Normal operating

Note:

1. All the test modes can be supply by Built-in Li-ion battery and adapter, only the result of the worst case was recorded in the report, if no other cases.
2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.

6. RADIATED EMISSION

6.1 MEASUREMENT PROCEDURE

1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High - Low scan is not required in this case.


The following table is the setting of spectrum analyzer and receiver.'

Spectrum Parameter	Setting
Start Frequency	1GHz
Stop Frequency	26.5GHz
RB/VB(Emission in restricted band)	1MHz/1MHz for Peak, 1MHz/10Hz for Average
RB/VB(Emission in non-restricted band)	1MHz/1MHz for Peak


Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP

6.2 TEST SETUP


RADIATED EMISSION TEST SETUP BELOW 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz



6.3 TEST RESULT (Worst Modulation: GFSK)

RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

RADIATED EMISSION BELOW 1GHZ

RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL-HORIZONTAL



Site: site #1 Polarization: *Horizontal* Temperature: 26

Limit: FCC Class B 3M Radiation Power: Humidity: 60 %

EUT: Classic Case with Bluetooth Keyboard for 7" Tablets

M/N:8020576


Mode:Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna	Table	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		Height	Degree	
1	*	47.7832	20.89	8.39	29.28	40.00	-10.72	peak			
2		96.2833	25.86	0.05	25.91	43.50	-17.59	peak			
3		144.7833	15.64	15.23	30.87	43.50	-12.63	peak			
4		608.7667	5.24	22.93	28.17	46.00	-17.83	peak			
5		747.8000	5.25	26.57	31.82	46.00	-14.18	peak			
6		891.6833	6.52	28.39	34.91	46.00	-11.09	peak			

RESULT: PASS

RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL –VERTICAL



Site: site #1 Polarization: *Vertical* Temperature: 26
Limit: FCC Class B 3M Radiation Power: Humidity: 60 %
EUT: Classic Case with Bluetooth Keyboard for 7" Tablets
M/N:8020576
Mode:Low Channel TX
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		96.2833	20.26	10.07	30.33	43.50	-13.17	peak			
2		144.7833	15.42	15.23	30.65	43.50	-12.85	peak			
3	*	215.9167	21.81	12.60	34.41	43.50	-9.09	peak			
4		264.4166	18.07	14.34	32.41	46.00	-13.59	peak			
5		359.8000	13.16	18.80	31.96	46.00	-14.04	peak			
6		784.9833	4.59	27.11	31.70	46.00	-14.30	peak			

RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The “Factor” value can be calculated automatically by software of measurement system.

RADIATED EMISSION TEST- (30MHZ-1GHZ)-MIDDLE CHANNEL-HORIZONTAL



Site: site #1

Polarization: *Horizontal*

Temperature: 26

Limit: FCC Class B 3M Radiation

Power:

Humidity: 60 %

EUT:Classic Case with Bluetooth Keyboard for 7" Tablets

M/N:8020576

Mode:Middle Channel TX

Note:-

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	144.7833	19.14	15.23	34.37	43.50	-9.13	peak			
2		215.9167	15.22	10.56	25.78	43.50	-17.72	peak			
3		359.8000	3.56	18.80	22.36	46.00	-23.64	peak			
4		663.7333	4.36	24.22	28.58	46.00	-17.42	peak			
5		747.8000	5.25	26.57	31.82	46.00	-14.18	peak			
6		957.9667	2.60	29.92	32.52	46.00	-13.48	peak			

RESULT: PASS

RADIATED EMISSION TEST- (30MHZ-1GHZ)- MIDDLE CHANNEL -VERTICAL



Site: site #1 Polarization: **Vertical** Temperature: 26
Limit: FCC Class B 3M Radiation Power: Humidity: 60 %
EUT:Classic Case with Bluetooth Keyboard for 7" Tablets
M/N:8020576
Mode:Middle Channel TX
Note:


No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		120.5333	19.10	11.95	31.05	43.50	-12.45	peak			
2		143.1667	18.43	15.22	33.65	43.50	-9.85	peak			
3	*	215.9167	23.81	12.60	36.41	43.50	-7.09	peak			
4		264.4166	18.07	14.34	32.41	46.00	-13.59	peak			
5		359.8000	13.16	18.80	31.96	46.00	-14.04	peak			
6		607.1500	6.93	23.75	30.68	46.00	-15.32	peak			

RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The “Factor” value can be calculated automatically by software of measurement system.

RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL-HORIZONTAL




Site: site #1 Polarization: *Horizontal* Temperature: 26
 Limit: FCC Class B 3M Radiation Power: Humidity: 60 %
 EUT:Classic Case with Bluetooth Keyboard for 7" Tablets
 M/N:8020576
 Mode:High Channel TX
 Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	47.7832	22.89	8.39	31.28	40.00	-8.72	peak			
2		96.2833	23.86	0.05	23.91	43.50	-19.59	peak			
3		144.7833	18.14	15.23	33.37	43.50	-10.13	peak			
4		240.1667	10.45	12.94	23.39	46.00	-22.61	peak			
5		747.8000	5.25	26.57	31.82	46.00	-14.18	peak			
6		957.9667	2.60	29.92	32.52	46.00	-13.48	peak			

RESULT: PASS

RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL -VERTICAL



Site: site #1 Polarization: *Vertical* Temperature: 26

Limit: FCC Class B 3M Radiation Power: Humidity: 60 %

EUT:Classic Case with Bluetooth Keyboard for 7" Tablets

M/N:8020576

Mode:High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	144.7833	18.92	15.23	34.15	43.50	-9.35	peak			
2		215.9167	21.31	12.60	33.91	43.50	-9.59	peak			
3		264.4166	17.57	14.34	31.91	46.00	-14.09	peak			
4		359.8000	13.16	18.80	31.96	46.00	-14.04	peak			
5		717.0833	6.39	25.68	32.07	46.00	-13.93	peak			
6		890.0667	2.40	28.35	30.75	46.00	-15.25	peak			

RESULT: PASS


Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system

RADIATED

RADIATED EMISSION ABOVE 1GHZ

RADIATED EMISSION ABOVE 1GHZ (1-10th Harmonics)-LOW CHANNEL-HORIZONTAL




Site: site #1 Polarization: **Horizontal** Temperature: 26
Limit: RSS-GEN Class B 3M Radiation above 1GHZ(Power: Humidity: 60 %
EUT:Classic Case with Bluetooth Keyboard for 7" Tablets
M/N:8020576
Mode: Low Channel TX
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2402.000	107.83	-9.68	98.15	74.00	24.15	peak			
2		3591.667	46.13	-7.33	38.80	74.00	-35.20	peak			
3		4750.000	42.66	-2.45	40.21	74.00	-33.79	peak			

RESULT: PASS

RADIATED EMISSION ABOVE 1GHZ (1-10th Harmonics)-LOW CHANNEL –VERTICAL




Site: site #1 Polarization: **Vertical** Temperature: 26
Limit: RSS-GEN Class B 3M Radiation above 1GHZ(Pt6)wer: Humidity: 60 %
EUT:Classic Case with Bluetooth Keyboard for 7" Tablets
M/N:8020576
Mode: Low Channel TX
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		1350.000	53.23	-15.44	37.79	74.00	-36.21	peak			
2	*	2402.000	108.08	-9.68	98.40	74.00	24.40	peak			
3		3341.667	47.28	-8.04	39.24	74.00	-34.76	peak			

RESULT: PASS

RADIATED EMISSION ABOVE 1GHZ (1-10th Harmonics)-MIDDLE CHANNEL-HORIZONTAL



Site: site #1

Polarization: *Horizontal*

Temperature: 26

Limit: RSS-GEN Class B 3M Radiation above 1GHZ(PIayer:

Humidity: 60 %

EUT:Classic Case with Bluetooth Keyboard for 7" Tablets

M/N:8020576


Mode: Middle Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2441.000	107.87	-9.63	98.24	74.00	24.24	peak			
2		3683.333	47.65	-6.76	40.89	74.00	-33.11	peak			
3		5825.000	42.45	-1.66	40.79	74.00	-33.21	peak			

RESULT: PASS

RADIATED EMISSION ABOVE 1GHZ (1-10th Harmonics) - MIDDLE CHANNEL –VERTICAL



Site: site #1 Polarization: *Vertical* Temperature: 26

Limit: RSS-GEN Class B 3M Radiation above 1GHZ(PLower): Humidity: 60 %

EUT:Classic Case with Bluetooth Keyboard for 7" Tablets


M/N:8020576

Mode: Middle Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2441.000	107.80	-9.63	98.17	74.00	24.17	peak			
2		3741.667	44.04	-6.40	37.64	74.00	-36.36	peak			
3		5058.333	40.47	-1.80	38.67	74.00	-35.33	peak			

RESULT: PASS



Site: site #1 Polarization: **Horizontal** Temperature: 26

Limit: RSS-GEN Class B 3M Radiation above 1GHZ(PI over: Humidity: 60 %

EUT:Classic Case with Bluetooth Keyboard for 7" Tablets


M/N:8020576

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	108.17	-9.59	98.58	74.00	24.58	peak			
2		3700.000	44.41	-6.66	37.75	74.00	-36.25	peak			
3		5683.333	39.32	-1.73	37.59	74.00	-36.41	peak			

RESULT: PASS



Site: site #1 Polarization: **Vertical** Temperature: 26

Limit: RSS-GEN Class B 3M Radiation above 1GHZ(Power): Humidity: 60 %

EUT:Classic Case with Bluetooth Keyboard for 7" Tablets

M/N:8020576

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	107.88	-9.59	98.29	74.00	24.29	peak			
2		3566.667	44.69	-7.48	37.21	74.00	-36.79	peak			
3		5941.667	39.55	-1.61	37.94	74.00	-36.06	peak			

RESULT: PASS

Note: 6~25GHz at least have 20dB margin. No recording in the test report.

Factor=Antenna Factor+ Cable loss-Amplifier gain, Margin=Measurement-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

7. BAND EDGES EMISSION

7.1 MEASUREMENT PROCEDURE


- 1, Set the EUT Work on the top, the bottom operation frequency individually.
2. Set SPA Start or Stop Frequency = Operation Frequency, RBW \geq 1%span, VBW \geq RBW
3. The band edges was measured and recorded.

7.2 TEST SET-UP

The same as described in section 6.2

7.3 TEST RESULT

TEST PLOT OF BAND EDGE FOR LOW CHANNEL (3Mbps)



Site: site #1 Polarization: *Horizontal* Temperature: 26

Limit: RSS-GEN Class B 3M Radiation above 1GHZ(Power: Humidity: 60 %


EUT:Classic Case with Bluetooth Keyboard for 7" Tablets

M/N:8020576

Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2275.167	51.10	-9.82	41.28	74.00	-32.72	peak			
2		2390.000	51.94	-9.69	42.25	74.00	-31.75	peak			
3	*	2402.000	107.73	-9.68	98.05	74.00	24.05	peak			



Site: site #1 Polarization: **Vertical** Temperature: 26

Limit: RSS-GEN Class B 3M Radiation above 1GHZ(Power: Humidity: 60 %

EUT:Classic Case with Bluetooth Keyboard for 7" Tablets


M/N:8020576

Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2291.225	48.68	-9.80	38.88	74.00	-35.12	peak			
2		2390.000	51.65	-9.69	41.96	74.00	-32.04	peak			
3	*	2402.000	108.09	-9.68	98.41	74.00	24.41	peak			

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL (3Mbps)



Site: site #1 Polarization: *Horizontal* Temperature: 26

Limit: RSS-GEN Class B 3M Radiation above 1GHZ(Power: 60 %)


EUT:Classic Case with Bluetooth Keyboard for 7" Tablets

M/N:8020576

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	108.05	-9.59	98.46	74.00	24.46	peak			
2		2483.500	48.88	-9.59	39.29	74.00	-34.71	peak			
3		2496.993	50.01	-9.57	40.44	74.00	-33.56	peak			



Site: site #1 Polarization: *Vertical* Temperature: 26

Limit: RSS-GEN Class B 3M Radiation above 1GHZ(Power: 72 dBuV/m) Humidity: 60 %

EUT:Classic Case with Bluetooth Keyboard for 7" Tablets

M/N:8020576



Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	107.95	-9.59	98.36	74.00	24.36	peak			
2		2483.500	51.19	-9.59	41.60	74.00	-32.40	peak			
3		2495.563	52.15	-9.57	42.58	74.00	-31.42	peak			

APPENDIX A
PHOTOGRAPHS OF THE TEST SETUP

RADIATED EMISSION



APPENDIX B: PHOTOGRAPHS OF EUT
TOP VIEW OF EUT




BOTTOM VIEW OF EUT



FRONT VIEW OF EUT



BACK VIEW OF EUT



LEFT VIEW OF EUT




RIGHT VIEW OF EUT




OPEN VIEW OF EUT



INTERNAL VIEW OF EUT-1



INTERNAL VIEW OF EUT-2



INTERNAL VIEW OF EUT-3



----END OF REPORT----