SPECIFICATION

Shenzhen Guandetong Electronic Limited



Shenzhen Guandetong Electronic Co., Ltd.

2.4G/5.8G 5DB white antenna with SMA female

pinProduct Specification

connection	frequer rang	
Frequency band wire name	editio	on A1
Customer part number Guandeton g No	Guande part nur	
R F design	RF Man	ager
Structural design	Structi Manag	
Technical Director	Date	2024-3-4

Customer confirmation:		
Does the assembly meet your company's requirements:	□ок	\square NG

Confidentiality requirements of Shenzhen Guanditong Electronic Co., Ltd. . The company has proprietary technology to provide the information, which should be strictly confidential, it shall not be disclosed to any person or company without the prior written consent of Shenzhen Guanditong Electronic Co., Ltd. .

catalogue

(Cover 1
cat	ralogue2
1,	Product pictures
2,	Product parameters
3,	S11(VSWR、Return、Smith)
4、	Structural drawings
5、	Antenna gain and Apple plot
6、	Environmental performance test

Address: 3/F, Tower D, Huanguan Nanmaoyuan Industrial Park, Guanhu Street, Longhua District, Shenzhen. Tel: 0755-88298396 fax: 0755-89733896

http://www.szgdtrf.com

Confidentiality requirements of Shenzhen Guanditong Electronic Co., Ltd. . The company has proprietary technology to provide the information, which should be strictly confidential, it shall not be disclosed to any person or company without the prior written consent of Shenzhen Guanditong Electronic Co., Ltd. .

1. Product pictures



2. Product parameters

Product testing parameters									
Product name	2.4/5.8G 5DB antenna	(Model Type)	GDT-P2. 4-5. 8						
(Electrical Specifications)									
(Frenquency Range)	2400-2500MHz 5200-5800MHZ	(Polarization) nernendicul							
(Impedance)	50 ohm	Radiation							
(VSWR)	≤ 2.0	(Power)	50W						
(Gain)	0.04-5.4dBi	(Bandwidth	100M						
(Mechanical Specifications)									
(Dimensions)	195mm \pm 0.3mm	(Chassis Color)	white						
(Connector)	SMA plug	(Chassis Material)	ABS+TPE						
(Working Temperature)	-40 ℃ -+85 ℃	(Limit Temperature) -40° C							

Address: 3/F, Tower D, Huanguan Nanmaoyuan Industrial Park, Guanhu Street, Longhua District, Shenzhen. Tel: 0755-88298396 fax: 0755-89733896


http://www.szgdtrf.com

Confidentiality requirements of Shenzhen Guanditong Electronic Co., Ltd. . The company has proprietary technology to provide the information, which should be strictly confidential, it shall not be disclosed to any person or company without the prior written consent of Shenzhen Guanditong Electronic Co., Ltd. .

3, S11(VSWR, Return, Smith)



4. Structural drawings




Address: 3/F, Tower D, Huanguan Nanmaoyuan Industrial Park, Guanhu Street, Longhua District, Shenzhen. Tel: 0755-88298396 fax: 0755-89733896 http://www.szgdtrf.com

Confidentiality requirements of Shenzhen Guanditong Electronic Co., Ltd.. The company has proprietary technology to provide the information, which should be strictly confidential, it shall not be disclosed to any person or company without the prior written consent of Shenzhen Guanditong Electronic Co., Ltd..


5. Antenna gain and Apple plot

Test	Freq.	TRP	Gain	Directivit	Efficienc	Efficienc	Max	Theta of	Phi of	Min	Theta of	Phi of	AVG	Max/Min	Max/AVG	Min/AVG
Point ID	(MHz)	(dBm)	(dBi)	y (dBi)	y (%)	y (dB)	(dBm)	Max	Max	(dBm)	Min	Min	(dBm)	(dB)	(dB)	(dB)
1	2400.0	2400.00	1.67	5.87	38.0%	-4.20	1.67	9000	16680	-95.99	0	0	-5.04	97.66	6.70	-90.95
2	2410.0	2410.00	1.97	6.17	38.0%	-4.20	1.97	9000	16680	-95.99	Ō	0	-4.84	97.96	6.81	-91.15
3	2420.0	2420.00	2.35	6.47	38.8%	-4.11	2.35	9000	16680	-95.99	0	0	-4.52	98.34	6.87	-91.47
4	2430.0	2430.00	2.95	6.73	41.8%	-3.78	2.95	9000	16680	-95.99	0	0	-4.05	98.93	7.00	-91.94
5	2440.0	2440.00	2.81	6.71	40.8%	-3.90	2.81	9000	16680	-95.99	0	0	-4.25	98.80	7.06	-91.74
6	2450.0	2450.00	2.73	6.72	39.9%	-3.99	2.73	9000	16680	-95.99	0	0	-4.37	98.72	7.09	-91.62
Z	2460.0	2460.00	2.91	6.80	40.8%	-3.89	2.91	9000	6000	-95.99	0	0	-4.30	98.89	7.20	-91.69
8	2470.0	2470.00	3.01	6.78	42.0%	-3.77	3.01	9000	6000	-95.99	0	0	-4.40	99.00	7.41	-91.59
9	2480.0	2480.00	2.94	6.63	42.8%	-3.69	2.94	9000	6000	-95.99	0	0	-4.71	98.93	7.65	-91.28
10	2490.0	2490.00	3.05	6.76	42.5%	-3.71	3.05	9000	6000	-95.99	0	0	-4.81	99.04	7.85	-91.18
11	2500.0	2500.00	3.09	6.78	42.7%	-3.69	3.09	9000	6000	-95.99	0	0	-4.84	99.07	7.92	-91.15
12	5100.0	5100.00	0.23	7.41	19.1%	-7.19	0.23	7500	1500	-95.99	0	0	-7.35	96.22	7.57	-88.64
13	5120.0	5120.00	0.11	7.49	18.3%	-7.38	0.11	7500	1500	-95.99	0	0	-7.73	96.10	7.84	-88.26
14	5140.0	5140.00	1.10	7.36	23.7%	-6.26	1.10	7500	1500	-95.99	0	0	-6.56	97.09	7.66	-89.43
15	5160.0	5160.00	0.92	7.06	24.3%	-6.15	0.92	7500	1500	-95.99	0	0	-6.68	96.91	7.60	-89.31
16	5180.0	5180.00	0.96	6.88	25.6%	-5.92	0.96	7500	1500	-95.99	0	0	-6.55	96.95	7.51	-89.44
17	5200.0	5200.00	1.11	6.74	27.4%	-5.63	1.11	7500	1500	-95.99	0	0	-6.64	97.10	7.75	-89.35
18	5220.0	5220.00	0.04	6.24	24.0%	-6.20	0.04	7500	1500	-95.99	0	0	-7.38	96.03	7.41	-88.61
19	5240.0	5240.00	0.99	6.75	26.6%	-5.76	0.99	7500	1500	-95.99	0	0	-6.86	96.98	7.85	-89.13
20	5260.0	5260.00	1.10	7.11	25.1%	-6.01	1.10	7500	1500	-95.99	0	0	-6.78	97.08	7.87	-89.21
21	5280.0	5280.00	1.41	6.28	32.6%	-4.87	1.41	7500	1500	-95.99	0	0	-5.57	97.40	6.98	-90.42
22	5300.0	5300.00	2.17	6.36	38.1%	-4.20	2.17	10500	1500	-95.99	0	0	-4.85	98.16	7.02	-91.14
23	5320.0	5320.00	2.68	6.02	46.4%	-3.33	2.68	9000	10500	-95.99	0	0	-4.33	98.67	7.01	-91.66
24	5340.0	5340.00	2.55	5.69	48.5%	-3.15	2.55	9000	10500	-95.99	0	0	-4.04	98.54	6.58	-91.95
25	5360.0	5360.00	2.73	5.74	50.1%	-3.01	2.73	9000	10500	-95.99	0	0	-3.85	98.72	6.58	-92.14
26	5380.0	5380.00	2.44	5.68	47.4%	-3.24	2.44	7500	1500	-95.99	0	0	-3.88	98.43	6.32	-92.11
<u>27</u>	5400.0	5400.00	2.55	6.33	41.9%	-3.78	2.55	9000	10500	-95.99	0	0	-4.33	98.54	6.88	-91.65
28	5420.0	5420.00	2.66	6.59	40.4%	-3.93	2.66	4500	3000	-95.99	0	0	-4.16	98.65	6.82	-91.83
29	5440.0	5440.00	3.27	7.01	42.2%	-3.75	3.27	4500	3000	-95.99	0	0	-3.88	99.26	7.15	-92.11
30	5460.0	5460.00	3.67	7.51	41.3%	-3.84	3.67	4500	3000	-95.99	0	0	-3.90	99.66	7.57	-92.09
31	5480.0	5480.00	3.67	7.35	42.9%	-3.68	3.67	4500	3000	-95.99	0	0	-3.98	99.66	7.65	-92.01
32	5500.0	5500.00	4.80	7.55	53.0%	-2.76	4.80	4500	3000	-95.99	0	0	-3.13	100.78	7.93	-92.86
33	5520.0	5520.00	4.39	6.91	56.0%	-2.52	4.39	4500	3000	-95.99	0	0	-3.11	100.38	7.50	-92.88
34	5540.0	5540.00	3.87	7.10	47.6%	-3.22	3.87	4500	3000	-95.99	0	0	-3.96	99.86	7.83	-92.03
35	5560.0	5560.00	3.71	6.96	47.4%	-3.24	3.71	4500	3000	-95.99	0	0	-4.06	99.70	7.78	-91.93
<u>36</u>	5580.0	5580.00	3.58	6.71	48.6%	-3.13	3.58	4500	3000	-95.99	0	0	-3.85	99.57	7.43	-92.14
37.	5600.0	5600.00	3.88	6.93	49.6%	-3.05	3.88	4500	3000	-95.99	0	0	-3.98	99.87	7.86	-92.01
38	5620.0	5620.00	2.64	5.92	46.9%	-3.29	2.64	7500	1500	-95.99	0	0	-4.02	98.63	6.66	-91.97
<u>39</u>	5640.0	5640.00	3.87	6.73	51.7%	-2.87	3.87	7500	1500	-95.99	0	0	-3.59	99.86	7.46	-92.40
40	5660.0	5660.00	3.83	6.36	55.8%	-2.54	3.83	6000	1500	-95.99	0	0	-3.39	99.82	7.22	-92.60
41	5680.0	5680.00	4.67	6.57	64.5%	-1.90	4.67	12000	7500	-95.99	0	0	-3.00	100.66	7.67	-92.99
42	5700.0	5700.00	5.40	7.57	60.6%	-2.17	5.40	12000	6000	-95.99	0	0	-3.06	101.39	8.45	-92.93
43	5720.0	5720.00	4.89	7.02	61.2%	-2.13	4.89	12000	6000	-95.99	0	0	-2.86	100.88	7.75	-93.13
44	5740.0	5740.00	4.26	6.63	57.9%	-2.37	4.26	12000	1500	-95.99	0	0	-3.24	100.25	7.49	-92.75
45	5760.0	5760.00	3.86	6.41	55.6%	-2.55	3.86	12000	6000	-95.99	0	0	-3.38	99.85	7.24	-92.61
<u>46</u>	5780.0	5780.00	3.30	5.96	54.1%	-2.67	3.30	9000	7500	-95.99	0	0	-3.55	99.29	6.85	-92.44
47	5800.0	5800.00	2.80	6.09	46.9%	-3.29	2.80	12000	1500	-95.99	0	0	-4.49	98.79	7.29	-91.50



Address: 3/F, Tower D, Huanguan Nanmaoyuan Industrial Park, Guanhu Street, Longhua District, Shenzhen. Tel: 0755-88298396 fax: 0755-89733896 http://www.szgdtrf.com

Confidentiality requirements of Shenzhen Guanditong Electronic Co., Ltd.. The company has proprietary technology to provide the information, which should be strictly confidential, it shall not be disclosed to any person or company without the prior written consent of Shenzhen Guanditong Electronic Co., Ltd..



6. Environmental performance test

project	Project test conditions	Specifications			
Storage environment	The test temperature, humidity and air pressure are as follows when there is no specific condition: 1. The temperature is - 30 °C^+80 °C 2. Relative humidity: 45% - 85% 3. The air pressure is 86kpa-106kpa	Normal electrical and mechanical performance			
High and low temperature test	,				
Constant damp heat resistance test	Relative humidity: 95 \pm 3%, test temperature: 40 °C. After lasting for 2h, The electrical performance shall be measured within 5 minutes after the test object is taken out, and the test object shall be within the normal range Part 1-2H, check the appearance quality	The size shall meet the requirements and Mechanical and electrical performance			
vibration test	Vibration frequency range: 10-55HZ, displacement amplitude: 0.35MM, acceleration amplitude: 50.0M/s, frequency sweep cycles: 30 times				
Drop test	Drop test Free fall for 3 times in the direction of mutually perpendicular axes at a height of 1M				

Address: 3/F, Tower D, Huanguan Nanmaoyuan Industrial Park, Guanhu Street, Longhua District, Shenzhen. Tel: 0755-88298396 fax: 0755-89733896 http://www.szgdtrf.com