

TEST REPORT

Product Name : IP66 Waterproof Wireless IP Camera
Model Number : FI9925W, FI9935W, FI9945W, FI9925W Pro
FCC ID : ZDEFI9925W

Prepared for : ShenZhen Foscam Intelligent Technology Co., Ltd.
Address : Room 902, Unit B, Building 7, Xingke 1st Street, Vanke
Cloud City Phase 1, Nanshan Dist., Shenzhen, China.

Prepared by : EMTEK (DONGGUAN) CO., LTD.
Address : -1&2/F., Building 2, Zone A, Zhongda Marine Biotechnology
Research and Development Base, No.9, Xincheng Avenue,
Songshanhu High-technology Industrial Development Zone,
Dongguan, Guangdong, China

TEL: +86-0769-22807078
FAX: +86-0769-22807079

Report Number : EDG2502240114E00702R
Date(s) of Tests : February 13, 2025 to March 21, 2025
Date of issue : March 21, 2025

Table of Contents

1. TEST RESULT CERTIFICATION	3
2. EUT SPECIFICATION	5
3. TEST REQUIREMENT:	6
RF EXPOSURE EVALUATION	6
4. MEASUREMENT RESULT	7



1. TEST RESULT CERTIFICATION

Applicant : ShenZhen Foscam Intelligent Technology Co., Ltd.

Address : Room 902, Unit B, Building 7, Xingke 1st Street, Vanke Cloud City Phase 1, Nanshan Dist., Shenzhen, China.

Manufacturer : ShenZhen Foscam Intelligent Technology Co., Ltd.

Address : Room 902, Unit B, Building 7, Xingke 1st Street, Vanke Cloud City Phase 1, Nanshan Dist., Shenzhen, China.

Factory : ShenZhen Foscam Intelligent Technology Co., Ltd.

Address : 701, 7th Floor, Building D, Guangming Port Intelligent Manufacturing Innovation Park, No. 8 Jinjun Road, Huangjiang Town, Dongguan, Guangdong, China, 523769

EUT : IP66 Waterproof Wireless IP Camera

Model Name : FI9925W, FI9935W, FI9945W, FI9925W Pro

Trademark : FOSCAM

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
§ 15.247(i), § 2.1093	PASS


The above equipment was tested by EMTEK(DONGGUAN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules FCC § 15.247(i), § 2.1093.

The test results of this report relate only to the tested sample identified in this report

Date of Test : February 13, 2025 to March 21, 2025

Prepared by : 

Warren Deng /Editor

Reviewer : 

Tim Dong /Supervisor

Approve & Authorized Signer : 

Sam Lv / Manager

Modified History

Version	Report No.	Revision Date	Summary
	EDG2502240114E00702R	/	Original Report



2. EUT Specification

Characteristics	Description
Product:	IP66 Waterproof Wireless IP Camera
Model Number:	FI9925W, FI9935W, FI9945W, FI9925W Pro (The Model: FI9925W is the same as the Model: FI9910W Pro and FI9925W Pro in hardware aspect. The difference in model number serves as marketing strategy.)
Sample:	1#
Data Rate:	DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM/256QAM/1024QAM for 802.11ax;
Modulation:	DSSS, OFDM
Operating Frequency Range(s) :	2412-2462MHz for 802.11b/g/n(HT20)/ax(HE20);
Transmit Power Max:	16.55 dBm(0.045186 W)
Antenna Gain:	3.09 dBi
Power supply:	DC 12V 1A from Adapter
Evaluation applied:	☒ MPE Evaluation ☐ SAR Evaluation

3. Test Requirement:

RF EXPOSURE EVALUATION

According to §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,²⁴ where

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation²⁵
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval. One antenna is available for the EUT. The minimum separation distance is 5mm.

4. Measurement Result

gain:	3.09 dBi	WIFI 2.4G FCC EMF							
Mode	Frequen cy (MHz)	Output Power (dBm)	E.I.R.P(d Bm)	Target Power W/toleran ce (dBm)	Max tune up power(dB m) tolerance	Max tuneup power(m W) tolerance	Power Density at R=20cm (mW/cm2)	Limit (mW /cm2)	Verdi ct
802.11b	2412	16.55	19.64	19±1	20	100.00	0.040526	1	PAS S
	2437	16.54	19.63	19±1	20	100.00	0.040526	1	PAS S
	2462	16.02	19.11	19±1	20	100.00	0.040526	1	PAS S
802.11g	2412	14.86	17.95	17±1	18	63.10	0.025570	1	PAS S
	2437	14.92	18.01	18±1	19	79.43	0.032191	1	PAS S
	2462	14.46	17.55	17±1	18	63.10	0.025570	1	PAS S
802.11n(HT2 0)	2412	13.16	16.25	16±1	17	50.12	0.020311	1	PAS S
	2437	13.36	16.45	16±1	17	50.12	0.020311	1	PAS S
	2462	11.96	15.05	15±1	16	39.81	0.016134	1	PAS S
802.11ax(HE 20)	2412	13.81	16.9	16±1	17	50.12	0.020311	1	PAS S
	2437	13.55	16.64	16±1	17	50.12	0.020311	1	PAS S
	2462	11.96	15.05	15±1	16	39.81	0.016134	1	PAS S

According to KDB 447498, no stand-alone required for WIFI antenna, and no simultaneous SAR measurement is required.

*** End of Report ***