

No. 1 Workshop, M-10, Middle section, Science & Technology

Park, Shenzhen, Guangdong, China 518057 Telephone: +86 (0) 755 2601 2053

Fax: +86 (0) 755 2671 0594

Email: sgs\_internet\_operations@sgs.com

Report No.: SZEMO11040144801

Page : 1 of 14

# 1 Cover Page

# FCC REPORT

Application No.: SZEMO110401448RF

**Applicant:** Fujian Amison Photoelectricity CO. LTD.

Product Name: Toy-R/C Monster V-Blk Wheel

**Model Name:** 1641331

**Operation Frequency:** 27.145MHz

FCC ID: ZDP27T1101

Standards: FCC PART 15, SUBPART-C Section 15.227: 2009

**Date of Receipt** 2011-04-01

**Date of Test** 2011-04-06 to 2011-04-07

**Date of Issue** 2011-04-13

Test Result : PASS \*

Authorized Signature:

Jack Zhang

**EMC Laboratory Manager** 

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

<sup>\*</sup> In the configuration tested, the EUT complied with the standards specified above..



Report No.: SZEMO11040144801

Page : 2 of 14

## 2 Contents

			Page
1	C	COVER PAGE	1
2	C	CONTENTS	2
3	Т	EST SUMMARY	3
4	C	GENERAL INFORMATION	4
	4.1	CLIENT INFORMATION	4
	4.2	GENERAL DESCRIPTION OF E.U.T.	4
	4.3	E.U.T. ENVIRONMENT AND TEST MODES	
	4.4	TEST LOCATION	
	4.5	OTHER INFORMATION REQUESTED BY THE CUSTOMER	5
	4.6	TEST FACILITY	5
	4.7	TEST INSTRUMENTS LIST	
5	T	EST RESULT & MEASUREMENT DATA	7
	5.1	ANTENNA REQUIRMENT	7
	5.2	RADIATED EMISSIONS	7
	5.3	OCCUPIED BANDWIDTH	10
6	F	PHOTOGRAPHS - TEST SETUP (TEST MODEL NO.: 1641331)	11
7	F	PHOTOGRAPHS - EUT CONSTRUCTION DETAILS (TEST MODEL NO.: 1641331)	)12-14



Report No.: SZEMO11040144801

Page : 3 of 14

# 3 Test Summary

Test Item	Section in CFR 47	Result	
Radiated Emission	Section 15.227	Pass	
Occupied Bandwidth	Section 15.215	Pass	

Remark: Pass: The EUT complies with the essential requirements in the standard.

Fail: The EUT does not comply with the essential requirements in the standard.



Report No.: SZEMO11040144801

Page : 4 of 14

## 4 General Information

#### 4.1 Client Information

Applicant:	Fujian Amison Photoelectricity CO. LTD.
Address of Applicant:	Kada Industrial Zone Development Zone Zhaoan County Zhang zhou City Fujian Province P.R. China

## 4.2 General Description of E.U.T.

Product Name:	Toy-R/C Monster V-Blk Wheel
Trade Name:	N/A
Model No.:	1641331
Request Age Grading:	6+
Operation Frequency:	27.145MHz
Product Type;	Remote control toy
Power supply:	9.0V DC (1*9.0V" 6F22"Size Battery)

## 4.3 E.U.T. Environment and test modes

Operating Environment:	
Temperature:	25.0 °C
Humidity:	50 % RH
Atmospheric Pressure:	1010 mbar
Test mode:	
Tx mode:	Keep the EUT in transmitting mode

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEMO11040144801

Page : 5 of 14

#### 4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch E&E Lab

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

## 4.5 Other Information Requested by the Customer

None.

## 4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations

#### CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

#### VCCI

The 3m Semi-anechoic chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2197 and C-2383 respectively.

Date of Registration: September 29, 2008. Valid until September 28, 2011.

#### FCC – Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 556682, June 27, 2008.

#### Industry Canada (IC)

The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1.



Report No.: SZEMO11040144801

Page : 6 of 14

## 4.7 Test Instruments List

RE i	RE in Chamber									
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)				
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	2010-06-17	2011-06-17				
2	EMI Test Receiver	Rohde & Schwarz	ESIB26	SEL0023	2010-11-05	2011-11-05				
3	EMI Test software	AUDIX	E3	SEL0050	N/A	N/A				
4	Coaxial cable	SGS	N/A	SEL0028	2008-06-18	2011-06-18				
5	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0015	2010-11-09	2011-11-09				
6	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEL0006	2010-11-09	2011-11-09				
7	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEL0053	2010-06-02	2011-06-02				

RE LOOP						
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date	Cal.Due date
	<b>=</b> qa.po				(yyyy-mm-dd)	(YYYY-MM-DD)
EMC0701	Loop Antenna	Laplace Instruments	RF300	N/A	2010-05-10	2011-05-10
EMC0702	Calibration Dipole for EN55015 RE	SGS-CSTC	N/A	N/A		
EMC0409	Software	Rohde & Schwarz	ESK1	N/A	N/A	N/A
EMC0506	EMI Test Receiver	Rohde & Schwarz	ESCS30	100085	2010-11-23	2011-11-23



Report No.: SZEMO11040144801

Page : 7 of 14

## 5 Test Result & Measurement Data

## 5.1 Antenna requirment

**Standard requirement:** FCC Part15 C Section 15.203

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

## 5.2 Radiated Emissions

OIL Hadiatod Ellifotiono					
Test Requirement:	FCC Part15 C Section 15.227				
Test Method:	ANSI C63.10: 2009				
Measurement Distance:	3m (Semi-Anechoic Chamber)				
Requirements:	Carrier Power below 80dBuV/m at 3m (Average).				
	Out of band emissions shall not exceed:				
	40.0 dBμV/m between 30MHz & 88MHz				
	43.5 dBμV/m between 88MHz & 216MHz				
	46.0 dBμV/m between 216MHz & 960MHz				
	54.0 dBμV/m between 960MHz & 1000MHz				
Detector:	QP: for frequency range: 25MHz to 30MHz (RBW=9kHz, VBW=30KHz QP: for frequency range:30MHz to 1000MHz (RBW=120kHz, VBW=300kHz)				
	Peak: for frequency range above 1000MHz (RBW=1MHz, VBW=3MHz)				
Test Procedure:	The equipment under test (EUT) was placed at the middle of the 80 cm height turntable, and the turntable is 3 meters far from the measuring antenna. During the testing, the EUT was operated standalone and arranged for maximum emissions. The EUT was tested in three orthogonal planes.  The measurement was performed with the EUT rotated 360 °, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained.				
Test Result:	The EUT complies with FCC Part 15-C Section 15.227 requirements.				

#### 27.145MHz Mode

Test Procedure: For testing performed with the loop antenna, testing was performed in accordance to ANSI C63.10: 2009, section 8.2.1. The center of the loop was positioned 1 m above the ground and positioned with its plane vertical at the specified distance from the EUT. During testing the loop was rotated about its vertical axis for maximum response at each azimuth and also investigated with the loop positioned in the horizontal plane.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEMO11040144801

Page : 8 of 14


## **Fundamental Signal Emission:**

Test Frequency	Peak (d	dΒμV/m)	Limit	Margin (dB)	
(MHz)	Vertical	Horizontal	(dBµV/m)	Vertical	Horizontal
27.145	59.74	50.14	100.00	40.26	49.86

Test Frequency	Average	(dBµV/m)	Limit	Marg	in (dB)
(MHz)	Vertical	Horizontal	(dBµV/m)	Vertical	Horizontal
27.145	57.56	47.63	80.00	22.44	32.37

## **Spurious Emission Test (QP):**

#### **Vertical Antenna Polarisation:**



Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)
54.047	0.80	7.66	27.28	41.78	22.96	40.00	-17.04
81.096	1.10	7.82	27.23	40.68	22.37	40.00	-17.63
244.350	1.65	12.13	26.55	41.11	28.34	46.00	-17.66
324.617	1.98	14.80	26.60	42.56	32.74	46.00	-13.26
462.562	2.46	17.35	27.52	39.71	32.00	46.00	-14.00


"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEMO11040144801

Page : 9 of 14

#### **Horizontal Antenna Polarisation:**



Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)
81.096	1.100	7.820	27.230	38.300	19.990	40.000	-20.010
108.533	1.230	8.680	27.140	31.590	14.360	43.500	-29.140
244.350	1.650	12.130	26.550	36.260	23.490	46.000	-22.510
270.939	1.770	12.720	26.470	35.230	23.250	46.000	-22.750
297.113	1.890	13.760	26.410	44.050	33.290	46.000	-12.710

#### Remark:

According to 15.35 (b) When average radiated emission measurements are specified in the regulations, including emission measurements below 1000 MHz, there is also a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules, e.g., see Section 15.255.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/terms.e-document.htm">www.sgs.com/terms.e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




Report No.: SZEMO11040144801

Page : 10 of 14

5.3 Occupied Bandwidth	
Test Requirement:	FCC Part 15 C Section 15.215 (C)
Test Method:	ANSI C63.10: 2009
Frequency range:	Operation within the band 26.960 – 27.280 MHz
Requirements:	Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the 20 dB bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.
Method of measurement:	The useful radiated emission from the EUT was detected by the spectrum analyser with peak detector. The vertical Scale is set to 10dB per division. The horizontal scale is set to 34KHz per division.
Test Result:	The unit does meet the FCC Part 15 C Section 15.215 requirements.

The graph as below: represents the emissions take for this device.



"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."