### FCC 47 CFR PART 15 SUBPART C

### **TEST REPORT**

For

**Time Lapse Camera TLC120** 

Model: TLC120A

**Trade Name: brinno** 

Issued to

Brinno Incorporated 4F, No.107, Zhouzi St., Taipei City, 11493, Taiwan, (R.O.C.)

Issued by

Compliance Certification Services Inc. No.11, Wugong 6th Rd., Wugu Dist., New Taipei City 24891, Taiwan. (R.O.C.) http://www.ccsrf.com service@ccsrf.com

Issued Date: March 15, 2016





**Note**: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document.

# **Revision History**

	Issue		Effect	
Rev.	Date	Revisions	Page	Revised By
00	March 15, 2016	Initial Issue	ALL	Doris Chu

Page 2 Rev. 00

# **TABLE OF CONTENTS**

1. TE	ST RESULT CERTIFICATION	4
2. El	JT DESCRIPTION	5
3. TE	EST METHODOLOGY	б
3.1 3.2 3.3	EUT CONFIGURATIONEUT EXERCISE	6 6 7
4 IN	STRUMENT CALIBRATION	g
4.1 4.2 4.3	MEASURING INSTRUMENT CALIBRATION	9
5 F	ACILITIES AND ACCREDITATIONS	11
	FACILITIES EQUIPMENT TABLE OF ACCREDITATIONS AND LISTINGS	11
6 SI	ETUP OF EQUIPMENT UNDER TEST	13
6.1 6.2	SETUP CONFIGURATION OF EUTSUPPORT EQUIPMENT	
7 FC	CC PART 15.247 REQUIREMENTS	14
7.1 7.2 7.3 7.4 7.5 7.6 7.7	PEAK POWER	17 18 19 29
APPE	NDIX I PHOTOGRAPHS OF TEST SETUP	48
ΔPPF	NDIX 1 - PHOTOGRAPHS OF FUT	

# 1. TEST RESULT CERTIFICATION

**Applicant:** Brinno Incorporated

4F, No.107, Zhouzi St., Taipei City, 11493, Taiwan, (R.O.C.)

Reference No.: T150529W04-RP2

Report No.: T160118W01-RP2

**Equipment Under Test:** Time Lapse Camera TLC120

Trade Name: brinno TLC120A

**Date of Test:** January 19 ~ February 26, 2016

APPLICABLE STANDARDS			
STANDARD TEST RESULT			
FCC 47 CFR Part 15 Subpart C	No non-compliance noted		

# We hereby certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10: 2013 and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.203, 15.207, 15.209, 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.

Approved by: Reviewed by:

Miller Lee Manager

Compliance Certification Services Inc.

Willer Loe

Angel Cheng Section Manager

Compliance Certification Services Inc.

Thosel Charl

Page 4 Rev. 00

Reference No.: T150529W04-RP2 FCC ID: ZDX-TLC120A Report No.: T160118W01-RP2

# 2. EUT DESCRIPTION

Product	Time Lapse Camera TLC120
Trade Name	brinno
Model Number	TLC120A
Received Date	January 18, 2016
Power Supply	DC 3.7V powered from Host device.
Frequency Range	2402MHz ~ 2480MHz
Transmit Power	-1.58 dBm
Modulation Technique	GFSK (1Mbps)
Number of Channels	40 Channels
Antenna Specification	CIRO / PCAK0000-12 Gain: 1.0 dBi
Antenna Designation	Print Chip Antenna

# Remark:

- 1. The sample selected for test was production product and was provided by manufacturer.
- 2. This submittal(s) (test report) is intended for FCC ID: **ZDX-TLC120A** filing to comply with Section 15.203, 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.

Page 5 Rev. 00

### 3. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10: 2013 and FCC CFR 47 Part 15.203, 15.207, 15.209, 15.247, KDB 558074 D01 DTS Meas Guidance v03r04.

Reference No.: T150529W04-RP2

Report No.: T160118W01-RP2

### 3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

### 3.2 EUT EXERCISE

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.203, 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

### 3.3 GENERAL TEST PROCEDURES

#### **Conducted Emissions**

According to the requirements in ANSI C63.10: 2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

### **Radiated Emissions**

The EUT is placed on a turn table, which is 1.5 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in ANSI C63.10: 2013.

Page 6 Rev. 00

## 3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

Reference No.: T150529W04-RP2

Report No.: T160118W01-RP2

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	( <sup>2</sup> )
13.36 - 13.41	322 - 335.4		

<sup>&</sup>lt;sup>1</sup> Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

Page 7 Rev. 00

<sup>&</sup>lt;sup>2</sup> Above 38.6

<sup>(</sup>b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

Reference No.: T150529W04-RP2

Report No.: T160118W01-RP2

### 3.5 DESCRIPTION OF TEST MODES

The EUT (model: TLC120A) had been tested under operating condition.

Software used to control the EUT for staying in continuous transmitting mode was programmed.

After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz and power line conducted emissions below 30MHz, which worst case was in normal link mode only.

### **BT 4.0**

Tested Channel	Frequency (MHz)
Low	2402
Mid	2440
High	2480

The field strength of spurious emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in lie-down position (X axis) and the worst case was recorded.

Page 8 Rev. 00

# **4 INSTRUMENT CALIBRATION**

### 4.1 MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

### **4.2 MEASUREMENT EQUIPMENT USED**

### **Equipment Used for Emissions Measurement**

Remark: Each piece of equipment is scheduled for calibration once a year.

Conducted Emissions Test Site							
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due			
Spectrum Analyzer	Agilent	E4446A	US42510252	12/07/2016			
Thermostatic/Humidity Chamber	TAICHY	MHG-150LF	930619	10/07/2016			
AC Power Source	EXTECH	6205	1140845	N.C.R			
DC Power Supply	ABM	8301HD	D011531	N.C.R			
Power Meter	Anritsu	ML2495A	1012009	07/07/2016			
Power Sensor	Anritsu	MA2411A	0917072	07/07/2016			
Spectrum Analyzer	ROHDE&SCHWAR	Z FSV40	101073	07/19/2016			
		u 966 Chamber A					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due			
Spectrum Analyzer	Agilent	E4446A	US42510268	02/14/2017			
EMI Test Receiver	R&S	ESCI	100064	06/03/2016			
Bilog Antenna	Sunol Sciences	JB3	A030105	08/05/2016			
Horn Antenna	EMCO	3117	00055165	02/23/2017			
Horn Antenna	EMCO	3116	26370	01/14/2017			
Turn Table	CCS	CC-T-1F	N/A	N.C.R			
Antenna Tower	CCS	CC-A-1F	N/A	N.C.R			
Controller	CCS	CC-C-1F	N/A	N.C.R			
Pre-Amplifier	MITEQ	1652-3000	1490939	08/09/2016			
Pre-Amplifier	EMC	EMC 012635	980151	06/04/2016			
Pre-Amplifier	MITEQ	AMF-6F-260400- 40-8P	985646	01/13/2017			
Coaxial Cable	Huber+Suhner	102	29212/2	01/11/2017			
Coaxial Cable	Huber+Suhner	102	29406/2	01/11/2017			
Test S/W		EZ-EMC (	CCS-3A1RE)				

Page 9 Rev. 00

Conducted Emission room # B							
Name of Equipment Manufacturer Model Serial Number Calibratio							
EMI Test Receiver	R&S	ESCI	101073	09/08/2016			
LISN	R&S	ENV216	101054	06/06/2016			
LISN	SCHWARZBECK	NSLK 8127	8127-541	11/22/2016			
Capacitive Voltage Probe	FCC	F-CVP-1	100185	03/12/2016			
Test S/W	CCS-3A1-CE						

Reference No.: T150529W04-RP2

Report No.: T160118W01-RP2

# **4.3 MEASUREMENT UNCERTAINTY**

PARAMETER	UNCERTAINTY
Powerline Conducted Emission	+/- 1.2575
3M Semi Anechoic Chamber / <200M	+/- 4.0138
3M Semi Anechoic Chamber / 200M~1000M	+/- 3.9483
3M Semi Anechoic Chamber / 1G~8G	+/- 2.5975
3M Semi Anechoic Chamber / 8G~18G	+/- 2.6112
3M Semi Anechoic Chamber / 18G~26G	+/- 2.7389
3M Semi Anechoic Chamber / 26G~40G	+/- 2.9683

**Remark**: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Page 10 Rev. 00

# 5 FACILITIES AND ACCREDITATIONS 5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at
 No.139, Wugong Rd., Wugu Dist., New Taipei City 24891, Taiwan (R.O.C.)
 Tel: 886-2-2298-4086 / Fax: 886-2-2298-1470
 No.11, Wugong 6th Rd., Wugu Dist., New Taipei City 24891, Taiwan. (R.O.C.)
 Tel: 886-2-2299-9720 / Fax: 886-2-2298-4045
 No.81-1, Lane 210, Bade 2nd Rd., Lujhu Township, Taoyuan County 33841, TAIWAN, R.O.C.
 Tel: 886-3-324-0332 / Fax: 886-3-324-5235

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10: 2013 and CISPR Publication 22.

### **5.2 EQUIPMENT**

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, ridged waveguide, horn and/or Loop. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

Page 11 Rev. 00

Reference No.: T150529W04-RP2

Report No.: T160118W01-RP2

# 5.3 TABLE OF ACCREDITATIONS AND LISTINGS

Country	Agency	Scope of Accreditation	Logo
USA	FCC	3M Semi Anechoic Chamber (FCC MRA: TW1039) to perform FCC Part 15 measurements	FCC MRA: TW1039
Taiwan	TAF	LP0002, RTTE01, FCC Method-47 CFR Part 15 Subpart C, D, E, RSS-210, RSS-310 IDA TS SRD, AS/NZS 4268, AS/NZS 4771, TS 12.1 & 12,2, ETSI EN 300 440-1, ETSI EN 300 440-2, ETSI EN 300 328, ETSI EN 300 220-1, ETSI EN 300 220-2, ETSI EN 301 893, ETSI EN 301 489-1/3/7/17 FCC OET Bulletin 65 + Supplement C, EN 50360, EN 50361, EN 50371, RSS 102, EN 50383, EN 50385, EN 50392, IEC 62209, CNS 14958-1, CNS 14959 FCC Method -47 CFR Part 15 Subpart B IEC / EN 61000-3-2, IEC / EN 61000-3-3, IEC / EN 61000-4-2/3/4/5/6/8/11	Testing Laboratory 1309
Canada	Industry Canada	3M Semi Anechoic Chamber (IC 2324G-1 / IC 2324G-2) to perform	<b>Canada</b> IC 2324G-1 IC 2324G-2

<sup>\*</sup> No part of this report may be used to claim or imply product endorsement by A2LA or any agency of the US Government.

Page 12 Rev. 00

# **6 SETUP OF EQUIPMENT UNDER TEST**

### **6.1 SETUP CONFIGURATION OF EUT**

See test photographs attached in Appendix II for the actual connections between EUT and support equipment.

Reference No.: T150529W04-RP2

Report No.: T160118W01-RP2

### **6.2 SUPPORT EQUIPMENT**

No	Device Type	Brand	Model	Series No.	FCC ID	Data Cable	Power Cord
1	Notebook PC	TOSHIBA	Satellite M840	N/A	PPD-AR5B225	N/a	AC I/P: Unshielded, 1.8m DC O/P: Unshielded, 1.8m with a core

#### Remark:

- 1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

Page 13 Rev. 00

**7 FCC PART 15.247 REQUIREMENTS** 

### 7.1 6DB BANDWIDTH


### LIMIT

According to §15.247(a)(2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Reference No.: T150529W04-RP2

Report No.: T160118W01-RP2

### **Test Configuration**



### **TEST PROCEDURE**

The transmitter output is connected to the spectrum analyzer. Set the RBW = 1%-5% of the emission bandwidth, VBW  $\geq$  3 x RBW, Detector = Peak, Trace mode = max hold, Sweep = auto couple. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

### **TEST RESULTS**

No non-compliance noted


#### **Test Data**

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (kHz)	Test Result
Low	2402	0.8493		PASS
Mid	2440	0.8814	>500	PASS
High	2480	0.8573		PASS

Page 14 Rev. 00


### **Test Plot**

### 6dB Bandwidth (CH Low)



Date: 21.JAN.2016 10:24:49


### 6dB Bandwidth (CH Mid)



Date: 21.JAN.2016 10:28:14

Page 15 Rev. 00

# 6dB Bandwidth (CH High)



Date: 21.JAN.2016 10:29:49

Page 16 Rev. 00

FCC ID: ZDX-TLC120A Report No.: T160118W01-RP2

Reference No.: T150529W04-RP2


### **7.2 PEAK POWER**

### LIMIT

The maximum peak output power of the intentional radiator shall not exceed the following:

- 1. According to §15.247(b)(3), for systems using digital modulation in the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz: 1 Watt.
- 2. According to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### **Test Configuration**



### **TEST PROCEDURE**

The transmitter output is connected to the Power Meter. The Power Meter is set to the peak power detection.

### **TEST RESULTS**

No non-compliance noted

### **Test Data**

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Limit (W)	Test Result
Low	2402	*-1.58	0.0007		PASS
Mid	2440	-2.65	0.0005	1	PASS
High	2480	-3.68	0.0004		PASS

Page 17 Rev. 00


Reference No.: T150529W04-RP2 FCC ID: ZDX-TLC120A Report No.: T160118W01-RP2

# 7.3 AVERAGE POWER

# LIMIT

None; for reporting purposes only.

# **Test Configuration**



# **TEST PROCEDURE**

The transmitter output is connected to the Power Meter. The Power Meter is set to the average power detection.

# **TEST RESULTS**

No non-compliance noted.

# **Test Data**

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)
Low	2402	-2.12	0.0006
Mid	2440	-3.25	0.0005
High	2480	-4.31	0.0004

Page 18 Rev. 00 FCC ID: ZDX-TLC120A Report No.: T160118W01-RP2

Reference No.: T150529W04-RP2


### 7.4 BAND EDGES MEASUREMENT

### LIMIT


According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

### **Test Configuration**

#### For Radiated Emission above 1GHz



### **For Conducted**



Page 19 Rev. 00

### **TEST PROCEDURE**

#### For Radiated

- 1. The EUT is placed on a turntable, which is 1.5m above the ground plane.
- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.

Reference No.: T150529W04-RP2

Report No.: T160118W01-RP2

- 3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
- 4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
  - (a) PEAK: RBW=1MHz / VBW=3MHz / Sweep=AUTO
  - (b) AVERAGE: RBW=1MHz,

if duty cycle ≥ 98%, VBW=10Hz.

if duty cycle<98% VBW=1/T.

**BT4.0:** ≥98%, VBW=10Hz

- 5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.
- 6. Result = Spectrum Reading + cable loss(spectrum to Amp) Amp Gain + Cable loss(Amp to receive Ant) + Receive Ant

#### For Conducted

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 100 kHz.


### **TEST RESULTS**

Refer to attach spectrum analyzer data chart.

Page 20 Rev. 00

# **Band Edges (CH Low)**


# **Detector mode: Peak**



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2383.032	60.82	-2.55	58.27	74.00	-15.73	peak
2	2402.310	101.13	-2.41	98.72	74.00	24.72	peak

Page 21 Rev. 00

**Detector mode: Average** 




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2390.000	39.70	-2.49	37.21	54.00	-16.79	AVG
2	2402.106	100.32	-2.41	97.91	54.00	43.91	AVG

Page 22 Rev. 00

# **Band Edges (CH Mid)**


# **Detector mode: Peak**



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2376.500	53.51	-2.60	50.91	74.00	-23.09	peak
2	2439.960	101.86	-2.21	99.65	74.00	25.65	peak
3	2492.590	53.52	-1.91	51.61	74.00	-22.39	peak

Page 23 Rev. 00

**Detector mode: Average** 




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2390.000	39.38	-2.49	36.89	54.00	-17.11	AVG
2	2440.150	101.81	-2.21	99.60	54.00	45.60	AVG
3	2483.500	39.41	-1.99	37.42	54.00	-16.58	AVG

Page 24 Rev. 00

# **Band Edges (CH High)**


# **Detector mode: Peak**



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2479.676	100.96	-2.03	98.93	74.00	24.93	peak
2	2502.308	62.57	-1.85	60.72	74.00	-13.28	peak

Page 25 Rev. 00


**Detector mode: Average** 



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2480.086	100.85	-2.03	98.82	54.00	44.82	AVG
2	2483.500	41.24	-1.99	39.25	54.00	-14.75	AVG

Page 26 Rev. 00


**Conducted Band Edges (CH Low)** 



No.	Frequency	Reading	Correct	Result	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	
1	2399.964	58.77	-2.41	56.36	peak
2	2402.004	101.07	-2.41	98.66	peak

Page 27 Rev. 00

**Conducted Band Edges (CH High)** 



No.	Frequency	Reading	Correct	Result	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	
1	2480.004	100.86	-2.03	98.83	peak
2	2502.226	55.43	-1.85	53.58	peak

Page 28 Rev. 00

### 7.5 PEAK POWER SPECTRAL DENSITY

### LIMIT


1. According to §15.247(e), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

Reference No.: T150529W04-RP2

Report No.: T160118W01-RP2

2. According to §15.247(f), the digital modulation operation of the hybrid system, with the frequency hopping turned off, shall comply with the power density requirements of paragraph (d) of this section.

### **Test Configuration**



### **TEST PROCEDURE**

The transmitter output is connected to a spectrum analyzer. Set the RBW = 3 kHz, VBW = 30 kHz, span to 1.5 times the DTS bandwidth, Detector = peak, Trace mode = max hold, Sweep = auto couple. Use the peak marker function to determine the maximum amplitude level within the RBW.

# **TEST RESULTS**

No non-compliance noted


### **Test Data**

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Result
Low	2402	-11.95		PASS
Mid	2440	-11.61	8.00	PASS
High	2480	-11.15		PASS

Page 29 Rev. 00


### **Test Plot**

# PPSD (CH Low)



Date: 1.DEC.2015 18:52:17


# PPSD (CH Mid)



Date: 1.DEC.2015 18:54:21

Page 30 Rev. 00

# PPSD (CH High)



Date: 1.DEC.2015 18:57:51

Page 31 Rev. 00



### 7.6 RADIATED EMISSIONS

## LIMIT

1. According to §15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Reference No.: T150529W04-RP2 Report No.: T160118W01-RP2

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

**Remark:** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.


2. In the emission table above, the tighter limit applies at the band edges.

Frequency (MHz)	Field Strength (μV/m at 3-meter)	Field Strength (dBµV/m at 3-meter)
0.009 - 0.490	2400/F(kHz) +80	20LOG((2400/F(kHz))+80)
0.490 - 1.705	24000/F(kHz) +40	20LOG((24000/F(kHz))+40)
1.705 – 30.0	30	69.54
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54


Page 32 Rev. 00

# **Test Configuration**

### 9kHz ~ 30MHz




### 30MHz ~ 1GHz



Page 33 Rev. 00

### **Above 1 GHz**



Page 34 Rev. 00

# **TEST PROCEDURE**

1. The EUT is placed on a turntable, Above 1 GHz is 1.5m high and below 1 GHz is 0.8m high above ground plane.

Reference No.: T150529W04-RP2

Report No.: T160118W01-RP2

- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- 4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 6. Set the spectrum analyzer in the following setting as:

Below 1GHz:

RBW=100kHz / VBW=300kHz / Sweep=AUTO

Above 1GHz:

- (a) PEAK: RBW=1MHz / VBW=3MHz / Sweep=AUTO
- (b) AVERAGE: RBW=1MHz, if duty cycle≥98%, VBW=10Hz. if duty cycle<98% VBW=1/T. BT4.0: ≥98%, VBW=10Hz
- 7. Repeat above procedures until the measurements for all frequencies are complete.
- 8. Result = Spectrum Reading + cable loss(spectrum to Amp) Amp Gain + Cable loss(Amp to receive Ant) + Receive Ant

**Note:** We checked every harmonics frequencies from Fundamental frequencies with reduced VBW, and we mark a point to prove pass or not if we find any emission. For this case, there are no emissions hidden in the noise floor.

Page 35 Rev. 00


Reference No.: T150529W04-RP2 FCC ID: ZDX-TLC120A Report No.: T160118W01-RP2

### **Below 1 GHz**

Operation Mode: Normal Link Test Date: January 28, 2016

27℃ **Temperature:** Tested by: Jason Lu

**Humidity:** 53 % RH **Polarity:** Ver.



Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
125.0600	49.97	-15.57	34.40	43.50	-9.10	peak	V
250.1900	46.02	-16.27	29.75	46.00	-16.25	peak	V
500.4500	45.57	-9.23	36.34	46.00	-9.66	peak	V
600.3600	42.01	-7.75	34.26	46.00	-11.74	peak	V
727.4300	36.31	-5.44	30.87	46.00	-15.13	peak	V
874.8700	30.90	-3.49	27.41	46.00	-18.59	peak	V

### Remark:


- No emission found between lowest internal used/generated frequency to *30MHz* (9kHz~30MHz)
- 2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using peak/quasi-peak detector mode.
- 3. Quasi-peak test would be performed if the peak result were greater than the quasi-peak limit or as required by the applicant.
- 4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 5. Margin (dB) = Remark result (dBuV/m) - Quasi-peak limit (dBuV/m).

Page 36 Rev. 00

Operation Mode: Normal Link Test Date: January 28, 2016

**Temperature:** 27 °C **Tested by:** Jason Lu

**Humidity:** 53 % RH **Polarity:** Hor.



Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
125.0600	49.55	-15.57	33.98	43.50	-9.52	peak	Н
250.1900	58.36	-16.27	42.09	46.00	-3.91	peak	Н
375.3200	46.37	-12.29	34.08	46.00	-11.92	peak	Н
500.4500	47.58	-9.23	38.35	46.00	-7.65	peak	Н
730.3400	46.17	-5.37	40.80	46.00	-5.20	peak	Н
746.8300	43.97	-4.99	38.98	46.00	-7.02	peak	Н

### Remark:


- 1. No emission found between lowest internal used/generated frequency to 30MHz (9kHz~30MHz)
- 2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using peak/quasi-peak detector mode.
- 3. Quasi-peak test would be performed if the peak result were greater than the quasi-peak limit or as required by the applicant.
- 4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 5. Margin (dB) = Remark result (dBuV/m) Quasi-peak limit (dBuV/m).

Page 37 Rev. 00


# **Above 1 GHz**

# GFSK / TX / CH Low

**Polarity: Vertical** 



# **Polarity: Horizontal**



Page 38 Rev. 00 Above 1 GHz

**Operation Mode:** GFSK / TX / CH Low **Test Date:** January 19, 2016

Reference No.: T150529W04-RP2

Report No.: T160118W01-RP2

Temperature:27 °CTested by:Jason LuHumidity:53 % RHPolarity:Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Pol. (H/V)
4804.000	49.63	5.04	54.67	74.00	-19.33	peak	V
4804.000	44.43	5.04	49.47	54.00	-4.53	AVG	V
7206.000	43.74	12.62	56.36	74.00	-17.64	peak	V
9608.000	42.73	17.60	60.33	74.00	-13.67	peak	V
N/A							
4804.000	48.56	5.04	53.60	74.00	-20.40	peak	Н
4804.000	45.84	5.04	50.88	54.00	-3.12	AVG	Н
7206.000	42.52	12.62	55.14	74.00	-18.86	peak	Н
9608.000	40.74	17.60	58.34	74.00	-15.66	peak	Н
N/A							

### Remark:


- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
- 3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
- 4. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 6. Margin (dB) = Remark result (dBuV/m) Average limit (dBuV/m).

Page 39 Rev. 00


#### Reference No.: T150529W04-RP2 FCC ID: ZDX-TLC120A Report No.: T160118W01-RP2

# GFSK / TX / CH Mid

# **Polarity: Vertical**



# **Polarity: Horizontal**



Page 40 Rev. 00 Operation Mode: GFSK / TX / CH Mid Test Date: January 19, 2016

Reference No.: T150529W04-RP2

Report No.: T160118W01-RP2

Temperature: 27 °C Tested by: Jason Lu

Humidity: 53 % RH Polarity: Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Pol. (H/V)
4880.000	51.31	5.25	56.56	74.00	-17.44	peak	V
4880.000	44.38	5.25	49.63	54.00	-4.37	AVG	V
7320.000	41.91	12.97	54.88	74.00	-19.12	peak	V
7320.000	30.06	12.97	43.03	54.00	-10.97	AVG	V
9760.000	41.28	17.60	58.88	74.00	-15.12	peak	V
N/A							
4880.000	47.88	5.25	53.13	74.00	-20.87	peak	Н
4880.000	46.52	5.25	51.77	54.00	-2.23	AVG	Н
7320.000	42.10	12.97	55.07	74.00	-18.93	peak	Н
7320.000	32.03	12.97	45.00	54.00	-9.00	AVG	Н
9760.000	41.70	17.60	59.30	74.00	-14.70	peak	Н
N/A							


### Remark:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
- 3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
- 4. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 6. Margin (dB) = Remark result (dBuV/m) Average limit (dBuV/m).


Page 41 Rev. 00

# GFSK / TX / CH High

### **Polarity: Vertical**



### **Polarity: Horizontal**



Page 42 Rev. 00

**Operation Mode:** GFSK / TX / CH High **Test Date:** January 19, 2016

Reference No.: T150529W04-RP2

Report No.: T160118W01-RP2

Temperature: 27°C Tested by: Jason Lu

Humidity: 53 % RH Polarity: Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Pol. (H/V)
4960.000	45.83	5.46	51.29	74.00	-22.71	peak	V
4960.000	34.89	5.46	40.35	54.00	-13.65	AVG	V
7440.000	42.76	13.33	56.09	74.00	-17.91	peak	V
7440.000	32.34	13.33	45.67	54.00	-8.33	AVG	V
9920.000	40.59	17.60	58.19	74.00	-15.81	peak	V
N/A							
4960.000	42.54	5.46	48.00	74.00	-26.00	peak	Н
4960.000	40.20	5.46	45.66	54.00	-8.34	AVG	Н
7440.000	40.87	13.33	54.20	74.00	-19.80	peak	Н
7440.000	31.33	13.33	44.66	54.00	-9.34	AVG	Н
9920.000	41.27	17.60	58.87	74.00	-15.13	peak	Н
N/A							

### Remark:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
- 3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
- 4. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 6. Margin (dB) = Remark result (dBuV/m) Average limit (dBuV/m).

Page 43 Rev. 00

### 7.7 POWERLINE CONDUCTED EMISSIONS

### LIMIT

According to §15.207(a), except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50  $\mu\text{H}/50$  ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Reference No.: T150529W04-RP2

Report No.: T160118W01-RP2

Frequency Range	Limits (dBµV)				
(MHz)	Quasi-peak	Average			
0.15 to 0.50	66 to 56*	56 to 46*			
0.50 to 5	56	46			
5 to 30	60	50			

### **Test Configuration**

See test photographs attached in Appendix II for the actual connections between EUT and support equipment.

### **TEST PROCEDURE**

- 1. The EUT was placed on a table, which is 0.8m above ground plane.
- 2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 3. Repeat above procedures until all frequency measured were complete.

Page 44 Rev. 00

# **TEST RESULTS**

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.

### **Test Data**

Operation Mode: Normal Link Test Date: February 26, 2016

**Temperature:** 24 °C **Tested by:** Dennis Li

**Humidity:** 50% RH

Freq. (MHz)	QP Reading (dBuV)	AV Reading (dBuV)	Corr. factor (dB/m)	QP Result (dBuV/m)	AV Result (dBuV/m)	QP Limit (dBuV)	AV Limit (dBuV)	QP Margin (dB)	AV Margin (dB)	Note
0.1525	46.95	40.83	9.69	56.64	50.52	65.86	55.86	-9.22	-5.34	L1
0.1665	48.10	39.14	9.69	57.79	48.83	65.13	55.13	-7.34	-6.30	L1
0.4178	34.33	21.96	9.71	44.04	31.67	57.49	47.49	-13.45	-15.82	L1
0.4860	36.86	26.25	9.81	46.67	36.06	56.24	46.24	-9.57	-10.18	L1
0.5100	33.88	22.29	9.84	43.72	32.13	56.00	46.00	-12.28	-13.87	L1
0.5899	39.50	27.70	9.95	49.45	37.65	56.00	46.00	-6.55	-8.35	L1
0.6460	35.71	24.39	10.03	45.74	34.42	56.00	46.00	-10.26	-11.58	L1
0.7820	33.68	23.55	10.22	43.90	33.77	56.00	46.00	-12.10	-12.23	L1
0.9220	30.36	22.16	10.41	40.77	32.57	56.00	46.00	-15.23	-13.43	L1
1.0339	35.87	26.21	10.49	46.36	36.70	56.00	46.00	-9.64	-9.30	L1
1.4140	31.19	18.04	10.20	41.39	28.24	56.00	46.00	-14.61	-17.76	L1
1.6300	31.90	21.45	10.04	41.94	31.49	56.00	46.00	-14.06	-14.51	L1
1.9300	33.66	23.74	9.81	43.47	33.55	56.00	46.00	-12.53	-12.45	L1
2.2180	32.29	21.80	9.76	42.05	31.56	56.00	46.00	-13.95	-14.44	L1
2.6580	32.70	20.78	9.78	42.48	30.56	56.00	46.00	-13.52	-15.44	L1
3.7660	32.57	20.92	9.82	42.39	30.74	56.00	46.00	-13.61	-15.26	L1
4.7260	31.74	21.09	9.83	41.57	30.92	56.00	46.00	-14.43	-15.08	L1

### Remark:

- 1. Measuring frequencies from 0.15 MHz to 30MHz.
- 2. The emissions measured in frequency range from 0.15 MHz to 30MHz were made with an instrument using Quasi-peak detector and average detector.
- 3. The IF bandwidth of SPA between 0.15MHz and 30MHz was 10 kHz; the IF bandwidth of Test Receiver between 0.15MHz and 30MHz was 9 kHz:
- 4. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line)

Page 45 Rev. 00

FCC ID: ZDX-TLC120A Report No.: T160118W01-RP2

Reference No.: T150529W04-RP2

Operation Mode: Normal Link Test Date: February 26, 2016

Temperature: 24 °C Tested by: Dennis Li

Humidity: 50% RH

Freq. (MHz)	QP Reading (dBuV)	AV Reading (dBuV)	Corr. factor (dB/m)	QP Result (dBuV/m)	AV Result (dBuV/m)	QP Limit (dBuV)	AV Limit (dBuV)	QP Margin (dB)	AV Margin (dB)	Note
0.1660	40.90	32.05	9.64	50.54	41.69	65.15	55.16	-14.61	-13.47	L2
0.2097	34.56	22.79	9.64	44.20	32.43	63.21	53.22	-19.01	-20.79	L2
0.4660	34.24	22.05	9.74	43.98	31.79	56.58	46.58	-12.60	-14.79	L2
0.5019	36.57	23.08	9.79	46.36	32.87	56.00	46.00	-9.64	-13.13	L2
0.5581	34.78	20.27	9.87	44.65	30.14	56.00	46.00	-11.35	-15.86	L2
0.5897	37.71	25.40	9.91	47.62	35.31	56.00	46.00	-8.38	-10.69	L2
0.6496	34.87	24.26	10.00	44.87	34.26	56.00	46.00	-11.13	-11.74	L2
0.7018	26.79	11.66	10.07	36.86	21.73	56.00	46.00	-19.14	-24.27	L2
0.7824	32.65	20.47	10.18	42.83	30.65	56.00	46.00	-13.17	-15.35	L2
1.0062	26.31	17.64	10.48	36.79	28.12	56.00	46.00	-19.21	-17.88	L2
1.3300	31.50	19.30	10.23	41.73	29.53	56.00	46.00	-14.27	-16.47	L2
1.4980	27.58	15.29	10.10	37.68	25.39	56.00	46.00	-18.32	-20.61	L2
2.5820	32.62	20.45	9.74	42.36	30.19	56.00	46.00	-13.64	-15.81	L2


### Remark:

- 1. Measuring frequencies from 0.15 MHz to 30MHz.
  - 2. The emissions measured in frequency range from 0.15 MHz to 30MHz were made with an instrument using Quasi-peak detector and average detector.
  - 3. The IF bandwidth of SPA between 0.15MHz and 30MHz was 10 kHz; the IF bandwidth of Test Receiver between 0.15MHz and 30MHz was 9 kHz;
  - 4. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line)


Page 46 Rev. 00

# **Test Plots**

# Conducted emissions (Line 1)



# Conducted emissions (Line 2)



Page 47 Rev. 00