Reference No.: T150529W04-MF Report No.: T160118W01-MF

IEEE C95.1 2005 KDB 447498 D01 V06 47 C.F.R. Part 1, Subpart I, Section 1.1310 47 C.F.R. Part 2, Subpart J, Section 2.1091

RF EXPOSURE REPORT

For

Time Lapse Camera TLC120

Model: TLC120A

Trade Name: brinno

Issued to

Brinno Incorporated 4F, No.107, Zhouzi St., Taipei City, 11493, Taiwan, (R.O.C.)

Issued by

Compliance Certification Services Inc.
No.11, Wugong 6th Rd., Wugu Dist.,
New Taipei City 24891, Taiwan. (R.O.C.)
http://www.ccsrf.com
service@ccsrf.com
Issued Date: March 28, 2016

Testing Laboratory 1309



Report No.: T160118W01-MF

Reference No.: T150529W04-MF

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	March 28, 2016	Initial Issue	ALL	Doris Chu
01	April 15, 2016	1. Added Chapter 5	P.7	Doris Chu

TABLE OF CONTENTS

Reference No.: T150529W04-MF Report No.: T160118W01-MF

1.	LIMIT	. 4
2.	EUT SPECIFICATION	. 4
3.	TEST RESULTS	. 5
4.	MAXIMUM PERMISSIBLE EXPOSURE	. 6
5	SIMILI TANFOLIS TRANSMISSION SAR ANALYSIS	7

1. LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

Reference No.: T150529W04-MF

Report No.: T160118W01-MF

2. EUT SPECIFICATION

EUT	Time Lapse Camera TLC120						
Model	TLC120A						
Trade Name	brinno						
Frequency band (Operating)							
Device category	☐ Portable (<20cm separation) ☐ Mobile (>20cm separation) ☐ Others						
Exposure classification	☐ Occupational/Controlled exposure (S = 5mW/cm²) ☐ General Population/Uncontrolled exposure (S=1mW/cm²)						
Antenna Specification	Print Chip Antenna: CIRO / PCAK0000-12 Antenna Gain: 1.00 dBi (Numeric gain: 1.26)						
Maximum Average output power	Bluetooth 4.0: -2.12 dBm (0.614 mW) IEEE 802.11b Mode: 17.44 dBm (55.463 mW) IEEE 802.11g Mode: 16.17 dBm (41.400 mW)						
Maximum Tune up Power	Bluetooth 4.0: -1.00 dBm (0.794 mW) IEEE 802.11b Mode: 19.00 dBm (79.433 mW) IEEE 802.11g Mode: 18.00 dBm (63.096 mW)						
Evaluation applied							

3. TEST RESULTS

No non-compliance noted.

Calculation

$$E = \frac{\sqrt{30 \times P \times G}}{d} \quad \& \quad S = \frac{E^2}{377}$$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = *Distance in meters*

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377d^2}$$

Changing to units of mW and cm, using:

$$P(mW) = P(W) / 1000$$
 and

$$d(cm) = d(m) / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2}$$
 Equation 1

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

 $S = Power density in mW / cm^2$

Reference No.: T150529W04-MF

Report No.: T160118W01-MF

FCC ID: ZDX-TLC120A Report No.: T160118W01-MF

Reference No.: T150529W04-MF

4. MAXIMUM PERMISSIBLE EXPOSURE

Substituting the MPE safe distance using d = 20 cm into Equation 1:

 $S = 0.000199 \times P \times G$

Where P = Power in mW

G = *Numeric* antenna gain

 $S = Power density in mW / cm^2$

Bluetooth 4.0:

E	Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
	1	2402	0.794	1.26	20	0.0002	1

IEEE 802.11b mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
6	2437	79.433	1.26	20	0.0199	1

IEEE 802.11g mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
11	2462	63.096	1.26	20	0.0158	1

5. SIMULTANEOUS TRANSMISSION SAR ANALYSIS

Both of the 2.4GHz band and Bluetooth can transmit simultaneously, the formula of calculated the MPE is:

Reference No.: T150529W04-MF

Report No.: T160118W01-MF

CPD1 / LPD1 + CPD2 / LPD2 +etc. < 1

CPD = Calculation power density

LPD = Limit of power density

Therefore, the worst-case situation is 0.0002 / 1 + 0.0199 / 1 = 0.0201, which is less than "1".