

APPLICATION CERTIFICATION FCC Part 15C
On Behalf of
Shenzhen Leader Digital-tech Weitong Co., Ltd.

MID
Model No.: GN3X

FCC ID: ZDYG3X

Prepared for : Shenzhen Leader Digital-tech Weitong Co., Ltd.
Address : 4 Floor, Dongjiang Environmental Building, Central
Nanshan District, Shenzhen, China

Prepared by : ACCURATE TECHNOLOGY CO., LTD
Address : F1, Bldg. A, Changyuan New Material Port, Keyuan Rd.
Science & Industry Park, Nanshan, Shenzhen, Guangdong
P.R. China

Tel: (0755) 26503290
Fax: (0755) 26503396

Report Number : ATE20120034
Date of Test : January 9-February 2, 2012
Date of Report : February 9, 2012

TABLE OF CONTENTS

Description	Page
Test Report Certification	
1. GENERAL INFORMATION	5
1.1. Description of Device (EUT).....	5
1.2. Description of Test Facility	6
1.3. Measurement Uncertainty	6
2. MEASURING DEVICE AND TEST EQUIPMENT	7
3. OPERATION OF EUT DURING TESTING	8
3.1. Operating Mode	8
3.2. Configuration and peripherals	8
4. TEST PROCEDURES AND RESULTS	9
5. 6DB BANDWIDTH MEASUREMENT	10
5.1. Block Diagram of Test Setup.....	10
5.2. The Requirement For Section 15.247(a)(2).....	10
5.3. EUT Configuration on Measurement	10
5.4. Operating Condition of EUT	10
5.5. Test Procedure	11
5.6. Test Result	11
6. MAXIMUM PEAK OUTPUT POWER	22
6.1. Block Diagram of Test Setup.....	22
6.2. The Requirement For Section 15.247(b)(3).....	22
6.3. EUT Configuration on Measurement	22
6.4. Operating Condition of EUT	22
6.5. Test Procedure	23
6.6. Test Result	23
7. POWER SPECTRAL DENSITY MEASUREMENT.....	34
7.1. Block Diagram of Test Setup.....	34
7.2. The Requirement For Section 15.247(e).....	34
7.3. EUT Configuration on Measurement	34
7.4. Operating Condition of EUT	34
7.5. Test Procedure	35
7.6. Test Result	35
8. BAND EDGE COMPLIANCE TEST	46
8.1. Block Diagram of Test Setup.....	46
8.2. The Requirement For Section 15.247(d)	46
8.3. EUT Configuration on Measurement	46
8.4. Operating Condition of EUT	47
8.5. Test Procedure	47
8.6. Test Result	48
9. RADIATED SPURIOUS EMISSION TEST	73
9.1. Block Diagram of Test Setup.....	73
9.2. The Limit For Section 15.247(d)	74
9.3. Restricted bands of operation	74
9.4. Configuration of EUT on Measurement	75
9.5. Operating Condition of EUT	75

9.6.	Test Procedure	75
9.7.	The Field Strength of Radiation Emission Measurement Results	76
10.	CONDUCTED SPURIOUS EMISSION COMPLIANCE TEST	139
10.1.	Block Diagram of Test Setup.....	139
10.2.	The Requirement For Section 15.247(d)	139
10.3.	EUT Configuration on Measurement	139
10.4.	Operating Condition of EUT	140
10.5.	Test Procedure	140
10.6.	Test Result	140
11.	AC POWER LINE CONDUCTED EMISSION FOR FCC PART 15 SECTION 15.207(A) 168	
11.1.	Block Diagram of Test Setup.....	168
11.2.	The Emission Limit	168
11.3.	Configuration of EUT on Measurement	169
11.4.	Operating Condition of EUT	169
11.5.	Test Procedure	169
11.6.	Power Line Conducted Emission Measurement Results	170
12.	ANTENNA REQUIREMENT.....	179
12.1.	The Requirement	179
12.2.	Antenna Construction	179

Test Report Certification

Applicant : Shenzhen Leader Digital-tech Weitong Co., Ltd.
Manufacturer : Shenzhen Leader Digital-tech Weitong Co., Ltd.
EUT Description : MID
(A) MODEL NO.: GN3X
(B) SERIAL NO.: N/A
(C) POWER SUPPLY: DC 7.4V (Li-polymer battery);
AC 120V/60Hz (Adaptor input)

Measurement Procedure Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247
ANSI C63.4: 2003

The device described above is tested by ACCURATE TECHNOLOGY CO. LTD to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.247 limits. The measurement results are contained in this test report and ACCURATE TECHNOLOGY CO. LTD is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of ACCURATE TECHNOLOGY CO. LTD.

Date of Test : January 9-February 2, 2012

Prepared by :

Apple Lv

(Engineer)

Approved & Authorized Signer :

Heim

(Manager)

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT	:	MID
Model Number	:	GN3X (Note: X=1-9 These samples are same except for the appearance is difference. So we prepare the GN32 for FCC test.)
Frequency Band (Wifi)	:	2412-2462MHz
Frequency Band (Bluetooth)	:	2402MHz-2480MHz
Number of Channels	:	11
Antenna Gain	:	0dBi
Power Supply	:	DC 7.4V (Li-polymer battery); AC 120V/60Hz (Adaptor input)
Adapter	:	Model number: FLD181-120150-11B25B Input: AC 100-240V; 50/60Hz 0.5A Output: DC 12V; 1.5A Output line: Non-shielded, Non-detachable, 1.4m
Data Rate	:	IEEE 802.11b: 11Mbps IEEE 802.11g: 54Mbps IEEE 802.11n: 150Mbps
Applicant	:	Shenzhen Leader Digital-tech Weitong Co., Ltd.
Address	:	4 Floor, Dongjiang Environmental Building, Central Nanshan District, Shenzhen, China
Manufacturer	:	Shenzhen Leader Digital-tech Weitong Co., Ltd.
Address	:	4 Floor, Dongjiang Environmental Building, Central Nanshan District, Shenzhen, China
Date of sample received	:	January 9, 2012
Date of Test	:	January 9-February 2, 2012

1.2. Description of Test Facility

EMC Lab	:	Accredited by TUV Rheinland Shenzhen
		Listed by FCC
		The Registration Number is 752051
		Listed by Industry Canada
		The Registration Number is 5077A-2
		Accredited by China National Accreditation Committee for Laboratories
		The Certificate Registration Number is L3193
Name of Firm	:	ACCURATE TECHNOLOGY CO. LTD
Site Location	:	F1, Bldg. A, Changyuan New Material Port, Keyuan Rd. Science & Industry Park, Nanshan, Shenzhen, Guangdong P.R. China

1.3. Measurement Uncertainty

Conducted Emission Expanded Uncertainty	=	2.23dB, k=2
Radiated emission expanded uncertainty (9kHz-30MHz)	=	3.08dB, k=2
Radiated emission expanded uncertainty (30MHz-1000MHz)	=	4.42dB, k=2
Radiated emission expanded uncertainty (Above 1GHz)	=	4.06dB, k=2

2. MEASURING DEVICE AND TEST EQUIPMENT

Table 1: List of Test and Measurement Equipment

Kind of equipment	Manufacturer	Type	S/N	Calibrated until
EMI Test Receiver	Rohde&Schwarz	ESCS30	100307	Jan. 7, 2013
EMI Test Receiver	Rohde&Schwarz	ESPI3	101526/003	Jan. 7, 2013
Spectrum Analyzer	Agilent	E7405A	MY45115511	Jan. 7, 2013
Pre-Amplifier	Rohde&Schwarz	CBLU118354 0-01	3791	Jan. 7, 2013
Loop Antenna	Schwarzbeck	FMZB1516	1516131	Jan. 7, 2013
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	Jan. 7, 2013
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	Jan. 7, 2013
Horn Antenna	Schwarzbeck	BBHA9170	9170-359	Jan. 7, 2013
LISN	Rohde&Schwarz	ESH3-Z5	100305	Jan. 7, 2013
LISN	Schwarzbeck	NSLK8126	8126431	Jan. 7, 2013

3. OPERATION OF EUT DURING TESTING

3.1.Operating Mode

The mode is used: **802.11b Transmitting mode**

Low Channel: 2412MHz

Middle Channel: 2437MHz

High Channel: 2462MHz

802.11g Transmitting mode

Low Channel: 2412MHz

Middle Channel: 2437MHz

High Channel: 2462MHz


802.11n Transmitting mode

Low Channel: 2412MHz

Middle Channel: 2437MHz

High Channel: 2462MHz

3.2.Configuration and peripherals




4. TEST PROCEDURES AND RESULTS

FCC Rules	Description of Test	Result
Section 15.247(a)(2)	6dB Bandwidth Test	Compliant
Section 15.247(e)	Power Spectral Density Test	Compliant
Section 15.247(b)(3)	Maximum Peak Output Power Test	Compliant
Section 15.247(d)	Band Edge Compliance Test	Compliant
Section 15.247(d) Section 15.209	Radiated Spurious Emission Test	Compliant
Section 15.247(d)	Conducted Spurious Emission Test	Compliant
Section 15.207	AC Power Line Conducted Emission Test	Compliant
Section 15.203	Antenna Requirement	Compliant

5. 6DB BANDWIDTH MEASUREMENT

5.1. Block Diagram of Test Setup



5.2. The Requirement For Section 15.247(a)(2)

Section 15.247(a)(2): Systems using digital modulation techniques may operate in the 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

5.3. EUT Configuration on Measurement

The following equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

5.3.1. MID (EUT)

Model Number	:	GN32
Serial Number	:	N/A
Manufacturer	:	Shenzhen Leader Digital-tech Weitong Co., Ltd.

5.4. Operating Condition of EUT

5.4.1. Setup the EUT and simulator as shown as Section 5.1.

5.4.2. Turn on the power of all equipment.

5.4.3. Let the EUT work in TX modes measure it. The transmit frequency are 2412-2462MHz. We select 2412MHz, 2437MHz, 2462MHz TX frequency to transmit.

5.5. Test Procedure

5.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

5.5.2. Set RBW of spectrum analyzer to 100kHz and VBW to 300kHz.

5.5.3. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

5.6. Test Result

PASS.

Date of Test:	January 14, 2012	Temperature:	25°C
EUT:	MID	Humidity:	50%
Model No.:	GN32	Power Supply:	AC 120V/60Hz
Test Mode:	TX	Test Engineer:	Pei

The test was performed with 802.11b

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)
Low	2412	11.41	> 0.5MHz
Middle	2437	11.20	> 0.5MHz
High	2462	11.09	> 0.5MHz

The test was performed with 802.11g

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)
Low	2412	16.00	> 0.5MHz
Middle	2437	16.62	> 0.5MHz
High	2462	16.61	> 0.5MHz

The test was performed with 802.11n

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)
Low	2412	17.62	> 0.5MHz
Middle	2437	17.00	> 0.5MHz
High	2462	17.94	> 0.5MHz


The spectrum analyzer plots are attached as below.

802.11b Channel Low 2412MHz


802.11b Channel Low 2412MHz



*RBW 100 kHz Delta 2 [T1]
 VBW 300 kHz 1.02 dB
 SWT 2.5 ms 11.410000000 MHz




802.11b Channel Middle 2437MHz



802.11b Channel High 2462MHz



1 PK
MAXH



802.11g Channel Low 2412MHz




*RBW 100 kHz Delta 2 [T1]
 VBW 300 kHz -1.12 dB
 SWT 2.5 ms 16.000000 MHz

Ref 20 dBm

Att 50 dB

1 PK
 MAXH




Center 2.412 GHz


2 MHz/

Span 20 MHz


802.11g Channel Middle 2437MHz




802.11g Channel High 2462MHz




802.11n Channel Low 2412MHz



802.11n Channel Low 2437MHz




802.11n Channel Low 2462MHz



6. MAXIMUM PEAK OUTPUT POWER

6.1. Block Diagram of Test Setup



6.2. The Requirement For Section 15.247(b)(3)

Section 15.247(b)(3): For systems using digital modulation in the 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz bands: 1 Watt.

6.3. EUT Configuration on Measurement

The following equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

6.3.1. MID (EUT)

Model Number	: GN32
Serial Number	: N/A
Manufacturer	: Shenzhen Leader Digital-tech Weitong Co., Ltd.

6.4. Operating Condition of EUT

6.4.1. Setup the EUT and simulator as shown as Section 6.1.

6.4.2. Turn on the power of all equipment.

6.4.3. Let the EUT work in TX modes measure it. The transmit frequency are 2412-2462MHz. We select 2412MHz, 2437MHz, 2462MHz TX frequency to transmit.

6.5. Test Procedure

6.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

6.5.2. Set RBW of spectrum analyzer to 1MHz and VBW to 3MHz.

6.5.3. Measurement the maximum peak output power.

6.6. Test Result

PASS.

Date of Test:	January 14, 2012	Temperature:	25°C
EUT:	MID	Humidity:	50%
Model No.:	GN32	Power Supply:	AC 120V/60Hz
Test Mode:	TX	Test Engineer:	Pei

The test was performed with 802.11b

Channel	Frequency (MHz)	Peak Output Power (dBm)	Peak Output Power (mW)	Limits dBm / W
Low	2412	9.42	8.75	30 dBm / 1 W
Middle	2437	9.26	8.43	30 dBm / 1 W
High	2462	10.13	10.30	30 dBm / 1 W

The test was performed with 802.11g

Channel	Frequency (MHz)	Peak Output Power (dBm)	Peak Output Power (mW)	Limits dBm / W
Low	2412	10.18	10.42	30 dBm / 1 W
Middle	2437	9.85	9.66	30 dBm / 1 W
High	2462	10.45	11.09	30 dBm / 1 W


The test was performed with 802.11n				
Channel	Frequency (MHz)	Peak Output Power (dBm)	Peak Output Power (mW)	Limits dBm / W
Low	2412	9.56	9.03	30 dBm / 1 W
Middle	2437	8.85	7.67	30 dBm / 1 W
High	2462	9.45	8.81	30 dBm / 1 W

The spectrum analyzer plots are attached as below.

802.11b Channel Low 2412MHz




802.11b Channel Middle 2437MHz



802.11b Channel High 2462MHz



1 PK
MAXH




Tx Channel
Bandwidth

16 MHz


Power

10.13 dBm


802.11g Channel Low 2412MHz




802.11g Channel Middle 2437MHz



802.11g Channel High 2462MHz




802.11n Channel High 2412MHz



802.11n Channel High 2437MHz




802.11n Channel High 2462MHz



7. POWER SPECTRAL DENSITY MEASUREMENT

7.1. Block Diagram of Test Setup



7.2. The Requirement For Section 15.247(e)

Section 15.247(e): For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

7.3. EUT Configuration on Measurement

The following equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

7.3.1. MID (EUT)

Model Number	:	GN32
Serial Number	:	N/A
Manufacturer	:	Shenzhen Leader Digital-tech Weitong Co., Ltd.

7.4. Operating Condition of EUT

7.4.1. Setup the EUT and simulator as shown as Section 7.1.

7.4.2. Turn on the power of all equipment.

7.4.3. Let the EUT work in TX modes measure it. The transmit frequency are 2412-2462MHz. We select 2412MHz, 2437MHz, 2462MHz TX frequency to transmit.

7.5. Test Procedure

7.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

7.5.2. Set RBW of spectrum analyzer to 3kHz and VBW to 10kHz, sweep time = Span/3kHz.

7.5.3. Measurement the maximum power spectral density.

7.6. Test Result

PASS.

Date of Test:	January 18, 2012	Temperature:	25°C
EUT:	MID	Humidity:	50%
Model No.:	GN32	Power Supply:	AC 120V/60Hz
Test Mode:	TX	Test Engineer:	Pei

The test was performed with 802.11b			
Channel	Frequency (MHz)	Power Spectral Density (dBm)	Limits (dBm)
Low	2412	-5.10	8 dBm
Middle	2437	-6.71	8 dBm
High	2462	-5.74	8 dBm


The test was performed with 802.11g			
Channel	Frequency (MHz)	Power Spectral Density (dBm)	Limits (dBm)
Low	2412	-24.98	8 dBm
Middle	2437	-26.81	8 dBm
High	2462	-24.20	8 dBm

The test was performed with 802.11n


Channel	Frequency (MHz)	Power Spectral Density (dBm)	Limits (dBm)
Low	2412	-23.13	8 dBm
Middle	2437	-26.81	8 dBm
High	2462	-25.20	8 dBm

The spectrum analyzer plots are attached as below.


802.11b Channel Low 2412MHz




802.11b Channel Middle 2437MHz




802.11b Channel High 2462MHz




802.11g Channel Low 2412MHz




802.11g Channel Middle 2437MHz




802.11g Channel High 2462MHz




802.11n Channel High 2412MHz



802.11n Channel High 2437MHz




802.11n Channel High 2462MHz



8. BAND EDGE COMPLIANCE TEST

8.1. Block Diagram of Test Setup



8.2. The Requirement For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

8.3. EUT Configuration on Measurement

The following equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

8.3.1. MID (EUT)

Model Number	:	GN32
Serial Number	:	N/A
Manufacturer	:	Shenzhen Leader Digital-tech Weitong Co., Ltd.

8.4. Operating Condition of EUT

8.4.1. Setup the EUT and simulator as shown as Section 8.1.

8.4.2. Turn on the power of all equipment.

8.4.3. Let the EUT work in TX modes measure it. The transmit frequency are 2412-2462MHz. We select 2412MHz, 2462MHz TX frequency to transmit.

8.5. Test Procedure

Conducted Band Edge:

8.5.1. The transmitter output was connected to the spectrum analyzer via a low loss cable.

8.5.2. Set RBW of spectrum analyzer to 100kHz and VBW to 300kHz.

Radiate Band Edge:

8.5.3. The EUT is placed on a turntable, which is 0.8m above the ground plane and worked at highest radiated power.

8.5.4. The turntable was rotated for 360 degrees to determine the position of maximum emission level.

8.5.5. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.

8.5.6. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:

RBW=1MHz, VBW=1MHz

8.5.7. The band edges was measured and recorded.

8.6.Test Result

Pass

Conducted test


Date of Test:	January 14, 2012	Temperature:	25°C
EUT:	MID	Humidity:	50%
Model No.:	GN32	Power Supply:	AC 120V/60Hz
Test Mode:	TX	Test Engineer:	Pei

The test was performed with 802.11b		
Frequency (MHz)	Result of Band Edge (dBc)	Limit of Band Edge (dBc)
2412	37.59	> 20dBc
2462	36.79	> 20dBc

The test was performed with 802.11g		
Frequency (MHz)	Result of Band Edge (dBc)	Limit of Band Edge (dBc)
2412	33.58	> 20dBc
2462	32.12	> 20dBc

The test was performed with 802.11n		
Frequency (MHz)	Result of Band Edge (dBc)	Limit of Band Edge (dBc)
2412	32.26	> 20dBc
2462	32.45	> 20dBc


802.11b Channel Low 2412MHz



802.11b Channel High 2462MHz



1 PK
MAXH



802.11g Channel Low 2412MHz



*RBW 100 kHz Delta 2 [T1]
 VBW 300 kHz -33.25 dB
 SWT 10 ms -28.480000000 MHz


Ref 20 dBm

Att 50 dB

SWT 10 ms

-28.480000000 MHz

1 PK
 MAXH



MHz/

Span 80 MHz

802.11g Channel High 2462MHz



*RBW 100 kHz Delta 2 [T1]
 VBW 300 kHz -32.56 dB
 SWT 10 ms 38.880000000 MHz


Ref 20 dBm

Att 50 dB

SWT 10 ms

38.880000000 MHz

1 PK
 MAXH



Center 2.4635 GHz

° MHz/

Span 80 MHz

802.11n Channel High 2412MHz



*RBW 100 kHz Delta 2 [T1]
 VBW 300 kHz -32.45 dB
 SWT 10 ms -21.920000000 MHz


Ref 20 dBm

Att 50 dB

SWT 10 ms

-21.920000000 MHz

1 PK
 MAXH



Center 2.4 GHz


8 MHz/

Span 80 MHz

802.11n Channel High 2462MHz



*RBW 100 kHz Delta 2 [T1]
 VBW 300 kHz -32.67 dB
 SWT 10 ms 34.560000000 MHz



Radiated Band Edge Result

Date of Test:	January 18, 2012	Temperature:	25°C
EUT:	MID	Humidity:	50%
Model No.:	GN32	Power Supply:	AC 120V/60Hz
Test Mode:	802.11b Channel Low 2412MHz	Test Engineer:	Pei

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
-	-	-	-	-	-	-	-	-	-	Vertical
-	-	-	-	-	-	-	-	-	-	Horizontal

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:
Result = Reading + Corrected Factor
3. Display the measurement of peak values.

Date of Test:	January 18, 2012	Temperature:	25°C
EUT:	MID	Humidity:	50%
Model No.:	GN32	Power Supply:	AC 120V/60Hz
Test Mode:	802.11b Channel High 2462MHz	Test Engineer:	Pei

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
-	-	-	-	-	-	-	-	-	-	Vertical
-	-	-	-	-	-	-	-	-	-	Horizontal

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:
Result = Reading + Corrected Factor
3. Display the measurement of peak values.

Date of Test:	January 18, 2012	Temperature:	25°C
EUT:	MID	Humidity:	50%
Model No.:	GN32	Power Supply:	AC 120V/60Hz
Test Mode:	802.11g Channel Low 2412MHz	Test Engineer:	Pei

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
-	-	-	-	-	-	-	-	-	-	Vertical
-	-	-	-	-	-	-	-	-	-	Horizontal

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$
3. Display the measurement of peak values.

Date of Test:	January 18, 2012	Temperature:	25°C
EUT:	MID	Humidity:	50%
Model No.:	GN32	Power Supply:	AC 120V/60Hz
Test Mode:	802.11g Channel High 2462MHz	Test Engineer:	Pei

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
-	-	-	-	-	-	-	-	-	-	Vertical
-	-	-	-	-	-	-	-	-	-	Horizontal

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:
Result = Reading + Corrected Factor
3. Display the measurement of peak values.

Date of Test:	January 18, 2012	Temperature:	25°C
EUT:	MID	Humidity:	50%
Model No.:	GN32	Power Supply:	AC 120V/60Hz
Test Mode:	802.11n Channel Low 2412MHz	Test Engineer:	Pei

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
-	-	-	-	-	-	-	-	-	-	Vertical
-	-	-	-	-	-	-	-	-	-	Horizontal

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$
3. Display the measurement of peak values.

Date of Test:	January 18, 2012	Temperature:	25°C
EUT:	MID	Humidity:	50%
Model No.:	GN32	Power Supply:	AC 120V/60Hz
Test Mode:	802.11n Channel High 2462MHz	Test Engineer:	Pei

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
-	-	-	-	-	-	-	-	-	-	Vertical
-	-	-	-	-	-	-	-	-	-	Horizontal

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:
Result = Reading + Corrected Factor
3. Display the measurement of peak values.


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1833

Standard: FCC Part 15 PEAK 2.4G

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: MID

Mode: TX Channel 1 (802.11b)

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 2012/01/18

Time: 23:15:17

Engineer Signature: Bob

Distance:

Note: Report No.:ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1832

Standard: FCC Part 15 PEAK 2.4G

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: MID

Mode: TX Channel 1 (802.11b)

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2012/01/18

Time: 23:11:09

Engineer Signature: Bob

Distance:

Note: Report No.:ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Bob #1830
Standard: FCC Part 15 PEAK 2.4G
Test item: Radiation Test
Temp.(C)/Hum.(%) 24 C / 48 %
EUT: MID
Mode: TX Channel 11 (802.11b)
Model: GN32
Manufacturer: Leader Digital-tech Weitong

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 2012/01/18
Time: 23:05:45
Engineer Signature: Bob
Distance:

Note: Report No.:ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Bob #1831

Standard: FCC Part 15 PEAK 2.4G

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: MID

Mode: TX Channel 11 (802.11b)

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2012/01/18

Time: 23:07:21

Engineer Signature: Bob

Distance:

Note: Report No.:ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Bob #1826	Polarization: Horizontal
Standard: FCC Part 15 PEAK 2.4G	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2012/01/18
Temp.(C)/Hum.(%) 24 C / 48 %	Time: 22:55:09
EUT: MID	Engineer Signature: Bob
Mode: TX Channel 1 (802.11g)	Distance:
Model: GN32	
Manufacturer: Leader Digital-tech Weitong	

Note: Report No.:ATE20120034




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1827

Standard: FCC Part 15 PEAK 2.4G

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: MID

Mode: TX Channel 1 (802.11g)

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2012/01/18

Time: 22:56:35

Engineer Signature: Bob

Distance:

Note: Report No.:ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1829

Standard: FCC Part 15 PEAK 2.4G

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: MID

Mode: TX Channel 11 (802.11g)

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 2012/01/18

Time: 23:01:23

Engineer Signature: Bob

Distance:

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1828

Standard: FCC Part 15 PEAK 2.4G

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: MID

Mode: TX Channel 11 (802.11g)

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2012/01/18

Time: 23:00:19

Engineer Signature: Bob

Distance:

Note: Report No.:ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1822

Standard: FCC Part 15 PEAK 2.4G

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: MID

Mode: TX Channel 1 (802.11n)

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 2012/01/18

Time: 22:42:51

Engineer Signature: Bob

Distance:

Note: Report No.:ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1823

Standard: FCC Part 15 PEAK 2.4G

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: MID

Mode: TX Channel 1 (802.11n)

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2012/01/18

Time: 22:44:01

Engineer Signature: Bob

Distance:

Note: Report No.:ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Bob #1825	Polarization: Horizontal
Standard: FCC Part 15 PEAK 2.4G	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2012/01/18
Temp.(C)/Hum.(%) 24 C / 48 %	Time: 22:50:06
EUT: MID	Engineer Signature: Bob
Mode: TX Channel 11 (802.11n)	Distance:
Model: GN32	
Manufacturer: Leader Digital-tech Weitong	

Note: Report No.:ATE20120034




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1824

Standard: FCC Part 15 PEAK 2.4G

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: MID

Mode: TX Channel 11 (802.11n)

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2012/01/18

Time: 22:48:57

Engineer Signature: Bob

Distance:

Note: Report No.:ATE20120034




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------

9. RADIATED SPURIOUS EMISSION TEST

9.1. Block Diagram of Test Setup


9.1.1. Block diagram of connection between the EUT and peripherals



Setup: Transmitting mode

(EUT: MID)

9.1.2. Semi-Anechoic Chamber Test Setup Diagram



9.2.The Limit For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

9.3.Restricted bands of operation

9.3.1.FCC Part 15.205 Restricted bands of operation

(a) Except as shown in paragraph (d) of this section, Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

¹Until February 1, 1999, this restricted band shall be 0.490-0.510

²Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emission appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000MHz, Compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

9.4.Configuration of EUT on Measurement

The following equipment are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

9.4.1.MID (EUT)

Model Number : GN32
 Serial Number : N/A
 Manufacturer : Shenzhen Leader Digital-tech Weitong Co., Ltd.

9.5.Operating Condition of EUT

9.5.1.Setup the EUT and simulator as shown as Section 9.1.

9.5.2.Turn on the power of all equipment.

9.5.3.Let the EUT work in TX modes measure it. The transmit frequency are 2412-2462MHz. We select 2412MHz, 2437MHz, 2462MHz TX frequency to transmit.

9.6.Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4: 2003 on radiated emission measurement. The EUT was tested in 3 orthogonal planes. The worst-case data rate for this channel to be 1Mbps for 802.11b mode and 6Mbps for 802.11g mode, based on previous with 802.11 WLAN product design architectures.

The bandwidth of test receiver (R&S ESI26) is set at 120kHz in 30-1000MHz. and set at 1MHz in above 1000MHz.

The frequency range from 30MHz to 25000MHz is checked.

The final measurement in band 9-90kHz, 110-490kHz and above 1000MHz is performed with Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.

The field strength is calculated by adding the antenna factor, and cable loss, and subtracting the amplifier gain from the measured reading. The basic equation calculation is as follows:

Result = Reading + Corrected Factor

Where Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

9.7.The Field Strength of Radiation Emission Measurement Results

PASS.

Date of Test:	January 18, 2012	Temperature:	25°C
EUT:	MID	Humidity:	50%
Model No.:	GN32	Power Supply:	AC 120V/60Hz
Test Mode:	802.11b Channel Low 2412MHz	Test Engineer:	Pei

For 30MHz-1000MHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading (dBμV/m)	Factor Corr. (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
153.9254	25.27	14.56	39.83	43.50	-3.67	Vertical
218.1194	24.12	16.63	40.75	46.00	-5.25	Vertical
500.1302	17.20	23.99	41.19	46.00	-4.81	Vertical
153.9254	24.19	14.56	38.75	43.50	-4.75	Horizontal
192.9837	22.62	16.04	38.66	43.50	-4.84	Horizontal
278.3546	21.98	18.28	40.26	46.00	-5.74	Horizontal

For 1GHz-25GHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading(dBμV/m)		Factor Corr. (dB)	Result(dBμV/m)		Limit(dBμV/m)		Margin(dBμV/m)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
-	-	-	-	-	-	-	-	-	-	Vertical
-	-	-	-	-	-	-	-	-	-	Horizontal

Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.

2. *: Denotes restricted band of operation.

Date of Test:	January 18, 2012	Temperature:	25°C
EUT:	MID	Humidity:	50%
Model No.:	GN32	Power Supply:	AC 120V/60Hz
Test Mode:	802.11b Channel Middle 2437MHz	Test Engineer:	Pei

For 30MHz-1000MHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading (dBμV/m)	Factor Corr. (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
168.0540	24.53	14.70	39.23	43.50	-4.27	Vertical
182.9379	24.25	15.87	40.12	43.50	-3.38	Vertical
694.4673	15.08	26.44	41.52	46.00	-4.48	Vertical
208.4701	23.70	16.29	39.99	43.50	-3.51	Horizontal
218.1194	24.21	16.63	40.84	46.00	-5.16	Horizontal
236.3095	23.18	16.80	39.98	46.00	-6.02	Horizontal

For 1GHz-25GHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading(dBμV/m)		Factor Corr. (dB)	Result(dBμV/m)		Limit(dBμV/m)		Margin(dBμV/m)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
-	-	-	-	-	-	-	-	-	-	Vertical
-	-	-	-	-	-	-	-	-	-	Horizontal

Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.**2. *: Denotes restricted band of operation.**

Date of Test:	January 18, 2012	Temperature:	25°C
EUT:	MID	Humidity:	50%
Model No.:	GN32	Power Supply:	AC 120V/60Hz
Test Mode:	802.11b Channel High 2462MHz	Test Engineer:	Pei

For 30MHz-1000MHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading (dBμV/m)	Factor Corr. (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
172.1887	23.26	15.17	38.43	43.50	-5.07	Vertical
236.3095	21.73	16.50	38.23	46.00	-7.77	Vertical
555.2269	14.27	25.33	39.60	46.0	-6.40	Vertical
183.9379	24.02	15.98	40.00	43.50	-3.50	Horizontal
218.1194	23.35	16.63	39.98	46.00	-6.02	Horizontal
694.4763	14.18	26.44	40.62	46.00	-5.38	Horizontal

For 1GHz-25GHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading(dBμV/m)		Factor Corr. (dB)	Result(dBμV/m)		Limit(dBμV/m)		Margin(dBμV/m)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
-	-	-	-	-	-	-	-	-	-	Vertical
-	-	-	-	-	-	-	-	-	-	Horizontal

Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.**2. *: Denotes restricted band of operation.**

Date of Test:	January 18, 2012	Temperature:	25°C
EUT:	MID	Humidity:	50%
Model No.:	GN32	Power Supply:	AC 120V/60Hz
Test Mode:	802.11g Channel Low 2412MHz	Test Engineer:	Pei

For 30MHz-1000MHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading (dBμV/m)	Factor Corr. (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
172.7878	25.16	15.30	40.46	43.50	-3.04	Vertical
193.7838	24.15	16.10	40.25	43.50	-3.25	Vertical
669.6023	16.23	26.13	42.36	46.00	-3.64	Vertical
192.7838	22.55	16.04	38.59	43.50	-4.91	Horizontal
209.9259	23.15	16.35	39.50	43.50	-4.00	Horizontal
646.4529	14.11	26.06	40.17	46.00	-5.83	Horizontal

For 1GHz-25GHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading(dBμV/m)		Factor Corr. (dB)	Result(dBμV/m)		Limit(dBμV/m)		Margin(dBμV/m)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
-	-	-	-	-	-	-	-	-	-	Vertical
-	-	-	-	-	-	-	-	-	-	Horizontal

Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.**2. *: Denotes restricted band of operation.**

Date of Test:	January 18, 2012	Temperature:	25°C
EUT:	MID	Humidity:	50%
Model No.:	GN32	Power Supply:	AC 120V/60Hz
Test Mode:	802.11g Channel Middle 2437MHz	Test Engineer:	Pei

For 30MHz-1000MHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading (dBμV/m)	Factor Corr. (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
169.2247	25.08	14.71	39.79	43.50	-3.71	Vertical
183.2379	24.16	15.87	40.03	43.50	-3.47	Vertical
622.2167	14.24	26.06	40.30	46.00	-5.70	Vertical
193.2383	23.22	16.04	39.26	43.50	-4.24	Horizontal
211.0924	23.25	16.39	39.64	43.50	-3.86	Horizontal
693.5763	15.23	26.43	41.66	46.00	-4.34	Horizontal

For 1GHz-25GHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading(dBμV/m)		Factor Corr. (dB)	Result(dBμV/m)		Limit(dBμV/m)		Margin(dBμV/m)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
-	-	-	-	-	-	-	-	-	-	Vertical
-	-	-	-	-	-	-	-	-	-	Horizontal

Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.**2. *: Denotes restricted band of operation.**

Date of Test:	January 18, 2012	Temperature:	25°C
EUT:	MID	Humidity:	50%
Model No.:	GN32	Power Supply:	AC 120V/60Hz
Test Mode:	802.11g Channel High 2462MHz	Test Engineer:	Pei

For 30MHz-1000MHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading (dBμV/m)	Factor Corr. (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
178.2744	24.02	15.77	39.79	43.50	-3.71	Vertical
279.3546	21.17	18.28	39.45	46.00	-6.55	Vertical
576.9882	15.09	25.38	40.47	46.00	-5.53	Vertical
163.3206	25.03	14.64	39.67	43.50	-3.83	Horizontal
218.1194	23.10	16.63	39.73	46.00	-6.27	Horizontal
683.8260	14.17	26.36	40.53	46.00	-5.74	Horizontal

For 1GHz-25GHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading(dBμV/m)		Factor Corr. (dB)	Result(dBμV/m)		Limit(dBμV/m)		Margin(dBμV/m)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
-	-	-	-	-	-	-	-	-	-	Vertical
-	-	-	-	-	-	-	-	-	-	Horizontal

Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.**2. *: Denotes restricted band of operation.**

Date of Test:	January 18, 2012	Temperature:	25°C
EUT:	MID	Humidity:	50%
Model No.:	GN32	Power Supply:	AC 120V/60Hz
Test Mode:	802.11n Channel Low 2412MHz	Test Engineer:	Pei

For 30MHz-1000MHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading (dBμV/m)	Factor Corr. (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
191.7732	23.27	16.06	39.33	43.50	-4.17	Vertical
214.3557	24.28	16.51	40.79	43.50	-2.71	Vertical
513.1487	18.00	24.09	42.09	46.00	-3.91	Vertical
154.6254	24.38	14.56	38.94	43.50	-4.56	Horizontal
193.7838	23.21	16.03	39.24	43.50	-4.26	Horizontal
710.6941	14.23	26.83	41.15	46.00	-4.85	Horizontal

14.32**For 1GHz-25GHz**

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading(dBμV/m)		Factor Corr. (dB)	Result(dBμV/m)		Limit(dBμV/m)		Margin(dBμV/m)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
-	-	-	-	-	-	-	-	-	-	Vertical
-	-	-	-	-	-	-	-	-	-	Horizontal

Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.**2. *: Denotes restricted band of operation.**

Date of Test:	January 18, 2012	Temperature:	25°C
EUT:	MID	Humidity:	50%
Model No.:	GN32	Power Supply:	AC 120V/60Hz
Test Mode:	802.11n Channel Middle 2437MHz	Test Engineer:	Pei

For 30MHz-1000MHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading (dBμV/m)	Factor Corr. (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
170.5919	25.11	14.84	39.95	43.50	-3.55	Vertical
183.9379	24.24	15.90	40.14	43.50	-3.36	Vertical
236.3095	25.16	16.50	41.66	46.00	-4.34	Vertical
193.7838	23.17	16.03	39.20	43.50	-4.30	Horizontal
218.1194	24.35	16.63	40.98	46.00	-5.02	Horizontal
385.1960	19.22	21.72	40.94	46.00	-5.06	Horizontal

For 1GHz-25GHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading(dBμV/m)		Factor Corr. (dB)	Result(dBμV/m)		Limit(dBμV/m)		Margin(dBμV/m)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
-	-	-	-	-	-	-	-	-	-	Vertical
-	-	-	-	-	-	-	-	-	-	Horizontal

Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.**2. *: Denotes restricted band of operation.**

Date of Test:	January 18, 2012	Temperature:	25°C
EUT:	MID	Humidity:	50%
Model No.:	GN32	Power Supply:	AC 120V/60Hz
Test Mode:	802.11n Channel High 2462MHz	Test Engineer:	Pei

For 30MHz-1000MHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading (dBμV/m)	Factor Corr. (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
153.9254	25.62	14.56	40.18	43.50	-3.32	Vertical
170.9919	25.46	14.93	40.39	43.50	-3.11	Vertical
465.2561	17.57	23.43	41.00	46.00	-5.00	Vertical
210.6579	24.10	16.37	40.47	43.50	-3.03	Horizontal
324.5896	21.14	19.53	40.67	46.00	-5.33	Horizontal
554.2269	16.20	25.32	41.52	46.00	-4.48	Horizontal

For 1GHz-25GHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading(dBμV/m)		Factor Corr. (dB)	Result(dBμV/m)		Limit(dBμV/m)		Margin(dBμV/m)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
-	-	-	-	-	-	-	-	-	-	Vertical
-	-	-	-	-	-	-	-	-	-	Horizontal

Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.**2. *: Denotes restricted band of operation.**


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1484

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: MID

Mode: TX Channel 1 (802.11b)

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 2012/01/18

Time: 8/32/23

Engineer Signature: Bob

Distance: 3m

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	153.9254	24.19	14.56	38.75	43.50	-4.75	QP			
2	192.9837	22.62	16.04	38.66	43.50	-4.84	QP			
3	278.3546	21.98	18.28	40.26	48.00	-5.74	QP			


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 966 chamber
 Tel:+86-0755-28503290
 Fax:+86-0755-28503396

Job No.: Bob #1485

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: MID

Mode: TX Channel 1 (802.11b)

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2012/01/18

Time: 8/32/50

Engineer Signature: Bob

Distance: 3m

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	153.9254	25.27	14.56	39.83	43.50	-3.67	QP			
2	218.1194	24.12	16.63	40.75	46.00	-5.25	QP			
3	500.1302	17.20	23.99	41.19	46.00	-4.81	QP			


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #625

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: MID

Mode: TX Channel 1 (802.11b)

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 2012/01/18

Time: 16:57:41

Engineer Signature: Bob

Distance: 3m

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Bob #626
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 24 C / 48 %
EUT: MID
Mode: TX Channel 1 (802.11b)
Model: GN32
Manufacturer: Leader Digital-tech Weitong

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 2012/01/18
Time: 16:59:09
Engineer Signature: Bob
Distance: 3m

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 968 chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

 Job No.: Bob #1545
 Standard: FCC Class B 3M Radiated
 Test item: Radiation Test
 Temp.(C)/Hum.(%) 25 C / 50 %
 EUT: MID
 Mode: TX Channel 1 (802.11b)
 Model: GN32
 Manufacturer: Leader Digital-tech Weitong

 Polarization: Horizontal
 Power Source: AC 120V/60Hz
 Date: 2012/01/18
 Time: 14:57:50
 Engineer Signature: Bob
 Distance: 3m

Note: Report No.:ATE20120034




ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 988 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503398

Job No.: Bob #1548

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 50 %

EUT: MID

Mode: TX Channel 1 (802.11b)

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2012/01/18

Time: 15:01:26

Engineer Signature: Bob

Distance: 3m

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 986 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1487

Polarization: Horizontal

Standard: FCC Class B 3M Radiated

Power Source: AC 120V/60Hz

Test item: Radiation Test

Date: 2012/01/18

Temp.(C)/Hum.(%) 24 C / 48 %

Time: 8/34/46

EUT: MID

Engineer Signature: Bob


Mode: TX Channel 6 (802.11b)

Distance: 3m

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	208.4701	23.70	16.29	39.99	43.50	-3.51	QP			
2	218.1194	24.21	16.63	40.84	46.00	-5.16	QP			
3	236.3095	23.18	16.80	39.98	46.00	-6.02	QP			


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

 Job No.: Bob #1486
 Standard: FCC Class B 3M Radiated
 Test item: Radiation Test
 Temp.(C)/Hum.(%) 24 C / 48 %
 EUT: MID
 Mode: TX Channel 8 (802.11b)
 Model: GN32
 Manufacturer: Leader Digital-tech Weitong

 Polarization: Vertical
 Power Source: AC 120V/60Hz
 Date: 2012/01/18
 Time: 8/34/00
 Engineer Signature: Bob
 Distance: 3m

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	168.0540	24.53	14.70	39.23	43.50	-4.27	QP			
2	182.9379	24.25	15.87	40.12	43.50	-3.38	QP			
3	604.4763	15.08	26.44	41.52	48.00	-4.48	QP			


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #628
 Standard: FCC Class B 3M Radiated
 Test item: Radiation Test
 Temp.(C)/Hum.(%) 24 C / 48 %
 EUT: MID
 Mode: TX Channel 6 (802.11b)
 Model: GN32
 Manufacturer: Leader Digital-tech Weitong

Polarization: Horizontal
 Power Source: AC 120V/60Hz
 Date: 2012/01/18
 Time: 17:02:45
 Engineer Signature: Bob
 Distance: 3m

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #627

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: MID

Mode: TX Channel 6 (802.11b)

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2012/01/18

Time: 17:01:23

Engineer Signature: Bob

Distance: 3m

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1548

Polarization: Horizontal

Standard: FCC Class B 3M Radiated

Power Source: AC 120V/60Hz

Test item: Radiation Test

Date: 2012/01/18

Temp.(C)/Hum.(%) 25 C / 50 %

Time: 15:09:14

EUT: MID

Engineer Signature: Bob


Mode: TX Channel 6 (802.11b)

Distance: 3m

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China


Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1547	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2012/01/18
Temp.(C)/Hum.(%) 25 C / 50 %	Time: 15:05:40
EUT: MID	Engineer Signature: Bob
Mode: TX Channel 6 (802.11b)	Distance: 3m
Model: GN32	
Manufacturer: Leader Digital-tech Weitong	

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

 Job No.: Bob #1488
 Standard: FCC Class B 3M Radiated
 Test item: Radiation Test
 Temp.(C)/Hum.(%) 24 C / 48 %
 EUT: MID
 Mode: TX Channel 11 (802.11b)
 Model: GN32
 Manufacturer: Leader Digital-tech Weitong

 Polarization: Horizontal
 Power Source: AC 120V/60Hz
 Date: 2012/01/18
 Time: 8/35/26
 Engineer Signature: Bob
 Distance: 3m

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	183.9379	24.02	15.98	40.00	43.50	-3.50	QP			
2	218.1194	23.35	16.63	39.98	46.00	-6.02	QP			
3	694.4763	14.18	26.44	40.62	46.00	-5.38	QP			


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 986 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1489

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: MID

Mode: TX Channel 11 (802.11b)

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2012/01/18

Time: 8/35/56

Engineer Signature: Bob

Distance: 3m

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	172.1887	23.26	15.17	38.43	43.50	-5.07	QP			
2	236.3095	21.73	16.50	38.23	46.00	-7.77	QP			
3	555.2269	14.27	25.33	39.60	46.00	-6.40	QP			


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #629

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: MID

Mode: TX Channel 11(802.11b)

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 2012/01/18

Time: 17:04:06

Engineer Signature: Bob

Distance: 3m

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #630

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: MID

Mode: TX Channel 11 (802.11b)

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2012/01/18

Time: 17:05:28

Engineer Signature: Bob

Distance: 3m

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1549

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 50 %

EUT: MID

Mode: TX Channel 11 (802.11b)

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 2012/01/18

Time: 15:13:25

Engineer Signature: Bob

Distance: 3m

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1550

Polarization: Vertical

Standard: FCC Class B 3M Radiated

Power Source: AC 120V/60Hz

Test item: Radiation Test

Date: 2012/01/18

Temp.(C)/Hum.(%) 25 C / 50 %

Time: 15:16:58

EUT: MID

Engineer Signature: Bob


Mode: TX Channel 11 (802.11b)

Distance: 3m

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1495

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: MID

Mode: TX Channel 1 (802.11g)

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 2012/01/18

Time: 8/39/44

Engineer Signature: Bob

Distance: 3m

Note: Report No.:ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	192.7838	22.55	16.04	38.59	43.50	-4.91	QP			
2	209.9259	23.15	16.35	39.50	43.50	-4.00	QP			
3	646.4529	14.11	26.06	40.17	46.00	-5.83	QP			


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

 Job No.: Bob #1494
 Standard: FCC Class B 3M Radiated
 Test item: Radiation Test
 Temp.(C)/Hum.(%) 24 C / 48 %
 EUT: MID
 Mode: TX Channel 1 (802.11g)
 Model: GN32
 Manufacturer: Leader Digital-tech Weitong

 Polarization: Vertical
 Power Source: AC 120V/60Hz
 Date: 2012/01/18
 Time: 8/39/04
 Engineer Signature: Bob
 Distance: 3m

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	172.7878	25.16	15.30	40.46	43.50	-3.04	QP			
2	193.7838	24.15	16.10	40.25	43.50	-3.25	QP			
3	669.6023	16.23	26.13	42.36	46.00	-3.64	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #632
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 24 C / 48 %
EUT: MID
Mode: TX Channel 1 (802.11g)
Model: GN32
Manufacturer: Leader Digital-tech Weitong

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 2012/01/18
Time: 17:08:29
Engineer Signature: Bob
Distance: 3m

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #631

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: MID

Mode: TX Channel 1 (802.11g)

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2012/01/18

Time: 17:07:02

Engineer Signature: Bob

Distance: 3m

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 986 chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

 Job No.: Bob #1552
 Standard: FCC Class B 3M Radiated
 Test item: Radiation Test
 Temp.(C)/Hum.(%) 25 C / 50 %
 EUT: MID
 Mode: TX Channel 1 (802.11g)
 Model: GN32
 Manufacturer: Leader Digital-tech Weitong

 Polarization: Horizontal
 Power Source: AC 120V/60Hz
 Date: 2012/01/18
 Time: 15:26:21
 Engineer Signature: Bob
 Distance: 3m

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 986 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1551

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 50 %

EUT: MID

Mode: TX Channel 1 (802.11g)

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2012/01/18

Time: 15:22:48

Engineer Signature: Bob

Distance: 3m

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

 Job No.: Bob #1492
 Standard: FCC Class B 3M Radiated
 Test item: Radiation Test
 Temp.(C)/Hum.(%) 24 C / 48 %
 EUT: MID
 Mode: TX Channel 6 (802.11g)
 Model: GN32
 Manufacturer: Leader Digital-tech Weitong

 Polarization: Horizontal
 Power Source: AC 120V/60Hz
 Date: 2012/01/18
 Time: 8/38/08
 Engineer Signature: Bob
 Distance: 3m

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	193.2838	23.22	16.04	39.26	43.50	-4.24	QP			
2	211.0924	23.25	16.39	39.64	43.50	-3.86	QP			
3	693.5763	15.23	26.43	41.66	48.00	-4.34	QP			


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

 Job No.: Bob #1493
 Standard: FCC Class B 3M Radiated
 Test item: Radiation Test
 Temp.(C)/Hum.(%) 24 C / 48 %
 EUT: MID
 Mode: TX Channel 6 (802.11g)
 Model: GN32
 Manufacturer: Leader Digital-tech Weitong

 Polarization: Vertical
 Power Source: AC 120V/60Hz
 Date: 2012/01/18
 Time: 8/38/39
 Engineer Signature: Bob
 Distance: 3m

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	169.2247	25.08	14.71	39.79	43.50	-3.71	QP			
2	183.2379	24.16	15.87	40.03	43.50	-3.47	QP			
3	622.2167	14.24	26.06	40.30	46.00	-5.70	QP			


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #633

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: MID

Mode: TX Channel 6 (802.11g)

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 2012/01/18

Time: 17:09:55

Engineer Signature: Bob

Distance: 3m

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #634

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: MID

Mode: TX Channel 6 (802.11g)

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2012/01/18

Time: 17:11:15

Engineer Signature: Bob

Distance: 3m

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

 F1.Bldg.A, Changyuan New Material Port Keyuan Rd,
 Science & Industry Park, Nanshan Shenzhen, P.R.China

Site: 986 chamber


Tel: +86-0755-26503290

Fax: +86-0755-26503396

 Job No.: Bob #1553
 Standard: FCC Class B 3M Radiated
 Test item: Radiation Test
 Temp.(C)/Hum.(%) 25 C / 50 %
 EUT: MID
 Mode: TX Channel 8 (802.11g)
 Model: GN32
 Manufacturer: Leader Digital-tech Weitong

 Polarization: Horizontal
 Power Source: AC 120V/60Hz
 Date: 2012/01/18
 Time: 15:30:38
 Engineer Signature: Bob
 Distance: 3m

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1554

Polarization: Vertical

Standard: FCC Class B 3M Radiated

Power Source: AC 120V/60Hz

Test item: Radiation Test

Date: 2012/01/18

Temp.(C)/Hum.(%) 25 C / 50 %

Time: 15:34:11

EUT: MID

Engineer Signature: Bob


Mode: TX Channel 6 (802.11g)

Distance: 3m

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 986 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1491

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: MID

Mode: TX Channel 11 (802.11g)

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 2012/01/18

Time: 8/37/27

Engineer Signature: Bob

Distance: 3m

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	163.3206	25.03	14.64	39.67	43.50	-3.83	QP			
2	218.1194	23.10	16.63	39.73	46.00	-6.27	QP			
3	683.8260	14.17	26.36	40.53	46.00	-5.47	QP			


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1490
 Standard: FCC Class B 3M Radiated
 Test item: Radiation Test
 Temp.(C)/Hum.(%) 24 C / 48 %
 EUT: MID
 Mode: TX Channel 11 (802.11g)
 Model: GN32
 Manufacturer: Leader Digital-tech Weitong

Polarization: Vertical
 Power Source: AC 120V/60Hz
 Date: 2012/01/18
 Time: 8/36/41
 Engineer Signature: Bob
 Distance: 3m

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	178.2744	24.02	15.77	39.79	43.50	-3.71	QP			
2	279.3546	21.17	18.28	39.45	46.00	-6.55	QP			
3	576.9882	15.09	25.38	40.47	46.00	-5.53	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #636

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: MID

Mode: TX Channel 11(802.11g)

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 2012/01/18

Time: 17:14:05

Engineer Signature: Bob

Distance: 3m

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Bob #635	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2012/01/18
Temp.(C)/Hum.(%) 24 C / 48 %	Time: 17:12:46
EUT: MID	Engineer Signature: Bob
Mode: TX Channel 11 (802.11g)	Distance: 3m
Model: GN32	
Manufacturer: Leader Digital-tech Weitong	

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

 Job No.: Bob #1558
 Standard: FCC Class B 3M Radiated
 Test item: Radiation Test
 Temp.(C)/Hum.(%) 25 C / 50 %
 EUT: MID
 Mode: TX Channel 11 (802.11g)
 Model: GN32
 Manufacturer: Leader Digital-tech Weitong

 Polarization: Horizontal
 Power Source: AC 120V/60Hz
 Date: 2012/01/18
 Time: 15:41:59
 Engineer Signature: Bob
 Distance: 3m

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

 Job No.: Bob #1555
 Standard: FCC Class B 3M Radiated
 Test item: Radiation Test
 Temp.(C)/Hum.(%) 25 C / 50 %
 EUT: MID
 Mode: TX Channel 11 (802.11g)
 Model: GN32
 Manufacturer: Leader Digital-tech Weitong

 Polarization: Vertical
 Power Source: AC 120V/60Hz
 Date: 2012/01/18
 Time: 15:38:24
 Engineer Signature: Bob
 Distance: 3m

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

 F1.Bldg.A, Changyuan New Material Port Keyuan Rd,
 Science & Industry Park, Nanshan Shenzhen, P.R.China

Site: 966 chamber

Tel: +86-0755-26503290

Fax: +86-0755-26503396

Job No.: Bob #1498

Polarization: Horizontal

Standard: FCC Class B 3M Radiated

Power Source: AC 120V/60Hz

Test item: Radiation Test

Date: 2012/01/18

Temp.(C)/Hum.(%) 24 C / 48 %

Time: 8/40/36

EUT: MID

Engineer Signature: Bob


Mode: TX Channel 1 (802.11n)

Distance: 3m

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	154.6254	24.38	14.56	38.94	43.50	-4.56	QP			
2	193.7838	23.21	16.03	39.24	43.50	-4.26	QP			
3	710.6941	14.32	26.83	41.15	46.00	-4.85	QP			


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1497

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: MID

Mode: TX Channel 1 (802.11n)

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2012/01/18

Time: 8/41/24

Engineer Signature: Bob

Distance: 3m

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	191.7732	23.27	16.06	39.33	43.50	-4.17	QP			
2	214.3557	24.28	16.51	40.79	43.50	-2.71	QP			
3	513.1487	18.00	24.09	42.09	46.00	-3.91	QP			


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #637

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: MID

Mode: TX Channel 1 (802.11n)

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 2012/01/18

Time: 17:15:43

Engineer Signature: Bob

Distance: 3m

Note: Report No.: ATE20120034





ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Bob #638
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 24 C / 48 %
EUT: MID
Mode: TX Channel 1 (802.11n)
Model: GN32
Manufacturer: Leader Digital-tech Weitong

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 2012/01/18
Time: 17:17:01
Engineer Signature: Bob
Distance: 3m

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 988 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503398

Job No.: Bob #1562
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 24 C / 48 %
EUT: MID
Mode: TX Channel 1 (802.11n)
Model: GN32
Manufacturer: Leader Digital-tech Weitong

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 2012/01/18
Time: 15:55:57
Engineer Signature: Bob
Distance:

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 986 chamber

Tel:+86-0755-28503290

Fax:+86-0755-28503396

Job No.: Bob #1563

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: MID

Mode: TX Channel 1 (802.11n)

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2012/01/18

Time: 15:57:43

Engineer Signature: Bob

Distance:

Note: Report No.: ATE20120034




ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 986 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1499

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: MID

Mode: TX Channel 6 (802.11n)

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 2012/01/18

Time: 8/43/12

Engineer Signature: Bob

Distance: 3m

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	193.7838	23.17	16.03	39.20	43.50	-4.30	QP			
2	218.1194	24.35	16.63	40.98	46.00	-5.02	QP			
3	385.1960	19.22	21.72	40.94	46.00	-5.06	QP			


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1498

Polarization: Vertical

Standard: FCC Class B 3M Radiated

Power Source: AC 120V/60Hz

Test item: Radiation Test

Date: 2012/01/18

Temp.(C)/Hum.(%) 24 C / 48 %

Time: 8/41/47

EUT: MID

Engineer Signature: Bob


Mode: TX Channel 6 (802.11n)

Distance: 3m

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	170.5919	25.11	14.84	39.95	43.50	-3.55	QP			
2	183.9379	24.24	15.90	40.14	43.50	-3.36	QP			
3	236.3095	25.16	16.50	41.66	46.00	-4.34	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #640
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 24 C / 48 %
EUT: MID
Mode: TX Channel 6 (802.11n)
Model: GN32
Manufacturer: Leader Digital-tech Weitong

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 2012/01/18
Time: 17:20:01
Engineer Signature: Bob
Distance: 3m

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Bob #639
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 24 C / 48 %
EUT: MID
Mode: TX Channel 6 (802.11n)
Model: GN32
Manufacturer: Leader Digital-tech Weitong

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 2012/01/18
Time: 17:18:48
Engineer Signature: Bob
Distance: 3m

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China


Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1561	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2012/01/18
Temp.(C)/Hum.(%) 24 C / 48 %	Time: 15:53:01
EUT: MID	Engineer Signature: Bob
Mode: TX Channel 8 (802.11n)	Distance:
Model: GN32	
Manufacturer: Leader Digital-tech Weitong	

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 986 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1560

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: MID

Mode: TX Channel B (802.11n)

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2012/01/18

Time: 15:51:02

Engineer Signature: Bob

Distance:

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1500

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: MID

Mode: TX Channel 11 (802.11n)

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 2012/01/18

Time: 8/43/35

Engineer Signature: Bob

Distance: 3m

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	210.6579	24.10	16.37	40.47	43.50	-3.03	QP			
2	324.5896	21.14	19.53	40.67	46.00	-5.33	QP			
3	554.2269	18.20	25.32	41.52	46.00	-4.48	QP			


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1501

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: MID

Mode: TX Channel 11 (802.11n)

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2012/01/18

Time: 8/44/12

Engineer Signature: Bob

Distance: 3m

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	153.9254	25.62	14.56	40.18	43.50	-3.32	QP			
2	170.9919	25.46	14.93	40.39	43.50	-3.11	QP			
3	465.2561	17.57	23.43	41.00	46.00	-5.00	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #637

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: MID

Mode: TX Channel 1 (802.11n)

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 2012/01/18

Time: 17:15:43

Engineer Signature: Bob

Distance: 3m

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #638

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: MID

Mode: TX Channel 1 (802.11n)

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2012/01/18

Time: 17:17:01

Engineer Signature: Bob

Distance: 3m

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 986 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1562

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: MID

Mode: TX Channel 1 (802.11n)

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 2012/01/18

Time: 15:55:57

Engineer Signature: Bob

Distance:

Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 986 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1563

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: MID

Mode: TX Channel 1 (802.11n)

Model: GN32

Manufacturer: Leader Digital-tech Weitong

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2012/01/18

Time: 15:57:43

Engineer Signature: Bob

Distance:


Note: Report No.: ATE20120034



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------

10.CONDUCTED SPURIOUS EMISSION COMPLIANCE TEST

10.1.Block Diagram of Test Setup



10.2.The Requirement For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

10.3.EUT Configuration on Measurement

The following equipment is installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

10.3.1.MID (EUT)

Model Number	:	GN32
Serial Number	:	N/A
Manufacturer	:	Shenzhen Leader Digital-tech Weitong Co., Ltd.

10.4.Operating Condition of EUT

10.4.1.Setup the EUT and simulator as shown as Section 10.1.

10.4.2.Turn on the power of all equipment.

10.4.3.Let the EUT work in TX modes measure it. The transmit frequency are 2412-2462MHz. We select 2412MHz, 2437MHz, 2462MHz TX frequency to transmit.

10.5.Test Procedure

10.5.1.The transmitter output was connected to the spectrum analyzer via a low loss cable.

10.5.2.Set RBW of spectrum analyzer to 100kHz and VBW to 300kHz.


10.5.3.The Conducted Spurious Emission was measured and recorded.

10.6.Test Result


Pass.

The spectrum analyzer plots are attached as below.


TX 802.11b Channel Low 2412MHz (30MHz-1GHz)




TX 802.11b Channel Low 2412MHz (1GHz-5GHz)




TX 802.11b Channel Low 2412MHz (5GHz-10GHz)




TX 802.11b Channel Low 2412MHz (10GHz-15GHz)




TX 802.11b Channel Low 2412MHz (15GHz-20GHz)




TX 802.11b Channel Low 2412MHz (20GHz-25GHz)




TX 802.11b Channel Middle 2437MHz (30MHz-1GHz)




TX 802.11b Channel Middle 2437MHz (1GHz-5GHz)




TX 802.11b Channel Middle 2437MHz (5GHz-10GHz)




TX 802.11b Channel Middle 2437MHz (10GHz-15GHz)




TX 802.11b Channel Middle 2437MHz (15GHz-20GHz)




TX 802.11b Channel Middle 2437MHz (20GHz-25GHz)




TX 802.11b Channel High 2462MHz (30MHz-1GHz)




TX 802.11b Channel High 2462MHz (1GHz-5GHz)




TX 802.11b Channel High 2462MHz (5GHz-10GHz)




TX 802.11b Channel High 2462MHz (10GHz-15GHz)




TX 802.11b Channel High 2462MHz (15GHz-20GHz)




TX 802.11b Channel High 2462MHz (20GHz-25GHz)




TX 802.11g Channel Low 2412MHz (30MHz-1GHz)




TX 802.11g Channel Low 2412MHz (1GHz-5GHz)




TX 802.11g Channel Low 2412MHz (5GHz-10GHz)




TX 802.11g Channel Low 2412MHz (10GHz-15GHz)




TX 802.11g Channel Low 2412MHz (15GHz-20GHz)




TX 802.11g Channel Low 2412MHz (20GHz-25GHz)




TX 802.11g Channel Middle 2437MHz (30MHz-1GHz)




TX 802.11g Channel Middle 2437MHz (1GHz-5GHz)




TX 802.11g Channel Middle 2437MHz (5GHz-10GHz)




TX 802.11g Channel Middle 2437MHz (10GHz-15GHz)




TX 802.11g Channel Middle 2437MHz (15GHz-20GHz)




TX 802.11g Channel Middle 2437MHz (20GHz-25GHz)




TX 802.11g Channel High 2462MHz (30MHz-1GHz)




TX 802.11g Channel High 2462MHz (1GHz-5GHz)




TX 802.11g Channel High 2462MHz (5GHz-10GHz)




TX 802.11g Channel High 2462MHz (10GHz-15GHz)




TX 802.11g Channel High 2462MHz (15GHz-20GHz)




TX 802.11g Channel High 2462MHz (20GHz-25GHz)




TX 802.11n Channel Low 2412MHz (30MHz-1GHz)




TX 802.11n Channel Low 2412MHz (1GHz-5GHz)




TX 802.11n Channel Low 2412MHz (5GHz-10GHz)




TX 802.11n Channel Low 2412MHz (10GHz-15GHz)




TX 802.11n Channel Low 2412MHz (15GHz-20GHz)




TX 802.11n Channel Low 2412MHz (20GHz-25GHz)




TX 802.11n Channel Middle 2437MHz (30MHz-1GHz)




TX 802.11n Channel Middle 2437MHz (1GHz-5GHz)




TX 802.11n Channel Middle 2437MHz (5GHz-10GHz)




TX 802.11n Channel Middle 2437MHz (10GHz-15GHz)




TX 802.11n Channel Middle 2437MHz (15GHz-20GHz)




TX 802.11n Channel Middle 2437MHz (20GHz-25GHz)




TX 802.11n Channel High 2462MHz (30MHz-1GHz)




TX 802.11n Channel High 2462MHz (1GHz-5GHz)




TX 802.11n Channel High 2462MHz (5GHz-10GHz)




TX 802.11n Channel High 2462MHz (10GHz-15GHz)



TX 802.11n Channel High 2462MHz (15GHz-20GHz)




TX 802.11n Channel High 2462MHz (20GHz-25GHz)




11.AC POWER LINE CONDUCTED EMISSION FOR FCC PART 15 SECTION 15.207(A)

11.1.Block Diagram of Test Setup

11.1.1.Block diagram of connection between the EUT and simulators



11.1.2.Shielding Room Test Setup Diagram



11.2.The Emission Limit

11.2.1.Conducted Emission Measurement Limits According to Section 15.207(a)

Frequency (MHz)	Limit dB(μ V)	
	Quasi-peak Level	Average Level
0.15 - 0.50	66.0 – 56.0 *	56.0 – 46.0 *
0.50 - 5.00	56.0	46.0
5.00 - 30.00	60.0	50.0

* Decreases with the logarithm of the frequency.

11.3.Configuration of EUT on Measurement

The following equipment are installed on the Conducted Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

11.3.1.MID (EUT)

Model Number	:	GN32
Serial Number	:	N/A
Manufacturer	:	Shenzhen Leader Digital-tech Weitong Co., Ltd.

11.4.Operating Condition of EUT

11.4.1.Setup the EUT and simulator as shown as Section 11.1.

11.4.2.Turn on the power of all equipment.

11.4.3.Let the EUT work in TX (802.11b Channel Middle, 802.11g Channel Middle, 802.11n Channel Middle) mode measure it.

11.5.Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.4: 2003 on Conducted Emission Measurement.

The bandwidth of test receiver (R & S ESCS30) is set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

11.6.Power Line Conducted Emission Measurement Results

PASS.

The frequency range from 150kHz to 30MHz is checked.

Date of Test:	January 19, 2012	Temperature:	25°C
EUT:	MID	Humidity:	50%
Model No.:	GN32	Power Supply:	AC 120V/60Hz
Test Mode:	TX 802.11b Channel Middle	Test Engineer:	Pei

Frequency (MHz)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector	Line
0.613500	32.70	56	-23.3	QP	Neutral
1.563000	34.10	56	-21.9	QP	
12.646500	47.00	60	-13.0	QP	
12.574500	42.30	50	-7.7	AV	
12.579000	45.20	50	-4.8	AV	
12.849000	44.20	50	-5.8	AV	
0.613500	32.70	56	-23.3	QP	Live
1.35000	35.30	56	-20.7	QP	
12.763500	47.20	60	-12.8	QP	
1.356000	30.70	46	-15.3	AV	
12.493500	45.80	50	-4.2	AV	
12.768000	47.30	50	-2.7	AV	

Emissions attenuated more than 20 dB below the permissible value are not reported.

The spectral diagrams are attached as below.

Date of Test:	January 19, 2012	Temperature:	25°C
EUT:	MID	Humidity:	50%
Model No.:	GN32	Power Supply:	AC 120V/60Hz
Test Mode:	TX 802.11g Channel Middle	Test Engineer:	Pei

Frequency (MHz)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector	Line
0.338664	37.40	59	-21.6	QP	Neutral
0.613892	32.40	56	-23.6	QP	
12.503887	39.90	60	-20.1	QP	
11.966695	42.90	50	-7.1	AV	
12.305810	42.40	50	-7.6	AV	
12.503887	32.90	50	-17.1	AV	
0.337314	37.20	59	-21.8	QP	Live
0.613892	32.60	56	-23.4	QP	
12.705153	47.30	60	-12.7	QP	
11.683472	42.70	50	-7.3	AV	
12.159314	45.00	50	-5.0	AV	
12.705153	46.90	50	-3.1	AV	

Emissions attenuated more than 20 dB below the permissible value are not reported.
The spectral diagrams are attached as below.

Date of Test:	January 11, 2012	Temperature:	25°C
EUT:	MID	Humidity:	50%
Model No.:	GN32	Power Supply:	AC 120V/60Hz
Test Mode:	TX 802.11n Channel Middle	Test Engineer:	Pei

Frequency (MHz)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector	Line
0.611446	34.00	56	-22.0	QP	Neutral
0.882795	31.90	56	-24.1	QP	
12.454071	46.10	60	-13.9	QP	
0.406930	35.50	48	-12.5	AV	
2.107702	30.20	46	-15.8	AV	
12.454071	42.50	50	-7.5	AV	
0.338664	37.30	59	-21.7	QP	Live
4.835277	30.50	56	-25.5	QP	
12.654535	46.50	60	-13.5	QP	
0.406930	35.80	48	-12.2	AV	
3.335693	31.20	46	-14.8	AV	
12.654535	44.70	50	-5.3	AV	

Emissions attenuated more than 20 dB below the permissible value are not reported.
The spectral diagrams are attached as below.


ACCURATE TECHNOLOGY CO.,LTD**CONDUCTED EMISSION STANDARD FCC PART 15 B**

EUT: MID M/N:GN32
 Manufacturer: Leader Digital-tech Weitong
 Operating Condition: TX Channel 6 (802.11b)
 Test Site: 1#Shielding Room
 Operator: Bob
 Test Specification: L 120V/60Hz
 Comment: Mains port
 Report No.: ATE20120034

SCAN TABLE: "V 150K-30MHz fin"

Short Description: _SUB_STD_VTERM2 1.70

Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
Frequency	Frequency	Width				
150.0 kHz	30.0 MHz	0.8 %	QuasiPeak	1.0 s	9 kHz	NSLK8126 2008
Average						

**MEASUREMENT RESULT: "WK-0902-01_fin"**

1/19/2012 10:16AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.613500	32.70	12.0	56	23.3	QP	L1	GND
1.356000	35.30	11.8	56	20.7	QP	L1	GND
12.763500	47.20	11.2	60	12.8	QP	L1	GND

MEASUREMENT RESULT: "WK-0902-01_fin2"

1/19/2012 10:16AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
1.356000	30.70	11.8	46	15.3	AV	L1	GND
12.493500	45.80	11.2	50	4.2	AV	L1	GND
12.768000	47.30	11.2	50	2.7	AV	L1	GND


ACCURATE TECHNOLOGY CO.,LTD**CONDUCTED EMISSION STANDARD FCC PART 15 B**

EUT: MID M/N:GN32
 Manufacturer: Leader Digital-tech Weitong
 Operating Condition: TX Channel 6 (802.11b)
 Test Site: 1#Shielding Room
 Operator: Bob
 Test Specification: N 120V/60Hz
 Comment: Mains port
 Report No.: ATE20120034

SCAN TABLE: "V 150K-30MHz fin"

Short Description: _SUB_STD_VTERM2 1.70

Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
Frequency 150.0 kHz	Frequency 30.0 MHz	Width 0.8 %	QuasiPeak	1.0 s	9 kHz	NSLK8126 2008
			Average			

**MEASUREMENT RESULT: "WK-0902-02_fin"**

1/19/2012 10:23AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.613500	32.70	12.0	56	23.3	QP	N	GND
1.563000	34.10	11.7	56	21.9	QP	N	GND
12.646500	47.00	11.2	60	13.0	QP	N	GND

MEASUREMENT RESULT: "WK-0902-02_fin2"

1/19/2012 10:23AM


Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
12.574500	42.30	11.2	50	7.7	AV	N	GND
12.579000	45.20	11.2	50	4.8	AV	N	GND
12.849000	44.20	11.2	50	5.8	AV	N	GND

ACCURATE TECHNOLOGY CO.,LTD**CONDUCTED EMISSION STANDARD FCC PART 15 B**

EUT: MID M/N:GN32
 Manufacturer: Leader Digital-tech Weitong
 Operating Condition: TX Channel 6 (802.11g)
 Test Site: 1#Shielding Room
 Operator: Bob
 Test Specification: L 120V/60Hz
 Comment: Mains port
 Report No.: ATE20120034

SCAN TABLE: "V 150K-30MHz fin"

Short Description: SUB STD VTERM2 1.70
 Start Stop Step Detector Meas. IF Transducer
 Frequency Frequency Width Time Bandw.
 150.0 kHz 30.0 MHz 0.8 % QuasiPeak 1.0 s 9 kHz NSLK8126 2008
 Average

**MEASUREMENT RESULT: "WK-1117-01_fin"**

1/19/2012 9:49AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.337314	37.20	11.7	59	21.8	QP	L1	GND
0.613892	32.60	11.9	56	23.4	QP	L1	GND
12.705153	47.30	11.2	60	12.7	QP	L1	GND

MEASUREMENT RESULT: "WK-1117-01_fin2"

1/19/2012 9:49AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
11.683472	42.70	11.2	50	7.3	AV	L1	GND
12.159314	45.00	11.2	50	5.0	AV	L1	GND
12.705153	46.90	11.2	50	3.1	AV	L1	GND


ACCURATE TECHNOLOGY CO.,LTD**CONDUCTED EMISSION STANDARD FCC PART 15 B**

EUT: MID M/N:GN32
 Manufacturer: Leader Digital-tech Weitong
 Operating Condition: TX Channel 6 (802.11g)
 Test Site: 1#Shielding Room
 Operator: Bob
 Test Specification: N 120V/60Hz
 Comment: Mains port
 Report No.: ATE20120034

SCAN TABLE: "V 150K-30MHz fin"

Short Description: SUB STD VTERM2 1.70

Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
Frequency	Frequency	Width				
150.0 kHz	30.0 MHz	0.8 %	QuasiPeak	1.0 s	9 kHz	NSLK8126 2008
Average						

**MEASUREMENT RESULT: "WK-1117-02_fin"**

1/19/2012 9:52AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.338664	37.40	11.7	59	21.6	QP	N	GND
0.613892	32.40	11.9	56	23.6	QP	N	GND
12.503887	39.90	11.2	60	20.1	QP	N	GND

MEASUREMENT RESULT: "WK-1117-02_fin2"

1/19/2012 9:52AM


Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
11.966695	42.90	11.2	50	7.1	AV	N	GND
12.305810	42.40	11.2	50	7.6	AV	N	GND
12.503887	32.90	11.2	50	17.1	AV	N	GND

ACCURATE TECHNOLOGY CO.,LTD**CONDUCTED EMISSION STANDARD FCC PART 15 B**

EUT: MID M/N:GN32
 Manufacturer: Leader Digital-tech Weitong
 Operating Condition: TX Channel 6 (802.11n)
 Test Site: 1#Shielding Room
 Operator: Bob
 Test Specification: L 120V/60Hz
 Comment: Mains port
 Report No.: ATE20120034

SCAN TABLE: "V 150K-30MHz fin"

Short Description: SUB STD VTERM2 1.70
 Start Stop Step Detector Meas. IF Transducer
 Frequency Frequency Width Time Bandw.
 150.0 kHz 30.0 MHz 0.8 % QuasiPeak 1.0 s 9 kHz NSLK8126 2008
 Average

**MEASUREMENT RESULT: "WK-1117-03_fin"**

1/19/2012 10:56AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.338664	37.30	11.7	59	21.7	QP	L1	GND
4.835277	30.50	11.4	56	25.5	QP	L1	GND
12.654535	46.50	11.2	60	13.5	QP	L1	GND

MEASUREMENT RESULT: "WK-1117-03_fin2"

1/19/2012 10:56AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.406930	35.80	11.8	48	12.2	AV	L1	GND
3.335693	31.20	11.5	46	14.8	AV	L1	GND
12.654535	44.70	11.2	50	5.3	AV	L1	GND

ACCURATE TECHNOLOGY CO., LTD**CONDUCTED EMISSION STANDARD FCC PART 15 B**


EUT: MID M/N:GN32
 Manufacturer: Leader Digital-tech Weitong
 Operating Condition: TX Channel 6 (802.11n)
 Test Site: 1#Shielding Room
 Operator: Bob
 Test Specification: N 120V/60Hz
 Comment: Mains port
 Report No.: ATE20120034

SCAN TABLE: "V 150K-30MHz fin"

Short Description: SUB STD VTERM2 1.70

Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
150.0 kHz	30.0 MHz	0.8 %	QuasiPeak	1.0 s	9 kHz	NSLK8126 2008

 Average

**MEASUREMENT RESULT: "WK-1117-04_fin"**

1/19/2012 11:00AM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.611446	34.00	12.0	56	22.0	QP	N	GND
0.882795	31.90	11.9	56	24.1	QP	N	GND
12.454071	46.10	11.2	60	13.9	QP	N	GND

MEASUREMENT RESULT: "WK-1117-04_fin2"

1/19/2012 11:00AM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.406930	35.50	11.8	48	12.5	AV	N	GND
2.107702	30.20	11.6	46	15.8	AV	N	GND
12.454071	42.50	11.2	50	7.5	AV	N	GND


12.ANTENNA REQUIREMENT

12.1.The Requirement

According to Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

12.2.Antenna Construction

Device is equipped with unique antenna, which isn't displaced by other antenna. Therefore, the equipment complies with the antenna requirement of Section 15.203.



Antenna