

TEST REPORT

Testing Laboratory:**SK Tech Co., Ltd.**

88, Geulgaeul-ro, 81beon-gil,
Wabu-eup, Namyangju-si,
Gyeonggi-do, Korea
TEL: +82-31-576-2204
FAX: +82-31-576-2205

Test Report Number: SKT-RFC-190001**Date of issue: June 14, 2019****Applicant:****KYUNGWOO SYSTECH, INC.**

#401, Daeryung Post Tower 5, 68, Digital-ro 9, Geumcheon-gu, Seoul,
South Korea

Manufacturer:**KYUNGWOO SYSTECH, INC.**

#401, Daeryung Post Tower 5, 68, Digital-ro 9, Geumcheon-gu, Seoul,
South Korea

Product:**SMK CONTROLLER UNIT****Model:****SMK-DWS-00****FCC ID:****ZE8-SMK-DWS-00****Project number:****SKTEU18-1194****EUT received:****December 4, 2018****Applied standards:** ANSI C63.10-2013 and ANSI C63.4-2014**Rule parts:** FCC Part 15 Subpart C - Intentional radiators**Equipment Class:** DSC - Part 15 Security/Remote Control Transmitter**Remarks to the standards:** None

The above equipment has been tested by SK Tech Co., Ltd., and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product or system, which was tested.

**Wonsik Ham / Testing Engineer****Jongsoo Yoon / Technical Manager**

This report shall not be reproduced except in full, without the written approval of SK Tech Co., Ltd. The client should not use it to claim product endorsement by any government agencies.



Revision History of Test Report

Rev.	Revisions	Effect page	Approved by	Date
-	Initial issue	All	Jongsoo Yoon	Jun. 14, 2019



TABLE OF CONTENTS

1	Summary of test results	4
2	Description of equipment under test (EUT)	5
3	Test and measurement conditions	6
3.1.	Test configuration (arrangement of EUT)	6
3.2.	Description of support units (accessory equipment).....	6
3.3.	Interconnection and I/O cables.....	6
3.4.	Measurement Uncertainty (U)	6
3.5.	Test date	6
4	Facilities and accreditations	7
4.1.	Facilities.....	7
4.2.	Accreditations	7
4.3.	List of test and measurement instruments.....	7
5	Test and measurements	8
5.1.	Antenna requirement	8
5.2.	20 dB Emission Bandwidth	9
5.3.	Transmission Time.....	11
5.4.	Radiated emissions	14



1 Summary of test results

Requirement	CFR 47 Section	Result
Antenna Requirement	15.203	Meets the requirements
20dB Emission Bandwidth	15.231(c)	Meets the requirements
Transmission Time	15.231(a)	Meets the requirements
Spurious Emission, Band Edge, and Restricted bands	15.231(b), 15.205(a), 15.209(a)	Meets the requirements
AC power line Conducted emissions	15.207(a)	N/A

Note: The EUT is operated from the battery (DC 12 V or DC 24 V) in a vehicle, and therefore the test suites related to AC Mains port were not applicable.

**2 Description of equipment under test (EUT)**

Product: SMK CONTROLLER UNIT
Model: SMK-DWS-00
Serial number: None (prototype)

Model differences:

Model name	Difference	Tested (checked)
SMK-DWS-00	fully tested model that was provided by the applicant	<input checked="" type="checkbox"/>

Technical data:

Power source	DC 12 V / DC 24 V (powered from the battery in a vehicle)	
Local Oscillator or X-Tal	4 MHz, 8 MHz, 16 MHz, 26 MHz	
Transmit Frequency	433.92 MHz	133 kHz
Antenna Type	Integral chip antenna	Integral loop coil antenna (3 pcs)
Type of Modulation	GFSK	ASK
RF Output power	74.70 dB μ V/m (PEAK) (measured @ 3m)	86.10 dB μ V/m(PEAK) (measured @ 3m)

Note: * The test report for Equipment Class DCD was issued with other test report number.

** The test report for the compliance with FCC Part 15B as a digital device was issued with other test report number.

I/O port	Type	Q'ty	Remark
CN1	26-pin connector (DC IN, ACC, Actuator, etc.)	1	
CN2	16-pin connector (LF ANT, SSB ANT, CAN. etc.)	1	

Modification of EUT during the compliance testing:

The two test samples were provided for the tests; SAMPLE #1, which modified by the firmware for the periodic operation and for reducing the RF power setting, was used for all the tests, except for the measurements of Transmission Time for which SAMPLE #2 was used considering the normal operation.

The firmware of the EUTs was modified as below:


- In the normal operation, the product shortly transmitted RF signals. Therefore the SAMPLE #1 was modified for the tests in order to repeatedly transmit the RF signals as described on the page 16. The SAMPLE #1 were operated in the test mode by pressing the SSB button to sequentially change the operating mode (Unmodulated TX 433.92 MHz, Stand-by, Internal LF 133 kHz TX, External LF 133 kHz TX, External SSB LF 134 kHz TX, and then Modulated 433.92 MHz).
- The SAMPLE #1 was modified again, in order to meet the electric field strength limit at the fundamental frequency. The applicant changed the value for RF power setting to reduce the emission level during the radiated emission measurements. The version of the new firmware was v1.0.0.



3 Test and measurement conditions

3.1. Test configuration (arrangement of EUT)

The EUT was operated from DC Power Supply (12 V or 24 V). The measurements were taken while the EUT (SAMPLE #1) was repeatedly transmitting the RF signals with the maximum duty cycle provided by the applicant. In order to transmit RF signals, the SSB button on the EUT was pressed 6 times.



NOTE: the Transmission Time was measured in the normal operation for the EUT (SAMPLE #2; without the firmware modification used for the periodic operation of SAMPLE #1). The RF signals manually transmitted when pairing with SMK FOB (FCC ID: ZE8-SMK-DWS-01, model SMK-DWS-01) in order for the EUT to register SMK FOB. The software (SMK_DWS_JIG.exe) was used to activate the EUT during the Transmission Time measurements. The Test jig was connected for the normal operation.

3.2. Description of support units (accessory equipment)

The following support units or accessories were used to form a representative test configuration during the tests.

#	Equipment	Manufacturer	Model No.	Serial No.
1	DC Power Supply	HP	6633A	2838A-01000

3.3. Interconnection and I/O cables

The following support units or accessories were used to form a representative test configuration during the tests.

#	Start		End		Cable	
	Name	I/O port	Name	I/O port	length (m)	shielded (Y/N)
	EUT	DC IN	DC Power Supply	DC OUT	2.0	N

Note: 1) All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2) Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

3.4. Measurement Uncertainty (U)

Measurement Item	Combined Standard Uncertainty U_c	Expanded Uncertainty $U = k \times U_c (k = 2)$
Conducted RF power	±1.49 dB	±2.98 dB
Conducted emissions	±1.42 dB	±2.84 dB
Radiated emissions (9 kHz to 30 MHz)	±2.30 dB	±4.60 dB
Radiated emissions (30 MHz to 1000 MHz)	±2.53 dB	±5.06 dB
Radiated emissions (1 GHz to 6 GHz)	±2.62 dB	±5.24 dB

3.5. Test date

Date Tested	January 8, 2019 – April 11, 2019
-------------	----------------------------------



4 Facilities and accreditations

4.1. Facilities

All of the measurements described in this report were performed at SK Tech Co., Ltd

Site I: 88, Geulgaeul-ro 81beon-gil, Wabu-eup, Namyangju-si, Gyeonggi-do, Korea

Site II: 124-8, Geulgaeul-ro, Wabu-eup, Namyangju-si, Gyeonggi-do, Korea

The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-4. The sites comply with the Normalized Site Attenuation requirements given in ANSI C63.4, and site VSWR requirements specified in CISPR 16-1-4. The measuring apparatus and ancillary equipment conform to CISPR 16-1 series.

4.2. Accreditations

The laboratory has been also notified to FCC by RRA as a Conformity Assessment Body, and designated to perform compliance testing on equipment subject to Supplier's Declaration of Conformity (SDoC) and Certification under Parts 15 and 18 of the FCC Rules.

Designation No. KR0007

4.3. List of test and measurement instruments

No	Description	Model	Manufacturer	Serial No.	Cal. due	Use
1	Spectrum Analyzer	E4405B	Agilent	US40520856	2020.02.25	<input checked="" type="checkbox"/>
2	Spectrum Analyzer	E4440A	Agilent	MY46186322	2019.06.18	<input checked="" type="checkbox"/>
3	EMI Test Receiver	ESR26	Rohde&Schwarz	101441	2019.08.29	<input checked="" type="checkbox"/>
4	EMI Test Receiver	ESIB40	Rohde&Schwarz	100277	2020.02.26	<input checked="" type="checkbox"/>
5	EMI Test Receiver	PMM9010F	Narda	020WW40105	2020.06.10	
6	Pulse limiter	ESH3-Z2	Rohde&Schwarz	100604	2020.06.10	
7	AMN (LISN)	ENV 216	Rohde&Schwarz	102047	2020.02.25	
8	AMN (LISN)	FCC-LISN-50-32-2-01-480V	FCC	141455	2020.06.10	
9	Pre-amplifier (30 MHz - 1 GHz)	MLA-10K01-B01-27	TSJ	2005350	2020.06.11	<input checked="" type="checkbox"/>
10	Pre-amplifier (30 MHz - 1 GHz)	8447D	HP	2944A07994	2020.06.10	
11	Pre-amplifier (1 GHz - 18 GHz)	MLA-100M18-B02-38	TSJ	1539546	2020.02.25	<input checked="" type="checkbox"/>
16	Attenuator (10dB)	8491B	HP	38072	2020.06.10	
17	Attenuator (6dB)	18N5W	API Technology	-	2020.06.10	<input checked="" type="checkbox"/>
18	High Pass Filter	WHKE3-500.2-610-4000-40SS	Wainwright	1	2019.06.20	<input checked="" type="checkbox"/>
19	VHF Precision Dipole Antenna (TX/RX)	VHAP	Schwarzbeck	1014 / 1015	2020.06.11	
20	UHF Precision Dipole Antenna (TX/RX)	UHAP	Schwarzbeck	989 / 990	2020.09.17	
21	Loop Antenna	HFH2-Z2	Schwarzbeck	863048/019	2020.12.18	<input checked="" type="checkbox"/>
22	BILOG Broadband Antenna	VULB9168	Schwarzbeck	9168-230	2019.07.20	<input checked="" type="checkbox"/>
23	Horn Antenna (1 GHz - 18 GHz)	BBHA 9120D	Schwarzbeck	9120D-816	2021.06.10	<input checked="" type="checkbox"/>
24	Horn Antenna (15 GHz - 40 GHz)	BBHA9170	Schwarzbeck	BBHA9170318	2020.07.23	
25	Vector Signal Generator	E4438C	Agilent	MY42080359	2020.02.26	
26	PSG analog signal generator	E8257D	Agilent	MY45141255	2020.06.10	
27	DC Power Supply	6633A	HP	2838A-01000	2020.06.10	<input checked="" type="checkbox"/>
28	DC Power Supply	6633A	HP	3325A04972	2020.06.10	
29	Digital Thermo-Hygrometer	608-H1	Testo	-	2019.06.21	<input checked="" type="checkbox"/>
30	Temperature/Humidity Chamber	DJ-THC02	DAE JIN ENG	06071	2020.02.27	



5 Test and measurements

5.1. Antenna requirement

5.1.1 Regulation

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

5.1.2 Result:

PASS

The EUT has an internal chip antenna and meets the requirements of this section.



5.2. 20 dB Emission Bandwidth

5.2.1 Regulation

According to §15.231(c), The bandwidth of the emission shall be no wider than 0.25 % of the center frequency for devices operating above 70 MHz and below 900 MHz. Bandwidth is determined at the points 20 dB down from the modulated carrier.

5.2.2 Test Procedure

The EUT (SAMPLE #1) repeatedly transmitted RF signals and the small antenna, to which the Spectrum Analyzer was connected, placed in the vicinity of the EUT. The Occupied Bandwidth (99 %) and 20 dB emission bandwidth were measured with the following setting according to ANSI C63.10, 12.4.

- (a) Set RBW = approximately 1 % of the emission bandwidth
- (b) Set the VBW > RBW
- (c) Detector = peak
- (d) Trace mode = max hold

5.2.3 Test Results: **PASS**

Table 1: Measured values of the 20 dB Emission Bandwidth

Operated from DC 12 V

Operating frequency	Occupied Bandwidth (99 %)	20 dB Emission Bandwidth	Limit
433.92 MHz	75.3 kHz	78.4 kHz	< 1084.8 kHz


Operated from DC 24 V

Operating frequency	Occupied Bandwidth (99 %)	20 dB Emission Bandwidth	Limit
433.92 MHz	75.3 kHz	78.2 kHz	< 1084.8 kHz




Figure 1. Plot of the 20 dB Emission Bandwidth & Occupied Bandwidth

Operated from DC 12 V



Operated from DC 24 V





5.3. Transmission Time

5.3.1 Regulation

- (1) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.
- (2) A transmitter activated automatically shall cease transmission within 5 seconds after activation.
- (3) Periodic transmissions at regular predetermined intervals are not permitted. However, polling or supervision transmissions, including data, to determine system integrity of transmitters used in security or safety applications are allowed if the total duration of transmissions does not exceed more than two seconds per hour for each transmitter. There is no limit on the number of individual transmissions, provided the total transmission time does not exceed two seconds per hour.

5.3.2 Test Procedure

The EUT (SAMPLE #2) transmitted RF signals and the small antenna, to which the Spectrum Analyzer was connected, placed in the vicinity of the EUT. The Transmission Time was measured in the normal operating conditions for pairing with SMK FOB after sending the RF command by the software. The Spectrum Analyzer was set as below:

- (a) Set the center frequency to the operating frequency
- (b) Set RBW > 20 dB Emission Bandwidth (or Occupied Bandwidth)
- (c) Set Trigger level to start the measurement when the EUT transmitted RF signals
- (d) Set Sweep time to capture the pulse trains and/or to capture the burst ON time

5.3.3 Test Results:

PASS

Table 2: Measured values of the Transmission Time

Operated from DC 12 V


Operating frequency	Transmission Type	Transmission Time	Limit
		[ms]	[s]
433.92 MHz	Manually	4.72	5

Operated from DC 24 V


Operating frequency	Transmission Type	Transmission Time	Limit
		[ms]	[s]
433.92 MHz	Manually	4.72	5



Figure 2. Plot of the Transmission Time (Operated from DC 12 V)




Manual transmission when sending the RF command for pairing with SMK FOB by the software
[remark: two burst signals with lower signal level was for SMK FOB]




Transmission time (duration) for the operation



Figure 2. Plot of the Transmission Time (cont.) (Operated from DC 24 V)



Manual transmission when sending the RF command for pairing with SMK FOB by the software
[remark: two burst signals with lower signal level was for SMK FOB]



Transmission time (duration) for the operation



5.4. Radiated emissions

5.4.1 Regulation

FCC 47CFR15 – 15.231

According to §15.231(b), the field strength of emissions from intentional radiators operated under this section shall not exceed the following:

Fundamental frequency (MHz)	Field strength of fundamental (μ V/m) @ 3 m	Field strength of spurious emissions (μ V/m) @ 3 m
40.66 – 40.70	2,250	225
70 – 130	1,250	125
130 – 174	1,250 to 3,750**	125 to 375**
174 – 260	3,750	375
260 – 470	3,750 to 12,500**	375 to 1,250**
Above 470	12,500	1,250

** linear interpolations

The limits on the field strength of the spurious emissions in the above table are based on the fundamental frequency of the intentional radiator. Spurious emissions shall be attenuated to the average (or, alternatively, CISPR quasi-peak) limits shown in this table or to the general limits shown in §15.209, whichever limit permits a higher field strength.

FCC 47CFR15 – 15.209

(a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field strength limit (μ V/m)	Field strength limit (dB μ V/m)	Measurement Distance (m)
0.009 – 0.490	$2400/F$ (kHz) = 266.7 – 4.9	48.5 – 13.8	300
0.490 – 1.705	$24000/F$ (kHz) = 49.0 – 14.1	33.8 – 23.0	30
1.705 – 30.0	30	29.5	30
30 – 88	100	40.0	3
88 – 216	150	43.5	3
216 – 960	200	46.0	3
Above 960	500	54.0	3

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

Compliance with the provisions of §15.205 shall be demonstrated using the measurement instrumentation specified in that section.



5.4.2 Measurement Procedure

The EUT (SAMPLE #1) repeatedly transmitted RF signals and the following measurement procedure specified in ANSI C63.10-2013 was used.

Radiated Emissions Test, 9 kHz to 30 MHz (Magnetic Field Test)

- (a) The preliminary radiated measurements were performed to determine the frequency producing the maximum emissions at a distance of 3 meters according to Section 15.31(f)(2).
- (b) The EUT was placed on the top of the 0.8-meter height, 1 × 1.5 meter non-metallic table.
- (c) Emissions from the EUT are maximized by adjusting the orientation of the Loop antenna and rotating the EUT on the turntable. Manipulating the system cables also maximizes EUT emissions if applicable.
- (d) To obtain the final measurement data, each frequency found during preliminary measurements was re-examined and investigated. The test-receiver system was set up to average, peak, and quasi-peak detector function with specified bandwidth.
- (e) The EUT was situated in three orthogonal planes (if appropriate).

Radiated Emissions Test, above 30 MHz


- (a) The preliminary radiated measurements were performed to determine the frequency producing the maximum emissions in an anechoic chamber at a distance of 3 meters.
- (b) The EUT was placed on the top of the 0.8-meter height (or 1.5 meter height for above 1 GHz), 1 × 1.5 meter non-metallic table. To find the maximum emission levels, the height of a measuring antenna was changed and the turntable was rotated 360°.
- (c) The antenna polarization was also changed from vertical to horizontal. The spectrum was scanned from 30 to 1000 MHz using the Bilog broadband antenna, and from 1 GHz to tenth harmonic of the highest fundamental frequency using the horn antenna.
- (d) Each frequency found during preliminary measurements was re-examined and investigated. The test-receiver system was set up to average, peak, and quasi-peak detector function with specified bandwidth.
- (e) The EUT was situated in three orthogonal planes (if appropriate).

Measurement software: TEPTO-DV/RE_Version: 3.1.0044




Figure 3. RF signals during the measurements achieved by the modification of firmware

In normal operation, the EUT transmitted one burst signal when sending RF signals for pairing with SMK FOB as the section 5.3 of this test report. The firmware of the EUT (SAMPLE #1) was modified in order to repeatedly transmit the RF signals with the duration 4.6 ms and period 26 ms. According to FCC Part 15.35(b), the measurement of the field strength was performed by averaging over one complete pulse train (4.6 ms) because the pulse train did not exceed 0.1 seconds. [remark: Figure 3 were taken before the change of the value for RF power setting to reduce the emission level, and the final measurements of the field strength were performed for SAMPLE #1 with lower RF power setting value after checking the same periodic operation of the RF signals]



Periodic operation for the radiated emission measurements



Duration of the burst signals



5.4.3 Test Results:

PASS

Table 3: Measured values of the Field strength

For the measurements under below 30 MHz

Freq. (kHz)	RBW (kHz)	Reading (dB μ V)			AF (dB/m)	Cable Loss (dB)	Actual (dB μ V/m)			Limit (at 3m) (dB μ V/m)			Margin (dB)			Remark
		PK	AV	QP			PK	AV	QP	PK	AV	QP	PK	AV	QP	
		No Radiated Spurious Emissions Found														

Actual (dB μ V/m) = Reading + AF + Cable Loss

Margin (dB) = Limit – Actual

Note: These test results were measured at the 3 m distance.



For the measurements from 30 MHz to 1 GHz (for X-axis, 12 V), except for the emissions in 15.205

Frequency (MHz)	Pol. (V/H)	Height (m)	Reading (dB μ V)		AMP (dB)	AF (dB/m)	CL (dB)	Actual (dB μ V/m)		Limit (dB μ V/m)		Margin (dB)	
			PK	AV				PK	AV	PK	AV	PK	AV
433.928	H	1.00	49.5	48.5	0.0	22.4	2.8	74.7	73.7	100.8	80.8	26.1	7.1
433.928	V	1.25	41.3	39.7	0.0	22.4	2.8	66.5	64.9	100.8	80.8	34.3	15.9
880.011	H	1.23	35.6	32.6	30.0	29.3	4.0	38.9	35.9	80.8	60.8	41.9	24.9
911.998	H	1.16	36.5	33.6	30.2	29.6	4.1	40.0	37.1	80.8	60.8	40.8	23.7
943.981	H	1.09	35.2	31.5	30.5	29.8	4.2	38.7	35.0	80.8	60.8	42.1	25.8
944.003	V	2.11	31.7	26.0	30.5	29.8	4.2	35.2	29.5	80.8	60.8	45.6	31.3

For the measurements from 30 MHz to 1 GHz (for Y-axis, 12 V), except for the emissions in 15.205

Frequency (MHz)	Pol. (V/H)	Height (m)	Reading (dB μ V)		AMP (dB)	AF (dB/m)	CL (dB)	Actual (dB μ V/m)		Limit (dB μ V/m)		Margin (dB)	
			PK	AV				PK	AV	PK	AV	PK	AV
433.928	H	1.00	47.7	46.6	0.0	22.4	2.8	72.9	71.8	100.8	80.8	27.9	9.0
433.928	V	1.28	45.9	44.7	0.0	22.4	2.8	71.1	69.9	100.8	80.8	29.7	10.9
879.998	H	1.06	33.7	30.1	30.0	29.3	4.0	37.0	33.4	80.8	60.8	43.8	27.4
880.014	V	1.50	33.1	29.3	30.0	29.3	4.0	36.4	32.6	80.8	60.8	44.4	28.2
911.990	H	1.05	34.3	30.8	30.2	29.6	4.1	37.8	34.3	80.8	60.8	43.0	26.5
944.023	H	1.01	32.9	27.9	30.5	29.8	4.2	36.4	31.4	80.8	60.8	44.4	29.4
944.028	V	1.26	31.9	26.8	30.5	29.8	4.2	35.4	30.3	80.8	60.8	45.4	30.5

For the measurements from 30 MHz to 1 GHz (for Z-axis, 12 V), except for the emissions in 15.205

Frequency (MHz)	Pol. (V/H)	Height (m)	Reading (dB μ V)		AMP (dB)	AF (dB/m)	CL (dB)	Actual (dB μ V/m)		Limit (dB μ V/m)		Margin (dB)	
			PK	AV				PK	AV	PK	AV	PK	AV
433.928	H	1.00	44.6	43.2	0.0	22.4	2.8	69.8	68.4	100.8	80.8	31.0	12.4
433.928	V	1.45	41.6	40.1	0.0	22.4	2.8	66.8	65.3	100.8	80.8	34.0	15.5
880.001	V	1.67	32.8	28.1	30.0	29.3	4.0	36.1	31.4	80.8	60.8	44.7	29.4
880.005	H	1.12	34.3	31.1	30.0	29.3	4.0	37.6	34.4	80.8	60.8	43.2	26.4
912.013	H	1.05	34.9	31.4	30.2	29.6	4.1	38.4	34.9	80.8	60.8	42.4	25.9
943.997	V	1.47	33.4	28.9	30.5	29.8	4.2	36.9	32.4	80.8	60.8	43.9	28.4
944.010	H	1.05	36.3	33.2	30.5	29.8	4.2	39.8	36.7	80.8	60.8	41.0	24.1

V/H: Vertical / Horizontal polarization

AMP, AF and CL: pre-amplifier gain, antenna factor and cable loss including an attenuator/filter if used

Actual = Reading - AMP + AF + CL

Margin = Limit - Actual



For the measurements from 30 MHz to 1 GHz (for X-axis, 24 V), except for the emissions in 15.205

Frequency (MHz)	Pol. (V/H)	Height (m)	Reading (dB μ V)		AMP (dB)	AF (dB/m)	CL (dB)	Actual (dB μ V/m)		Limit (dB μ V/m)		Margin (dB)	
			PK	AV				PK	AV	PK	AV	PK	AV
433.928	H	1.00	49.5	48.5	0.0	22.4	2.8	74.7	73.7	100.8	80.8	26.1	7.1
433.928	V	1.25	41.4	39.8	0.0	22.4	2.8	66.5	65.0	100.8	80.8	34.3	15.8
879.992	H	1.22	35.5	32.3	30.0	29.3	4.0	38.8	35.6	80.8	60.8	42.0	25.2
911.981	H	1.15	36.1	33.2	30.2	29.6	4.1	39.6	36.7	80.8	60.8	41.2	24.1
944.002	V	2.12	32.3	26.5	30.5	29.8	4.2	35.8	30.0	80.8	60.8	45.0	30.8
944.023	H	1.09	35.2	31.3	30.5	29.8	4.2	38.7	34.8	80.8	60.8	42.1	26.0

For the measurements from 30 MHz to 1 GHz (for Y-axis, 24 V), except for the emissions in 15.205

Frequency (MHz)	Pol. (V/H)	Height (m)	Reading (dB μ V)		AMP (dB)	AF (dB/m)	CL (dB)	Actual (dB μ V/m)		Limit (dB μ V/m)		Margin (dB)	
			PK	AV				PK	AV	PK	AV	PK	AV
433.928	H	1.00	47.7	46.6	0.0	22.4	2.8	72.9	71.8	100.8	80.8	27.9	9.0
433.928	V	1.28	45.8	44.6	0.0	22.4	2.8	71.0	69.8	100.8	80.8	29.8	11.0
879.984	H	1.06	33.3	29.6	30.0	29.3	4.0	36.6	32.9	80.8	60.8	44.2	27.9
879.995	V	1.53	33.8	30.0	30.0	29.3	4.0	37.1	33.3	80.8	60.8	43.7	27.5
911.993	H	1.05	34.6	30.9	30.2	29.6	4.1	38.1	34.4	80.8	60.8	42.7	26.4
944.022	H	1.00	32.4	27.5	30.5	29.8	4.2	35.9	31.0	80.8	60.8	44.9	29.8

For the measurements from 30 MHz to 1 GHz (for Z-axis, 24 V), except for the emissions in 15.205

Frequency (MHz)	Pol. (V/H)	Height (m)	Reading (dB μ V)		AMP (dB)	AF (dB/m)	CL (dB)	Actual (dB μ V/m)		Limit (dB μ V/m)		Margin (dB)	
			PK	AV				PK	AV	PK	AV	PK	AV
433.928	H	1.00	44.6	43.3	0.0	22.4	2.8	69.8	68.5	100.8	80.8	31.0	12.3
433.928	V	1.45	41.7	40.1	0.0	22.4	2.8	66.9	65.3	100.8	80.8	33.9	15.5
848.012	H	1.16	33.9	30.3	29.9	29.0	3.9	36.9	33.3	80.8	60.8	43.9	27.5
880.006	H	1.12	34.3	30.8	30.0	29.3	4.0	37.6	34.1	80.8	60.8	43.2	26.7
911.993	H	1.05	35.3	32.1	30.2	29.6	4.1	38.8	35.6	80.8	60.8	42.0	25.2
943.988	H	1.06	36.9	33.4	30.5	29.8	4.2	40.4	36.9	80.8	60.8	40.4	23.9

V/H: Vertical / Horizontal polarization

AMP, AF and CL: pre-amplifier gain, antenna factor and cable loss including an attenuator/filter if used

Actual = Reading - AMP + AF + CL

Margin = Limit - Actual



For the measurements from 30 MHz to 1 GHz with CISPR quasi-peak detector
(emissions in the restricted bands specified in 15.205)

Operated from DC 12 V

Frequency (MHz)	Pol. (V/H)	Height (m)	Reading (dB μ V)	AMP (dB)	AF (dB/m)	CL (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Remark
975.994	H	1.09	35.9	30.6	30.0	4.2	39.5	54.0	14.5	X-axis
975.999	V	2.01	32.7	30.6	30.0	4.2	36.3	54.0	17.7	Y-axis
976.023	H	1.01	34.2	30.6	30.0	4.2	37.8	54.0	16.2	Z-axis

Operated from DC 24 V

Frequency (MHz)	Pol. (V/H)	Height (m)	Reading (dB μ V)	AMP (dB)	AF (dB/m)	CL (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Remark
975.976	H	1.09	35.8	30.6	30.0	4.2	39.4	54.0	14.6	X-axis
976.015	V	1.26	33.2	30.6	30.0	4.2	36.8	54.0	17.2	Y-axis
976.002	H	1.01	34.9	30.6	30.0	4.2	38.5	54.0	15.5	Z-axis
976.009	V	1.12	32.2	30.6	30.0	4.2	35.8	54.0	18.2	Z-axis

V/H: Vertical / Horizontal polarization

AMP, AF and CL: pre-amplifier gain, antenna factor and cable loss including an attenuator/filter if used

Actual = Reading - AMP + AF + CL

Margin = Limit - Actual

remark: the Reading value was measured with PEAK detector, and the CISPR quasi-peak detector was not used because the PEAK values were low the QP limits.



For the measurements above 1 GHz (for X-axis, 12 V)

Frequency (MHz)	Pol. (V/H)	Height (m)	Reading (dB μ V)		AMP (dB)	AF (dB/m)	CL (dB)	Actual (dB μ V/m)		Limit (dB μ V/m)		Margin (dB)	
			PK	AV				PK	AV	PK	AV	PK	AV
1423.913	V	1.05	44.9	34.9	39.6	25.0	6.1	36.4	26.4	74.0	54.0	37.6	27.6
1424.022	H	1.84	46.3	39.0	39.6	25.0	6.1	37.8	30.5	74.0	54.0	36.2	23.5
1456.076	H	1.56	45.0	36.8	39.6	25.1	6.1	36.6	28.4	74.0	54.0	37.4	25.6
1456.242	V	1.41	45.3	36.4	39.6	25.1	6.1	36.9	28.0	74.0	54.0	37.1	26.0
1487.970	H	1.11	45.3	37.5	39.6	25.1	6.2	37.0	29.2	74.0	54.0	37.0	24.8

For the measurements above 1 GHz (for Y-axis, 12 V)

Frequency (MHz)	Pol. (V/H)	Height (m)	Reading (dB μ V)		AMP (dB)	AF (dB/m)	CL (dB)	Actual (dB μ V/m)		Limit (dB μ V/m)		Margin (dB)	
			PK	AV				PK	AV	PK	AV	PK	AV
1104.073	V	1.02	44.3	34.7	39.5	24.3	5.4	34.5	24.9	74.0	54.0	39.5	29.1
1264.040	H	2.22	46.2	38.9	39.5	24.7	5.7	37.1	29.8	74.0	54.0	36.9	24.2
1392.217	V	2.15	46.4	37.7	39.6	24.9	6.0	37.7	29.0	74.0	54.0	36.3	25.0
1455.817	H	1.32	45.5	38.1	39.6	25.1	6.1	37.1	29.7	74.0	54.0	36.9	24.3

For the measurements above 1 GHz (for Z-axis, 12 V)

Frequency (MHz)	Pol. (V/H)	Height (m)	Reading (dB μ V)		AMP (dB)	AF (dB/m)	CL (dB)	Actual (dB μ V/m)		Limit (dB μ V/m)		Margin (dB)	
			PK	AV				PK	AV	PK	AV	PK	AV
1007.924	H	2.14	48.9	44.1	39.5	24.1	5.1	38.6	33.8	74.0	54.0	35.4	20.2
1392.013	H	2.01	45.3	36.2	39.6	24.9	6.0	36.6	27.5	74.0	54.0	37.4	26.5
1424.002	V	2.25	43.7	33.6	39.6	25.0	6.1	35.2	25.1	74.0	54.0	38.8	28.9
1455.977	V	1.45	46.7	40.5	39.6	25.1	6.1	38.3	32.1	74.0	54.0	35.7	21.9
1456.017	H	1.43	44.7	34.6	39.6	25.1	6.1	36.3	26.2	74.0	54.0	37.7	27.8

V/H: Vertical / Horizontal polarization

AMP, AF and CL: pre-amplifier gain, antenna factor and cable loss including an attenuator/filter if used

Actual = Reading - AMP + AF + CL

Margin = Limit - Actual



For the measurements above 1 GHz (for X-axis, 24 V)

Frequency (MHz)	Pol. (V/H)	Height (m)	Reading (dB μ V)		AMP (dB)	AF (dB/m)	CL (dB)	Actual (dB μ V/m)		Limit (dB μ V/m)		Margin (dB)	
			PK	AV				PK	AV	PK	AV	PK	AV
1007.697	H	1.71	46.5	38.8	39.5	24.1	5.1	36.2	28.5	74.0	54.0	37.8	25.5
1263.953	V	3.53	43.4	32.5	39.5	24.7	5.7	34.3	23.4	74.0	54.0	39.7	30.6
1391.999	V	1.88	44.1	34.8	39.6	24.9	6.0	35.4	26.1	74.0	54.0	38.6	27.9
1455.900	H	2.47	45.5	37.7	39.6	25.1	6.1	37.1	29.3	74.0	54.0	36.9	24.7
1520.066	H	1.49	43.1	31.5	39.6	25.2	6.3	35.0	23.4	74.0	54.0	39.0	30.6

For the measurements above 1 GHz (for Y-axis, 24 V)

Frequency (MHz)	Pol. (V/H)	Height (m)	Reading (dB μ V)		AMP (dB)	AF (dB/m)	CL (dB)	Actual (dB μ V/m)		Limit (dB μ V/m)		Margin (dB)	
			PK	AV				PK	AV	PK	AV	PK	AV
1007.851	V	1.55	46.3	38.4	39.5	24.1	5.1	36.0	28.1	74.0	54.0	38.0	25.9
1296.203	H	1.03	44.0	33.7	39.5	24.7	5.8	35.0	24.7	74.0	54.0	39.0	29.3
1391.668	H	2.07	44.9	35.6	39.6	24.9	6.0	36.2	26.9	74.0	54.0	37.8	27.1
1392.189	V	2.24	45.9	37.1	39.6	24.9	6.0	37.2	28.4	74.0	54.0	36.8	25.6
1423.854	V	2.26	45.7	36.2	39.6	25.0	6.1	37.2	27.7	74.0	54.0	36.8	26.3

For the measurements above 1 GHz (for Z-axis, 24 V)

Frequency (MHz)	Pol. (V/H)	Height (m)	Reading (dB μ V)		AMP (dB)	AF (dB/m)	CL (dB)	Actual (dB μ V/m)		Limit (dB μ V/m)		Margin (dB)	
			PK	AV				PK	AV	PK	AV	PK	AV
1007.838	H	1.93	48.9	43.7	39.5	24.1	5.1	38.6	33.4	74.0	54.0	35.4	20.6
1008.008	V	3.74	46.4	38.6	39.5	24.1	5.1	36.1	28.3	74.0	54.0	37.9	25.7
1360.155	V	1.96	45.9	37.7	39.6	24.9	6.0	37.2	29.0	74.0	54.0	36.8	25.0
1424.020	H	2.04	45.7	38.8	39.6	25.0	6.1	37.2	30.3	74.0	54.0	36.8	23.7
1455.895	V	3.65	44.8	35.7	39.6	25.1	6.1	36.4	27.3	74.0	54.0	37.6	26.7
1552.176	H	1.50	44.1	34.4	39.6	25.3	6.3	36.1	26.4	74.0	54.0	37.9	27.6
1668.049	H	3.06	42.0	28.9	39.8	25.5	6.6	34.3	21.2	74.0	54.0	39.7	32.8

V/H: Vertical / Horizontal polarization

AMP, AF and CL: pre-amplifier gain, antenna factor and cable loss including an attenuator/filter if used

Actual = Reading - AMP + AF + CL

Margin = Limit - Actual




Figure 4. Emission plot for the preliminary radiated measurements

The worst-case plots were attached.

Operated from DC 12 V

Frequency Range: 9 kHz ~ 150 kHz



Frequency Range : 150 kHz ~ 1.5 MHz



Frequency Range 1.5 MHz ~ 30 MHz




Remark: during the measurements, the correction factor (antenna factor and cable loss) was compensated as Offset 20 dB.

Therefore the plots represented the measured results of the field strength in spite of the unit dB μ V.



Operated from DC 24 V

Frequency Range: 9 kHz ~ 150 kHz



Frequency Range: 150 kHz ~ 1.5 MHz



Frequency Range: 1.5 MHz ~ 30 MHz




Remark: during the measurements, the correction factor (antenna factor and cable loss) was compensated as Offset 20 dB.

Therefore the plots represented the measured results of the field strength in spite of the unit dB μ V.



Frequency Range: 30 MHz ~ 600 MHz


Operated from DC 12 V





Frequency Range: 30 MHz ~ 600 MHz



Operated from DC 24 V





Frequency Range: 600 MHz ~ 1 GHz



Operated from DC 12 V





Frequency Range: 600 MHz ~ 1 GHz



Operated from DC 24 V





Frequency Range: 1 GHz ~ 5 GHz

Operated from DC 12 V





Frequency Range: 1 GHz ~ 5 GHz

Operated from DC 24 V

