

TEST REPORT

Testing Laboratory:**SK Tech Co., Ltd.**

88, Geulgaetul-ro, 81beon-gil,
Wabu-eup, Namyangju-si,
Gyeonggi-do, Korea
TEL: +82-31-576-2204
FAX: +82-31-576-2205

Test Report Number: SKT-RFC-200002**Date of issue: Aug 28, 2020****Applicant:****KYUNGWOO SYSTECH INC.**

#401, Daeryung Post Tower 5, 68, Digital-ro 9, Geumcheon-gu, Seoul,
South Korea

Manufacturer:**KYUNGWOO SYSTECH INC.**

#401, Daeryung Post Tower 5, 68, Digital-ro 9, Geumcheon-gu, Seoul,
South Korea

Product:

SMK READER

Model:**SMK-HXV-10****FCC ID:**

ZE8- SMK-HXV-10

Project number:

SKTEU20-0470

EUT received:

April 28, 2020

Applied standards:

ANSI C63.10-2013 and ANSI C63.4-2014

Rule parts:

FCC Part 15 Subpart C - Intentional radiators

Equipment Class:**DCD - Part 15 Low Power Transmitter Below 1705kHz****Remarks to the standards:** None

The above equipment has been tested by SK Tech Co., Ltd., and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product or system, which was tested.

Ahn downon / **Testing Engineer**Changmin Kim / **Technical Manager**

This report shall not be reproduced except in full, without the written approval of SK Tech Co., Ltd. The client should not use it to claim product endorsement by any government agencies.



Revision History of Test Report

Rev.	Revisions	Effect page	Approved by	Date
-	Initial issue	All	Changmin Kim	Aug 28, 2020



TABLE OF CONTENTS

1	Summary of test results	4
2	Description of equipment under test (EUT)	5
3	Test and measurement conditions	6
	3.1. Test configuration (arrangement of EUT)	6
	3.2. Description of support units (accessory equipment).....	6
	3.3. Interconnection and I/O cables	6
	3.4. Measurement Uncertainty (<i>U</i>)	6
	3.5. Test date	6
4	Facilities and accreditations	7
	4.1. Facilities.....	7
	4.2. Accreditations	7
	4.3. List of test and measurement instruments.....	7
5	Test and measurements	8
	5.1. Antenna requirement	8
	5.2. Radiated emissions	9



1 Summary of test results

Requirement	CFR 47 Section	Result
Antenna Requirement	15.203	Meets the requirements
Radiated Emissions	15.209(a)	Meets the requirements
AC power line Conducted emissions	15.207(a)	N/A

Note: The EUT is operated from the battery (DC 12 V or DC 24 V) in a vehicle, and therefore the test suites related to AC Mains port were not applicable.



2 Description of equipment under test (EUT)

Product: SMK READER
Model: SMK-HXV-10
Serial number: None (prototype)

Model differences:

Model name	Difference	Tested (checked)
SMK-HXV-10	fully tested model that was provided by the applicant	☒

Technical data:

Power source	DC 12 V / DC 24 V (powered from the battery in a vehicle)	
Local Oscillator or X-Tal	8 MHz, 26 MHz	
Transmit Frequency	433.92 MHz	125 kHz
Antenna Type	Integral chip antenna	Integral loop coil antenna
Type of Modulation	GFSK	ASK
RF Output power	86.4 dBμV/m (PEAK) (measured @ 3m)	89.3 dBμV/m(PEAK) (measured @ 3m)

Note: * The test report for Equipment Class DSC was issued with other test report number.

** The test report for the compliance with FCC Part 15B as a digital device was issued with other test report number.


I/O port	Type	Q'ty	Remark
CN1	12-pin connector (DC IN, ACC, Actuator, LF ANT, etc.)	1	



3 Test and measurement conditions

3.1. Test configuration (arrangement of EUT)

The EUT was operated from DC Power Supply (12 V or 24 V).



3.2. Description of support units (accessory equipment)

The following support units or accessories were used to form a representative test configuration during the tests.

#	Equipment	Manufacturer	Model No.	Serial No.
1	DC Power Supply	HP	6633A	2838A-01000

3.3. Interconnection and I/O cables

The following support units or accessories were used to form a representative test configuration during the tests.

#	Start		End		Cable	
	Name	I/O port	Name	I/O port	length (m)	shielded (Y/N)
1	EUT	DC IN	DC Power Supply	DC OUT	2.0	N

3.4. Measurement Uncertainty (U)

Measurement Item	Combined Standard Uncertainty U_c	Expanded Uncertainty $U = k \times U_c (k = 2)$
Conducted emissions	$1.4 \pm \text{dB}$	$2.8 \pm \text{dB}$
Radiated emissions (9 kHz to 30 MHz)	$1.45 \pm \text{dB}$	$2.9 \pm \text{dB}$
Radiated emissions (30 MHz to 1000 MHz)	$2.5 \pm \text{dB}$	$5.0 \pm \text{dB}$

3.5. Test date

Date Tested	July 15, 2020 – August 3, 2020
-------------	--------------------------------



4 Facilities and accreditations

4.1. Facilities

All of the measurements described in this report were performed at SK Tech Co., Ltd

Site I: 88, Geulgaetul-ro 81beon-gil, Wabu-eup, Namyangju-si, Gyeonggi-do, Korea

Site II: 124-8, Geulgaetul-ro, Wabu-eup, Namyangju-si, Gyeonggi-do, Korea

The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-4. The sites comply with the Normalized Site Attenuation requirements given in ANSI C63.4, and site VSWR requirements specified in CISPR 16-1-4. The measuring apparatus and ancillary equipment conform to CISPR 16-1 series.

4.2. Accreditations

The laboratory has been also notified to FCC by RRA as a Conformity Assessment Body, and designated to perform compliance testing on equipment subject to Supplier's Declaration of Conformity (SDoC) and Certification under Parts 15 and 18 of the FCC Rules.

Designation No. KR0007

4.3. List of test and measurement instruments

No	Description	Model	Manufacturer	Serial No.	Cal. due	Use
1	EMI Test Receiver	ESR26	Rohde&Schwarz	101441	2021.07.24	☒
2	EMI Test Receiver	ESIB40	Rohde&Schwarz	100277	2021.02.25	☒
3	Pre-amplifier (30 MHz - 1 GHz)	MLA-10K01-B01-27	TSJ	2005350	2021.06.08	☒
4	Pre-amplifier (1 GHz - 18 GHz)	MLA-100M18-B02-38	TSJ	1539546	2021.02.03	☒
5	Attenuator (6dB)	18N5W	API Technology	-	2021.07.06	☒
6	Loop Antenna	HFH2-Z2	Schwarzbeck	863048/019	2021.12.20	☒
7	BILOG Broadband Antenna	VULB9168	Schwarzbeck	9168-230	2021.07.06	☒
9	DC Power Supply	6633A	HP	2838A-01000	2021.06.09	☒
10	Signal Generator	SMB100A	R & S	180704	2021-02-25	☒
11	Digital Thermo-Hygrometer	608-H1	Testo	-	2021.06.11	☒



5 Test and measurements

5.1. Antenna requirement

5.1.1 Regulation

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

5.1.2 Result:

PASS

The EUT has an Internal loop antenna and meets the requirements of this section.



5.2. Radiated emissions

5.2.1 Regulation

FCC 47CFR15 - 15.209

- (a) Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field strength limit ($\mu\text{V/m}$)	Field strength limit ($\text{dB}\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	$2400/F$ (kHz) = 266.7 - 4.9	48.5 - 13.8	300
0.490 - 1.705	$24000/F$ (kHz) = 49.0 - 14.1	33.8 - 23.0	30
1.705 - 30.0	30	29.5	30
30 - 88	100	40.0	3
88 - 216	150	43.5	3
216 - 960	200	46.0	3
Above 960	500	54.0	3

* The emission limits shown in the above table are based on measurement instrumentation employing a CISPR quasi-peak detector. For the frequency bands 9 - 90 kHz, 110 - 490 kHz and above 1000 MHz, the radiated emission limits are based on measurements employing an average detector.

* The lower limit shall apply at the transition frequencies.

5.2.2 Measurement Procedure

The EUT repeatedly transmitted RF signals and the following measurement procedure specified in ANSI C63.10-2013 was used

Radiated Emissions Test, 9 kHz to 30 MHz (Magnetic Field Test)

- The preliminary radiated measurements were performed to determine the frequency producing the maximum emissions at a distance of 3 meters according to Section 15.31(f)(2).
- The EUT was placed on the top of the 0.8-meter height, 1 × 1.5 meter non-metallic table.
- Emissions from the EUT are maximized by adjusting the orientation of the Loop antenna and rotating the EUT on the turntable. Manipulating the system cables also maximizes EUT emissions if applicable.
- To obtain the final measurement data, each frequency found during preliminary measurements was re-examined and investigated. The test-receiver system was set up to average, peak, and quasi-peak detector function with specified bandwidth.
- The EUT was situated in three orthogonal planes (if appropriate).

Radiated Emissions Test, above 30 MHz

- The preliminary radiated measurements were performed to determine the frequency producing the maximum emissions in an anechoic chamber at a distance of 3 meters.
- The EUT was placed on the top of the 0.8-meter height (or 1.5 meter height for above 1 GHz), 1 × 1.5 meter non-metallic table. To find the maximum emission levels, the height of a measuring antenna was changed and the turntable was rotated 360°.
- The antenna polarization was also changed from vertical to horizontal. The spectrum was scanned from 30 to 1000 MHz using the Bilog broadband antenna, and from 1 GHz to tenth harmonic of the highest fundamental frequency using the horn antenna.



- (d) Each frequency found during preliminary measurements was re-examined and investigated. The test-receiver system was set up to average, peak, and quasi-peak detector function with specified bandwidth.
- (e) The EUT was situated in three orthogonal planes (if appropriate).

5.2.3 Calculation of the field strength limits below 30 MHz

- (a) No special calculation for obtaining the field strength in dB μ V/m is necessary, because the EMI receiver and the active loop antenna operate as a system, where the reading gives directly the field strength result (dB μ V/m). The antenna factors and cable losses are already taken into consideration.
- (b) For test distance other than what is specified, but fulfilling the requirements of section 15.31 (f) (2) the field strength is calculated by adding additionally an extrapolation factor of 40dB/decade (inverse linear distance for field strength measurements).
- (c) All following emission measurements were performed using the test receiver's average, peak, and quasi-peak detector function with specified bandwidth.
- (d) The basic equation is as follows;

$$FS = RA + DF$$

Where

FS = Field strength in dB μ V/m

RA = Receiver Amplitude in dB μ V/m

DF = Distance Extrapolation Factor in dB

Where $DF = 40\log(D_{TEST} / D_{SPEC})$ where D_{TEST} = Test Distance and D_{SPEC} = Specified Distance

$DF = 40\log(3m/300m) = -80$ dB, for frequency band: 0.009 to 0.490 MHz

$DF = 40\log(3m/30m) = -40$ dB, for frequency band: 0.490 to 30 MHz



5.2.4 Test Results:

PASS

Table 1: Measured values of the Field strength - Internal Loop antenna

X-axis is worst-case configuration among 3 axis.

For the measurements under below 30 MHz (DC 12 V)

Freq. (kHz)	RBW (kHz)	Reading (dBμV)		AF (dB/m)	Cable Loss (dB)	Actual (dBμV/m)		Limit (at 3m) (dBμV/m)		Margin (dB)		Remark
		PK	AV			PK	AV	PK	AV	PK	AV	
125.0	0.2	69.0	41.1	20.2	0.1	89.3	61.4	125.7	105.7	36.4	44.3	X-axis
280.0	0.2	21.0	8.0	20.1	0.1	41.2	28.2	118.7	98.7	77.5	70.5	

For the measurements under below 30 MHz (DC 24 V)

Freq. (kHz)	RBW (kHz)	Reading (dBμV)		AF (dB/m)	Cable Loss (dB)	Actual (dBμV/m)		Limit (at 3m) (dBμV/m)		Margin (dB)		Remark
		PK	AV			PK	AV	PK	AV	PK	AV	
125.0	0.2	69	41.1	20.2	0.1	89.3	61.4	125.7	105.7	36.4	44.3	X-axis
280.0	0.2	21.4	8.3	20.1	0.1	41.6	28.5	118.7	98.7	77.1	70.2	

Actual (dBμV/m) = Reading + AF + Cable Loss

Margin (dB) = Limit – Actual

Note: These test results were measured at the 3 m distance.



Table 4: Measured values of the Field strength - Internal Loop antenna

For the measurements from 30 MHz to 1 GHz (Internal Loop antenna, DC 12 V)

Frequency (MHz)	Pol. (V/H)	Height (m)	Reading (dBμV)	AMP (dB)	AF (dB/m)	CL (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
87.536	V	1.12	39.5	30.3	14.0	1.3	24.5	40.0	15.5	X-axis
152.204	H	1.94	43.8	30.0	18.9	1.7	34.4	43.5	9.1	
287.992	H	1.19	50.5	30.0	19.0	2.3	41.8	46.0	4.2	
360.000	H	1.01	42.1	30.1	20.7	2.6	35.3	46.0	10.7	
904.008	H	1.00	30.7	30.3	29.3	4.1	33.8	46.0	12.2	

For the measurements from 30 MHz to 1 GHz (Internal Loop antenna, DC 24 V)

Frequency (MHz)	Pol. (V/H)	Height (m)	Reading (dBμV)	AMP (dB)	AF (dB/m)	CL (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
89.474	H	3.90	41.4	30.3	13.8	1.3	26.2	43.5	17.3	X-axis
152.786	H	2.08	43.7	30.0	18.9	1.7	34.3	43.5	9.2	
287.990	H	1.06	50.6	30.0	19.0	2.3	41.9	46.0	4.1	
359.987	H	1.01	41.8	30.1	20.7	2.6	35.0	46.0	11.0	
919.975	H	1.01	31.9	30.4	29.5	4.1	35.1	46.0	10.9	

V/H: Vertical / Horizontal polarization

AMP, AF and CL: pre-amplifier gain, antenna factor and cable loss including an attenuator/filter if used

Actual = Reading - AMP + AF + CL



Margin = Limit - Actual



Figure 1. Emission plot for the preliminary radiated measurements



The worst-case plots were attached.

Internal Loop antenna (DC 12 V)







Internal Loop antenna (DC 24 V)





Frequency Range: 30 MHz ~ 1 GHz

Internal Loop antenna (DC 12 V)





Frequency Range: 30 MHz ~ 1 GHz

Internal Loop antenna (DC 24 V)

