FCC Test Report

Report No.: AGC00B110104F2

FCC ID : ZEATSN51B

PRODUCT DESIGNATION: Portable scanner

BRAND NAME : N/A

TEST MODEL : TSN51B

CLIENT : Sky Light Digital Limited

DATE OF ISSUE : Mar.23, 2011

STANDARD(S) : FCC Part 15 Rules

Attestation of Global Compliance Co., Ltd.

CAUTION: This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.

Page 1 of 60

VERIFICATION OF COMPLIANCE

	Sky Light Digital Limited		
Applicant	Rm.1009 Kwong Sang Hong Centre,151-153 Hoi Bun Road,Kwun Tong,Kowloon,Hong Kong		
NA - must - storm - m	Sky Light Electronic(ShenZhen)Limited		
Manufacturer	No.6 Building,JinBi Industrial Area,HuangTian,BaoAn,Shenzhen,China.		
Product Designation	Portable scanner		
Brand Name	N/A		
Model Name	TSN51B,TSN52B,TSN53B,TSN54B		
Model difference	The above models all the same except for appearance color.		
FCC ID	ZEATSN51B		
Report Number	AGC00B110104F2		
Date of Test	Mar.16, 2011 to Mar.23, 2011		

WE HEREBY CERTIFY THAT:

The above equipment was tested by Attestation of Global Compliance Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2003) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC Rules Part 15.247.

Checked By:

Mary Liu Mar.23, 2011

Authorized By

Forrest Lei Mar.23, 2011

TABLE OF CONTENTS

1. GENERAL INFORMATION	4
1.1 PRODUCT DESCRIPTION	
1.3 RECEIVER INPUT BANDWIDTH 1.4 EXAMPLE OF A HOPPING SEQUENCY IN DATA MODE	
1.5 EQUALLY AVERAGE USE OF FREQUENCIES AND BEHAVIOUR	
1.6 RELATED SUBMITTAL(S) / GRANT (S)	
1.7 TEST METHODOLOGY	
1.8 TEST FACILITY 1.9 SPECIAL ACCESSORIES	
1.10 EQUIPMENT MODIFICATIONS	
2. SYSTEM TEST CONFIGURATION	
2.1 CONFIGURATION OF TESTED SYSTEM2 EQUIPMENT USED IN TESTED SYSTEM	
3. SUMMARY OF TEST RESULTS	8
4. DESCRIPTION OF TEST MODES	8
5 MAXIMUM OUTPUT POWER	9
5.1 MEASUREMENT PROCEDURE	
5.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	9
5.3 MEASUREMENT EQUIPMENT USED	1(
5.4 LIMITS AND MEASUREMENT RESULT	
6 20 DB BANDWIDTH	
6.1 MEASUREMENT PROCEDURE	12
6.3 MEASUREMENT EQUIPMENT USED	
6.4 LIMITS AND MEASUREMENT RESULTS	
7. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY (N/A)	
7.1 MEASUREMENT PROCEDURE	
7.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	
7.3 MEASUREMENT EQUIPMENT USED	
8. OUT OF BAND EMISSION	
8.1 MEASUREMENT PROCEDURE	
8.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	
8.3 MEASUREMENT EQUIPMENT USED	19
8.4 LIMITS AND MEASUREMENT RESULT	
9 BAND EDGE EMISSION	29
9.1 MEASUREMENT PROCEDURE	
9.2 TEST SET-UP	
9.3 TEST RESULT	
10 NUMBER OF HOPPING FREQUENCY	
10.1 MEASUREMENT PROCEDURE	
10.2 TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)	
10.4 LIMITS AND MEASUREMENT RESULT	

Report No.: AGC00B110104F2 Page 3 of 60

11	TIME OF OCCUPANCY (DWELL TIME)
11.1 MEASUREMENT PROCEDURE	36
11.2 TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)	
11.3 MEASUREMENT EQUIPMENT USED	36
11.4 LIMITS AND MEASUREMENT RESULT	36
12. FREQUENCY SEPARATION	43
12.1 MEASUREMENT PROCEDURE	43
12.2 TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)	
12.3 MEASUREMENT EQUIPMENT USED	
12.4 LIMITS AND MEASUREMENT RESULT	
13 FCC LINE CONDUCTED EMISSION TEST	46
13.1 LIMITS OF LINE CONDUCTED EMISSION TEST	
13.2 BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST	
13.3 PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION	
13.4 FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	
13.5 TEST RESULT OF LINE CONDUCTED EMISSION TEST	
14 FCC RADIATED EMISSION TEST	50
14.1 LIMITS OF RADIATED EMISSION TEST	
14.2 BLOCK DIAGRAM OF RADIATED EMISSION TEST	
14.3 PRELIMINARY PROCEDURE OF RADIATED EMISSION TEST	
14.4 FINAL PROCEDURE OF RADIATED EMISSION TEST	
14.5 TEST RESULT OF RADIATED EMISSION TEST	
APPENDIX I	
PHOTOGRAPHS OF THE EUT	54
APPENDIX II	60
PHOTOGRAPHS OF THE TEST SETUP	60

Page 4 of 60

1. GENERAL INFORMATION

1.1 PRODUCT DESCRIPTION

The EUT is a **Portable scanner** designed as an "Communication Device". It is designed by way of utilizing the FHSS technology to achieve the system operation.

A major technical description of EUT is described as following

Operation Frequency	2.402 GHz to 2.480GHz
Rated Output Power	Bluetooth (1Mbps) 1.89dBm Bluetooth EDR (2Mbps) 1.74dBm Bluetooth EDR(3Mbps) 1.79 dBm
Modulation	GFSK, π /4-DQPSK, 8-DPSK
Number of channels	79
Antenna Designation	Integrated Antenna
Antenna Gain	0.83dBi
Power Supply	DC4.2V by battery or USB Operated

1.2 TABLE OF CARRIER FREQUENCYS

Frequency Band	Channel Number	Frequency	
	0	2402MHZ	
	1	2403MHZ	
2400-2402 5MUZ	:	:	
2400~2483.5MHZ	38	2440 MHZ	
	39	2441 MHZ	
	40	2442 MHZ	
	:	:	
	77	2479 MHZ	
	78	2480 MHZ	

1.3 RECEIVER INPUT BANDWIDTH

The input bandwidth of the receiver is 1MHZ,In every connection one Bluetooth device is the master and the other one is slave. The master determines the hopping sequence. The slave follows this sequence. Both devices shift between RX and TX time slot according to the clock of the master. Additionally the type of connection(e.g. single of multislot packet) is set up at the beginning of the connection. The master adapts its hopping frequency and its TX/RX timing according to the packet type of the connection. Also the slave of the connection will use these settings. Repeating of a packet has no influence on the hopping sequence. The hopping sequence generated by the master of the connection will be followed in any case. That means, a repeated packet will not

be send on the same frequency, it is send on the next frequency of the hopping sequence.

Page 5 of 60

1.4 EXAMPLE OF A HOPPING SEQUENCY IN DATA MODE

Example of a 79 hopping sequence in data mode: 40,21,44,23,42,53,46,55,48,33,52,35,50,65,54,67 56,37,60,39,58,69,62,71,64,25,68,27,66,57,70,59 72,29,76,31,74,61,78,63,01,41,05,43,03,73,07,75 09,45,13,47,11,77,15,00,64,49,66,53,68,02,70,06 01,51,03,55,05,04

1.5 EQUALLY AVERAGE USE OF FREQUENCIES AND BEHAVIOUR

The generation of the hopping sequence in connection mode depends essentially on two input values:

1 LAP/UAP of the master of the connection

2 Internal master clock

The LAP(lower address part) are the 24 LSB's of the 48 BD_ADDRESS. The BD_ADDRESS is an unambiguous number of every Bluetooth unit. The UAP(upper address part) are the 24MSB's of the 48BD_ADDRESS

The internal clock of a Bluetooth unit is derived from a free running clock which is never adjusted and Is never turned off. For synchronisation with other units only offset are used. It has no relation to the time Of the day. Its resolution is at least half the RX/TX slot length of 312.5us. The clock has a cycle of about One day(23h30). In most case it is implemented as 28 bit counter. For the deriving of the hopping sequence the entire.

LAP(24 bits),4LSB's(4bits)(Input 1) and the 27MSB's of the clock(Input 2) are used. With this input values different mathematical procedures(permutations, additions, XOR-operations) are performed to generate te

Sequence. This will be done at the beginning of every new transmission.

Regarding short transmissions the Bluetooth system has the following behaviour:

The first connection between the two devices is established, a hopping sequence was generated. For Transmitting the wanted data the complete hopping sequence was not used. The connection ended. The second connection will be established. A new hopping sequence is generated. Due to the fact the Bluetooth clock has a different value, because the period between the two transmission is longer(and it Cannot be shorter)than the minimum resolution of the clock(312.5us). The hopping sequence will always Differ from the first one.

1.6 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID**: **ZEATSN51B** filling to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

1.7 TEST METHODOLOGY

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4 (2003). Radiated testing was performed at an antenna to EUT distance 3 meters.

Page 6 of 60

1.8 TEST FACILITY

All measurement facilities used to collect the measurement data are located at Attestation of Global Compliance Co., Ltd.

1F., No.2 Building, Huafeng No.1 Technical Industrial Park, Sanwei, Xixiang, Baoan District, Shenzhen The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4: 2003. FCC register No.: 259865

1.9 SPECIAL ACCESSORIES

Not available for this EUT intended for grant.

1.10 EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

Page 7 of 60

2. SYSTEM TEST CONFIGURATION

2.1 CONFIGURATION OF TESTED SYSTEM

EUT

2.2 EQUIPMENT USED IN TESTED SYSTEM

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID
1	Portable scanner	N/A	TSN51B	ZEATSN51B

Page 8 of 60

3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.207	Conduction Emission	Compliant
§15.209	Radiated Emission	Compliant
§15.247	Maximum Output Power	Compliant
§15.247	20 dB Bandwidth	Compliant
§15.247	Band Edges	Compliant
§15.247	Spurious Emission	Compliant
§15.247	Frequency Separation	Compliant
§15.247	Number of Hopping Frequency	Compliant
§15.247	Time of Occupancy	Compliant

4. DESCRIPTION OF TEST MODES

- 1. The EUT has been set to operate continuously on the lowest, middle and highest operation frequency individually.
- 2. The EUT stays in continuous transmitting mode on the operation frequency being set.


Page 9 of 60

5 MAXIMUM OUTPUT POWER

5.1 MEASUREMENT PROCEDURE

- 1. The EUT was placed on a turn table which is 0.8m above ground plane.
- 2. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 3. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 4. Set SPA Centre Frequency = Operation Frequency, RBW= 3 MHz, VBW= 3 MHz.
- 5. Set SPA Trace 1 Max hold, then View.

5.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)



Report No.: AGC00B110104F2 Page 10 of 60

5.3 MEASUREMENT EQUIPMENT USED

Description	Manufacturer	Model	SERIAL NUMBER	Cal. Date	Cal. Due
Spectrum Analyzer	Agilent	E4440A	N/A	06/29/2010	06/28/2011
Amplifier	EM	EM30180	0607030	06/29/2010	06/28/2011
Horn Antenna	EM	EM-AH-10180	N/A	06/29/2010	06/28/2011
EMI Test Receiver	Rohde & Schwarz	ESCI	N/A	06/29/2010	06/28/2011
Amplifier	EM	EM30180	N/A	06/29/2010	06/28/2011
Bilogical Antenna	A.H. Systems Inc.	SAS-521-4	N/A	06/29/2010	06/28/2011
Loop Antenna	Daze	ZN30900N	SEL0097	06/29/2010	06/28/2011
Isolation Transformer	LETEAC	LTBK		06/29/2010	06/28/2011

Report No.: AGC00B110104F2 Page 11 of 60

5.4 LIMITS AND MEASUREMENT RESULT

1MBPS LIMITS AND MEASUREMENT RESULT				
Frequency (GHz)	Result (dBm)	Applicable Limits (dBm)	Pass or Fail	
2.402	1.89	30	Pass	
2.441	1.57	30	Pass	
2.480	1.68	30	Pass	

2MBPS LIMITS AND MEASUREMENT RESULT				
Frequency (GHz)	Result (dBm)	Applicable Limits (dBm)	Pass or Fail	
2.402	1.74	30	Pass	
2.441	1.69	30	Pass	
2.480	1.58	30	Pass	

3MBPS LIMITS AND MEASUREMENT RESULT				
Frequency (GHz)	Result (dBm)	Applicable Limits (dBm)	Pass or Fail	
2.402	1.55	30	Pass	
2.441	1.49	30	Pass	
2.480	1.79	30	Pass	

Page 12 of 60

6 20 DB BANDWIDTH

6.1 MEASUREMENT PROCEDURE

- 1. The EUT was placed on a turn table which is 0.8m above ground plane.
- 2. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 3, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set SPA Centre Frequency = Operation Frequency, RBW= 100 KHz, VBW= 100 KHz.
- 4. Set SPA Trace 1 Max hold, then View.

6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The Same as described in Section 5.2

6.3 MEASUREMENT EQUIPMENT USED

The same as described in Section 5.3

6.4 LIMITS AND MEASUREMENT RESULTS


BLUETOOTH 1MBPS LIMITS AND MEASUREMENT RESULT				
Applicable Limite	Measurement Result			
Applicable Limits	Test Data (MHz)		Criteria	
	Low Channel	0.957	PASS	
	Middle Channel	0.960	PASS	
	High Channel	0.969	PASS	

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



Page 13 of 60

TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL




TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



Page 14 of 60


BLUETOOTH 2MBPS LIMITS AND MEASUREMENT RESULT					
Applicable Limite	Measurement Result				
Applicable Limits	Test Da	Criteria			
	Low Channel	1.301	PASS		
	Middle Channel	1.282	PASS		
	High Channel	1.300	PASS		

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



Page 15 of 60

TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



Page 16 of 60


BLUETOOTH 3MBPS LIMITS AND MEASUREMENT RESULT					
Applicable Limits		Measurement Result			
Applicable Limits	Test Da	Criteria			
	Low Channel	1.3	PASS		
	Middle Channel	1.299	PASS		
	High Channel	1.298	PASS		

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



Page 17 of 60

TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL




Page 18 of 60

7. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY (N/A)

7.1 MEASUREMENT PROCEDURE

- (1). The EUT was placed on a turn table which is 0.8m above ground plane.
- (2). Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- (3), Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- (4). Set SPA Centre Frequency = Operation Frequency, RBW= 3 KHz, VBW= 10 KHz., Sweep time= Auto
- (5). Set SPA Trace 1 Max hold, then View.

7.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)



7.3 MEASUREMENT EQUIPMENT USED

SHIELDING ROOM					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Agilent	E4440A	N/A	06/29/2010	06/28/2011

7.4 LIMITS AND MEASUREMENT RESULT

LIMITS AND MEASUREMENT RESULT					
Applicable Limite	Measurement Result				
Applicable Limits	Test Data (di	Criteria			
	Low Channel				
8 dBm / 3KHz	Middle Channel				
	High Channel				

Page 19 of 60

8. OUT OF BAND EMISSION

8.1 MEASUREMENT PROCEDURE

- 1. The EUT was placed on a turn table which is 0.8m above ground plane.
- 2. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 3, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set SPA Centre Frequency = Operation Frequency, RBW= 100 KHz, VBW= 100 KHz.
- 4. Set SPA Trace 1 Max hold, then View.

8.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The Same as described in section 5.2

- 1. Conducted test setup
- 2. Radiated Emission test Setup below 1GHz and Above 1GHz

8.3 MEASUREMENT EQUIPMENT USED


The Same as described in section 5.3


8.4 LIMITS AND MEASUREMENT RESULT

LIMITS AND MEASUREMENT RESULT					
Applicable Limite	Measurement Result				
Applicable Limits	Test Data	Criteria			
In any 100 KHz Bandwidth Outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produce by the intentional radiator shall be at least 20 dB below that in 100KHz bandwidth within the band that contains the highest	At least -20dBc than the limit Specified on the BOTTOM Channel	PASS			
level of the desired power. In addition, radiation emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in§15.209(a))	At least -20dBc than the limit Specified on the TOP Channel	PASS			

Report No.: AGC00B110104F2 Page 20 of 60


TEST PLOT OF OUT OF BAND EMISSIONS FOR LOW CHANNEL(1Mbps)






Report No.: AGC00B110104F2 Page 21 of 60


TEST PLOT OF OUT OF BAND EMISSIONS FOR MIDDLE CHANNEL (1Mbps)






Page 22 of 60


TEST PLOT OF OUT OF BAND EMISSIONS FOR HIGH CHANNEL(1Mbps)






Page 23 of 60


TEST PLOT OF OUT OF BAND EMISSIONS FOR HIGH CHANNEL(2Mbps)






Report No.: AGC00B110104F2 Page 24 of 60

TEST PLOT OF OUT OF BAND EMISSIONS FOR HIGH CHANNEL(3Mbps)





Page 25 of 60

RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequency to 30MHz.

RADIATED EMISSION BELOW 1GHZ

EUT	Portable scanner	Model Name	TSN51B
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC4.2V
Test Mode	BT2402MHZ	Modulation	GFSK

Freq. (MHZ)	Ant.Pol. H/V	Detector (PK/QP)	Reading (dBuV)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
42.77	Н	Peak	15.02	15.33	30.35	40	-9.65
124.78	Н	Peak	16.03	14.11	30.14	43.5	-13.36
175.02	Н	Peak	10.97	15.66	26.63	43.5	-16.87
421.74	Н	Peak	12.85	18.74	31.95	46	-14.05
640.89	Н	Peak	9.36	26.02	35.38	46	-10.62
917.25	Н	Peak	8.48	25.14	33.62	46	-12.38
56.25	V	Peak	15.45	10.25	25.70	40	-14.30
78.03	V	Peak	18.25	10.74	28.99	40	-11.01
132.78	V	Peak	19.62	13.88	33.50	43.5	-10.00
174.00	V	Peak	13.47	18.76	32.23	43.5	-11.27
725.12	V	Peak	6.87	25.33	32.20	46	-13.80
940.28	V	Peak	5.02	27.02	32.04	46	-13.96

Report No.: AGC00B110104F2 Page 26 of 60

EUT	Portable scanner	Model Name	TSN51B
	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC4.2V
Test Mode	BT2441MHZ	Modulation	GFSK

Freq. (MHZ)	Ant.Pol. H/V	Detector (PK/QP)	Reading (dBuV)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
	Н	Peak					
	Н	Peak					
	V	Peak					
	V	Peak					

EUT	Portable scanner	Model Name	TSN51B
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC4.2V
Test Mode	BT2480MHZ	Modulation	GFSK

Freq. (MHZ)	Ant.Pol. H/V	Detector (PK/QP)	Reading (dBuV)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
	Н	Peak					
	Н	Peak					
	V	Peak					
	V	Peak					

Report No.: AGC00B110104F2 Page 27 of 60

EUT	Portable scanner	Model Name	TSN51B
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC4.2V
Test Mode	BT2402/2441/2480MHZ	Modulation	π /4-DQPSK 8-DPSK

Freq. (MHZ)	Ant.Pol. H/V	Detector (PK/QP)	Reading (dBuV)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
	Н	Peak					
	Н	Peak					
	V	Peak					
	V	Peak					

Note: "--"means the mode at least have 20dB margin.

Page 28 of 60

RADIATED EMISSION ABOVE 1GHZ

EUT	Portable scanner	Model Name	TSN51B
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC4.2V
Test Mode	BT2402/2441/2480MHZ	Modulation	GFSK

Freq.	Ant.Pol.	Peak	AV	Factor	Re	sult	Peak	AV	Margin
(MHZ)	H/V	Reading (dBuV)	Reading (dBuV)	(dB)	Peak (dBuV/m)	AV (dBuV/m)	Limit (dBuV/m)	Limit (dBuV/m)	
	Н								
	Н								
	V								
	V								

EUT	Portable scanner	Model Name	TSN51B
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC4.2V
Test Mode	BT2402/2441/2480MHZ	Modulation	π /4-DQPSK 8-DPSK

Freq.	Ant.Pol.	Peak	AV	Factor	Re	sult	Peak	AV	Margin
(MHZ)	H/V	Reading (dBuV)	Reading (dBuV)	(dB)	Peak (dBuV/m)	AV (dBuV/m)	Limit (dBuV/m)	Limit (dBuV/m)	
	Н								
	Н								
	V								
	V								

Note: This Handheld EUT was tested in 3 orthogonal positions and the worst-case data was presented. Note:"---"means the mode at least have 20dB margin.

Page 29 of 60

9 BAND EDGE EMISSION

9.1 MEASUREMENT PROCEDURE


- 1, Set the EUT Work on the top, the bottom operation frequency individually.
- 2. Set SPA Start or Stop Frequency = Operation Frequency, RBW= 100kHz,
- 3. The band edges was measured and recorded.

9.2 TEST SET-UP

The Same as described in section 5.2


9.3 TEST RESULT






Page 30 of 60






TEST PLOT OF BAND ELDG FOR LOW CHANNEL(2Mbps)




Page 31 of 60






TEST PLOT OF BAND ELDG FOR LOW CHANNEL(3Mbps)



Page 32 of 60



Page 33 of 60

EUT	Portable scanner	Model Name	TSN51B
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC4.2V
Test Mode	BT2402MHZ	Modulation	GFSK

Freq.	Ant.Pol.	Peak	AV	Factor	Re	sult	Peak	AV	Margin
(MHZ)	H/V	Reading (dBuV)	Reading (dBuV)	(dB)	Peak (dBuV/m)	AV (dBuV/m)	Limit (dBuV/m)	Limit (dBuV/m)	
	Н								
	Н								
	V								
	V								

EUT	Portable scanner	Model Name	TSN51B
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC4.2V
Test Mode	BT2480MHZ	Modulation	GFSK

Freq.	Ant.Pol.	Peak	AV	Factor	Re	sult	Peak	AV	Margin
(MHZ)	H/V	Reading (dBuV)	Reading (dBuV)	(dB)	Peak (dBuV/m)	AV (dBuV/m)	Limit (dBuV/m)	Limit (dBuV/m)	
	Н		-						
	Н								
	V								
	V								

Note: "--"means other frequencies at least have 20dB margin.

The other modulation modes comply with standard requirement and at least have 20dB margin.

Page 34 of 60

10 NUMBER OF HOPPING FREQUENCY

10.1 MEASUREMENT PROCEDURE

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer.
- 3. Set the spectrum analyzer Start = 2.4GHz Stop = 2.4835GHz
- 4. Set the Spectrum Analyzer as RBW = 100KHZ

10.2 TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 5.2

1. Conducted Method.


10.3 MEASUREMENT EQUIPMENT USED

The Same as described in section 5.3

10.4 LIMITS AND MEASUREMENT RESULT

TOTAL NO. OF HOPPING CHANNEL	LIMIT (NO. OF CH)	MEASUREMENT (NO. OF CH)	RESULT
	>=15	79	PASS

Page 35 of 60



Page 36 of 60

11 TIME OF OCCUPANCY (DWELL TIME)

11.1 MEASUREMENT PROCEDURE

- 1. Place the EUT on the table and set it in transmitting mode
- 2. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer
- 3. Set center frequency of spectrum analyzer = Operating frequency
- 4. Set the spectrum analyzer as RBW, VBW=1MHz, Span = 0 Hz,

11.2 TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 5.2 Conducted Method

11.3 MEASUREMENT EQUIPMENT USED

The same as described in section 5.3

11.4 LIMITS AND MEASUREMENT RESULT


Bluetooth 1Mbps Test Result

Channel	Time of Pulse for DH5 (ms)	Period Time (s)	Sweep Time (ms)	Limit (ms)
Low	2.90	31.6	309.33	400
Middle	2.86	31.6	305.07	400
High	2.88	31.6	307.20	400


Low Channel Time 2.90*(1600/6)/79*31.6=309.33ms Middle Channel Time 2.86*(1600/6)/79*31.6=305.07ms High Channel Time 2.88*(1600/6)/79*31.6=307.20ms

Page 37 of 60

TEST PLOT OF LOW CHANNEL




TEST PLOT OF MIDDLE CHANNEL



Page 38 of 60

TEST PLOT OF HIGH CHANNEL




Bluetooth 2Mbps Test Result

Channel	Time of Pulse for DH5 (ms)	Period Time (s)	Sweep Time (ms)	Limit (ms)
Low	2.92	31.6	311.47	400
Middle	2.88	31.6	307.20	400
High	2.893	31.6	308.59	400


Low Channel Time 2.92*(1600/6)/79*31.6=311.47ms Middle Channel Time 2.88*(1600/6)/79*31.6=307.20ms High Channel Time 2.893*(1600/6)/79*31.6=308.59ms

Page 39 of 60

TEST PLOT OF LOW CHANNEL




TEST PLOT OF MIDDLE CHANNEL



Page 40 of 60

TEST PLOT OF HIGH CHANNEL




Bluetooth 3Mbps Test Result

Channel	Time of Pulse for DH5 (ms)	Period Time (s)	Sweep Time (ms)	Limit (ms)
Low	2.905	31.6	309.87	400
Middle	2.905	31.6	309.87	400
High	2.917	31.6	311.15	400


Low Channel Time 2.905*(1600/6)/79*31.6=309.87ms Middle Channel Time 2.905*(1600/6)/79*31.6=309.87ms High Channel Time 2.917*(1600/6)/79*31.6=311.15ms

Page 41 of 60

TEST PLOT OF LOW CHANNEL




TEST PLOT OF MIDDLE CHANNEL



Page 42 of 60





Page 43 of 60

12. FREQUENCY SEPARATION 12.1 MEASUREMENT PROCEDURE

- 1. Place the EUT on the table and set it in transmitting mode
- 2. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer
- 3. Set center frequency of spectrum analyzer = Middele of Operating frequency
- 4. Set the spectrum analyzer as RBW, VBW=100KHz, Span = 5 MHz,

12.2 TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 5.2

12.3 MEASUREMENT EQUIPMENT USED


The same as described in section 5.3

12.4 LIMITS AND MEASUREMENT RESULT

BLUETOOTH 1MBPS TEST RESULT

BEGET GOTTI TIMBI G TEGT REGGET								
CHANNEL	CHANNEL SEPARATION	LIMIT	RESULT					
OHAMMEL	KHz	KHz						
CH00-CH01	1000	>=25 KHz or 2/3 20 dB BW	Pass					

TEST PLOT FOR FREQUENCY SEPARATION




Page 44 of 60

BLUETOOTH 2MBPS TEST RESULT

CHANNEL	CHANNEL SEPARATION	LIMIT	RESULT
OHANNEL	KHz	KHz	
CH00-CH01	1155	>=25 KHz or 2/3 20 dB BW	Pass

TEST PLOT FOR FREQUENCY SEPARATION




Page 45 of 60

TEST PLOT FOR FREQUENCY SEPARATION

CHANNEL	CHANNEL SEPARATION	LIMIT	RESULT
OHAMMEL	KHz KHz		
CH00-CH01	995	>=25 KHz or 2/3 20 dB BW	Pass

TEST PLOT FOR FREQUENCY SEPARATION




Page 46 of 60

13 FCC LINE CONDUCTED EMISSION TEST

13.1 LIMITS OF LINE CONDUCTED EMISSION TEST

Fraguency	Maximum RF Line Voltage						
Frequency	Q.P.(dBuV)	Average(dBuV)					
150kHz~500kHz	66-56	56-46					
500kHz~5MHz	56	46					
5MHz~30MHz	60	50					

13.2 BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



A: Powered through filter

^{**}Note: 1. The lower limit shall apply at the transition frequency.

2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz

Page 47 of 60

13.3 PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1) The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2) Support equipment, if needed, was placed as per ANSI C63.4.
- 3) All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4) All support equipments received AC120V power from a LISN, if any.
- 5) The EUT received DC4.5V by adapter and adapter received AC120V from LISN.
- 6) The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7) Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8) During the above scans, the emissions were maximized by cable manipulation.
- 9) The following test mode(s) were scanned during the preliminary test:

Preliminary Line Conducted Emission Test										
Frequency Range Investigated 150 KHz TO 30 MHz										
Mode of operation	Date	Report No.	Data#	Worst Mode						
Charging	03/21/2011	AGC00B110104F2	TSN51B-1(L,N)	\boxtimes						

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

13.4 FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST


- 1) EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2) A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3) The test data of the worst case condition(s) was reported on following Data page.

Page 48 of 60

13.5 TEST RESULT OF LINE CONDUCTED EMISSION TEST

Line Conducted Emission Test Line 1-L

Conducted Emission Measurement



Limit: FCC Class B Conduction(QP)

EUT: Portable scanner

M/N: TSN51B Mode: Charging


Note:

No.	Freq.		ading_L (dBuV)		Correct Factor		asuren (dBuV)			nit uV)		rgin dB)	P/F	Comment
	(MHz)	Peak	QP	AVG	dB	Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1980	43.50	42.01	32.04	10.21	53.71	52.22	42.25	63.69	53.69	-11.47	-11.44	Р	
2	0.2620	36.04	34.58	26.36	10.27	46.31	44.85	36.63	61.36	51.36	-16.51	-14.73	Р	
3	0.6540	37.53		7.25	10.33	47.86		17.58	56.00	46.00	-8.14	-28.42	Р	
4	1.3020	17.18		10.17	10.38	27.56		20.55	56.00	46.00	-28.44	-25.45	Р	
5	2.9340	20.46		12.23	10.53	30.99		22.76	56.00	46.00	-25.01	-23.24	Р	
6	8.7420	16.63		5.93	10.28	26.91		16.21	60.00	50.00	-33.09	-33.79	Р	

Page 49 of 60

Line Conducted Emission Test Line 2-N

Conducted Emission Measurement



Limit: FCC Class B Conduction(QP)

EUT: Portale scanner M/N: TSN51B Mode: Charging Note:

No.	Freq.		ading_L (dBuV)		Correct Factor		asurer (dBuV)			mit luV)		rgin dB)	P/F	Comment
	(MHz)	Peak	QP	AVG	dB	Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1980	42.19		31.66	10.21	52.40		41.87	63.69	53.69	-11.29	-11.82	Р	
2	0.2620	34.33		24.03	10.27	44.60		34.30	61.36	51.36	-16.76	-17.06	Р	
3	0.3300	26.97		16.92	10.30	37.27		27.22	59.45	49.45	-22.18	-22.23	Р	
4	0.6540	23.85		21.00	10.33	34.18		31.33	56.00	46.00	-21.82	-14.67	Р	
5	1.9020	21.30		9.04	10.25	31.55		19.29	56.00	46.00	-24.45	-26.71	Р	
6	3.3500	22.26		11.68	10.52	32.78		22.20	56.00	46.00	-23.22	-23.80	Р	

Power:

Humidity: 60 %

Page 50 of 60


14 FCC RADIATED EMISSION TEST

14.1 LIMITS OF RADIATED EMISSION TEST

Frequency (MHz)	Distance (m)	Maximum Field Strength Limit (dBuV/m/ Q.P.)
30~88	3	40.0
88~216	3	43.5
216~960	3	46.0
Above 960	3	54.0

^{**}Note: The lower limit shall apply at the transition frequency.

14.2 BLOCK DIAGRAM OF RADIATED EMISSION TEST



Page 51 of 60

14.3 PRELIMINARY PROCEDURE OF RADIATED EMISSION TEST

1) The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden turntable with a height of 0.8 meters is used which is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used).

- 2) All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 3) The EUT received DC4.2V by battery.
- 4) The antenna was placed at 3 meter away from the EUT as stated in FCC Part 15. The antenna connected to the Analyzer via a cable and at times a pre-amplifier would be used.
- 5) The Analyzer / Receiver quickly scanned from 30MHz to 1000MHz. The EUT test program was started. Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- 6) The test mode was scanned during the preliminary test. Then, the EUT and cable(s) configuration, antenna position, polarization and turntable position of the above highest emission level were recorded for final testing.

Preliminary Radiated Emission Test										
Frequency Range Investigated 30MHz TO 1GHZ										
Mode of operation	Date	Report No.	Data#	Worst Mode						
Bluetooth	03/21/2011	AGC00B110104F2	TSN51B-0(H,V)							

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

14.4 FINAL PROCEDURE OF RADIATED EMISSION TEST

EUT and support equipment were set up on the turntable as per step 6 of the preliminary test.

The Analyzer / Receiver scanned from 30MHz to 1000MHz. Emissions were scanned and measured rotating the EUT to 360 degrees, varying cable placement and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.


Recorded at least the six highest emissions. Emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit and Q.P/Peak. reading is presented.

The test data of the worst case condition(s) was reported on the Summary Data page.

Page 52 of 60

14.5 TEST RESULT OF RADIATED EMISSION TEST

Test Result of Radiated Emission Test-Horizontal-3m



Site: site #1

Limit: FCC Class B 3M Radiation

EUT: Portable scanner

M/N: TSN51B Mode:Bluetooth

Note:

ent	Limit	Over	Detector	Antenna Height	Table Degree	Commont

Temperature: 26

Humidity: 60 %

N	0.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		•	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
Ţ	1		59.1000	6.84	18.84	25.68	40.00	-14.32	peak			
2	2	×	185.2000	16.43	15.96	32.39	43.50	-11.11	peak			
3	3		479.4333	11.39	21.67	33.06	46.00	-12.94	peak			
	1		603.9167	4.44	24.95	29.39	46.00	-16.61	peak			


Polarization: Horizontal

Power: DC4.5V

Distance: 3m

Page 53 of 60

Test Result of Radiated Emission Test-Vertical-3m



Site: site #1 Limit: FCC Class B 3M Radiation

EUT: Portable scanner

Freq.

MHz

59.1000

156.1000

479.4333

720.3167

M/N: TSN51B Mode: Bluetooth Note:

No.

1

2

3

Polarization: Vertical Temperature: 26 Humidity: 60 % Power: DC4.5V

Distance: 3m

Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
7.06	19.08	26.14	40.00	-13.86	peak			
17.63	13.49	31.12	43.50	-12.38	peak			
10.28	21.67	31.95	46.00	-14.05	peak			
5.20	26.15	31.35	46.00	-14.65	peak			

Page 54 of 60

APPENDIX I PHOTOGRAPHS OF THE EUT

WHOLE VIEW OF SAMPLE



TOP VIEW OF SAMPLE



Page 55 of 60






LEFT VIEW OF SAMPLE



Page 56 of 60






FRONT VIEW OF SAMPLE




Page 57 of 60





Page 58 of 60






INTERNAL VIEW OF SAMPLE-3



Report No.: AGC00B110104F2 Page 59 of 60




Page 60 of 60

APPENDIX II PHOTOGRAPHS OF THE TEST SETUP

LINE COMDUCTED EMISSION TEST SETUP



RADIATED EMISSION TEST SETUP



----END OF REPORT----