



## SAR EVALUATION REPORT

For

### WITTS COMMUNICATION TECHNOLOGY LIMITED

FLAT A-B, 11/F, WAH LIK IND CTR, 459-469 CASTLE PEAK RD.,

TSUEN WAN, N.T., HONG KONG

**FCC ID: ZEW851**

<b>Report Type:</b> Original Report	<b>Product Type:</b> GSM Mobile Phone
<b>Test Engineer:</b> <u>Cabin Hu</u>	<i>Cabin . Hu</i>
<b>Report Number:</b> <u>RSZ110519010-20</u>	
<b>Report Date:</b> <u>2011-06-14</u>	
<b>Reviewed By:</b> William Chen EMC Engineer	<i>William . Chan .</i>
<b>Prepared By:</b> Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008	

**Note:** This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Shenzhen). This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP\*, NIST, or any agency of the Federal Government.

\* This report contain data that are not covered by the NVLAP accreditation and are marked with an asterisk “★”

Summary of Test Results	
<b>Rule Part(s):</b>	CFR 47 §2.1093
<b>Test Procedure(s):</b>	FCC OET Bulletin 65C IEEE 1528-2003
<b>Device Type:</b>	Portable device
<b>Exposure Category</b>	Population/Uncontrolled
<b>Modulation:</b>	GMSK
<b>TX Frequency Range:</b>	824-849 MHz (Cellular Band) 1850-1910 MHz (PCS Band)
<b>Maximum Conducted Power Tested:</b>	GSM850: 31.8 dBm PCS19900: 28.9 dBm
<b>Antenna Type(s):</b>	Internal Antenna
<b>Body-Worn Accessories:</b>	Headset
<b>Face-Head Accessories:</b>	None
<b>Battery Type(s) Tested:</b>	3.7VDC/1100mAh Rechargeable Battery
<b>Max. SAR Level(s) Measured:</b>	0.346 W/Kg, 1g Head Tissue (Cellular Band) 0.345 W/Kg, 1g Body Tissue (Cellular Band) 0.492 W/Kg, 1g Head Tissue (PCS Band) 0.232 W/Kg, 1g Body Tissue (PCS Band)

This wireless device has been shown to be capable of compliance for localized specific absorption rate (SAR) for General Population/Uncontrolled Exposure limits specified in ANSI/IEEE Standards and has been tested in accordance with the measurement procedures specified in FCC OET 65 Supplement C and IEEE 1528-2003.

**The results and statements contained in this report pertain only to the device(s) evaluated.**



**EUT Photo**

## DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	RSZ110519010-20	Original Report	2011-06-14

## TABLE OF CONTENTS

<b>REFERENCE, STANDARDS AND GUILDELINE</b>	5
SAR LIMITS .....	6
<b>EUT DESCRIPTION</b>	7
TECHNICAL SPECIFICATION .....	7
<b>FACILITIES AND ACCREDITATION</b>	8
<b>DESCRIPTION OF TEST SYSTEM</b>	9
<b>EQUIPMENT LIST AND CALIBRATION</b>	16
EQUIPMENTS LIST & CALIBRATION INFO.....	16
<b>SAR MEASUREMENT SYSTEM VERIFICATION</b>	17
LIQUID VERIFICATION.....	17
SYSTEM ACCURACY VERIFICATION .....	20
<b>EUT TEST STRATEGY AND METHODOLOGY</b>	21
TEST POSITIONS FOR DEVICE OPERATING NEXT TO A PERSON'S EAR.....	21
CHEEK/TOUCH POSITION .....	22
EAR/TILT POSITION.....	22
TEST POSITIONS FOR BODY-WORN AND OTHER CONFIGURATIONS .....	23
SAR EVALUATION PROCEDURE.....	24
<b>SAR MEASUREMENT RESULTS</b>	25
SAR TEST DATA.....	25
<b>APPENDIX A – MEASUREMENT UNCERTAINTY</b>	27
<b>APPENDIX B – PROBE CALIBRATION CERTIFICATES</b>	28
<b>APPENDIX C – DIPOLE CALIBRATION CERTIFICATES</b>	68
<b>APPENDIX D – SAR SYSTEM VALIDATION DATA</b>	78
<b>APPENDIX E – EUT SCAN RESULTS</b> .....	86
<b>APPENDIX F – CONDUCTED OUTPUT POWER MEASUREMENT</b>	106
TEST BLOCK DIAGRAM AND PROCEDURE .....	106
TEST EQUIPMENT LIST AND DETAILS.....	106
TEST RESULTS .....	106
<b>APPENDIX G – EUT TEST POSITION PHOTOS</b> .....	108
LIQUID DEPTH $\geq 15$ CM.....	108
BODY-WORN BACK SETUP PHOTO .....	108
LEFT HEAD TOUCH SETUP PHOTO .....	109
LEFT HEAD TILT SETUP PHOTO .....	109
RIGHT HEAD TOUCH SETUP PHOTO .....	110
RIGHT HEAD TILT SETUP PHOTO .....	110
<b>APPENDIX H – EUT PHOTOS</b> .....	111
EUT – FRONT SIDE VIEW.....	111
EUT – BACK SIDE VIEW .....	111
EUT- BATTERY UNCOVER VIEW .....	112
EUT – RIGHT SIDE VIEW .....	112
EUT – LEFT SIDE VIEW .....	113
EUT- HEADSET VIEW .....	113
<b>APPENDIX I - INFORMATIVE REFERENCES</b> .....	114

## REFERENCE, STANDARDS AND GUILDELINE

### FCC:

The Report and Order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 mW/g as recommended by the ANSI/IEEE standard C95.1-1992 [6] for an uncontrolled environment (Paragraph 65). According to the Supplement C of OET Bulletin 65 "Evaluating Compliance with FCC Guide-lines for Human Exposure to Radio frequency Electromagnetic Fields", released on Jun 29, 2001 by the FCC, the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.

This report describes the methodology and results of experiments performed on wireless data terminal. The objective was to determine if there is RF radiation and if radiation is found, what is the extent of radiation with respect to safety limits. SAR (Specific Absorption Rate) is the measure of RF exposure determined by the amount of RF energy absorbed by human body (or its parts) – to determine how the RF energy couples to the body or head which is a primary health concern for body worn devices. The limit below which the exposure to RF is considered safe by regulatory bodies in North America is 1.6 mW/g average over 1 gram of tissue mass.

### CE:

The order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 2 mW/g as recommended by the EN50360 for an uncontrolled environment. According to the Standard, the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.

This report describes the methodology and results of experiments performed on wireless data terminal. The objective was to determine if there is RF radiation and if radiation is found, what is the extent of radiation with respect to safety limits. SAR (Specific Absorption Rate) is the measure of RF exposure determined by the amount of RF energy absorbed by human body (or its parts) – to determine how the RF energy couples to the body or head which is a primary health concern for body worn devices. The limit below which the exposure to RF is considered safe by regulatory bodies in Europe is 2 mW/g average over 10 gram of tissue mass.

The test configurations were laid out on a specially designed test fixture to ensure the reproducibility of measurements. Each configuration was scanned for SAR. Analysis of each scan was carried out to characterize the above effects in the device.

## SAR Limits

FCC Limit (1g Tissue)

EXPOSURE LIMITS	SAR (W/kg)	
	(General Population / Uncontrolled Exposure Environment)	(Occupational / Controlled Exposure Environment)
Spatial Average (averaged over the whole body)	0.08	0.4
Spatial Peak (averaged over any 1 g of tissue)	1.60	8.0
Spatial Peak (hands/wrists/feet/ankles averaged over 10 g)	4.0	20.0

CE Limit (10g Tissue)

EXPOSURE LIMITS	SAR (W/kg)	
	(General Population / Uncontrolled Exposure Environment)	(Occupational / Controlled Exposure Environment)
Spatial Average (averaged over the whole body)	0.08	0.4
Spatial Peak (averaged over any 10 g of tissue)	2.0	10
Spatial Peak (hands/wrists/feet/ankles averaged over 10 g)	4.0	20.0

Population/Uncontrolled Environments are defined as locations where there is the exposure of individual who have no knowledge or control of their exposure.

Occupational/Controlled Environments are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure (i.e. as a result of employment or occupation).

General Population/Uncontrolled environments Spatial Peak limit 1.6W/kg (FCC) & 2 W/kg (CE) applied to the EUT.

## EUT DESCRIPTION

This Bay Area Compliance Laboratories Corp. test report has been prepared on behalf of WITTIS COMMUNICATION TECHNOLOGY LIMITED, and their product, Model: 851, FCC ID: ZEW851 or the EUT (Equipment Under Test) as referred to in the rest of this report.

### Technical Specification

Item	Contents
Modulation	GMSK
Frequency Band	Cellular Band: 824-849 MHz (TX) 869-894 MHz (RX) PCS Band: 1850-1910 MHz (TX) 1930-1990 MHz (RX)
Dimensions (L*W*H)	111 mm (L)× 61 mm (W)×13 mm (H)
Weight	100 g
Power Source	3.7 VDC/1100 mAh Rechargeable Battery
Operation Mode	Head and Body-worn

## FACILITIES AND ACCREDITATION

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect data is located at 6/F, the 3rd Phase of WanLi Industrial Building, Shi Hua Road, Fu Tian Free Trade Zone, Shenzhen, Guangdong, P.R. of China

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at <http://ts.nist.gov/Standards/scopes/2007070.htm>

## DESCRIPTION OF TEST SYSTEM

These measurements were performed with ALSAS 10 Universal Integrated SAR Measurement system from APREL Laboratories.



### ALSAS-10U System Description

ALSAS-10-U is fully compliant with the technical and scientific requirements of IEEE 1528, IEC 62209, CENELEC, ARIB, ACA, and the Federal Communications Commission. The system comprises of a six axes articulated robot which utilizes a dedicated controller. ALSAS-10U uses the latest methodologies. And FDTD modeling to provide a platform which is repeatable with minimum uncertainty.

### Applications

Predefined measurement procedures compliant with the guidelines of CENELEC, IEEE, IEC, FCC, etc are utilized during the assessment for the device. Automatic detection for all SAR maxima are embedded within the core architecture for the system, ensuring that peak locations used for centering the zoom scan are within a 1mm resolution and a 0.05mm repeatable position. System operation range currently available up-to 6 GHz in simulated tissue.

### Area Scans

Area scans are defined prior to the measurement process being executed with a user defined variable spacing between each measurement point (integral) allowing low uncertainty measurements to be conducted. Scans defined for FCC applications utilize a 10mm<sup>2</sup> step integral, with 1mm interpolation used to locate the peak SAR area used for zoom scan assessments.

Where the system identifies multiple SAR peaks (which are within 25% of peak value) the system will provide the user with the option of assessing each peak location individually for zoom scan averaging.

### Zoom Scan (Cube Scan Averaging)

The averaging zoom scan volume utilized in the ALSAS-10U software is in the shape of a cube and the side dimension of a 1 g or 10 g mass is dependent on the density of the liquid representing the simulated tissue. A density of 1000 kg/m<sup>3</sup> is used to represent the head and body tissue density and not the phantom liquid density, in order to be consistent with the definition of the liquid dielectric properties, i.e. the side length of the 1 g cube is 10mm, with the side length of the 10 g cube 21.5mm.

When the cube intersects with the surface of the phantom, it is oriented so that 3 vertices touch the surface of the shell or the center of a face is tangent to the surface. The face of the cube closest to the surface is modified in order to conform to the tangent surface.

The zoom scan integer steps can be user defined so as to reduce uncertainty, but normal practice for typical test applications (including FCC) utilize a physical step of 5x5x8 (8mmx8mmx5mm) providing a volume of 32mm in the X & Y axis, and 35mm in the Z axis.

### ALSAS-10U Interpolation and Extrapolation Uncertainty


The overall uncertainty for the methodology and algorithms used during the SAR calculation was evaluated using the data from IEEE 1528 based on the example f3 algorithm:

$$f_3(x, y, z) = A \frac{a^2}{\frac{a^2}{4} + x'^2 + y'^2} \cdot \left( e^{-\frac{2z}{a}} + \frac{a^2}{2(a + 2z)^2} \right)$$

### Isotropic E-Field Probe

The isotropic E-Field probe has been fully calibrated and assessed for isotropicity, and boundary effect within a controlled environment. Depending on the frequency for which the probe is calibrated the method utilized for calibration will change.

The E-Field probe utilizes a triangular sensor arrangement as detailed in the diagram below:



SAR is assessed with a calibrated probe which moves at a default height of 5mm from the center of the diode, which is mounted to the sensor, to the phantom surface (in the Z Axis). The 5mm offset height has been selected so as to minimize any resultant boundary effect due to the probe being in close proximity to the phantom surface.

The following algorithm is an example of the function used by the system for linearization of the output from the probe when measuring complex modulation schemes.

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

## Isotropic E-Field Probe Specification

<b>Calibration in Air</b>	Frequency Dependent Below 2 GHz Calibration in air performed in a TEM Cell Above 2 GHz Calibration in air performed in waveguide
<b>Sensitivity</b>	0.70 $\mu\text{V}/(\text{V}/\text{m})^2$ to 0.85 $\mu\text{V}/(\text{V}/\text{m})^2$
<b>Dynamic Range</b>	0.0005 W/kg to 100 W/kg
<b>Isotropic Response</b>	Better than 0.2 dB
<b>Diode Compression Point (DCP)</b>	Calibration for Specific Frequency
<b>Probe Tip Radius</b>	< 5 mm
<b>Sensor Offset</b>	1.56 (+/- 0.02 mm)
<b>Probe Length</b>	290 mm
<b>Video Bandwidth</b>	@ 500 Hz: 1 dB @ 1.02 kHz: 3 dB
<b>Boundary Effect</b>	Less than 2% for distance greater than 2.4 mm
<b>Spatial Resolution</b>	Diameter less than 5 mm Compliant with Standards

## Boundary Detection Unit and Probe Mounting Device

ALSAS-10U incorporates a boundary detection unit with a sensitivity of 0.05mm for detecting all types of surfaces. The robust design allows for detection during probe tilt (probe normalize) exercises, and utilizes a second stage emergency stop. The signal electronics are fed directly into the robot controller for high accuracy surface detection in lateral and axial detection modes (X, Y, & Z).

The probe is mounted directly onto the Boundary Detection unit for accurate tooling and displacement calculations controlled by the robot kinematics. The probe is connect to an isolated probe interconnect where the output stage of the probe is fed directly into the amplifier stage of the Daq-Paq.

## Daq-Paq (Analog to Digital Electronics)

ALSAS-10U incorporates a fully calibrated Daq-Paq (analog to digital conversion system) which has a 4 channel input stage, sent via a 2 stage auto-set amplifier module. The input signal is amplified accordingly so as to offer a dynamic range from 5 $\mu\text{V}$  to 800mV. Integration of the fields measured is carried out at board level utilizing a Co-Processor which then sends the measured fields down into the main computational module in digitized form via an RS232 communications port. Probe linearity and duty cycle compensation is carried out within the main Daq-Paq module.

<b>ADC</b>	12 Bit
<b>Amplifier Range</b>	20 mV to 200 mV and 150 mV to 800 mV
<b>Field Integration</b>	Local Co-Processor utilizing proprietary integration algorithms
<b>Number of Input Channels</b>	4 in total 3 dedicated and 1 spare
<b>Communication</b>	Packet data via RS232

## Axis Articulated Robot

ALSAS-10U utilizes a six axis articulated robot, which is controlled using a Pentium based real-time movement controller. The movement kinematics engine utilizes proprietary (Thermo CRS) interpolation and extrapolation algorithms, which allow full freedom of movement for each of the six joints within the working envelope. Utilization of joint 6 allows for full probe rotation with a tolerance better than 0.05mm around the central axis.



<b>Robot/Controller Manufacturer</b>	Thermo CRS
<b>Number of Axis</b>	Six independently controlled axis
<b>Positioning Repeatability</b>	0.05 mm
<b>Controller Type</b>	Single phase Pentium based C500C
<b>Robot Reach</b>	710 mm
<b>Communication</b>	RS232 and LAN compatible

## ALSAS Universal Workstation

ALSAS Universal workstation allows for repeatability and fast adaptability. It allows users to do calibration, testing and measurements using different types of phantoms with one set up, which significantly speeds up the measurement process.

## Universal Device Positioner

The universal device positioner allows complete freedom of movement of the EUT. Developed to hold a EUT in a free-space scenario any additional loading attributable to the material used in the construction of the positioner has been eliminated. Repeatability has been enhanced through the linear scales which form the design used to indicate positioning for any given test scenario in all major axes. A 15° tilt indicator is included for the aid of cheek to tilt movements for head SAR analysis. Overall uncertainty for measurements have been reduced due to the design of the Universal device positioner, which allows positioning of a device in as near to a free-space scenario as possible, and by providing the means for complete repeatability.




### Phantom Types

The ALSAS-10U allows the integration of multiple phantom types. SAM Phantoms fully compliant with IEEE 1528, Universal Phantom, and Universal Flat.

### APREL SAM Phantoms

The SAM phantoms developed using the IEEE SAM CAD file. They are fully compliant with the requirements for both IEEE 1528 and FCC Supplement C. Both the left and right SAM phantoms are interchangeable, transparent and include the IEEE 1528 grid with visible NF and MB lines.



**APREL Laboratories Universal Phantom**

The Universal Phantom is used on the ALSAS-10U as a system validation phantom. The Universal Phantom has been fully validated both experimentally from 800MHz to 6GHz and numerically using XFDTD numerical software.

The shell thickness is 2mm overall, with a 4mm spacer located at the NF/MB intersection providing an overall thickness of 6mm in line with the requirements of IEEE-1528.

The design allows for fast and accurate measurements, of handsets, by allowing the conservative SAR to be evaluated at on frequency for both left and right head experiments in one measurement.



## Tissue Dielectric Parameters for Head and Body Phantoms

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in P1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations described in Reference [12] and extrapolated according to the head parameters specified in P1528.

Ingredients (% by weight)	Frequency (MHz)									
	450		835		915		1900		2450	
Tissue Type	Head	Body	Head	Body	Head	Body	Head	Body	Head	Body
Water	38.56	51.16	41.45	52.4	41.05	56.0	54.9	40.4	62.7	73.2
Salt (NaCl)	3.95	1.49	1.45	1.4	1.35	0.76	0.18	0.5	0.5	0.04
Sugar	56.32	46.78	56.0	45.0	56.5	41.76	0.0	58.0	0.0	0.0
HEC	0.98	0.52	1.0	1.0	1.0	1.21	0.0	1.0	0.0	0.0
Bactericide	0.19	0.05	0.1	0.1	0.1	0.27	0.0	0.1	0.0	0.0
Triton x-100	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	36.8	0.0
DGBE	0.0	0.0	0.0	0.0	0.0	0.0	44.92	0.0	0.0	26.7
Dielectric Constant	43.42	58.0	42.54	56.1	42.0	56.8	39.9	54.0	39.8	52.5
Conductivity (s/m)	0.85	0.83	0.91	0.95	1.0	1.07	1.42	1.45	1.88	1.78

## Recommended Tissue Dielectric Parameters for Head and Body

Frequency (MHz)	Head Tissue		Body Tissue	
	$\epsilon_r$	$\sigma$ (S/m)	$\epsilon_r$	$\sigma$ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800-2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5800	35.3	5.27	48.2	6.00


## EQUIPMENT LIST AND CALIBRATION

### Equipments List & Calibration Info

Equipment	Model	Calibration Date	S/N
CRS F3 robot	ALS-F3	N/A	RAF0805352
CRS F3 Software	ALS-F3-SW	N/A	N/A
CRS C500C controller	ALS-C500	N/A	RCF0805379
Probe mounting device & Boundary Detection Sensor System	ALS-PMDPS-3	N/A	120-00270
Universal Work Station	ALS-UWS	N/A	100-00157
Data Acquisition Package	ALS-DAQ-PAQ-3	N/A	110-00212
Miniature E-Field Probe	ALS-E-020	2010-08-20	273
Dipole, 835 MHz	ALS-D-835-S-2	2010-09-20	180-00558
Dipole, 1900 MHz	ALS-D-1900-S-2	2010-09-20	210-00710
Dipole Spacer	ALS-DS-U	N/A	250-00907
R&S, universal Communication Tester	CMU200	2010-06-28	1100.0008.02
Device holder/Positioner	ALS-H-E-SET-2	N/A	170-00510
Left ear SAM phantom	ALS-P-SAM-L	N/A	130-00311
Right ear SAM phantom	ALS-P-SAM-R	N/A	140-00359
UniPhantom	ALS-P-UP-1	N/A	150-00413
Simulated Tissue 835 MHz Head	ALS-T-835-1-H	Each Time	270-01002
Simulated Tissue 835 MHz Body	ALS-T-835-1-B	Each Time	270-02101
Simulated Tissue 1900 MHz Head	ALS-T-1900-1-H	Each Time	295-01103
Simulated Tissue 1900 MHz Body	ALS-T-1900-1-B	Each Time	295-02102
Signal Generator	HP8648C	2010-09-18	3426A01345
Power Amplifier	5S1G4	N/A	71377
Spectrum Analyzer	FSEM30	2010-07-05	849720/019

## SAR MEASUREMENT SYSTEM VERIFICATION

### Liquid Verification



Liquid Verification Setup Block Diagram

### Liquid Verification Results

Frequency (MHz)	Liquid Type	Liquid Parameter		Result
		$\epsilon_r$	$\sigma$ (S/m)	
835	Head	41.13	0.90	In Tolerance
835	Body	55.57	1.00	In Tolerance
1900	Head	39.54	1.45	In Tolerance
1900	Body	53.58	1.54	In Tolerance

\*The liquid verification date is 2011-06-13.

Please refer to the following tables


850 MHz Head			850 MHz Body		
Frequency	e'	e''	Frequency	e'	e''
824000000	41.239070	19.482276	824000000	55.668542	21.530923
824500000	41.140096	19.438513	824500000	55.570684	21.543467
825000000	41.149027	19.439575	825000000	55.605128	21.534734
825500000	41.093419	19.437139	825500000	55.615639	21.506951
826000000	41.079131	19.449876	826000000	55.551883	21.534899
826500000	41.115811	19.416892	826500000	55.561189	21.518760
827000000	41.106112	19.465370	827000000	55.607230	21.511223
827500000	41.159633	19.417159	827500000	55.603061	21.488985
828000000	41.130211	19.412942	828000000	55.565919	21.467992
828500000	41.151852	19.478996	828500000	55.564279	21.511702
829000000	41.169770	19.493285	829000000	55.616283	21.490643
829500000	41.187689	19.507523	829500000	55.592683	21.475779
830000000	41.180639	19.507586	830000000	55.601988	21.459639
830500000	41.176895	19.443662	830500000	55.588179	21.441135
831000000	41.139007	19.483833	831000000	55.561235	21.505312
831500000	41.119598	19.476861	831500000	55.576610	21.475777
832000000	41.106195	19.415846	832000000	55.563949	21.401485
832500000	41.143589	19.424587	832500000	55.556597	21.458148
833000000	41.110251	19.442519	833000000	55.513916	21.450688
833500000	41.114200	19.481412	833500000	55.589985	21.464520
834000000	41.142296	19.419475	834000000	55.591319	21.412762
834500000	41.133890	19.451310	834500000	55.577944	21.438400
835000000	41.131179	19.480386	835000000	55.572569	21.435096
835500000	41.142485	19.419139	835500000	55.602858	21.436792
836000000	41.156945	19.439272	836000000	55.533659	21.373552
836500000	41.100397	19.484485	836500000	55.541507	21.396532
837000000	41.151657	19.431812	837000000	55.490113	21.365190
837500000	41.098311	19.413797	837500000	55.551842	21.356530
838000000	41.157568	19.390089	838000000	55.537646	21.393412
838500000	41.103906	19.481145	838500000	55.501076	21.400406
839000000	41.133552	19.481247	839000000	55.552419	21.379132
839500000	41.129112	19.434003	839500000	55.504966	21.357499
840000000	41.110203	19.427124	840000000	55.467860	21.348343
840500000	41.122111	19.401220	840500000	55.492727	21.315382
841000000	41.144114	19.429276	841000000	55.512465	21.311738
841500000	41.130107	19.384938	841500000	55.489085	21.352011
842000000	41.111298	19.378114	842000000	55.497484	21.347217
842500000	41.107465	19.387657	842500000	55.478524	21.342098
843000000	41.106362	19.406702	843000000	55.459608	21.336973
843500000	41.088303	19.420256	843500000	55.456775	21.331085
844000000	41.081846	19.420219	844000000	55.486778	21.339667
844500000	41.061892	19.372708	844500000	55.425933	21.394351
845000000	41.054123	19.403856	845000000	55.467502	21.376602
845500000	41.034228	19.356449	845500000	55.385403	21.320091
846000000	40.976493	19.391583	846000000	55.355785	21.286687
846500000	41.032361	19.394267	846500000	55.419313	21.325480
847000000	41.021999	19.344299	847000000	55.412183	21.294243
847500000	40.998214	19.390150	847500000	55.406230	21.349145
848000000	40.987891	19.340260	848000000	55.389749	21.321557
848500000	40.985761	19.390053	848500000	55.370856	21.370616
849000000	40.963361	19.333536	849000000	55.367495	21.348738

1900 MHz Head				1900 MHz Body		
Frequency	e'	e''		Frequency	e'	e''
1850000000	39.478610	13.366870		1850000000	53.645454	14.480796
1851200000	39.418751	13.361087		1851200000	53.622284	14.466712
1852400000	39.456570	13.396661		1852400000	53.686385	14.479179
1853600000	39.443260	13.374058		1853600000	53.669560	14.422185
1854800000	39.413738	13.373502		1854800000	53.754054	14.494712
1856000000	39.430893	13.370912		1856000000	53.719638	14.505759
1857200000	39.414608	13.377163		1857200000	53.694041	14.463921
1858400000	39.388352	13.386597		1858400000	53.613155	14.464384
1859600000	39.396932	13.365389		1859600000	53.642919	14.455040
1860800000	39.409803	13.365474		1860800000	53.556430	14.416007
1862000000	39.375788	13.400745		1862000000	53.570107	14.450965
1863200000	39.360663	13.394299		1863200000	53.593462	14.488532
1864400000	39.358201	13.412881		1864400000	53.604894	14.454745
1865600000	39.345819	13.410752		1865600000	53.595596	14.443386
1866800000	39.364041	13.491163		1866800000	53.553135	14.428334
1868000000	39.392506	13.559249		1868000000	53.564825	14.427820
1869200000	39.493048	13.723217		1869200000	53.529032	14.436675
1870400000	39.554675	13.824789		1870400000	53.495102	14.447518
1871600000	39.559667	13.883734		1871600000	53.611296	14.471867
1872800000	39.543492	13.865688		1872800000	53.627067	14.508877
1874000000	39.524983	13.858146		1874000000	53.659030	14.534766
1875200000	39.551338	13.993799		1875200000	53.641599	14.489694
1876400000	39.574590	13.981024		1876400000	53.691150	14.559330
1877600000	39.546801	13.925198		1877600000	53.693190	14.556309
1878800000	39.560899	13.969257		1878800000	53.721560	14.577895
1880000000	39.495501	13.868142		1880000000	53.780839	14.608722
1881200000	39.535303	13.871902		1881200000	53.731026	14.585635
1882400000	39.504845	13.812059		1882400000	53.732655	14.594078
1883600000	39.507685	13.800156		1883600000	53.686126	14.586724
1884800000	39.473094	13.767013		1884800000	53.698143	14.581953
1886000000	39.480759	13.758075		1886000000	53.686913	14.617227
1887200000	39.504933	13.732735		1887200000	53.635219	14.595973
1888400000	39.492803	13.730387		1888400000	53.633579	14.592512
1889600000	39.501626	13.699787		1889600000	53.686970	14.624701
1890800000	39.474963	13.721608		1890800000	53.736286	14.615732
1892000000	39.506741	13.727231		1892000000	53.722501	14.623523
1893200000	39.499494	13.694925		1893200000	53.678710	14.602670
1894400000	39.494753	13.708799		1894400000	53.595103	14.558673
1895600000	39.515118	13.724611		1895600000	53.618449	14.610688
1896800000	39.486809	13.729607		1896800000	53.576622	14.591972
1898000000	39.494827	13.735322		1898000000	53.580847	14.590659
1899200000	39.517498	13.707838		1899200000	53.609008	14.574837
1900400000	39.535207	13.719325		1900400000	53.586037	14.600908
1901600000	39.530520	13.733152		1901600000	53.570919	14.570423
1902800000	39.542786	13.736113		1902800000	53.575195	14.569059
1904000000	39.519174	13.720275		1904000000	53.580079	14.552262
1905200000	39.538399	13.724717		1905200000	53.606396	14.582854
1906400000	39.549488	13.716496		1906400000	53.680534	14.580350
1907600000	39.545513	13.694078		1907600000	53.601410	14.529376
1908800000	39.500272	13.686243		1908800000	53.587596	14.596964
1910000000	39.507106	13.722396		1910000000	53.496302	14.560935

## System Accuracy Verification

Prior to the assessment, the system validation kit was used to test whether the system was operating within its specifications of  $\pm 10\%$ . The validation results are tabulated below. And also the corresponding SAR plot is attached as well in the SAR plots files.

### System Verification Setup Block Diagram



### System Check Results

Frequency (MHz)	Liquid Type	1 g SAR (W/Kg)	Target Value (W/Kg)	Result
835	Head	9.721	9.5	In Tolerance
1900	Head	41.691	39.7	In Tolerance
835	Body	9.651	9.54	In Tolerance
1900	Body	40.688	39.7	In Tolerance


\* All SAR values are normalized to 1 Watt forward power.

## EUT TEST STRATEGY AND METHODOLOGY

### Test Positions for Device Operating Next to a Person's Ear

This category includes most wireless handsets with fixed, retractable or internal antennas located toward the top half of the device, with or without a foldout, sliding or similar keypad cover. The handset should have its earpiece located within the upper  $\frac{1}{4}$  of the device, either along the centerline or off-centered, as perceived by its users. This type of handset should be positioned in a normal operating position with the “test device reference point” located along the “vertical centerline” on the front of the device aligned to the “ear reference point”. The “test device reference point” should be located at the same level as the center of the earpiece region. The “vertical centerline” should bisect the front surface of the handset at its top and bottom edges. A “ear reference point” is located on the outer surface of the head phantom on each ear spacer. It is located 1.5 cm above the center of the ear canal entrance in the “phantom reference plane” defined by the three lines joining the center of each “ear reference point” (left and right) and the tip of the mouth.

A handset should be initially positioned with the earpiece region pressed against the ear spacer of a head phantom. For the SCC-34/SC-2 head phantom, the device should be positioned parallel to the “N-F” line defined along the base of the ear spacer that contains the “ear reference point”. For interim head phantoms, the device should be positioned parallel to the cheek for maximum RF energy coupling. The “test device reference point” is aligned to the “ear reference point” on the head phantom and the “vertical centerline” is aligned to the “phantom reference plane”. This is called the “initial ear position”. While maintaining these three alignments, the body of the handset is gradually adjusted to each of the following positions for evaluating SAR:



## Cheek/Touch Position


The device is brought toward the mouth of the head phantom by pivoting against the “ear reference point” or along the “N-F” line for the SCC-34/SC-2 head phantom.

This test position is established:

- When any point on the display, keypad or mouthpiece portions of the handset is in contact with the phantom.
- (or) When any portion of a foldout, sliding or similar keypad cover opened to its intended self-adjusting normal use position is in contact with the cheek or mouth of the phantom.

For existing head phantoms – when the handset loses contact with the phantom at the pivoting point, rotation should continue until the device touches the cheek of the phantom or breaks its last contact from the ear spacer.

### Cheek /Touch Position



## Ear/Tilt Position


With the handset aligned in the “Cheek/Touch Position”:

1) If the earpiece of the handset is not in full contact with the phantom’s ear spacer (in the “Cheek/Touch position”) and the peak SAR location for the “Cheek/Touch” position is located at the ear spacer region or corresponds to the earpiece region of the handset, the device should be returned to the “initial ear position” by rotating it away from the mouth until the earpiece is in full contact with the ear spacer.

2) (otherwise) The handset should be moved (translated) away from the cheek perpendicular to the line passes through both “ear reference points” (note: one of these ear reference points may not physically exist on a split head model) for approximate 2-3 cm. While it is in this position, the device handset is tilted away from the mouth with respect to the “test device reference point” until the inside angle between the vertical centerline on the front surface of the phone and the horizontal line passing through the ear reference point is by 15-80°. After the tilt, it is then moved (translated) back toward the head perpendicular to the line passes through both “ear reference points” until the device touches the phantom or the ear spacer. If the antenna touches the head first, the positioning process should be repeated with a tilt angle less than 15° so that the device and its antenna would touch the phantom simultaneously. This test position may require a device holder or positioner to achieve the translation and tilting with acceptable positioning repeatability.

If a device is also designed to transmit with its keypad cover closed for operating in the head position, such positions should also be considered in the SAR evaluation. The device should be tested on the left and right side of the head phantom in the "Cheek/Touch" and "Ear/Tilt" positions. When applicable, each configuration should be tested with the antenna in its fully extended and fully retracted positions. These test configurations should be tested at the high, middle and low frequency channels of each operating mode; for example, AMPS, CDMA, and TDMA. If the SAR measured at the middle channel for each test configuration (left, right, Cheek/Touch, Ear/Ear, extended and retracted) is at least 2.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s). If the transmission band of the test device is less than 10 MHz, testing at the high and low frequency channels is optional.

#### Ear /Tilt 15° Position



#### **Test positions for body-worn and other configurations**

Body-worn operating configurations should be tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in normal use configurations. Devices with a headset output should be tested with a headset connected to the device. When multiple accessories that do not contain metallic components are supplied with the device, the device may be tested with only the accessory that dictates the closest spacing to the body. When multiple accessories that contain metallic components are supplied with the device, the device must be tested with each accessory that contains a unique metallic component. If multiple accessories share an identical metallic component (e.g., the same metallic belt-clip used with different holsters with no other metallic components), only the accessory that dictates the closest spacing to the body must be tested.

Body-worn accessories may not always be supplied or available as options for some devices that are intended to be authorized for body-worn use. A separation distance of 1.5 cm between the back of the device and a flat phantom is recommended for testing body-worn SAR compliance under such circumstances. Other separation distances may be used, but they should not exceed 2.5 cm. In these cases, the device may use body-worn accessories that provide a separation distance greater than that tested for the device provided however that the accessory contains no metallic components.

## SAR Evaluation Procedure

The evaluation was performed with the following procedure:

Step 1: Measurement of the SAR value at a fixed location above the ear point or central position was used as a reference value for assessing the power drop. The SAR at this point is measured at the start of the test and then again at the end of the testing.

Step 2: The SAR distribution at the exposed side of the head was measured at a distance of 4 mm from the inner surface of the shell. The area covered the entire dimension of the head or EUT and the horizontal grid spacing was 15 mm x 15 mm. Based on these data, the area of the maximum absorption was determined by spline interpolation. The first Area Scan covers the entire dimension of the EUT to ensure that the hotspot was correctly identified.

Step 3: Around this point, a volume of 30 mm x 30 mm x 21 mm was assessed by measuring 5 x 5 x 7 points. On the basis of this data set, the spatial peak SAR value was evaluated under the following procedure:

- 1) The data at the surface were extrapolated, since the center of the dipoles is 1.2 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.3 mm. The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip.
- 2) The maximum interpolated value was searched with a straightforward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1 g or 10 g) were computed by the 3D-Spline interpolation algorithm. The 3D-Spline is composed of three one dimensional splines with the "Not a knot"-condition (in x, y and z-directions). The volume was integrated with the trapezoidal-algorithm. One thousand points (10 x 10 x 10) were interpolated to calculate the averages.

All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.

Step 4: Re-measurement of the SAR value at the same location as in Step 1. If the value changed by more than 5%, the evaluation was repeated.

## SAR MEASUREMENT RESULTS

This page summarizes the results of the performed dosimetric evaluation. The plots with the corresponding SAR distributions, which reveal information about the location of the maximum SAR with respect to the device, could be found in Appendix E.

### SAR Test Data

#### Environmental Conditions

Temperature:	21° C
Relative Humidity:	56%
ATM Pressure:	1005 mbar

\* Testing was performed by Cabin Hu on 2011.06.13----2011.06.14.

Cellular Band:

EUT Position	Frequency (MHz)		Test Mode	Antenna Type	1g SAR Value (W/Kg)	FCC Limit (W/Kg)
	Channel	MHz				
Left Head Cheek	128 (Low)	824.2	GSM	Integral	0.343	1.6
	190 (Middle)	836.6	GSM	Integral	0.332	1.6
	251 (High)	848.8	GSM	Integral	0.346	1.6
Left Head Tilt	128 (Low)	824.2	GSM	Integral	/	1.6
	190 (Middle)	836.6	GSM	Integral	/	1.6
	251 (High)	848.8	GSM	Integral	0.124	1.6
Right Head Cheek	128 (Low)	824.2	GSM	Integral	/	1.6
	190 (Middle)	836.6	GSM	Integral	/	1.6
	251 (High)	848.8	GSM	Integral	0.335	1.6
Right Head Tilt	128 (Low)	824.2	GSM	Integral	/	1.6
	190 (Middle)	836.6	GSM	Integral	/	1.6
	251 (High)	848.8	GSM	Integral	0.121	1.6
Body-Worn Back	190 (Middle)	836.6	GSM	Integral	0.182	1.6
	128 (Low)	824.2	GPRS	Integral	0.311	1.6
	190 (Middle)	836.6	GPRS	Integral	0.330	1.6
	251 (High)	848.8	GPRS	Integral	0.345	1.6

PCS Band:

EUT Position	Frequency (MHz)		Test Mode	Antenna Type	1g SAR Value (W/Kg)	FCC Limit (W/Kg)
	Channel	MHz				
Left Head Cheek	512 (Low)	1850.2	GSM	Integral	0.492	1.6
	661 (Middle)	1880.0	GSM	Integral	0.490	1.6
	810 (High)	1909.8	GSM	Integral	0.483	1.6
Left Head Tilt	512 (Low)	1850.2	GSM	Integral	0.139	1.6
	661 (Middle)	1880.0	GSM	Integral	/	1.6
	810 (High)	1909.8	GSM	Integral	/	1.6
Right Head Cheek	512 (Low)	1850.2	GSM	Integral	0.484	1.6
	661 (Middle)	1880.0	GSM	Integral	/	1.6
	810 (High)	1909.8	GSM	Integral	/	1.6
Right Head Tilt	512 (Low)	1850.2	GSM	Integral	0.129	1.6
	661 (Middle)	1880.0	GSM	Integral	/	1.6
	810 (High)	1909.8	GSM	Integral	/	1.6
Body-Worn Back	512 (Low)	1850.2	GSM	Integral	0.110	1.6
	512 (Low)	1850.2	GPRS	Integral	0.203	1.6
	661 (Middle)	1880.0	GPRS	Integral	0.232	1.6
	810 (High)	1909.8	GPRS	Integral	0.182	1.6

**Note:** Body-worn with GPRS mode was tested with 2 slots configuration.

## APPENDIX A – MEASUREMENT UNCERTAINTY

The uncertainty budget has been determined for the measurement system and is given in the following Table.

### Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	$c_i^1$ (1-g)	$c_i^1$ (10-g)	Standard Uncertainty (1-g) %	Standard Uncertainty (10-g) %
<b>Measurement System</b>							
Probe Calibration	3.5	normal	1	1	1	3.5	3.5
Axial Isotropy	3.7	rectangular	$\sqrt{3}$	$(1-cp)^{1/2}$	$(1-cp)^1_{/2}$	1.5	1.5
Hemispherical Isotropy	10.9	rectangular	$\sqrt{3}$	$\sqrt{cp}$	$\sqrt{cp}$	4.4	4.4
Boundary Effect	1.0	rectangular	$\sqrt{3}$	1	1	0.6	0.6
Linearity	4.7	rectangular	$\sqrt{3}$	1	1	2.7	2.7
Detection Limit	1.0	rectangular	$\sqrt{3}$	1	1	0.6	0.6
Readout Electronics	1.0	normal	1	1	1	1.0	1.0
Response Time	0.8	rectangular	$\sqrt{3}$	1	1	0.5	0.5
Integration Time	1.7	rectangular	$\sqrt{3}$	1	1	1.0	1.0
RF Ambient Condition	3.0	rectangular	$\sqrt{3}$	1	1	1.7	1.7
Probe Positioner Mech.	0.4	rectangular	$\sqrt{3}$	1	1	0.2	0.2
<b>Restriction</b>							
Probe Positioning with respect to Phantom Shell	2.9	rectangular	$\sqrt{3}$	1	1	1.7	1.7
Extrapolation and Integration	3.7	rectangular	$\sqrt{3}$	1	1	2.1	2.1
Test Sample Positioning	4.0	normal	1	1	1	4.0	4.0
Device Holder Uncertainty	2.0	normal	1	1	1	2.0	2.0
Drift of Output Power	3.2	rectangular	$\sqrt{3}$	1	1	1.8	1.8
<b>Phantom and Setup</b>							
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	$\sqrt{3}$	1	1	2.0	2.0
Liquid Conductivity(target)	5.0	rectangular	$\sqrt{3}$	0.7	0.5	2.0	1.4
Liquid Conductivity(meas.)	0.0	normal	1	0.7	0.5	0.0	0.0
Liquid Permittivity(target)	5.0	rectangular	$\sqrt{3}$	0.6	0.5	1.7	1.4
Liquid Permittivity(meas.)	0.0	normal	1	0.6	0.5	0.0	0.0
Combined Uncertainty		RSS				9.4	9.2
Combined Uncertainty (coverage factor=2)		Normal(k=2)				18.8	18.5

**APPENDIX B – PROBE CALIBRATION CERTIFICATES****NCL CALIBRATION LABORATORIES**

Calibration File No.: CP-1139

Client.: BACL

**C E R T I F I C A T E   O F   C A L I B R A T I O N**

It is certified that the equipment identified below has been calibrated in the  
**NCL CALIBRATION LABORATORIES** by qualified personnel following recognized  
procedures and using transfer standards traceable to NRC/NIST.

Equipment: Miniature Isotropic RF Probe 835 MHz

Manufacturer: APREL Laboratories

Model No.: E-020

Serial No.: 273

Calibration in Head Tissue

Calibration Procedure: SSI/DRB-TP-D01-032-E020-V2

Project No: BACB-E020-5537

Calibrated: 20<sup>th</sup> August 2010  
Released on: 24<sup>th</sup> August 2010

This Calibration Certificate is Incomplete Unless Accompanied with the Calibration Results Summary

Released By: **NCL CALIBRATION LABORATORIES**

51 SPECTRUM WAY  
NEPEAN, ONTARIO  
CANADA K2R 1E6

Division of APREL Lab.  
TEL: (613) 820-4988  
FAX: (613) 820-4161

**NCL Calibration Laboratories**

Division of APREL Laboratories.

**Introduction**

This Calibration Report reproduces the results of the calibration performed in line with the SSI/DRB-TP-D01-032-E020-V2 E-Field Probe Calibration Procedure. The results contained within this report are for APREL E-Field Probe E-020 273.

**References**


SSI/DRB-TP-D01-032-E020-V2 E-Field Probe Calibration Procedure  
IEEE 1528 "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques"  
SSI-TP-011 Tissue Calibration Procedure

**Conditions**

Probe 273 was a re-calibration.

**Ambient Temperature of the Laboratory:** 22 °C +/- 0.5°C  
**Temperature of the Tissue:** 21 °C +/- 0.5°C

We the undersigned attest that to the best of our knowledge the calibration of this probe has been accurately conducted and that all information contained within this report has been reviewed for accuracy.

  
Stuart Nicol  
Jesse Hones

**NCL Calibration Laboratories**

Division of APREL Laboratories.

**Calibration Results Summary**

<b>Probe Type:</b>	E-Field Probe E-020
<b>Serial Number:</b>	273
<b>Frequency:</b>	835 MHz
<b>Sensor Offset:</b>	1.56 mm
<b>Sensor Length:</b>	2.5 mm
<b>Tip Enclosure:</b>	Ertalyte*
<b>Tip Diameter:</b>	<5 mm
<b>Tip Length:</b>	60 mm
<b>Total Length:</b>	290 mm

\*Resistive to recommended tissue recipes per IEEE-1528

**Sensitivity in Air**

<b>Channel X:</b>	1.2 $\mu$ V/(V/m) <sup>2</sup>
<b>Channel Y:</b>	1.2 $\mu$ V/(V/m) <sup>2</sup>
<b>Channel Z:</b>	1.2 $\mu$ V/(V/m) <sup>2</sup>
<b>Diode Compression Point:</b>	95 mV

**NCL Calibration Laboratories**

Division of APREL Laboratories.

**Sensitivity in Head Tissue Measured****Frequency:** 835 MHz**Epsilon:** 41.04 (+/-5%)      **Sigma:** 0.89 S/m (+/-5%)**ConvF****Channel X:** 6.5**Channel Y:** 6.5**Channel Z:** 6.5

Tissue sensitivity values were calculated using the load impedance of the APREL Laboratories Daq-Paq.

**Boundary Effect:**

Uncertainty resulting from the boundary effect is less than 2% for the distance between the tip of the probe and the tissue boundary, when less than 2.44mm.

**Spatial Resolution:**

The measured probe tip diameter is 5 mm (+/- 0.01 mm) and therefore meets the requirements of SSI/DRB-TP-D01-032 for spatial resolution.


---

Page 4 of 10

This page has been reviewed for content and attested to on Page 2 of this document.

**NCL Calibration Laboratories**

Division of APREL Laboratories.



**Receiving Pattern 835 MHz (Air)**

Page 5 of 10

This page has been reviewed for content and attested to on Page 2 of this document.

**NCL Calibration Laboratories**

Division of APREL Laboratories.

**Isotropy Error 835 MHz (Air)****Isotropicity Tissue:**


0.10 dB

Page 6 of 10

This page has been reviewed for content and attested to on Page 2 of this document.

**NCL Calibration Laboratories**

Division of APREL Laboratories.


**Dynamic Range**

Page 7 of 10

This page has been reviewed for content and attested to on Page 2 of this document.

**NCL Calibration Laboratories**

Division of APREL Laboratories.

**Video Bandwidth****Probe Frequency Characteristics**

**Video Bandwidth at 500 Hz** 1 dB  
**Video Bandwidth at 1.02 KHz:** 3 dB

**NCL Calibration Laboratories**

Division of APREL Laboratories.

**Conversion Factor Uncertainty Assessment****Frequency:** 835MHz**Epsilon:** 41.04 (+/-5%) **Sigma:** 0.89 S/m (+/-5%)**ConvF****Channel X:** 6.5 7%(K=2)**Channel Y:** 6.5 7%(K=2)**Channel Z:** 6.5 7%(K=2)

To minimize the uncertainty calculation all tissue sensitivity values were calculated using a load impedance of 5 MΩ.

**Boundary Effect:**

For a distance of 2.5mm the evaluated uncertainty (increase in the probe sensitivity) is less than 2%.

**NCL Calibration Laboratories**

Division of APREL Laboratories.

**Test Equipment**

The test equipment used during Probe Calibration, manufacturer, model number and, current calibration status are listed and located on the main APREL server R:\NCL\Calibration Equipment\Instrument List May 2010.

---

Page 10 of 10

This page has been reviewed for content and attested to on Page 2 of this document.

**NCL CALIBRATION LABORATORIES**

Calibration File No.: CP-1140

Client.: BACL

**C E R T I F I C A T E   O F   C A L I B R A T I O N**

It is certified that the equipment identified below has been calibrated in the  
**NCL CALIBRATION LABORATORIES** by qualified personnel following recognized  
procedures and using transfer standards traceable to NRC/NIST.

Equipment: Miniature Isotropic RF Probe 835 MHz

Manufacturer: APREL Laboratories

Model No.: E-020

Serial No.: 273

Calibration in Body Tissue

Calibration Procedure: SSI/DRB-TP-D01-032-E020-V2

Project No: BACB-E020-5537

Calibrated: 20<sup>th</sup> August 2010  
Released on: 24<sup>th</sup> August 2010

This Calibration Certificate is Incomplete Unless Accompanied with the Calibration Results Summary

Released By: \_\_\_\_\_

**NCL CALIBRATION LABORATORIES**

51 SPECTRUM WAY  
NEPEAN, ONTARIO  
CANADA K2R 1E6

Division of APREL Lab.  
TEL: (613) 820-4988  
FAX: (613) 820-4161

**NCL Calibration Laboratories**

Division of APREL Laboratories.

**Introduction**

This Calibration Report reproduces the results of the calibration performed in line with the SSI/DRB-TP-D01-032-E020-V2 E-Field Probe Calibration Procedure. The results contained within this report are for APREL E-Field Probe E-020 273.

**References**


SSI/DRB-TP-D01-032-E020-V2 E-Field Probe Calibration Procedure  
IEEE 1528 "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques"  
SSI-TP-011 Tissue Calibration Procedure

**Conditions**

Probe 273 was a re- calibration.

**Ambient Temperature of the Laboratory:** 22 °C +/- 0.5°C  
**Temperature of the Tissue:** 21 °C +/- 0.5°C

We the undersigned attest that to the best of our knowledge the calibration of this probe has been accurately conducted and that all information contained within this report has been reviewed for accuracy.

  
Stuart Nicol  
Jesse Hones

**NCL Calibration Laboratories**

Division of APREL Laboratories.

**Calibration Results Summary**

<b>Probe Type:</b>	E-Field Probe E-020
<b>Serial Number:</b>	273
<b>Frequency:</b>	835 MHz
<b>Sensor Offset:</b>	1.56 mm
<b>Sensor Length:</b>	2.5 mm
<b>Tip Enclosure:</b>	Ertalyte*
<b>Tip Diameter:</b>	<5 mm
<b>Tip Length:</b>	60 mm
<b>Total Length:</b>	290 mm

\*Resistive to recommended tissue recipes per IEEE-1528

**Sensitivity in Air**

<b>Channel X:</b>	1.2 $\mu$ V/(V/m) <sup>2</sup>
<b>Channel Y:</b>	1.2 $\mu$ V/(V/m) <sup>2</sup>
<b>Channel Z:</b>	1.2 $\mu$ V/(V/m) <sup>2</sup>
<b>Diode Compression Point:</b>	95 mV

**NCL Calibration Laboratories**

Division of APREL Laboratories.

**Sensitivity in Body Tissue Measured**

**Frequency:** 835 MHz

**Epsilon:** 55.91 (+/-5%) **Sigma:** 0.98 S/m (+/-5%)

**ConvF**

**Channel X:** 6.7

**Channel Y:** 6.7

**Channel Z:** 6.7

Tissue sensitivity values were calculated using the load impedance of the APREL Laboratories Daq-Paq.

**Boundary Effect:**

Uncertainty resulting from the boundary effect is less than 2% for the distance between the tip of the probe and the tissue boundary, when less than 2.44mm.

**Spatial Resolution:**

The measured probe tip diameter is 5 mm (+/- 0.01 mm) and therefore meets the requirements of SSI/DRB-TP-D01-032 for spatial resolution.


---

Page 4 of 10

This page has been reviewed for content and attested to on Page 2 of this document.



**NCL Calibration Laboratories**

Division of APREL Laboratories.

**Receiving Pattern 835 MHz (Air)**

**NCL Calibration Laboratories**

Division of APREL Laboratories.


**Isotropy Error 835 MHz (Air)****Isotropicity in Tissue:** 0.10 dB

Page 6 of 10

This page has been reviewed for content and attested to on Page 2 of this document.

**NCL Calibration Laboratories**

Division of APREL Laboratories.


**Dynamic Range**

Page 7 of 10

This page has been reviewed for content and attested to on Page 2 of this document.

**NCL Calibration Laboratories**

Division of APREL Laboratories.

**Video Bandwidth****Probe Frequency Characteristics**

**Video Bandwidth at 500 Hz** 1 dB  
**Video Bandwidth at 1.02 KHz:** 3 dB

**NCL Calibration Laboratories**

Division of APREL Laboratories.

**Conversion Factor Uncertainty Assessment****Frequency:** 835MHz**Epsilon:** 55.91 (+/-5%) **Sigma:** 0.98 S/m (+/-5%)**ConvF****Channel X:** 6.7 7%(K=2)**Channel Y:** 6.7 7%(K=2)**Channel Z:** 6.7 7%(K=2)

To minimize the uncertainty calculation all tissue sensitivity values were calculated using a load impedance of 5 MΩ.

**Boundary Effect:**

For a distance of 2.4mm the evaluated uncertainty (increase in the probe sensitivity) is less than 2%.

**NCL Calibration Laboratories**

Division of APREL Laboratories.

**Test Equipment**

The test equipment used during Probe Calibration, manufacturer, model number and, current calibration status are listed and located on the main APREL server R:\NCL\Calibration Equipment\Instrument List May 2010.

---

Page 10 of 10

This page has been reviewed for content and attested to on Page 2 of this document.

**NCL CALIBRATION LABORATORIES**

Calibration File No.: CP-1141

Client.: BACL

**C E R T I F I C A T E   O F   C A L I B R A T I O N**

It is certified that the equipment identified below has been calibrated in the  
**NCL CALIBRATION LABORATORIES** by qualified personnel following recognized  
procedures and using transfer standards traceable to NRC/NIST.

Equipment: Miniature Isotropic RF Probe 1900 MHz

Manufacturer: APREL Laboratories

Model No.: E-020

Serial No.: 273


Calibration in Head Tissue

Calibration Procedure: SSI/DRB-TP-D01-032-E020-V2

Project No: BACB-E020-5537

Calibrated: 21<sup>st</sup> August 2010  
Released on: 24<sup>th</sup> August 2010

This Calibration Certificate is Incomplete Unless Accompanied with the Calibration Results Summary

Released By: **NCL CALIBRATION LABORATORIES**

51 SPECTRUM WAY  
NEPEAN, ONTARIO  
CANADA K2R 1E6

Division of APREL Lab.  
TEL: (613) 820-4988  
FAX: (613) 820-4161

**NCL Calibration Laboratories**

Division of APREL Laboratories.

**Introduction**

This Calibration Report reproduces the results of the calibration performed in line with the SSI/DRB-TP-D01-032-E020-V2 E-Field Probe Calibration Procedure. The results contained within this report are for APREL E-Field Probe E-020 273.

**References**


SSI/DRB-TP-D01-032-E020-V2 E-Field Probe Calibration Procedure  
IEEE 1528 "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques"  
SSI-TP-011 Tissue Calibration Procedure

**Conditions**

Probe 273 was a re-calibration.

**Ambient Temperature of the Laboratory:** 22 °C +/- 0.5°C  
**Temperature of the Tissue:** 21 °C +/- 0.5°C

We the undersigned attest that to the best of our knowledge the calibration of this probe has been accurately conducted and that all information contained within this report has been reviewed for accuracy.

  
Stuart Nicol  
Jesse Hones

---

Page 2 of 10

This page has been reviewed for content and attested to on Page 2 of this document.

**NCL Calibration Laboratories**

Division of APREL Laboratories.

**Calibration Results Summary**

<b>Probe Type:</b>	E-Field Probe E-020
<b>Serial Number:</b>	273
<b>Frequency:</b>	1900 MHz
<b>Sensor Offset:</b>	1.56 mm
<b>Sensor Length:</b>	2.5 mm
<b>Tip Enclosure:</b>	Ertalyte*
<b>Tip Diameter:</b>	<5 mm
<b>Tip Length:</b>	60 mm
<b>Total Length:</b>	290 mm

\*Resistive to recommended tissue recipes per IEEE-1528

**Sensitivity in Air**

<b>Channel X:</b>	1.2 $\mu$ V/(V/m) <sup>2</sup>
<b>Channel Y:</b>	1.2 $\mu$ V/(V/m) <sup>2</sup>
<b>Channel Z:</b>	1.2 $\mu$ V/(V/m) <sup>2</sup>
<b>Diode Compression Point:</b>	95 mV

**NCL Calibration Laboratories**

Division of APREL Laboratories.

**Sensitivity in Head Tissue Measured****Frequency:** 1900 MHz**Epsilon:** 38.90 (+/-5%)      **Sigma:** 1.39 S/m (+/-5%)**ConvF****Channel X:** 5.25**Channel Y:** 5.25**Channel Z:** 5.25

Tissue sensitivity values were calculated using the load impedance of the APREL Laboratories Daq-Paq.

**Boundary Effect:**

Uncertainty resulting from the boundary effect is less than 2% for the distance between the tip of the probe and the tissue boundary, when less than 2.44mm.

**Spatial Resolution:**

The measured probe tip diameter is 5 mm (+/- 0.01 mm) and therefore meets the requirements of SSI/DRB-TP-D01-032 for spatial resolution.


---

Page 4 of 10

This page has been reviewed for content and attested to on Page 2 of this document.



**NCL Calibration Laboratories**

Division of APREL Laboratories.

**Receiving Pattern 1900 MHz (Air)**

**NCL Calibration Laboratories**

Division of APREL Laboratories.

**Isotropy Error 1900 MHz (Air)****Isotropicity in Tissue:**


0.10 dB

Page 6 of 10

This page has been reviewed for content and attested to on Page 2 of this document.


**NCL Calibration Laboratories**

Division of APREL Laboratories.

**Dynamic Range**

**NCL Calibration Laboratories**

Division of APREL Laboratories.

**Video Bandwidth****Probe Frequency Characteristics**

**Video Bandwidth at 500 Hz** 1 dB  
**Video Bandwidth at 1.02 KHz:** 3 dB

**NCL Calibration Laboratories**

Division of APREL Laboratories.

**Conversion Factor Uncertainty Assessment****Frequency:** 1900MHz**Epsilon:** 38.90 (+/-5%) **Sigma:** 1.39 S/m (+/-5%)**ConvF****Channel X:** 5.25 7%(K=2)**Channel Y:** 5.25 7%(K=2)**Channel Z:** 5.25 7%(K=2)

To minimize the uncertainty calculation all tissue sensitivity values were calculated using a load impedance of 5 MΩ.

**Boundary Effect:**

For a distance of 2.4mm the evaluated uncertainty (increase in the probe sensitivity) is less than 2%.

**NCL Calibration Laboratories**

Division of APREL Laboratories.

**Test Equipment**

The test equipment used during Probe Calibration, manufacturer, model number and, current calibration status are listed and located on the main APREL server R:\NCL\Calibration Equipment\Instrument List May 2010.

---

Page 10 of 10

This page has been reviewed for content and attested to on Page 2 of this document.

**NCL CALIBRATION LABORATORIES**

Calibration File No.: CP-1142

Client.: BACL

**C E R T I F I C A T E   O F   C A L I B R A T I O N**

It is certified that the equipment identified below has been calibrated in the  
**NCL CALIBRATION LABORATORIES** by qualified personnel following recognized  
procedures and using transfer standards traceable to NRC/NIST.

Equipment: Miniature Isotropic RF Probe 1900 MHz

Manufacturer: APREL Laboratories

Model No.: E-020

Serial No.: 273

Calibration in Body Tissue

Calibration Procedure: SSI/DRB-TP-D01-032-E020-V2  
Project No: BACB-E020-5537

Calibrated: 21<sup>st</sup> August 2010  
Released on: 24<sup>th</sup> August 2010

This Calibration Certificate is Incomplete Unless Accompanied with the Calibration Results Summary

Released By: **NCL CALIBRATION LABORATORIES**

51 SPECTRUM WAY  
NEPEAN, ONTARIO  
CANADA K2R 1E6

Division of APREL Lab.  
TEL: (613) 820-4988  
FAX: (613) 820-4161

**NCL Calibration Laboratories**

Division of APREL Laboratories.

**Introduction**

This Calibration Report reproduces the results of the calibration performed in line with the SSI/DRB-TP-D01-032-E020-V2 E-Field Probe Calibration Procedure. The results contained within this report are for APREL E-Field Probe E-020 273.

**References**


SSI/DRB-TP-D01-032-E020-V2 E-Field Probe Calibration Procedure  
IEEE 1528 "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques"  
SSI-TP-011 Tissue Calibration Procedure

**Conditions**

Probe 273 was a re-calibration.

**Ambient Temperature of the Laboratory:** 22 °C +/- 0.5°C  
**Temperature of the Tissue:** 21 °C +/- 0.5°C

We the undersigned attest that to the best of our knowledge the calibration of this probe has been accurately conducted and that all information contained within this report has been reviewed for accuracy.

  
Stuart Nicol  
Jesse Hones

**NCL Calibration Laboratories**

Division of APREL Laboratories.

**Calibration Results Summary**

<b>Probe Type:</b>	E-Field Probe E-020
<b>Serial Number:</b>	273
<b>Frequency:</b>	1900 MHz
<b>Sensor Offset:</b>	1.56 mm
<b>Sensor Length:</b>	2.5 mm
<b>Tip Enclosure:</b>	Ertalyte*
<b>Tip Diameter:</b>	<5 mm
<b>Tip Length:</b>	60 mm
<b>Total Length:</b>	290 mm

\*Resistive to recommended tissue recipes per IEEE-1528

**Sensitivity in Air**

<b>Channel X:</b>	1.2 $\mu$ V/(V/m) <sup>2</sup>
<b>Channel Y:</b>	1.2 $\mu$ V/(V/m) <sup>2</sup>
<b>Channel Z:</b>	1.2 $\mu$ V/(V/m) <sup>2</sup>
<b>Diode Compression Point:</b>	95 mV

**NCL Calibration Laboratories**

Division of APREL Laboratories.

**Sensitivity in Body Tissue Measured****Frequency:** 1900 MHz**Epsilon:** 53.11 (+/-5%)      **Sigma:** 1.56 S/m (+/-5%)**ConvF****Channel X:** 5.15**Channel Y:** 5.15**Channel Z:** 5.15

Tissue sensitivity values were calculated using the load impedance of the APREL Laboratories Daq-Paq.

**Boundary Effect:**

Uncertainty resulting from the boundary effect is less than 2% for the distance between the tip of the probe and the tissue boundary, when less than 2.44mm.

**Spatial Resolution:**

The measured probe tip diameter is 5 mm (+/- 0.01 mm) and therefore meets the requirements of SSI/DRB-TP-D01-032 for spatial resolution.


---

Page 4 of 10

This page has been reviewed for content and attested to on Page 2 of this document.



**NCL Calibration Laboratories**

Division of APREL Laboratories.

**Receiving Pattern 1900 MHz (Air)**

**NCL Calibration Laboratories**

Division of APREL Laboratories.

**Isotropy Error 1900 MHz (Air)****Isotropicity in Tissue:**


0.10 dB

Page 6 of 10

This page has been reviewed for content and attested to on Page 2 of this document.

**NCL Calibration Laboratories**

Division of APREL Laboratories.


**Dynamic Range**

Page 7 of 10

This page has been reviewed for content and attested to on Page 2 of this document.

**NCL Calibration Laboratories**

Division of APREL Laboratories.

**Video Bandwidth****Probe Frequency Characteristics**

**Video Bandwidth at 500 Hz** 1 dB  
**Video Bandwidth at 1.02 KHz:** 3 dB

**NCL Calibration Laboratories**

Division of APREL Laboratories.

**Conversion Factor Uncertainty Assessment****Frequency:** 1900MHz**Epsilon:** 53.11 (+/-5%) **Sigma:** 1.56 S/m (+/-5%)**ConvF****Channel X:** 5.15 7%(K=2)**Channel Y:** 5.15 7%(K=2)**Channel Z:** 5.15 7%(K=2)

To minimize the uncertainty calculation all tissue sensitivity values were calculated using a load impedance of 5 MΩ.

**Boundary Effect:**

For a distance of 2.4mm the evaluated uncertainty (increase in the probe sensitivity) is less than 2%.

**NCL Calibration Laboratories**

Division of APREL Laboratories.

**Test Equipment**

The test equipment used during Probe Calibration, manufacturer, model number and, current calibration status are listed and located on the main APREL server R:\NCL\Calibration Equipment\Instrument List May 2010.

---

Page 10 of 10

This page has been reviewed for content and attested to on Page 2 of this document.

**APPENDIX C – DIPOLE CALIBRATION CERTIFICATES**

Bay Area Compliance Laboratories Corp.  
1274 Anvilwood Ave, Sunnyvale, CA 94089  
Tel: (408)732-9162 / Fax: (408)732-9164

**Verification of Calibration Report**

**Report Number:** CAL 2010-09-20

**Description:** Dipole Antenna

**Manufacturer:** APREL Laboratories

**Model Number:** ALS-D-835-S-2

**Serial Number:** SN: 180-00558

**Date of Calibration:** 20 Sept 2010

**Condition Received:** In Tolerance

**Condition Returned:** In Tolerance

**Conditions and results of calibration:** See attachment

This device has been instrumented, measured and calibrated in accordance with the Bay Area Compliance Laboratories Corp. ("BACL") Quality Assurance Manual procedures and the results being traceable to the National Institute of Standards and Technology (NIST). The BACL Quality System is accredited by NVLAP to ISO/IEC 17025:2005. Unless stated otherwise; Measurement Uncertainties are derived from ISO Guide to the Determination of Uncertainties with a Coverage Factor of  $k = 2$  for a 95% level of confidence, no sampling plan or other process was used for this calibration (unless stated otherwise), the results reported herein apply only to the calibration of the item described above, and limitations of use (if any) shall be stated this Calibration Report.

**Calibrated By:**

A handwritten signature in black ink, appearing to read 'Zhang Quina'.

9/20/2010

Date

**Reviewed By:**

A handwritten signature in black ink, appearing to read 'Zhang Victor'.

9/21/2010

Date

**Quality Assurance:**

A handwritten signature in black ink, appearing to read 'Mellberg Hans'.

21 SEP 2010

Date

## Attachment

### Ambient Environment of Calibration

Temperature	Relative Humidity	Pressure
22 ° C	56.5 %	102.78 k Pa

### Equipment List

Description	Manufacturer	Model	Serial #	Cal Date
Signal Generator	HP	8648C	3426A00417	2010-08-30
Network Analyzer	HP	8753D	3410A04346	2010-06-03
Power meter	Agilent	E4419B	MY41291511	2010-09-01
Power Sensor	Agilent	E9301A	MY41497252	2010-02-19
Reference Probe	SPEAG	ET3DV6	1604	2010-09-16

### Measurement Conditions

<b>DASY Version</b>	DASY4	V4.7
<b>Extrapolation</b>	Advanced Extrapolation	
<b>Phantom</b>	Flat Phantom	
<b>Distance Dipole Center-TSL</b>	15 mm	With Spacer
<b>Area Scan resolution</b>	dx,dy = 15 mm	
<b>Zoom Scan resolution</b>	dx,dy,dz = 5 mm	
<b>Frequency</b>	835 MHz ± 1MHz	

### Calibration is performed According to the Following Standards:

1. IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
2. IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devise used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
3. DASY 4 System Handbook

**Calibration Data:****Head TSL Parameters**

The following parameters and calculations were applied

	Temperature	Permittivity	Conductivity
Nominal Head TSL Parameters	22.0°C	41.5	0.90
Measured Head TSL Parameters	22.0°C	41.5	0.89
Head TSL Temperature during test	23.0°C		

**SAR result with Head TSL**

SAR average over 1 cm <sup>3</sup> (1g) of Head TSL	Condition	
SAR measured	500 mW input power	4.77 mW / g
SAR normalized	Normalized to 1W	9.54 mW / g
SAR for nominal Head TSL parameters <sup>1</sup>	Normalized to 1W	9.5 mW / g ± 10%

SAR average over 10 cm <sup>3</sup> (10g) of Head TSL	Condition	
SAR measured	500 mW input power	3.02 mW / g
SAR normalized	Normalized to 1W	6.04 mW / g
SAR for nominal Head TSL parameters <sup>1</sup>	Normalized to 1W	6.2 mW / g ± 10%

**Antenna Parameters with Head TSL**

Impedance, transformed to feed point	56.174 Ω
Return Loss	-23.458 dB

**DASY4 Validation Report for Head TSL****Test Laboratory: Bay Area Compliance Lab Corp.(BACL)****System Performance Test (835 MHz Head Tissue)****DUT: Dipole 835 MHz; Type: ALS-D835-S-2; Serial: SN: 180-00558**


Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.89$  mho/m;  $\epsilon_r = 41.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>


Phantom section: Flat Section

## DASY4 Configuration:


- Probe: ET3DV6 - SN1604; ConvF(6.26, 6.26, 6.26); Calibrated: 9/16/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 11/8/2007
- Phantom: SAM with CRP; Type: Twin SAM; Serial: TP-1032
- Measurement SW: DASY4, V4.6 Build 23; Post processing SW: SEMCAD, V1.8 Build 184

**d = 15 mm, Pin = 0.5W /Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 5.08 mW/g**d = 15 mm, Pin = 0.5W /Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm  
Reference Value = 77.8 V/m; Power Drift = -0.113 dB  
Peak SAR (extrapolated) = 7.35 W/kg**SAR(1 g) = 4.77 mW/g; SAR(10 g) = 3.02 mW/g**  
Maximum value of SAR (measured) = 5.16 mW/g

## Impedance Measurement Plot for Head TSL



## Return Loss Measurement Plot for Head TSL





Bay Area Compliance Laboratories Corp.  
1274 Anvilwood Ave, Sunnyvale, CA 94089  
Tel: (408)732-9162 / Fax: (408)732-9164

## Verification of Calibration Report

**Report Number:** CAL 2010-09-20

**Description:** Dipole Antenna

**Manufacturer:** APREL Laboratories

**Model Number:** ALS-D-1900-S-2

**Serial Number:** SN: 210-00710

**Date of Calibration:** 20 Sept 2010

**Condition Received:** In Tolerance

**Condition Returned:** In Tolerance

**Conditions and results of calibration:** See attachment

This device has been instrumented, measured and calibrated in accordance with the Bay Area Compliance Laboratories Corp. ("BACL") Quality Assurance Manual procedures and the results being traceable to the National Institute of Standards and Technology (NIST). The BACL Quality System is accredited by NVLAP to ISO/IEC 17025:2005. Unless stated otherwise; Measurement Uncertainties are derived from ISO Guide to the Determination of Uncertainties with a Coverage Factor of  $k = 2$  for a 95% level of confidence, no sampling plan or other process was used for this calibration (unless stated otherwise), the results reported herein apply only to the calibration of the item described above, and limitations of use (if any) shall be stated this Calibration Report.

**Calibrated By:**

Quinn Jiang

9/20/2010

Date

**Reviewed By:**

Victor Zhang

9/21/2010

Date

**Quality Assurance:**

Hans Mellberg

21 SEP 2010

Date

## Attachment

### Ambient Environment of Calibration

Temperature	Relative Humidity	Pressure
22 ° C	53.5 %	104.55 k Pa

### Equipment List

Description	Manufacturer	Model	Serial #	Cal Date
Signal Generator	HP	8648C	3426A00417	2010-08-30
Network Analyzer	HP	8753D	3410A04346	2010-06-03
Power meter	Agilent	E4419B	MY41291511	2010-09-01
Power Sensor	Agilent	E9301A	MY41497252	2010-02-19
Reference Probe	SPEAG	ET3DV6	1604	2010-09-16

### Measurement Conditions

<b>DASY Version</b>	DASY4	
<b>Extrapolation</b>	Advanced Extrapolation	
<b>Phantom</b>	Flat Phantom	
<b>Distance Dipole Center-TSL</b>	10 mm	With Spacer
<b>Area Scan resolution</b>	dx,dy = 15 mm	
<b>Zoom Scan resolution</b>	dx,dy,dz = 5 mm	
<b>Frequency</b>	1900 MHz ± 1MHz	

### Calibration is performed According to the Following Standards:

1. IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
2. IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devise used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
3. DASY 4 System Handbook

**Calibration Data:****Head TSL Parameters**

The following parameters and calculations were applied

	Temperature	Permittivity	Conductivity
Nominal Head TSL Parameters	22.0°C	40.0	1.40
Measured Head TSL Parameters	(22.0±0.3)°C	39.9	1.38
Head TSL Temperature during test	(23.0±0.3)°C		

**SAR result with Head TSL**

SAR average over 1 cm <sup>3</sup> (1g) of Head TSL	Condition	
SAR measured	500 mW input power	18.8 mW / g
SAR normalized	Normalized to 1W	37.6 mW / g
SAR for nominal Head TSL parameters <sup>1</sup>	Normalized to 1W	39.7 mW / g ± 10%

SAR average over 10 cm <sup>3</sup> (10g) of Head TSL	Condition	
SAR measured	500 mW input power	9.58 mW / g
SAR normalized	Normalized to 1W	19.16 mW / g
SAR for nominal Head TSL parameters <sup>1</sup>	Normalized to 1W	20.5 mW / g ± 10%

**Antenna Parameters with Head TSL**

Impedance, transformed to feed point	50.727 Ω
Return Loss	-35.881 dB

<sup>1</sup>Correction to nominal TSL parameters according to DASY 4 System Handbook, chapter "SAR Sensitivities"

**DASY4 Validation Report for Head TSL****Test Laboratory: Bay Area Compliance Lab Corp.(BACL)****System Performance Test (1900 MHz Head Tissue)****DUT: Dipole 1900 MHz; Type: ALS-D-1900-S-2; Serial: SN: 210-00710**

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1


Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.38$  mho/m;  $\epsilon_r = 39.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1604; ConvF(5.04, 5.04, 5.04); Calibrated: 9/16/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 11/8/2007
- Phantom: SAM with CRP; Type: Twin SAM; Serial: TP-1032
- Measurement SW: DASY4, V4.6 Build 23; Post processing SW: SEMCAD, V1.8 Build 184

**d =10 mm, Pin = 0.5W /Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 20.7 mW/g**d =10 mm, Pin = 0.5W /Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm  
Reference Value = 127.5 V/m; Power Drift = -0.054 dB  
Peak SAR (extrapolated) = 34.7 W/kg**SAR(1 g) = 18.8 mW/g; SAR(10 g) = 9.58 mW/g**  
Maximum value of SAR (measured) = 21.3 mW/g

**Impedance Measurement Plot for Head TSL****Return Loss Measurement Plot for Head TSL**

## APPENDIX D – SAR SYSTEM VALIDATION DATA

### Test Laboratory: Bay Area Compliance Lab Corp. (Shenzhen)

#### System Performance Check 835 MHz, Head Tissue

#### Dipole 835 MHz; Type: ALS-D-835-S-2; S/N: 180-00558

##### Product Data

Device Name : Dipole 835 MHz  
 Serial No. : 180-00558  
 Type : Dipole  
 Model : ALS-D-835-S-2  
 Frequency : 835.00 MHz  
 Max. Transmit Pwr : 1 W  
 Drift Time : 3 min(s)  
 Power Drift-Start : 10.176 W/kg  
 Power Drift-Finish : 10.074 W/kg  
 Power Drift (%) : -0.922

##### Phantom Data

Name : APREL-Uni  
 Type : Uni-Phantom  
 Size (mm) : 280 x 280 x 200  
 Serial No. : System Default  
 Location : Center  
 Description : Default  
 Phantom Data

##### Tissue Data

Type : HEAD  
 Serial No. : 270-01002  
 Frequency : 835.00 MHz  
 Last Calib. Date : 10-Jun -2011  
 Temperature : 20.00 °C  
 Ambient Temp. : 21.00 °C  
 Humidity : 56.00 RH%  
 Epsilon : 41.13 F/m  
 Sigma : 0.90 S/m  
 Density : 1000.00 kg/cu. m


##### Probe Data

Name : E-Field  
 Model : E-020  
 Type : E-Field Triangle  
 Serial No. : 273  
 Last Calib. Date : 20-Aug-2010  
 Frequency : 835.00 MHz  
 Duty Cycle Factor : 1  
 Conversion Factor : 6.5  
 Probe Sensitivity : 1.20 1.20 1.20 μV/(V/m)2  
 Compression Point : 95.00 mV  
 Offset : 1.56 mm

##### Measurement Data

Crest Factor : 1  
 Scan Type : Complete  
 Tissue Temp. : 21.00 °C  
 Ambient Temp. : 21.00 °C  
 Area Scan : 7x9x1 : Measurement x=10mm, y=10mm, z=4mm  
 Zoom Scan : 7x7x7 : Measurement x=5mm, y=5mm, z=5mm

1 gram SAR value : 9.721 W/kg  
10 gram SAR value : 6.049 W/kg  
Area Scan Peak SAR : 10.324 W/kg  
Zoom Scan Peak SAR : 15.814 W/kg



### 835 MHz System Check with Head Tissue

**Test Laboratory: Bay Area Compliance Lab Corp. (Shenzhen)****System Performance Check 835 MHz, Body Tissue****Dipole 835 MHz; Type: ALS-D-835-S-2; S/N: 180-00558**

## Product Data

Device Name : Dipole 835 MHz  
Serial No. : 180-00558  
Type : Dipole  
Model : ALS-D-835-S-2  
Frequency : 835.00 MHz  
Max. Transmit Pwr : 1 W  
Drift Time : 3 min(s)  
Power Drift-Start : 10.066 W/kg  
Power Drift-Finish : 10.026 W/kg  
Power Drift (%) : -0.391

## Phantom Data

Name : APREL-Uni  
Type : Uni-Phantom  
Size (mm) : 280 x 280 x 200  
Serial No. : System Default  
Location : Center  
Description : Default  
Phantom Data

## Tissue Data

Type : Body  
Serial No. : 270-02101  
Frequency : 835.00 MHz  
Last Calib. Date : 10-Jun -2011  
Temperature : 20.00 °C  
Ambient Temp. : 21.00 °C  
Humidity : 56.00 RH%  
Epsilon : 55.57 F/m  
Sigma : 1.00 S/m  
Density : 1000.00 kg/cu. m


## Probe Data

Name : E-Field  
Model : E-020  
Type : E-Field Triangle  
Serial No. : 273  
Last Calib. Date : 20-Aug-2010  
Frequency : 835.00 MHz  
Duty Cycle Factor : 1  
Conversion Factor : 6.7  
Probe Sensitivity : 1.20 1.20 1.20 µV/(V/m)2  
Compression Point : 95.00 mV  
Offset : 1.56 mm

## Measurement Data

Crest Factor : 1  
Scan Type : Complete  
Tissue Temp. : 21.00 °C  
Ambient Temp. : 21.00 °C  
Area Scan : 7x9x1 : Measurement x=10mm, y=10mm, z=4mm  
Zoom Scan : 7x7x7 : Measurement x=5mm, y=5mm, z=5mm

1 gram SAR value : 9.651 W/kg  
10 gram SAR value : 6.042 W/kg  
Area Scan Peak SAR : 10.936 W/kg  
Zoom Scan Peak SAR : 15.013 W/kg



### 835 MHz System Check with Body Tissue

**Test Laboratory: Bay Area Compliance Lab Corp. (Shenzhen)****System Performance Check 1900 MHz, Head Tissue****Dipole 1900 MHz; Type: ALS-D-1900-S-2; S/N: 210-00710****Product Data**

Device Name : Dipole 1900MHz  
Serial No. : 210-00710  
Type : Dipole  
Model : ALS-D-1900-S-2  
Frequency : 1900.00 MHz  
Max. Transmit Pwr : 1 W  
Drift Time : 3 min(s)  
Power Drift-Start : 45.508 W/kg  
Power Drift-Finish : 45.221 W/kg  
Power Drift (%) : 0.545

**Phantom Data**

Name : APREL-Uni  
Type : Uni-Phantom  
Size (mm) : 280 x 280 x 200  
Serial No. : System Default  
Location : Center  
Description : Default

**Tissue Data**

Type : HEAD  
Serial No. : 295-01103  
Frequency : 1900.00 MHz  
Last Calib. Date : 10-Jun-2011  
Temperature : 20.00 °C  
Ambient Temp. : 21.00 °C  
Humidity : 56.00 RH%  
Epsilon : 39.54 F/m  
Sigma : 1.45 S/m  
Density : 1000.00 kg/cu. m


**Probe Data**

Name : E-Field  
Model : E-020  
Type : E-Field Triangle  
Serial No. : 273  
Last Calib. Date : 21-Aug-2010  
Frequency : 1900.00 MHz  
Duty Cycle Factor : 1  
Conversion Factor : 5.25  
Probe Sensitivity : 1.20 1.20 1.20 µV/(V/m)2  
Compression Point : 95.00 mV  
Offset : 1.56 mm

**Measurement Data**

Crest Factor : 1  
Scan Type : Complete  
Tissue Temp. : 20.00 °C  
Ambient Temp. : 20.00 °C  
Area Scan : 7x9x1 : Measurement x=10mm, y=10mm, z=4mm  
Zoom Scan : 7x7x7 : Measurement x=5mm, y=5mm, z=5mm

1 gram SAR value : 41.691 W/kg  
10 gram SAR value : 21.315 W/kg  
Area Scan Peak SAR : 45.694 W/kg  
Zoom Scan Peak SAR : 80.675 W/kg



### 1900 MHz System Check with Head Tissue

**Test Laboratory: Bay Area Compliance Lab Corp. (Shenzhen)****System Performance Check 1900 MHz, Body Tissue****Dipole 1900 MHz; Type: ALS-D-1900-S-2; S/N: 210-00710****Product Data**

Device Name : Dipole 1900MHz  
Serial No. : 210-00710  
Type : Dipole  
Model : ALS-D-1900-S-2  
Frequency : 1900.00 MHz  
Max. Transmit Pwr : 1 W  
Drift Time : 3 min(s)  
Power Drift-Start : 38.089 W/kg  
Power Drift-Finish : 38.563 W/kg  
Power Drift (%) : 0.910

**Phantom Data**

Name : APREL-Uni  
Type : Uni-Phantom  
Size (mm) : 280 x 280 x 200  
Serial No. : System Default  
Location : Center  
Description : Default

**Tissue Data**

Type : Body  
Serial No. : 295-02102  
Frequency : 1900.00 MHz  
Last Calib. Date : 10-Jun-2011  
Temperature : 20.00 °C  
Ambient Temp. : 21.00 °C  
Humidity : 56.00 RH%  
Epsilon : 53.58 F/m  
Sigma : 1.54 S/m  
Density : 1000.00 kg/cu. m


**Probe Data**

Name : E-Field  
Model : E-020  
Type : E-Field Triangle  
Serial No. : 273  
Last Calib. Date : 21-Aug-2010  
Frequency : 1900.00 MHz  
Duty Cycle Factor : 1  
Conversion Factor : 5.15  
Probe Sensitivity : 1.20 1.20 1.20 μV/(V/m)2  
Compression Point : 95.00 mV  
Offset : 1.56 mm

**Measurement Data**

Crest Factor : 1  
Scan Type : Complete  
Tissue Temp. : 20.00 °C  
Ambient Temp. : 21.00 °C  
Area Scan : 7x9x1 : Measurement x=10mm, y=10mm, z=4mm  
Zoom Scan : 7x7x7 : Measurement x=5mm, y=5mm, z=5mm

1 gram SAR value : 40.688 W/kg  
10 gram SAR value : 20.603 W/kg  
Area Scan Peak SAR : 45.946 W/kg  
Zoom Scan Peak SAR : 74.466 W/kg



### 1900 MHz System Check with Body Tissue

## APPENDIX E – EUT SCAN RESULTS

### Test Laboratory: Bay Area Compliance Lab Corp. (Shenzhen)

#### Left Head Cheek (835 MHz Low Channel)

##### Measurement Data

Test mode : GSM  
Crest Factor : 8  
Scan Type : Complete  
Area Scan : 13x9x1: Measurement x=10mm, y=10mm, z=4mm  
Zoom Scan : 7x7x7: Measurement x=5mm, y=5mm, z=5mm  
Power Drift-Start : 0.017 W/kg  
Power Drift-Finish : 0.017 W/kg  
Power Drift (%) : -1.151


##### Tissue Data

Type : HEAD  
Frequency : 835.00 MHz  
Epsilon : 41.13 F/m  
Sigma : 0.90 S/m  
Density : 1000.00 kg/cu. m

##### Probe Data

Serial No. : 273  
Frequency : 835.00 MHz  
Duty Cycle Factor : 8  
Conversion Factor : 6.5  
Probe Sensitivity : 1.20 1.20 1.20  $\mu$ V/(V/m)<sup>2</sup>  
Compression Point : 95.00 mV  
Offset : 1.56 mm  
  
1 gram SAR value : 0.343 W/kg  
10 gram SAR value : 0.247 W/kg  
Area Scan Peak SAR : 0.354 W/kg  
Zoom Scan Peak SAR : 0.560 W/kg

**Plot 1#**



**Test Laboratory: Bay Area Compliance Lab Corp. (Shenzhen)****Left Head Cheek (835 MHz Middle Channel)****Measurement Data**

Test mode : GSM  
Crest Factor : 8  
Scan Type : Complete  
Area Scan : 13x9x1 : Measurement x=10mm, y=10mm, z=4mm  
Zoom Scan : 7x7x7 : Measurement x=5mm, y=5mm, z=5mm  
Power Drift-Start : 0.016 W/kg  
Power Drift-Finish : 0.016 W/kg  
Power Drift (%) : -3.894


**Tissue Data**

Type : HEAD  
Frequency : 835.00 MHz  
Epsilon : 41.13 F/m  
Sigma : 0.90 S/m  
Density : 1000.00 kg/cu. m

**Probe Data**

Serial No. : 273  
Frequency : 835.00 MHz  
Duty Cycle Factor : 8  
Conversion Factor : 6.5  
Probe Sensitivity : 1.20 1.20 1.20  $\mu$ V/(V/m)<sup>2</sup>  
Compression Point : 95.00 mV  
Offset : 1.56 mm

1 gram SAR value : 0.332 W/kg  
10 gram SAR value : 0.193 W/kg  
Area Scan Peak SAR : 0.366 W/kg  
Zoom Scan Peak SAR : 0.570 W/kg

**Plot 2#**

**Test Laboratory: Bay Area Compliance Lab Corp. (Shenzhen)****Left Head Cheek (835 MHz High Channel)****Measurement Data**

Test mode : GSM  
 Crest Factor : 8  
 Scan Type : Complete  
 Area Scan : 13x9x1 : Measurement x=10mm, y=10mm, z=4mm  
 Zoom Scan : 7x7x7 : Measurement x=5mm, y=5mm, z=5mm  
 Power Drift-Start : 0.052 W/kg  
 Power Drift-Finish : 0.051 W/kg  
 Power Drift (%) : -2.128


**Tissue Data**

Type : HEAD  
 Frequency : 835.00 MHz  
 Epsilon : 41.13 F/m  
 Sigma : 0.90 S/m  
 Density : 1000.00 kg/cu. m

**Probe Data**

Serial No. : 273  
 Frequency : 835.00 MHz  
 Duty Cycle Factor : 8  
 Conversion Factor : 6.5  
 Probe Sensitivity : 1.20 1.20 1.20  $\mu$ V/(V/m)<sup>2</sup>  
 Compression Point : 95.00 mV  
 Offset : 1.56 mm

1 gram SAR value : 0.346 W/kg  
 10 gram SAR value : 0.216 W/kg  
 Area Scan Peak SAR : 0.365 W/kg  
 Zoom Scan Peak SAR : 0.640 W/kg

**Plot 3#**

**Test Laboratory: Bay Area Compliance Lab Corp. (Shenzhen)****Left Head Tilt (835 MHz High Channel)****Measurement Data**

Test mode : GSM  
 Crest Factor : 8  
 Scan Type : Complete  
 Area Scan : 13x9x1 : Measurement x=10mm, y=10mm, z=4mm  
 Zoom Scan : 7x7x7 : Measurement x=5mm, y=5mm, z=5mm  
 Power Drift-Start : 0.047 W/kg  
 Power Drift-Finish : 0.046 W/kg  
 Power Drift (%) : -2.606


**Tissue Data**

Type : HEAD  
 Frequency : 835.00 MHz  
 Epsilon : 41.13 F/m  
 Sigma : 0.90 S/m  
 Density : 1000.00 kg/cu. m

**Probe Data**

Serial No. : 273  
 Frequency : 835.00 MHz  
 Duty Cycle Factor : 8  
 Conversion Factor : 6.5  
 Probe Sensitivity : 1.20 1.20 1.20  $\mu$ V/(V/m)<sup>2</sup>  
 Compression Point : 95.00 mV  
 Offset : 1.56 mm

1 gram SAR value : 0.124 W/kg  
 10 gram SAR value : 0.080 W/kg  
 Area Scan Peak SAR : 0.140 W/kg  
 Zoom Scan Peak SAR : 0.330 W/kg

**Plot 4#**

**Test Laboratory: Bay Area Compliance Lab Corp. (Shenzhen)****Right Head Cheek (835 MHz High Channel)**

## Measurement Data

Test mode : GSM  
Crest Factor : 8  
Scan Type : Complete  
Area Scan : 13x9x1 : Measurement x=10mm, y=10mm, z=4mm  
Zoom Scan : 7x7x7 : Measurement x=5mm, y=5mm, z=5mm  
Power Drift-Start : 0.045 W/kg  
Power Drift-Finish : 0.045 W/kg  
Power Drift (%) : -0.780


## Tissue Data

Type : HEAD  
Frequency : 835.00 MHz  
Epsilon : 41.13 F/m  
Sigma : 0.90 S/m  
Density : 1000.00 kg/cu. m

## Probe Data

Serial No. : 273  
Frequency : 835.00 MHz  
Duty Cycle Factor : 8  
Conversion Factor : 6.5  
Probe Sensitivity : 1.20 1.20 1.20  $\mu$ V/(V/m)<sup>2</sup>  
Compression Point : 95.00 mV  
Offset : 1.56 mm

1 gram SAR value : 0.335 W/kg  
10 gram SAR value : 0.208 W/kg  
Area Scan Peak SAR : 0.340 W/kg  
Zoom Scan Peak SAR : 0.530 W/kg

**Plot 5#**

**Test Laboratory: Bay Area Compliance Lab Corp. (Shenzhen)****Right Head Tilt (835 MHz High Channel)****Measurement Data**

Test mode : GSM  
Crest Factor : 8  
Scan Type : Complete  
Area Scan : 13x9x1 : Measurement x=10mm, y=10mm, z=4mm  
Zoom Scan : 7x7x7 : Measurement x=5mm, y=5mm, z=5mm  
Power Drift-Start : 0.026 W/kg  
Power Drift-Finish : 0.026 W/kg  
Power Drift (%) : 2.580


**Tissue Data**

Type : HEAD  
Frequency : 835.00 MHz  
Epsilon : 41.13 F/m  
Sigma : 0.90 S/m  
Density : 1000.00 kg/cu. m

**Probe Data**

Serial No. : 273  
Frequency : 835.00 MHz  
Duty Cycle Factor : 8  
Conversion Factor : 6.5  
Probe Sensitivity : 1.20 1.20 1.20  $\mu$ V/(V/m)<sup>2</sup>  
Compression Point : 95.00 mV  
Offset : 1.56 mm

1 gram SAR value : 0.121 W/kg  
10 gram SAR value : 0.088 W/kg  
Area Scan Peak SAR : 0.128 W/kg  
Zoom Scan Peak SAR : 0.270 W/kg

**Plot 6#**

**Test Laboratory: Bay Area Compliance Lab Corp. (Shenzhen)****Body- worn Back (835 MHz High Channel)****Measurement Data**

Test mode : GSM  
Crest Factor : 8  
Scan Type : Complete  
Area Scan : 9x13x1: Measurement x=10mm, y=10mm, z=4mm  
Zoom Scan : 7x7x7 : Measurement x=5mm, y=5mm, z=5mm  
Power Drift-Start : 0.033 W/kg  
Power Drift-Finish : 0.034 W/kg  
Power Drift (%) : 3.083


**Tissue Data**

Type : BODY  
Frequency : 835.00 MHz  
Epsilon : 55.57 F/m  
Sigma : 1.00 S/m  
Density : 1000.00 kg/cu. m

**Probe Data**

Serial No. : 273  
Frequency : 835.00 MHz  
Duty Cycle Factor : 8  
Conversion Factor : 6.7  
Probe Sensitivity : 1.20 1.20 1.20  $\mu$ V/(V/m)<sup>2</sup>  
Compression Point : 95.00 mV  
Offset : 1.56 mm

1 gram SAR value : 0.182 W/kg  
10 gram SAR value : 0.110 W/kg  
Area Scan Peak SAR : 0.216 W/kg  
Zoom Scan Peak SAR : 0.481 W/kg

**Plot 7#**

**Test Laboratory: Bay Area Compliance Lab Corp. (Shenzhen)****Body- worn Back (835 MHz Low Channel)**

## Measurement Data

Test mode : GPRS  
Crest Factor : 4  
Scan Type : Complete  
Area Scan : 9x13x1: Measurement x=10mm, y=10mm, z=4mm  
Zoom Scan : 7x7x7 : Measurement x=5mm, y=5mm, z=5mm  
Power Drift-Start : 0.027 W/kg  
Power Drift-Finish : 0.027 W/kg  
Power Drift (%) : 1.032


## Tissue Data

Type : BODY  
Frequency : 835.00 MHz  
Epsilon : 55.57 F/m  
Sigma : 1.00 S/m  
Density : 1000.00 kg/cu. m

## Probe Data

Serial No. : 273  
Frequency : 835.00 MHz  
Duty Cycle Factor : 4  
Conversion Factor : 6.7  
Probe Sensitivity : 1.20 1.20 1.20  $\mu$ V/(V/m)<sup>2</sup>  
Compression Point : 95.00 mV  
Offset : 1.56 mm

1 gram SAR value : 0.311 W/kg  
10 gram SAR value : 0.163 W/kg  
Area Scan Peak SAR : 0.352 W/kg  
Zoom Scan Peak SAR : 0.560 W/kg

**Plot 8#**

**Test Laboratory: Bay Area Compliance Lab Corp. (Shenzhen)****Body- worn Back (835 MHz Middle Channel)****Measurement Data**

Test mode : GPRS  
Crest Factor : 4  
Scan Type : Complete  
Area Scan : 9x13x1: Measurement x=10mm, y=10mm, z=4mm  
Zoom Scan : 7x7x7 : Measurement x=5mm, y=5mm, z=5mm  
Power Drift-Start : 0.027 W/kg  
Power Drift-Finish : 0.028 W/kg  
Power Drift (%) : 2.991


**Tissue Data**

Type : BODY  
Frequency : 835.00 MHz  
Epsilon : 55.57 F/m  
Sigma : 1.00 S/m  
Density : 1000.00 kg/cu. m

**Probe Data**

Serial No. : 273  
Frequency : 835.00 MHz  
Duty Cycle Factor : 4  
Conversion Factor : 6.7  
Probe Sensitivity : 1.20 1.20 1.20  $\mu$ V/(V/m)<sup>2</sup>  
Compression Point : 95.00 mV  
Offset : 1.56 mm

1 gram SAR value : 0.330 W/kg  
10 gram SAR value : 0.192 W/kg  
Area Scan Peak SAR : 0.372 W/kg  
Zoom Scan Peak SAR : 0.570 W/kg

**Plot 9#**

**Test Laboratory: Bay Area Compliance Lab Corp. (Shenzhen)****Body- worn Back (835 MHz High Channel)**

## Measurement Data

Test mode : GPRS  
Crest Factor : 4  
Scan Type : Complete  
Area Scan : 9x13x1: Measurement x=10mm, y=10mm, z=4mm  
Zoom Scan : 7x7x7 : Measurement x=5mm, y=5mm, z=5mm  
Power Drift-Start : 0.026 W/kg  
Power Drift-Finish : 0.026 W/kg  
Power Drift (%) : 1.417


## Tissue Data

Type : BODY  
Frequency : 835.00 MHz  
Epsilon : 55.57 F/m  
Sigma : 1.00 S/m  
Density : 1000.00 kg/cu. m

## Probe Data

Serial No. : 273  
Frequency : 835.00 MHz  
Duty Cycle Factor : 4  
Conversion Factor : 6.7  
Probe Sensitivity : 1.20 1.20 1.20  $\mu$ V/(V/m)<sup>2</sup>  
Compression Point : 95.00 mV  
Offset : 1.56 mm

1 gram SAR value : 0.345 W/kg  
10 gram SAR value : 0.206 W/kg  
Area Scan Peak SAR : 0.340 W/kg  
Zoom Scan Peak SAR : 0.590 W/kg

**Plot 10#**

**Test Laboratory: Bay Area Compliance Lab Corp. (Shenzhen)****Left Head Cheek (1900 MHz Low Channel)****Measurement Data**

Test mode : GSM  
Crest Factor : 8  
Scan Type : Complete  
Area Scan : 13x9x1: Measurement x=10mm, y=10mm, z=4mm  
Zoom Scan : 7x7x7: Measurement x=5mm, y=5mm, z=5mm  
Power Drift-Start : 0.043 W/kg  
Power Drift-Finish : 0.043 W/kg  
Power Drift (%) : 2.156


**Tissue Data**

Type : HEAD  
Frequency : 1900.00 MHz  
Epsilon : 39.54 F/m  
Sigma : 1.45 S/m  
Density : 1000.00 kg/cu. m

**Probe Data**

Serial No. : 273  
Frequency : 1900.00 MHz  
Duty Cycle Factor : 8  
Conversion Factor : 5.25  
Probe Sensitivity : 1.20 1.20 1.20  $\mu$ V/(V/m)<sup>2</sup>  
Compression Point : 95.00 mV  
Offset : 1.56 mm

1 gram SAR value : 0.492 W/kg  
10 gram SAR value : 0.257 W/kg  
Area Scan Peak SAR : 0.590 W/kg  
Zoom Scan Peak SAR : 0.980 W/kg

**Plot 11#**

**Test Laboratory: Bay Area Compliance Lab Corp. (Shenzhen)****Left Head Cheek (1900 MHz Middle Channel)****Measurement Data**

Test mode : GSM  
Crest Factor : 8  
Scan Type : Complete  
Area Scan : 13x9x1: Measurement x=10mm, y=10mm, z=4mm  
Zoom Scan : 7x7x7: Measurement x=5mm, y=5mm, z=5mm  
Power Drift-Start : 0.028 W/kg  
Power Drift-Finish : 0.028 W/kg  
Power Drift (%) : 2.073


**Tissue Data**

Type : HEAD  
Frequency : 1900.00 MHz  
Epsilon : 39.54 F/m  
Sigma : 1.45 S/m  
Density : 1000.00 kg/cu. m

**Probe Data**

Serial No. : 273  
Frequency : 1900.00 MHz  
Duty Cycle Factor : 8  
Conversion Factor : 5.25  
Probe Sensitivity : 1.20 1.20 1.20  $\mu$ V/(V/m)<sup>2</sup>  
Compression Point : 95.00 mV  
Offset : 1.56 mm

1 gram SAR value : 0.490 W/kg  
10 gram SAR value : 0.274 W/kg  
Area Scan Peak SAR : 0.623 W/kg  
Zoom Scan Peak SAR : 1.851 W/kg

**Plot 12#**

**Test Laboratory: Bay Area Compliance Lab Corp. (Shenzhen)****Left Head Cheek (1900 MHz High Channel)****Measurement Data**

Test mode : GSM  
Crest Factor : 8  
Scan Type : Complete  
Area Scan : 13x9x1: Measurement x=10mm, y=10mm, z=4mm  
Zoom Scan : 7x7x7: Measurement x=5mm, y=5mm, z=5mm  
Power Drift-Start : 0.024 W/kg  
Power Drift-Finish : 0.024 W/kg  
Power Drift (%) : 1.514


**Tissue Data**

Type : HEAD  
Frequency : 1900.00 MHz  
Epsilon : 39.54 F/m  
Sigma : 1.45 S/m  
Density : 1000.00 kg/cu. m

**Probe Data**

Serial No. : 273  
Frequency : 1900.00 MHz  
Duty Cycle Factor : 8  
Conversion Factor : 5.25  
Probe Sensitivity : 1.20 1.20 1.20  $\mu$ V/(V/m)<sup>2</sup>  
Compression Point : 95.00 mV  
Offset : 1.56 mm

1 gram SAR value : 0.483 W/kg  
10 gram SAR value : 0.219 W/kg  
Area Scan Peak SAR : 0.586 W/kg  
Zoom Scan Peak SAR : 0.930 W/kg

**Plot 13#**

**Test Laboratory: Bay Area Compliance Lab Corp. (Shenzhen)****Left Head Tilt (1900 MHz Low Channel)****Measurement Data**

Test mode : GSM  
 Crest Factor : 8  
 Scan Type : Complete  
 Area Scan : 13x9x1 : Measurement x=10mm, y=10mm, z=4mm  
 Zoom Scan : 7x7x7 : Measurement x=5mm, y=5mm, z=5mm  
 Power Drift-Start : 0.018 W/kg  
 Power Drift-Finish : 0.018 W/kg  
 Power Drift (%) : 1.664


**Tissue Data**

Type : HEAD  
 Frequency : 1900.00 MHz  
 Epsilon : 39.54 F/m  
 Sigma : 1.45 S/m  
 Density : 1000.00 kg/cu. m

**Probe Data**

Serial No. : 273  
 Frequency : 1900.00 MHz  
 Duty Cycle Factor : 8  
 Conversion Factor : 5.25  
 Probe Sensitivity : 1.20 1.20 1.20  $\mu$ V/(V/m)<sup>2</sup>  
 Compression Point : 95.00 mV  
 Offset : 1.56 mm

1 gram SAR value : 0.139 W/kg  
 10 gram SAR value : 0.053 W/kg  
 Area Scan Peak SAR : 0.232 W/kg  
 Zoom Scan Peak SAR : 0.460 W/kg

**Plot 14#**

**Test Laboratory: Bay Area Compliance Lab Corp. (Shenzhen)****Right Head Cheek (1900 MHz Low Channel)****Measurement Data**

Test mode : GSM  
Crest Factor : 8  
Scan Type : Complete  
Area Scan : 13x9x1 : Measurement x=10mm, y=10mm, z=4mm  
Zoom Scan : 7x7x7 : Measurement x=5mm, y=5mm, z=5mm  
Power Drift-Start : 0.011 W/kg  
Power Drift-Finish : 0.011 W/kg  
Power Drift (%) : 1.250


**Tissue Data**

Type : HEAD  
Frequency : 1900.00 MHz  
Epsilon : 39.54 F/m  
Sigma : 1.45 S/m  
Density : 1000.00 kg/cu. m

**Probe Data**

Serial No. : 273  
Frequency : 1900.00 MHz  
Duty Cycle Factor : 8  
Conversion Factor : 5.25  
Probe Sensitivity : 1.20 1.20 1.20  $\mu$ V/(V/m)<sup>2</sup>  
Compression Point : 95.00 mV  
Offset : 1.56 mm

1 gram SAR value : 0.484 W/kg  
10 gram SAR value : 0.227 W/kg  
Area Scan Peak SAR : 0.489 W/kg  
Zoom Scan Peak SAR : 0.890 W/kg

**Plot 15#**

**Test Laboratory: Bay Area Compliance Lab Corp. (Shenzhen)****Right Head Tilt (1900 MHz Low Channel)****Measurement Data**

Test mode : GSM  
Crest Factor : 8  
Scan Type : Complete  
Area Scan : 13x9x1 : Measurement x=10mm, y=10mm, z=4mm  
Zoom Scan : 7x7x7 : Measurement x=5mm, y=5mm, z=5mm  
Power Drift-Start : 0.009 W/kg  
Power Drift-Finish : 0.009 W/kg  
Power Drift (%) : 2.542


**Tissue Data**

Type : HEAD  
Frequency : 1900.00 MHz  
Epsilon : 39.54 F/m  
Sigma : 1.45 S/m  
Density : 1000.00 kg/cu. m

**Probe Data**

Serial No. : 273  
Frequency : 1900.00 MHz  
Duty Cycle Factor : 8  
Conversion Factor : 5.25  
Probe Sensitivity : 1.20 1.20 1.20  $\mu$ V/(V/m)2  
Compression Point : 95.00 mV  
Offset : 1.56 mm

1 gram SAR value : 0.129 W/kg  
10 gram SAR value : 0.074 W/kg  
Area Scan Peak SAR : 0.130 W/kg  
Zoom Scan Peak SAR : 0.320 W/kg

**Plot 16#**

**Test Laboratory: Bay Area Compliance Lab Corp. (Shenzhen)****Body- worn Back (1900 MHz Low Channel)****Measurement Data**

Test mode : GSM  
Crest Factor : 8  
Scan Type : Complete  
Area Scan : 9x13x1: Measurement x=10mm, y=10mm, z=4mm  
Zoom Scan : 7x7x7 : Measurement x=5mm, y=5mm, z=5mm  
Power Drift-Start : 0.023 W/kg  
Power Drift-Finish : 0.024 W/kg  
Power Drift (%) : 2.848


**Tissue Data**

Type : BODY  
Frequency : 1900.00 MHz  
Epsilon : 53.58 F/m  
Sigma : 1.54 S/m  
Density : 1000.00 kg/cu. m

**Probe Data**

Serial No. : 273  
Frequency : 1900.00 MHz  
Duty Cycle Factor : 8  
Conversion Factor : 5.15  
Probe Sensitivity : 1.20 1.20 1.20  $\mu$ V/(V/m)2  
Compression Point : 95.00 mV  
Offset : 1.56 mm

1 gram SAR value : 0.110 W/kg  
10 gram SAR value : 0.063 W/kg  
Area Scan Peak SAR : 0.133 W/kg  
Zoom Scan Peak SAR : 0.350 W/kg

**Plot 17#**

**Test Laboratory: Bay Area Compliance Lab Corp. (Shenzhen)****Body- worn Back (1900 MHz Low Channel)****Measurement Data**

Test mode : GPRS  
Crest Factor : 4  
Scan Type : Complete  
Area Scan : 9x13x1: Measurement x=10mm, y=10mm, z=4mm  
Zoom Scan : 7x7x7 : Measurement x=5mm, y=5mm, z=5mm  
Power Drift-Start : 0.024 W/kg  
Power Drift-Finish : 0.025 W/kg  
Power Drift (%) : 1.995


**Tissue Data**

Type : BODY  
Frequency : 1900.00 MHz  
Epsilon : 53.58 F/m  
Sigma : 1.54 S/m  
Density : 1000.00 kg/cu. m

**Probe Data**

Serial No. : 273  
Frequency : 1900.00 MHz  
Duty Cycle Factor : 4  
Conversion Factor : 5.15  
Probe Sensitivity : 1.20 1.20 1.20  $\mu$ V/(V/m)<sup>2</sup>  
Compression Point : 95.00 mV  
Offset : 1.56 mm

1 gram SAR value : 0.203 W/kg  
10 gram SAR value : 0.092 W/kg  
Area Scan Peak SAR : 0.175 W/kg  
Zoom Scan Peak SAR : 0.420 W/kg

**Plot 18#**

**Test Laboratory: Bay Area Compliance Lab Corp. (Shenzhen)****Body- worn Back (1900 MHz Middle Channel)****Measurement Data**

Test mode : GPRS  
Crest Factor : 4  
Scan Type : Complete  
Area Scan : 9x13x1: Measurement x=10mm, y=10mm, z=4mm  
Zoom Scan : 7x7x7 : Measurement x=5mm, y=5mm, z=5mm  
Power Drift-Start : 0.019 W/kg  
Power Drift-Finish : 0.019 W/kg  
Power Drift (%) : -1.358


**Tissue Data**

Type : BODY  
Frequency : 1900.00 MHz  
Epsilon : 53.58 F/m  
Sigma : 1.54 S/m  
Density : 1000.00 kg/cu. m

**Probe Data**

Serial No. : 273  
Frequency : 1900.00 MHz  
Duty Cycle Factor : 4  
Conversion Factor : 5.15  
Probe Sensitivity : 1.20 1.20 1.20  $\mu$ V/(V/m)<sup>2</sup>  
Compression Point : 95.00 mV  
Offset : 1.56 mm

1 gram SAR value : 0.232 W/kg  
10 gram SAR value : 0.129 W/kg  
Area Scan Peak SAR : 0.315 W/kg  
Zoom Scan Peak SAR : 0.540 W/kg

**Plot 19#**

**Test Laboratory: Bay Area Compliance Lab Corp. (Shenzhen)****Body- worn Back (1900 MHz High Channel)**

## Measurement Data

Test mode : GPRS  
Crest Factor : 4  
Scan Type : Complete  
Area Scan : 9x13x1: Measurement x=10mm, y=10mm, z=4mm  
Zoom Scan : 7x7x7 : Measurement x=5mm, y=5mm, z=5mm  
Power Drift-Start : 0.021 W/kg  
Power Drift-Finish : 0.022 W/kg  
Power Drift (%) : 1.853


## Tissue Data

Type : BODY  
Frequency : 1900.00 MHz  
Epsilon : 53.58 F/m  
Sigma : 1.54 S/m  
Density : 1000.00 kg/cu. m

## Probe Data

Serial No. : 273  
Frequency : 1900.00 MHz  
Duty Cycle Factor : 4  
Conversion Factor : 5.15  
Probe Sensitivity : 1.20 1.20 1.20  $\mu$ V/(V/m)<sup>2</sup>  
Compression Point : 95.00 mV  
Offset : 1.56 mm


1 gram SAR value : 0.182 W/kg  
10 gram SAR value : 0.084 W/kg  
Area Scan Peak SAR : 0.181 W/kg  
Zoom Scan Peak SAR : 0.370 W/kg

**Plot 20#**

## APPENDIX F – CONDUCTED OUTPUT POWER MEASUREMENT

### Test Block Diagram and Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.



### Test Equipment List and Details

Manufacturer	Equipment Description	Model NO.	Serial No.	Calibration Date
Rohde & Schwarz	Communication Tester	CMU200	1100.0008.02	2010-06-28
Rohde & Schwarz	Spectrum Analyzer	FSEM30	849720/019	2010-07-05

### Test Results

GSM:

Band	Frequency (MHz)	Conducted Output Power (GSM Mode)	
		(dBm)	(Watt)
Cellular	824.2	31.6	1.445
	836.6	31.6	1.445
	848.8	31.8	1.513
PCS	1850.2	28.9	0.776
	1880.0	28.8	0.758
	1909.8	28.8	0.758

GPRS:

Band	Channel No	Frequency (MHz)	RF Output Power (dBm)			
			1 slot	2 slots	3 slots	4 slots
GSM850	128	824.2	31.72	30.99	Not support	Not support
	190	836.6	31.74	31.01	Not support	Not support
	251	848.8	31.82	31.10	Not support	Not support
PCS1900	512	1850.2	28.71	28.24	Not support	Not support
	661	1880.0	28.68	28.26	Not support	Not support
	810	1909.8	28.67	28.12	Not support	Not support

For SAR, the time based average power is relevant, the difference in between depends on the duty cycle of the TDMA signal.


Number of Time slot	1	2	3	4
Duty Cycle	1:8	1:4	1:2.66	1:2
Time based Ave. power compared to slotted Ave. power	-9 dB	-6 dB	-4.25 dB	-3 dB
Crest Factor	8	4	2.66	2

The time based average power


Band	Channel No	Frequency (MHz)	Time based average Power (dBm)	
			1 slot	2 slots
GSM850	128	824.2	22.72	24.99
	190	836.6	22.74	25.01
	251	848.8	22.82	25.10
PCS1900	512	1850.2	19.71	22.24
	661	1880.0	19.68	22.26
	810	1909.8	19.67	22.12

**APPENDIX G – EUT TEST POSITION PHOTOS**

**Liquid Depth  $\geq$  15 cm**




**Body-worn Back Setup Photo**




**Left Head Touch Setup Photo**



**Left Head Tilt Setup Photo**



**Right Head Touch Setup Photo**



**Right Head Tilt Setup Photo**



**APPENDIX H – EUT PHOTOS****EUT – Front Side View****EUT – Back Side View**

## **EUT- Battery Uncover View**



## **EUT – Right Side View**



**EUT – Left Side View****EUT- Headset View**

## APPENDIX I - INFORMATIVE REFERENCES

[1] Federal Communications Commission, \Report and order: Guidelines for evaluating the environmental effects of radiofrequency radiation", Tech. Rep. FCC 96-326, FCC, Washington, D.C. 20554, 1996.

[2] David L. Means Kwok Chan, Robert F. Cleveland, \Evaluating compliance with FCC guidelines for human exposure to radiofrequency electromagnetic fields", Tech. Rep., Federal Communication Commission, O\_ce of Engineering & Technology, Washington, DC, 1997.

[3] Thomas Schmid, Oliver Egger, and Niels Kuster, \Automated E-eld scanning system for dosimetric assessments", IEEE Transactions on Microwave Theory and Techniques, vol. 44, pp. 105{113, Jan. 1996.

[4] Niels Kuster, Ralph Kastle, and Thomas Schmid, \Dosimetric evaluation of mobile communications equipment with known precision", IEICE Transactions on Communications, vol. E80-B, no. 5, pp. 645{652, May 1997.

[5] CENELEC, \Considerations for evaluating of human exposure to electromagnetic fields (EMFs) from mobile telecommunication equipment (MTE) in the frequency range 30MHz - 6GHz", Tech. Rep., CENELEC, European Committee for Electrotechnical Standardization, Brussels, 1997.

[6] ANSI, ANSI/IEEE C95.1-1992: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz, The Institute of Electrical and Electronics Engineers, Inc., New York, NY 10017, 1992.

[7] Katja Pokovic, Thomas Schmid, and Niels Kuster, \Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies", in ICECOM \_ 97, Dubrovnik, October 15{17, 1997, pp. 120-24.

[8] Katja Pokovic, Thomas Schmid, and Niels Kuster, \E-field probe with improved isotropy in brain simulating liquids", in Proceedings of the ELMAR, Zadar, Croatia, 23{25 June, 1996, pp. 172-175.

[9] Volker Hombach, Klaus Meier, Michael Burkhardt, Eberhard K. uhn, and Niels Kuster, \The dependence of EM energy absorption upon human head modeling at 900 MHz", IEEE Transactions on Microwave Theory and Techniques, vol. 44, no. 10, pp. 1865-1873, Oct. 1996.

[10] Klaus Meier, Ralf Kastle, Volker Hombach, Roger Tay, and Niels Kuster, \The dependence of EM energy absorption upon human head modeling at 1800 MHz", IEEE Transactions on Microwave Theory and Techniques, Oct. 1997, in press.

[11] W. Gander, Computermathematik, Birkhaeuser, Basel, 1992.

[12] W. H. Press, S. A. Teukolsky, W. T. Vetterling, and B. P. Flannery, Numerical Recepies in C, The Art of Scientific Computing, Second Edition, Cambridge University Press, 1992. Dosimetric Evaluation of Sample device, month 1998 9

[13] NIS81 NAMAS, \The treatment of uncertainty in EMC measurement", Tech. Rep., NAMAS Executive, National Physical Laboratory, Teddington, Middlesex, England, 1994.

[14] Barry N. Taylor and Christ E. Kuyatt, \Guidelines for evaluating and expressing the uncertainty of NIST measurement results", Tech. Rep., National Institute of Standards and Technology, 1994. Dosimetric Evaluation of Sample device, month 1998 10.

\*\*\*\*\* END OF REPORT \*\*\*\*\*