Page 1 of 42

FCC Test Report

Report No.: AGC00021130301F2B

FCC ID : ZG8BSH558

APPLICATION PURPOSE : Original Equipment

PRODUCT DESIGNATION: Bluetooth Stereo Headset

BRAND NAME : N/A

MODEL NAME : BSH558

CLIENT : LANYA ELECTRONIC Co., Ltd.

DATE OF ISSUE : Mar.26,2013

STANDARD(S) : FCC Part 15 Rules

REPORT VERSION: V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd

CAUTION:

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.

Page 2 of 42

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Mar.26,2013	Valid	Original Report

TABLE OF CONTENTS

1. VERIFICATION OF CONFORMITY	5
2. GENERAL INFORMATION	6
2.1. PRODUCT DESCRIPTION	6
2.2. TEST STANDARDS	6
2.3. RELATED SUBMITTAL(S)/GRANT(S)	6
2.4. TEST METHODOLOGY	6
2.5. SPECIAL ACCESSORIES	7
2.6. EQUIPMENT MODIFICATIONS	7
3. MEASUREMENT UNCERTAINTY	8
4. DESCRIPTION OF TEST MODES	
5. SYSTEM TEST CONFIGURATION	9
5.1. CONFIGURATION OF EUT SYSTEM	9
5.2. EQUIPMENT USED IN EUT SYSTEM	9
5.3. SUMMARY OF TEST RESULTS	9
6. TEST FACILITY	10
7. §15.203-ANTENNA REQUIREMENT	11
7.1. STANDARD APPLICABLE	11
7.2. TEST RESULT	11
8. §15.209, §15.249 RADIATED EMISSION	12
8.1. MEASUREMENT UNCERTAINTY	12
8.2. STANDARD APPLICABLE	12
8.3. TEST PROCEDURE	13
8.4. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	13
8.5. TEST RESULTS	15
9. §15.249 EMISSION BANDWIDTH	28

9.1. STANDARD APPLICABLE	28
9.2. TEST PROCEDURE	28
9.3. SUMMARY OF TEST RESULTS/PLOTS	28
10. FCC LINE CONDUCTED EMISSION TEST	30
10.1. LIMITS	30
10.2. TEST SETUP	30
10.3. PRELIMINARY PROCEDURE	31
10.4. FINAL TEST PROCEDURE	31
10.5. TEST RESULT OF POWER LINE	32
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	34
APPENDIX B: PHOTOGRAPHS OF EUT	36

Page 5 of 42

1. VERIFICATION OF CONFORMITY

Applicant	LANYA ELECTRONIC Co., Ltd.		
Address	3-5F, Workshop of 6,Lijincheng Science & Technology Industrial Area, The East Road of Industrial Area, longhua Street, Bao'an District, Shenzhen City, Guangdong Province, P.R.China		
Manufacturer LANYA ELECTRONIC CO., Ltd.			
Address	3-5F, Workshop of 6,Lijincheng Science & Technology Industrial Area, The East Road of Industrial Area, longhua Street, Bao'an District, Shenzhen City, Guangdong Province, P.R.China		
Product Designation	Bluetooth Stereo Headset		
Brand Name	N/A		
Test Model	BSH558		
Date of test	Mar.19,2013 to Mar.26,2013		
Deviation	None		
Condition of Test Sample	Normal		
Report Template	AGCRT-US-BLE/RF (2013-03-01)		

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2003) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC Rules Part 15.249.

Wall Huang Mar.26,2013

Checked By

Forrest Lei Mar.26,2013

Authorized By

Solger Zhang Mar.26,2013

Page 6 of 42

2. GENERAL INFORMATION

2.1. PRODUCT DESCRIPTION

The EUT is a Bluetooth Stereo Headset designed as a "Communication Device". It is designed by way of utilizing the FHSS technology to achieve the system operation.

A major technical description of EUT is described as following

rimajor toominosi doodhiption or zor to doodhibad do follonning				
Operation Frequency	2.402 GHz to 2.480GHz			
RF Output Power	2.53dBm			
Bluetooth Version:	V 4.0			
Modulation	GFSK			
Number of channels	40			
Antenna Designation	Integrated Antenna			
Antenna Gain	2.0dBi			
Power Supply	DC3.7V by Built-in Li-ion Battery			
Note:BT is active when charging. The USB port only used for charging and can't be used to transfer data with PC				

Note:BT is active when charging. The USB port only used for charging and can't be used to transfer data with PC

2.2. TEST STANDARDS

The following report of is prepared on behalf of the Attestation of Global Compliance Co., Ltd. in accordance with FCC Part 15, Subpart C, and section 15.249, 15.203 and 15.209 of the Federal Communication Commission rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.249, 15.203 and 15.209 of the Federal Communication Commission rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission/immunity, should be checked to ensure compliance has been maintained.

2.3. RELATED SUBMITTAL(S)/GRANT(S)

This submittal(s) (test report) is intended for **FCC ID: ZG8BSH558** filling to comply with Section 15.249 of the FCC Part 15, Subpart C Rules.

2.4. TEST METHODOLOGY

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions. The EUT was tested in all three orthogonal planes and the worse case was showed.

Page 7 of 42

2.5. SPECIAL ACCESSORIES

Refer to section 2.2.

2.6. EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

Page 8 of 42

3. MEASUREMENT UNCERTAINTY

Conducted measurement: +/- 2.75dB Radiated measurement: +/- 3.2dB

4. DESCRIPTION OF TEST MODES

TEST MODE DESCRIPTION				
NO.	TEST MODE DESCRIPTION	WORST		
1	Low channel TX			
2	Middle channel TX			
3	High channel TX			
4	Normal Hopping	V		

Note:


- 1. V means EMI worst mode.
- 2. All the test modes can be supply by Built-in Li-ion battery, only the result of the worst case was recorded in the report if no any records.
- 3. For Radiated Emission, 3axis were chosen for testing for each applicable mode.

Page 9 of 42

5. SYSTEM TEST CONFIGURATION

5.1. CONFIGURATION OF EUT SYSTEM

Configuration: Normal Operating



Configuration: Continuous TX



5.2. EQUIPMENT USED IN EUT SYSTEM

Item	Equipment	Mfr/Brand	Model/Type No.	Remark
1	Bluetooth Stereo Headset	N/A	BSH558	EUT
2	PC	DELL	INSPIRON	A.E

5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.203	Antenna Requirement	Compliant
§15.207	Power Line Conducted Emission	Compliant
§15.209	General Requirement	Compliant
§15.249	Emission Bandwidth	Compliant
§15.249	Spurious Emission	Compliant

Page 10 of 42

6. TEST FACILITY

Site	Attestation of Global Compliance (Shenzhen) Co., Ltd		
Location	2/F., Building 2, No.1-No.4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang, Bao'an District, Shenzhen, Guangdong, China		
Description	The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2003.		

ALL TEST EQUIPMENT LIST

Description	Manufacturer	Model	S/N	Cal. Date	Cal. Due
PSA SERIES SPECTRUM ANALYZER	AGILENT	E4440A	US41421290	07/18/2012	07/17/2013
BICONICAL ANTENNA	A.H.	SAS-521-4	128	06/08/2012	06/07/2013
LOOP ANTENNA	R&S	HM525	N/A	07/18/2012	07/17/2013
HORN ANTENNA	EM	EM-AH-10180	N/A	07/18/2012	07/17/2013
HORN ANTENNA	A.H. Systems Inc.	SAS-574	1	07/18/2012	07/17/2013
AMPLIFIER	EM	EM30180	0607030	02/28/2013	02/27/2014
COAXIAL CABLE	SCHWARZBECK	AK9513	9513-10	07/18/2012	07/17/2013
POSITIONING CONTROLLER	MF	MF-7802	MF780208147	07/18/2012	07/17/2013
RECEIVER ANTENNA	ETS	2175	57337	07/18/2012	07/17/2013
COAXIAL CABLE	ETS	SUCOFLEX 104	25498514	07/18/2012	07/17/2013

Page 11 of 42

7. §15.203-ANTENNA REQUIREMENT

7.1. STANDARD APPLICABLE

According to FCC 15.203, An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

7.2. TEST RESULT

This product has a permanent antenna, fulfill the requirement of this section.

Page 12 of 42

8. §15.209, §15.249 RADIATED EMISSION

8.1. MEASUREMENT UNCERTAINTY

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement is +/-3.2 dB.

8.2. STANDARD APPLICABLE

Except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental Field Strength (mV/m)	Field Strength of Harmonics (µ V/m)
902-928MHz	50	500
2400-2483.5MHz	50	500
5725-5875MHz	50	500
24.0-24.25GHz	250	2500

Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency	Field Strength	Measurement Distance
(MHz)	(μ V/m)	(m)
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500*	3

In the above emission table, the tighter limit applies at the band edges.


Frequency (MHz)	Field Strength (Field Strength (dB μ V/m at 3-meter)		
30-88	100	40		
88-216	150	43.5		
216-960	200	46		
Above 960	500	54		

Page 13 of 42


8.3. TEST PROCEDURE

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.249 and FCC Part 15.209 Limit

8.4. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) BELOW 30MHz:




30MHz-1000MHz:



Report No.: AGC00021130301F2B Page 14 of 42

ABOVE 1000MHz:



Page 15 of 42

8.5. TEST RESULTS

8.5.1. TEST RESULT OF RADIATED EMISSION TEST (9KHZ-30MHZ)


Freq. (MHz)	Level (dB uV)	Over Limit (dB)	Limit Line (dB uV)	Remark
		1		Seen to Note

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be report.

Page 16 of 42

8.5.2. TEST RESULT

RADIATED EMISSION TEST (30MHZ-1GHZ)-LOW CHANNEL-HORIZONTAL



Site: site #1 Polarization: Horizontal Temperature: 26
Limit: FCC Class B 3M Radiation Power: Humidity: 60 %

EUT: Bluetooth Stereo Headset Distance: 3M

M/N: BSH558


Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		60.7167	24.35	4.06	28.41	40.00	-11.59	peak			
2		144.7832	17.86	12.90	30.76	43.50	-12.74	peak			
3		270.8833	17.69	17.22	34.91	46.00	-11.09	peak			
4	*	435.7832	15.75	21.26	37.01	46.00	-8.99	peak			
5		513.3832	12.92	21.17	34.09	46.00	-11.91	peak			
6		838.3333	0.62	31.08	31.70	46.00	-14.30	peak			

Page 17 of 42

RADIATED EMISSION TEST (30MHZ-1GHZ)-LOW CHANNEL -VERTICAL



Site: site #1 Limit: FCC Class B 3M Radiation

EUT: Bluetooth Stereo Headset

M/N: BSH558

Mode: Low Channel TX

Note:

Polarization:	Vertical	Temperature: 26
Power:		Humidity: 60 %

Distance: 3M


No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		199.7500	25.74	8.23	33.97	43.50	-9.53	peak			
2		240.1666	18.76	14.23	32.99	46.00	-13.01	peak			
3	*	552.1833	15.07	23.79	38.86	46.00	-7.14	peak			
4		621.7000	9.93	25.03	34.96	46.00	-11.04	peak			
5		679.8999	7.41	25.82	33.23	46.00	-12.77	peak			
6		799.5333	5.53	28.13	33.66	46.00	-12.34	peak			

Temperature: 26

Humidity: 60 %

Page 18 of 42

RADIATED EMISSION TEST (30MHZ-1GHZ)-MIDDLE CHANNEL-HORIZONTAL



Polarization: Horizontal

Site: site #1 Limit: FCC Class B 3M Radiation

EUT: Bluetooth Stereo Headset

M/N: BSH558

Mode: Middle Channel TX

Note:


Distance: 3M		

N	o.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		-	MHz	dBu∀	dB/m	dBuV/m	dBu∀/m	dB		cm	degree	
	1		80.1166	17.63	11.92	29.55	40.00	-10.45	peak			
	2		240.1666	21.49	12.18	33.67	46.00	-12.33	peak			
Ţ.	3		270.8833	17.69	17.22	34.91	46.00	-11.09	peak			
-	4	*	435.7832	16.75	21.26	38.01	46.00	-7.99	peak			
	5		506.9166	14.26	22.04	36.30	46.00	-9.70	peak			
-	6		767.2000	5.14	27.76	32.90	46.00	-13.10	peak			

Power:

Page 19 of 42

RADIATED EMISSION TEST (30MHZ-1GHZ)- MIDDLE CHANNEL -VERTICAL



Site: site #1 Limit: FCC Clas

EUT: Bluetooth

M/N: BSH558

Mode: Middle Channel TX


Note:

	Polarization: Ve	ertical	Temperature:	26
ass B 3M Radiation	Power:		Humidity: 60	%
th Stereo Headset	Distance: 3M			

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		60.7167	23.35	4.06	27.41	40.00	-12.59	peak			
2		199.7500	25.51	7.21	32.72	43.50	-10.78	peak			
3	*	435.7832	16.25	21.26	37.51	46.00	-8.49	peak			
4		463.2667	15.48	21.54	37.02	46.00	-8.98	peak			
5		560.2667	12.53	24.02	36.55	46.00	-9.45	peak		·	
6		846.4166	3.17	30.63	33.80	46.00	-12.20	peak		·	

Page 20 of 42

RADIATED EMISSION TEST (30MHZ-1GHZ)-HIGH CHANNEL-HORIZONTAL



Site: site #1 Limit: FCC Class B 3M Radiation

EUT: Bluetooth Stereo Headset

M/N: BSH558

Mode: High Channel TX

Note:


Polarization:	Horizontai	remperature: 26	
Power:		Humidity: 60 %	

Distance: 3M

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		80.1166	19.63	11.92	31.55	40.00	-8.45	peak			
2		270.8833	17.19	17.22	34.41	46.00	-11.59	peak			
3		435.7832	17.75	21.26	39.01	46.00	-6.99	peak			
4	*	463.2667	17.98	21.54	39.52	46.00	-6.48	peak			
5		560.2667	12.53	24.02	36.55	46.00	-9.45	peak			
6		843.1833	3.99	30.99	34.98	46.00	-11.02	peak			

Page 21 of 42

RADIATED EMISSION TEST (30MHZ-1GHZ)-HIGH CHANNEL -VERTICAL



Site: site #1 Limit: FCC Class B 3M Radiation

EUT: Bluetooth Stereo Headset

M/N: BSH558

Mode: High Channel TX

Note:

Polarization:	Vertical	Temperature:	26
Power:		Humidity: 60	%


Distance: 3M

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu√/m	dBu∀/m	dB		cm	degree	
1		139.9333	18.48	11.56	30.04	43.50	-13.46	peak			
2		240.1666	19.76	14.23	33.99	46.00	-12.01	peak			
3	*	544.1000	14.92	23.56	38.48	46.00	-7.52	peak			
4		621.7000	10.43	25.03	35.46	46.00	-10.54	peak			
5		679.8999	9.41	25.82	35.23	46.00	-10.77	peak			
6		799.5333	6.03	28.13	34.16	46.00	-11.84	peak			

Page 22 of 42

8.5.3TEST RESULT

RADIATED EMISSION TEST(ABOVE 1GHZ)-LOW CHANNEL-HORIZONTAL



Site: site #1 Polarization: Horizontal Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: Bluetooth Stereo Headset Distance: 3m

M/N: BSH558

Mode: Low Channel TX

Note:


No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Ov er	Detector	Antenna Height	Table Degree	Comment
		MHz	aBuV	dB/m	dBuV/m	dBuV/m	dB		стп	degree	
1	*	2402.056	75.13	0.00	75.13	74.00	1.13	peak			
2		4000.000	44.60	0.00	44.60	74.00	-29.40	peak			
3		5091.667	46.99	0.00	46.99	74.00	-27.01	peak			

RESULT: PASS

Note : Marker2 is fundamental frequency and the Average result is 45.42 dBuV/m.

Page 23 of 42

RADIATED EMISSION TEST(ABOVE 1GHZ)-LOW CHANNEL-VERTICAL



Site: site #1 Polarization: Vertical Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: Bluetooth Stereo Headset Distance: 3m

M/N: BSH558

Mode: Low Channel TX

Note:


No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Ov er	Detector	Antenna Height		Comment
		MHz	dBuV	dB/m	dBuV/m	dBu∀/m	dB		cm	degree	
1	*	2402.023	74.13	0.00	74.13	74.00	0.13	peak			
2		4291.667	47.28	0.00	47.28	74.00	-26.72	peak			
3		5200.000	48.01	0.00	48.01	74.00	-25.99	peak			

RESULT: PASS

Note: Marker 2 is fundamental frequency and the Average result is 45.33dBuV/m. 6~25GHz at least have 20dB margin. No recording in the test report.

Page 24 of 42

RADIATED EMISSION TEST(ABOVE 1GHZ)-MIDDLE CHANNEL-HORIZONTAL



Site: site #1 Polarization: Horizontal Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: Bluetooth Stereo Headset Distance: 3m

M/N: BSH558

Mode: Middle Channel TX

Note:


No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2442.115	74.30	0.00	74.30	74.00	0.30	peak			
2		3883.333	43.36	0.00	43.36	74.00	-30.64	peak			
3		4716.667	42.64	0.00	42.64	74.00	-31.36	peak			

RESULT: PASS

Note: Marker 2 fundamental frequency and the Average result is 44.41dBuV/m.

Page 25 of 42

RADIATED EMISSION TEST(ABOVE 1GHZ)-MIDDLE CHANNEL-VERTICAL



Site: site #1 Polarization: Vertical Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: Bluetooth Stereo Headset Distance: 3m

M/N: BSH558

Mode: Middle Channel TX

Note:


No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Ov er	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dΒ		ст	degree	
1	*	2442.087	74.59	0.00	74.59	74.00	0.59	peak			
2		3791.667	40.81	0.00	40.81	74.00	-33.19	peak			
3		5550.000	43.96	0.00	43.96	74.00	-30.04	peak			

RESULT: PASS

Note: Marker 2 is the fundamental frequency and the Average result is 43.93dBuV/m.

Page 26 of 42

RADIATED EMISSION TEST(ABOVE 1GHZ)-HIGH CHANNEL-HORIZONTAL



Site: site #1 Polarization: *Horizontal* Temperature: 26 Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: Bluetooth Stereo Headset Distance: 3m

M/N: BSH558

Mode: High Channel TX

Note:


No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Ov er	Detector	Antenna Height	Table Degree	Comment
		MHz	aBuV	dB/m	dBuV/m	dBuV/m	dB		стп	degree	
1	*	2480.158	74.48	0.00	74.48	74.00	0.48	peak			
2		3550.000	45.07	0.00	45.07	74.00	-28.93	peak			
3		4866.667	45.63	0.00	45.63	74.00	-28.37	peak			

RESULT: PASS

Note: Marker 2 is the fundamental frequency and the Average result is 44.56dBuV/m.

Page 27 of 42

RADIATED EMISSION TEST(ABOVE 1GHZ)-HIGH CHANNEL-VERTICAL



Site: site #1 Polarization: Vertical Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: Bluetooth Stereo Headset Distance: 3m

M/N: BSH558

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Ov er	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dĐ		cm	degree	
1	*	2480.115	74.55	0.00	74.55	74.00	0.55	peak			
2		3983.333	42.48	0.00	42.48	74.00	-31.52	peak			
3		4650.000	41.80	0.00	41.80	74.00	-32.20	peak			

RESULT: PASS

Note: Marker 2 is the fundamental frequency and the Average result is 44.21dBuV/m.

Page 28 of 42

9. §15.249 EMISSION BANDWIDTH

9.1. STANDARD APPLICABLE

Note; for reporting purposes only.

9.2. TEST PROCEDURE

With the EUT's antenna attached, the EUT's 20dB Bandwidth power was received by the test antenna, which was connected to the spectrum analyzer with the START, and STOP frequencies set to the EUT's operation band.

9.3. SUMMARY OF TEST RESULTS/PLOTS


Channel	Emission Bandwidth (KHz)	Limit (KHz)
Low	1.186	
Middle	1.235	N/A
High	1.142	

Low Channel Test Result



Page 29 of 42

Middle Channel Test Result



High Channel Test Result



Report No.: AGC00021130301F2B Page 30 of 42

10. FCC LINE CONDUCTED EMISSION TEST


10.1. LIMITS

Francisco	Maximum RF	Line Voltage
Frequency	Q.P.(dBuV)	Average(dBuV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz

10.2. TEST SETUP



A: Powered through filter

Page 31 of 42

10.3. PRELIMINARY PROCEDURE

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.

- 2. Support equipment, if needed, was placed as per ANSI C63.4.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4. All support equipments received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received power by PC which received power by a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The following test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.


10.4. FINAL TEST PROCEDURE

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.

Page 32 of 42

10.5. TEST RESULT OF POWER LINE

Line Conducted Emission Test Line 1-L



Site: Conduction Phase: L1 Temperature: 26
Limit: FCC Class B Conduction(QP) Power: Humidity: 60 %

EUT: Bluetooth Stereo Headset

M/N: BSH558

Mode: Normal Hopping


Note:

No.	Freq.		ding_L (dBuV)		Correct Factor	Measurement (dBuV)						Margin (dB)		Comment
	(MHz)	Peak	QP	AVG	dB	Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1539	41.29		19.82	10.16	51.45		29.98	65.78	55.78	-14.33	-25.80	Р	
2	0.3457	36.96		20.42	10.31	47.27		30.73	59.06	49.06	-11.79	-18.33	Р	
3	0.4620	34.84		28.91	10.37	45.21		39.28	56.66	46.66	-11.45	-7.38	Р	
4	1.3020	32.53		21.61	10.38	42.91		31.99	56.00	46.00	-13.09	-14.01	Р	
5	2.1939	32.45		26.07	10.30	42.75		36.37	56.00	46.00	-13.25	-9.63	Р	
6	5.9298	32.48		16.85	10.28	42.76		27.13	60.00	50.00	-17.24	-22.87	Р	

Humidity: 60 %

Page 33 of 42

Line Conducted Emission Test Line 1-N



Limit: FCC Class B Conduction(QP)

EUT: Bluetooth Stereo Headset

M/N: BSH558

Mode: Normal Hopping

Note:

No.	Freq.	Rea	ding_L (dBuV)		Correct Factor	I			ı	nit uV)	Mai (d	rgin IB)	P/F	Comment
	(MHz)	Peak	QP	AVG	dB	Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1499	40.33		18.90	10.16	50.49		29.06	66.00	56.00	-15.51	-26.94	Р	
2	0.4138	33.59		25.10	10.34	43.93		35.44	57.57	47.57	-13.64	-12.13	Р	
3	1.2138	31.59		19.93	10.37	41.96		30.30	56.00	46.00	-14.04	-15.70	Р	
4	2.3100	32.18		24.65	10.35	42.53		35.00	56.00	46.00	-13.47	-11.00	Р	
5	4.5979	32.53		19.46	10.22	42.75		29.68	56.00	46.00	-13.25	-16.32	Р	
6	14.3537	30.50		20.42	10.12	40.62		30.54	60.00	50.00	-19.38	-19.46	Р	

Power:


Page 34 of 42

APPENDIX A: PHOTOGRAPHS OF TEST SETUP


FCC LINE CONDUCTED EMISSION TEST SETUP



FCC RADIATED EMISSION TEST SETUP



Report No.: AGC00021130301F2B Page 35 of 42



Page 36 of 42

APPENDIX B: PHOTOGRAPHS OF EUT

TOP VIEW OF EUT



BOTTOM VIEW OF EUT



Report No.: AGC00021130301F2B Page 37 of 42

FRONT VIEW OF EUT



BACK VIEW OF EUT



Page 38 of 42

LEFT VIEW OF EUT



RIGHT VIEW OF EUT



Page 39 of 42

OPEN VIEW OF EUT-1




OPEN VIEW OF EUT-2




Report No.: AGC00021130301F2B Page 40 of 42

INTERNAL VIEW OF EUT-1




INTERNAL VIEW OF EUT-2




Report No.: AGC00021130301F2B Page 41 of 42

INTERNAL VIEW OF EUT-3




INTERNAL VIEW OF EUT-4



Page 42 of 42

INTERNAL VIEW OF EUT-5



----END OF REPORT----