



Shenzhen Huatongwei International Inspection Co., Ltd.

Keji S,12th , Road, Hi-tech Industrial Park, Shenzhen, Guangdong, China

Phone:86-755-26748099

Fax:86-755-26748089

<http://www.szhtw.com.cn>



MPE TEST REPORT

FCC Per 47 CFR 2.1091(b)

Report Reference No. : TRE1211008102

FCC ID : ZG8BSK11

Compiled by

(position+printed name+signature) : File administrators Eric Zhang

Eric Zhang

Supervised by

(position+printed name+signature) : Test Engineer Tim Zhang

Tim Zhang

Approved by

(position+printed name+signature) : Manager Wenliang Li

Wenliang Li

Date of issue : Nov 30, 2012

Testing Laboratory Name : Shenzhen Huatongwei International Inspection Co., Ltd

Address : Keji Nan No.12 Road, Hi-tech Park, Shenzhen, China

Applicant's name : LANYA ELECTRONIC Co., Ltd.

Address : 3-5F, Workshop of 6,Lijincheng Science&Technology Industrial Area,The East Road of Industrial AREA, longhua Street, Bao'an District, Shenzhen City, Guangdong Province, P.R.China

Test specification:

Standard : FCC Per 47 CFR 2.1091(b)

TRF Originator : Shenzhen Huatongwei International Inspection CO., Ltd

Master TRF : Dated 2006-06

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description : Bluetooth Speaker

Trade Mark : /

Model/Type reference : BSK11

Modulation : GFSK

Listed Models : /

Result : **Positive**

TEST REPORT

Test Report No. :	TRE1211008102	Nov 30, 2012
		Date of issue

Equipment under Test : Bluetooth Speaker

Model /Type : BSK11

Listed Models : /

Applicant : **LANYA ELECTRONIC Co., Ltd.**

Address : 3-5F, Workshop of 6,Lijincheng Science&Technology Industrial Area,The East Road of Industrial AREA, longhua Street,Bao'an District,Shenzhen City,Guangdong Province,P.R.China

Manufacturer : **LANYA ELECTRONIC Co., Ltd.**

Address : 3-5F, Workshop of 6,Lijincheng Science&Technology Industrial Area,The East Road of Industrial AREA, longhua Street,Bao'an District,Shenzhen City,Guangdong Province,P.R.China

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

<u>1.</u>	<u>S U M M A R Y</u>	4
1.1.	EUT configuration	4
1.2.	Power supply system utilised	4
1.3.	Description of the test mode	4
1.4.	Related Submittal(s) / Grant (s)	4
1.5.	Modifications	4
1.6.	NOTE	5
<u>2.</u>	<u>T E S T E N V I R O N M E N T</u>	6
2.1.	Address of the test laboratory	6
2.2.	Environmental conditions	6
2.3.	Statement of the measurement uncertainty	6
<u>3.</u>	<u>M E T H O D O F M E A S U R E M E N T</u>	7
3.1.	Applicable Standard	7
3.2.	Limit	7
3.3.	MPE Calculation Method	7
<u>4.</u>	<u>C O N C L U S I O N</u>	8

1. SUMMARY

1.1. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- supplied by the manufacturer

- supplied by the lab

<input type="radio"/>	Power Cable	Length (m) :	/
		Shield :	/
		Detachable :	/
<input type="radio"/>	Multimeter	Manufacturer :	/
		Model No. :	/

1.2. Power supply system utilised

Power supply voltage	:	<input type="radio"/>	120V / 60 Hz	<input type="radio"/>	115V / 60Hz
		<input type="radio"/>	12 V DC	<input type="radio"/>	24 V DC
		<input checked="" type="radio"/>	Other (specified in blank below)		

DC 3.7V from battery

1.3. Description of the test mode

The EUT has been tested under typical operating condition. There are EDR (Enhanced Data Rate) and BDR (Basic Data Rate) mode. The Applicant provides communication tools software to control the EUT for staying in continuous transmitting and receiving mode for testing. There are 79 channels of EUT, and the test carried out at the lowest channel, middle channel and highest channel .

Frequency Range:	2400-2483.5MHz
Channel number:	79 channels
Modulation type:	Frequency Hopping Spread Spectrum
Antenna:	PCB Antenna
Bluetooth version:	V3.0

1.4. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for **FCC ID: ZG8BSK11** filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

1.5. Modifications

No modifications were implemented to meet testing criteria.

1.6. NOTE

1. The functions of the EUT are listed as below:

	Test Standards	Reference Report
Bluetooth	FCC Part 15 Subpart C (Section15.247)	TRE1211008101
Bluetooth	MPE report	TRE1211008102

2. The frequency bands used in this EUT are listed as follows:

Frequency Band(MHz)	2400-2483.5	5150-5350	5470-5725	5725-5850
EUT	√	—	—	—

2. TEST ENVIRONMENT

2.1. Address of the test laboratory

Shenzhen Huatongwei International Inspection Co., Ltd
Keji Nan No.12 Road, Hi-tech Park, Shenzhen, China
Phone: 86-755-26715686 Fax: 86-755-26748089

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 (2009) and CISPR Publication 22.

2.2. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

2.3. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 " and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Huatongwei laboratory is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.57 dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

3. Method of measurement

3.1. Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §RSS-102, Devices that have a radiating element normally operating at separation distances greater than 20 cm between the user and the device shall undergo an RF exposure evaluation. SAR evaluation may be performed in lieu of an RF exposure evaluation for devices operating below 6 GHz with a separation distance of greater than 20 cm between the user and the device.

According to §1.1310 and §2.1091 RF exposure is calculated.

OET Bulletin 65 Supplement C [June 2001]: Evaluating Compliance with FCC Guidelines for Human Exposure to Radio frequency Electromagnetic Fields

3.2. Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

3.3. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna is 1 dBi, the RF power density can be obtained.

TEST RESULTS**BDR mode**

Test Frequency (MHz)	Minimum Separation Distance	Output Power (dBm)	Output Power (mW)	Antenna Gain (Numeric)	Power Density Limit (mW/cm ²)	Power Density At 20 cm (mW/cm ²)	Test Results
2402	20.00	6.59	4.560	1.259	1.000	0.001142	Pass
2441	20.00	6.90	4.898	1.259	1.000	0.001227	Pass
2480	20.00	6.89	4.887	1.259	1.000	0.001225	Pass

EDR mode

Test Frequency (MHz)	Minimum Separation Distance	Output Power (dBm)	Output Power (mW)	Antenna Gain (Numeric)	Power Density Limit (mW/cm ²)	Power Density At 20 cm (mW/cm ²)	Test Results
2402	20.00	5.89	3.882	1.259	1.000	0.000973	Pass
2441	20.00	6.17	4.140	1.259	1.000	0.001037	Pass
2480	20.00	6.00	3.981	1.259	1.000	0.000998	Pass

4. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 (b) for the uncontrolled RF Exposure.

.....End of Report.....