



Product Name	Gateway
Model No.	HSC04-0
FCC ID	ZGXHSC04

Applicant	Chromagic Technologies Corporation
Address	5 of 2nd Fl., No.611, Sec.1, Wanshou Rd., Kwei Shan,
TaoyuanHsien 333, Taiwan.	

Date of Receipt	Oct. 27, 2011
Issued Date	Dec. 27, 2011
Report No.	11B041R-RFUSP30V01
Report Version	V1.0





The test results relate only to the samples tested.

The test report shall not be reproduced except in full without the written approval of QuieTek Corporation. This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government



Test Report Certification

Issued Date: Dec. 27, 2011 Report No.: 11B041R-RFUSP30V01



Product Name	Gateway
Applicant	Chromagic Technologies Corporation
Address	5 of 2nd Fl., No.611, Sec.1, Wanshou Rd., Kwei Shan, TaoyuanHsien 333,
	Taiwan.
Manufacturer	Chromagic Technologies Corporation
Model No.	HSC04-0
EUT Rated Voltage	AC 100-240V, 50-60Hz (by Adapter); DC 6V (by Battery)
EUT Test Voltage	AC 120V/60Hz (by Adapter); DC 6V (by Battery)
Trade Name	Chromagic Technologies Corporation
Applicable Standard	FCC CFR Title 47 Part 15 Subpart C: 2010
	ANSI C63.4: 2003
Test Result	Complied

Test results relate only to the samples tested.

The test report shall not be reproduced except in full without the written approval of QuieTek Corporation. This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

Documented By	:	Genie Chang
	_	(G : A1 G : 1: (G : Gl)

(Senior Adm. Specialist / Genie Chang)

Tested By: Vincent chu

(Engineer / Vincent Chu)

Approved By :

(Manager / Vincent Lin)



TABLE OF CONTENTS

De	scription	Page
1.	GENERAL INFORMATION	4
1.1.	EUT Description	4
1.2.	Operational Description	
1.3.	Tested System Datails	
1.4.	Configuration of Test System	
1.5.	EUT Exercise Software	
1.6.	Test Facility	
2.	Conducted Emission	8
2.1.	Test Equipment	
2.2.	Test Setup	
2.3.	Limits	9
2.4.	Test Procedure	9
2.5.	Uncertainty	
2.6.	Test Result of Conducted Emission	10
3.	Radiated Emission	12
3.1.	Test Equipment	12
3.2.	Test Setup	13
3.3.	Limits	14
3.4.	Test Procedure	14
3.5.	Uncertainty	15
3.6.	Test Result of Radiated Emission	16
4.	Band Edge	21
4.1.	Test Equipment	
4.2.	Test Setup	
4.3.	Limits	
4.4.	Test Procedure	
4.5.	Uncertainty	
4.6.	Test Result of Band Edge	23
5.	Duty Cycle	25
5.1.	Test Equipment	25
5.2.	Test Setup	
5.3.	Uncertainty	
5.4.	Test Result of Duty Cycle	26
6.	EMI Reduction Method During Compliance Testing	27

Attachment 1: EUT Test Photographs
Attachment 2: EUT Detailed Photographs



1. GENERAL INFORMATION

1.1. EUT Description

Product Name	Gateway
Trade Name	Chromagic Technologies Corporation
Model No.	HSC04-0
FCC ID	ZGXHSC04
Frequency Range	923MHz
Channel Control	N/A
Antenna Type	Monopole
Channel Number	1
Type of Modulation	FSK
AC Adapter	MFR: GOE, M/N: GS018-090
	Input: AC 100-240V~50/60Hz, 0.5A
	Output: DC 9.0V, 2A
	Cable Out: Non-Shielded, 1.8m

- 1. The EUT is a Gateway with a built-in 923MHz transceiver.
- 2. These tests are conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 15 Subpart C Paragraph 15.249 for spread spectrum devices.
- 3. The radiation measurements are performed in X, Y, Z axis positioning. Only the worst case is shown in the report.

|--|




1.3. Tested System Datails

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

P	oduct	Manufacturer	Model No.	Serial No.	Power Cord
1	IPod nano	Apple	A1199	YM706KKGVQ5	N/A

Sign	nal Cable Type	Signal cable Description
A	USB Cable	Non-Shielded, 1.2m
В	RJ45 Cable	Non-Shielded, 1.0m
C	RJ45 Cable	Non-Shielded, 1.0m

1.4. Configuration of Test System



1.5. EUT Exercise Software

- (1) Setup the EUT as shown in section 1.4
- (2) Inserts the battery, start continuous transmit
- (3) Verify that the EUT works correctly.



1.6. Test Facility

Ambient conditions in the laboratory:

Items	Required (IEC 68-1)	Actual	
Temperature (°C)	15-35	20-35	
Humidity (%RH)	25-75	50-65	
Barometric pressure (mbar)	860-1060	950-1000	

The related certificate for our laboratories about the test site and management system can be downloaded from

QuieTek Corporation's Web Site: http://www.quietek.com/tw/ctg/cts/accreditations.htm

The address and introduction of QuieTek Corporation's laboratories can be founded in our Web

site: http://www.quietek.com/

Site Description: File on

Federal Communications Commission

FCC Engineering Laboratory 7435 Oakland Mills Road Columbia, MD 21046

Registration Number: 92195

Accreditation on NVLAP NVLAP Lab Code: 200533-0

Site Name: Quietek Corporation

Site Address: No. 5-22, Ruei-Shu Valley, Ruei-Ping Tsuen,

Lin-Kou Shiang, Taipei,

Taiwan, R.O.C.

TEL: 886-2-8601-3788 / FAX: 886-2-8601-3789

E-Mail: service@quietek.com

FCC Accreditation Number: TW1014



2. Conducted Emission


2.1. Test Equipment

	Equipment	Manufacturer	Model No. / Serial No.	Last Cal.	Remark
X	Test Receiver	R & S	ESCS 30 / 825442/018	Sep., 2011	
X	Artificial Mains Network	R & S	ENV4200 / 848411/10	Feb., 2011	Peripherals
X	LISN	R & S	ESH3-Z5 / 825562/002	Feb., 2011	EUT
	DC LISN	Schwarzbeck	8226 / 176	Mar, 2011	EUT
X	Pulse Limiter	R & S	ESH3-Z2 / 357.8810.52	Feb., 2011	
	No.1 Shielded Room				

Note:

- 1. All equipments are calibrated every one year.
- 2. The test instruments marked by "X" are used to measure the final test results.

2.2. Test Setup





2.3. Limits

FCC Part 15 Subpart C Paragraph 15.207 (dBuV) Limit						
Frequency	Limits					
MHz	QP	AV				
0.15 - 0.50	66-56	56-46				
0.50-5.0	56	46				
5.0 - 30	60	50				

Remarks: In the above table, the tighter limit applies at the band edges.

2.4. Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm /50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs.)

Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2003 on conducted measurement.

Conducted emissions were invested over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

2.5. Uncertainty

 \pm 2.26 dB



2.6. Test Result of Conducted Emission

Product : Gateway

Test Item : Conducted Emission Test

Power Line : Line 1

Test Mode : Mode 1: Transmit

Frequency	Correct	Reading	Measurement	Margin	Limit
	Factor	Level	Level		
MHz	dB	dBuV	dBuV	dB	dBuV
Line 1					
Quasi-Peak					
0.224	9.840	22.130	31.970	-31.916	63.886
0.459	9.840	26.690	36.530	-20.641	57.171
0.752	9.850	21.050	30.900	-25.100	56.000
1.283	9.850	20.600	30.450	-25.550	56.000
1.873	9.860	20.080	29.940	-26.060	56.000
3.060	9.870	20.000	29.870	-26.130	56.000
Average					
0.224	9.840	7.120	16.960	-36.926	53.886
0.459	9.840	15.310	25.150	-22.021	47.171
0.752	9.850	8.850	18.700	-27.300	46.000
1.283	9.850	8.200	18.050	-27.950	46.000
1.873	9.860	7.970	17.830	-28.170	46.000
3.060	9.870	8.380	18.250	-27.750	46.000

- 1. All Reading Levels are Quasi-Peak and average value.
- 2. "means the worst emission level.
- 3. Measurement Level = Reading Level + Correct Factor



Test Item : Conducted Emission Test

Power Line : Line 2

Test Mode : Mode 1: Transmit

Frequency	Correct	Reading	Measurement	Margin	Limit
	Factor	Level	Level		
MHz	dB	dBuV	dBuV	dB	dBuV
Line 2					_
Quasi-Peak					
0.162	9.840	25.770	35.610	-30.047	65.657
0.220	9.840	21.790	31.630	-32.370	64.000
0.455	9.840	21.570	31.410	-25.876	57.286
0.666	9.840	25.580	35.420	-20.580	56.000
1.373	9.850	14.640	24.490	-31.510	56.000
3.002	9.868	15.000	24.868	-31.132	56.000
Average					
0.162	9.840	10.310	20.150	-35.507	55.657
0.220	9.840	6.190	16.030	-37.970	54.000
0.455	9.840	10.270	20.110	-27.176	47.286
0.666	9.840	15.960	25.800	-20.200	46.000
1.373	9.850	2.650	12.500	-33.500	46.000
3.002	9.868	3.580	13.448	-32.552	46.000

- 1. All Reading Levels are Quasi-Peak and average value.
- 2. "means the worst emission level.
- 3. Measurement Level = Reading Level + Correct Factor



3. Radiated Emission

3.1. Test Equipment

The following test equipment are used during the radiated emission test:

Test Site		Equipment	Manufacturer	Model No./Serial No.	Last Cal.
⊠Site # 3	X	Bilog Antenna	Schaffner Chase	CBL6112B/2673	Sep., 2011
	X	Horn Antenna	Schwarzbeck	BBHA9120D/D305	Sep., 2011
		Horn Antenna	Schwarzbeck	BBHA9170/208	Jul., 2011
	X	Pre-Amplifier	QTK	QTK-AMP-03 / 0003	May, 2011
	X	Pre-Amplifier	QTK	AP-180C / CHM_0906076	Sep., 2011
		Pre-Amplifier	MITEQ	AMF-4D-180400-45-6P/ 925975	Mar, 2011
	X	Spectrum Analyzer	Agilent	E4407B / US39440758	May, 2011
	X	Test Receiver	R & S	ESCS 30/ 825442/018	Sep., 2011
	X	Coaxial Cable	QuieTek	QTK-CABLE/ CAB5	Feb., 2011
	X	Controller	QuieTek	QTK-CONTROLLER/ CTRL3	N/A
	X	Coaxial Switch	Anritsu	MP59B/6200265729	N/A


Note: 1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

2. The test instruments marked with "X" are used to measure the final test results.




3.2. Test Setup

Radiated Emission Below 1GHz



Radiated Emission Above 1GHz



Page: 13 of 29



3.3. Limits

➤ General Radiated Emission Limits

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 20dB below the level of the fundamental or to the general radiated emission limits in paragraph 15.209, whichever is the lesser attenuation.

FCC Part 15 Subpart C Paragraph 15.209(a) Limits						
Frequency MHz	uV/m @3m	dBuV/m@3m				
30-88	100	40				
88-216	150	43.5				
216-960	200	46				
Above 960	500	54				

Remarks: E field strength $(dBuV/m) = 20 \log E$ field strength (uV/m)

3.4. Test Procedure

The EUT was setup according to ANSI C63.4, 2003 and tested compliance to FCC 47CFR 15.249 requirements.

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned between 1 meter and 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.4: 2003 on radiated measurement.

The resolution bandwidth below 1GHz setting on the field strength meter is 120 kHz and above 1GHz is 1MHz.

Radiated emission measurements below 1GHz are made using broadband Bilog antenna and above 1GHz are made using Horn Antennas.

The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with the measurement antenna kept pointed at the source of the emission both in azimuth and elevation, with the polarization of the antenna oriented for maximum response. The antenna is pointed at an angle towards the source of the emission, and the EUT is rotated in both height and polarization to maximize the measured emission. The emission is kept within the illumination area of the 3 dB bandwidth of the antenna.

The worst radiated emission is measured on the Final Measurement.

The measurement frequency range from 30MHz - 10th Harmonic of fundamental was investigated.



3.5. Uncertainty

- ± 3.9 dB above 1GHz
- ± 3.8 dB below 1GHz



3.6. Test Result of Radiated Emission

Product : Gateway

Test Item : Fundamental Radiated Emission

Test Site : No.3OATS

Test Mode : Mode 1: Transmit (Z-Axis)

Frequency	Correct Factor	Reading Level	Measurement Level	Margin	Limit
MHz	dB	dBuV	dBuV/m	dB	dBuV/m
Horizontal Peak Detector:					
923.000	28.293	83.700	111.993	-2.007	114.000
Vertical Peak Detector:					
923.000	28.293	69.300	97.593	-16.407	114.000

- 1. Measurement Level = Reading Level + Correct Factor.
- 2. Correct Factor = Antenna Factor + Cable Loss PreAMP.
- 3. The average measurement was not performed when the peak measured data under the limit of average detection. If the readings given are average, peak measurement should also be supplied.



Average Detector:					
Frequency	Peak	Duty Cycle	Measurement	Margin	Limit
	Measurement	Correct Factor	Level		
MHz	dBuV/m	dB	dBuV/m	dB	dBuV/m
Horizontal					
Average Detector:					
923	111.993	-26.936	85.057	-8.943	94.000
Vertical Average Detector:					
923	97.593	-26.936	70.657	-23.343	94.000

- 1. AVG Measurement=Peak Measurement + Duty Cycle Correct Factor
- 2. The Duty Cycle is refer to section 5.



Test Item : Harmonic Radiated Emission Data

Test Site : No.3 OATS

Test Mode : Mode 1: Transmit

Frequency	Correct	Reading	Measurement	Margin	Limit
	Factor	Level	Level		
MHz	dB	dBuV	dBuV/m	dB	dBuV/m
Horizontal					
Peak Detector:					
1846.000	-4.230	49.620	45.390	-28.610	74.000
2769.000	-0.785	37.750	36.965	-37.035	74.000
3692.000	-0.973	40.190	39.217	-34.783	74.000
4615.000	2.092	38.700	40.792	-33.208	74.000

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. Measurement Level = Reading Level + Correct Factor.
- 5. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.
- 7. The emission levels of other frequencies are very lower than the limit and not show in test report.



Test Item : Harmonic Radiated Emission Data

Test Site : No.3 OATS

Test Mode : Mode 1: Transmit

Frequency	Correct	Reading	Measurement	Margin	Limit
	Factor	Level	Level		
MHz	dB	dBuV	dBuV/m	dB	dBuV/m
Vertical					
Peak Detector:					
1846.000	-2.941	50.220	47.279	-26.721	74.000
2769.000	-0.968	41.160	40.192	-33.808	74.000
3692.000	0.171	42.450	42.621	-31.379	74.000
4615.000	5.939	42.910	48.849	-25.151	74.000

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. Measurement Level = Reading Level + Correct Factor.
- 5. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.
- 7. The emission levels of other frequencies are very lower than the limit and not show in test report.



Test Item : General Radiated Emission Data

Test Site : No.3 OATS

Test Mode : Mode 1: Transmit

Frequency	Correct	Reading	Measurement	Margin	Limit
	Factor	Level	Level		
MHz	dB	dBuV	dBuV/m	dB	dBuV/m
Horizontal					
107.600	-7.058	40.217	33.159	-10.341	43.500
270.560	-5.007	34.595	29.588	-16.412	46.000
458.740	0.833	30.765	31.598	-14.402	46.000
573.200	2.537	36.398	38.935	-7.065	46.000
743.920	3.326	31.883	35.209	-10.791	46.000
860.320	5.656	33.498	39.154	-6.846	46.000
Vertical					
61.040	-4.316	38.098	33.782	-6.218	40.000
109.540	-0.418	30.784	30.366	-13.134	43.500
379.200	-1.505	29.247	27.741	-18.259	46.000
528.580	-0.462	30.473	30.011	-15.989	46.000
747.800	2.166	37.153	39.319	-6.681	46.000
838.980	2.611	33.605	36.216	-9.784	46.000

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. Measurement Level = Reading Level + Correct Factor.
- 5. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.
- 7. The emission levels of other frequencies are very lower than the limit and not show in test report.



4. Band Edge

4.1. Test Equipment

The following test equipments are used during the band edge tests:


Test Site	Equipment		Manufacturer	Model No./Serial No.	Last Cal.
⊠Site # 3	X	Bilog Antenna	Schaffner Chase	CBL6112B/2673	Sep., 2011
		Horn Antenna	Schwarzbeck	BBHA9120D/D305	Sep., 2011
		Horn Antenna	Schwarzbeck	BBHA9170/208	Jul., 2011
		Pre-Amplifier	QTK	AP-180C / CHM_0906076	Sep., 2011
	X	Spectrum Analyzer	Agilent	E4407B / US39440758	May, 2011
	X	Test Receiver	R & S	ESCS 30/ 825442/018	Sep., 2011
	X	Coaxial Cable	QuieTek	QTK-CABLE/ CAB5	Feb., 2011
	X	Controller	QuieTek	QTK-CONTROLLER/ CTRL3	N/A
	X	Coaxial Switch	Anritsu	MP59B/6200265729	N/A

Note:

- 1. All equipments are calibrated every one year.
- 2. The test equipments marked by "X" are used to measure the final test results.

4.2. Test Setup

RF Radiated Measurement:





4.3. Limits

Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

4.4. Test Procedure

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.

Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.4: 2003 on radiated measurement.

The bandwidth setting below 1GHz and above 1GHz on the field strength meter is 120 kHz and 1MHz, respectively.

4.5. Uncertainty

Radiated is \pm 3.9 dB



4.6. Test Result of Band Edge

Product : Gateway

Test Item : Band Edge Data
Test Site : No.3 OATS


Test Mode : Mode 1: Transmit

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Margin (dB)	Quasi-Peak Limit (dBuV/m)	Result
01(Quasi-Peak)	902.000	27.920	10.676	38.596	-7.404	46.000	Pass
01(Quasi-Peak)	928.000	27.350	16.597	43.947	-2.053	46.000	Pass

Figure Channel 01:

Horizontal (Quasi-Peak)



- 1. Quasi-Peak measurements: RBW=100kHz,VBW=1MHz,Sweep: Auto.
- 2. "*", means this data is the worst emission level.
- 3. Measurement Level = Reading Level + Correct Factor.



Test Item : Band Edge Data
Test Site : No.3 OATS


Test Mode : Mode 1: Transmit

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Margin (dB)	Quasi-Peak Limit (dBuV/m)	Result
01(Quasi-Peak)	902.000	5.360	28.736	34.096	-11.904	46.000	Pass
01(Quasi-Peak)	928.000	5.708	31.139	36.847	-9.153	46.000	Pass

Figure Channel 01:

Vertical (Quasi-Peak)



- 1. Quasi-Peak measurements: RBW=100kHz,VBW=1MHz,Sweep: Auto.
- 2. "*", means this data is the worst emission level.
- 3. Measurement Level = Reading Level + Correct Factor.



5. Duty Cycle

5.1. Test Equipment


The following test equipments are used during the band edge tests:

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
	Spectrum Analyzer	R&S	FSP40 / 100170	Jun, 2011
	Spectrum Analyzer	Agilent	E4407B / US39440758	Jun, 2011
X	Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2011

Note: 1. All equipments are calibrated every one year.

2. The test equipments marked by "X" are used to measure the final test results.

5.2. Test Setup



5.3. Uncertainty

 \pm 150Hz




5.4. Test Result of Duty Cycle

Product : Gateway

Test Item : Duty Cycle Data
Test Site : No.3 OATS

Test Mode : Mode 1: Transmit



Time on of 100ms= 4.500 ms

Duty Cycle= 4.5ms / 100ms= 0.045

Duty Cycle correction factor= 20 LOG 0.045= -26.936 dB

Duty Cycle correction factor	-26.936	dB	
-------------------------------------	---------	----	--



6. EMI Reduction Method During Compliance Testing

No modification was made during testing.