



**Nemko**

**Nemko USA, Inc.**

11696 Sorrento Valley Rd., Suite F

San Diego, CA 92121-1024

Phone (858) 755-5525 Fax (858) 452-1810

---

## CERTIFICATION TEST REPORT

Report Number: 2011 05175152 FCC

Project Number: 1028680

Nex Number: 175152

Applicant: MICROPOWER TECHNOLOGIES  
4225 EXECUTIVE SQUARE, SUITE 430  
La Jolla, CA 92037

Equipment Under Test (EUT): WIRELESS DIGITAL CAMERA SYSTEM

Model: MPT-2500

FCC ID: ZHXMPT2500

In Accordance With: FCC Part 15 Subpart C, 15.247

Tested By: Nemko USA Inc.  
11696 Sorrento Valley Road, Suite F  
San Diego, CA 92121

Authorized By:   
\_\_\_\_\_  
ALAN LAUDANI, EMC/RF Test Engineer

Date: MAY 11, 2011

Total Number of Pages: 41



## Section1: Summary of Test Results

### 1.1 General

All measurements are traceable to national standards

These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with FCC Part 15; Subpart C.. Radiated tests were conducted in accordance with ANSI C63.4-2003. Radiated emissions are made on an open area test site. A description of the test facility is on file with the FCC.

The assessment summary is as follows:

Apparatus Assessed: Wireless Digital Camera System

Model: MPT-2500

Specification: FCC Part 15 Subpart C, 15.247

Date Received in Laboratory: May 5, 2011

Compliance Status: Complies

Exclusions: None

Non-compliances: None



## 1.2 Report Release History

| Revision | Date         | Comments         |              |
|----------|--------------|------------------|--------------|
| -        | May 11, 2011 | Prepared By:     | Alan Laudani |
| -        | May 11, 2011 | Initial Release: | Alan Laudani |

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025.

Nemko USA Inc. authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko USA Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

TESTED BY:   
Date: May 11, 2011  
ALAN LAUDANI, EMC Test Engineer

## TABLE OF CONTENTS

|  |           |
|--|-----------|
| <b>Section1: Summary of Test Results .....</b>                 | <b>2</b>  |
| 1.1 General .....  | 2         |
| 1.2 Report Release History .....                               | 3         |
| <b>Section 2: Equipment Under Test.....</b>                    | <b>5</b>  |
| 2.1 Product Identification.....                                | 5         |
| 2.2 Theory of Operation .....                                  | 6         |
| 2.3 Technical Specifications of the EUT .....                  | 7         |
| <b>Section 3: Test Conditions .....</b>                        | <b>8</b>  |
| 3.1 Specifications .....                                       | 8         |
| 3.3 Test Environment.....                                      | 8         |
| 3.4 Test Equipment .....                                       | 9         |
| <b>Section 4: Observations .....</b>                           | <b>10</b> |
| 4.1 Modifications Performed During Assessment.....             | 10        |
| 4.2 Record Of Technical Judgements.....                        | 10        |
| 4.3 EUT Parameters Affecting Compliance .....                  | 10        |
| 4.4 Deviations From Laboratory Test Procedures .....           | 10        |
| 4.5 Test Deleted.....  | 10        |
| 4.6 Additional Observations .....                              | 10        |
| <b>Section 5: Results Summary.....</b>                         | <b>11</b> |
| 5.1 Test Results .....   | 11        |
| <b>Appendix A: Test Results.....</b>                           | <b>12</b> |
| Power Line Conducted Emissions .....                           | 12        |
| 20 dB Bandwidth .....  | 13        |
| Minimum 6dB RF Bandwidth.....                                  | 16        |
| Peak Output Power .....  | 19        |
| Band-edge Compliance of RF Conducted /Radiated Emissions ..... | 20        |
| Spurious RF Conducted Emissions .....                          | 26        |
| Spurious Radiated Emissions .....                              | 30        |
| Power Spectral Density for Digitally Modulated Devices .....   | 32        |

## Section 2: Equipment Under Test

### 2.1 Product Identification

The Equipment Under Test was identified as follows:

| DEVICE                                      | MANUFACTURER<br>MODEL #<br>SERIAL #                                   | POWER CABLE |
|---|---|-------------|
| EUT - Wireless Digital Camera System Camera | MicroPower Technologies<br>Model: MPT-2500<br>Serial #: E48174C000009 | NA          |

|                |           |
|----------------|-----------|
| Connection     | I/O Cable |
| No connections |           |





## 2.2 Theory of Operation

The MPT-2500 and MPT-2700 comprise a Wireless Digital Camera System. Control commands communicate through the 902 to 928 MHz band radio and the Camera Data communicate through the 2400 to 2483.5 MHz band radio. The camera MPT-2500 is powered by a battery charged by Solar panels and the Hub MPT-2500 is powered by the AC mains (120 VAC 60 Hz) and connects to a network via Ethernet. The hub may have a display, mouse and serial cable when in setup or operation.

The EUT's performance during test was evaluated against the performance criterion specified by applicable test standards. Performance results are detailed in the test results section of this report.

This test report is for the MPT-2500 Camera section of the system. The camera's transmitters were set into a test mode for testing.

### 2.3 Technical Specifications of the EUT

Manufacturer: **MicroPower Technologies**

Operating Frequencies: 909.798 MHz to 920.596 MHz  
in the 902 -928 MHz Band  
2412.0 MHz to 2462.0 MHz  
in the 2400 -2483.5 MHz Band

Rated Power: Low band: 0.014 W  
High band: 0.641 W

Modulation: Low band: GFSK,  
High band: Digital

Antenna Connector: Type N, professionally installed  
Type "Reverse SMA", professionally installed.

Power Source: 3 solar panels, 6 VDC battery

## Section 3: Test Conditions

### 3.1 Specifications

The apparatus was assessed against the following specifications:

*FCC Part 15 Subpart C, 15.247*

Operation within the bands 902-928 MHz, 2400-2483.5 MHz, 5725-5850 MHz and 24.0-24.25 GHz bands.

### 3.3 Test Environment

All tests were performed under the following environmental conditions:

|                    |                   |
|--------------------|-------------------|
| Temperature range  | 16-22°C           |
| Humidity range     | 39-45%            |
| Pressure range     | 102.0 – 102.3 kPa |
| Power supply range | 6VDC nominal      |

### 3.4 Test Equipment

| Nemko ID | Device                      | Manufacturer    | Model   | Serial Number | Cal Date  | Cal Due Date |
|----------|-----------------------------|-----------------|---------|---------------|-----------|--------------|
| --       | DC power supply             | Micronta        | --      | --            | NCR       | NCR          |
| 115      | Antenna, Bicon              | EMCO            | 3104    | 3020          | 9/28/2010 | 9/28/2011    |
| 317      | Preamplifier                | HP              | 8449A   | 2749A00167    | 5/7/2010  | 5/7/2011     |
| 625      | Antenna, Dbl Ridge Horn     | EMCO            | 3116    | 2325          | 2/1/2010  | 2/1/2012     |
| 755      | Antenna, LPA                | EMCO            | 3147    | 1246          | 7/23/2009 | 7/23/2011    |
| 813      | Multimeter                  | Fluke           | 111     | 78130060      | 9/16/2009 | 9/16/2011    |
| 835      | Spectrum Analyzer           | Rohde & Schwarz | RHDFSEK | 829058/005    | 7/12/2010 | 7/12/2011    |
| 877      | Antenna, DRG Horn, .7-18GHz | AH Systems      | SAS-571 | 688           | 8/16/2010 | 8/16/2012    |
| 898      | EMI Receiver & filter set   | HP              | 8546A   | 3625A00348    | 6/22/2010 | 6/22/2011    |
| 899      | Filter Section              | HP              | 85460A  | 3448A00288    | 6/22/2010 | 6/22/2011    |
| 946      | Peak Power Sensor           | HP              | 84815A  | 3318A01726    | 9/28/2010 | 9/28/2011    |
| 947      | Peak Power Analyzer         | HP              | 8991A   | 3621A00906    | 9/28/2010 | 9/28/2011    |

Registration of the OATS are on file with the Federal Communications Commission, and are also registered with Industry Canada under Site Numbers 2040B-1 and 2040B-2.

## Section 4: Observations

### 4.1 Modifications Performed During Assessment

No modifications were performed during assessment.

### 4.2 Record Of Technical Judgements

No technical judgements were made during the assessment.

### 4.3 EUT Parameters Affecting Compliance

The user of the apparatus could not alter parameters that would affect compliance.

### 4.4 Deviations From Laboratory Test Procedures

No deviations from Laboratory Test Procedure

### 4.5 Test Deleted

No Tests were deleted from this assessment.

### 4.6 Additional Observations

There were no additional observations made during this assessment.



## Section 5: Results Summary

This section contains the following:

FCC Part 15 Subpart C:

The column headed "Required" indicates whether the associated clauses were invoked for the apparatus under test. The following abbreviations are used:

N No: not applicable / not relevant

Y Yes: Mandatory i.e. the apparatus shall conform to these tests.

N/T Not Tested, mandatory but not assessed. (See section 4.4 Test deleted)

The results contained in this section are representative of the operation of the apparatus as originally submitted.

### 5.1 Test Results

| Part 15C     | Test Description                                       | Required | Result |
|--------------|--|----------|--------|
| 15.207 (a)   | Conducted Emission Limit                               | NA       | Pass   |
| 15.215(c)    | 20 dB & 99% Bandwidth                                  | Y        | Pass   |
| 15.247(a)(2) | Minimum 6dB RF Bandwidth                               | Y        | Pass   |
| 15.247(b)(3) | Peak Output Power                                      | Y        | Pass   |
| 15.247(d)    | Band-edge Compliance of RF Conducted Emissions         | Y        | Pass   |
| 15.247 (d)   | Spurious RF Conducted Emissions                        | Y        | Pass   |
| 15.247 (d)   | Spurious Radiated Emissions                            | Y        | Pass   |
| 15.247(e)    | Power Spectral Density for Digitally Modulated Devices | Y        | Pass   |



## Appendix A: Test Results

### Power Line Conducted Emissions

15.207(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

| Frequency of emission (MHz) | Conducted limit (dB $\mu$ V) |           |
|-----------------------------|------------------------------|-----------|
|                             | Quasi-peak                   | Average   |
| 0.15–0.5                    | 66 to 56*                    | 56 to 46* |
| 0.5–5                       | 56                           | 46        |
| 5–30                        | 60                           | 50        |

\*Decreases with the logarithm of the frequency.

### Test Conditions:

|                     |                            |              |              |
|---------------------|----------------------------|--------------|--------------|
| Sample Number:      | MPT-2500                   | Temperature: | °C           |
| Date:               |                            | Humidity:    | %            |
| Modification State: | Low, Mid and High Channels | Tester:      | Alan Laudani |
|                     |                            | Laboratory:  | Nemko SR2    |

Test Results: EUT does not connect to AC mains

**20 dB Bandwidth**

(c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

**Test Conditions:**

|                     |                            |              |              |
|---------------------|----------------------------|--------------|--------------|
| Sample Number:      | MPT-2500                   | Temperature: | 21°C         |
| Date:               | May 6, 9, 2011             | Humidity:    | 39%          |
| Modification State: | Low, Mid and High Channels | Tester:      | Alan Laudani |
| Laboratory:         |                            |              | Nemko        |

Test Results: See attached plots.


**Additional Observations:**

- This was a conducted test.
- Span is wide enough to capture the channel transmission
- RBW is 1% of the span
- VBW is 3X RBW
- Sweep is auto, Detector is Peak, Trace is Max Hold
- Used Spectrum Analyzer's programmed function.

| Channel Range      | Observed 20 dB bandwidth |
|--------------------|--------------------------|
| Low (909.798 MHz)  | 909.5 kHz                |
| Mid (914.596 MHz)  | 921.8 kHz                |
| High (920.595 MHz) | 931.8 kHz                |


| Channel Range     | Observed 20 dB bandwidth |
|-------------------|--------------------------|
| Low (2412.0 MHz)  | 16.4 MHz                 |
| Mid (2437.0 MHz)  | 16.8 MHz                 |
| High (2462.0 MHz) | 16.6 MHz                 |

Low Band  
20 dB Band Width




www.nemko.com


**(Mid Channel)**



**(High Channel)**




## 20 dB Band Width




Date: 06.MAY 2011 12:57:55

(Mid Channel)



(High Channel)



**Minimum 6dB RF Bandwidth**

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

**Test Conditions:**

|                     |                            |              |              |
|---------------------|----------------------------|--------------|--------------|
| Sample Number:      | MPT-2500                   | Temperature: | 21°C         |
| Date:               | February 1, 2011           | Humidity:    | 39%          |
| Modification State: | Low, Mid and High Channels | Tester:      | Alan Laudani |

Laboratory:


Nemko

**Test Results:** EUT complies, See attached plots.**Additional Observations:**

- This is a conducted test
- RBW is set to 100kHz
- VBW is 3X RBW
- Sweep is auto
- Detector is Peak
- Trace is Max Hold
- For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK output reading was plotted; a DISPLAY line was drawn 6 dB lower than PEAK level. The 6 dB bandwidth was determined from where the channel output spectrum intersected the display line.
- EUT complies as 6 dB BW > 500 kHz


| Channel Range      | Observed 6 dB bandwidth |
|--------------------|-------------------------|
| Low (909.798 MHz)  | 739 kHz                 |
| Mid (914.596 MHz)  | 739 kHz                 |
| High (920.595 MHz) | 739 kHz                 |

| Channel Range     | Observed 6 dB bandwidth |
|-------------------|-------------------------|
| Low (2412.0 MHz)  | 15.2 MHz                |
| Mid (2437.0 MHz)  | 15.2 MHz                |
| High (2462.0 MHz) | 15.2 MHz                |




Date: 09.MAY 2011 12:35:54

(Mid Channel) 739 kHz




Date: 09.MAY.2011 12:37:04




Date: 09.MAY.2011 12:33:08

**(Low Channel) 6 dB Bandwidth is 15.2 MHz**




Date: 06.MAY 2011 12:42:04

**(Mid Channel) 15.2 MHz**



Date: 06.MAY 2011 12:40:34

**(High Channel) 15.2 MHz**



Date: 06.MAY 2011 12:39:27

**Peak Output Power**

(3) For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signalling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the *maximum conducted output power* is the highest total transmit power occurring in any mode.

**Test Conditions:**

|                     |                            |              |              |
|---------------------|----------------------------|--------------|--------------|
| Sample Number:      | MPT-2500                   | Temperature: | 21°C         |
| Date:               | May 6, 2011                | Humidity:    | 39%          |
| Modification State: | Low, Mid and High Channels | Tester:      | Alan Laudani |
| Laboratory:         |                            |              | Nemko        |

**Test Results: Table below****Additional Observations:**

- This is a conducted test. 11 dB was offset for the attenuator and cable used.
- Input voltage to the EUT was varied +/-15%. The solar panel and battery were bypassed and a lab power supply, monitored by a calibrated multimeter, used.
- Peak Power meter used.

| Channel Range      | Voltage | dBm   | Watts |
|--------------------|---------|-------|-------|
| Low (909.798 MHz)  | 5.1 VDC | 11.47 | 0.014 |
|                    | 6.0 VDC | 11.47 | 0.014 |
|                    | 6.9 VDC | 11.47 | 0.014 |
| Mid (914.596 MHz)  | 5.1 VDC | 9.19  | 0.008 |
|                    | 6.0 VDC | 9.19  | 0.008 |
|                    | 6.9 VDC | 8.98  | 0.008 |
| High (920.595 MHz) | 5.1 VDC | 10.19 | 0.010 |
|                    | 6.0 VDC | 10.45 | 0.011 |
|                    | 6.9 VDC | 10.19 | 0.010 |
| Channel Range      | Voltage | dBm   | Watts |
| Low (2412.0 MHz)   | 5.1 VDC | 27.38 | 0.547 |
|                    | 6.0 VDC | 27.61 | 0.577 |
|                    | 6.9 VDC | 27.95 | 0.624 |
| Mid (2437.0 MHz)   | 5.1 VDC | 28.04 | 0.637 |
|                    | 6.0 VDC | 28.07 | 0.641 |
|                    | 6.9 VDC | 27.95 | 0.624 |
| High (2462.0 MHz)  | 5.1 VDC | 27.38 | 0.547 |
|                    | 6.0 VDC | 26.91 | 0.491 |
|                    | 6.9 VDC | 27.77 | 0.598 |

**Band-edge Compliance of RF Conducted /Radiated Emissions**

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

**Test Conditions:**

|                     |                       |              |              |
|---------------------|-----------------------|--------------|--------------|
| Sample Number:      | MPT-2500              | Temperature: | 21°C         |
| Date:               | May 6, 2011           | Humidity:    | 44%          |
| Modification State: | Low and High Channels | Tester:      | Alan Laudani |
|                     |                       | Laboratory:  | Nemko        |

**Test Results:**

See attached plots and radiated emissions table.

**Additional Observations:**

- This is a Radiated Emissions test.

**Low Band:**

- Span is wide enough to capture the peak level of the emission operating on the channel closest to the band edges (Lower and Upper).
- Band edges were measured with quasi-peak detector.
- Band edge plots show no effect of lowest, highest channel.
- VBW is 3X RBW
- Sweep is auto.
- Detector is Peak, Trace is Max Hold


**High Band:**

- Span is wide enough to capture the peak level of the emission operating on the channel closest to the band edges (Lower and Upper).
- For Lower bandedge (no restricted zone) RBW is 100kHz
- For Lower bandedge, the peak level reading was taken and a display line was drawn 20 dBc below this level, which will be the limit for this test.
- For Upper bandedge (restricted zone) RBW is 1MHz
- For Upper bandedge (restricted zone) Limit is 74 dBuV/m peak @ 3m
- For Upper bandedge (restricted zone) Limit is 54 dBuV/m average @ 3m
- VBW is 3X RBW
- Sweep is auto.
- Detector is Peak, Trace is Max Hold
- Average = Peak + Duty Cycle Factor

FCC ID: ZHXMPT2500


Report Number: 2011 05175152 FCC  
Specification: FCC Part 15 Subpart C, 15.247

Low band Duty Cycle = -20dB  
EUT transmits 1.33 milliseconds x 2 times = 2.66 milliseconds



$$DCF = 20 \times \log(2.66/100) < -20\text{dB, limited to } -20\text{dB}$$


High band Duty Cycle = -20dB  
EUT transmits 0.361 milliseconds x 1 times = 0.361 milliseconds



$$DCF = 20 \times \log(.036/100) < -20\text{dB, limited to } -20\text{dB}$$






Scan centered at Lowest channel



www.nemko.com


Scan centered at Highest channel





## High Channel centered at 2462 MHz

Emission @ marker reported in table as passing Peak &amp; Average



## Emissions Table

| Radiated Emissions Data  |                          |                          |      |                     |               |                           |                                  |                            |                  |           |                      |
|--|--------------------------|--------------------------|------|---------------------|---------------|---------------------------|----------------------------------|----------------------------|------------------|-----------|----------------------|
| Job # :  | 1028680                  |                          |      | Date :              | 5-10-2011     |                           | Page                             | 1                          | of               | 1         |                      |
| NEX #:   | 175152                   |                          |      | Time :              | PM            |                           |                                  |                            |                  |           |                      |
|  |                          |                          |      | Staff :             | AAL           |                           |                                  |                            |                  |           |                      |
| Client Name :  | MICROPOWER TECHNOLOGIES  |                          |      |                     |               |                           | EUT Voltage :                    | solar                      |                  |           |                      |
| EUT Name :   | WIRELESS DIGITAL CAMERA  |                          |      |                     |               |                           | EUT Frequency :                  |                            |                  |           |                      |
| EUT Model #:   | MPT-2500                 |                          |      |                     |               |                           | Phase:                           | 1                          |                  |           |                      |
| EUT Serial #:  | NA                       |                          |      |                     |               |                           | NOATS                            |                            |                  |           |                      |
| EUT Config. :  | transmit                 |                          |      |                     |               |                           | SOATS                            | X                          |                  |           |                      |
| Specification :  | CFR47 Part 15, Subpart C |                          |      |                     |               |                           | Distance < 1000 MHz:             | 3 m                        |                  |           |                      |
| Loop Ant. #:   | NA                       |                          |      | Temp. (°C) :        |               |                           | 19                               |                            |                  |           |                      |
| Bicon Ant.#:   | 115 3m                   |                          |      | Humidity (%) :      |               |                           | 47                               |                            |                  |           |                      |
| Log Ant.#:   | 110 3m                   |                          |      | Spec An.#:          |               |                           | 898                              | 835                        |                  |           |                      |
| DRG Ant. #   | 877                      |                          |      | Spec An. Display #: |               |                           | 898                              | 835                        |                  |           |                      |
| Cable LF#:   | SOATS                    |                          |      | QP #:               |               |                           | 898                              |                            |                  |           |                      |
| Cable HF#:   | SOATS                    |                          |      | PreSelect#:         |               |                           | 899                              |                            |                  |           |                      |
| Preamp LF#:  | NA                       |                          |      |                     |               |                           |                                  |                            |                  |           |                      |
| Preamp HF#   | 919                      |                          |      |                     |               |                           |                                  |                            |                  |           |                      |
| Quasi-Peak RBW: 120 kHz  |                          |                          |      |                     |               |                           |                                  |                            |                  |           |                      |
| Video Bandwidth 300 kHz  |                          |                          |      |                     |               |                           |                                  |                            |                  |           |                      |
| Peak RBW: 1 MHz  |                          |                          |      |                     |               |                           |                                  |                            |                  |           |                      |
| Video Bandwidth 3 MHz  |                          |                          |      |                     |               |                           |                                  |                            |                  |           |                      |
| Average = peak + DCF   |                          |                          |      |                     |               |                           |                                  |                            |                  |           |                      |
| Measurements below 1 GHz are Quasi-Peak values, unless otherwise stated. |                          |                          |      |                     |               |                           |                                  |                            |                  |           |                      |
| Measurements above 1 GHz are Average values, unless otherwise stated.    |                          |                          |      |                     |               |                           |                                  |                            |                  |           |                      |
| Meas. Freq. (MHz)  | Meter Reading Vertical   | Meter Reading Horizontal | Det. | EUT Side F/L/R/B    | Ant. Height m | Max. Reading (dB $\mu$ V) | Corrected Reading (dB $\mu$ V/m) | Spec. limit (dB $\mu$ V/m) | CR/SL Diff. (dB) | Pass Fail | Comment              |
| 902.0  | 11.9                     | 10.7                     | Q    | -                   | 1.0           | 11.9                      | 39.6                             | 46.0                       | -6.5             | Pass      | band edge            |
| 928.0  | 10.6                     | 10.5                     | Q    | -                   | 1.0           | 10.6                      | 38.3                             | 46.0                       | -7.8             | Pass      | band edge            |
| 2389.9   | 37.3                     | 36.9                     | P    | -                   | 1.0           | 37.3                      | 70.3                             | 74.0                       | -3.7             | Pass      | band edge Restricted |
| 2389.9   | 17.3                     | 16.9                     | A    | -                   | 1.0           | 17.3                      | 50.3                             | 54.0                       | -3.7             | Pass      | band edge Restricted |
| 2400.0   | 39.4                     | 36.4                     | P    | -                   | 1.0           | 39.4                      | 74.3                             | 98.0                       | -23.7            | Pass      | 100 kHz rbw          |
| 2400.0   | 19.4                     | 16.4                     | A    | -                   | 1.0           | 19.4                      | 54.3                             | 78.0                       | -23.7            | Pass      | 100 kHz rbw          |
| 2412.0   | 83.1                     |                          | P    | -                   | 1.0           | 83.1                      | 118.0                            |                            |                  |           | 1 MHz rbw            |
| 2483.5   | 26.0                     | 25.5                     | P    | -                   | 1.0           | 26                        | 60.9                             | 74.0                       | -13.1            | Pass      | band edge            |
| 2483.5   | 6.0                      | 5.5                      | A    | -                   | 1.0           | 6                         | 40.9                             | 54.0                       | -13.1            | Pass      | DCF= -20             |

## Spurious RF Conducted Emissions

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### Test Conditions:

|                     |                            |              |              |
|---------------------|----------------------------|--------------|--------------|
| Sample Number:      | MPT-2500                   | Temperature: | 21°C         |
| Date:               | May 6, 2011                | Humidity:    | 44%          |
| Modification State: | Low, Mid and High Channels | Tester:      | Alan Laudani |
| Laboratory:         |                            |              | Nemko        |


### Test Results:

See attached plots.


### Additional Observations:

- This is a conducted test. 11.0 dB was offset for the cable used.
- The peak level reading was taken at the carrier frequency with the peak power meter (blue line), then a display line was drawn 20 dBc below this level (red line) which will be the limit for this test.
- RBW is 100 kHz
- VBW is 3X RBW
- Sweep is auto.
- Detector is Peak, Trace is Max Hold
- Emissions were searched from 30 MHz to 902 MHz and 928 MHz to 9,500 MHz.
- Emissions were searched from 30 MHz to 2400 MHz and from 2483.5 MHz to 25000 MHz.
- EUT complies.

Low band:  
Low Channel




Mid Channel




922.4 MHz -58.1 dBm

High Channel




922.8 MHz –23.9 dBm

High Band:  
Low Channel


2394.4 MHz –40.9 dBm

## Mid Channel



2394.9 MHz -40.8 dBm

## High Channel



2398.9 MHz -40.5 dBm

## Spurious Radiated Emissions

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### Test Conditions:

|                     |                            |              |              |
|---------------------|----------------------------|--------------|--------------|
| Sample Number:      | MPT-2500                   | Temperature: | 16°C         |
| Date:               | May 6, 2011                | Humidity:    | 44%          |
| Modification State: | Low, Mid and High Channels | Tester:      | Alan Laudani |
| Laboratory:         |                            |              | Nemko        |

Test Results: EUT complies.

- Emissions were searched from 30 MHz to 25000 MHz
- No other emissions within 20 dB of the limit were detected.
- No harmonics of the transmit frequencies were detected.
- The digital emissions did not vary when the transmitter channels were changed.
- Transmitter channels were investigated at low, mid and high channels; low and high band.

## Radiated Emissions Data

|                 |                          |        |                     |                      |                 |   |     |  |
|-----------------|--------------------------|--------|---------------------|----------------------|-----------------|---|-----|--|
| Job # :         | 1028680                  | Date : | 5-10-2011           | Page                 | 1               | of  | 1   |  |
| NEX #:          | 175152                   | Time : | PM                  |                      |                 |   |     |  |
| Client Name :   | MICROPOWER TECHNOLOGIES  |        |                     | EUT Voltage :        | solar           |   |     |  |
| EUT Name :      | WIRELESS DIGITAL CAMERA  |        |                     | EUT Frequency :      |                 |   |     |  |
| EUT Model #:    | MPT-2500                 |        |                     | Phase:               | 1               |   |     |  |
| EUT Serial #:   | E48174C000009            |        |                     | NOATS                |                 |   |     |  |
| EUT Config.:    | transmit                 |        |                     | SOATS                | X               |   |     |  |
| Specification : | CFR47 Part 15, Subpart C |        |                     | Distance < 1000 MHz: | 3 m             |   |     |  |
| Loop Ant. #:    | NA                       |        |                     | Distance > 1000 MHz: | 3 m             |   |     |  |
| Bicon Ant.#:    | 115                      | 3m     | Temp. (°C) :        | 19                   | RBW             |   |     |  |
| Log Ant. #:     | 110                      | 3m     | Humidity (%) :      | 47                   | Video Bandwidth |   |     |  |
| DRG Ant. #      | 877                      |        | Spec An. #:         | 898                  | 835             | Peak  | RBW |  |
| Cable LF#:      | SOATS                    |        | Spec An. Display #: | 898                  | 835             | Video Bandwidth   |     |  |
| Cable HF#:      | SOATS                    |        | QP #:               | 898                  |                 | Average = peak + DCF  |     |  |
| Preamp LF#:     | NA                       |        | PreSelect#:         | 899                  |                 |   |     |  |
| Preamp HF#      | 919                      |        |                     |                      |                 | Measurements below 1 GHz are Quasi-Peak values, unless otherwise specified. |     |  |
|                 |                          |        |                     |                      |                 | Measurements above 1 GHz are Average values, unless otherwise specified.    |     |  |

Measurements above 1 GHz are Average values, unless otherwise stated.

Measurements above 1 GHz are Average values, unless otherwise stated.

**Power Spectral Density for Digitally Modulated Devices**

(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

**Test Conditions:**

|                     |                            |              |              |
|---------------------|----------------------------|--------------|--------------|
| Sample Number:      | MPT-2500                   | Temperature: | 21°C         |
| Date:               | May 9, 2011                | Humidity:    | 44%          |
| Modification State: | Low, Mid and High Channels | Tester:      | Alan Laudani |
|                     |                            |              | Laboratory:  |
|                     |                            |              | Nemko        |

**Test Results:**



See attached plots.

**Additional Observations:**


- This is a conducted test. 11.0 dB was offset for the attenuator and cable used.
- RBW is 3kHz
- VBW is 10kHz
- Span is set to 1.5 MHz
- Sweep is set to 1.5MHz/3kHz or 500 seconds
- Trace is set to Peak, Max hold.
- Limit is 8 dBm
- EUT complies

| Frequency      | PSD (dBm) |
|----------------|-----------|
| 910.021948 MHz | 5.94      |
| 914.819948 MHz | 3.17      |
| 920.818948 MHz | 4.52      |

| Frequency       | PSD (dBm) |
|-----------------|-----------|
| 2411.999323 MHz | -1.50     |
| 2436.998500 MHz | -0.69     |
| 2462.000058 MHz | -1.84     |




High Band, Low Channel – Max level is  $-1.5$  dBm



www.nemko.com

Mid Channel  $-0.69$  dBm



High Channel  $-1.84$  dBm

