



# FCC 47 CFR PART 15 SUBPART C

## TEST REPORT

*For*

**Applicant :** Win Accord Ltd.

**Address :** 12F, No.225, Sec. 5, Nanjing E. Rd., Songshan Dist,  
Taipei City 105, Taiwan

**Product Name :** MID-PTT 726

**Model Name :** PT07102-46-XXX, WayteQ xPAD-70

**Brand Name :** N/A

**FCC ID :** ZIG-PTT726

**Report No. :** STS110317F3

**Date of Issue :** May 16,2011

**Issued by :** Most Technology Service Co., Ltd.

**Address :** No.5, Langshan 2nd Rd., North Hi-Tech Industrial Park ,Nanshan,  
Shenzhen, Guangdong ,China

**Tel :** 86-755-8617 0306

**Fax :** 86-755-8617 0310

*The report consists 44 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by MOST. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver.*

**TABLE OF CONTENTS**

1. VERIFICATION OF CONFORMITY .....	4
2. GENERAL INFORMATION .....	5
2.1 Product Information .....	5
2.2 Objective .....	6
2.3 Test Standards and Results .....	6
2.4 Environmental Conditions .....	6
3. TEST FACILITY .....	7
3.1 TEST FACILITY .....	7
3.2 GENERAL TEST PROCEDURES .....	7
3.3 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS .....	8
4. SETUP OF EQUIPMENT UNDER TEST .....	9
4.1 SUPPORT EQUIPMENT .....	9
4.2 TEST EQUIPMENT LIST .....	10
5. 47 CFR Part 15C 15.247 Requirements .....	11
5.1 Peak Output Power .....	11
5.1.1 Requirement .....	11
5.1.2 Test Description .....	11
5.1.3 Test Setup .....	11
5.1.4 EUT Setup and Operating Conditions .....	11
5.1.5 Test Result .....	11
5.2 6dB Bandwidth .....	13
5.2.1 Requirement .....	13
5.2.2 Test Description .....	13
5.2.3 Test Setup .....	13
5.2.4 Test Procedure .....	13
5.2.5 EUT Setup and Operating Conditions .....	13
5.2.6 Test Result .....	13
5.3 Power Spectrum Density .....	15
5.3.1 limits of Power Spectrum Density .....	15
5.3.2 Test Procedure .....	15
5.3.3 Test Setup .....	15
5.3.4 EUT Setup and Operating Conditions .....	15
5.3.5 Test Result .....	15
5.4 Band Edge .....	17
5.4.1 Requirement of the standard .....	17
5.4.2 Test Procedure .....	17

5.4.3 Test Setup.....	17
5.4.4 EUT Setup and Operating Conditions.....	17
5.4.5 Test Result.....	17
5.5 Conducted Spurious Emission.....	19
5.5.1 Requirement of the standard .....	19
5.5.2 Test Procedure .....	19
5.5.3 Test Setup.....	19
5.5.4 EUT Setup and Operating Conditions.....	19
5.5.5 Test Result.....	20
5.6 Radiated Emission Test.....	24
5.6.1 Requirement .....	24
5.6.2 Test Description .....	25
5.6.3 Test Description .....	26
5.6.4 Test Result.....	27
5.7 Power Line Conducted Emission Test .....	29
5.7.1 Limits of Line Conducted Emission Test.....	29
5.7.2 Block Diagram of Test Setup .....	29
5.7.3 Preliminary Procedure of Line Conducted Emission Test.....	30
5.7.4 Final Procedure of Line Conducted Emission Test.....	30
5.7.5 Test Result of Line Conducted Emission Test .....	31
APPENDIX 1 .....	33
PHOTOGRAPHS OF TEST SETUP .....	33
APPENDIX 2 .....	36
PHOTOGRAPHS OF EUT .....	36

**1. VERIFICATION OF CONFORMITY****Equipment Under Test:** MID-PTT 726**Brand Name:** N/A**Model Number:** PT07102-46-XXX, WayteQ xPAD-70**FCC ID:** ZIG-PTT726**Applicant:** Win Accord Ltd.

12F, No.225, Sec. 5, Nanjing E. Rd., Songshan Dist, Taipei City 105, Taiwan

**Manufacturer:** Win Accord Ltd.


7F, Garden City Cyber Port, Nanhui Road A, No.1079, Nanshan District, Shenzhen, China

**Technical Standards:** 47 CFR Part 15 Subpart C**File Number:** STS110317F3**Date of test:** April 20, 2011- May 16,2011**Deviation:** None**Condition of Test Sample:** Normal**Test Result:** PASS

The above equipment was tested by MOST for compliance with the requirements set forth in FCC rules and the Technical Standards mentioned above. This said equipment in the configuration described in this report shows the maximum emission levels emanating from equipment and the level of the immunity endurance of the equipment are within the compliance requirements.


The test results of this report relate only to the tested sample identified in this report.

Tested by (+ signature):




Petter Ping May 16,2011

Review by (+ signature):



July Wen May 16,2011

Approved by (+ signature):



Terry Yang May 16,2011

## 2. GENERAL INFORMATION

### 2.1 Product Information

<b>Product</b>	MID-PTT 726
<b>Trade Name</b>	N/A
<b>Model Number</b>	PT07102-46-XXX
<b>Power Supply</b>	DC 5V by AC/DC adapter 100~240V 50/60Hz
<b>Frequency Range</b>	IEEE 802.11b/g mode: 11 Channels (2412MHz – 2462MHz) IEEE 802.11n Standard-20 MHz Channel mode: 11 Channels (2412MHz – 2462MHz) IEEE 802.11n Wide-40 MHz Channel mode: 7 Channels (2422MHz – 2452MHz)
<b>Modulation Type</b>	IEEE 802.11b mode: DSSS (1, 2, 5.5 and 11 Mpbs) IEEE 802.11g mode: OFDM (6, 9, 12, 18, 24, 36, 48 and 54 Mpbs) IEEE 802.11n Standard-20 MHz Channel mode: OFDM (6.5, 13, 19.5, 26, 39, 52, 58.5, 65.0Mbps) IEEE 802.11n Wide-40 MHz Channel mode: OFDM (13.5, 27, 40.5, 54, 81, 108, 121.5, 135Mbps)
<b>Channel Number</b>	11
<b>Temperature Range</b>	-20°C ~ 55°C

**NOTE:**

1. Please refer to Appendix I for the photographs of the EUT. For a more detailed features description about the EUT, please refer to User's Manual.

## 2.2 Objective

The objective of the report is to perform tests according to 47 CFR Part 15 Subpart C for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 15 (10-1-05 Edition)	Radio Frequency Devices

## 2.3 Test Standards and Results

Test items and the results are as bellow:

No.	Section	Description	Result	Date of Test
1	15.247(b)	Peak Output Power	PASS	2011-05-10
2	15.247(a)	Bandwidth	PASS	2011-05-10
3	15.247(d)	Peak Power Spectral Density	PASS	2011-05-10
4	15.247(c)	Conducted Spurious Emission	PASS	2011-05-10
5	15.247(c)	Band Edge	PASS	2011-05-10
6	15.209 15.247(c)	Radiated Emission	PASS	2011-05-10
7	15.207	Power Line Conducted Emission Test	PASS	2011-05-12

*Note:* 1. The test result judgment is decided by the limit of measurement standard  
2. The information of measurement uncertainty is available upon the customer's request.

## 2.4 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

- Temperature: 15-35°C
- Humidity: 30-60 %
- Atmospheric pressure: 86-106 kPa

### 3. TEST FACILITY

#### 3.1 TEST FACILITY

Test Site: Most Technology Service Co.,ltd

Location: No.5, Langshan 2nd Rd., North Hi-Tech Industrial park , Nanshan Shenzhen, Guangdong ,China

Description: There is one 3m semi-anechoic an area test sites and two line conducted labs for final test. The Open Area Test Sites and the Line Conducted labs are constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2009 and CISPR 16 requirements. The FCC Registration Number is **490827**.

Site Filing: The site description is on file with the Federal Communications Commission, 7435 Oakland Mills Road, Columbia, MD 21046.

Instrument Tolerance: All measuring equipment is in accord with ANSI C63.4:2009 and CISPR 16 requirements that meet industry regulatory agency and accreditation agency requirement.

Ground Plane: Two conductive reference ground planes were used during the Line Conducted Emission, one in vertical and the other in horizontal. The dimensions of these ground planes are as below. The vertical ground plane was placed distancing 40 cm to the rear of the wooden test table on where the EUT and the support equipment were placed during test. The horizontal ground plane projected 50 cm beyond the footprint of the EUT system and distanced 80 cm to the wooden test table. For Radiated Emission Test, one horizontal conductive ground plane extended at least 1m beyond the periphery of the EUT and the largest measuring antenna, and covered the entire area between the EUT and the antenna.

#### 3.2 GENERAL TEST PROCEDURES

##### **EUT Function and Test Mode**

The EUT has been tested under normal operating (TX) and standby (RX) condition.

The field strength of radiation emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis).

The following data show only with the worst case setup.

The worst case of Y axis was reported.

Based on client request, all normal using modes of the Bluetooth function were tested but only the worst test data of the worst mode is reported by this report.

##### Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4:2009,Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4:2009.

**3.3 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS**

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	( <sup>2</sup> )
13.36 - 13.41			

<sup>1</sup> Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

<sup>2</sup> Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

**4. SETUP OF EQUIPMENT UNDER TEST****4.1 SUPPORT EQUIPMENT**

Device Type	Brand	Model	FCC ID	Series No.	Data Cable	Power Cord
---	---	---	---	---	---	---

*Remark:*

*All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.*

## 4.2 TEST EQUIPMENT LIST

**Instrumentation:** The following list contains equipment used at Most for testing. The equipment conforms to the CISPR 16-1 / ANSI C63.2 Specifications for Electromagnetic Interference and Field Strength Instrumentation from 10 kHz to 1.0 GHz or above.

No.	Equipment	Manufacturer	Model No.	S/N	Calibration due date
1	Test Receiver	Rohde & Schwarz	ESCI	100492	2012/03/14
2	L.I.S.N.	Rohde & Schwarz	ENV216	100093	2012/03/14
3	Coaxial Switch	Anritsu Corp	MP59B	6200283933	2012/03/14
4	Terminator	Hubersuhner	50Ω	No.1	2012/03/14
5	RF Cable	SchwarzBeck	N/A	No.1	2012/03/14
6	Test Receiver	Rohde & Schwarz	ESPI	101202	2012/03/14
7	Bilog Antenna	SCHWARZBECK	BBHA9120D	D69250	2012/03/14
8	Cable	Resenberger	N/A	NO.1	2012/03/14
9	Cable	SchwarzBeck	N/A	NO.2	2012/03/14
10	Cable	SchwarzBeck	N/A	NO.3	2012/03/14
11	DC Power Filter	DuoJi	DL2×30B	N/A	2012/03/14
12	Single Phase Power Line Filter	DuoJi	FNF 202B30	N/A	2012/03/14
13	3 Phase Power Line Filter	DuoJi	FNF 402B30	N/A	2012/03/14
14	Test Receiver	Rohde & Schwarz	ESCI	100492	2012/03/14
15	Absorbing Clamp	Luthi	MDS21	3635	2012/03/14
16	Coaxial Switch	Anritsu Corp	MP59B	6200283933	2012/03/14
17	AC Power Source	Kikusui	AC40MA	LM003232	2012/03/14
18	Test Analyzer	Kikusui	KHA1000	LM003720	2012/03/14
19	Line Impedance Network	Kikusui	LIN40MA-PCR-L	LM002352	2012/03/14
20	ESD Tester	Kikusui	KES4021	LM003537	2012/03/14
21	EMCPRO System	EM Test	UCS-500-M4	V0648102026	2012/03/14
22	Signal Generator	IFR	2032	203002/100	2012/03/14
23	Amplifier	A&R	150W1000	301584	2012/03/14
24	CDN	FCC	FCC-801-M2-25	47	2012/03/14
25	CDN	FCC	FCC-801-M3-25	107	2012/03/14
26	EM Injection Clamp	FCC	F-203I-23mm	403	2012/03/14
27	RF Cable	MIYAZAKI	N/A	No.1/No.2	2012/03/14
28	Universal Radio Communication Tester	ROHDE&SCHWARZ	CMU200	0304789	2012/03/14
29	Telecommunication Antenna	European Antennas	PSA 75301R/170	0304213	2012/03/14
30	Telecommunication Test Equipment	R&S	CMU200	N/A	2012/03/14

**NOTE:** Equipments listed above have been calibrated and are in the period of validation.

## 5. 47 CFR Part 15C 15.247 Requirements

### 5.1 Peak Output Power


#### 5.1.1 Requirement

According to FCC section 15.247(b)(1), for frequency hopping systems that operates in the 2400MHz to 2483.5MHz band employing at least 75 hopping channels, the maximum peak output power of the intentional radiator shall not exceed 1Watt. For all other frequency hopping systems in the 2400MHz to 2483.5MHz band, it is 0.125Watts.

#### 5.1.2 Test Description

The EUT was connected to the Spectrum Analyzer. The radio frequency load attached to the EUT antenna terminal was 50 Ohm. The loss of the cables and the test system is calibrated to correct the reading.

#### 5.1.3 Test Setup



#### 5.1.4 EUT Setup and Operating Conditions

Controlled by an embedded test program provided by applicant, the EUT was set to continuous transmitting at maximum peak output power and different data rate(802.11b 11Mbps,802.11g 54Mbps),Lowest ,middle and highest channel were measured respectively.

#### 5.1.5 Test Result

802.11b:

Channel	Frequency (MHz)	Peak Output Power (dBm)	Peak Output Power (W)	Limit (W)	Result
Low	2412	12.83	0.0192	0.125	PASS
Mid	2437	12.85	<b>0.0193</b>		PASS
High	2462	12.79	0.0190		PASS

802.11g:

Channel	Frequency (MHz)	Peak Output Power (dBm)	Peak Output Power (W)	Limit (W)	Result
Low	2412	11.45	<b>0.0140</b>	0.125	PASS
Mid	2437	11.40	0.0138		PASS
High	2462	11.36	0.0137		PASS

802.11 n-20MHz:

Channel	Frequency (MHz)	Peak Output Power (dBm)	Peak Output Power (W)	Limit (W)	Result
Low	2412	11.15	<b>0.0141</b>	0.125	PASS
Mid	2437	11.11	0.0129		PASS
High	2462	11.08	0.0128		PASS

802.11n-40MHz:

Channel	Frequency (MHz)	Peak Output Power (dBm)	Peak Output Power (W)	Limit (W)	Result
Low	2422	11.09	<b>0.0129</b>	0.125	PASS
Mid	2437	11.05	0.0127		PASS
High	2452	11.06	0.0128		PASS

## 5.2 6dB Bandwidth

### 5.2.1 Requirement


Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands.

The minimum 6 dB bandwidth shall be at least 500 kHz.

### 5.2.2 Test Description

The EUT was connected to the Spectrum Analyzer. The radio frequency load attached to the EUT antenna terminal was 50 Ohm. The loss of the cables and the test system is calibrated to correct the reading.

### 5.2.3 Test Setup



### 5.2.4 Test Procedure

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW = 100 kHz, VBW = RBW, Span = 20MHz, Sweep = auto.
4. Mark the peak frequency and -6dB (upper and lower) frequency.
5. Repeat until all the rest channels are investigated.

### 5.2.5 EUT Setup and Operating Conditions

Controlled by an embedded test program provided by applicant, the EUT was set to continuous transmitting at maximum peak output power and different data rate(802.11b 11Mbps,802.11g 54Mbps),Lowest ,middle and highest channel were measured respectively.

### 5.2.6 Test Result

802.11b:

Channel	Frequency (MHz)	Bandwidth (kHz)	Limit (kHz)	Margin (kHz)
Low	2412	12850	>500	PASS
Mid	2437	12860		PASS
High	2462	12900		PASS

## 802.11g

Channel	Frequency (MHz)	Bandwidth (kHz)	Limit (kHz)	Margin (kHz)
Low	2412	16610	>500	PASS
Mid	2437	16610		PASS
High	2462	16620		PASS

## 802.11 n-20MHz:

Channel	Frequency (MHz)	Bandwidth (kHz)	Limit (kHz)	Margin (kHz)
Low	2412	16620	>500	PASS
Mid	2437	16600		PASS
High	2462	16610		PASS

## 802.11 n-40MHz:

Channel	Frequency (MHz)	Bandwidth (kHz)	Limit (kHz)	Margin (kHz)
Low	2422	16620	>500	PASS
Mid	2437	16600		PASS
High	2452	16610		PASS

### 5.3 Power Spectrum Density


#### 5.3.1 limits of Power Spectrum Density

1. For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.
2. The direct sequence operating of the hybrid system, with the frequency hopping operation turned off, shall comply with the power density requirements of paragraph (d) of this section.

#### 5.3.2 Test Procedure

1. Place the EUT on the table and set it in transmitting mode.  
Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set the spectrum analyzer as RBW = 3kHz, VBW = 10kHz, Span = 300kHz, Sweep=100s
3. Record the max. Reading.
4. Repeat the above procedure until the measurements for all frequencies are completed.

#### 5.3.3 Test Setup



#### 5.3.4 EUT Setup and Operating Conditions

Controlled by an embedded test program provided by applicant, the EUT was set to continuous transmitting at maximum peak output power and different data rate(802.11b 11Mbps,802.11g 54Mbps),Lowest ,middle and highest channel were measured respectively.

#### 5.3.5 Test Result

802.11b:

Channel	Frequency	Peak Power Spectrum Density (dBm)	Limit (dBm)	Result
Low	2412	-26.12	8.00	PASS
Mid	2437	-26.35		PASS
High	2472	-27.06		PASS

802.11g:

Channel	Frequency	Peak Power Spectrum Density (dBm)	Limit (dBm)	Result
Low	2412	-30.58	8.00	PASS
Mid	2437	-31.43		PASS
High	2462	-31.66		PASS

802.11 n-20MHz:

Channel	Frequency	Peak Power Spectrum Density (dBm)	Limit (dBm)	Result
Low	2412	-32.46	8.00	PASS
Mid	2437	-31.28		PASS
High	2462	-32.09		PASS

802.11 n-40MHz:

Channel	Frequency	Peak Power Spectrum Density (dBm)	Limit (dBm)	Result
Low	2422	-32.51	8.00	PASS
Mid	2437	-32.79		PASS
High	2452	-33.42		PASS

## 5.4 Band Edge


### 5.4.1 Requirement of the standard

According to §15.247(c), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

### 5.4.2 Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above the ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
  - (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
  - (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.

### 5.4.3 Test Setup



### 5.4.4 EUT Setup and Operating Conditions

Controlled by an embedded test program provided by applicant, the EUT was set to continuous transmitting at maximum peak output power and different data rate(802.11b 11Mbps,802.11g 54Mbps), Lowest ,middle and highest channel were measured respectively.

### 5.4.5 Test Result

The radio frequency power beyond the band edge was 20dB below the peak output power, measured with 100 KHz resolution bandwidth.

The EUT operates at continuous transmit test mode. The peak and average test data of the lowest and highest channels are tested to verify the band edge emissions.

Test Mode		Channel Marked Frequency	Limit (dBuv/m)	Test Result Highest Emission (dBuv/m)			
				Vertical		Horizontal	
				Peak	Average	Peak	Average
802.11 b	Low Channel	2300MHz	74(Peak) 54(Average)	30.23	20.11	30.16	20.08
		2390MHz		32.12	23.26	30.45	22.19
	High Channel	2483.5MHz		46.42	40.13	46.22	40.16
		2500MHz		31.28	23.01	30.48	23.05
802.11 g	Low Channel	2300MHz	74(Peak) 54(Average)	30.15	20.26	30.04	20.01
		2390MHz		45.28	24.68	46.85	24.26
	High Channel	2483.5MHz		46.38	40.15	46.75	40.34
		2500MHz		30.69	22.45	30.53	23.26
802.11 n -20MHz	Low Channel	2300MHz	74(Peak) 54(Average)	30.36	20.51	30.24	20.12
		2390MHz		46.49	23.90	46.12	24.74
	High Channel	2483.5MHz		46.05	40.31	46.66	40.29
		2500MHz		30.82	22.48	30.54	23.35
802.11 n -40MHz	Low Channel	2300MHz	74(Peak) 54(Average)	30.23	20.14	30.25	20.12
		2390MHz		43.96	23.42	47.09	24.66
	High Channel	2483.5MHz		45.51	40.66	47.25	40.89
		2500MHz		30.44	22.76	31.46	23.94

## 5.5 Conducted Spurious Emission


### 5.5.1 Requirement of the standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

### 5.5.2 Test Procedure

1. Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.
2. The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 KHz. The video bandwidth is set to 100 KHz.
3. Measurements are made over the 30MHz to 26.5GHz range with the transmitter set to the lowest, middle, and highest channels.

### 5.5.3 Test Setup



### 5.5.4 EUT Setup and Operating Conditions

Controlled by an embedded test program provided by applicant, the EUT was set to continuous transmitting at maximum peak output power and different data rate(802.11b 11Mbps,802.11g 54Mbps),Lowest ,middle and highest channel were measured respectively.

**5.5.5 Test Result**

Channel	Frequency (MHz)	Fundamental Level (dBm)	Emission Level Limit (dBm)
802.11b Low	2412	12.83	-7.17
802.11b Mid	2437	12.85	-7.15
802.11b High	2462	12.79	-7.21
802.11g Low	2412	11.45	-8.55
802.11g Mid	2437	11.40	-8.60
802.11g High	2462	11.36	-8.64
802.11 n-20M Low	2412	11.15	-8.85
802.11 n-20M Mid	2437	11.11	-8.89
802.11 n-20M High	2462	11.08	-8.92
802.11 n-40M Low	2422	11.09	-8.91
802.11 n-40M Mid	2437	11.05	-8.95
802.11 n-40M High	2452	11.06	-8.94

NO.	Frequency	Measurement Bandwidth	Emission Level (dBm)	Limit	Margin
				dBm	dB
<b>TX:802.11 b Low Channel</b>					
1	<1000	100	\	-7.17	>20
2	4824	100	-37.45	-7.17	>20
3	7236	100	\	-7.17	>20
4	9648	100	\	-7.17	>20
5	12060	100	\	-7.17	>20
6	other	100	\	-7.17	>20
<b>TX: 802.11 b Middle Channel</b>					
1	<1000	100	\	-7.15	>20
2	4874	100	-36.86	-7.15	>20
3	7311	100	\	-7.15	>20
4	9748	100	\	-7.15	>20
5	12185	100	\	-7.15	>20
6	other	100	\	-7.15	>20
<b>TX: 802.11 b High Channel</b>					
1	<1000	100	\	-7.21	>20
2	4924	100	-37.14	-7.21	>20
3	7386	100	\	-7.21	>20
4	9848	100	\	-7.21	>20
5	12310	100	\	-7.21	>20
6	other	100	\	-7.21	>20
<b>Measurement uncertainty:±3.2dB</b>					

NO.	Frequency	Measurement Bandwidth	Emission Level (dBm)	Limit	Margin
				dBm	dB
<b>TX:802.11 g Low Channel</b>					
1	<1000	100	\	-8.55	>20
2	4824	100	-38.26	-8.55	>20
3	7236	100	\	-8.55	>20
4	9648	100	\	-8.55	>20
5	12060	100	\	-8.55	>20
6	other	100	\	-8.55	>20
<b>TX: 802.11 g Middle Channel</b>					
1	<1000	100	\	-8.60	>20
2	4874	100	-39.45	-8.60	>20
3	7311	100	\	-8.60	>20
4	9748	100	\	-8.60	>20
5	12185	100	\	-8.60	>20
6	other	100	\	-8.60	>20

<b>TX: 802.11 g High Channel</b>					
NO.	Frequency	Measurement Bandwidth	Emission Level (dBm)	Limit	Margin
	MHz	KHz		dBm	dB
1	<1000	100	\	-8.64	>20
2	4924	100	-39.68	-8.64	>20
3	7386	100	\	-8.64	>20
4	9848	100	\	-8.64	>20
5	12310	100	\	-8.64	>20
6	other	100	\	-8.64	>20

**Measurement uncertainty:±3.2dB**

NO.	Frequency	Measurement Bandwidth	Emission Level (dBm)	Limit	Margin
	MHz	KHz		dBm	dB
<b>TX:802.11 n-20MHz Low Channel</b>					
1	<1000	100	\	-8.85	>20
2	4824	100	-39.23	-8.85	>20
3	7236	100	\	-8.85	>20
4	9648	100	\	-8.85	>20
5	12060	100	\	-8.85	>20
6	other	100	\	-8.85	>20
<b>TX: 802.11 n-20MHz Middle Channel</b>					
1	<1000	100	\	-8.89	>20
2	4874	100	-39.68	-8.89	>20
3	7311	100	\	-8.89	>20
4	9748	100	\	-8.89	>20
5	12185	100	\	-8.89	>20
6	other	100	\	-8.89	>20
<b>TX: 802.11 n-20MHz High Channel</b>					
1	<1000	100	\	-8.92	>20
2	4924	100	-40.25	-8.92	>20
3	7386	100	\	-8.92	>20
4	9848	100	\	-8.92	>20
5	12310	100	\	-8.92	>20
6	other	100	\	-8.92	>20

**Measurement uncertainty:±3.2dB**

NO.	Frequency	Measurement Bandwidth	Emission Level (dBm)	Limit	Margin
	MHz	KHz		dBm	dB
<b>TX:802.11 n-40MHz Low Channel</b>					
1	<1000	100	\	-8.91	>20
2	4824	100	-39.61	-8.91	>20
3	7236	100	\	-8.91	>20
4	9648	100	\	-8.91	>20

5	12060	100	\	-8.91	>20
6	other	100	\	-8.91	>20
<b>TX: 802.11 n-40MHz Middle Channel</b>					
1	<1000	100	\	-8.95	>20
2	4874	100	-39.94	-8.95	>20
3	7311	100	\	-8.95	>20
4	9748	100	\	-8.95	>20
5	12185	100	\	-8.95	>20
6	other	100	\	-8.95	>20
<b>TX: 802.11 n-40MHz High Channel</b>					
1	<1000	100	\	-8.94	>20
2	4924	100	-40.76	-8.94	>20
3	7386	100	\	-8.94	>20
4	9848	100	\	-8.94	>20
5	12310	100	\	-8.94	>20
6	other	100	\	-8.94	>20
<b>Measurement uncertainty:±3.2dB</b>					

*Note: Data of measurement within this frequency range shown “\ ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*

## 5.6 Radiated Emission Test

### 5.6.1 Requirement

According to FCC section 15.247(c), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ( $\mu$ V/m)	Measurement Distance (m)
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

**Remark:** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.


In the above emission table, the tighter limit applies at the band edges.

Frequency (MHz)	Field Strength ( $\mu$ V/m)	Measurement Distance (m)
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3


### 5.6.2 Test Description

#### Test Setup:

##### Below 1GHz:



##### Above 1GHz:



### 5.6.3 Test Description

### 5.6.4 Test Result

#### Below 1 GHz:

<b>Operation Mode:</b>	Operationg Mode	<b>Test Date:</b>	2010-05-10
<b>Temperature:</b>	20°C	<b>Tested by:</b>	Petter Ping
<b>Humidity:</b>	70 % RH	<b>Polarity:</b>	Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
--	V	--	--	--	--	--	--	--	>20	Peak
N/A										
<hr/>										
--	H	--	--	--	--	--	--	--	>20	Peak
N/A										

#### Note:

1. The emission behaviour belongs to narrowband spurious emission.
2. Remark"---"means that the emission level is too low to be measured
3. The frequency is mainly from the environment noise.

**Above 1 GHz**

**Operation Mode:** Operationg Mode      **Test Date:** 2010-05-10  
**Temperature:** 20°C      **Tested by:** Petter Ping  
**Humidity:** 70 % RH      **Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
4860.02	V	30.45	--	8.24	38.69	--	74.00	54.00	-15.31	Peak
N/A									>20	
4860.02	H	29.64	--	8.24	37.88	--	74.00	54.00	-16.12	Peak
N/A									>20	

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
  - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
  - b. AV Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms

40cm

80cm

Communication  
Antenna

FCC ID: ZIG-PTT726

EUT

>80cm

Report No.: MOST110317F3

## 5.7 Power Line Conducted Emission Test


### 5.7.1 Limits of Line Conducted Emission Test

Frequency	LISN		
	Q.P.( dBuV)	Receiver	Average( dBuV)
150kHz-500kHz	66-56		56-46
500kHz-5MHz	56	System	46
5MHz-30MHz	60	Simulator	50

**\*\*Note:** 1. the lower limit shall apply at the transition frequency.

2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz

### 5.7.2 Block Diagram of Test Setup



### 5.7.3 Preliminary Procedure of Line Conducted Emission Test

- 1) The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per FCC Part 15 (see Test Facility for the dimensions of the ground plane used). When the EUT is floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2) Support equipment, if needed, was placed as per FCC Part 15.
- 3) All I/O cables were positioned to simulate typical actual usage as per FCC Part 15.
- 4) The EUT received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5) All support equipments received power from a second LISN supplying power of AC 120V/60Hz, if any.
- 6) The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7) Analyzer / Receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes.
- 8) During the above scans, the emissions were maximized by cable manipulation.
- 9) The following test mode(s) were scanned during the preliminary test:

Preliminary Conducted Emission Test				
Frequency Range Investigated		150KHz TO 30 MHz		
Mode of operation	Date	Report No.	Data#	Worst Mode
WiFi Mode	2011-05-12	STS110317F3	1_(L, N)	<input checked="" type="checkbox"/>

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

### 5.7.4 Final Procedure of Line Conducted Emission Test

EUT and support equipment was set up on the test bench as per step 9 of the preliminary test. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less -2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector. The test data of the worst case condition(s) was reported on the Summary Data page.

## 5.7.5 Test Result of Line Conducted Emission Test



Address: No.5, Langshan 2nd Rd., North Hi-Tech Industrial park  
Guangdong, China  
Tel: 0755-86170306 Fax: 0755-86170310


## Conducted Emission Measurement

File: PT07102-46-XXX

Data #11

Date: 2011/05/12

Time: 22:49:06



Site: site #1

Phase: L1

Temperature: 26

Limit: FCC Part15 B Class B QP

Power: AC 120V/60Hz

Humidity: 60 %

EUT: MID-PTT 726

M/N: PT07102-46-XXX

Mode: FULL LOAD

Note: GP302U-050-200

No.	Mlk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dB			
1	*	0.2340	40.63	11.77	52.40	62.31	-9.91	peak	
2		0.3420	34.36	11.05	45.41	59.15	-13.74	peak	
3		1.4420	26.59	9.56	36.15	56.00	-19.85	peak	
4		2.9700	20.94	9.97	30.91	56.00	-25.09	peak	
5		8.4860	17.75	9.91	27.66	60.00	-32.34	peak	

\*:Maximum data x:Over limit !:over margin



Address: No.5, Langshan 2nd Rd., North Hi-Tech Industrial park  
Guangdong, China  
Tel: 0755-86170306 Fax: 0755-86170310


## Conducted Emission Measurement

File: PT07102-46-XXX

Data #6

Date: 2011/05/12

Time: 22:34:18



Site: site #1

Phase: *N*

Temperature: 26

Limit: EN55022 Class B QP

Power: AC 230V/50Hz

Humidity: 60 %

EUT: MID-PTT 726

M/N: PT07102-46-XXX

Mode: FULL LOAD

Note: ADS-12G-06 05010GP

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
1	*	0.1540	48.00	9.24	57.24	65.78	-8.54	peak	
2		0.1860	44.08	11.16	55.24	64.21	-8.97	peak	
3		0.9420	29.41	10.00	39.41	56.00	-16.59	peak	
4		2.9780	20.99	9.98	30.97	56.00	-25.03	peak	
5		6.8020	22.29	10.92	33.21	60.00	-26.79	peak	


\*:Maximum data    x:Over limit    !:over margin


**APPENDIX 1**  
**PHOTOGRAPHS OF TEST SETUP**

CONDUCTED EMISSION TEST SETUP



RADIATED EMISSION TEST SETUP





**APPENDIX 2**  
**PHOTOGRAPHS OF EUT**

FRONT VIEW OF SAMPLE



BACK VIEW OF SAMPLE



LEFT VIEW OF SAMPLE



RIGHT VIEW OF SAMPLE



TOP VIEW OF SAMPLE




BOTTOM VIEW OF SAMPLE



PHOTO OF POWER SUPPLY



INTERNAL PHOTO OF SAMPLE – 1




INTERNAL PHOTO OF SAMPLE – 2




INTERNAL PHOTO OF SAMPLE -3




INTERNAL PHOTO OF SAMPLE-4



INTERNAL PHOTO OF SAMPLE-5



INTERNAL PHOTO OF ADAPTER-1



INTERNAL PHOTO OF ADAPTER-2



----END OF REPORT----