# FCC TEST REPORT

for

Nanjing Panda Information Industry Co., Ltd.

Tablet Model No.: R70B200

Prepared for : Nanjing Panda Information Industry Co., Ltd.

Address : East of 2F, 17 Building, 301 East Zhongshan Road, Nanjing

P.R.China

Prepared By : Anbotek Compliance Laboratory Limited

Address : 1/F, 1 /Building, SEC Industrial Park, No.4 Qianhai Road,

Nanshan District, Shenzhen, 518054, China

Tel: (86) 755-26014771 Fax: (86) 755-26014772

Report Number : 201106810F

Date of Test : Jun. 30~Jul.09, 2011

Date of Report : Jul. 11, 2011

# TABLE OF CONTENT

# Description

Page Test Report 1. GENERAL INFORMATION......4 1.1. Description of Device (EUT).......4 1.2. Auxiliary Equipment Used during Test......5 1.3. Description of Test Facility .......6 2. MEASURING DEVICE AND TEST EQUIPMENT......7 3. TEST METHODOLOGY ....... 3.3. List of channels: 4.5. Test Procedure \_\_\_\_\_\_\_\_11 5. FCC PART 15.247 REQUIREMENTS FOR DSSS & OFDM MODULATION....... 14 5.1 Test Setup 14 5.6 Radiated Emissions 31 5.6.2. Test Configuration: 31 

APPENDIX I (Photos of EUT) (7 Pages)

# **TEST REPORT**

Applicant : Nanjing Panda Information Industry Co., Ltd.

Manufacturer : Nanjing Panda Information Industry Co., Ltd.

EUT : Tablet

Model No. : R70B200

Serial No. : N/A

Rating : 5V==, 2.0A

Trade Mark : N/A

Measurement Procedure Used:

Approved & Authorized Signer:

FCC Part15 Subpart C, Paragraph 15.247: 2010

The device described above is tested by Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Anbotek Compliance Laboratory Limited

Date of Test:	Jun. 30~Jul.09, 2011					
Prepared by :						
	Zock reng					
	(Engineer / Rock Zeng)					
Reviewer :						
	Coa. Kiang					
	(Project Manager / Coco Xiang)					

(Manager / Tom Chen)

# 1. GENERAL INFORMATION

# 1.1. Description of Device (EUT)

EUT : Tablet(Wireless Network Card only)

Model Number : R70B200

Test Power Supply:  $120V\sim$ , 60Hz for Adapter

Switching Adapter: Model: ADS-12G-06 05010GPCU

Input: 100~240V~ 50/60Hz Max. 0.3A

Output: 5V == 2.0A

UL, FCC

**RF** Transmission

Frequency

: 2412-2462MHz(802.11b/g/n HT20)

Channels : 11

Antenna Gain : 3.4dBi

Antenna Type : Internal antenna

Applicant : Nanjing Panda Information Industry Co., Ltd.

Address : East of 2F, 17 Building, 301 East Zhongshan Road, Nanjing

P.R.China

Manufacturer : Nanjing Panda Information Industry Co., Ltd.

Address : East of 2F, 17 Building, 301 East Zhongshan Road, Nanjing

P.R.China

Date of receiver : Jun. 30, 2011

Date of Test : Jun. 30~Jul.09, 2011

# 1.2. Auxiliary Equipment Used during Test

DESCRIPTION	MANUFACTURER	MODEL NO.(SHIELD)	S/N(LENGTH)
Monitor	Lenovo	X61	L3-L3729 08/03
Earphone	Ouyun	OH601	
SD card	Kingston	SD4/4GBFE	
USB flash drive	Kingston	USB/4GB	

Signal Cable Type	Signal cable Description
HDMI Cable	Shielded, 2.0m, with two ferrite cores bonded.
Earphone Cable	Non-Shielded, 2.0m
USB Cable	Non-Shielded, 0.5m

# 1.3. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

### **CNAS - LAB Code: L3503**

Anbotek Compliance Laboratory Limited., Laboratory has been assessed and in compliance with CNAS/CL01: 2006 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of Testing Laboratories.

### FCC-Registration No.: 752021

Anbotek Compliance Laboratory Limited, EMC Laboratory has been registed and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 752021, August 20, 2010.

# IC-Registration No.: 8058A-1

Anbotek Compliance Laboratory Limited., EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration 8058A, August 30, 2010.

### **Test Location**

All Emissions tests were performed at

Anbotek Compliance Laboratory Limited. at 1/F, 1 /Building, SEC Industrial Park, No.4 Qianhai Road, Nanshan District, Shenzhen, 518054, China

# 1.4. Measurement Uncertainty

Radiation Uncertainty : Ur = 4.3dB

Conduction Uncertainty : Uc = 3.4dB

# 2. MEASURING DEVICE AND TEST EQUIPMENT

The following test equipments were used during test:

The following	s test equipments w	cic uscu dui	ing test.		
Equipment	Manufacturer	Model #	Serial #	Data of Cal.	<b>Due Data</b>
EMI Test Receiver	Rohde & Schwarz	ESCI	100119	Mar.03, 2011	Mar.02, 2012
EMI Test Receiver	Rohde & Schwarz	ESIB26	100249	Sep.22, 2010	Sep.21, 2011
EMI Test Software	SHURPLE	ESK1	N/A	N/A	N/A
Spectrum Analyzer	Agilent	E7405A	MY45114970	Jun.21, 2011	Jun.20, 2012
Signal Generator	Rohde & Schwarz	SMR27	100124	Jul.06, 2010	Jul.05, 2012
Signal Generator	Rohde & Schwarz	SML03	102319	Aug.01, 2010	Aug.01, 2012
AC Power Source	Sepcial power system	YF650	N/A	N/A	N/A
Absorbing Clamp	Rohde & Schwarz	MDS21	100218	Apr.30, 2010	Apr.29, 2012
Power Meter	Rohde & Schwarz	NRVD	101287	Jul.19, 2009	Jul.18, 2011
Coaxial Cable	N/A	N/A	N/A	May.31, 2011	May.30, 2012
Coaxial Cable	N/A	N/A	N/A	May.31, 2011	May.30, 2012
Coaxial Cable	N/A	N/A	N/A	May.31, 2011	May.30, 2012
Universal radio					
Communication	Rohde & Schwarz	CMU200	101724	Sep.08, 2009	Sep.07, 2011
tester					
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	N/A	N/A	N/A
BiConilog Antenna	ETS-LINDGREN	3142C	00042670	Mar.03, 2011	Mar.02, 2012
BiConilog Antenna	ETS-LINDGREN	3142C	00042673	Mar.03, 2011	Mar.02, 2012
Loop Antenna	ETS-LINGREN	6502	00071730	Mar.03, 2011	Mar.02, 2012
Double-ridged	ETS-LINDGREN	3117	00035926	Dec.30, 2009	Dec.29, 2011
Waveguide horn	L15-LINDOKEN	3117	00033720	Dec.30, 2007	Dec.29, 2011
Double-ridged	ETS-LINDGREN	3117	00041545	Dec.30, 2009	Dec.29, 2011
Waveguide horn	E15-LINDOKEN	3117	00041545	Dec.30, 2009	Dec.29, 2011
Pre-amplifier	CD	PAM0203	804203	Jun.21, 2011	Jun.20, 2012
RF Switch	CD	RSU-M3	706543	Jun.21, 2011	Jun.20, 2012
Thermo-/Hygrometer	N/A	TH01	N/A	May.03, 2011	May.02, 2012
Shielding Room	Zhong Yu Electronic	N/A	N/A	N/A	N/A
3m Anechoic Chamber	Zhong Yu Electronic	N/A	N/A	Apr.28, 2010	Apr.27, 2012

# 3. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4: 2003 and FCC Part 15, Paragraph 15.247

# 3.1. Summary of Test Results

The EUT has been tested according to the following specifications:

Standard	Test Type	Result	Notes
FCC Part 15, Paragraph 15.107, 15.207	Conducted Emission Test	PASS	Complies
FCC Part 15, Paragraph 15.247(b)(1)	Peak Output Power	PASS	Complies
FCC Part 15, Paragraph 15.247(a)(2)	6dB Bandwidth	PASS	Complies
FCC Part 15, Paragraph 15.247(c)	100kHz Bandwidth of Frequency Band Edges	PASS	Complies
FCC Part 15, Paragraph 15.209(a)(f)	Spurious Emission	PASS	Complies
FCC Part 15, Paragraph 15.247(a)(1)	Frequency Separation	-	N/A
FCC Part 15, Paragraph 15.247(a)(1)(iii)	Number of Hopping Frequency	-	N/A
FCC Part 15, Paragraph 15.247(a)(1)(iii)	Time of Occupancy	-	N/A
FCC Part 15, Paragraph 15.247(c)	Peak Power Density	PASS	Complies

<sup>\*</sup> The digital circuit porting of the EUT has been tested and verified to comply with FCC Part 15, Subpart B., Class B Digital Devices and the associated Radio Receiver has also been tested and found to comply with FCC Part 15, Subpart B – Radio Receivers.

# 3.2. Description of Test Modes

The EUT has been tested under operating condition.

Software used to control the EUT for staying in continuous transmitting and receiving mode isprogrammed.

IEEE802.11b: Channel 1(2412MHz), Channel 6(2437MHz) and Channel 11(2462MHz) with 1Mbps highest data rate (worst case) are chosen for the final testing.

IEEE802.11g: Channel 1(2412MHz), Channel 6(2437MHz) and Channel 11(2462MHz) with 6Mbps data rate (the worst case) are chosen for the final testing.

IEEE802.11n HT20: Channel 1(2412MHz), Channel 6(2437MHz) and Channel 11(2462MHz) with 6.5Mbps data rate (the worst case) are chosen for the final testing.

# 3.3. List of channels:

√ - available


X - tested

Number	Frequency(MHz)	802.11 b/g/	n HT20
1	2412	√	X
2	2417	√	
3	2422	√	
4	2427	√	
5	2432	√	
6	2437	√	X
7	2442	√	
8	2447	√	
9	2452	√	
10	2457	√	
11	2462	√	X

# 4. Conducted Emission Test

# 4.1. Block Diagram of Test Setup

4.1.1. Block diagram of connection between the EUT and simulators



(EUT: Tablet)

# 4.2. Power Line Conducted Emission Measurement Limits (15.207)

Frequency	Limits dB(μV)			
MHz	Quasi-peak Level	Average Level		
0.15 ~ 0.50	66 ~ 56*	56 ~ 46*		
0.50 ~ 5.00	56	46		
5.00 ~ 30.00	60	50		

Notes: 1. \*Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

# 4.3. Configuration of EUT on Measurement

The following equipments are installed on Power Line Conducted Emission Measurement to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

EUT : Tablet Model Number : R70B200

Applicant : Nanjing Panda Information Industry Co., Ltd.

# 4.4. Operating Condition of EUT

- 4.4.1. Setup the EUT and simulator as shown as Section 4.1.
- 4.4.2. Turn on the power of all equipment.
- 4.4.3. Let the EUT work in test mode (ON) and measure it.

# 4.5. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.4-2009 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9KHz.

The frequency range from 150KHz to 30MHz is checked.

The test results are reported on Section 4.6.

# 4.6. Power Line Conducted Emission Measurement Results **PASS.**

The frequency range from 150KHz to 30 MHz is investigated.

Please refer the following pages.

# CONDUCTED EMISSION TEST DATA

EUT: Tablet M/N: R70B200

**Operating Condition:** On


Test Site: 1# Shielded Room

Operator: Well Wang

**Test Specification:** AC 120V/60Hz for Adapter

Comment: Live Line

Tem:25℃ Hum:50%



# MEASUREMENT RESULT: "NJ110630101 fin"

0/2011 10: Frequency MHz	47AM Level dBμV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.298500	49.00	10.2	60	11.3	QP	L1	GND
0.532500	43.10	10.2	56	12.9	QP	L1	GND
0.609000	42.50	10.2	56	13.5	QP	L1	GND
1.266000	41.40	10.3	56	14.6	QP	L1	GND
2.175000	39.50	10.4	56	16.5	QP	L1	GND
4.129500	38.10	10.5	56	17.9	QP	L1	GND

# MEASUREMENT RESULT: "NJ110630101 fin2"

6,	/30/2011 10: Frequency		Transd	Limit	Margin	Detector	Line	PE
	MHZ	dΒμV	dB	dΒμV	dB			
	0.298500	30.50	10.2	50	19.8	AV	L1	GND
	0.316500	34.10	10.2	50	15.7	AV	L1	GND
	0.357000	30.20	10.2	49	18.6	AV	L1	GND
	0.604500	27.70	10.2	46	18.3	AV	L1	GND
	0.802500	28.20	10.2	46	17.8	AV	L1	GND
	4.764000	27.40	10.5	46	18.6	AV	L1	GND

# CONDUCTED EMISSION TEST DATA

EUT: Tablet M/N: R70B200

Operating Condition: On

Test Site: 1# Shielded Room

Operator: Well Wang


Test Specification: AC 120V/60Hz for Adapter

Comment: Neutral Line

Tem:25℃ Hum:50%

# SCAN TABLE: "Voltage (150K~30M) FIN"

Short Description: 150K-30M Disturbance Voltages



# MEASUREMENT RESULT: "NJ110630102 fin"


6/30/2011 10	:52AM						
Frequency	Level	Transd	Limit	Margin	Detector	Line	PE
MHz	dΒμV	dB	dΒμV	dB			
0.321000	45.50	10.2	60	14.2	QP	N	GND
0.384000	42.20	10.2	58	16.0	QP	N	GND
0.627000	38.80	10.2	56	17.2	QP	N	GND
1.023000	38.80	10.3	56	17.2	QP	N	GND
2.202000	36.60	10.4	56	19.4	QP	N	GND
4.755000	38.10	10.5	56	17.9	QP	N	GND

# MEASUREMENT RESULT: "NJ110630102 fin2"

6/30/2011 10: Frequency MHz	52AM Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.321000	30.50	10.2	50	19.2	AV	N	GND
0.384000	28.80	10.2	48	19.4	AV	N	GND
0.586500	24.30	10.2	46	21.7	AV	N	GND
1.243500	24.40	10.3	46	21.6	AV	N	GND
1.486500	24.10	10.4	46	21.9	AV	N	GND
4.755000	27.50	10.5	46	18.5	AV	N	GND

# 5. FCC Part 15.247 Requirements for DSSS & OFDM Modulation

# 5.1 Test Setup



# 5.2 6dB Bandwidth

### a. Limt

For the direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz.

### **b.** Test Procedure

- 1. Place the EUT on the table and set it in the transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set the spectrum analyzer as RBW = 100kHz, VBW = RBW, Span = 50MHz, Sweep = auto.
- 4. Mark the peak frequency and –6dB (upper and lower) frequency.
- 5. Repeat until all the rest channels are investigated.

### c. Test Setup

See 5.1

### d. Test Results

Pass

# e. Test Data


Test mode: IEEE 802.11b


Channel	Frequency	Bandwidth	Limit	Results
Chamiei	(MHz)	(MHz)	(kHz)	Resuits
Low	2412	10.10		Pass
Mid	2437	10.00	>500	Pass
High	2462	10.00		Pass
Test mode: IEEE 802.11g				
Channel	Frequency	Bandwidth	Limit	Results
Chamiei	(MHz)	(MHz)	(kHz)	Results
Low	2412	16.30		Pass
Mid	2437	16.40	>500	Pass
High	2462	16.60		Pass
Test mode: IEEE 802.11n H	T20			
Channel	Frequency	Bandwidth	Limit	Results
Chamiei	(MHz)	(MHz)	(kHz)	Results
Low	2412	17.60		Pass
Mid	2437	17.70	>500	Pass
High	2462	17.70		Pass

### f. Test Plots

See the following page.














Test Mode: 802.11g---Mid




















# 5.3 Maximum Peak output power test

#### a. Limt

The maximum peak output power of the intentional radiator shall not exceed the following:

- 1. For systems using digital modulation in the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz: 1 watt (30dBm).
- 2. Except as shown in paragraphs (b)(3) (i), (ii) and (iii) of this section, if transmitting antenna of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### b. Configuration of Measurement



### c. Test Procedure

The EUT was setup to ANSI C63.4, 2003; tested to DTS test procedure of Oct 2007 KDB558074 for compliance to FCC 47CFR 15.247 requirements. For FCC §15.247(b) the power output was measured on the EUT using a 50 ohm SMA cable connected to peak power meter via power sensor. Peak output power was read directly from power meter. The test was performed at 3 channels (lowest, middle and highest).

### d. Test Results

Pass

### e. Test Data

Test mode: IEEE 802.11b

Chamal	Frequency	Maximum tra	ansmit power	Li	mit	D a gult
Channel	(MHz)	(dBm)	(watts)	(dBm)	(watts)	Result
Low	2412	6.21	0.00418			Pass
Mid	2437	6.35	0.00432	30	1	Pass
High	2462	5.44	0.00350			Pass

Test mode: IEEE 802.11g

Channel	Frequency	Maximum tra	ansmit power	Li	mit	Result
Chamiei	(MHz)	(dBm)	(watts)	(dBm)	(watts)	Result
Low	2412	3.53	0.00225			Pass
Mid	2437	6.12	0.00409	30	1	Pass
High	2462	4.24	0.00265	]		Pass

Test mode: IEEE 802.11n HT20

Chammal	Frequency	Maximum tra	ansmit power	Li	mit	Dagult
Channel	(MHz)	(dBm)	(watts)	(dBm)	(watts)	Result
Low	2412	8.83	0.00764			Pass
Mid	2437	9.58	0.00908	30	1	Pass
High	2462	8.79	0.00757			Pass

# 5.4 Band Edges Measurement


### a. Limt

According to §15.247(c), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in15.209(a).

### **b.** Test Procedure

- 1. The EUT is placed on a turntable, which is 0.8m above the ground plane.
- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
- 4. Peak detector: RBW=100KHz, VBW=100KHz, SWT=AUTO Average detector: RBW=1MHz, VBW=10Hz, SWT=AUTO The EUT is tested in 9\*6\*6 Chamber.
- 5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.

# c. Test Setup



### d. Test Results

Pass


### e. Test Data


Test mode: IEEE 802.11b


Channel	Restrict Freq. Band (MHz)	Detector Mode	Maximum level (dBμV/m)	Limit (dBm)	Margin (dB)
Low	2310~2390	PK	56.02	74	-17.98
		AV	40.50	54	-13.50
High	2483.5~2500	PK	56.70	74	-17.30
		AV	40.60	54	-13.60
Test mode: I	EEE 802.11g	•		•	•
Channel	Restrict Freq. Band	Detector Mode	Maximum level	Limit	Margin
	(MHz)		$(dB\mu V/m)$	(dBm)	(dB)
Low	2310~2390	PK	60.62	74	-13.38
		AV	44.00	54	-10.00
High	2483.5~2500	PK	63.60	74	-10.40
		AV	44.80	54	-9.20
Test mode: I	EEE 802.11n HT20				
Channel	Restrict Freq. Band	Detector Mode	Maximum level	Limit	Margin
	(MHz)		$(dB\mu V/m)$	(dBm)	(dB)
Low	2310~2390	PK	66.10	74	-7.90
		AV	48.60	54	-5.40
High	2483.5~2500	PK	65.34	74	-8.66
		AV	48.30	54	-5.70


### f. Test Plots

See the following page.











Center 2.326 GHz






20 MHz/

Span 200 MHz





# 5.5 Peak Power Spectral Density

### a. Limt

- 1. For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.
- 2. The direct sequence operating of the hybrid system, with the frequency hopping operation turned off, shall comply with the power density requirements of paragraph (d) of this section.

### **b.** Test Procedure

- 1. Place the EUT on the table and set it in transmitting mode. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 2. Set the spectrum analyzer as RBW = 3kHz, VBW = 10kHz, Span = 1.5MHz, Sweep=500s
- 3. Record the max. reading.
- 4. Repeat the above procedure until the measurements for all frequencies are completed.

### c. Test Setup

See 5.1

### d. Test Results

Pass

### e. Test Data

Test mode: IEEE 802.11b


Channel	Frequency	PPSD(average)	$\Sigma$ PPSD	Limit	Margin	Result
Chamiei	(MHz)	(dBm)	(dBm)	(dBm)	(dB)	Result
Low	2412	-5.21	-		-13.21	Pass
Mid	2437	-4.45	-	8.00	-12.45	Pass
High	2462	-4.62	-		-12.62	Pass
Test mode: IEEE	802.11g					
Channel	Frequency	PPSD(average)	$\Sigma$ PPSD	Limit	Margin	Result
Chainei	(MHz)	(dBm)	(dBm)	(dBm)	(dB)	Resuit
Low	2412	-7.57	-		-15.57	Pass
Mid	2437	-7.00	-	8.00	-15.00	Pass
High	2462	-6.07	-		-14.07	Pass
Test mode: IEEE	802.11n HT20					
Channel	Frequency	PPSD(average)	$\Sigma$ PPSD	Limit	Margin	Result
Chamiei	(MHz)	(dBm)	(dBm)	(dBm)	(dB)	Resuit
Low 2412		-6.97	-2.17 *		-10.17	Pass
Mid 2437		-7.51	-2.71 *	8.00	-10.71	Pass
High			-1.96 *		-9.96	Pass

<sup>\*</sup> with 4.8dB correction factor


### f. Test Plot

See the following pages


802.11 b CH--Low




### CH--Mid









# 802.11g CH--Low




### CH--Mid











### CH--Mid



# CH--High



# 5.6 Radiated Emissions

# 5.6.1. Requirements (15.209 & 15.205):

# 5.6.1.1. Test Limits (< 30 MHZ)

Frequency	Field Strength	Measurement Distance
(MHz)	(microvolts/meter)	(meters)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30


### 5.6.1.2. Test Limits ( $\geq$ 30 MHZ)

FIELD STRENGTH	FIELD STRENGTH	S15.209	
of Fundamental:	of Harmonics	30 - 88 MHz	40 dBuV/m @3M
902-928 MHZ		88 - 216 MHz	43.5
2.4-2.4835 GHz		216 - 960 MHz	46
$94 dB\mu V/m @3m$	$54 dB\mu V/m @3m$	ABOVE 960 MHz	54dBuV/m


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

# 5.6.2. Test Configuration:


# 5.6.2.1. 9k to 30MHz emissions:



### 5.6.2.2. 30M to 1G emissions:



# 5.6.2.3. 1G to 40G emissions:



# 5.6.3. Test Procedure

The EUT is placed on a turn table which is 0.8 meter high above the ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.

Measurements are made on 9KHz to 30MHz and 30MHz to 26GHz range with the transmitter set to the lowest, middle, and highest channels.

All readings from 30MHz to 1GHz are quasi-peak values with a resolution bandwidth of 120kHz. All reading are above 1GHz, peak & average values with a resolution bandwidth of 1MHz. The EUT is tested in 9\*6\*6 Chamber.

The test results are listed in Section 5.6.4.

# 5.6.4. Test Results

### **Below 30MHz**

There is no emissions were detected below 30MHz

# From 30MHz to 1 GHz

Operation Mode: Normal link
Test Date: May 04, 2011
Temperature: 25°C
Tested by: Rock Zeng
Humidity: 70 % RH
Polarity: Ver. / Hor.

Hummarty. 70	70 1111					1 Olality. VC	71. / 1101.
Freq.	Ant.Pol.	Detector	Detector	Factor	Actual FS	Limit 3m	Safe
(MHz)			Mode	(dB)	(dBuV/m)	(dBuV/m)	Margin
		(PK/QP)	(PK/QP)				(dB)
166.650	V	Peak	53.40	-15.40	38.00	43.50	-5.50
333.686	V	Peak	53.93	-13.17	40.76	46.00	-5.24
399.166	V	Peak	49.39	-8.58	40.81	46.00	-5.19
421.020	V	Peak	49.40	-8.13	41.47	46.00	-4.73
490.000	V	Peak	47.46	-7.56	40.90	46.00	-6.10
638.180	V	Peak	44.33	-4.84	40.49	46.00	-6.51
142.050	Н	Peak	54.52	-16.59	37.93	43.50	-5.57
161.460	Н	Peak	55.42	-15.01	40.41	43.50	-3.09
178.950	Н	Peak	54.44	-14.78	39.66	43.50	-3.84
324.500	Н	Peak	51.42	-10.15	41.27	46.00	-4.73
330.666	Н	Peak	50.46	-9.87	41.59	46.00	-5.41
598.716	Н	Peak	45.62	-5.68	39.94	46.00	-6.06

#### Notes:

- 1. Measuring frequencies from 30 MHz to the 1GHz and the IF bandwidth of SPA between 30MHz to 1GHz was 100kHz.
- 2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak/Quasi-peak detector mode.

<sup>3.</sup> Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Test Date: May 04, 2011

### Above 1 GHz

Operation Mode: TX / IEEE 802.11b / CH Low

Temperature: 25°C Tested by: Rock Zeng Humidity: 70 % RH Polarity: Ver. / Hor.

eq. Ant.Po. H/V  Hz) H/V  H H  H H  H	Level (dBuV) 47.86 40.05 43.87	Factor (dB)  35.76  35.76  37.85	Loss (dB) 4.58 4.58	Factor (dB) 34.94	Peak (dBuV/) 53.26	AV (dBuV/)	Peak Limit (dBuV/)	(dBuV/)	(dB)	Remark Peak
4 H ) H	40.05	35.76			53.26		74.00	54.00	-20.74	Peak
) Н			4.58	24.04					20.7.	Loun
+	43.87	27.05		34.94		45.46	74.00	54.00	-8.54	AVG
) II		37.83	5.63	35.25	52.09		74.00			Peak
3 H	43.61	39.39	6.34	35.70	53.64		74.00			Peak
60 H										
72 H										
34 H										
96 H										
08 H										
20 H										
7	H H H H H H H H H H H H H H H H H H H	72 H 64 H 66 H 68 H 60 H	H	12	12		12			C    H

1.	4824	V	48.08	35.13	4.58	34.94		52.85	74.00	54.00	-1.15	AVG
2.	4824	V	52.06	35.13	4.58	34.94	56.83		74.00	54.00	-17.17	Peak
3.	7240	V	44.07	36.90	5.63	35.25	51.34		74.00			Peak
4.	9648	V	45.05	38.57	6.34	35.70	54.26		74.00			Peak
5.	12060	V										
6.	14472	V										
7.	16884	V										
8.	19296	V										
9.	21708	V										
10.	24120	V										

Note: An item 3 and 4 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emission

8.

9.

10.

19496

21933

24370

V

V

V

---

---

Operation Mode: TX / IEEE 802.11b / CH Mid

Test Date: May 04, 2011 Temperature: 25°C Tested by: Rock Zeng Humidity: 70 % RH Polarity: Ver. / Hor.

	Humidity	<u>/: /0 %</u>	KH						1	Polari	ity: Ver.	/ Hor.
Item	Freq.	Ant.Pol	Read	Antenna	Cable	Preamp	Le	vel	Peak Limi	AV Limit	Margin	
	(MHz)	H/V	Level (dBuV)	Factor (dB)	Loss (dB)	Factor (dB)	Peak (dBuV/)	AV (dBuV/)	(dBuV/)	(dBuV/)	(dB)	Remark
1.	4874	Н	41.19	35.83	4.61	34.93		46.70	74.00	54.00	-7.30	AVG
2.	4874	Н	48.76	35.83	4.61	34.93	54.28		74.00	54.00	-19.72	Peak
3.	7311	Н	42.70	37.86	5.64	35.26	50.94		74.00	54.00	-3.06	Peak
4.	9748	Н	43.24	39.51	6.36	35.70	53.40		74.00			Peak
5.	12185	Н										
6.	14622	Н										
7.	17059	Н										
8.	19496	Н										
9.	21933	Н										
10.	24370	Н										
Note:	An item 4	are on ur	n-restricted	band, so the	e limit is	-20dB for	the field str	rength of the	e fundament	al emission		
1.	4874	V	48.00	35.18	4.61	34.93		52.87	74.00	54.00	-1.13	AVG
2.	4874	V	52.14	35.18	4.61	34.93	57.01		74.00	54.00	-16.99	Peak
3.	7311	V	43.32	36.92	5.64	35.26	50.62		74.00	54.00	-3.38	Peak
4.	9748	V	43.69	38.71	6.36	35.70	53.05		74.00			Peak
5.	12185	V										
6.	14622	V										
7.	17059	V										

Note: An item 4 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emission

---

---

---

---

---

---

---

---

---

---

---

24620

Operation Mode: TX / IEEE 802.11b / CH High

Test Date: May 04, 2011 Temperature: 25°C Tested by: Rock Zeng Humidity: 70 % RH Polarity: Ver. / Hor.

	Trainiaity	. 70 /0	1111							1 01411	ity. VCI.	, 1101.
Item	Freq. (MHz)	Ant.Pol H/V	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Le Peak (dBuV/)	vel AV (dBuV/)	Peak Limit (dBuV/)	AV Limit (dBuV/)	Margin (dB)	Remark
1.	4924	Н	40.50	35.90	4.68	34.92		46.16	74.00	54.00	-7.84	AVG
2.	4924	Н	48.77	35.90	4.68	34.92	54.43		74.00	54.00	-19.57	Peak
3.	7386	Н	42.66	37.88	5.65	35.28	50.91		74.00	54.00	-3.09	Peak
4.	9848	Н	43.86	39.61	6.38	35.70	54.15		74.00			Peak
5.	12310	Н										
6.	14772	Н										
7.	17234	Н										
8.	19696	Н										
9.	22158	Н										
10.	24620	Н					1					
Note:	An item 4	are on un	-restricted	band, so the	e limit is	-20dB for	the field str	rength of the	e fundament	al emission		
1.	4924	V	51.81	35.23	4.68	34.92	56.80		74.00	54.00	-17.20	Peak
2.	4924	V	47.64	35.23	4.68	34.92		52.63	74.00	54.00	-1.37	AVG
3.	7386	V	43.40	36.96	5.65	35.28	50.73		74.00	54.00	-3.27	Peak
4.	9848	V	43.65	38.81	6.38	35.70	53.14		74.00			Peak
5.	12310	V										
6.	14772	V										
7.	17234	V										
8.	19696	V										
9.	22158	V										

Note: An item 4 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emission

Operation Mode: TX / IEEE 802.11g / CH Low

Test Date: May 04, 2011 Temperature: 25°C Tested by: Rock Zeng Humidity: 70 % RH Polarity: Ver. / Hor.

Item	Freq. (MHz)	Ant.Pol H/V	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Le Peak (dBuV/)	vel AV (dBuV/)	Peak Limit	AV Limit (dBuV/)	Margin (dB)	Remark
1.	4824	Н	46.12	35.76	4.58	34.94	51.52		74.00		-22.48	Peak
2.	4824	Н	31.17	35.76	4.58	34.94		36.57		54.00	-17.43	AVG
3.	7240	Н	43.17	37.85	5.63	35.25	51.40					Peak
4.	9648	Н	43.41	39.39	6.34	35.70	53.44					Peak
5.	12060	Н										
6.	14472	Н										
7.	16884	Н										
8.	19296	Н										
9.	21708	Н										
10.	24120	Н										
Note:	An item 3	and 4 are	on un-rest	ricted band,	so the li	mit is -20d	lB for the fi	ield strength	of the fund	amental em	ission	
1.	4824	V	34.70	35.13	4.58	34.94		39.48	74.00	54.00	-14.52	AVG
2.	4824	V	46.81	35.13	4.58	34.94	51.58		74.00	54.00	-22.42	Peak
3.	7240	V	43.70	36.90	5.63	35.25	50.97					Peak
4.	9648	V	43.27	38.59	6.34	35.70	52.50					Peak
5.	12060	V										
6.	14472	V										
7.	16884	V										
8.	19296	V										
9.	21708	V										
10.	24120	V										

Note: An item 3 and 4 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emission

V

V

V

V

---

17059

19496

21933

24370

6.

7.

8.

9.

Operation Mode: TX / IEEE 802.11g / CH Mid

Test Date: May 04, 2011 Temperature: 25°C Tested by: Rock Zeng

	Humidity	: 70 %	RH							Polari	ty: Ver.	/ Hor.
Item	Freq. (MHz)	Ant.Pol H/V	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Le Peak (dBuV/)	vel AV (dBuV/)	Peak Limit (dBuV/)	AV Limit (dBuV/)	Margin (dB)	Remark
1.	4874	Н	44.32	35.83	4.61	34.93	49.84			54.00	-4.16	Peak
2.	7311	Н	42.24	37.86	5.64	35.26	50.48			54.00	-3.52	Peak
3.	9748	Н	43.05	39.51	6.36	35.70	53.21					Peak
4.	12185	Н										
5.	14622	Н										
6.	17059	Н					-					
7.	19496	Н										
8.	21933	Н										
9.	24370	Н					-					
Note:	An item 3	are on un	-restricted	band, so the	limit is	-20dB for	the field str	rength of the	e fundament	al emission		
1.	4874	V	45.07	35.18	4.61	34.93	49.94			54.00	-4.06	Peak
2.	7311	V	43.68	36.92	5.64	35.26	50.98			54.00	-3.02	Peak
3.	9748	V	43.31	38.71	6.36	35.70	52.68					Peak
4.	12185	V										
5.	14622	V										

---

---

Note: An item 3 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emission

Operation Mode: TX / IEEE 802.11g / CH High

Test Date: May 04, 2011 Temperature: 25°C Tested by: Rock Zeng Humidity: 70 % RH Polarity: Ver. / Hor.

	Humiaity	: /0 %	KH							Polar	ity: ver.	/ Hor.
Item	Freq. (MHz)	Ant.Pol H/V	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Le Peak (dBuV/)	AV (dBuV/)	Peak Limit (dBuV/)	AV Limit (dBuV/)	Margin (dB)	Remark
1.	4924	Н	42.74	35.90	4.68	34.92	48.40			54.00	-5.60	Peak
2.	7386	Н	42.05	37.88	5.65	35.28	50.30			54.00	-3.70	Peak
3.	9848	Н	43.75	39.61	6.38	35.70	54.04					Peak
4.	12310	Н										
5.	14772	Н										
6.	17234	Н										
7.	19696	Н										
8.	22158	Н										
9.	24620	Н										
Note:	An item 4	are on ur	n-restricted	band, so the	e limit is	-20dB for	the field str	rength of the	e fundament	al emission		
1.	4924	V	44.05	35.23	4.68	34.92	49.04			54.00	-4.96	Peak
2.	7386	V	43.23	36.96	5.65	35.28	50.56			54.00	-3.44	Peak
3.	9848	V	43.18	38.81	6.38	35.70	52.67					Peak
4.	12310	V										
5.	14772	V										
6.	17234	V										
7.	19696	V										
8.	22158	V										
9.	24620	V										

Operation Mode: TX / IEEE 802.11n HT20/ CH Low

Test Date: May 04, 2011 Temperature: 25°C Tested by: Rock Zeng Humidity: 70 % RH Polarity: Ver. / Hor.

Item			Read	Antenna	Cable	s Factor	Level		Dools Limit	AVLimit	Marain	
	Freq. Ant.Pol (MHz) H/V	Level (dBuV)	Factor (dB)	Loss (dB)	Peak (dBuV/)		AV (dBuV/)	(dBuV/)	(dBuV/)	(dB)	Remark	
1.	4824	Н	43.85	35.76	4.18	34.94	48.85			54.00	-5.15	Peak
2.	7240	Н	42.09	37.85	5.43	35.25	50.11					Peak
3.	9648	Н	42.86	39.39	6.71	35.70	53.25					Peak
4.	12060	Н										
5.	14472	Н										
6.	16884	Н										
7.	19296	Н										
8.	21708	Н										
9.	24120	Н										
Note:	An item 2	and 3 are	on un-rest	ricted band,	so the li	mit is -20d	dB for the fi	eld strength	of the fund	amental em	ission	
1.	4824	V	43.12	35.13	4.18	34.94	47.49			54.00	-6.51	Peak
2.	7240	V	42.30	36.90	5.43	35.25	49.37					Peak
3.	9648	V	42.73	38.57	6.70	35.70	52.30					Peak
4.	12060	V										
5.	14472	V										
6.	16884	V										
7.	19296	V										
8.	21708	V										
9.	24120	V										

Operation Mode: TX / IEEE 802.11n HT20/ CH Mid

Test Date: May 04, 2011 Temperature: 25°C Tested by: Rock Zeng Humidity: 70 % RH Polarity: Ver. / Hor.

Item	Freq.	Freq. Ant.Pol		Antenna	Cable	Preamp		vel	Peak Limit	AV Limit	Margin	D1-
	(MHz)	H/V	Level (dBuV)	Factor (dB)	Loss (dB)	Factor (dB)	Peak (dBuV/)	AV (dBuV/)	(dBuV/)	(dBuV/)	(dB)	Remark
1.	4874	Н	44.59	35.83	4.16	34.93	49.65			54.00	-4.35	Peak
2.	7311	Н	42.25	37.86	5.36	35.26	50.21			54.00		Peak
3.	9748	Н	42.27	39.51	6.77	35.70	52.85					Peak
4.	12185	Н										
5.	14622	Н										
6.	17059	Н										
7.	19496	Н										
8.	21933	Н										
9.	24370	Н										
Note:	An item 2	and 3 are	on un-rest	ricted band,	so the li	mit is -20d	dB for the fi	ield strength	of the fund	amental em	ission	
1.	4874	V	43.32	35.18	4.16	34.93	47.73			54.00	-6.27	Peak
2.	7311	V	42.44	36.92	5.36	35.26	49.46			54.00	-4.54	Peak
3.	9748	V	42.80	38.71	6.77	35.70	52.58					Peak
4.	12185	V										
5.	14622	V										
6.	17059	V										
7.	19496	V										
8.	21933	V										
9	2/1370	V										

Operation Mode: TX / IEEE 802.11n HT20/ CH High
Temperature: 25°C
Tested by: Rock Zeng

Humidity: 70 % RH

Polarity: Ver. / Hor.

Item	Freq. Ant.Pol		nt Pol Read Antenna C		Cable	Preamp	Level		Dools Limis	AV Limit	Margin		
	-	_	H/V	Level	Factor	Loss	Factor	Peak	AV	(dBuV/)	AV Limit (dBuV/)	(dB)	Remark
	(WITIZ)	11/ V	(dBuV)	(dB)	(dB)	(dB)	(dBuV/)	(dBuV/)	(dDd V/)	(dDd V/)	(ub)		
1.	4924	Н	43.29	35.90	4.14	34.92	48.41			54.00	-5.59	Peak	
2.	7386	Н	43.11	37.88	5.27	35.28	50.99			54.00	-3.01	Peak	
3.	9848	Н	42.84	39.63	6.88	35.70	53.65					Peak	
4.	12310	Н											
5.	14772	Н											
6.	17234	Н											
7.	19696	Н											
8.	22158	Н											
9.	24620	Н											
Note:	An item 3	are on un	ı-restricted	band, so the	limit is	-20dB for	the field str	rength of th	e fundament	al emission			
1.	4924	V	42.77	35.23	4.14	34.92	47.23			54.00	-6.77	Peak	
2.	7386	V	42.60	36.96	5.27	35.28	49.55			54.00	-4.45	Peak	
3.	9848	V	42.77	38.81	6.85	35.70	52.73					Peak	
4.	12310	V											
5.	14772	V											
6.	17234	V											
7.	19696	V											
8.	22158	V											
9.	24620	V											
Note:	An item 3	are on un	-restricted	band, so the	limit is	-20dB for	the field str	rength of th	e fundament	al emission			

# Notes:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shownin Actual FS column.
- 4. Spectrum setting:
- a. Peak Setting 1GHz 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
- b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.
- 5. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.