



A D T

RF EXPOSURE REPORT

REPORT NO.: SA990712C17A

MODEL NO.: BSMBB08

FCC ID: ZJ5BSMBB08

APPLICANT: Buffalo Kokuyo Supply Inc.

ADDRESS: AKAMONDORI Bldg., 30-20, Ohsu 3-chome,
Naka-ku, Nagoya. Aichi, 460-8315, Japan

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.)
Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang,
Taipei Hsien 244, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan
Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This test report consists of 5 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced, except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval or endorsement by any government agency. The test results in the report only apply to the tested sample.



A D T

TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1. CERTIFICATION.....	4
2. REDUCED CONDITION FOR SAR	5
3. MAXIMUM MEASURED POWER OF EUT.....	5
4. CONCLUSION	5



A D T

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
Original release	NA	Sep. 02, 2011



A D T

1. CERTIFICATION

PRODUCT: Bluetooth Optical Mouse

MODEL NO.: BSMBB08

BRAND: iBUFFALO

APPLICANT: Buffalo Kokuyo Supply Inc.

TESTED: Aug. 27 ~ Aug. 30, 2011

TEST SAMPLE: ENGINEERING SAMPLE

STANDARDS: FCC Part 2 (Section 2.1093)

FCC OET Bulletin 65, Supplement C (01-01)

IEEE C95.1

The above equipment (model: BSMBB08) have been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Polly Chien, DATE : Sep. 02, 2011
Polly Chien / Specialist

APPROVED BY : Gary Chang, DATE : Sep. 02, 2011
Gary Chang / Technical Manager

2. REDUCED CONDITION FOR SAR

When output power is $\leq 60/f(\text{GHz})$ mW, SAR evaluation is not required.

3. MAXIMUM MEASURED POWER OF EUT

Conducted power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	Threshold for SAR (dBm)
2.95	1.07	4.02	13.84

4. CONCLUSION

No SAR evaluation is required since output power of EUT is less than threshold of SAR.