



TEST REPORT

FCC ID: ZJP-SR250**Product: Bluetooth Soundbar****Model No.: SR250****Additional Model No.: N/A****Trade Mark: SAMESAY, CKY****Report No.: WSCT-NVLAP-R&E190900021A-BT****Issued Date: Nov. 15, 2019**

Issued for:

**Shenzhen SKY DRAGON Audio-video Technology Co.,LTD
B16,Laneway 3,Liuxian 2RD,District71,Baoan,shenzhen**

Issued By:

**World Standardization Certification & Testing Group Co., Ltd.
Building A-B, Baoshi Science & Technology Park, Baoshi Road
Bao'an District, Shenzhen, Guangdong, China****TEL: +86-755-26996192****FAX: +86-755-86376605**

Note: The results contained in this report pertain only to the tested sample. This report shall not be reproduced, except in full, without written approval of World Standardization Certification & Testing Group Co.,Ltd. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.





Table of Contents

1. GENERAL INFORMATION	3
1.1 GENERAL DESCRIPTION OF EUT	4
1.2 FACILITIES AND ACCREDITATIONS	5
1.3 DESCRIPTION OF TEST MODES	6
1.4 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	7
1.5 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	8
2. SUMMARY OF TEST RESULTS	9
3. MEASUREMENT INSTRUMENTS	10
4. EMC EMISSION TEST	11
4.1 CONDUCTED EMISSION MEASUREMENT	11
4.2 RADIATED EMISSION MEASUREMENT	17
5. NUMBER OF HOPPING CHANNEL	31
5.1 APPLIED PROCEDURES / LIMIT	31
5.2 TEST RESULTS	32
6. AVERAGE TIME OF OCCUPANCY	34
6.1 APPLIED PROCEDURES / LIMIT	34
6.2 TEST RESULTS	36
7. HOPPING CHANNEL SEPARATION MEASUREMENT	42
7.1 APPLIED PROCEDURES / LIMIT	42
7.2 TEST RESULTS	43
8. BANDWIDTH TEST	52
8.1 APPLIED PROCEDURES / LIMIT	52
8.2 TEST RESULTS	53
9. PEAK OUTPUT POWER TEST	62
9.1 APPLIED PROCEDURES / LIMIT	62
9.2 TEST RESULTS	63
10. 100KHZ BAND EDGES MEASUREMENT	68
10.1 APPLIED PROCEDURES / LIMIT	68
11. ANTENNA APPLICATION	78
11.1 ANTENNA REQUIREMENT	78
12. TEST SETUP PHOTOGRAPHS	79



For Question,
Please Contact with WSCT
www.wsct-cert.com

1. GENERAL INFORMATION

Product:	Bluetooth Soundbar
Model No.:	SR250
Additional Model:	N/A
Applicant:	Shenzhen SKY DRAGON Audio-video Technology Co.,LTD
Address:	B16,Laneway 3,Liuxian 2RD,District71,Baoan,shenzhen
Manufacturer:	Huizhou Clinav Industrial Development Co.,LTD
Address:	Shangnan Village Committee,Yuanzhou Town BoLuo County, Huizhou City, Guangdong
Data of receipt	Oct. 24, 2019
Date of Test:	Oct. 29, 2019 to Nov. 12, 2019
Applicable Standards:	FCC CFR Title 47 Part 15 Subpart C Section 15.247, 558074 D01 15.247 Meas Guidance v05r02

The above equipment has been tested by World Standardization Certification & Testing Group Co., Ltd. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested By: Jim Han
(Jim Han)

Date: Nov. 15, 2019

Check By: Qin Shuiquan
(Qin Shuiquan)

Date: Nov. 15, 2019

Approved By: Wang Fengbing
(Wang Fengbing)

Date: Nov. 15, 2019





1.1 GENERAL DESCRIPTION OF EUT

Equipment Type:	Bluetooth Soundbar
Model No.:	SR250
Additional Model:	N/A
Trade Mark	SAMESAY ,CKY
Applicant:	Shenzhen SKY DRAGON Audio-video Technology Co.,LTD
Address:	B16,Laneway 3,Liuxian 2RD,District71,Baoan,shenzhen
Manufacturer:	Huizhou Clinav Industrial Development Co.,LTD
Address:	Shangnan Village Committee,Yuanzhou Town BoLuo County, Huizhou City, Guangdong
Software version:	V1.2
Hardware version:	V40
Extreme Temp. Tolerance:	0°Cto + 80°C
Battery information:	N/A
Adapter Information:	Adapter: JDA0301800130WUS Input: AC 100-240V~50/60Hz 0.8A Output: DC 18.0V=1.30A
Operating Frequency	2402-2480MHz(TX/RX)
Channels	79
Channel Spacing	1MHz
Modulation Type	GFSK, $\pi/4$ -DQPSK, 8-DPSK
Version	3.0
Antenna Type:	PCB Antenna
Antenna gain:	0dBi

Note: N/A stands for no applicable.

Models difference

N/A





1.2 FACILITIES AND ACCREDITATIONS

All measurement facilities used to collect the measurement data are located at **Building A-B, Baoshi Science & Technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China of the World Standardization Certification & Testing Group Co., Ltd.**

The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

Registration Number: 366353

1.2.1 ACCREDITATIONS

Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

USA	NVLAP (The certificate registration number is NVLAP LAB CODE:600142-0)
Japan	VCCI (The certificate registration number is C-4790, R-3684, G-837)
Canada	INDUSTRY CANADA (The certificated registration number is 7700A-1)
China	CNAS (The certificated registration number is L3732)

Copies of granted accreditation certificates are available for downloading from our web site,
<http://www.wsct-cert.com>

1.2.2 TEST DESCRIPTION

1.2.2.1 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 3.2\text{dB}$
2	RF power, conducted	$\pm 0.16\text{dB}$
3	Spurious emissions, conducted	$\pm 0.21\text{dB}$
4	All emissions, radiated (<1G)	$\pm 4.7\text{dB}$
5	All emissions, radiated (>1G)	$\pm 4.7\text{dB}$
6	Temperature	$\pm 0.5^\circ\text{C}$
7	Humidity	$\pm 2\%$





1.3 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Modulation type	Mode
1Mbps	Mode 1 、 Mode 2 、 Mode 3 、 Mode 4
2Mbps	
3Mbps	

Pretest Mode	Description
Mode 1	CH00
Mode 2	CH39
Mode 3	CH78
Mode 4	Normal Hopping

For Conducted Emission	
Final Test Mode	Description
Mode 4	Normal Hopping

For Radiated Emission	
Final Test Mode	Description
Mode 1	CH00
Mode 2	CH39
Mode 3	CH78
Mode 4	Normal Hopping

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The data rate was set in 1Mbps,2 Mbps,3 Mbps for radiated emission due to the highest RF output power.
- (3) Record the worst case of each test item in this report.



1.4 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS

Test software Version	N/A		
Frequency	2402 MHz	2441 MHz	2480 MHz
Parameters(1Mbps)	DEF	DEF	DEF
Parameters(2Mbps)	DEF	DEF	DEF
Parameters(3Mbps)	DEF	DEF	DEF

1.4.1 CONFIGURATION OF SYSTEM UNDER TEST



(EUT: Bluetooth Soundbar)

**1.5 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)**

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
1	Adapter	/	JDA0301800130WUS	/	/
2	Earphone	/	N/A	/	/

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.





2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247(a)(1)	Hopping Channel Separation	PASS	
15.247(b)(1)	Peak Output Power	PASS	
15.247(c)	Radiated Spurious Emission	PASS	
15.247(a)(iii)	Number of Hopping Frequency	PASS	
15.247(a)(iii)	Dwell Time	PASS	
15.247(a)(1)	Bandwidth	PASS	
15.247(d)	100kHz Band Edges	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this test report.

(2)The manufacture declare the equipment comply with the all the technical requirements in 15.247(g). 15.247(h).

The equipment are not required to employ all available hopping channels during each trans mission. it can be presented with a continuous data (or information) stream. the equipment can recognize other users within the spectrum band so that it individually and independently chooses and adapts its hop sets to avoid hopping on occupied channels.



3. MEASUREMENT INSTRUMENTS

NAME OF EQUIPMENT	MANUFACTURER	MODEL	SERIAL NUMBER	Calibration Date	Calibration Due.
EMI Test Receiver	R&S	ESCI	100005	10/29/2019	10/28/2020
LISN	AFJ	LS16	16010222119	10/29/2019	10/28/2020
LISN(EUT)	Mestec	AN3016	04/10040	10/29/2019	10/28/2020
Universal Radio Communication Tester	R&S	CMU 200	1100.0008.02	10/29/2019	10/28/2020
Coaxial cable	Megalon	LMR400	N/A	10/29/2019	10/28/2020
GPIB cable	Megalon	GPIB	N/A	10/29/2019	10/28/2020
Spectrum Analyzer	R&S	FSU	100114	10/29/2019	10/28/2020
Pre Amplifier	H.P.	HP8447E	2945A02715	10/29/2019	10/28/2020
Pre-Amplifier	CDSI	PAP-1G18-38	--	10/29/2019	10/28/2020
Bi-log Antenna	SUNOL Sciences	JB3	A021907	10/29/2019	10/28/2020
9*6*6 Anechoic	--	--	--	10/29/2019	10/28/2020
Horn Antenna	COMPLIANCE ENGINEERING	CE18000	--	10/29/2019	10/28/2020
Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-631	10/29/2019	10/28/2020
Cable	TIME MICROWAVE	LMR-400	N-TYPE04	10/29/2019	10/28/2020
System-Controller	CCS	N/A	N/A	N.C.R	N.C.R
Turn Table	CCS	N/A	N/A	N.C.R	N.C.R
Antenna Tower	CCS	N/A	N/A	N.C.R	N.C.R
RF cable	Murata	MXHQ87WA3000		10/29/2019	10/28/2020
Loop Antenna	EMCO	6502	00042960	10/29/2019	10/28/2020
Horn Antenna	SCHWARZBECK	BBHA 9170	1123	10/29/2019	10/28/2020
Power meter	Anritsu	ML2487A	6K00003613	10/29/2019	10/28/2020
Power sensor	Anritsu	MX248XD	--	10/29/2019	10/28/2020





4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Conducted limit (dB μ V)		Conducted limit (dB μ V)
	Quasi-peak	Quasi-peak	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz




4.1.2 TEST PROCEDURE

- The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

4.1.5 EUT OPERATING CONDITIONS


The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



4.1.6 TEST RESULTS

Temperature	26 °C	Relative Humidity	54%
Pressure	1010hPa	Voltage	120V/60Hz
Test Mode	Mode 4		

L:




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.1620	48.04	10.41	58.45	65.36	-6.91	QP
2		0.2460	17.90	10.42	28.32	51.89	-23.57	AVG
3	*	0.2660	44.09	10.42	54.51	61.24	-6.73	QP
4		0.3220	42.15	10.43	52.58	59.65	-7.07	QP
5		0.4140	20.27	10.45	30.72	47.57	-16.85	AVG
6		0.4500	38.79	10.46	49.25	56.87	-7.62	QP
7		0.5700	35.65	10.48	46.13	56.00	-9.87	QP
8		0.7700	12.44	10.49	22.93	46.00	-23.07	AVG
9		1.8460	15.95	10.64	26.59	46.00	-19.41	AVG
10		3.0740	22.43	10.67	33.10	46.00	-12.90	AVG
11		9.5540	33.73	10.78	44.51	60.00	-15.49	QP
12		11.9900	10.92	10.90	21.82	50.00	-28.18	AVG



For Question,
Please Contact with WSCT
wsct-cert.com

N:



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1	*	0.1539	48.21	10.41	58.62	65.78	-7.16	QP
2		0.2340	44.62	10.42	55.04	62.30	-7.26	QP
3		0.2340	21.56	10.42	31.98	52.30	-20.32	AVG
4		0.3620	40.94	10.44	51.38	58.68	-7.30	QP
5		0.4140	39.87	10.45	50.32	57.57	-7.25	QP
6		0.4140	21.55	10.45	32.00	47.57	-15.57	AVG
7		0.5660	35.99	10.48	46.47	56.00	-9.53	QP
8		0.6140	16.15	10.48	26.63	46.00	-19.37	AVG
9		1.2260	15.38	10.54	25.92	46.00	-20.08	AVG
10		3.0500	23.29	10.67	33.96	46.00	-12.04	AVG
11		3.6580	19.89	10.68	30.57	46.00	-15.43	AVG
12		29.9100	37.32	10.96	48.28	60.00	-11.72	QP

Note: 1. All the modes have been investigated, and only worst mode is presented in this report.

2. Over = Reading Level + Correct Factor - Limit.



世标检测认证股份
World Standardization Certification & Testing Group Co., Ltd.

ADD: Building A-B Baoshi Science & technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China
TEL: 86-755-26996143/26996144/26996145/26996192 FAX: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: www.wsct-cert.com

Member of the WSCT INC.




For Question,
Please Contact with WSCT
www.wsct-cert.com

Temperature	26 °C	Relative Humidity	54%
Pressure	1010hPa	Voltage	240V/50Hz
Test Mode	Mode 4		

L:

80.0 dBuV




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1547	47.53	10.41	57.94	65.74	-7.80	QP
2		0.1580	14.32	10.41	24.73	55.56	-30.83	AVG
3	*	0.2900	42.67	10.43	53.10	60.52	-7.42	QP
4		0.3220	8.18	10.43	18.61	49.65	-31.04	AVG
5		0.4140	8.12	10.45	18.57	47.57	-29.00	AVG
6		0.4420	38.45	10.46	48.91	57.02	-8.11	QP
7		0.9220	30.45	10.50	40.95	56.00	-15.05	QP
8		1.5260	10.86	10.59	21.45	46.00	-24.55	AVG
9		3.2299	2.64	10.67	13.31	46.00	-32.69	AVG
10		5.4218	26.13	10.70	36.83	60.00	-23.17	QP
11		9.3658	28.95	10.78	39.73	60.00	-20.27	QP
12		29.8978	13.53	10.96	24.49	50.00	-25.51	AVG



For Question,
Please Contact with WSCT
www.wsct-cert.com

N:



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1	*	0.1532	50.64	10.41	61.05	65.82	-4.77	QP
2		0.2589	42.72	10.42	53.14	61.46	-8.32	QP
3		0.3940	39.76	10.45	50.21	57.98	-7.77	QP
4		0.4100	8.77	10.45	19.22	47.65	-28.43	AVG
5		0.7980	3.86	10.49	14.35	46.00	-31.65	AVG
6		1.5020	11.42	10.59	22.01	46.00	-23.99	AVG
7		3.5820	3.45	10.68	14.13	46.00	-31.87	AVG
8		5.3418	25.17	10.70	35.87	60.00	-24.13	QP
9		9.4539	30.17	10.78	40.95	60.00	-19.05	QP
10		11.7499	0.65	10.88	11.53	50.00	-38.47	AVG
11		29.8900	12.08	10.96	23.04	50.00	-26.96	AVG
12		30.0000	29.66	10.96	40.62	60.00	-19.38	QP

Note: 1. All the modes have been investigated, and only worst mode is presented in this report.

2. Over = Reading Level + Correct Factor - Limit.



世标检测认证股份
World Standardization Certification & Testing Group Co., Ltd.

ADD: Building A-B Baoshi Science & technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China
 TEL: 86-755-26996143/26996144/26996145/26996192 FAX: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: www.wsct-cert.com

Member of the WSCT INC.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 Radiated Emission Limits (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 1Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP





4.2.2 TEST PROCEDURE

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

4.2.3 DEVIATION FROM TEST STANDARD

No deviation

4.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz






For Question,
e Contact with WSCT
www.wsct-cert.com

(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



4.2.5.1 RESULTS (Below 30 MHz)

Test Mode	Mode 1/ Mode 2/ Mode 3	Polarization	Horizontal / Vertical
Temperature	20 °C	Relative Humidity	48%
Pressure	1010 hPa		

Freq. (MHz)	Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	State P/F
--	--	--	--	P
--	--	--	--	P

NOTE:

No result in this part for margin above 20dB.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.






For Question,
Please Contact with WSCT
www.wsct-cert.com

4.2.5.2 TEST RESULTS (Between 30M – 1000 MHz)

Test Mode	Mode 1 with GFSK modulation	Pressure	1010 hPa
Temperature	20 °C	Relative Humidity	48%

H:




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		33.0949	28.56	3.61	32.17	40.00	-7.83	QP
2		46.6664	33.61	-3.03	30.58	40.00	-9.42	QP
3		103.4419	29.88	-3.15	26.73	43.50	-16.77	QP
4	*	239.9874	46.36	-5.18	41.18	46.00	-4.82	QP
5	!	325.5957	42.90	-1.94	40.96	46.00	-5.04	QP
6		480.5276	33.36	0.22	33.58	46.00	-12.42	QP



For Question,
Please Contact with WSCT
www.wsct-cert.com

V:



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	30.5306	28.60	4.59	33.19	40.00	-6.81	QP
2		41.8596	32.66	-0.80	31.86	40.00	-8.14	QP
3		108.2667	38.22	-2.21	36.01	43.50	-7.49	QP
4		239.9874	40.14	-5.18	34.96	46.00	-11.04	QP
5		357.9287	33.09	-1.48	31.61	46.00	-14.39	QP
6		480.5276	33.60	0.22	33.82	46.00	-12.18	QP

Note: 1. All the modes have been investigated, and only worst mode is presented in this report.

2. Over = Reading Level + Correct Factor - Limit.



世标检测认证股份
World Standardization Certification & Testing Group Co., Ltd.

ADD: Building A-B Baoshi Science & technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China
TEL: 86-755-26996143/26996144/26996145/26996192 FAX: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: www.wsct-cert.com

Member of the WSCT INC.



4.2.5.3 TEST RESULTS(1GHz to 25GHz)

Pressure	1010 hPa	Test Mode	Mode 1 TX(1Mbps)
Temperature	20 °C	Relative Humidity	48%

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4804	V	60.22	41.85	74	54	-13.78	-12.15
7206	V	58.56	39.89	74	54	-15.44	-14.11
4804	H	59.78	39.02	74	54	-14.22	-14.98
7206	H	59.92	40.92	74	54	-14.08	-13.08

Remark: All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Pressure	1010 hPa	Test Mode	Mode 2 TX(2Mbps)
Temperature	20 °C	Relative Humidity	48%

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4882	V	59.46	40.81	74	54	-14.54	-13.19
7323	V	59.12	40.26	74	54	-14.88	-13.74
4882	H	58.75	39.37	74	54	-15.25	-14.63
7323	H	58.73	39.73	74	54	-15.27	-14.27

Remark: All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Pressure	1010 hPa	Test Mode	Mode 3 TX(3Mbps)
Temperature	20 °C	Relative Humidity	48%

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4960	V	59.46	40.78	74	54	-14.54	-13.22
7440	V	58.95	40.10	74	54	-15.05	-13.90
4960	H	59.19	39.59	74	54	-14.81	-14.41
7440	H	59.55	40.55	74	54	-14.45	-13.45

Remark: All emissions not reported were more than 20dB below the specified limit or in the noise floor.





4.2.5.4 TEST RESULTS (Restricted Bands Requirements)

Test result for 1Mbps Mode:

Polarization	Vertical	Test Mode	TX /Mode1-1Mbps(CH0)
Temperature	20 °C	Relative Humidity	48%
Pressure	1010 hPa		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2387	62.50	-8.77	53.73	74	20.27	peak
2387	53.44	-8.77	44.67	54	9.33	AVG
2390	59.69	-8.73	50.96	74	23.04	peak
2390	57.80	-8.73	49.07	54	4.93	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.

Polarization	Horizontal	Test Mode	TX /Mode1-1Mbps(CH0)
Temperature	20 °C	Relative Humidity	48%
Pressure	1010 hPa		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2384	64.33	-8.77	55.56	74	18.44	peak
2384	57.72	-8.77	48.95	54	5.05	AVG
2390	61.53	-8.73	52.80	74	21.20	peak
2390	56.82	-8.73	48.09	54	5.91	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.





Polarization	Vertical	Test Mode	TX /Mode 3-1Mbps(CH78)
Temperature	20 °C	Relative Humidity	48%
Pressure	1010 hPa		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2483.5	61.71	-8.17	53.54	74	20.46	peak
2483.5	57.04	-8.17	48.87	54	5.13	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.

Polarization	Horizontal	Test Mode	TX /Mode 3-1Mbps(CH78)
Temperature	20 °C	Relative Humidity	48%
Pressure	1010 hPa		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2483.5	61.25	-8.17	53.08	74	20.92	peak
2483.5	57.52	-8.17	49.35	54	4.65	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.

Test result for 2Mbps Mode:

Polarization	Vertical	Test Mode	TX /Mode1-2Mbps(CH0)
Temperature	20 °C	Relative Humidity	48%
Pressure	1010 hPa		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2387	61.23	-8.77	52.46	74	21.54	peak
2387	53.77	-8.77	45.00	54	9.00	AVG
2390	61.38	-8.73	52.65	74	21.35	peak
2390	58.09	-8.73	49.36	54	4.64	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.



Polarization	Horizontal	Test Mode	TX /Mode1-2Mbps(CH0)
Temperature	20 °C	Relative Humidity	48%
Pressure	1010 hPa		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2384	61.73	-8.77	52.96	74	21.04	peak
2384	56.46	-8.77	47.69	54	6.31	AVG
2390	62.35	-8.73	53.62	74	20.38	peak
2390	57.31	-8.73	48.58	54	5.42	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.

Polarization	Vertical	Test Mode	TX /Mode3-2Mbps(CH78)
Temperature	20 °C	Relative Humidity	48%
Pressure	1010 hPa		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2483.5	61.60	-8.17	53.43	74	20.57	peak
2483.5	57.51	-8.17	49.34	54	4.66	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.

Polarization	Horizontal	Test Mode	TX /Mode3-2Mbps(CH78)
Temperature	20 °C	Relative Humidity	48%
Pressure	1010 hPa		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2483.5	61.36	-8.17	53.19	74	20.81	peak
2483.5	55.93	-8.17	47.76	54	6.24	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.



**Test result for 3Mbps Mode:**

Polarization	Vertical	Test Mode	TX /Model 1-3Mbps(CH0)
Temperature	20 °C	Relative Humidity	48%
Pressure	1010 hPa		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2387	63.44	-8.77	54.67	74	19.33	peak
2387	56.04	-8.77	47.27	54	6.73	AVG
2390	63.10	-8.73	54.37	74	19.63	peak
2390	58.32	-8.73	49.59	54	4.41	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.

Polarization	Horizontal	Test Mode	TX /Mode 1-3Mbps(CH0)
Temperature	20 °C	Relative Humidity	48%
Pressure	1010 hPa		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2384	64.30	-8.77	55.53	74	18.47	peak
2384	55.67	-8.77	46.90	54	7.10	AVG
2390	62.82	-8.73	54.09	74	19.91	peak
2390	56.07	-8.73	47.34	54	6.66	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.





Polarization	Vertical	Test Mode	TX /Model 3-3Mbps(CH78)
Temperature	20 °C	Relative Humidity	48%
Pressure	1010 hPa		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2483.5	62.19	-8.17	54.02	74	19.98	peak
2483.5	55.68	-8.17	47.51	54	6.49	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.

Polarization	Horizontal	Test Mode	TX /Model 3-3Mbps(CH78)
Temperature	20 °C	Relative Humidity	48%
Pressure	1010 hPa		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2483.5	59.35	-8.17	51.18	74	22.82	peak
2483.5	55.83	-8.17	47.66	54	6.34	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.





Test result for hopping mode:

Polarization	Vertical	Test Mode	hopping mode-1Mbps
Temperature	20 °C	Relative Humidity	48%
Pressure	1010 hPa		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2387	63.29	-8.77	54.52	74	19.48	peak
2387	57.39	-8.77	48.62	54	5.38	AVG
2390	61.49	-8.73	52.76	74	21.24	peak
2390	56.06	-8.73	47.33	54	6.67	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.

Polarization	Horizontal	Test Mode	Hopping mode-1Mbps
Temperature	20 °C	Relative Humidity	48%
Pressure	1010 hPa		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2387	64.63	-8.77	55.86	74	18.14	peak
2387	56.60	-8.77	47.83	54	6.17	AVG
2390	59.94	-8.73	51.21	74	22.79	peak
2390	56.93	-8.73	48.20	54	5.80	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.

Polarization	Vertical	Test Mode	Hopping mode-1Mbps
Temperature	20 °C	Relative Humidity	48%
Pressure	1010 hPa		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2483.5	58.47	-8.17	50.30	74	23.70	peak
2483.5	55.35	-8.17	47.18	54	6.82	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.



Polarization	Horizontal	Test Mode	Hopping mode-1Mbps	For Question Please Contact with WSCT www.wsct-cert.com
Temperature	20 °C	Relative Humidity	48%	
Pressure	1010 hPa			

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2483.5	60.15	-8.17	51.98	74	22.02	peak
2483.5	56.12	-8.17	47.95	54	6.05	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.





5. NUMBER OF HOPPING CHANNEL

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)(iii)	Number of Hopping Channel	≥15	2400-2483.5	PASS

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> Operating Frequency Range
RB	1MHz
VB	3MHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


5.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting: RBW= 1MHz, VBW=3MHz, Sweep time = Auto.

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP




5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.




5.2 TEST RESULTS

Mode	Hopping channel numbers	Limit	Result
GFSK, P/4-DQPSK, 8DPSK	79	15	PASS






P/4-DQPSK



Date: 30.OCT.2019 10:36:22

8DPSK



Date: 30.OCT.2019 10:37:23





6. AVERAGE TIME OF OCCUPANCY

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)(iii)	Average Time of Occupancy	0.4sec	2400-2483.5	PASS

6.1.2 TEST PROCEDURE

- The EUT test port was connected to the spectrum analyzer with RF cable and antenna connector.
- Set RBW of spectrum analyzer to 1MHz and VBW to 3MHz.
- Use a video trigger with the trigger level set to enable triggering only on full pulses.
- Sweep Time is more than once pulse time.
- Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- Measure the maximum time duration of one single pulse.
- Set the EUT for 1DH5, 2DH5 and 3DH5 packet transmitting.
- Measure the maximum time duration of one single pulse.
- Dwell time = Pulse time*(1600/6/79)*31.6S


6.1.3 DEVIATION FROM STANDARD

No deviation.





6.1.4 TEST SETUP



6.1.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.




For Question,
Please Contact with WSCT
www.wsct-cert.com

6.2 TEST RESULTS

Note: *the worst case is 1Mbps as result in this part.*


Pressure	1012 hPa	Test Mode	DH1-1Mbps
Temperature	25°C	Relative Humidity	60%

Data Packet	Frequency	Pulse time(ms)	Dwell Time(S)	Limits (S)
1DH5	2402MHz	2.927	0.312	0.4
1DH5	2441MHz	2.927	0.312	0.4
1DH5	2480MHz	2.927	0.312	0.4






CH39-1DH5




CH78-1DH5





Pressure	1012 hPa	Test Mode	DH3-1Mbps
Temperature	25°C	Relative Humidity	60%


Data Packet	Frequency	Pulse time(ms)	Dwell Time(S)	Limits (S)
2DH5	2402MHz	2.927	0.312	0.4
2DH5	2441MHz	2.927	0.312	0.4
2DH5	2480MHz	2.927	0.312	0.4






For Question,
Please Contact with WSCT
www.wsct-cert.com

CH39-2DH5




CH78-2DH5





Pressure	1012 hPa	Test Mode	DH5-1Mbps
Temperature	25°C	Relative Humidity	60%


Data Packet	Frequency	Pulse time(ms)	Dwell Time(S)	Limits (S)
3DH5	2402MHz	2.934	0.313	0.4
3DH5	2441MHz	2.934	0.313	0.4
3DH5	2480MHz	2.934	0.313	0.4






For Question,
Please Contact with WSCT
www.wsct-cert.com

CH39-3DH5



CH78-3DH5





7. HOPPING CHANNEL SEPARATION MEASUREMENT

7.1 APPLIED PROCEDURES / LIMIT

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	Resolution (or IF) Bandwidth (RBW) $\geq$ 1% of the span
VB	Video (or Average) Bandwidth (VBW) $\geq$ RBW
Detector	Peak
Trace	Max hold
Sweep Time	Auto


7.1.2 TEST PROCEDURE

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Set the spectrum analyzer as follows: Span = wide enough to capture the peaks of two adjacent channels: Resolution (or IF) Bandwidth (RBW) $\geq$ 1% of the span; Video (or Average) Bandwidth (VBW) $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold
3. Measure the separation between the peaks of the adjacent channels using the marker-delta function.
4. Repeat above procedures until all frequencies measured were complete.

7.1.3 DEVIATION FROM STANDARD

No deviation.

7.1.4 TEST SETUP



7.1.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.




7.2 TEST RESULTS

Pressure	1012 hPa	Test Mode	CH00 / CH39 /CH78 (1Mbps Mode)
Temperature	25°C	Relative Humidity	60%
Test Result	Pass		


Channel number	Channel frequency (MHz)	Separation Read value (KHz)	Separation limit (KHz)
00	2402	1000	20dB BW
39	2441	1000	20dB BW
78	2480	1000	20dB BW

Note: 20db bandwidth refer to section9.6






CH39 -1Mbps



Date: 29.OCT.2019 10:04:53



CH78 -1Mbps



Date: 29.OCT.2019 10:07:13






Pressure	1012 hPa	Test Mode	CH00 / CH39 /CH78 (2Mbps Mode)
Temperature	25°C	Relative Humidity	60%
Test Result	Pass		


Channel number	Channel frequency (MHz)	Separation Read value (KHz)	Separation limit (KHz)
00	2402	1005	2/3 *20dB BW
39	2441	1005	2/3 *20dB BW
78	2480	1005	2/3 *20dB BW

Note: 20db bandwidth refer to section 9.6






CH39 -2Mbps



Date: 29.OCT.2019 10:21:12



CH78 -2Mbps



Date: 29.OCT.2019 10:23:27





Pressure	1012 hPa	Test Mode	CH00 / CH39 /CH78 (3Mbps Mode)
Temperature	25°C	Relative Humidity	60%
Test Result	Pass		


Channel number	Channel frequency (MHz)	Separation Read value (KHz)	Separation limit (KHz)
00	2402	1000	2/3 *20dB BW
39	2441	1005	2/3 *20dB BW
78	2480	1000	2/3 *20dB BW

Note: 20db bandwidth refer to section 9.6





CH39 -3Mbps




Date: 29.OCT.2019 10:29:49





CH78 -3Mbps



Date: 29.OCT.2019 10:33:06





8. BANDWIDTH TEST

8.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)	Bandwidth	(20dB bandwidth)	2400-2483.5	PASS

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	30kHz
VB	100 kHz
Detector	Peak
Trace	Max hold
Sweep Time	Auto


8.1.2 TEST PROCEDURE

1. Check the calibration of the measuring instrument (spectrum analyzer) using either an internal calibrator or a known signal from an external generator.
2. Set the spectrum analyzer as follows: VBW =30kHz, RBW=100kHz, Sweep = auto Detector function = peak ,Trace = max hold
3. Measure the highest amplitude appearing on spectral display and record the level to calculate results.
4. Repeat above procedures until all frequencies measured were complete.

8.1.3 DEVIATION FROM STANDARD

No deviation.

8.1.4 TEST SETUP



8.1.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.




8.2 TEST RESULTS

Note: *the worst case is DH5 as result in this part.*

Pressure	1012 hPa	Test Mode	CH00/CH39/C78(1Mbps)
Temperature	25°C	Relative Humidity	60%

Frequency	20dB Bandwidth (kHz)	Result
2402 MHz	1048	PASS
2441 MHz	1035	PASS
2480 MHz	1029	PASS


CH00 -1Mbps



Date: 29.OCT.2019 10:39:36




CH39 -1Mbps





CH78 -1Mbps






Note: **the worst case is DH5as result in this part.**

Pressure	1012 hPa	Test Mode	CH00/CH39/C78(2Mbps)
Temperature	25°C	Relative Humidity	60%


Frequency	20dB Bandwidth (kHz)	Result
2402 MHz	1370	PASS
2441 MHz	1365	PASS
2480 MHz	1365	PASS

CH00 -2Mbps






CH39 -2Mbps





CH78 -2Mbps




Note: **the worst case is DH5as result in this part.**

Pressure	1012 hPa	Test Mode	CH00/CH39/C78(3Mbps)
Temperature	25°C	Relative Humidity	60%

Frequency	20dB Bandwidth (kHz)	Result
2402 MHz	1346	PASS
2441 MHz	1351	PASS
2480 MHz	1351	PASS


CH00 -3Mbps



Date: 29.OCT.2019 11:02:22



CH39 -3Mbps




Date: 29.OCT.2019 11:04:59





CH78 -3Mbps





9. PEAK OUTPUT POWER TEST

9.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (b)(i)	Peak Output Power	1W for 1Mbps 0.125W for 2/3Mbps	2400-2483.5	PASS

9.1.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Setting : RBW $\geq$ the 20 dB bandwidth of the emission being measured
 Span $\geq$ approximately 3 times the 20 dB bandwidth, centered on a hop ping channel
 VBW $\geq$ RBW
 Sweep = auto
 Detector function = peak
 Trace = max hold

9.1.3 DEVIATION FROM STANDARD

No deviation.

9.1.4 TEST SETUP



9.1.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.




9.2 TEST RESULTS

Pressure	1012 hPa	Test Mode	CH00/ CH39 /CH78 (1M/2M/3Mbps Mode)
Temperature	25°C	Relative Humidity	60%

Test Channel	Frequency (MHz)	Peak Output Power (dBm)	LIMIT(dBm)	Result
1Mbps				
CH00	2402	1.23	30	Pass
CH39	2441	1.23	30	Pass
CH78	2480	0.83	30	Pass
2Mbps				
CH00	2402	3.27	20.97	Pass
CH39	2441	3.29	20.97	Pass
CH78	2480	2.91	20.97	Pass
3Mbps				
CH00	2402	3.68	20.97	Pass
CH39	2441	3.73	20.97	Pass
CH78	2480	3.33	20.97	Pass

1Mbps
Channel: Low




Date: 29.OCT.2019 11:11:30






For Question,
Please Contact with WSCT
www.wsct-cert.com

Channel: Middle



Channel: High



世标检测认证股份
World Standardization Certification & Testing Group Co., Ltd.


ADD: Building A-B Baoshi Science & technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China
TEL: 86-755-26996143/26996144/26996145/26996192 FAX: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: www.wsct-cert.com

Member of the WSCT INC.




For Question,
Please Contact with WSCT
www.wsct-cert.com

**2Mbps
Channel: Low**



Date: 29.OCT.2019 11:14:47

Channel: Middle



Date: 29.OCT.2019 11:15:46



世标检测认证股份
World Standardization Certification & Testing Group Co., Ltd.


ADD: Building A-B Baoshi Science & technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China
TEL: 86-755-26996143/26996144/26996145/26996192 FAX: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: www.wsct-cert.com

Member of the WSCT INC.




For Question,
Please Contact with WSCT
www.wsct-cert.com

Channel: High



Date: 29.OCT.2019 11:16:19

3Mbps
Channel: Low



Date: 29.OCT.2019 11:16:58





世标检测认证股份
World Standardization Certification & Testing Group Co., Ltd.

ADD: Building A-B Baoshi Science & technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China
TEL: 86-755-26996143/26996144/26996145/26996192 FAX: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: www.wsct-cert.com

Member of the WSCT INC.



For Question,
Please Contact with WSCT
www.wsct-cert.com






10. 100KHZ BAND EDGES MEASUREMENT

10.1 APPLIED PROCEDURES / LIMIT



FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(d)	Band Edges Measurement	(20dB bandwidth)	2400-2483.5	PASS

1Mbps
Channel: Low






For Question,
Please Contact with WSCT
www.wsct-cert.com






For Question,
Please Contact with WSCT
www.wsct-cert.com

Channel: High



3Mbps
Channel: Low



世标检测认证股份
World Standardization Certification & Testing Group Co., Ltd.


ADD: Building A-B Baoshi Science & technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China
TEL: 86-755-26996143/26996144/26996145/26996192 FAX: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: www.wsct-cert.com

Member of the WSCT INC.



For Question,
Please Contact with WSCT
www.wsct-cert.com

Channel: High



世标检测认证股份
World Standardization Certification & Testing Group Co.,Ltd.



ADD: Building A-B Baoshi Science & technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China
TEL: 86-755-26996143/26996144/26996145/26996192 FAX: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: www.wsct-cert.com

Member of the WSCT INC.



For Question,
Please Contact with WSCT
www.wsct-cert.com

Hopping







For Question,
Please Contact with WSCT
www.wsct-cert.com

1Mbps

Channel: Low



Channel: Middle



世标检测认证股份
World Standardization Certification & Testing Group Co., Ltd.


ADD: Building A-B Baoshi Science & technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China
TEL: 86-755-26996143/26996144/26996145/26996192 FAX: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: www.wsct-cert.com

Member of the WSCT INC.




For Question,
Please Contact with WSCT
www.wsct-cert.com

Channel: High





2Mbps
Channel: Low






For Question,
Please Contact with WSCT
www.wsct-cert.com






For Question,
Please Contact with WSCT
www.wsct-cert.com



Date: 30.OCT.2019 10:27:08



Date: 30.OCT.2019 10:30:35




世标检测认证股份
World Standardization Certification & Testing Group Co.,Ltd.

ADD: Building A-B Baoshi Science & technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China
TEL: 86-755-26996143/26996144/26996145/26996192 FAX: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: www.wsct-cert.com

Member of the WSCT INC.



For Question,
Please Contact with WSCT
www.wsct-cert.com



世标检测认证股份
World Standardization Certification & Testing Group Co.,Ltd.

ADD: Building A-B Baoshi Science & technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China
TEL: 86-755-26996143/26996144/26996145/26996192 FAX: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: www.wsct-cert.com

Member of the WSCT INC.



11. ANTENNA APPLICATION

11.1 ANTENNA REQUIREMENT


The EUT'S antenna is met the requirement of FCC part 15C section 15.203 and 15.247

FCC part 15C section 15.247 requirements: Systems operating in the 2402-2480MHz band that are used exclusively for fixed.

11.1.2 Result

The EUT's antenna Integral Antenna, The antenna's gain is 0dBi and meets the requirement.

Internal photograph of EUT



ANT




12. TEST SETUP PHOTOGRAPHS

CONDUCTED EMISSION TEST




RADIATED EMISSION TEST (Frequency from 30MHz to 1GHz)





**RADIATED EMISSION TEST
(Frequency above 1GHz)**



---END OF REPORT---

