



## FCC PART 15.227

### EMI MEASUREMENT AND TEST REPORT

For

### **Kam Yan Plastic Toys Factory Limited**

10/F Silver Tech Tower 26 Cheung Lee Street,  
Chai Wan, Hong Kong

**FCC ID: ZJY85200600911**

<b>Report Type:</b> Original Report	<b>Product Type:</b> Radio Control Turbo Runner
<b>Test Engineer:</b> <u>David Huang</u> <i>David huang</i>	
<b>Report Number:</b> <u>RSZ11051002</u>	
<b>Report Date:</b> <u>2011-06-02</u>	
<b>Reviewed By:</b> <u>EMC Engineer</u> <i>Merry Zhao</i> <i>merry_zhao</i>	
<b>Prepared By:</b> Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008	

**Note:** This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP\*, or any agency of the Federal Government.

\* This report contains data that are not covered by the NVLAP accreditation and are marked with an asterisk “★” (Rev.2)

## TABLE OF CONTENTS

<b>GENERAL INFORMATION.....</b>	<b>3</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
OBJECTIVE .....	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY .....	3
TEST FACILITY .....	3
<b>SYSTEM TEST CONFIGURATION.....</b>	<b>5</b>
JUSTIFICATION .....	5
EUT EXERCISE SOFTWARE .....	5
SPECIAL ACCESSORIES .....	5
EQUIPMENT MODIFICATIONS .....	5
CONFIGURATION OF TEST SETUP .....	5
BLOCK DIAGRAM OF TEST SETUP .....	5
<b>SUMMARY OF TEST RESULTS.....</b>	<b>6</b>
<b>FCC §15.203 - ANTENNA REQUIREMENT.....</b>	<b>7</b>
STANDARD APPLICABLE .....	7
<b>FCC §15.205, §15.209, §15.227(A) &amp; §15.227 (B) – FIELD STRENGTH AND RESTRICTED BAND EMISSIONS.....</b>	<b>8</b>
STANDARD APPLICABLE .....	8
MEASUREMENT UNCERTAINTY .....	8
EUT SETUP.....	8
EMI TEST RECEIVER SETUP.....	9
TEST EQUIPMENT LIST AND DETAILS.....	9
CORRECTED AMPLITUDE & MARGIN CALCULATION .....	9
TEST RESULTS SUMMARY .....	9
TEST DATA .....	10
<b>FCC §15.227- DUTY CYCLE .....</b>	<b>12</b>
LIMIT .....	12
TEST EQUIPMENT LIST AND DETAILS.....	12
TEST PROCEDURE .....	12
TEST DATA .....	12
<b>FCC §15.215(C) – 20 DB EMISSION BANDWIDTH.....</b>	<b>15</b>
APPLICABLE STANDARD .....	15
TEST EQUIPMENT LIST AND DETAILS.....	15
TEST PROCEDURE .....	15
TEST DATA .....	15

## GENERAL INFORMATION

---

### Product Description for Equipment under Test (EUT)

The *Kam Yan Plastic Toys Factory Limited*'s product, model number: 600 (FCC ID: ZJY85200600911) or the "EUT" as referred to in this report is a *Radio Control Turbo Runner*, which measures approximately: 10.0 cm (L) x 5.0 cm (W) x 2.75 cm (H), rated input voltage: DC 9V battery.

*All measurement and test data in this report was gathered from production sample serial number: 1105057 (Assigned by BACL, Shenzhen). The EUT was received on 2011-05-10.*

### Objective

This Type approval report is prepared on behalf of *Kam Yan Plastic Toys Factory Limited* in accordance with Part 2, Subpart J, and Part 15, Subparts A, B and C of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC rules, sec 15.203, 15.205, 15.209 and sec 15.227.

### Related Submittal(s)/Grant(s)

No related submittals.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

### Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect radiated and conducted emission measurement data is located in the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is an ISO/IEC 17025 guide accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at <http://ts.nist.gov/Standards/scopes/2007070.htm>

## SYSTEM TEST CONFIGURATION

### Justification

The system was configured for testing in an engineering mode which was selected by manufacturer.

### EUT Exercise Software

N/A.


### Special Accessories

The special Accessories were supplied by manufacturer.


### Equipment Modifications

No modifications were made to the unit tested.

### Configuration of Test Setup



### Block Diagram of Test Setup



**SUMMARY OF TEST RESULTS**

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.207	AC Line Conducted Emissions	N/A *
§15.205, §15.209, §15.227(a), §15.227(b)	Field Strength and Restricted Band Emissions	Compliance
§15.227	Duty Cycle	/
§15.215(c)	20 dB Emission Bandwidth	Compliance

**Note:** N/A\* - EUT is battery operation only.

## **FCC §15.203 - ANTENNA REQUIREMENT**

### **Standard Applicable**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

This product has a permanently attached antenna, fulfill the requirement of this section, and please refer to the EUT photos.

Test Result: Compliant

## FCC §15.205, §15.209, §15.227(a) & §15.227 (b) – FIELD STRENGTH AND RESTRICTED BAND EMISSIONS

### Standard Applicable

According to §15.227 (a), the field strength if any emission within this band shall not exceed 10,000 microvolts/meter at 3 meters.


(b) The field strength of any emissions which appear outside of this band shall not exceed the general radiated emission limits in §15.209.

### Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at Bay Area Compliance Laboratories Corp. (ShenZhen) is  $\pm 4.0$  dB.

### EUT Setup



The radiated emission tests were performed in the chamber B test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC Part 15 Subpart C section 15.227 limits.

## EMI Test Receiver Setup

According to FCC Rules, 47 CFR 15.33, the EUT emissions were investigated from 27 MHz to 1000 MHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency	RB/W	VB/W	IF B/W
9 kHz-30 MHz	10 kHz	30 kHz	9 kHz
30 MHz-1 GHz	100 kHz	300 kHz	120 kHz

## Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Pre-Amplifier	8447E	1937A01046	2010-11-15	2011-11-15
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2010-11-07	2011-11-06
Sunol Sciences	Bilog Antenna	JB1	A040904-2	2011-04-12	2012-04-11
EM Test	Loop Antenna	MS100	303298	2011-03-07	2012-03-07
ETS	Passive Loop Antenna	6512	00029604	2011-03-04	2012-03-04

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (ShenZhen) attests that all calibrations have been performed per the NVLAP requirements, traceable to NIST.

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter reading. The basic equation is as follows:

$$\text{Corr. Amp.} = \text{Meter Reading} + \text{Antenna Loss} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corr. Amp.}$$

## Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15.227, with the worst margin reading of:

**7.2 dB at 41.64 MHz in the Vertical polarization.**

**Test Data****Environmental Conditions**

Temperature:	25° C
Relative Humidity:	56%
ATM Pressure:	101.0kPa

Testing was performed by David Huang on 2011-05-30.

Test Mode: Transmitting

**1) Fundamental Measurement:**

Indicated		Table Angle Deg.	Test Antenna		Correction Factor			Correct. Amp. (dB $\mu$ V/m)	FCC Part 15.227		
Freq. (MHz)	Reading (dB $\mu$ V)		Height (m)	Detector (PK/AV)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre. Amp. (dB)		Limit (dB $\mu$ V/m)	Margin (dB)	Remarks
27.145	65.05	360	1.0	PK	28.69	1.22	25.86	69.10	100	30.90	Fund.


Field Strength of Fundamental Emission (Average)					
Freq. (MHz)	Peak Measurement @ 3m (dB $\mu$ V/m)	Duty Cycle Factor (dB)	Corrected Amp. (dB $\mu$ V/m)	FCC 15.227 Limit (dB $\mu$ V/m)	Result
27.145	69.10	-5.02	64.08	80	Pass

Depend on the duty cycle:

Duty Cycle Factor =  $20 \lg (1.94/3.46) = 20 \lg (0.561) = -5.02 \text{ dB}$

Average = Peak + Duty Cycle Factor

## 2) Spurious Emission:



Frequency (MHz)	Corrected Amplitude (dBµV/m)	Antenna Height (cm)	Antenna Polarity (H/V)	Turntable position (deg)	Correction Factor (dB)	Limit (dBµV/m)	Margin (dB)
41.640000	34.7	108.0	V	-6.0	-1.3	46.0	7.2
79.710000	25.3	249.0	V	35.0	-1.0	46.0	16.9
509.910000	37.3	165.0	V	90.0	-0.5	46.0	21.5
135.000000	33.6	250.0	V	163.0	-0.6	46.0	23.9
216.970000	25.1	233.0	V	42.0	-0.6	46.0	23.9
54.250000	25.7	308.0	V	-7.0	-1.1	46.0	24.2

Note: The above data is the worst case in the all polarity direction.

## 3) Out of Band Emission:

Indicated		Table Angle Degree	Antenna Height (m)	Detector (PK/AV)	Correction Factor			Cord. Amp. (dBµV/m)	Part 15.227 & 15.209	
Freq. (MHz)	S.A. Reading (dBµV)				Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. (dB)		Limit (dBµV/m)	Margin (dB)
27.28	14.61	360	1.0	PK	30.3	0.24	0	45.15	69.5	24.35
26.96	12.21	360	1.0	PK	30.3	0.24	0	42.75	69.5	26.75

## FCC §15.227- DUTY CYCLE

### Limit

Nil (No dedicated limit specified in the Rules).

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Spectrum Analyzer	FSEM30	849720/019	2010-08-28	2011-08-27
EM Test	Loop Antenna	MS100	303298	2011-03-07	2012-03-07

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed per the NVLAP requirements, traceable to NIST.


### Test Procedure

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer=operating frequency.
4. Set the spectrum analyzer as RBW, VBW =100 kHz, Span=0 Hz, Adjust Sweep=100 ms.
5. Repeat above procedures until all frequency measured were complete.


### Test Data

Duty cycle factor =  $20 \lg (1.94/3.46) = 20 \lg (0.561) = -5.02 \text{ dB}$ .


Duty Cycle:



Date: 30.MAY.2011 16:07:20



Date: 30.MAY.2011 16:06:12



Date: 30.MAY.2011 16:06:33

## FCC §15.215(c) – 20 dB EMISSION BANDWIDTH

### Applicable Standard

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Spectrum Analyzer	FSEM30	849720/019	2010-08-28	2011-08-27
EM Test	Loop Antenna	MS100	303298	2011-03-07	2012-03-07

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that indicated 20dB bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

### Test Data


#### Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.2 kPa

\*The testing was performed by David Huang on 2011-05-30.

Test Mode: Transmitting

### Emission Bandwidth



Date: 30.MAY.2011 17:17:24

\*\*\*\*\* END OF REPORT \*\*\*\*\*