



LS RESEARCH LLC

Wireless Product Development



TESTING CERT #1255.01

W66 N220 Commerce Court • Cedarburg, WI 53012

Phone: 262.375.4400 • Fax: 262.375.4248

www.lsr.com

TEST REPORT # TR 312142 B C-1489 FCCIC DTS
LSR Job #: C-1489

Compliance Testing of:

Logic PD 37x Torpedo + Wireless SOM

Test Date(s):

January 3rd to August 2nd 2012

Prepared For:

Logic PD

411 Washington Ave N. Suite 400


Minneapolis, MN 55401

This Test Report is issued under the Authority of:
Khairul Aidi Zainal, Senior EMC Engineer


Signature: 

Date: 8/2/12

Test Report Reviewed by: Tom Smith

Signature:  Date: 8/6/2012

Project Engineer:
Khairul Aidi Zainal, Senior EMC Engineer.

Signature:  Date: 8/2/12

This Test Report may not be reproduced, except in full, without written approval of LS Research, LLC.

TABLE OF CONTENTS

EXHIBIT 1. INTRODUCTION	4
1.1 - Scope.....	4
1.2 – Normative References	4
1.3 - LS Research, LLC Test Facility	5
1.4 – Location of Testing.....	5
1.5 – Test Equipment Utilized	5
EXHIBIT 2. PERFORMANCE ASSESSMENT	6
2.1 – Client Information	6
2.2 - Equipment Under Test (EUT) Information	6
2.3 - Associated Antenna Description	6
2.4 - EUT'S Technical Specifications	7
2.5 - Product Description.....	8
EXHIBIT 3. EUT OPERATING CONDITIONS & CONFIGURATIONS DURING TESTS	9
3.1 - Climate Test Conditions.....	9
3.2 - Applicability & Summary Of EMC Emission Test Results.....	9
3.3 - Modifications Incorporated In The EUT For Compliance Purposes.....	9
3.4 - Deviations & Exclusions From Test Specifications	9
EXHIBIT 4. DECLARATION OF CONFORMITY	10
EXHIBIT 5. RADIATED EMISSIONS TEST	11
5.1 - Test Setup.....	11
5.2 - Test Procedure	11
5.3 - Test Equipment Utilized	12
5.4 - Test Results	12
5.5 - Calculation of Radiated Emissions Limits and reported data.....	13
5.6 - Radiated Emissions Test Data Chart.....	14
5.7 – Screen Captures.	18
5.7.1 Transceivers operating in the 2400 to 2483.5 MHz band	21
5.7.2 Transceivers operating in the 5725 to 5850 MHz band	22
EXHIBIT 6. CONDUCTED EMISSIONS TEST, AC POWER LINE	25
6.1 Test Setup.....	25
6.2 Test Procedure	25
6.3 Test Equipment Utilized	25

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

6.4 Test Results	25
EXHIBIT 7. OCCUPIED BANDWIDTH	29
7.1 - Limits.....	29
7.2 - Method of Measurements	29
7.3 - Test Data	29
7.4 – Screen Captures	31
EXHIBIT 8. BAND EDGE MEASUREMENTS	32
8.1 - Method of Measurements	32
8.2. Band edge captures.....	33
8.2.2.2 WLAN.....	36
EXHIBIT 9. POWER OUTPUT (CONDUCTED): 15.247(b).....	39
9.1 - Method of Measurements	39
9.2 - Test Data	39
9.3 – Screen Captures.....	42
EXHIBIT 10. CONDUCTED SPURIOUS EMISSIONS: 15.247(d).....	45
10.1 - Limits.....	45
10.2 – Conducted Harmonic And Spurious RF Measurements	45
10.3 - Test Data	46
EXHIBIT 11. POWER SPECTRAL DENSITIES: 15.247(e).....	51
11.1 Limits.....	51
11.2 Test Data.....	52
11.3 Screen Captures – Power Spectral Density	54
EXHIBIT 12. FREQUENCY & POWER STABILITY OVER VOLTAGE VARIATIONS.....	57
EXHIBIT 13. MPE CALCULATIONS	58
13.1 2400 to 2483.5 MHz Band	58
13.2 5725 to 5850 MHz Band	59
APPENDIX A – Test Equipment List.....	60
APPENDIX B – Test Standards: CURRENT PUBLICATION DATES RADIO	62
APPENDIX C - Uncertainty Statement.....	63

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

EXHIBIT 1. INTRODUCTION

1.1 - Scope

References:	FCC Part 15, Subpart C, Section 15.247 RSS GEN issue 3 and RSS 210 issue 8 Annex 8
Title:	FCC : Telecommunication – Code of Federal Regulations, CFR 47, Part 15. IC : Low-power License-exempt Radio-communication Devices (All Frequency Bands): Category I Equipment
Purpose of Test:	To gain FCC and IC Certification Authorization for Low- Power License-Exempt Transmitters.
Test Procedures:	FCC KDB 558074 D01 DTS Measurement Guidance v01
Environmental Classification:	Commercial, Industrial or Business Residential

1.2 – Normative References

Publication	Year	Title
FCC CFR Parts 0-15	2012	Code of Federal Regulations – Telecommunications
ANSI C63.4	2003	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz.
RSS-210 Annex 8	2010	Low-power License-exempt Radio communication Devices (All Frequency Bands): Category I Equipment
RSS-GEN Issue 3	2010	General Requirements and Information for the Certification of Radio Apparatus
ANSI C63.10	2009	American National Standard for Testing Unlicensed Wireless Devices
FCC KDB 558074 D01 DTS Measurement Guidance v01	2012	Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

1.3 - LS Research, LLC Test Facility

LS Research, LLC is accredited by A2LA (American Association for Laboratory Accreditation) as conforming to ISO/IEC 17025, 2005 "General Requirements for the Competence of Calibration and Testing Laboratories".

LS Research, LLC's scope of accreditation includes all test methods listed herein, unless otherwise noted. Accreditation status can be verified at A2LA's web site: www.a2la2.net.

1.4 - Location of Testing

All testing was performed at the following location utilizing the facilities listed below, unless otherwise noted.

LS Research, LLC
W66 N220 Commerce Court
Cedarburg, Wisconsin, 53012 USA,

List of Facilities Located at LS Research, LLC:

Compact Chamber
Semi-Anechoic Chamber
Open Area Test Site (OATS)

1.5 - Test Equipment Utilized

A complete list of equipment utilized in testing is provided in Appendix A of this test report. Calibration dates are indicated in Appendix A. All test equipment is calibrated by a calibration laboratory accredited to the requirements of ISO/IEC 17025, and traceable to the SI standard.

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

EXHIBIT 2. PERFORMANCE ASSESSMENT

2.1 – Client Information

Manufacturer Name:	Logic PD
Address:	411 Washington Ave N. Suite 4, Minneapolis, MN 55401
Contact Name:	Joe Charboneau

2.2 - Equipment Under Test (EUT) Information

The following information has been supplied by the applicant.

Product Name:	37x Torpedo + Wireless SOM
Model Number:	SOMDM3730-30-2780AKCR-B
Serial Number:	2012M00619/2012M01222 (Radiated) 2012M00625/2012M01201 (Radiated) 2411M00976/4511M01290 (Radiated) 4511M01221(Radiated) 2911M00065/4511M01156 (Conducted) 2012M00627/2012M01206 (Conducted) 2012M00626/2012M01208(Conducted)

2.3 - Associated Antenna Description

The antenna associated with the EUT is a dual band isolated Magnetic dipole (IMD) with gains:

1. 2.5dBi peak between 2.39 to 2.49 GHz.
2. 3.5dBi peak between 4.9 to 5.9 GHz.

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

2.4 - EUT'S Technical Specifications

EUT Frequency Range (in MHz)	2402MHz – 2480MHz (BLE) 2412MHz – 2462MHz (WLAN) 5745MHz – 5825 MHz (WLAN 5.8GHz)
RF Power in Watts (Conducted measurement)	
Minimum:	2.4GHz WLAN: 802.11b = 0.0989 802.11g = 0.0354 802.11n HT20= 0.0292 5.8GHz WLAN: 802.11a = 0.0822 802.11n HT20 = 0.0429 Bluetooth LE: 0.00091
Maximum:	2.4GHz WLAN: 802.11b = 0.1135 802.11g = 0.0423 802.11n HT20= 0.0356 5.8GHz WLAN: 802.11a = 0.1340 802.11n HT20 = 0.1413 Bluetooth LE: 0.00098
Max Conducted Output Power (in dBm)	2.4GHz WLAN: 20.6 5.8GHz WLAN: 21.5 Bluetooth LE: -0.1
Field Strength at 3 meters (Maximum)	Not Applicable
Occupied Bandwidth (99% BW)	2.4GHz WLAN: 17.79 MHz 5.8GHz WLAN: 17.63 MHz Bluetooth LE: 1.592 MHz
Type of Modulation	GFSK,OFDM,DSSS
Occupied Bandwidth (6% BW)	WLAN: 17.80 MHz Bluetooth LE: 949.6 kHz
Transmitter Spurious (worst case) at 3 meters	52.96dBμV/m at 4960MHz
Stepped (Y/N)	N
Step Value:	N/A
Frequency Tolerance %, Hz, ppm	Better than 100 ppm
Transceiver Model # (if applicable)	WL1283 (Texas Instrument)
Microprocessor #	DM3730 (Texas Instrument)
Antenna Information	
Detachable/non-detachable	Detachable
Type	Dual band isolated magnetic dipole.
Gain	2.5dBi peak between 2.39 to 2.49 GHz. 3.5dBi peak between 4.9 to 5.9 GHz.
EUT will be operated under FCC Rule Part(s)	Title 47 part 15.247
EUT will be operated under RSS Rule Part(s)	RSS 210
Modular Filing	☒ Yes ☐ No
Portable or Mobile?	Mobile

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

RF Technical Information:

Type of Evaluation		SAR Evaluation: Device Used in the Vicinity of the Human Head
(check one)		SAR Evaluation: Body-worn Device
	X	RF Evaluation

If RF Evaluation checked above, test engineer to complete the following:

Evaluated against exposure limits: ☒ General Public Use ☐ Controlled Use

Duty Cycle used in evaluation: 100 %

Standard used for evaluation: OET 65

Measurement Distance: 20 cm

2400 to 2483.5 MHz Band

RF Value: **0.406** ☐ V/m ☐ A/m ☒ W/m²
☐ Measured ☐ Computed ☒ Calculated

5745 to 5850 MHz Band

RF Value: **0.629** ☐ V/m ☐ A/m ☒ W/m²
☐ Measured ☐ Computed ☒ Calculated

2.5 - Product Description

The 37x Torpedo + wireless SOM is an ultra-compact off-the-shelf solution for applications in markets where network connectivity is required and space is a premium. The product is used by OEM integrators to gain access to 802.11 a/b/g/n, Bluetooth, and GPS capabilities.

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

EXHIBIT 3. EUT OPERATING CONDITIONS & CONFIGURATIONS DURING TESTS

3.1 - Climate Test Conditions

Temperature:	70 -71° F
Humidity:	32-42%
Pressure:	728-741mmHg

3.2 - Applicability & Summary Of EMC Emission Test Results

FCC and IC Paragraph	Test Requirements	Compliance (Yes/No)
FCC : 15.207 IC : RSS GEN sect. 7.2.2	Power Line Conducted Emissions Measurements	Yes
FCC : 15.247 (a)(1) IC : RSS 210 A8.1 (a)	20 dB Bandwidth	Yes
FCC : 15.247(b) & 1.1310 IC : RSS 210 A8.4	Maximum Output Power	Yes
FCC : 15.247(i), 1.1307, 1.1310, 2.1091 & 2.1093 IC : RSS 102	RF Exposure Limit	Yes
FCC :15.247(d) IC : RSS 210 A8.5	RF Conducted Spurious Emissions at the Transmitter Antenna Terminal	Yes
FCC:15.247 (a)(2) IC: RSS 210 A8.2 (a)	6 dB Bandwidth of a Digital Modulation System	Yes
FCC:15.247 (d) IC: RSS 210 A8.2 (b)	Power Spectral Density of a Digital Modulation System	Yes
FCC : 15.247(c), 15.209 & 15.205 IC : RSS 210 A8.2(b), section 2.2, 2.6 and 2.7	Transmitter Radiated Emissions	Yes

The digital circuit portion of the EUT has been tested and verified to comply with FCC Part 15, Subpart B, Class B Digital Devices (RSS GEN and RSS 210 of IC) and the associated Radio Receiver has also been tested and found to comply with Part 15, Subpart B – Radio Receivers (RSS GEN and RSS 210 of IC). The Receiver Test Report is available upon request.

3.3 - Modifications Incorporated In The EUT For Compliance Purposes

☒ None ☐ Yes (explain below)

3.4 - Deviations & Exclusions From Test Specifications

☒ None ☐ Yes (explain below)

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

EXHIBIT 4. DECLARATION OF CONFORMITY

The EUT was found to MEET the requirements as described within the specification of FCC Title 47, CFR Part 15.247, and Industry Canada RSS-210, Issue 8 (2010), Annex 8.

Note: If some emissions are seen to be within 3 dB of their respective limits; as these levels are within the tolerances of the test equipment and site employed, there is a possibility that this unit, or a similar unit selected out of production may not meet the required limit specification if tested by another agency.

LS Research, LLC certifies that the data contained herein was taken under conditions that meet or exceed the requirements of the test specifications. The results in this Test Report apply only to the item(s) tested on the above-specified dates. Any modifications made to the EUT subsequent to the indicated test date(s) will invalidate the data herein, and void this certification.

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

EXHIBIT 5. RADIATED EMISSIONS TEST

5.1 - Test Setup

The test setup was assembled in accordance with Title 47, CFR FCC Part 15, RSS GEN and ANSI C63.4-2003. The EUT was placed on an 80cm high non-conductive pedestal, centered on a flush mounted 2-meter diameter turntable inside a 3 meter Semi-Anechoic, FCC listed Chamber. The EUT was operated in continuous transmit mode for final testing using power as provided by a bench DC power supply. The unit has the capability to operate on 3 channels, controllable via instructions on:

1. Linux for WLAN mode (radiated measurements).
2. HCI tester tool for Bluetooth LE mode.
3. RTTT (Texas Instrument) for WLAN mode (conducted measurements).

The applicable limits apply at a 3 meter distance. The calculations to determine these limits are detailed in the following pages. Please refer to Appendix A for a complete list of test equipment. The test sample was operated on one of three (3) standard channels to comply with FCC Part 15.31(m).

5.2 - Test Procedure

Radiated RF measurements were performed on the EUT in a 3 meter Semi-Anechoic, FCC listed Chamber. The frequency range from 30 MHz to 25000 MHz was scanned and investigated. The radiated RF emission levels were manually noted at the various fixed degree settings of azimuth on the turntable and antenna height. The EUT was placed on a non-conductive pedestal in the 3 meter Semi-Anechoic Chamber, with the antenna mast placed such that the antenna was 3 meters from the EUT. A Biconical Antenna was used to measure emissions from 30 MHz to 300 MHz, and a Log Periodic Antenna was used to measure emissions from 300 MHz to 1000 MHz. A Double-Ridged Waveguide Horn Antenna was used from 1 GHz to 18 GHz while a standard gain horn antenna was used in the 18 GHz to 25 GHz range. The maximum radiated RF emissions between 30MHz to 4 GHz were found by raising and lowering the sense antenna between 1 and 4 meters in height, using both horizontal and vertical antenna polarities. Between 4GHz to 25GHz, the sense antenna was raised and lowered between 1 and 1.8 meters in height.

The EUT was positioned in 3 orthogonal orientations.

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

5.3 - Test Equipment Utilized

A list of the test equipment and antennas utilized for the Radiated Emissions test can be found in Appendix A. This list includes calibration information and equipment descriptions. All equipment is calibrated and used according to the operation manuals supplied by the manufacturers. All calibrations of the antennas used were performed at a calibration laboratory accredited to ISO 17025, and are traceable to the SI standard. In addition, the Connecting Cables were measured for losses using a calibrated Signal Generator and an EMI Receiver. The resulting correction factors and the cable loss factors from these calibrations were entered into the EMI Receiver database. As a result, the data taken from the EMI Receiver accounts for the antenna correction factor as well as cable loss or other corrections, and can therefore be entered into the database as a corrected meter reading. The EMI Receiver was operated with a resolution bandwidth of 120 kHz for measurements below 1 GHz (video bandwidth of 300 kHz), and a bandwidth of 1 MHz for measurements above 1 GHz (video bandwidth of 1 MHz).

5.4 - Test Results

The EUT was found to **MEET** the Radiated Emissions requirements of Title 47 CFR, FCC Part 15.247 and Canada RSS-210, Issue 8 (2010), Annex 8 for a DTS transmitter. The frequencies with significant RF signal strength were recorded and plotted as shown in the Data Charts and Graphs.

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

5.5 - Calculation of Radiated Emissions Limits and reported data.

Reported data:

For both fundamental and spurious emissions measurement, the data reported includes all necessary correction factors. These correction factors are loaded onto the EMI receiver when measurements are performed.

Reported Measurement data = Raw receiver measurement (dB μ V/m) + Antenna correction Factor + Cable factor (dB) + Miscellaneous factors when applicable (dB) – amplification factor when applicable (dB).

Generic example of reported data at 200 MHz:

Reported Measurement data = 18.2 (raw receiver measurement) + 15.8 (antenna factor) + 1.45 (cable factor) = 35.45 (dB μ V/m).

As specified in 15.247 (d) and RSS 210 A8.5, radiated emissions that fall within the restricted band described in 15.205(c) for FCC and section 2.2 of RSS 210 for IC, must comply with the general emissions limit.

The following table depicts the general radiated emission limits above 30 MHz. These limits are obtained from Title 47 CFR, Part 15.209, for radiated emissions measurements. These limits were applied to any signals found in the 15.205 restricted bands. The mentioned limits correspond to those limits listed in RSS GEN.

Frequency (MHz)	3 m Limit μV/m	3 m Limit (dBμV/m)	1 m Limit (dBμV/m)
30-88	100	40.0	-
88-216	150	43.5	-
216-960	200	46.0	-
960-40,000	500	54.0	63.5

Sample conversion of field strength (μ V/m to dB μ V/m):

$\text{dB}\mu\text{V/m} = 20 \log_{10} (100) = 40 \text{ dB}\mu\text{V/m}$ (from 30-88 MHz)

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

5.6 - Radiated Emissions Test Data Chart

Manufacturer:	LS Research LLC					
Date(s) of Test:	February 14 th to July 9 th 2012					
Project Engineer(s):	Khairul Aidil Zainal					
Test Engineer(s):	Khairul Aidil Zainal, Peter Feilen, Mike Hintzke and Shane Rismeyer					
Voltage:	120 VAC					
Operation Mode:	continuous transmit, modulated					
Environmental Conditions in the Lab:	Temperature: 70° F Relative Humidity: 32%					
EUT Power:	X	Single Phase 120VAC		3 Phase	VAC	
		Battery		Other: Bench DC Supply		
EUT Placement:	X	80cm non-conductive pedestal		10cm Spacers		
EUT Test Location:	X	3 Meter Semi-Anechoic FCC Listed Chamber		3/10m OATS		
Measurements:		Pre-Compliance		Preliminary	X	Final
Detectors Used:	X	Peak	X	Quasi-Peak	X	Average

The following table depicts radiated emissions below 1 GHz:

Frequency (MHz)	Height (m)	Azimuth (degree)	Quasi Peak Reading (dBμV/m)	Quasi Peak Limit (dBμV/m)	Margin (dB)	Antenna Polarity	EUT orientation
185.3	1.00	3	28.9	43.5	14.6	H	S
209.6	1.52	0	27.7	43.5	15.8	H	S
296.6	1.00	0	27.0	46.0	19.0	V	S
299.2	1.00	0	25.2	46.0	20.8	H	V
46.7	1.00	101	24.9	40.0	15.1	V	V
32.9	1.00	0	25.9	40.0	14.1	V	V
100.5	1.00	76	26.4	43.5	17.1	V	F
184.0	1.00	255	30.8	43.5	12.7	H	F
520.0	1.00	238	41.6	46.0	4.4	V	S
468.0	1.00	0	28.8	46.0	17.2	H	S
520.0	1.65	198	42.8	46.0	3.2	H	V
520.0	1.00	74	37.2	46.0	8.8	V	V
380.8	1.00	212	26.3	46.0	19.7	H	F

Notes:

1. Measurements were made at 3 meters of separation from the EUT.
2. H: Horizontal, V: Vertical, S: Side, F: Flat.
3. Refer to exhibit 5.5 on explanation of how data is reported.

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

RADIATED EMISSIONS DATA CHART (continued)

5.6.1 Bluetooth LE

The following table depicts the level of radiated emissions of channel 2402 MHz in the restricted band:

Frequency (MHz)	Height (m)	Azimuth (degree)	Peak Reading (dBμV/m)	Avg Reading (dBμV/m)	Avg Limit (dBμV/m)	Margin (dB)	Antenna Polarity	EUT orientation
4804	1.05	206	58.3	53.9	63.5	9.6	Vertical	Flat
12010	1.02	61	55.6	44.7	63.5	18.8	Vertical	Side
19216	1	130	54.3	42.6	63.5	20.9	Vertical	Side

The following table depicts the level of significant radiated emissions of channel 2440 MHz in the restricted band:

Frequency (MHz)	Height (m)	Azimuth (degree)	Peak Reading (dBμV/m)	Avg Reading (dBμV/m)	Avg Limit (dBμV/m)	Margin (dB)	Antenna Polarity	EUT orientation
4880	1.11	234	59.3	56.6	63.5	6.9	Horizontal	Flat
7320	1	148	55.6	51.1	63.5	12.4	Horizontal	Side
12200	1	57	56.2	46.6	63.5	17.0	Horizontal	Side
19520	1	165	52.6	40.9	63.5	22.6	Vertical	Flat

The following table depicts the level of significant radiated emissions of channel 2480 MHz in the restricted band:

Frequency (MHz)	Height (m)	Azimuth (degree)	Peak Reading (dBμV/m)	Avg Reading (dBμV/m)	Avg Limit (dBμV/m)	Margin (dB)	Antenna Polarity	EUT orientation
4960	1.175	90.8	64.7	62.5	63.5	1.0	Vertical	Side
7440	1.19	226	0.0	46.3	63.5	17.2	Horizontal	Flat
12400	1	177	54.5	43.8	63.5	19.8	Horizontal	Flat
19840	1.04	202.6	52.5	41.3	74.0	32.7	Horizontal	Flat

Notes:

4. Measurements above 4 GHz were made at 1 meters of separation from the EUT. The limits were adjusted to reflect this measurement distance.
5. H: Horizontal, V: Vertical, S: Side, F: Flat.
6. Refer to exhibit 5.5 on explanation of how data is reported.

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

5.6.2 2.4GHz WLAN

The following table depicts the level of radiated emissions of channel 2412 MHz in the restricted band:

Frequency (MHz)	Height (m)	Azimuth (degree)	Peak Reading (dBμV/m)	Avg Reading (dBμV/m)	Avg Limit (dBμV/m)	Margin (dB)	Antenna Polarity	EUT orientation
4824	1.00	55	58.9	55.9	63.5	7.6	Vertical	Side
12060	1.00	67	58.7	52.6	63.5	10.9	Vertical	Side
14472	1.17	91	58.1	52.8	63.5	10.7	Vertical	Side

The following table depicts the level of significant radiated emissions of channel 2437 MHz in the restricted band:

Frequency (MHz)	Height (m)	Azimuth (degree)	Peak Reading (dBμV/m)	Avg Reading (dBμV/m)	Avg Limit (dBμV/m)	Margin (dB)	Antenna Polarity	EUT orientation
4874	1.03	194	63.3	61.3	63.5	2.2	Horizontal	Flat
7311	1.04	203	60.7	56.4	63.5	7.1	Vertical	Side
12185	1.00	136	62.3	57.9	63.5	5.6	Vertical	Side

The following table depicts the level of significant radiated emissions of channel 2462 MHz in the restricted band:

Frequency (MHz)	Height (m)	Azimuth (degree)	Peak Reading (dBμV/m)	Avg Reading (dBμV/m)	Avg Limit (dBμV/m)	Margin (dB)	Antenna Polarity	EUT orientation
4924	1.072	0	61.0	58.7	63.5	4.8	Horizontal	Vertical
7386	1.056	237.9	58.5	54.2	63.5	9.3	Horizontal	Flat
12310	1	132.5	60.2	55.3	63.5	8.3	Vertical	Side

Notes:

1. Measurements above 4 GHz were made at 1 meters of separation from the EUT. The limits were adjusted to reflect this measurement distance.
2. H: Horizontal, V: Vertical, S: Side, F: Flat.
3. Refer to exhibit 5.5 on explanation of how data is reported.

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

5.6.3 5.7GHz WLAN

The following table depicts the level of radiated emissions of channel 5745 MHz in the restricted band:

Frequency (MHz)	Height (m)	Azimuth (degree)	Peak Reading (dBμV/m)	Avg Reading (dBμV/m)	Avg Limit (dBμV/m)	Margin (dB)	Antenna Polarity	EUT orientation
11490	1.00	44	60.3	59.1	63.5	4.4	Horizontal	Side
22980	1.00	155	59.4	52.7	63.5	10.8	Horizontal	Flat

The following table depicts the level of significant radiated emissions of channel 5785 MHz in the restricted band:

Frequency (MHz)	Height (m)	Azimuth (degree)	Peak Reading (dBμV/m)	Avg Reading (dBμV/m)	Avg Limit (dBμV/m)	Margin (dB)	Antenna Polarity	EUT orientation
11570	1.00	46	60.9	58.4	63.5	5.1	Horizontal	Side

The following table depicts the level of significant radiated emissions of channel 5825 MHz in the restricted band:

Frequency (MHz)	Height (m)	Azimuth (degree)	Peak Reading (dBμV/m)	Avg Reading (dBμV/m)	Avg Limit (dBμV/m)	Margin (dB)	Antenna Polarity	EUT orientation
11650	1	50.2	58.2	55.4	63.5	8.1	Horizontal	Side

Notes:


1. Measurements above 4 GHz were made at 1 meters of separation from the EUT. The limits were adjusted to reflect this measurement distance.
2. H: Horizontal, V: Vertical, S: Side, F: Flat.
3. Refer to exhibit 5.5 on explanation of how data is reported.

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489


5.7 – Screen Captures.

The screen captures below are those using the Peak detector of the analyzer. In addition, the screen captures presented are those which were deemed to be an appropriate representation of the spectrum scan.

30 to 300 MHz, 3m distance.




300 to 1000 MHz, 3m distance.




Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

1000 to 2310 MHz, 3m distance.




2390 to 2400 MHz, 3m distance.




Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

2310 to 2390 MHz, 3m distance



2.4 GHz WLAN 1Mbps. Peak


2.4 GHz WLAN 1Mbps. Average



Note: The range 2483.5 to 2500 MHz is in section 8 of this report (Band-edges).


Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

2500 to 4000 MHz, 3m distance.




5.7.1 Transceivers operating in the 2400 to 2483.5 MHz band

4000 to 18000 MHz, 1m distance.




Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

18000 to 25000 MHz, 1m distance.




5.7.2 Transceivers operating in the 5725 to 5850 MHz band

1000 to 5460 MHz, 1m distance.




Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

5850 to 8000 MHz, 1m distance.




8000 to 18000 MHz, 1m distance.



Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

18000 to 40000 MHz, 1m distance.



Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

EXHIBIT 6. CONDUCTED EMISSIONS TEST, AC POWER LINE

6.1 Test Setup

The test area and setup are in accordance with ANSI C63.4 and with Title 47 CFR, FCC Part 15, Industry Canada RSS-210 and RSS GEN. The EUT was placed on a non-conductive wooden table, with a height of 80 cm above the reference ground plane. The EUT was connected to a USB port of a generic laptop and set to transmit. The Generic laptop power supply was then plugged into a 50 Ω (ohm), 50/250 μ H Line Impedance Stabilization Network (LISN). The AC power supply of 120V was provided via an appropriate broadband EMI Filter, and then to the LISN line input. Final readings were then taken and recorded. After the EUT was setup and connected to the LISN, the RF Sampling Port of the LISN was connected to a 10 dB Attenuator-Limiter, and then to EMI receiver System. The EMCO LISN used has the ability to terminate the unused port with a 50 Ω (ohm) load when switched to either L1 (line) or L2 (neutral).

6.2 Test Procedure

The EUT was investigated in continuous modulated transmit mode for this portion of the testing. The appropriate frequency range and bandwidths were selected on the EMI Receiver, and measurements were made. The bandwidth used for these measurements is 9 kHz, as specified in CISPR 16-1, Section 1, Table 1, for Quasi-Peak and Average detectors in the frequency range of 150 kHz to 30 MHz. Final readings were then taken and recorded.

This test was performed on the EUT while it was powered using a customer supplied wall AC to DC power supply.

6.3 Test Equipment Utilized

A list of the test equipment and accessories utilized for the Conducted Emissions test is provided in Appendix A. This list includes calibration information and equipment descriptions. All equipment is calibrated and used according to the operation manuals supplied by the manufacturers. Calibrations of the LISN and Limiter were performed at an IEC/ISO 17025 accredited calibration laboratory, traceable to the SI standard. All cables are calibrated and checked periodically for conformance. The emissions are measured on the EMI System, which has automatic correction for all factors stored in memory and allows direct readings to be taken.

6.4 Test Results

The EUT was found to **MEET** the Conducted Emission requirements of FCC Part 15.207 and RSS GEN 7.2.2 for Conducted Emissions for an Intentional Radiator. See the Data Charts and Graphs for more details of the test results.

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

6.5 FCC Limits of Conducted Emissions at the AC Mains Ports

Frequency Range (MHz)	Class B Limits (dB μ V)		Measuring Bandwidth
	Quasi-Peak	Average	
0.150 -0.50 *	66-56	56-46	RBW = 9 kHz VBW $\geq$ 9 kHz for QP VBW = 1 Hz for Average
0.5 – 5.0	56	46	
5.0 – 30	60	50	
* The limit decreases linearly with the logarithm of the frequency in this range.			

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

6.6

CONDUCTED EMISSIONS TEST DATA CHART

Frequency Range inspected: 150 KHz to 30 MHz

Manufacturer:	LS Research				
Date(s) of Test:	April 2 nd 2012				
Project Engineer:	Khairul Aidi Zainal				
Test Engineer:	Mike Hintzke				
Voltage:	120 VAC				
Operation Mode:	Continuous transmit, modulated				
Environmental Conditions in the Lab:	Temperature: 71° F Relative Humidity: 40%				
Test Location:	X	AC Mains Test area			Chamber
EUT Placed On:	X	40cm from Vertical Ground Plane			10cm Spacers
	X	80cm above Ground Plane			Other:
Measurements:		Pre-Compliance		Preliminary	X Final
Detectors Used:		Peak	X	Quasi-Peak	X Average


Frequency (MHz)	Line	QUASI-PEAK			AVERAGE		
		Q-Peak Reading (dBμV)	Q-Peak Limit (dBμ V)	Quasi-Peak Margin (dB)	Average Reading (dBμV)	Average Limit (dBμ V)	Average Margin (dB)
0.150	L1	42.2	66.0	23.8	25.4	56.0	30.6
0.621	L1	29.3	56.0	26.7	24.0	46.0	22.0
4.897	L1	34.3	56.0	21.7	28.6	46.0	17.4
13.520	L1	32.6	60.0	27.4	22.4	50.0	27.6
0.150	L2	41.7	66.0	24.3	26.8	56.0	29.2
4.905	L2	33.9	56.0	22.1	28.3	46.0	17.7
13.510	L2	35.3	60.0	24.7	26.2	50.0	23.8

Notes:

- 1) The emissions listed are characteristic of the power supply used, and did not change by the EUT.


Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

6.7 Test Setup Photo(s) – Conducted Emissions Test



6.8 Screen Captures – Conducted Emissions Test

These screen captures represent Peak Emissions. For conducted emission measurements, both a Quasi-Peak detector function and an Average detector function are utilized. The emissions must meet both the Quasi-peak limit and the Average limit as described in 47 CFR 15.207 and RSS GEN 7.2.2 (Table 2).



Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

EXHIBIT 7. OCCUPIED BANDWIDTH

Test Engineer(s): Peter Feilen and Khairul Aidi Zainal

7.1 - Limits

For a DTS system operating in the 2400 to 2483.5 MHz and 5725 to 5850 MHz band, the 6dB emission bandwidth limit is 500 kHz.

7.2 - Method of Measurements

Industry Canada (IC RSS GEN 4.6.1) also requires the measurement of the 99% bandwidth in addition to the 6dB emission bandwidth. For this portion of the tests, a direct measurement of the transmitted signal was performed at the antenna port of the EUT, via a cable connection to a spectrum analyzer. An attenuator was placed in series with the cable to protect the spectrum analyzer. The loss from the cable and the attenuator were added on the analyzer as gain offset settings there by allowing direct measurements, without the need for any further corrections. The EUT was configured to run in a continuous transmit mode, while being supplied with typical data as a modulation source. A bandwidth measurement function that is built into the spectrum analyzer was used to measure the 99 % bandwidth and the 6dB bandwidth

Measurement procedure used was FCC OET KDB 558074 D01 section 5.1.2 and ANSI 63.10 (2009) section 6.9.

7.3 - Test Data

7.3.1 Bluetooth LE

Data Rate	Channel	Frequency (MHz)	EBW 6 dB (kHz)	EBW 99% (MHz)
1 Mbps	0	2402	871.9	1.309
	19	2440	868.4	1.379
	39	2480	949.6	1.592

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

7.3.2 WLAN


Data Rate	Channel	Frequency (MHz)	EBW 6 dB (MHz)	EBW 99% (MHz)
1 Mbps 802.11 b	1	2412	9.10	14.16
	6	2437	9.13	14.25
	11	2462	9.13	14.12
54 MBPS 802.11g	1	2412	16.57	16.55
	6	2437	16.53	16.00
	11	2462	16.57	16.51
MCS7 802.11n HT20	1	2412	17.80	17.70
	6	2437	17.77	17.45
	11	2462	17.80	17.79
6 MBPS 802.11a	149	5745	15.58	16.28
	157	5785	15.58	16.33
	165	5825	15.58	16.28
MCS0 802.11n HT20	149	5745	15.70	17.53
	157	5785	15.75	17.52
	165	5825	15.60	17.60
MCS7 802.11n HT20	149	5745	17.77	17.63
	157	5785	17.73	17.55
	165	5825	17.80	17.55

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489


7.4 – Screen Captures

Note: Only maximum emission bandwidth plots shown.

7.4.1 Bluetooth LE



7.4.2 WLAN



Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

EXHIBIT 8. BAND EDGE MEASUREMENTS

Test Engineer(s): Adam Alger, Khairul Aidi Zainal, Peter Feilen

8.1 - Method of Measurements

FCC 15.247(d) require a measurement of spurious emission levels to be at least 20 dB lower than the fundamental emission level, in particular at the Band-Edges where the intentional radiator operates. Also, RSS 210 Section 2.2 requires that unwanted emissions meet limits listed in RSS GEN and also to the limits in the applicable annex. The EUT was operated in continuous transmit mode with continuous modulation, with internally generated data as the modulating source. The EUT was operated at the lowest channel for the investigation of the lower Band-Edge, and at the highest channel for the investigation of the higher Band-Edge.

The Band-edge measurements were performed conducted and radiated. The measurement of band-edge was performed to satisfy FCC 15.247(d).

Conducted measurements of the spurious emission were performed with a measurement bandwidth of 100kHz.


Measurement procedure used was FCC OET KDB 558074 D01 section 5.4 and ANSI 63.10 (2009) section 6.9.

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

8.2. Band edge captures.


8.2.1 Radiated Band-edge in Restricted Band:

8.2.1.1 Bluetooth LE



Note: The limits are: 74dBuV/m for Peak and 54dBuV/m for Average


8.2.1.2 WLAN 1MBPS



Note: The limits are: 74dBuV/m for Peak and 54dBuV/m for Average


Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

8.2.1.3 WLAN 6MBPS



Note: The limits are: 74dBuV/m for Peak and 54dBuV/m for Average


8.2.1.4 WLAN 54MBPS



Note: The limits are: 74dBuV/m for Peak and 54dBuV/m for Average

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489


8.2.1.5 WLAN MCS7



Note: The limits are: 74dBuV/m for Peak and 54dBuV/m for Average

8.2.2 Conducted Band-edge:

8.2.2.1 Bluetooth LE




Note: The limits are: 20 dB below the carrier.

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489


8.2.2.2 WLAN

2.4GHz 1 MBPS



Note: The limits are: 20 dB below the carrier.


2.4GHz 54 MBPS



Note: The limits are: 20 dB below the carrier.


Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

2.4GHz MCS7



Note: The limits are: 20 dB below the carrier.


5.7GHz 6 MBPS



Note: The limits are: 20 dB below the carrier.


Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

5.7GHz MCS0



Note: The limits are: 20 dB below the carrier.

5.7GHz MCS7



Note: The limits are: 20 dB below the carrier.

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

EXHIBIT 9. POWER OUTPUT (CONDUCTED): 15.247(b)

Test Engineer(s): Peter Feilen and Khairul Aidi Zainal

9.1 - Method of Measurements

The conducted RF output power of the EUT was measured at the antenna port using a short RF cable along with an attenuator as protection for the spectrum analyzer. The loss from the cable and the attenuator were added on the analyzer as gain offset settings there by allowing direct measurements without the need for any further corrections. The unit was configured to run in a continuous transmit mode, while being supplied with typical data as a modulation source. The spectrum analyzer was used with the appropriate resolution bandwidth, with measurements from a peak detector presented in the chart below.

Measurement procedure used was FCC OET KDB 558074 D01 section 5.2.1 and ANSI 63.10 (2009) section 6.10.

9.2 - Test Data

The data reported includes all necessary correction factors. These correction factors are loaded onto the EMI receiver when measurements are performed.

Reported Measurement data = Raw receiver measurement (dBm) + Cable factor (dB) + Miscellaneous factors when applicable (dB).

Generic example of reported data at 2440 MHz:

Reported Measurement data = 8.55 (raw receiver measurement in dBm) + 0.85 (cable factor in dB) = 9.4 (dBm).

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

9.2.1 Bluetooth LE

Chan	Frequency (MHz)	Power		Limit (dBm)	Margin (dB)
		(dBm)	(mW)		
0	2402	-0.1	0.98	30.0	30.1
19	2440	-0.4	0.91	30.0	30.4
39	2480	-0.1	0.98	30.0	30.1

9.2.2 2.4GHz WLAN

A. 2.4GHz WLAN 1 MBPS

Chan	Frequency (MHz)	Power		Limit (dBm)	Margin (dB)
		(dBm)	(mW)		
1	2412.0	20.0	98.9	30.0	10.1
6	2437.0	20.0	98.9	30.0	10.1
11	2462.0	20.6	113.5	30.0	9.5

B. 2.4GHz WLAN 54 MBPS

Chan	Frequency (MHz)	Power		Limit (dBm)	Margin (dB)
		(dBm)	(mW)		
1	2412.0	15.5	35.4	30.0	14.5
6	2437.0	16.1	40.8	30.0	13.9
11	2462.0	16.3	42.3	30.0	13.7

C. 2.4GHz WLAN MCS 7

Chan	Frequency (MHz)	Power		Limit (dBm)	Margin (dB)
		(dBm)	(mW)		
1	2412.0	14.7	29.2	30.0	15.4
6	2437.0	15.4	34.6	30.0	14.6
11	3462.0	15.5	35.6	30.0	14.5

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

9.2.3 5.7GHz WLAN

A. 5 GHz WLAN 6 MBPS

Chan	Frequency (MHz)	Power		Limit (dBm)	Margin (dB)
		(dBm)	(mW)		
149	5745.0	19.2	82.2	30.0	10.9
157	5785.0	21.3	133.4	30.0	8.8
165	5825.0	21.3	134.0	30.0	8.7

B. 5 GHz WLAN MCS0

Chan	Frequency (MHz)	Power		Limit (dBm)	Margin (dB)
		(dBm)	(mW)		
149	5745.0	19.1	81.8	30.0	10.9
157	5785.0	21.2	132.7	30.0	8.8
165	5825.0	21.5	141.3	30.0	8.5


C. 5 GHz WLAN MCS7

Chan	Frequency (MHz)	Power		Limit (dBm)	Margin (dB)
		(dBm)	(mW)		
149	5745.0	16.6	45.7	30.0	13.4
157	5785.0	16.3	42.9	30.0	13.7
165	5825.0	17.1	51.2	30.0	12.9

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489


9.3 – Screen Captures.

9.3.1 Bluetooth LE




9.3.2 2.4GHz WLAN

9.3.2.1 1MBPS




Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

9.3.2.2 54 MBPS




9.3.2.3 MCS7




9.3.3 5.7GHz WLAN

9.3.3.1 6MBPS




Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

9.3.3.2 MCS0



9.3.3.3 MCS7



Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

EXHIBIT 10. CONDUCTED SPURIOUS EMISSIONS: 15.247(d)

Test Engineer(s): Adam Alger and Khairul Aidil Zainal

10.1 - Limits

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 db below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

10.2 - Conducted Harmonic And Spurious RF Measurements

FCC Part 15.247(d) and IC RSS 210 A8.5 both require a measurement of conducted harmonic and spurious RF emission levels, as reference to the carrier level when measured in a 100 kHz bandwidth. For this test, the spurious and harmonic RF emissions from the EUT were measured at the EUT antenna port using a short RF cable along with an attenuator as protection for the spectrum analyzer. The loss from the cable and the attenuator were added on the analyzer as gain offset settings, thereby allowing direct readings of the measurements made without the need for any further corrections. A spectrum analyzer was used with the resolution bandwidth set to 100 kHz for this portion of the tests. The unit was configured to run in a continuous transmit mode, while being supplied with typical data as a modulation source. The spectrum analyzer was used with measurements from a peak detector presented in the chart below. Screen captures were acquired and any noticeable spurious and harmonic signals were identified and measured.

The data reported includes all necessary correction factors. These correction factors are loaded onto the EMI receiver when measurements are performed.

Reported Measurement data = Raw receiver measurement (dBm) + Cable factor (dB) + Miscellaneous factors when applicable (dB).

Generic example of reported data at 2440 MHz:

Reported Measurement data = 8.55 (raw receiver measurement in dBm) + 0.85 (cable factor in dB) = 9.4 (dBm).

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

10.3 - Test Data

The data presented below are samples selected from the various data rates and channels tested.

A. Bluetooth LE

	Channel low	Channel middle	Channel high
Fundamental	-0.8	-1.1	-0.9
2 nd Harmonic	-69.2	-73.5	-73.8
3 rd Harmonic	-65.5	-66.3	-68.0
4 th Harmonic	-66.0	-68.1	-70.6
5 th Harmonic	-55.0	-58.7	-66.3
6 th Harmonic	-63.8	-65.1	-66.3
7 th Harmonic	-75.1	-73.1	-74.4
8 th Harmonic	-72.8	-70.2	Note 2
9 th Harmonic	Note 2	Note 2	Note 2
10 th Harmonic	Note 2	Note 2	Note 2

Note:

1. All reported data are in dBm.
2. Spurious emission buried within system noise floor.

B. 2.4GHz WLAN 1MBPS

	Channel low	Channel middle	Channel high
Fundamental	9.9	9.1	9.4
2 nd Harmonic	-66.5	-66.1	-62.5
3 rd Harmonic	-71.7	-72.0	-72.5
4 th Harmonic	-53.1	-55.9	-56.1
5 th Harmonic	-63.9	-61.6	-59.5
6 th Harmonic	-54.2	-53.8	-55.3
7 th Harmonic	-70.6	NF	-73.6
8 th Harmonic	-73.2	-72.6	-68.3
9 th Harmonic	Note 2	Note 2	Note 2
10 th Harmonic	Note 2	Note 2	Note 2

Note:

1. All reported data are in dBm.
2. Spurious emission buried within system noise floor.

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489


C. 5 GHz WLAN
6MBPS

	Channel low	Channel middle	Channel high
Fundamental	6.8	5.9	7.3
2 nd Harmonic	-72.6	-73.8	-74.0
3 rd Harmonic	-54.5	-54.3	-55.2
4 th Harmonic	NOTE 2	-70.1	-70.7
5 th Harmonic	NOTE 2	NOTE 2	NOTE 2
6 th Harmonic	NOTE 2	NOTE 2	NOTE 2
7 th Harmonic	N/A	N/A	N/A
8 th Harmonic	N/A	N/A	N/A
9 th Harmonic	N/A	N/A	N/A
10 th Harmonic	N/A	N/A	N/A


Note:

1. All reported data are in dBm.
2. Spurious emission buried within system noise floor.

10.3.1 Bluetooth LE




Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489



Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

10.3.2 2.4GHz WLAN


10.3.2.1 1MBPS



Note: Range scan of Middle Channel


10.3.3 5.7GHz WLAN

10.3.3.1 6MBPS



Note: Range scan of Middle Channel

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489



Note: Range scan of Middle Channel

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

EXHIBIT 11. POWER SPECTRAL DENSITIES: 15.247(e)

Test Engineer(s): Peter Feilen

11.1 Limits

For digitally modulate systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

In accordance with FCC Part 15.247(e) and RSS 210 A8.2(b), the peak power spectral density should not exceed +8 dBm in any 3 kHz band. This measurement was performed along with the conducted power output readings performed as described in previous sections. The peak output frequency for each representative frequency was scanned, with a narrow bandwidth, and reduced sweep, and a power density measurement was performed.

Measurement procedure used was FCC OET KDB 558074 D01 section 5.3.1

The data reported includes all necessary correction factors. These correction factors are loaded onto the EMI receiver when measurements are performed.

Reported Measurement data = Raw receiver measurement (dBm) + Cable factor (dB) + Miscellaneous factors when applicable (dB).

Generic example of reported data at 2440 MHz:

Reported Measurement data = 8.55 (raw receiver measurement in dBm) + 0.85 (cable factor in dB) = 9.4 (dBm).

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

11.2 Test Data

Per FCC OET KDB 558074 D01, the power level in a 100kHz bandwidth was scaled to an equivalent value in kHz by applying a bandwidth correction factor (BWCF)

$$\text{BWCF} = 10\log(3\text{kHz}/100\text{kHz}) = -15.2\text{dB}$$

11.2.1 Bluetooth LE

Data Rate	Channel	Frequency (MHz)	*PKPSD 100 kHz (dBm)	*PKPSD 3 kHz (dBm)	PKPSD Limit (dBm)	PKPSD Margin (dB)
1 Mbps	0	2402	-0.75	-16.0	8.0	24.0
	19	2440	-1.10	-16.3	8.0	24.3
	39	2480	-0.86	-16.1	8.0	24.1

Sample calculation:

$$\text{PKPSD (2440MHz)} = -1.1\text{dBm (100kHz)} -15.2\text{dB} = -16.3\text{dBm (3kHz)}$$

11.2.2 WLAN

A. 2.4GHz WLAN 1 MBPS

CHANNEL (MHz)	PSD IN 100 kHz (dBm)	PSD IN 3kHz (dBm)	LIMIT (dBm)	MARGIN (dB)
2412.0	8.4	-6.8	8.0	14.8
2437.0	8.4	-6.8	8.0	14.8
2462.0	8.4	-6.8	8.0	14.8

B. 2.4GHz WLAN 54 MBPS

CHANNEL (MHz)	PSD IN 100 kHz (dBm)	PSD IN 3kHz (dBm)	LIMIT (dBm)	MARGIN (dB)
2412.0	0.8	-14.4	8.0	22.4
2437.0	1.0	-14.2	8.0	22.2
2462.0	0.9	-14.3	8.0	22.3

C. 2.4GHz WLAN MCS 7

CHANNEL (MHz)	PSD IN 100 kHz (dBm)	PSD IN 3kHz (dBm)	LIMIT (dBm)	MARGIN (dB)
2412.0	-0.1	-15.3	8.0	23.3
2437.0	-0.1	-15.3	8.0	23.3
2462.0	0.3	-14.9	8.0	22.9

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

D. 5 GHz WLAN 6 MBPS

CHANNEL (MHz)	PSD IN 100 kHz (dBm)	PSD IN 3kHz (dBm)	LIMIT (dBm)	MARGIN (dB)
5745.0	2.9	-12.3	8.0	20.3
5785.0	3.9	-11.3	8.0	19.3
5825.0	3.6	-11.6	8.0	19.6

E. 5 GHz WLAN MCS0

CHANNEL (MHz)	PSD IN 100 kHz (dBm)	PSD IN 3kHz (dBm)	LIMIT (dBm)	MARGIN (dB)
5745.0	5.1	-10.1	8.0	18.1
5785.0	7.7	-7.5	8.0	15.5
5825.0	7.1	-8.1	8.0	16.1


F. 5 GHz WLAN MCS7

CHANNEL (MHz)	PSD IN 100 kHz (dBm)	PSD IN 3kHz (dBm)	LIMIT (dBm)	MARGIN (dB)
5745.0	-0.6	-15.8	8.0	23.8
5785.0	0.3	-14.9	8.0	22.9
5825.0	0.3	-14.9	8.0	22.9

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489


11.3 Screen Captures – Power Spectral Density

11.3.1 Bluetooth LE




11.3.2 2.4GHz WLAN

11.3.2.1 1MBPS




Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

11.3.2.2 54MBPS




11.3.2.3 MCS 7




11.3.3 5.7GHz WLAN

11.3.3.1 6MBPS




Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

11.3.3.2 MCS0



11.3.3.3 MCS7



Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

EXHIBIT 12. FREQUENCY & POWER STABILITY OVER VOLTAGE VARIATIONS

Test Engineer(s): Khairul Aidi Zainal

The power and frequency stability of the device was examined as a function of the input voltage available to the EUT. A Spectrum Analyzer was used to measure the RF output power and frequency at the appropriate frequency markers. Power was supplied by an external bench-type DC power supply and was varied $\pm 15\%$ from the nominal.

4.25		5.0		5.75		Channel
Power (dBm)	Frequency (Hz)	Power (dBm)	Frequency (Hz)	Power (dBm)	Frequency (Hz)	
4.2	2412000010	4.3	2412000050	4.3	2412000100	1
5.5	2437000000	5.3	2437000100	5.3	2437000010	6
5.7	2462000000	5.7	2462000015	6.0	2462000000	11

4.25		5.0		5.75		Channel
Power (dBm)	Frequency (Hz)	Power (dBm)	Frequency (Hz)	Power (dBm)	Frequency (Hz)	
2.0	2402000459	2.0	2402000479	2.0	2402000479	0
1.8	2440000560	1.8	2440000560	1.8	2440000539	19
2.2	2480000580	2.2	2480000560	2.2	2480000539	39

4.25		5.0		5.75		Channel
Power(dBm)	Frequency (Hz)	Power(dBm)	Frequency (Hz)	Power(dBm)	Frequency (Hz)	
3.8	5745002200	3.9	5745002300	3.9	5745002340	149
4.5	5785002280	4.5	5785002360	4.5	5785002280	157
4.6	5825002160	4.5	5825002220	4.5	5825002320	165

The power was then cycled On/Off to observe system response. No unusual response was observed, the emission characteristics were well behaved, and the system returned to the same state of operation as before the power cycle.

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

EXHIBIT 13. MPE CALCULATIONS

The following MPE calculations are based on a measured conducted RF power of 20.6dBm at 2462MHz and 21.5dBm at 5825MHz as presented to the antenna. The gain of this antenna, based on the data sheet is 2.5dBi and 3.5dBi respectively.

13.1 2400 to 2483.5 MHz Band

Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Maximum peak output power at antenna input terminal: 20.60 (dBm)

Maximum peak output power at antenna input terminal: 114.815 (mW)

Antenna gain(typical): 2.5 (dBi)

Maximum antenna gain: 1.778 (numeric)

Prediction distance: 20 (cm)

Prediction frequency: 2462 (MHz)

MPE limit for uncontrolled exposure at prediction frequency: 1 (mW/cm²)

Power density at prediction frequency: 0.040619 (mW/cm²)

Maximum allowable antenna gain: 16.4 (dBi)

Margin of Compliance at 20 cm = 13.9 dB

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

13.2 5725 to 5850 MHz Band

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Maximum peak output power at antenna input terminal: 21.50 (dBm)

Maximum peak output power at antenna input terminal: 141.254 (mW)

Antenna gain(typical): 3.5 (dBi)

Maximum antenna gain: 2.239 (numeric)

Prediction distance: 20 (cm)

Prediction frequency: 5825 (MHz)

MPE limit for uncontrolled exposure at prediction frequency: 1 (mW/cm²)

Power density at prediction frequency: 0.062912 (mW/cm²)

Maximum allowable antenna gain: 15.5 (dBi)

Margin of Compliance at 20 cm = 12.0 dB

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

APPENDIX A – Test Equipment List



Date: 12-Dec-2011 Type Test: AC mains Job #: C-1333 and C-1489
 Prepared By: Aidi Customer: Logic PD Quote #: 311310

No.	Asset #	Description	Manufacturer	Model #	Serial #	Cal Date	Cal Due Date	Equipment Status
1	EE 960013	EMI Receiver	HP	8546A System	3617A00320;3448A	11/22/2011	11/22/2012	Active Calibration
2	EE 960014	EMI Receiver-filter section	HP	85460A	3448A00296	11/22/2011	11/22/2012	Active Calibration
3	AA 960072	Transient Limiter	HP	11947A	3107A02515	11/22/2011	11/22/2012	Active Calibration
4	AA 960075	LSN	EMCO	3810/2NM	9612-1710	9/19/2011	9/19/2012	Active Calibration

Project Engineer: Aidi Zainal Quality Assurance: Mike Hintzle



Date: 12-Dec-2011 Type Test: Conducted measurements Job #: C-1333
 Prepared By: Aidi Customer: Logic PD Quote #: 311310

No.	Asset #	Description	Manufacturer	Model #	Serial #	Cal Date	Cal Due Date	Equipment Status
1	AA 960143	Phaselix	Gore	E3001001048.0	5546519	6/1/2011	6/1/2012	Active Calibration
2	EE 960073	SpectrumAnalyzer	Agilent	E4446A	US45300564	4/25/2011	4/25/2012	Active Calibration
3	OC 000221C	SpectrumAnalyzer	HP	E4407B	US39160256	5/4/2011	5/4/2012	Active Calibration

Project Engineer: Aidi Quality Assurance: Peter



Date: 21-Jun-2012 Type Test: Cond Measurements Job #: C-1489
 Prepared By: Aidi Customer: Logic PD Quote #: 312142

No.	Asset #	Description	Manufacturer	Model #	Serial #	Cal Date	Cal Due Date	Equipment Status
1	AA 960143	Phaselix	Gore	E3001001048.0	5546519	6/1/2011	6/1/2013	Active Calibration
2	EE 960073	SpectrumAnalyzer	Agilent	E4446A	US45300564	5/9/2012	5/9/2013	Active Calibration
3	OC 000221C	SpectrumAnalyzer	HP	E4407B	US39160256	6/5/2012	6/5/2013	Active Calibration

Project Engineer: Aidi Zainal Quality Assurance: Mike Hintzle

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

Date : 21-Jun-2012

Type Test : Rad Band-Edge

Job # : C-1333 and C-1489

Prepared By : Aidi

Customer : Logic PD

Quote # : 312142

No.	Asset #	Description	Manufacturer	Model #	Serial #	Cal Date	Cal Due Date	Equipment Status
1	EE 960157	3Hz-13.2GHz Spectrum Analyzer	Agilent	E4402A	MY48250225	6/29/2012	6/29/2013	Active Calibration
2	EE 960158	RF Preselector	Agilent	N9039A	MY46520110	6/29/2012	6/29/2013	Active Calibration
3	EE 960013	EMI Receiver	HP	8540A System	3617A00320/3448A	11/22/2011	11/22/2012	Active Calibration
4	EE 960014	EMI Receiver-filter section	HP	85480A	3448A00296	11/22/2011	11/22/2012	Active Calibration
5	EE 960147	Pre-Amp	Adv. Micro	WLA612	123101	1/6/2012	1/6/2013	Active Calibration
6	EE 960161	26.5-40GHz LNA	Ducommun Techn	ALN-33144030	1103717-01	10/4/2011	10/4/2012	Active Calibration
7	EE 960146	Std. Gain Horn Ant. w/preamp	Adv. Micro	WLA622-4	123001	11/3/2011	11/3/2012	Active Calibration
8	AA 960144	Phas el'ex	Gore	EXD01D010720	5800373	6/1/2011	6/1/2013	Active Calibration
9	AA 960005	Biconical Antenna	EMCO	93110B	9601-2280	6/26/2012	6/26/2013	Active Calibration
10	AA 960078	Log Periodic Antenna	EMCO	93146	9701-4855	11/15/2011	11/15/2012	Active Calibration
11	AA 960081	Double Ridge Horn Antenna	EMCO	3115	6907	1/6/2012	1/6/2013	Active Calibration
12	AA 960137	Standard Gain Horn Ant.	EMCO	3160-10	69259	10/4/2011	10/4/2014	Active Calibration
13	AA 960007	Double Ridge Horn Antenna	EMCO	3115	9311-4138	5/16/2012	5/16/2013	Active Calibration
14	AA 960150	Bicon Antenna	ETS	3110B	0003-3346	11/15/2011	11/15/2012	Active Calibration

Project Engineer: Aidi

Quality Assurance: Shane

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

APPENDIX B – Test Standards: CURRENT PUBLICATION DATES RADIO

STANDARD #	DATE	Am. 1	Am. 2
ANSI C63.4	2003		
ANSI C63.10	2009		
FCC 47 CFR, Parts 0-15, 18, 90, 95	2012		
RSS GEN	2010		
RSS 210	2010		

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489

APPENDIX C - Uncertainty Statement

This uncertainty represents an expanded uncertainty expressed at approximately the 95 % confidence level, using a coverage factor of k=2.

Table of Expanded Uncertainty Values, (K=2) for Specified Measurements

Measurement Type	Particular Configuration	Uncertainty Values
Radiated Emissions	3 – Meter chamber, Biconical Antenna	4.24 dB
Radiated Emissions	3-Meter Chamber, Log Periodic Antenna	4.8 dB
Radiated Emissions	10-Meter OATS, Biconical Antenna	4.18 dB
Radiated Emissions	10-Meter OATS, Log Periodic Antenna	3.92 dB
Conducted Emissions	Shielded Room/EMCO LISN	1.60 dB
Radiated Immunity	3 Volts/Meter in 3-Meter Chamber	1.128 Volts/Meter
Conducted Immunity	3 Volts level	1.0 V

	PARAMETER	LSR ± Uncertainty
1	Radio Frequency, from F0	±1.3x10 ⁻⁷
2	Total RF conducted Power	±1.38 dB
3	RF conducted power density	±1.38 dB
4	Conducted spurious emissions	±1.38 dB
5	Radiated emissions	±4.87 dB
6	Temperature	±0.64° C
7	Humidity	±2.9 %
8	DC voltage	±0.03 %
9	Low frequency voltage	±0.1 %

Prepared For: LS Research	Model #: SOMDM3730-30-2780AKCR-B	Report #: TR 312142 B C-1489 FCCIC DTS
EUT: 37x Torpedo + Wireless SOM	Serial #: Refer to table in section 2.2	LSR Job #: C-1489