

**IEEE C95.1 2005**  
**KDB 447498 D01 V06**  
**47 C.F.R. Part 1, Subpart I, Section 1.1310**  
**47 C.F.R. Part 2, Subpart J, Section 2.1091**

## **RF EXPOSURE REPORT**

**For**

**Bicycle Power Meter**

**Model: Power Pro-R, Power Pro-L**

**Trade Name: GIANT**

*Issued to*

**Giant Manufacturing Co., Ltd.**  
**No.19, Shunfan Rd., Dajia Dist., Taichung City 437, Taiwan (R.O.C.)**

*Issued by*

**Compliance Certification Services Inc.**

**Wugu Laboratory**

**No.11, Wugong 6th Rd., Wugu Dist.,  
New Taipei City 24891, Taiwan. (R.O.C.)**

**<http://www.ccsrf.com>**

**Issued Date: April 17, 2018**



## Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	April 17, 2018	Initial Issue	ALL	Doris Chu

**TABLE OF CONTENTS**

<b>1. TEST RESULT CERTIFICATION .....</b>	<b>4</b>
<b>2. LIMIT .....</b>	<b>5</b>
<b>3. EUT SPECIFICATION .....</b>	<b>5</b>
<b>4. TEST RESULTS .....</b>	<b>6</b>
<b>5. MAXIMUM PERMISSIBLE EXPOSURE.....</b>	<b>7</b>

## 1. TEST RESULT CERTIFICATION

### We hereby certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10: 2013 and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.


APPLICABLE STANDARDS	
STANDARD	TEST RESULT
IEEE C95.1 2005	
KDB 447498 D03	
47 C.F.R. Part 1, Subpart I, Section 1.1310	No non-compliance noted
47 C.F.R. Part 2, Subpart J, Section 2.1091	

Approved by:



Sam Chuang  
Manager  
Compliance Certification Services Inc.

Tested by:



Doris Chu  
Report coordinator  
Compliance Certification Services Inc.

## 2. LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

## 3. EUT SPECIFICATION

<b>EUT</b>	Bicycle Power Meter								
<b>Model</b>	Power Pro-R, Power Pro-L								
<b>Model Discrepancy</b>	The two models use the same module, the difference for the fix location								
<b>Trade Name</b>	GIANT								
<b>Frequency band (Operating)</b>	<input checked="" type="checkbox"/> Bluetooth 4.0: 2402 ~ 2480MHz ANT+: 2401MHz ~ 2480MHz <input type="checkbox"/> Others								
<b>Device category</b>	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others								
<b>Exposure classification</b>	<input type="checkbox"/> Occupational/Controlled exposure ( $S = 5\text{mW/cm}^2$ ) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure ( $S=1\text{mW/cm}^2$ )								
<b>Antenna Specification</b>	Bluetooth 4.0: 0.00 dBi (Numeric gain: 1.00) ANT+: 0.00 dBi (Numeric gain: 1.00)  Type: Monopole Antenna								
<b>Max tune up Power</b>	<table border="1"><tr><td>Bluetooth 4.0:</td><td>0.00dBm</td><td>(1.000mW)</td></tr><tr><td>ANT+:</td><td>-4.00dBm</td><td>(0.398mW)</td></tr></table>			Bluetooth 4.0:	0.00dBm	(1.000mW)	ANT+:	-4.00dBm	(0.398mW)
Bluetooth 4.0:	0.00dBm	(1.000mW)							
ANT+:	-4.00dBm	(0.398mW)							
<b>Evaluation applied</b>	<input checked="" type="checkbox"/> MPE Evaluation* <input type="checkbox"/> SAR Evaluation <input type="checkbox"/> N/A								

---

## 4. TEST RESULTS

No non-compliance noted.

### Calculation

Given  $E = \frac{\sqrt{30 \times P \times G}}{d}$  &  $S = \frac{E^2}{377}$

Where  $E$  = Field strength in Volts / meter

$P$  = Power in Watts

$G$  = Numeric antenna gain

$d$  = Distance in meters

$S$  = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377d^2}$$

Changing to units of mW and cm, using:

$P$  (mW) =  $P$  (W) / 1000 and

$d$  (cm) =  $d$ (m) / 100

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where  $d$  = Distance in cm

$P$  = Power in mW

$G$  = Numeric antenna gain

$S$  = Power density in mW /  $cm^2$

## 5. MAXIMUM PERMISSIBLE EXPOSURE

Substituting the MPE safe distance using  $d = 20$  cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where  $P$  = Power in mW

$G$  = Numeric antenna gain

$S$  = Power density in mW / cm<sup>2</sup>

### Bluetooth 4.0:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm <sup>2</sup>	Limit (mW/cm <sup>2</sup> )
0	2402	1.000	1	20	0.0002	1.000

### ANT+:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm <sup>2</sup>	Limit (mW/cm <sup>2</sup> )
1	2401	0.398	1	20	0.0001	1.000