



SAR EVALUATION REPORT

For

Electronics Technology (Dongguan) Company Limited

No.161, Xin Min Road, Tong Luo Wei Industrial Zone, Jin Xia, Chang An Town, Dong Guan, Guang Dong, China

FCC ID: ZL9M72T2

Product Type: Report Type: Original Report MID Kenny Guo **Test Engineer:** Kenny Guo **Report Number:** RSZ110518001-20 **Report Date:** 2011-09-02 Merry Zhao **Reviewed By:** EMC Engineer Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, **Prepared By:** ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP*, or any agency of the Federal Government.

^{*} This report contains data that are not covered by the NVLAP accreditation and are marked with an asterisk "★" (Rev.2)

	Att	testation of Test Results				
	Company Name	Electronics Technology (Dongguan) Company Li	mited			
EUT	EUT Description	MID				
Information	FCC ID	ZL9M72T2				
	Model Number M72T2, M72C2, M72J2					
	Date Test	2011-09-02				
	Max. SAR I	Level (s) Measured	Limit (W/Kg)			
802.11b		0.089 W/Kg, 1g Body Tissue				
802.11g	1	0.083 W/Kg, 1g Body Tissue				
Applicable Standards	ANSI/IEEE C95.1: 1999 IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fileds, 3 kHz to 300 GHz ANSI/IEEE C95.3: 2002 IEEE Recommended Practice for Measurements and Computations of Radio Frequency Electromagnetic Fields With Respect to Human Exposure to SuchFields, 100 kHz—300 GHz OET BULLETIN 65 SUPPLEMENT C Evaluating Compliance with FCC Guidelines for Human Exposure To Radiofrequency Electromagnetic Fields IEEE1528: 2003 IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques					

Note: This wireless device has been shown to be capable of compliance for localized specific absorption rate (SAR) for General Population/Uncontrolled Exposure limits specified in ANSI/IEEE Standards and has been tested in accordance with the measurement procedures specified in FCC OET 65 Supplement C and IEEE 1528-2003.

The results and statements contained in this report pertain only to the device(s) evaluated.

FCC OET Bulletin 65-C 2 of 62

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	
EUT DESCRIPTION	5
TECHNICAL SPECIFICATION	5
REFERENCE, STANDARDS AND GUILDELINES	
SAR LIMITS	
FACILITIES AND ACCREDITATION	8
DESCRIPTION OF TEST SYSTEM	9
EQUIPMENT LIST AND CALIBRATION	10
EQUIPMENTS LIST & CALIBRATION INFORMATION	16
SAR MEASUREMENT SYSTEM VERIFICATION	17
Liquid Verification	
SYSTEM ACCURACY VERIFICATIONSAR SYSTEM CHECK RESULTS	
EUT TEST STRATEGY AND METHODOLOGY	
TEST POSITIONS FOR DEVICE OPERATING NEXT TO A PERSON'S EAR	
CHEEK/TOUCH POSITION	22
EAR/TILT POSITION	
SAR Evaluation Procedure	
OUTPUT POWER VERIFICATION	25
TEST BLOCK DIAGRAM AND PROCEDURE	
TEST RESULTS	
SAR MEASUREMENT RESULTS	
EUT SCAN RESULTS	27
APPENDIX A – MEASUREMENT UNCERTAINTY	37
APPENDIX B – PROBE CALIBRATION CERTIFICATES	38
APPENDIX C – DIPOLE CALIBRATION CERTIFICATES	48
APPENDIX D – EUT TEST POSITION PHOTOS	57
LIQUID DEPTH ≥ 15 CM.	
SETUP PHOTO - POSITION A (EUT BOTTOM SIDE TOUCH TO FLAT PHANTOM)	
SETUP PHOTO - POSITION B (EUT RIGHT SIDE TOUCH TO FLAT PHANTOM)	58
APPENDIX E – EUT PHOTOS	59
EUT – Front Side View	
EUT – BACK SIDE VIEW	
EUT-BOTTOM SIDE VIEW	
APPENDIX F - INFORMATIVE REFERENCES	
PRODUCT SIMILARITY DECLARATION LETTER	62

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	RSZ110518001-20	Original Report	2011-09-02

FCC OET Bulletin 65-C 4 of 62

EUT DESCRIPTION

Test report has been prepared on behalf of ELECTRONICS TECHNOLOGY (DONG GUAN) COMPANY LIMITED, and their product, FCC ID: ZL9M72T2, Model Number: M72T2, M72C2, M72J2 or the EUT (Equipment Under Test) as referred to this report is a MID, which was measured approximately: 19.75 cm (L) x 14.2 cm (W) x 0.85 cm (H), rated input voltage: DC 5V from USB, and DC 3.7 V Battery.

Report No.: RSZ110518001-20

Technical Specification

Product Type	Portable
Exposure Category:	Population/Uncontrolled
Antenna Type(s):	Internal Antenna
Body-Worn Accessories:	None
Face-Head Accessories:	None
Mode of Operation	802.11b/g
Frequency Band:	2412-2462 MHz
Conducted RF Power:	14.01 dBm (802.11b)
	12.30 dBm (802.11g)
Dimensions (L*W*H):	197 mm (L)×143 mm (W)×10 mm (H)
Weight:	233 g
Power Source:	3.7 VDC/25000mAh Rechargeable Battery
Normal Operation:	Tablet bottom face and Tablet edges.

FCC OET Bulletin 65-C 5 of 62

REFERENCE, STANDARDS AND GUILDELINES

FCC:

The Report and Order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 mW/g as recommended by the ANSI/IEEE standard C95.1-1992 [6] for an uncontrolled environment (Paragraph 65). According to the Supplement C of OET Bulletin 65 "Evaluating Compliance with FCC Guide-lines for Human Exposure to Radio frequency Electromagnetic Fields", released on Jun 29, 2001 by the FCC, the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.

Report No.: RSZ110518001-20

This report describes the methodology and results of experiments performed on wireless data terminal. The objective was to determine if there is RF radiation and if radiation is found, what is the extent of radiation with respect to safety limits. SAR (Specific Absorption Rate) is the measure of RF exposure determined by the amount of RF energy absorbed by human body (or its parts) – to determine how the RF energy couples to the body or head which is a primary health concern for body worn devices. The limit below which the exposure to RF is considered safe by regulatory bodies in North America is 1.6 mW/g average over 1 gram of tissue mass.

CE:

The order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 2 mW/g as recommended by EN62209-1 for an uncontrolled environment. According to the Standard, the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.

This report describes the methodology and results of experiments performed on wireless data terminal. The objective was to determine if there is RF radiation and if radiation is found, what is the extent of radiation with respect to safety limits. SAR (Specific Absorption Rate) is the measure of RF exposure determined by the amount of RF energy absorbed by human body (or its parts) – to determine how the RF energy couples to the body or head which is a primary health concern for body worn devices. The limit below which the exposure to RF is considered safe by regulatory bodies in Europe is 2 mW/g average over 10 gram of tissue mass.

The test configurations were laid out on a specially designed test fixture to ensure the reproducibility of measurements. Each configuration was scanned for SAR. Analysis of each scan was carried out to characterize the above effects in the device.

FCC OET Bulletin 65-C 6 of 62

SAR Limits

FCC Limit (1g Tissue)

	SAR (W/kg)			
EXPOSURE LIMITS	(General Population / Uncontrolled Exposure Environment)	(Occupational / Controlled Exposure Environment)		
Spatial Average (averaged over the whole body)	0.08	0.4		
Spatial Peak (averaged over any 1 g of tissue)	1.60	8.0		
Spatial Peak (hands/wrists/feet/ankles averaged over 10 g)	4.0	20.0		

CE Limit (10g Tissue)

	SAR (W/kg)			
EXPOSURE LIMITS	(General Population / Uncontrolled Exposure Environment)	(Occupational / Controlled Exposure Environment)		
Spatial Average (averaged over the whole body)	0.08	0.4		
Spatial Peak (averaged over any 10 g of tissue)	2.0	10		
Spatial Peak (hands/wrists/feet/ankles averaged over 10 g)	4.0	20.0		

Population/Uncontrolled Environments are defined as locations where there is the exposure of individual who have no knowledge or control of their exposure.

Occupational/Controlled Environments are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure (i.e. as a result of employment or occupation).

General Population/Uncontrolled environments Spatial Peak limit 1.6W/kg (FCC) & 2 W/kg (CE) applied to the EUT.

FCC OET Bulletin 65-C 7 of 62

FACILITIES AND ACCREDITATION

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect data is located at

Report No.: RSZ110518001-20

6/F, the 3rd Phase of WanLi Industrial Building, Shi Hua Road, Fu Tian Free Trade Zone, Shenzhen, Guangdong, P.R. of China

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (Lab Code 200707-0).

The current scope of accreditations can be found at http://ts.nist.gov/Standards/scopes/2007070.htm

FCC OET Bulletin 65-C 8 of 62

DESCRIPTION OF TEST SYSTEM

These measurements were performed with ALSAS 10 Universal Integrated SAR Measurement system from APREL Laboratories.

ALSAS-10U System Description

ALSAS-10-U is fully compliant with the technical and scientific requirements of IEEE 1528, IEC 62209, CENELEC, ARIB, ACA, and the Federal Communications Commission. The system comprises of a six axes articulated robot which utilizes a dedicated controller. ALSAS-10U uses the latest methodologies. And FDTD modeling to provide a platform which is repeatable with minimum uncertainty.

Applications

Predefined measurement procedures compliant with the guidelines of CENELEC, IEEE, IEC, FCC, etc are utilized during the assessment for the device. Automatic detection for all SAR maxima are embedded within the core architecture for the system, ensuring that peak locations used for centering the zoom scan are within a 1mm resolution and a 0.05mm repeatable position. System operation range currently available up-to 6 GHz in simulated tissue.

Area Scans

Area scans are defined prior to the measurement process being executed with a user defined variable spacing between each measurement point (integral) allowing low uncertainty measurements to be conducted. Scans defined for FCC applications utilize a 10mm2 step integral, with 1mm interpolation used to locate the peak SAR area used for zoom scan assessments.



Report No.: RSZ110518001-20

Where the system identifies multiple SAR peaks (which are within 25% of peak value) the system will provide the user with the option of assessing each peak location individually for zoom scan averaging.

Zoom Scan (Cube Scan Averaging)

The averaging zoom scan volume utilized in the ALSAS-10U software is in the shape of a cube and the side dimension of a 1 g or 10 g mass is dependent on the density of the liquid representing the simulated tissue. A density of 1000 kg/m3 is used to represent the head and body tissue density and not the phantom liquid density, in order to be consistent with the definition of the liquid dielectric properties, i.e. the side length of the 1 g cube is 10mm, with the side length of the 10 g cube 21,5mm.

When the cube intersects with the surface of the phantom, it is oriented so that 3 vertices touch the surface of the shell or the center of a face is tangent to the surface. The face of the cube closest to the surface is modified in order to conform to the tangent surface.

The zoom scan integer steps can be user defined so as to reduce uncertainty, but normal practice for typical test applications (including FCC) utilize a physical step of 5x5x8 (8mmx8mmx5mm) providing a volume of 32mm in the X & Y axis, and 35mm in the Z axis.

FCC OET Bulletin 65-C 9 of 62

ALSAS-10U Interpolation and Extrapolation Uncertainty


The overall uncertainty for the methodology and algorithms the used during the SAR calculation was evaluated using the data from IEEE 1528 based on the example f3 algorithm:

$$f_3(x, y, z) = A \frac{a^2}{\frac{a^2}{4} + {x'}^2 + {y'}^2} \cdot \left(e^{-\frac{2z}{a}} + \frac{a^2}{2(a+2z)^2} \right)$$

Isotropic E-Field Probe

The isotropic E-Field probe has been fully calibrated and assessed for isotropicity, and boundary effect within a controlled environment. Depending on the frequency for which the probe is calibrated the method utilized for calibration will change.

The E-Field probe utilizes a triangular sensor arrangement as detailed in the diagram below:



SAR is assessed with a calibrated probe which moves at a default height of 5mm from the center of the diode, which is mounted to the sensor, to the phantom surface (in the Z Axis). The 5mm offset height has been selected so as to minimize any resultant boundary effect due to the probe being in close proximity to the phantom surface.

The following algorithm is an example of the function used by the system for linearization of the output from the probe when measuring complex modulation schemes.

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

Isotropic E-Field Probe Specification

Calibration Method	Frequency Dependent Below 1 GHz Calibration in air performed in a TEM Cell Above 1 GHz Calibration in air performed in waveguide	
Sensitivity	$0.70 \ \mu V/(V/m)^2$ to $0.85 \ \mu V/(V/m)^2$	
Dynamic Range	0.0005 W/kg to 100 W/kg	
Isotropic Response	Better than 0.1 dB	
Diode Compression Point (DCP)	Calibration for Specific Frequency	
Probe Tip Diameter	< 2.9 mm	
Sensor Offset	1.56 (+/- 0.02 mm)	
Probe Length	289 mm	
Video Bandwidth	@ 500 Hz: 1 dB @ 1.02 kHz: 3 dB	
Boundary Effect	Less than 2.1% for distance greater than 0.58 mm	
Spatial Resolution The spatial resolution uncertainty is less than 1.5% for a diameter probe. The spatial resolution uncertainty is less than 1.0% for 2 diameter probe		

Report No.: RSZ110518001-20

Boundary Detection Unit and Probe Mounting Device

ALSAS-10U incorporates a boundary detection unit with a sensitivity of 0.05mm for detecting all types of surfaces. The robust design allows for detection during probe tilt (probe normalize) exercises, and utilizes a second stage emergency stop. The signal electronics are fed directly into the robot controller for high accuracy surface detection in lateral and axial detection modes (X, Y, & Z).

The probe is mounted directly onto the Boundary Detection unit for accurate tooling and displacement calculations controlled by the robot kinematics. The probe is connect to an isolated probe interconnect where the output stage of the probe is fed directly into the amplifier stage of the Daq-Paq.

Daq-Paq (Analog to Digital Electronics)

ALSAS-10U incorporates a fully calibrated Daq-Paq (analog to digital conversion system) which has a 4 channel input stage, sent via a 2 stage auto-set amplifier module. The input signal is amplified accordingly so as to offer a dynamic range from $5\mu V$ to 800mV. Integration of the fields measured is carried out at board level utilizing a Co-Processor which then sends the measured fields down into the main computational module in digitized form via an RS232 communications port. Probe linearity and duty cycle compensation is carried out within the main Daq-Paq module.

ADC	12 Bit	
Amplifier Range	20 mV to 200 mV and 150 mV to 800 mV	
Field Integration	Local Co-Processor utilizing proprietary integration algorithms	
Number of Input Channels 4 in total 3 dedicated and 1 spare		
Communication	Packet data via RS232	

Axis Articulated Robot

ALSAS-10U utilizes a six axis articulated robot, which is controlled using a Pentium based real-time movement controller. The movement kinematics engine utilizes proprietary (Thermo CRS) interpolation and extrapolation algorithms, which allow full freedom of movement for each of the six joints within the working envelope. Utilization of joint 6 allows for full probe rotation with a tolerance better than 0.05mm around the central axis.



Robot/Controller Manufacturer	Thermo CRS	
Number of Axis	Six independently controlled axis	
Positioning Repeatability	0.05 mm	
Controller Type	Single phase Pentium based C500C	
Robot Reach	710 mm	
Communication	RS232 and LAN compatible	

ALSAS Universal Workstation

ALSAS Universal workstation allows for repeatability and fast adaptability. It allows users to do calibration, testing and measurements using different types of phantoms with one set up, which significantly speeds up the measurement process.

Universal Device Positioner

The universal device positioner allows complete freedom of movement of the EUT. Developed to hold a EUT in a free-space scenario any additional loading attributable to the material used in the construction of the positioner has been eliminated. Repeatability has been enhanced through the linear scales which form the design used to indicate positioning for any given test scenario in all major axes. A 15° tilt indicator is included for the of aid cheek to tilt movements for head SAR analysis. Overall uncertainty for measurements have been reduced due to the design of the Universal device positioner, which allows positioning of a device in as near to a free-space scenario as possible, and by providing the means for complete repeatability.




Phantom Types

The ALSAS-10U allows the integration of multiple phantom types. SAM Phantoms fully compliant with IEEE 1528, Universal Phantom, and Universal Flat.

APREL SAM Phantoms

The SAM phantoms developed using the IEEE SAM CAD file. They are fully compliant with the requirements for both IEEE 1528 and FCC Supplement C. Both the left and right SAM phantoms are interchangeable, transparent and include the IEEE 1528 grid with visible NF and MB lines.




FCC OET Bulletin 65-C 13 of 62

APREL Laboratories Universal Phantom

The Universal Phantom is used on the ALSAS-10U as a system validation phantom. The Universal Phantom has been fully validated both experimentally from 800MHz to 6GHz and numerically using XFDTD numerical software.

The shell thickness is 2mm overall, with a 4mm spacer located at the NF/MB intersection providing an overall thickness of 6mm in line with the requirements of IEEE-1528.

The design allows for fast and accurate measurements, of handsets, by allowing the conservative SAR to be evaluated at on frequency for both left and right head experiments in one measurement.



Tissue Dielectric Parameters for Head and Body Phantoms

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in P1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations described in Reference [12] and extrapolated according to the head parameters specified in P1528.

Ingredients	Frequency (MHz)									
(% by weight)	45	50	83	35	91	15	19	00	24	50
Tissue Type	Head	Body	Head	Body	Head	Body	Head	Body	Head	Body
Water	38.56	51.16	41.45	52.4	41.05	56.0	54.9	40.4	62.7	73.2
Salt (Nacl)	3.95	1.49	1.45	1.4	1.35	0.76	0.18	0.5	0.5	0.04
Sugar	56.32	46.78	56.0	45.0	56.5	41.76	0.0	58.0	0.0	0.0
HEC	0.98	0.52	1.0	1.0	1.0	1.21	0.0	1.0	0.0	0.0
Bactericide	0.19	0.05	0.1	0.1	0.1	0.27	0.0	0.1	0.0	0.0
Triton x-100	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	36.8	0.0
DGBE	0.0	0.0	0.0	0.0	0.0	0.0	44.92	0.0	0.0	26.7
Dielectric Constant	43.42	58.0	42.54	56.1	42.0	56.8	39.9	54.0	39.8	52.5
Conductivity (s/m)	0.85	0.83	0.91	0.95	1.0	1.07	1.42	1.45	1.88	1.78

FCC OET Bulletin 65-C 14 of 62

Recommended Tissue Dielectric Parameters for Head and Body

Frequency	Head	Tissue	Body Tissue		
(MHz)	Er	O' (S/m)	Er	O'(S/m)	
150	52.3	0.76	61.9	0.80	
300	45.3	0.87	58.2	0.92	
450	43.5	0.87	56.7	0.94	
835	41.5	0.90	55.2	0.97	
900	41.5	0.97	55.0	1.05	
915	41.5	0.98	55.0	1.06	
1450	40.5	1.20	54.0	1.30	
1610	40.3	1.29	53.8	1.40	
1800-2000	40.0	1.40	53.3	1.52	
2450	39.2	1.80	52.7	1.95	
3000	38.5	2.40	52.0	2.73	
5800	35.3	5.27	48.2	6.00	

FCC OET Bulletin 65-C 15 of 62

EQUIPMENT LIST AND CALIBRATION


Equipments List & Calibration Information

Equipment	Model	Calibration Date	S/N
CRS F3 robot	ALS-F3	N/A	RAF0805352
CRS F3 Software	ALS-F3-SW	N/A	N/A
CRS C500C controller	ALS-C500	N/A	RCF0805379
Probe mounting device & Boundary Detection Sensor System	ALS-PMDPS-3	N/A	120-00270
Universal Work Station	ALS-UWS	N/A	100-00157
Data Acquisition Package	ALS-DAQ-PAQ-3	N/A	110-00212
Miniature E-Field Probe	ALS-E-020	2011-07-14	500-00283
Dipole, 2450 MHz	ALS-D-2450-S-2	2011-08-25	220-00758
Dipole Spacer	ALS-DS-U	N/A	250-00907
R & S, Universal Radio Communication Tester	CMU200	2011-06-28	1100.0008.02
Device holder/Positioner	ALS-H-E-SET-2	N/A	170-00510
UniPhantom	ALS-P-UP-1	N/A	150-00413
Simulated Tissue 2450 MHz Body	ALS-TS-2450-B	Each Time	290-01109
Signal Generator	HP8648C	2010-09-18	3426A01345
Power Amplifier	5S1G4	N/A	71377
Spectrum Analyzer	FSEM30	2011-07-05	849720/019

Report No.: RSZ110518001-20

SAR MEASUREMENT SYSTEM VERIFICATION

Liquid Verification



Liquid Verification Setup Block Diagram

Liquid Verification Results

Frequency	Frequency Liquid Liquid Parameter		Result		
(MHz)	Type	E r	O' (S/m)	Result	
2450	Body	51.45	1.92	In Tolerance	

^{*}Liquid Verification was performed on 2011-09-02


	2450 MHz Body					
Frequency	e'	e''				
2400	51.67533	15.61390				
2405	51.65834	15.61321				
2410	51.66140	15.57276				
2415	51.69573	15.59125				
2420	51.62280	15.62138				
2425	51.61739	15.60613				
2430	51.54977	15.64971				
2435	51.46351	15.62890				
2440	51.42193	15.66198				
2445	51.39471	15.65163				
2450	51.43815	15.70668				
2455	51.24469	15.65427				
2460	51.21659	15.63667				
2465	51.40547	15.65685				
2470	51.22584	15.67418				
2475	51.19688	15.62820				
2480	51.23075	15.68876				
2485	51.27245	15.64058				
2490	51.21853	15.69972				
2495	51.21066	15.64892				
2500	51.46257	15.68583				

FCC OET Bulletin 65-C 17 of 62

System Accuracy Verification

Prior to the assessment, the system validation kit was used to test whether the system was operating within its specifications of $\pm 10\%$. The validation results are tabulated below. And also the corresponding SAR plot is attached as well in the SAR plots files.

System Verification Setup Block Diagram



System Check Results

Date	Frequency (MHz)	Liquid Type	Measured SAR (W/Kg)		Target Value (W/Kg)	Delta (%)	Tolerance (%)
Sept. 02, 2011 2450	2450	Body	1 g	52.803	52.561	0.46	± 10
	2430		10 g	23.568	24.104	-2.22	± 10

^{*} All SAR values are normalized to 1 Watt forward power.

FCC OET Bulletin 65-C 18 of 62

Report No.: RSZ110518001-20

SAR SYSTEM CHECK RESULTS

Test Laboratory: Bay Area Compliance Lab Corp. (Shenzhen)

System Performance Check 2450 MHz, Body Liquid

Dipole 2450 MHz; Type: ALS-D-2450-S-2; S/N: 220-00758

Product Data

Device Name : Dipole 2450 MHz Serial No. : 220-00758 Type : Dipole

Model : ALS-D-2450-S-2 Frequency : 2450 MHz

 Max. Transmit Pwr
 : 1 W

 Drift Time
 : 3 min(s)

 Power Drift-Start
 : 50.478 W/kg

 Power Drift-Finish
 : 50.557 W/kg

 Power Drift (%)
 : 0.156

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : System Default

Location : Center Description : Default

Tissue Data

Type : Body Serial No. : 290-01109 Frequency : 2450 MHz Last Calib. Date : 18-Aug-2011 : 20.00 °C Temperature Ambient Temp. : 21.00 °C Humidity : 50.00 RH% Epsilon : 51.45 F/m Sigma : 1.92 S/m

Density : 1000.00 kg/cu. M

Probe Data

Name : E-Field Model : E-020

Type : E-Field Triangle
Serial No. : 500-00283
Last Calib. Date : 14-Jul-2011
Frequency : 2450 MHz

Duty Cycle Factor : 1 Conversion Factor : 4.3

Probe Sensitivity : 1.20 1.20 $\mu V/(V/m)^2$

Compression Point : 95.00 mV Offset : 1.56 mm


Measurement Data

Crest Factor : 1

Scan Type : Complete Tissue Temp. : 20.00 °C Ambient Temp. : 20.00 °C

Area Scan : 7x7x1 : Measurement x=10mm, y=10mm, z=4mm Zoom Scan : 7x7x7 : Measurement x=5mm, y=5mm, z=5mm

1 gram SAR value : 52.803 W/kg 10 gram SAR value : 23.568 W/kg Area Scan Peak SAR : 47.314 W/kg Zoom Scan Peak SAR : 98.102 W/kg



2450 MHz System Check with Body Liquid

FCC OET Bulletin 65-C 20 of 62


Report No.: RSZ110518001-20


EUT TEST STRATEGY AND METHODOLOGY

Test Positions for Device Operating Next to a Person's Ear

This category includes most wireless handsets with fixed, retractable or internal antennas located toward the top half of the device, with or without a foldout, sliding or similar keypad cover. The handset should have its earpiece located within the upper ¼ of the device, either along the centerline or off-centered, as perceived by its users. This type of handset should be positioned in a normal operating position with the "test device reference point" located along the "vertical centerline" on the front of the device aligned to the "ear reference point". The "test device reference point" should be located at the same level as the center of the earpiece region. The "vertical centerline" should bisect the front surface of the handset at its top and bottom edges. A "ear reference point" is located on the outer surface of the head phantom on each ear spacer. It is located 1.5 cm above the center of the ear canal entrance in the "phantom reference plane" defined by the three lines joining the center of each "ear reference point" (left and right) and the tip of the mouth.

A handset should be initially positioned with the earpiece region pressed against the ear spacer of a head phantom. For the SCC-34/SC-2 head phantom, the device should be positioned parallel to the "N-F" line defined along the base of the ear spacer that contains the "ear reference point". For interim head phantoms, the device should be positioned parallel to the cheek for maximum RF energy coupling. The "test device reference point" is aligned to the "ear reference point" on the head phantom and the "vertical centerline" is aligned to the "phantom reference plane". This is called the "initial ear position". While maintaining these three alignments, the body of the handset is gradually adjusted to each of the following positions for evaluating SAR:





FCC OET Bulletin 65-C 21 of 62

Cheek/Touch Position

The device is brought toward the mouth of the head phantom by pivoting against the "ear reference point" or along the "N-F" line for the SCC-34/SC-2 head phantom.

This test position is established:


• When any point on the display, keypad or mouthpiece portions of the handset is in contact with the phantom.

Report No.: RSZ110518001-20

o (or) When any portion of a foldout, sliding or similar keypad cover opened to its intended self-adjusting normal use position is in contact with the cheek or mouth of the phantom.

For existing head phantoms – when the handset loses contact with the phantom at the pivoting point, rotation should continue until the device touches the cheek of the phantom or breaks its last contact from the ear spacer.

Cheek / Touch Position



Ear/Tilt Position


With the handset aligned in the "Cheek/Touch Position":

- 1) If the earpiece of the handset is not in full contact with the phantom's ear spacer (in the "Cheek/Touch position") and the peak SAR location for the "Cheek/Touch" position is located at the ear spacer region or corresponds to the earpiece region of the handset, the device should be returned to the "initial ear position" by rotating it away from the mouth until the earpiece is in full contact with the ear spacer.
- 2) (otherwise) The handset should be moved (translated) away from the cheek perpendicular to the line passes through both "ear reference points" (note: one of these ear reference points may not physically exist on a split head model) for approximate 2-3 cm. While it is in this position, the device handset is tilted away from the mouth with respect to the "test device reference point" until the inside angle between the vertical centerline on the front surface of the phone and the horizontal line passing through the ear reference point is by 15°. After the tilt, it is then moved (translated) back toward the head perpendicular to the line passes through both "ear reference points" until the device touches the phantom or the ear spacer. If the antenna touches the head first, the positioning process should be repeated with a tilt angle less than 15° so that the device and its antenna would touch the phantom simultaneously. This test position may require a device holder or positioner to achieve the translation and tilting with acceptable positioning repeatability.

FCC OET Bulletin 65-C 22 of 62

If a device is also designed to transmit with its keypad cover closed for operating in the head position, such positions should also be considered in the SAR evaluation. The device should be tested on the left and right side of the head phantom in the "Cheek/Touch" and "Ear/Tilt" positions. When applicable, each configuration should be tested with the antenna in its fully extended and fully retracted positions. These test configurations should be tested at the high, middle and low frequency channels of each operating mode; for example, AMPS, CDMA, and TDMA. If the SAR measured at the middle channel for each test configuration (left, right, Cheek/Touch, Tile/Ear, extended and retracted) is at least 2.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s). If the transmission band of the test device is less than 10 MHz, testing at the high and low frequency channels is optional.

Ear /Tilt 15° Position



Test positions for body-worn and other configurations

Body-worn operating configurations should be tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in normal use configurations. Devices with a headset output should be tested with a headset connected to the device. When multiple accessories that do not contain metallic components are supplied with the device, the device may be tested with only the accessory that dictates the closest spacing to the body. When multiple accessories that contain metallic components are supplied with the device, the device must be tested with each accessory that contains a unique metallic component. If multiple accessories share an identical metallic component (e.g., the same metallic belt-clip used with different holsters with no other metallic components), only the accessory that dictates the closest spacing to the body must be tested.

Body-worn accessories may not always be supplied or available as options for some devices that are intended to be authorized for body-worn use. A separation distance of 1.5 cm between the back of the device and a flat phantom is recommended for testing body-worn SAR compliance under such circumstances. Other separation distances may be used, but they should not exceed 2.5 cm. In these cases, the device may use body-worn accessories that provide a separation distance greater than that tested for the device provided however that the accessory contains no metallic components.

FCC OET Bulletin 65-C 23 of 62

SAR Evaluation Procedure

The evaluation was performed with the following procedure:

Step 1: Measurement of the SAR value at a fixed location above the ear point or central position was used as a reference value for assessing the power drop. The SAR at this point is measured at the start of the test and then again at the end of the testing.

Report No.: RSZ110518001-20


- Step 2: The SAR distribution at the exposed side of the head was measured at a distance of 4 mm from the inner surface of the shell. The area covered the entire dimension of the head or EUT and the horizontal grid spacing was 10 mm x 10 mm. Based on these data, the area of the maximum absorption was determined by spline interpolation. The first Area Scan covers the entire dimension of the EUT to ensure that the hotspot was correctly identified.
- Step 3: Around this point, a volume of 35 mm x 35 mm x 35 mm was assessed by measuring 7x 7 x 7 points. On the basis of this data set, the spatial peak SAR value was evaluated under the following procedure:
 - 1) The data at the surface were extrapolated, since the center of the dipoles is 1.2 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.3 mm. The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip.
 - 2) The maximum interpolated value was searched with a straightforward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1 g or 10 g) were computed by the 3D-Spline interpolation algorithm. The 3D-Spline is composed of three one dimensional splines with the "Not a knot"-condition (in x, y and z-directions). The volume was integrated with the trapezoidal-algorithm. One thousand points (10 x 10 x 10) were interpolated to calculate the averages.
 - All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
- Step 4: Re-measurement of the SAR value at the same location as in Step 1. If the value changed by more than 5%, the evaluation was repeated.

FCC OET Bulletin 65-C 24 of 62

OUTPUT POWER VERIFICATION

Test Block Diagram and Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.



Test Results

Radio	Frequency	Conducted Output Power			
Mode	(MHz)	(dBm) (mW) 13.22 20.99			
802.11b	2412	13.22	20.99		
	2437	13.87	24.38		
	2462	14.01	25.17		
802.11g	2412	11.66	14.66		
	2437	12.30	16.98		
	2462	11.34	13.61		

FCC OET Bulletin 65-C 25 of 62

SAR MEASUREMENT RESULTS

This page summarizes the results of the performed dosimetric evaluation. The plots with the corresponding SAR distributions, which reveal information about the location of the maximum SAR with respect to the device, could be found in the following plots.

Test Environmental Conditions

Temperature:	21° C		
Relative Humidity:	51%		
ATM Pressure:	1002 mbar		

^{*} Testing was performed by Kenny Guo on 2011-09-02.

Radio Mode	Test Position	Frequency (MHz)		Antenna	1 g SAR Value	FCC Limit
		Channel	MHz	Type	(W/Kg)	(W/Kg)
802.11b	Position A	11	2412	Integral	0.084	1.6
	Position B	11	2412	Integral	0.086	1.6
	Position C	1	2412	Integral	0.057	1.6
		6	2437	Integral	0.076	1.6
		11	2462	Integral	0.089	1.6
802.11g	Position A	6	2437	Integral	0.077	1.6
	Position B	6	2437	Integral	0.073	1.6
	Position C	1	2412	Integral	0.045	1.6
		6	2437	Integral	0.083	1.6
		11	2462	Integral	0.053	1.6

Note: 1) Please refer to the details antenna location information in Appendix D of this report.

- 2) Position A: Bottom side of the EUT touches to the flat phantom directly
- 3) Position B: Right side of the EUT touches to the flat phantom directly
- 4) Position C: Back side of the EUT touches to the flat phantom directly

FCC OET Bulletin 65-C 26 of 62

EUT SCAN RESULTS

Test Laboratory: Bay Area Compliance Lab Corp. (Shenzhen)

802.11b; Position A (Channel - 11)

Measurement Data

Test mode : 802.11b Crest Factor : 1

Scan Type : Complete

Area Scan : 15x6x1: Measurement x=10mm, y=10mm, z=4mm Zoom Scan : 7x7x7: Measurement x=5mm, y=5mm, z=5mm

Power Drift-Start : 0.162 W/kg Power Drift-Finish : 0.158 W/kg Power Drift (%) : -3.334

Tissue Data

 Type
 : BODY

 Frequency
 : 2450 MHz

 Epsilon
 : 51.45 F/m

 Sigma
 : 1.92 S/m

 Density
 : 1000.00 kg/cu. m

Probe Data

Serial No. : 500-00283 Frequency : 2450 MHz


Duty Cycle Factor : 1 Conversion Factor : 4.3

Probe Sensitivity : 1.20 1.20 1.20 $\mu V/(V/m)$ 2

Compression Point : 95.00 mV Offset : 1.56 mm

1 gram SAR value : 0.084 W/kg 10 gram SAR value : 0.045 W/kg Area Scan Peak SAR : 0.085 W/kg Zoom Scan Peak SAR : 0.200 W/kg

Plot 1#



FCC OET Bulletin 65-C 27 of 62

802.11b; Position B (Channel - 11)

Measurement Data

Test mode : 802.11b Crest Factor : 1

Scan Type : Complete

Area Scan : 20x6x1 : Measurement x=10mm, y=10mm, z=4mm Zoom Scan : 7x7x7 : Measurement x=5mm, y=5mm, z=5mm

Power Drift-Start : 0.191 W/kg Power Drift-Finish : 0.196 W/kg Power Drift (%) : 3.168

Tissue Data

 Type
 : BODY

 Frequency
 : 2450 MHz

 Epsilon
 : 51.45 F/m

 Sigma
 : 1.92 S/m

 Density
 : 1000.00 kg/cu. m

Probe Data

Serial No. : 500-00283 Frequency : 2450 MHz


Duty Cycle Factor : 1 Conversion Factor : 4.3

Probe Sensitivity : 1.20 1.20 1.20 $\mu V/(V/m)2$

Compression Point : 95.00 mV Offset : 1.56 mm

1 gram SAR value : 0.086 W/kg 10 gram SAR value : 0.053 W/kg Area Scan Peak SAR : 0.094 W/kg Zoom Scan Peak SAR : 0.210 W/kg

Plot 2#



FCC OET Bulletin 65-C 28 of 62

802.11b; Position C (Channel - 1)

Measurement Data

Test mode : 802.11b Crest Factor : 1

Scan Type : Complete

Area Scan : 15x10x1 : Measurement x=10mm, y=10mm, z=4mm Zoom Scan : 7x7x7 : Measurement x=5mm, y=5mm, z=5mm

: 0.008 W/kg Power Drift-Start Power Drift-Finish : 0.008 W/kg : 0.103 Power Drift (%)

Tissue Data

Type : BODY Frequency : 2450 MHz Epsilon : 51.45 F/m Sigma : 1.92 S/m Density : 1000.00 kg/cu. m

Probe Data

Serial No. : 500-00283 Frequency : 2450 MHz

: 1 **Duty Cycle Factor** Conversion Factor


: 4.3

: 1.20 1.20 Probe Sensitivity 1.20 $\mu V/(V/m)2$

Compression Point : 95.00 mV : 1.56 mm Offset

1 gram SAR value : 0.057 W/kg 10 gram SAR value : 0.030 W/kg Area Scan Peak SAR : 0.056 W/kg Zoom Scan Peak SAR : 0.090 W/kg

Plot 3#



FCC OET Bulletin 65-C 29 of 62

802.11b; Position C (Channel - 6)

Measurement Data

Test mode : 802.11b Crest Factor : 1

Scan Type : Complete

Area Scan : 15x10x1 : Measurement x=10mm, y=10mm, z=4mm Zoom Scan : 7x7x7 : Measurement x=5mm, y=5mm, z=5mm

Power Drift-Start : 0.040 W/kg Power Drift-Finish : 0.040 W/kg Power Drift (%) : -0.146

Tissue Data

Type : BODY Frequency : 2450 MHz Epsilon : 51.45 F/m Sigma : 1.92 S/m Density : 1000.00 kg/cu. m

Probe Data

Serial No. : 500-00283 Frequency : 2450 MHz

: 1 **Duty Cycle Factor** Conversion Factor


: 4.3

: 1.20 1.20 Probe Sensitivity 1.20 $\mu V/(V/m)2$

Compression Point : 95.00 mV : 1.56 mm Offset

1 gram SAR value : 0.076 W/kg 10 gram SAR value : 0.037 W/kg Area Scan Peak SAR : 0.081 W/kg Zoom Scan Peak SAR : 0.112 W/kg

Plot 4#



FCC OET Bulletin 65-C 30 of 62

802.11b; Position C (Channel - 11)

Measurement Data

Test mode : 802.11b Crest Factor : 1

Scan Type : Complete

Area Scan : 15x10x1 : Measurement x=10mm, y=10mm, z=4mm Zoom Scan : 7x7x7 : Measurement x=5mm, y=5mm, z=5mm

Power Drift-Start : 0.014 W/kg Power Drift-Finish : 0.014 W/kg Power Drift (%) : 0.150

Tissue Data

 Type
 : BODY

 Frequency
 : 2450 MHz

 Epsilon
 : 51.45 F/m

 Sigma
 : 1.92 S/m

 Density
 : 1000.00 kg/cu. m

Probe Data

Serial No. : 500-00283 Frequency : 2450 MHz


Duty Cycle Factor : 1 Conversion Factor : 4.3

Probe Sensitivity : 1.20 1.20 1.20 $\mu V/(V/m)$ 2

Compression Point : 95.00 mV Offset : 1.56 mm

1 gram SAR value : 0.089 W/kg 10 gram SAR value : 0.044 W/kg Area Scan Peak SAR : 0.098 W/kg Zoom Scan Peak SAR : 0.135 W/kg

Plot 5#



FCC OET Bulletin 65-C 31 of 62

802.11g; Position A (Channel - 6)

Measurement Data

Test mode : 802.11g Crest Factor : 1

Scan Type : Complete

Area Scan : 15x6x1 : Measurement x=10mm, y=10mm, z=4mm Zoom Scan : 7x7x7 : Measurement x=5mm, y=5mm, z=5mm

Power Drift-Start : 0.017 W/kg Power Drift-Finish : 0.017 W/kg Power Drift (%) : 0.533

Tissue Data

 Type
 : BODY

 Frequency
 : 2450 MHz

 Epsilon
 : 51.45 F/m

 Sigma
 : 1.92 S/m

 Density
 : 1000.00 kg/cu. m

Probe Data

Serial No. : 500-00283 Frequency : 2450 MHz

Duty Cycle Factor : 1


Conversion Factor : 4.3

Probe Sensitivity : 1.20 1.20 1.20 $\mu V/(V/m)$ 2

Compression Point : 95.00 mV Offset : 1.56 mm

1 gram SAR value : 0.077 W/kg 10 gram SAR value : 0.037 W/kg Area Scan Peak SAR : 0.096 W/kg Zoom Scan Peak SAR : 0.150 W/kg

Plot 6#



FCC OET Bulletin 65-C 32 of 62

802.11g; Position B (Channel - 6)

Measurement Data

Test mode : 802.11g Crest Factor : 1

Scan Type : Complete

Area Scan : 20x6x1 : Measurement x=10mm, y=10mm, z=4mmZoom Scan : 7x7x7 : Measurement x=5mm, y=5mm, z=5mm

Power Drift-Start : 0.011 W/kg Power Drift-Finish : 0.011 W/kg Power Drift (%) : 0.207

Tissue Data

 Type
 : BODY

 Frequency
 : 2450 MHz

 Epsilon
 : 51.45 F/m

 Sigma
 : 1.92 S/m

 Density
 : 1000.00 kg/cu. m

Probe Data

Serial No. : 500-00283 Frequency : 2450 MHz


Duty Cycle Factor : 1 Conversion Factor : 4.3

Probe Sensitivity : 1.20 1.20 1.20 $\mu V/(V/m)2$

Compression Point : 95.00 mV Offset : 1.56 mm

1 gram SAR value : 0.073 W/kg 10 gram SAR value : 0.036 W/kg Area Scan Peak SAR : 0.091 W/kg Zoom Scan Peak SAR : 0.142 W/kg

Plot 7#



FCC OET Bulletin 65-C 33 of 62

802.11g; Position C (Channel -1)

Measurement Data

Test mode : 802.11g Crest Factor : 1

Scan Type : Complete

Area Scan : 16x10x1 : Measurement x=10mm, y=10mm, z=4mm Zoom Scan : 7x7x7 : Measurement x=5mm, y=5mm, z=5mm

Power Drift-Start : 0.013 W/kg Power Drift-Finish : 0.013 W/kg Power Drift (%) : 0.489

Tissue Data

 Type
 : BODY

 Frequency
 : 2450 MHz

 Epsilon
 : 51.45 F/m

 Sigma
 : 1.92 S/m

 Density
 : 1000.00 kg/cu. m

Probe Data

Serial No. : 500-00283 Frequency : 2450 MHz


Duty Cycle Factor : 1 Conversion Factor : 4.3

Probe Sensitivity : 1.20 1.20 1.20 $\mu V/(V/m)2$

Compression Point : 95.00 mV Offset : 1.56 mm

1 gram SAR value : 0.045 W/kg 10 gram SAR value : 0.028 W/kg Area Scan Peak SAR : 0.040 W/kg Zoom Scan Peak SAR : 0.077 W/kg

Plot 8#



FCC OET Bulletin 65-C 34 of 62

802.11g; Position C (Channel - 6)

Measurement Data

Test mode : 802.11g Crest Factor : 1

Scan Type : Complete

Area Scan : 16x10x1 : Measurement x=10mm, y=10mm, z=4mm Zoom Scan : 7x7x7 : Measurement x=5mm, y=5mm, z=5mm

Power Drift-Start : 0.015 W/kg Power Drift-Finish : 0.015 W/kg Power Drift (%) : 0.092

Tissue Data

 Type
 : BODY

 Frequency
 : 2450 MHz

 Epsilon
 : 51.45 F/m

 Sigma
 : 1.92 S/m

 Density
 : 1000.00 kg/cu. m

Probe Data

Serial No. : 500-00283 Frequency : 2450 MHz


Duty Cycle Factor : 1 Conversion Factor : 4.3

Probe Sensitivity : 1.20 1.20 1.20 $\mu V/(V/m)$ 2

Compression Point : 95.00 mV Offset : 1.56 mm

1 gram SAR value : 0.083 W/kg 10 gram SAR value : 0.042 W/kg Area Scan Peak SAR : 0.098 W/kg Zoom Scan Peak SAR : 0.250 W/kg

Plot 9#



FCC OET Bulletin 65-C 35 of 62

802.11g; Position C (Channel - 11)

Measurement Data

Test mode : 802.11g Crest Factor : 1

Scan Type : Complete

Area Scan : 15x10x1 : Measurement x=10mm, y=10mm, z=4mm Zoom Scan : 7x7x7 : Measurement x=5mm, y=5mm, z=5mm

Power Drift-Start : 0.022 W/kg Power Drift-Finish : 0.022 W/kg Power Drift (%) : -0.059

Tissue Data

 Type
 : BODY

 Frequency
 : 2450 MHz

 Epsilon
 : 51.45 F/m

 Sigma
 : 1.92 S/m

 Density
 : 1000.00 kg/cu. m

Probe Data

Serial No. : 500-00283 Frequency : 2450 MHz


Duty Cycle Factor : 1 Conversion Factor : 4.3

Probe Sensitivity : 1.20 1.20 1.20 $\mu V/(V/m)2$

Compression Point : 95.00 mV Offset : 1.56 mm

1 gram SAR value : 0.053 W/kg 10 gram SAR value : 0.025 W/kg Area Scan Peak SAR : 0.048 W/kg Zoom Scan Peak SAR : 0.080 W/kg

Plot 10#



FCC OET Bulletin 65-C 36 of 62

APPENDIX A – MEASUREMENT UNCERTAINTY

The uncertainty budget has been determined for the measurement system and is given in the following Table.

Measurement uncertainty for 300 MHz to 3 GHz

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c _i ¹ (1-g)	c _i ¹ (10-g)	Standard Uncertainty (1-g) %	Standard Uncertainty (10-g) %
Measurement System							
Probe Calibration	3.5	normal	1	1	1	3.5	3.5
Axial Isotropy	3.7	rectangular	$\sqrt{3}$	$(1-cp)^{1/2}$	$(1-cp)^1$	1.5	1.5
Hemispherical Isotropy	10.9	rectangular	$\sqrt{3}$	√ср	√ср	4.4	4.4
Boundary Effect	1.0	rectangular	$\sqrt{3}$	1	1	0.6	0.6
Linearity	4.7	rectangular	$\sqrt{3}$	1	1	2.7	2.7
Detection Limit	1.0	rectangular	$\sqrt{3}$	1	1	0.6	0.6
Readout Electronics	1.0	normal	1	1	1	1.0	1.0
Response Time	0.8	rectangular	$\sqrt{3}$	1	1	0.5	0.5
Integration Time	1.7	rectangular	$\sqrt{3}$	1	1	1.0	1.0
RF Ambient Condition -Noise	3.0	rectangular	$\sqrt{3}$	1	1	1.7	1.7
RF Ambient Condition - Reflections	3.0	rectangular	$\sqrt{3}$	1	1	1.7	1.7
Probe Positioner Mech. Restrictions	0.4	rectangular	$\sqrt{3}$	1	1	0.2	0.2
Restriction							
Probe Positioning with respect to Phantom Shell	2.9	rectangular	$\sqrt{3}$	1	1	1.7	1.7
Extrapolation and Integration	3.7	rectangular	$\sqrt{3}$	1	1	2.1	2.1
Test Sample Positioning	4.0	normal	1	1	1	4.0	4.0
Device Holder Uncertainty	2.0	normal	1	1	1	2.0	2.0
Drift of Output Power	0.4	rectangular	$\sqrt{3}$	1	1	0.2	0.2
		Phantor	n and Setu	ıp			
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	$\sqrt{3}$	1	1	2.0	2.0
Liquid Conductivity(target)	5.0	rectangular	$\sqrt{3}$	0.7	0.5	2.0	1.4
Liquid Conductivity(meas.)	2.6	normal	1	0.7	0.5	1.8	1.3
Liquid Permittivity(target)	5.0	rectangular	$\sqrt{3}$	0.6	0.5	1.7	1.4
Liquid Permittivity(meas.)	2.7	normal	1	0.6	0.5	1.6	1.4
Combined Uncertainty Combined Uncertainty (coverage factor=2)		RSS Normal(k=2)				9.7 19.4	9.4

FCC OET Bulletin 65-C 37 of 62

APPENDIX B – PROBE CALIBRATION CERTIFICATES

NCL CALIBRATION LABORATORIES

Report No.: RSZ110518001-20

Calibration File No.: 1251-1258

Client.: BACL Lab

CERTIFICATE OF CALIBRATION

It is certified that the equipment identified below has been calibrated in the NCL CALIBRATION LABORATORIES by qualified personnel following recognized procedures and using transfer standards traceable to NRC/NIST.

> Equipment: Miniature Isotropic RF Probe Record of Calibration Head and Body Manufacturer: APREL Laboratories

> > Model No.: E-020 Serial No.: 500-00283

Calibration Procedure: D01-032-E020-V2, D22-012-Tissue, D28-002-Dipole

Project No: BACL-5607

Calibrated: 14th July 2011 Released on: 14th July 2011

Approved By: Stuart Nicol

This Calibration Certificate is Incomplete Unless Accompanied with the Calibration Results Summary

Released By:

NCL CALIBRATION LABORATORIES

303 Terry Fox Drive, Suite 102 Kanata, Ontario CANADA K2K 3J1 Division of APREL TEL: (613) 435-8300 FAX: (613) 435-8306

FCC OET Bulletin 65-C 38 of 62

Division of APREL Inc.

Introduction

This Calibration Report reproduces the results of the calibration performed in line with the references listed below. Calibration is performed using accepted methodologies as per the references listed below. Probes are calibrated for air, and tissue and the values reported are the results from the physical quantification of the probe through meteorgical practices.

Calibration Method

Probes are calibrated using the following methods.

<1000MHz

TEM Cell for sensitivity in air

Standard phantom using temperature transfer method for sensitivity in tissue

>1000MHz

Waveguide* method to determine sensitivity in air and tissue

*Waveguide is numerically (simulation) assessed to determine the field distribution and power

The boundary effect for the probe is assessed using a standard flat phantom where the probe output is compared against a numerically simulated series of data points

References

- IEEE Standard 1528 (2003) including Amendment 1
 IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
- o EN 62209-1 (2006)

Human Exposure to RF Fields from hand-held and body-mounted wireless communication devices - Human models. instrumentation, and procedures-Part 1: Procedure to measure the Specific Absorption Rate (SAR) for hand-held mobile wireless devices

- o IEC 62209-2 Ed. 1.0 (2010-03)
 - Human exposure to RF fields from hand-held and body-mounted wireless devices Human models, instrumentation, and procedures Part 2: specific absorption rate (SAR) for wireless communication devices (30 MHz 6 GHz)
- TP-D01-032-E020-V2 E-Field probe calibration procedure
- D22-012-Tissue dielectric tissue calibration procedure
- D28-002-Dipole procedure for validation of SAR system using a dipole
- IEEE 1309 Draft Standard for Calibration of Electromagnetic Field Sensors and Probes, Excluding Antennas, from 9kHz to 40GHz

Page 2 of 10

This page has been reviewed for content and attested to on Page 2 of this document.

FCC OET Bulletin 65-C 39 of 62

Division of APREL Inc.

Conditions

Probe 500-00283 was a new probe taken from stock.

Ambient Temperature of the Laboratory: $22 \,^{\circ}\text{C}$ +/- $1.5 \,^{\circ}\text{C}$ Temperature of the Tissue: $21 \,^{\circ}\text{C}$ +/- $1.5 \,^{\circ}\text{C}$ Relative Humidity: < 60%

Primary Measurement Standards

Instrument	Serial Number	Cal due date
Power meter Anritsu MA2408A	90025437	Nov.4, 2011
Power Sensor Anritsu MA2481D	103555	Nov 4, 2011
Attenuator HP 8495A (70dB)	1944A10711	Sept. 14, 2011
Network Analyzer Anritsu MT8801C	MB11855	Feb. 8, 2012

Secondary Measurement Standards

Signal Generator Agilent E4438C -506 MY55182336 June 7, 2012

Attestation

The below named signatories have conducted the calibration and review of the data which is presented in this calibration report.

We the undersigned attest that to the best of our knowledge the calibration of this probe has been accurately conducted and that all information contained within this report has been reviewed for accuracy.

Stuart Nicol

Jesse Hones

Page 3 of 10

This page has been reviewed for content and attested to on Page 2 of this document.

FCC OET Bulletin 65-C 40 of 62

Division of APREL Inc.

Probe Summary

Probe Type: E-Field Probe E020

Serial Number: 500-00283

Frequency: As presented on page 5

 Sensor Offset:
 1.56

 Sensor Length:
 2.5

Tip Enclosure: Composite*

Tip Diameter: < 2.9 mm

 Tip Length:
 55 mm

 Total Length:
 289 mm

*Resistive to recommended tissue recipes per IEEE-1528

Sensitivity in Air

Diode Compression Point: 95 mV

FCC OET Bulletin 65-C 41 of 62

Page 4 of 10

This page has been reviewed for content and attested to on Page 2 of this document.

Division of APREL Inc.

Calibration for Tissue (Head H, Body B)

Frequency	Tissue Type	Measured Epsilon	Measured Sigma	Calibration Uncertainty	Tolerance Uncertainty for 5%*	Conversion Factor
450 H	Head	X	X	X	X	X
450 B	Body	X	X	X	X	X
750 H	Head	X	X	X	X	X
750 B	Body	X	X	X	X	X
835 H	Head	42.35	0.938	3.5	3.4	6.6
835 B	Body	56.65	1.018	3.5	3.4	6.6
900 H	Head	41.35	0.98	3.5	3.4	6
900 B	Body	56.08	1.05	3.5	3.4	6
1450 H	Head	X	X	X	X	X
1450 B	Body	X	X	X	X	X
1500 H	Head	X	X	X	X	X
1500 B	Body	X	X	X	X	X
1640 H	Head	X	X	X	X	X
1640 B	Body	X	X	X	X	X
1750 H	Head	38.72	1.35	3.5	3.4	5.1
1750 B	Body	51.62	1.48	3.5	3.4	4.8
1800 H	Head	X	Х	X	X	X
1800 B	Body	X	X	X	X	X
1900 H	Head	38.72	1.35	3.5	2.7	5.2
1900 B	Body	51.62	1.48	3.5	2.7	5
2000 H	Head	X	X	X	X	X
2000 B	Body	X	Х	X	X	X
2100 H	Head	X	X	X	X	X
2100 B	Body	X	X	X	X	X
2300 H	Head	X	Х	X	X	X
2300 B	Body	X	X	X	X	X
2450 H	Head	38.06	1.87	3.5	3.5	4.9
2450B	Body	50.22	2.03	3.5	3.5	4.3
2600 H	Head	X	X	X	X	X
2600 B	Body	X	X	X	X	X
3000 H	Head	X	X	X	X	X
3000 B	Body	X	X	X	X	X
3600 H	Head	X	X	X	X	X
3600 B	Body	X	X	X	X	X
5200 H	Head	X	X	X	X	X
5200 B	Body	X	X	X	X	X
5600 H	Head	X	X	X	X	X
5600 B	Body	X	X	X	X	X
5800 H	Head	X	X	X	Х	X
5800 B	Body	X	X	X	X	X

Page 5 of 10

This page has been reviewed for content and attested to on Page 2 of this document.

FCC OET Bulletin 65-C 42 of 62

Division of APREL Inc.

Boundary Effect:

Uncertainty resulting from the boundary effect is less than 2.1% for the distance between the tip of the probe and the tissue boundary, when less than 0.58mm.

Spatial Resolution:

The spatial resolution uncertainty is less than 1.5% for 4.9mm diameter probe. The spatial resolution uncertainty is less than 1.0% for 2.5mm diameter probe.

DAQ-PAQ Contribution

To minimize the uncertainty calculation all tissue sensitivity values were calculated using a load impedance of 5 $M\Omega$.

Boundary Effect:

For a distance of 0.58mm the worst case evaluated uncertainty (increase in the probe sensitivity) is less than 2.1%.

NOTES:

*The maximum deviation from the centre frequency when comparing the lower to upper range is listed.


Page 6 of 10

This page has been reviewed for content and attested to on Page 2 of this document.

FCC OET Bulletin 65-C 43 of 62

Division of APREL Inc.

Receiving Pattern Air





Page 7 of 10 This page has been reviewed for content and attested to on Page 2 of this document.

FCC OET Bulletin 65-C 44 of 62

Division of APREL Inc.

Isotropy Error Air





Isotropicity Tissue:


0.10 dB

Page 8 of 10
This page has been reviewed for content and attested to on Page 2 of this document.

FCC OET Bulletin 65-C 45 of 62

NCL Calibration Laboratories Division of APREL Inc.

Dynamic Range




Page 9 of 10
This page has been reviewed for content and attested to on Page 2 of this document.

46 of 62 FCC OET Bulletin 65-C

Division of APREL Inc.

Video Bandwidth

Probe Frequency Characteristics



Video Bandwidth at 500 Hz 1 dB Video Bandwidth at 1.02 KHz: 3 dB

Test Equipment

The test equipment used during Probe Calibration, manufacturer, model number and, current calibration status are listed and located on the main APREL server R:\NCL\Calibration Equipment\Instrument List May 2011.

This page has been reviewed for content and attested to on Page 2 of this document.

FCC OET Bulletin 65-C 47 of 62

Page 10 of 10

APPENDIX C – DIPOLE CALIBRATION CERTIFICATES

NCL CALIBRATION LABORATORIES

Report No.: RSZ110518001-20

Calibration File No: DC-1330 Project Number: BAC-dipole-cal-5619

CERTIFICATE OF CALIBRATION

It is certified that the equipment identified below has been calibrated in the NCL CALIBRATION LABORATORIES by qualified personnel following recognized procedures and using transfer standards traceable to NRC/NIST.

Validation Dipole (Head & Body)

Manufacturer: APREL Laboratories Part number: ALS-D-2450-S-2 Frequency: 2450 MHz Serial No: 220-00758

Customer: Bay Area Compliance Laboratory

Calibrated: 25th August, 2011 Released on: 25th August, 2011

This Calibration Certificate is Incomplete Unless Accompanied with the Calibration Results Summary

Released By:

NCL CALIBRATION LABORATORIES

Suite 102, 303 Terry Fox Dr. Kanata, ONTARIO GANADA K2K 3J1 Division of APREL Lab. TEL: (613) 435-8300 FAX: (613)435-8306

FCC OET Bulletin 65-C 48 of 62

Division of APREL Laboratories.

Conditions

Dipole 220-00758 was received in good condition and was a re-calibration.

Ambient Temperature of the Laboratory: 22 °C +/- 0.5°C Temperature of the Tissue: 21 °C +/- 0.5°C

We the undersigned attest that to the best of our knowledge the calibration of this device has been accurately conducted and that all information contained within this report has been reviewed for accuracy.

Stuart Nicol

C. Teodorian

Primary Measurement Standards Instrument Serial Number Cal due date 245025437 Power meter Anritsu MA2408A Nov.4, 2011 Power Sensor Anritsu MA2481D 103555 Nov 4, 2011 Attenuator HP 8495A (70dB) 1 944A10711 Aug.8, 2012 Network Analyzer Agilent E5071C 1334746J Feb. 8, 2012 Secondary Measurement Standards -506 MY55182336 June 7, 2012 Signal Generator Agilent E4438C

This page has been reviewed for content and attested to by signature within this document.

FCC OET Bulletin 65-C 49 of 62

Division of APREL Laboratories.

Calibration Results Summary

The following results relate the Calibrated Dipole and should be used as a quick reference for the user.

Mechanical Dimensions


Length: 52.4 mm **Height:** 30.3 mm

Electrical Specification

Tissue	Frequency	SWR:	Return Loss	Impedance
Head	2450 MHz	1.0459 U	-33.024 dB	48.533 Ω
Body	2450 MHz	1.1159 U	-25.235 dB	46.676 Ω

System Validation Results

Tissue	Frequency	1 Gram	10 Gram	Peak
Head	2450 MHz	52.667	24.518	105.920
Body	2450 MHz	52.561	24.104	108.940



3

This page has been reviewed for content and attested to by signature within this document.

FCC OET Bulletin 65-C 50 of 62

Division of APREL Laboratories.

Introduction

This Calibration Report has been produced in line with the SSI Dipole Calibration Procedure SSI-TP-018-ALSAS. The results contained within this report are for Validation Dipole 220-00758. The calibration routine consisted of a three-step process. Step 1 was a mechanical verification of the dipole to ensure that it meets the mechanical specifications. Step 2 was an Electrical Calibration for the Validation Dipole, where the SWR, Impedance, and the Return loss were assessed. Step 3 involved a System Validation using the ALSAS-10U, along with APREL E-020 130 MHz to 26 GHz E-Field Probe Serial Number 212.

References

SSI-TP-018-ALSAS Dipole Calibration Procedure

SSI-TP-016 Tissue Calibration Procedure

IEEE 1528 "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques"

IEC-62209 "Human exposure to radio frequency fields from hand-held and bodymounted wireless communication devices – Human models, instrumentation, and procedures"

Part 1: "Procedure to determine the Specific Absorption Rate (SAR) for hand-held devices used in close proximity of the ear (frequency range of 300 MHz to 3 GHz)" IEC-62209 "Human exposure to radio frequency fields from hand-held and bodymounted wireless communication devices – Human models, instrumentation, and procedures"

Part 2 Draft: "Procedure to determine the Specific Absorption Rate (SAR) for handheld devices used in close proximity of the ear (frequency range of 30 MHz to 6 GHz)"

Conditions

Dipole 220-00758 was a re-calibration.

Ambient Temperature of the Laboratory: 22 °C +/- 0.5°C Temperature of the Tissue: 20 °C +/- 0.5°C

Dipole Calibration uncertainty

The calibration uncertainty for the dipole is made up of various parameters presented below.

 Mechanical
 1%

 Positioning Error
 1.22%

 Electrical
 1.7%

 Tissue
 2.2%

 Dipole Validation
 2.2%

TOTAL 8.32% (16.64% K=2)

4

This page has been reviewed for content and attested to by signature within this document.

FCC OET Bulletin 65-C 51 of 62

Division of APREL Laboratories.

Dipole Calibration Results

Mechanical Verification

APREL	APREL	Measured	Measured
Length	Height	Length	Height
51.5 mm	30.4 mm	52.4 mm	30.3 mm

Electrical Calibration

Tissue Type	Return Loss:	SWR:	Impedance:
Head	-33.024 dB	1.0459 U	48.533 Ω
Body	-25.235 dB	1.1159 U	46.676 Ω

Tissue Validation

	Dielectric constant, ε _r	Conductivity, σ [S/m]
Head Tissue 2450MHz	38.2	1.82
Body Tissue 2450MHz	51.74	1.96

5


This page has been reviewed for content and attested to by signature within this document.


FCC OET Bulletin 65-C 52 of 62

NCL Calibration Laboratories Division of APREL Laboratories.

The Following Graphs are the results as displayed on the Vector Network Analyzer.

\$11 Parameter Return Loss






This page has been reviewed for content and attested to by signature within this document.


6

FCC OET Bulletin 65-C 53 of 62

NCL Calibration Laboratories Division of APREL Laboratories.

SWR





This page has been reviewed for content and attested to by signature within this document.

7

FCC OET Bulletin 65-C 54 of 62

Division of APREL Laboratories.

Smith Chart Dipole Impedance





This page has been reviewed for content and attested to by signature within this document.

8

FCC OET Bulletin 65-C 55 of 62

Division of APREL Laboratories.

Test Equipment

The test equipment used during Probe Calibration, manufacturer, model number and, current calibration status are listed and located on the main APREL server R:\NCL\Calibration Equipment\Instrument List May 2011.

a

This page has been reviewed for content and attested to by signature within this document.

FCC OET Bulletin 65-C 56 of 62

APPENDIX D – EUT TEST POSITION PHOTOS






Setup Photo - Position A (EUT Bottom Side touch to Flat Phantom)




FCC OET Bulletin 65-C 57 of 62

Setup Photo - Position B (EUT Right Side touch to Flat Phantom)




Setup Photo - Position C (EUT Back Side touch to Flat Phantom)



FCC OET Bulletin 65-C 58 of 62

APPENDIX E – EUT PHOTOS





EUT – Back Side View



FCC OET Bulletin 65-C 59 of 62

EUT- Bottom Side View



FCC OET Bulletin 65-C 60 of 62

APPENDIX F - INFORMATIVE REFERENCES

[1] Federal Communications Commission, \Report and order: Guidelines for evaluating the environmental effects of radiofrequency radiation", Tech. Rep. FCC 96-326, FCC, Washington, D.C. 20554, 1996.

Report No.: RSZ110518001-20

- [2] David L. Means Kwok Chan, Robert F. Cleveland, \Evaluating compliance with FCC guidelines for human exposure to radiofrequency electromagnetic fields", Tech. Rep., Federal Communication Commission, O_ce of Engineering & Technology, Washington, DC, 1997.
- [3] Thomas Schmid, Oliver Egger, and Niels Kuster, \Automated E-_eld scanning system for dosimetric assessments", IEEE Transactions on Microwave Theory and Techniques, vol. 44, pp. 105{113, Jan. 1996.
- [4] Niels Kuster, Ralph K.astle, and Thomas Schmid, \Dosimetric evaluation of mobile communications equipment with known precision", IEICE Transactions on Communications, vol. E80-B, no. 5, pp. 645{652, May 1997.
- [5] CENELEC, \Considerations for evaluating of human exposure to electromagnetic fields (EMFs) from mobile telecommunication equipment (MTE) in the frequency range 30MHz 6GHz", Tech. Rep., CENELEC, European Committee for Electrotechnical Standardization, Brussels, 1997.
- [6] ANSI, ANSI/IEEE C95.1-1992: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz, The Institute of Electrical and Electronics Engineers, Inc., New York, NY 10017, 1992.
- [7] Katja Pokovic, Thomas Schmid, and Niels Kuster, \Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies", in ICECOM _ 97, Dubrovnik, October 15{17, 1997, pp. 120-24.
- [8] Katja Pokovic, Thomas Schmid, and Niels Kuster, \E-field probe with improved isotropy in brain simulating liquids", in Proceedings of the ELMAR, Zadar, Croatia, 23 {25 June, 1996, pp. 172-175.
- [9] Volker Hombach, Klaus Meier, Michael Burkhardt, Eberhard K. uhn, and Niels Kuster, \The dependence of EM energy absorption upon human head modeling at 900 MHz", IEEE Transactions on Microwave Theory and Techniques, vol. 44, no. 10, pp. 1865-1873, Oct. 1996.
- [10] Klaus Meier, Ralf Kastle, Volker Hombach, Roger Tay, and Niels Kuster, \The dependence of EM energy absorption upon human head modeling at 1800 MHz", IEEE Transactions on Microwave Theory and Techniques, Oct. 1997, in press.
- [11] W. Gander, Computermathematik, Birkhaeuser, Basel, 1992.
- [12] W. H. Press, S. A. Teukolsky, W. T. Vetterling, and B. P. Flannery, Numerical Recepies in C, The Art of Scientific Computing, Second Edition, Cambridge University Press, 1992. Dosimetric Evaluation of Sample device, month 1998.9
- [13] NIS81 NAMAS, \The treatment of uncertainty in EMC measurement", Tech. Rep., NAMAS Executive, National Physical Laboratory, Teddington, Middlesex, England, 1994.
- [14] Barry N. Taylor and Christ E. Kuyatt, \Guidelines for evaluating and expressing the uncertainty of NIST measurement results", Tech. Rep., National Institute of Standards and Technology, 1994. Dosimetric Evaluation of Sample device, month 1998 10.
- [15] FCC OET KDB 447498 D01-Mobile and Portable Device RF Exposure Procedures.
- [16] FCC OET KDB 248227 D01-SAR Measurement Procedures for 802.11a/b/g Transmitters

FCC OET Bulletin 65-C 61 of 62

PRODUCT SIMILARITY DECLARATION LETTER

ELECTRONICS TECHNOLOGY (DONG GUAN) COMPANY LIMITED

No.161, Xin Min Road, Tong Luo Wei Industrial Zone, Jin Xia, Chang An Town, Dong Guan City, Guang Dong Province, China

Report No.: RSZ110518001-20

Tel: 0755-86335557 Fax: 0755-86335566

Date: 2011-07-01

Product Similarity Declaration

To Whom It May Concern,

We, <u>ELECTRONICS TECHNOLOGY</u> (<u>DONG GUAN</u>) <u>COMPANY LIMITED</u> hereby declare that our MID, Model Number: M72C2, M72J2 are electrically identical with the M72T2 that was certified by BACL. They are just different in appearance and model names, due to marketing purposes.

Please contact me if you have any question.

Signature:

Xiaona liu

Quality Manager

***** END OF REPORT *****

FCC OET Bulletin 65-C 62 of 62