

Test of Micro-Sensys GmbH RFID Pen Style Read/Write Unit ilD PENsolid HF to 47 CFR 15.225 and RSS-210 Issue 8

PHOTOGRAPHS OF TEST SET-UP

## ANNEX 1 TO TEST REPORT # EMCC-980398GB, 2016-04-11

EQUIPMENT UNDER TEST:	DEID Don Chilo Dood/Mito Unit	
Trade Name:	RFID Pen Style Read/Write Unit iID PENsolid HF	
Type Designation(s): Serial Number:	Sample #1: 102067	
Serial Number.	Sample #1: 102007 Sample #2: 102069	
Equipment Class:	Low Power Transceiver	
Manufacturer:	Micro-Sensys GmbH	
Address:	In der Hochstedter Ecke 2	
	99098 Erfurt	
	Germany	
Phone:	+49 361 59874-0	
Fax:	+49 361 59874-17	
RELEVANT STANDARD(S):	47 CFR 15.225; RSS-210 Issue 8	
MEASUREMENT PROCEDURE:		
⊠ RSS-Gen Issue 4		
CONTENTS		Page


Carrier frequency stability.....



Issue Date: 2016-04-11

Test of Micro-Sensys GmbH RFID Pen Style Read/Write Unit iID PENsolid HF to 47 CFR 15.225 and RSS-210 Issue 8


## 1 RADIATED AND CONDUCTED EMISSIONS TEST




Radiated emissions measurement at 3 m distance in SAC 9 kHz – 30 MHz



Radiated emissions measurement at 3 m distance at open field site;9 kHz – 30 MHz



Radiated emissions measurement at 3 m distance 30 MHz – 300 MHz



Radiated emissions measurement at 3 m distance 30 MHz – 300 MHz



Page 3 of 4

Issue Date: 2016-04-11

## Test of Micro-Sensys GmbH RFID Pen Style Read/Write Unit ilD PENsolid HF to 47 CFR 15.225 and RSS-210 Issue 8



Radiated emissions measurement orientation 1



Radiated emissions measurement orientation 2



Radiated emissions measurement orientation 3



Conducted emissions measurement 150 kHz – 30 MHz




Issue Date: 2016-04-11

Test of Micro-Sensys GmbH RFID Pen Style Read/Write Unit iID PENsolid HF to 47 CFR 15.225 and RSS-210 Issue 8

## **2 CARRIER FREQUENCY STABILITY**



Test setup frequency stability over supply power



Detailed view of DC connection with internal lithiumionen accumulator



Test setup frequency stability over temperature



Detailed view inside climatic chamber