

TEST REPORT

Reference No. : WTD23D12261064W005
FCC ID..... : ZLZ-BVVP10
Applicant : Shenzhen Mindray BIO-Medical electronics Co.,LTD.
Address : Mindray Building, Keji 12th Road South, Hi-tech Ind, Shenzhen, China
Manufacturer : Shenzhen Mindray BIO-Medical electronics Co.,LTD.
Address : 1203 Nanhuan Avenue, Guangming District, 518106 Shenzhen,
PEOPLE's REPUBLIC OF CHINA
Product Name : BeneVision VP10
Model No. : BeneVision VP10
Standards : FCC 47CFR Part 15 Section 15.407
Date of Receipt sample..... : 2024-08-24
Date of Test..... : 2024-09-24 to 2025-01-09
Date of Issue : 2025-08-05
Test Result : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company.

The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Testing Group Co., Ltd.

Address: No. 77, Houjie Section, Guantai Road, Houjie Town, Dongguan City, Guangdong, China

Tel: +86-769-2267 6998

Fax: +86-769-2267 6828

Compiled by:

James Cheng

James Cheng / Project Engineer

Approved by:

Deval Qin

Deval Qin / Designated Reviewer

2 Contents

	Page
1 COVER PAGE	1
2 CONTENTS	2
3 REVISION HISTORY	4
4 GENERAL INFORMATION	5
4.1 GENERAL DESCRIPTION OF E.U.T.	5
4.2 DETAILS OF E.U.T.	5
4.3 CHANNEL LIST.....	6
4.4 TEST MODE DESCRIPTION	8
4.5 TEST FACILITY	8
5 EQUIPMENT USED DURING TEST	9
5.1 EQUIPMENTS LIST	9
5.2 DESCRIPTION OF SUPPORT UNITS	10
5.3 MEASUREMENT UNCERTAINTY	10
6 TEST SUMMARY	11
7 DUTY CYCLE	12
7.1 SUMMARY OF TEST RESULTS.....	12
8 RADIATED EMISSIONS	19
8.1 EUT OPERATION.....	19
8.2 TEST SETUP	20
8.3 SPECTRUM ANALYZER SETUP	21
8.4 TEST PROCEDURE.....	22
8.5 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	22
8.6 SUMMARY OF TEST RESULTS.....	23
9 BAND EDGE	39
9.1 TEST PRODUCE.....	39
9.2 TEST RESULT.....	40
10 6 DB BANDWIDTH	52
10.1 TEST PROCEDURE	52
10.2 TEST RESULT	52
11 26 DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH	57
11.1 TEST PROCEDURE	57
11.2 TEST RESULT	57
12 CONDUCTED OUTPUT POWER	75
12.1 TEST PROCEDURE	75
12.2 TEST RESULT	76
13 POWER SPECTRAL DENSITY	95
13.1 TEST PROCEDURE	95
13.2 TEST RESULT	96
14 FREQUENCY STABILITY	115
14.1 TEST PROCEDURE	115
14.2 TEST RESULT	116
15 ANTENNA REQUIREMENT	118

16 RF EXPOSURE118

17 PHOTOGRAPHS OF TEST SETUP AND EUT.....118

3 Revision History

Test Report No.	Date of Receipt Sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTD23D12261064W005	2024-08-24	2024-09-24 to 2025-01-09	2025-08-05	Original	-	Valid

4 General Information

4.1 General Description of E.U.T.

Product:	BeneVision VP10
Model(s):	BeneVision VP10
Model Description:	N/A
Test Sample No.:	M51D-WF-117
Wi-Fi Specification:	5G-802.11a/n(HT20/40)
Hardware Version:	051-006392-00
Software Version:	svn: 19935

4.2 Details of E.U.T.

Operation Frequency:	802.11a/n(HT20): U-NII-1: 5180-5240MHz, U-NII-2A: 5260-5320MHz(DFS), U-NII-2C: 5500-5700MHz(DFS), U-NII-3: 5745-5825MHz 802.11n(HT40): U-NII-1: 5190-5230MHz, U-NII-2A: 5270-5310MHz(DFS), U-NII-2C: 5510-5670MHz(DFS), U-NII-3: 5755-5795MHz
Max. RF output power:	U-NII-1: 16.20dBm U-NII-2A: 15.43dBm U-NII-2C: 10.97dBm U-NII-3: 11.96dBm
Type of Modulation:	OFDM
Antenna installation:	FPC antenna
Antenna Gain:	2.88dBi
Note:	#: The antenna gain is provided by the applicant, and the applicant should be responsible for its authenticity, WALTEK lab has not verified the authenticity of its information.
Ratings:	DC 12V

4.3 Channel List

U-NII-1 (5.15-5.25GHz)			
channel	Frequency(MHz)	channel	Frequency(MHz)
36	5180	38	5190
40	5200	42	5210
44	5220	46	5230
48	5240		

U-NII-2A (5.25-5.35GHz)			
channel	Frequency(MHz)	channel	Frequency(MHz)
52	5260	54	5270
56	5280	58	5290
60	5300	62	5310
64	5320		

U-NII-2C (5.47-5.725GHz)			
channel	Frequency(MHz)	channel	Frequency(MHz)
100	5500	102	5510
104	5520	106	5530
108	5540	110	5550
112	5560	116	5580
118	5590	120	5600
122	5610	124	5620
126	5630	128	5640
132	5660	134	5670
136	5680	140	5700

U-NII-3 (5.725-5.85GHz)			
channel	Frequency(MHz)	channel	Frequency(MHz)
149	5745	151	5755
153	5765	155	5775
157	5785	159	5795
161	5805	165	5825

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Waltek Testing Group Co., Ltd.

<http://www.waltek.com.cn>

For 802.11a/n(HT20)

channel	Frequency(MHz)	channel	Frequency(MHz)
36	5180	40	5200
48	5240		

channel	Frequency(MHz)	channel	Frequency(MHz)
52	5260	56	5280
64	5320		

channel	Frequency(MHz)	channel	Frequency(MHz)
100	5500	120	5600
140	5700		

channel	Frequency(MHz)	channel	Frequency(MHz)
149	5745	157	5785
165	5825		

For 802.11n(HT40)

channel	Frequency(MHz)	channel	Frequency(MHz)
38	5190	46	5230

channel	Frequency(MHz)	channel	Frequency(MHz)
54	5270	62	5310

channel	Frequency(MHz)	channel	Frequency(MHz)
102	5510	110	5550
134	5670		

channel	Frequency(MHz)	channel	Frequency(MHz)
151	5755	159	5795

4.4 Test Mode Description

During testing, Channel and Power Controlling Software provided by the applicant was used to control the operating channel as well as the maximum output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Transmitting duty cycle is no less 98%.

The software is TermAssist and SecureCRT tool Use together.

Test Items	Mode	Data Rate	TX/RX
Radiated Emissions	802.11a(HT20)	6 Mbps	TX
	802.11n(HT20/40)	MCS0	TX
Duty Cycle	802.11a(HT20)	6 Mbps	TX
	802.11n(HT20/40))	MCS0	TX
Band Edge	802.11a(HT20)	6 Mbps	TX
	802.11n(HT20/40)	MCS0	TX
6dB Bandwidth	802.11a(HT20)	6 Mbps	TX
	802.11n(HT20/40)	MCS0	TX
26dB Bandwidth and 99% Occupied Bandwidth	802.11a(HT20)	6 Mbps	TX
	802.11n(HT20/40)	MCS0	TX
Conducted Output Power	802.11a(HT20)	6 Mbps	TX
	802.11n(HT20/40)	MCS0	TX
Power Spectral Density	802.11a(HT20)	6 Mbps	TX
	802.11n(HT20/40)	MCS0	TX
Frequency Stability	Un-modulation	/	TX

4.5 Test Facility

The test facility has a test site registered with the following organizations:

ISED CAB identifier: CN0013. Test Firm Registration No.: 7760A.

Waltek Testing Group Co., Ltd. Has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files.

Registration number 7760A, October 15, 2016.

FCC Designation No.: CN1201. Test Firm Registration No.: 523476.

Waltek Testing Group Co., Ltd. EMC Laboratory `has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration number 523476, September 10, 2019.

5 Equipment Used during Test

5.1 Equipments List

3m Semi-anechoic Chamber for Radiation Emissions Test site 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	Spectrum Analyzer	R&S	FSP30	100091	2024-04-22	2025-04-21
2	Amplifier	Agilent	8447D	2944A10178	2024-07-18	2025-07-17
3	Trilog Broadband Antenna	SCHWARZBECK	VULB9163	336	2024-07-21	2025-07-20
4	Coaxial Cable (below 1GHz)	Top	TYPE16(13M)	-	2024-04-22	2025-04-21
5	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120 D	667	2024-01-23	2025-01-22
6	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9170	335	2024-07-18	2025-07-17
7	Broadband Preamplifier	COMPLIANCE DIRECTION	PAP-1G18	2004	2024-07-18	2025-07-17
8	Coaxial Cable (above 1GHz)	ZT26-NJ-NJ-8M/FA	1GHz-18GHz	NA	2024-04-22	2025-04-21
3m Semi-anechoic Chamber for Radiation Emissions Test site 2#						
Item	Equipment	Manufacturer	Model No.	Serial No	Last Calibration Date	Calibration Due Date
1	Test Receiver	R&S	ESCI	101296	2024-04-22	2025-04-21
2	Trilog Broadband Antenna	SCHWARZBECK	VULB9160	9160-3325	2023-11-04 2024-11-04	2024-11-03 2025-11-03
3	Active Loop Antenna	Com-Power Corp.	AL-130R	10160007	2024-04-27	2025-04-26
4	Amplifier	ANRITSU	MH648A	M43381	2024-04-22	2025-04-21
5	Cable	HUBER+SUHNER	CBL2	525178	2024-04-22	2025-04-21
RF Conducted Testing						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	Spectrum Analyzer	R&S	FSP40	100501	2024-07-18	2025-07-17
2.	EXA Signal Analyzer	Malaysia Keysight	N9010A	MY50520207	2024-04-22	2025-04-21

Test Software:

Test Item	Software name	Software version
Radiated Emission(3m)	EZ-EMC	EZ-EMC(RA-03A1-1)

5.2 Description of Support Units

Equipment	Manufacturer	Model No.	Series No.
/	/	/	/

5.3 Measurement Uncertainty

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-6}$
RF Power	± 1.0 dB
RF Power Density	± 2.2 dB
Radiated Spurious Emissions test	± 5.03 dB (30M~1000MHz)
	± 5.47 dB (1000M~25000MHz)
Conducted Spurious Emissions test	± 3.64 dB (AC mains 150KHz~30MHz)

6 Test Summary

Test Items	Test Requirement	Result
Conducted Emissions	15.207(a)	N/A
Radiated Emissions	15.407(a) 15.205(a) 15.209(a)	PASS
Duty Cycle	KDB 789033	PASS
6dB Bandwidth	15.407(a)	PASS
26 dB Emission Bandwidth & 99% Occupied Bandwidth	15.407(a)	PASS
Maximum Conducted Output Power	15.407(a)	PASS
Power Spectral Density	15.407(a)	PASS
Restricted bands around fundamental frequency	15.407(a)	PASS
Antenna Requirement	15.203	PASS
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	1.1307(b)(1)	PASS

7 Duty cycle


Test Requirement:	FCC 47CFR Part 15 Section 15.407 KDB789033 D02 General U-NII Test Procedures New Rules v02r01, Section (B)
Test Method:	ANSI C63.10-2020+A1-2024
Test Limit:	N/A
Test Result:	PASS
Remark:	Through Pre-scan, and found 802.11a at lowest channel is the worst case. Only the worst case is recorded in the report.

7.1 Summary of Test Results


Type of Modulation	On time ms	Period ms	Duty Cycle linear	Duty Cycle %	Duty Cycle Factor(dB)	Average Factor(dB)
U-NII-1 802.11a	1.424	1.452	0.98	98.07	0.08	-0.17
U-NII-1 802.11n(HT20)	1.332	1.360	0.98	97.94	0.09	-0.18
U-NII-1 802.11n(HT40)	0.662	0.686	0.97	96.50	0.15	-0.31
U-NII-2A 802.11a	1.424	1.452	0.98	98.07	0.08	-0.17
U-NII-2A 802.11n(HT20)	1.328	1.360	0.98	97.65	0.10	-0.21
U-NII-2A 802.11n(HT40)	0.662	0.686	0.97	96.50	0.15	-0.31
U-NII-2C 802.11a	1.416	1.452	0.98	97.52	0.11	-0.22
U-NII-2C 802.11n(HT20)	1.320	1.360	0.97	97.06	0.13	-0.26
U-NII-2C 802.11n(HT40)	0.628	0.686	0.92	91.55	0.38	-0.77
U-NII-3 802.11a	1.420	1.448	0.98	98.07	0.08	-0.17
U-NII-3 802.11n(HT20)	1.332	1.360	0.98	97.94	0.09	-0.18
U-NII-3 802.11n(HT40)	0.660	0.686	0.96	96.21	0.17	-0.34

Test result plots shown as follows:


802.11a U-NII-1 Low channel




802.11n(HT20) U-NII-1 Low channel




802.11n(HT40) U-NII-1 Low channel




802.11a U-NII-2A Low channel




802.11n(HT20) U-NII-2A Low channel




802.11n(HT40) U-NII-2A Low channel




802.11a U-NII-2C Low channel




802.11n(HT20) U-NII-2C Low channel




802.11n(HT40) U-NII-2C Low channel




802.11a U-NII-3 Low channel



802.11n(HT20) U-NII-3 Low channel



802.11n(HT40) U-NII-3 Low channel



8 Radiated Emissions

Test Requirement: FCC 47CFR Part 15 Section 15.209 & 15.407

Test Method: ANSI C63.10-2020+A1-2024

Test Result: PASS

Measurement Distance: 3m

Limit:

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Distance	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	$2400/F(\text{kHz})$	300	$10000 * 2400/F(\text{kHz})$	$20\log^{(2400/F(\text{kHz}))} + 80$
0.490 ~ 1.705	$24000/F(\text{kHz})$	30	$100 * 24000/F(\text{kHz})$	$20\log^{(24000/F(\text{kHz}))} + 40$
1.705 ~ 30	30	30	$100 * 30$	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

8.1 EUT Operation

Operating Environment :

Temperature: 23.5 °C

Humidity: 52.1 % RH

Atmospheric Pressure: 101.2kPa


EUT Operation :

The test was performed in transmitting mode, the test data were shown in the report.


8.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10-2020+A1-2024.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



8.3 Spectrum Analyzer Setup

Below 30MHz

Sweep Speed Auto
IF Bandwidth.....10kHz
Video Bandwidth.....10kHz
Resolution Bandwidth.....10kHz

30MHz ~ 1GHz

Sweep Speed Auto
DetectorPK
Resolution Bandwidth.....100kHz
Video Bandwidth.....300kHz

Above 1GHz

Sweep Speed Auto
DetectorPK
Resolution Bandwidth.....1MHz
Video Bandwidth.....3MHz
DetectorAve.
Resolution Bandwidth.....1MHz
Video Bandwidth.....10Hz

8.4 Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above ground plane for below 1GHz and 1.5m for above 1GHz.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are performed in X,Y and Z axis positioning(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand),the worst condition was tested putting the eut in X axis,so the worst data were shown as follow.
8. A 2.4GHz high –pass filter is used during radiated emissions above 1GHz measurement.

8.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit}$$

8.6 Summary of Test Results

Test Frequency: 9KHz~30MHz

The measurements were more than 20 dB below the limit and not reported.

Test Frequency : 30MHz ~ 18GHz

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11a U-NII-1 Low Channel 5180MHz									
248.36	39.77	QP	4	1.8	H	-11.62	28.15	46.00	-17.85
248.36	46.15	QP	121	1.8	V	-11.62	34.53	46.00	-11.47
4510.19	53.72	PK	283	1.9	H	-2.03	51.69	74.00	-22.31
4510.19	44.14	Ave	283	1.9	H	-2.03	42.11	54.00	-11.89
5111.14	53.05	PK	238	1.1	H	-1.02	52.03	74.00	-21.97
5111.14	44.73	Ave	238	1.1	H	-1.02	43.71	54.00	-10.29
10360.00	42.32	PK	158	1.0	H	5.33	47.65	74.00	-26.35
10360.00	37.69	Ave	158	1.0	H	5.33	43.02	54.00	-10.98
802.11a U-NII-1 Middle channel 5200MHz									
248.36	39.22	QP	299	1.9	H	-11.62	27.60	46.00	-18.40
248.36	45.57	QP	20	1.9	V	-11.62	33.95	46.00	-12.05
4503.60	53.63	PK	115	1.9	H	-1.94	51.69	74.00	-22.31
4503.60	43.81	Ave	115	1.9	H	-1.94	41.87	54.00	-12.13
5134.58	52.56	PK	174	1.4	H	-1.06	51.50	74.00	-22.50
5134.58	45.07	Ave	174	1.4	H	-1.06	44.01	54.00	-9.99
10400.00	41.09	PK	257	1.9	H	5.21	46.30	74.00	-27.70
10400.00	36.30	Ave	257	1.9	H	5.21	41.51	54.00	-12.49

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11a U-NII-1 High channel 5240MHz									
248.36	38.11	QP	277	2.0	H	-11.62	26.49	46.00	-19.51
248.36	44.92	QP	69	1.8	V	-11.62	33.30	46.00	-12.70
4530.11	53.23	PK	342	1.6	H	-2.24	50.99	74.00	-23.01
4530.11	43.79	Ave	342	1.6	H	-2.24	41.55	54.00	-12.45
5144.87	51.76	PK	118	1.5	H	-1.09	50.67	74.00	-23.33
5144.87	45.10	Ave	118	1.5	H	-1.09	44.01	54.00	-9.99
10480.00	42.16	PK	266	1.3	H	5.14	47.30	74.00	-26.70
10480.00	37.21	Ave	266	1.3	H	5.14	42.35	54.00	-11.65
802.11a U-NII-2A Low Channel 5260MHz									
248.36	40.94	QP	53	1.3	H	-11.62	29.32	46.00	-16.68
248.36	45.32	QP	56	1.8	V	-11.62	33.70	46.00	-12.30
4519.78	54.06	PK	24	1.4	H	-2.03	52.03	74.00	-21.97
4519.78	40.80	Ave	24	1.4	H	-2.03	38.77	54.00	-15.23
5136.67	53.10	PK	37	1.4	H	-1.02	52.08	74.00	-21.92
5136.67	39.14	Ave	37	1.4	H	-1.02	38.12	54.00	-15.88
10520.00	41.42	PK	220	1.0	H	5.33	46.75	74.00	-27.25
10520.00	33.37	Ave	220	1.0	H	5.33	38.70	54.00	-15.30

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11a U-NII-2A middle channel 5280MHz									
248.36	39.66	QP	82	1.4	H	-11.62	28.04	46.00	-17.96
248.36	44.11	QP	336	1.1	V	-11.62	32.49	46.00	-13.51
4504.04	53.44	PK	155	1.7	H	-1.94	51.50	74.00	-22.50
4504.04	39.43	Ave	155	1.7	H	-1.94	37.49	54.00	-16.51
5142.51	53.54	PK	86	1.6	H	-1.06	52.48	74.00	-21.52
5142.51	39.25	Ave	86	1.6	H	-1.06	38.19	54.00	-15.81
10560.00	39.94	PK	135	1.2	H	5.21	45.15	74.00	-28.85
10560.00	32.84	Ave	135	1.2	H	5.21	38.05	54.00	-15.95
802.11a U-NII-2A High channel 5320MHz									
248.36	38.80	QP	248	1.3	H	-11.62	27.18	46.00	-18.82
248.36	42.71	QP	186	1.2	V	-11.62	31.09	46.00	-14.91
4524.68	52.42	PK	6	1.1	H	-2.24	50.18	74.00	-23.82
4524.68	37.99	Ave	6	1.1	H	-2.24	35.75	54.00	-18.25
5147.93	53.60	PK	67	1.4	H	-1.09	52.51	74.00	-21.49
5147.93	39.33	Ave	67	1.4	H	-1.09	38.24	54.00	-15.76
10640.00	41.04	PK	227	1.4	H	5.14	46.18	74.00	-27.82
10640.00	32.08	Ave	227	1.4	H	5.14	37.22	54.00	-16.78

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11a U-NII-2C Low Channel 5500MHz									
248.36	41.49	QP	296	1.5	H	-11.62	29.87	46.00	-16.13
248.36	46.30	QP	274	1.2	V	-11.62	34.68	46.00	-11.32
4514.02	53.65	PK	215	1.9	H	-2.03	51.62	74.00	-22.38
4514.02	39.90	Ave	215	1.9	H	-2.03	37.87	54.00	-16.13
5117.97	53.05	PK	330	1.2	H	-1.02	52.03	74.00	-21.97
5117.97	39.16	Ave	330	1.2	H	-1.02	38.14	54.00	-15.86
11000.00	41.97	PK	259	1.1	H	5.33	47.30	74.00	-26.70
11000.00	37.54	Ave	259	1.1	H	5.33	42.87	54.00	-11.13
802.11a U-NII-2C Middle channel 5600MHz									
248.36	40.99	QP	230	1.8	H	-11.62	29.37	46.00	-16.63
248.36	45.61	QP	107	1.8	V	-11.62	33.99	46.00	-12.01
4502.70	53.45	PK	288	1.3	H	-1.94	51.51	74.00	-22.49
4502.70	39.30	Ave	288	1.3	H	-1.94	37.36	54.00	-16.64
5129.49	53.24	PK	100	1.6	H	-1.06	52.18	74.00	-21.82
5129.49	38.71	Ave	100	1.6	H	-1.06	37.65	54.00	-16.35
11200.00	40.83	PK	311	1.8	H	5.21	46.04	74.00	-27.96
11200.00	36.42	Ave	311	1.8	H	5.21	41.63	54.00	-12.37

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11a U-NII-2C High channel 5700MHz									
248.36	39.89	QP	214	1.1	H	-11.62	28.27	46.00	-17.73
248.36	45.53	QP	56	1.6	V	-11.62	33.91	46.00	-12.09
4522.00	52.55	PK	270	1.4	H	-2.24	50.31	74.00	-23.69
4522.00	38.75	Ave	270	1.4	H	-2.24	36.51	54.00	-17.49
5129.57	52.78	PK	9	1.7	H	-1.09	51.69	74.00	-22.31
5129.57	38.91	Ave	9	1.7	H	-1.09	37.82	54.00	-16.18
11400.00	41.42	PK	120	1.6	H	5.14	46.56	74.00	-27.44
11400.00	36.66	Ave	120	1.6	H	5.14	41.80	54.00	-12.20
802.11a U-NII-3 Low Channel 5745MHz									
248.36	37.99	QP	247	1.4	H	-11.62	26.37	46.00	-19.63
248.36	44.58	QP	193	1.5	V	-11.62	32.96	46.00	-13.04
4535.33	52.47	PK	50	1.8	H	-2.06	50.41	74.00	-23.59
4535.33	43.40	Ave	50	1.8	H	-2.06	41.34	54.00	-12.66
5352.78	41.85	PK	109	2.0	H	5.93	47.78	74.00	-26.22
5352.78	36.54	Ave	109	2.0	H	5.93	42.47	54.00	-11.53
11490.00	45.44	PK	95	1.9	H	-1.25	44.19	74.00	-29.81
11490.00	38.45	Ave	95	1.9	H	-1.25	37.20	54.00	-16.80

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11a U-NII-3 middle channel 5785MHz									
248.36	37.15	QP	293	1.4	H	-11.62	25.53	46.00	-20.47
248.36	44.29	QP	245	1.0	V	-11.62	32.67	46.00	-13.33
4520.47	51.37	PK	110	1.5	H	-2.03	49.34	74.00	-24.66
4520.47	42.73	Ave	110	1.5	H	-2.03	40.70	54.00	-13.30
5376.28	40.94	PK	158	1.9	H	5.81	46.75	74.00	-27.25
5376.28	36.27	Ave	158	1.9	H	5.81	42.08	54.00	-11.92
11570.00	45.77	PK	135	1.4	H	-1.22	44.55	74.00	-29.45
11570.00	38.12	Ave	135	1.4	H	-1.22	36.90	54.00	-17.10
802.11a U-NII-3 High channel 5825MHz									
248.36	36.88	QP	179	1.5	H	-11.62	25.26	46.00	-20.74
248.36	43.89	QP	55	1.7	V	-11.62	32.27	46.00	-13.73
4529.08	50.07	PK	36	1.3	H	-1.84	48.23	74.00	-25.77
4529.08	41.67	Ave	36	1.3	H	-1.84	39.83	54.00	-14.17
5371.34	41.00	PK	51	1.7	H	5.84	46.84	74.00	-27.16
5371.34	36.78	Ave	51	1.7	H	5.84	42.62	54.00	-11.38
11650.00	46.18	PK	109	1.9	H	-1.30	44.88	74.00	-29.12
11650.00	39.78	Ave	109	1.9	H	-1.30	38.48	54.00	-15.52

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11n(HT20) U-NII-1 Low Channel 5180MHz									
248.36	36.75	QP	348	1.1	H	-11.62	25.13	46.00	-20.87
248.36	42.75	QP	305	1.2	V	-11.62	31.13	46.00	-14.87
4508.20	49.38	PK	62	1.5	H	-2.14	47.24	74.00	-26.76
4508.20	40.24	Ave	62	1.5	H	-2.14	38.10	54.00	-15.90
5139.77	46.95	PK	276	1.0	H	-1.06	45.89	74.00	-28.11
5139.77	37.62	Ave	276	1.0	H	-1.06	36.56	54.00	-17.44
10360.00	40.85	PK	175	1.9	H	5.33	46.18	74.00	-27.82
10360.00	37.41	Ave	175	1.9	H	5.33	42.74	54.00	-11.26
802.11n(HT20) U-NII-1 Middle channel 5200MHz									
248.36	36.62	QP	245	1.2	H	-11.62	25.00	46.00	-21.00
248.36	42.47	QP	358	1.8	V	-11.62	30.85	46.00	-15.15
4533.18	49.02	PK	292	1.3	H	-2.12	46.90	74.00	-27.10
4533.18	38.89	Ave	292	1.3	H	-2.12	36.77	54.00	-17.23
5143.99	47.33	PK	120	1.3	H	-1.06	46.27	74.00	-27.73
5143.99	37.19	Ave	120	1.3	H	-1.06	36.13	54.00	-17.87
10400.00	43.23	PK	16	1.3	H	5.21	48.44	74.00	-25.56
10400.00	37.05	Ave	16	1.3	H	5.21	42.26	54.00	-11.74

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11n(HT20) U-NII-1 High channel 5240MHz									
248.36	36.55	QP	191	1.2	H	-11.62	24.93	46.00	-21.07
248.36	43.59	QP	224	1.4	V	-11.62	31.97	46.00	-14.03
4512.35	48.40	PK	106	1.1	H	-1.96	46.44	74.00	-27.56
4512.35	37.42	Ave	106	1.1	H	-1.96	35.46	54.00	-18.54
5110.10	47.05	PK	269	1.4	H	-1.06	45.99	74.00	-28.01
5110.10	37.10	Ave	269	1.4	H	-1.06	36.04	54.00	-17.96
10480.00	42.98	PK	33	1.7	H	5.14	48.12	74.00	-25.88
10480.00	38.19	Ave	33	1.7	H	5.14	43.33	54.00	-10.67
802.11n(HT20) U-NII-2A Low Channel 5260MHz									
248.36	39.65	QP	65	2.0	H	-11.62	28.03	46.00	-17.97
248.36	41.80	QP	151	2.0	V	-11.62	30.18	46.00	-15.82
4513.81	37.21	PK	334	1.9	H	-2.03	35.18	74.00	-38.82
4513.81	44.16	Ave	334	1.9	H	-2.03	42.13	54.00	-11.87
5141.72	40.15	PK	244	1.8	H	-1.02	39.13	74.00	-34.87
5141.72	39.79	Ave	244	1.8	H	-1.02	38.77	54.00	-15.23
10520.00	37.60	PK	299	1.4	H	5.33	42.93	74.00	-31.07
10520.00	37.18	Ave	299	1.4	H	5.33	42.51	54.00	-11.49

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11n(HT20) U-NII-2A middle channel 5280MHz									
248.36	39.79	QP	103	2.0	H	-11.62	28.17	46.00	-17.83
248.36	42.07	QP	7	1.9	V	-11.62	30.45	46.00	-15.55
4526.61	36.78	PK	307	1.8	H	-1.94	34.84	74.00	-39.16
4526.61	44.35	Ave	307	1.8	H	-1.94	42.41	54.00	-11.59
5146.33	40.38	PK	115	1.1	H	-1.06	39.32	74.00	-34.68
5146.33	39.69	Ave	115	1.1	H	-1.06	38.63	54.00	-15.37
10560.00	37.54	PK	286	1.6	H	5.21	42.75	74.00	-31.25
10560.00	37.89	Ave	286	1.6	H	5.21	43.10	54.00	-10.90
802.11n(HT20) U-NII-2A High channel 5320MHz									
248.36	40.01	QP	282	1.2	H	-11.62	28.39	46.00	-17.61
248.36	40.71	QP	20	1.7	V	-11.62	29.09	46.00	-16.91
4517.12	35.43	PK	127	1.8	H	-2.24	33.19	74.00	-40.81
4517.12	43.17	Ave	127	1.8	H	-2.24	40.93	54.00	-13.07
5116.68	40.50	PK	28	1.5	H	-1.09	39.41	74.00	-34.59
5116.68	38.79	Ave	28	1.5	H	-1.09	37.70	54.00	-16.30
10640.00	36.31	PK	323	1.1	H	5.14	41.45	74.00	-32.55
10640.00	38.58	Ave	323	1.1	H	5.14	43.72	54.00	-10.28

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11n(HT20) U-NII-2C Low Channel 5500MHz									
248.36	36.94	QP	183	1.2	H	-11.62	25.32	46.00	-20.68
248.36	41.79	QP	155	2.0	V	-11.62	30.17	46.00	-15.83
4516.36	37.74	PK	286	1.8	H	-2.03	35.71	74.00	-38.29
4516.36	37.20	Ave	286	1.8	H	-2.03	35.17	54.00	-18.83
5134.01	48.05	PK	357	1.9	H	-1.02	47.03	74.00	-26.97
5134.01	37.07	Ave	357	1.9	H	-1.02	36.05	54.00	-17.95
11000.00	38.30	PK	251	1.9	H	5.33	43.63	74.00	-30.37
11000.00	34.62	Ave	251	1.9	H	5.33	39.95	54.00	-14.05
802.11n(HT20) U-NII-2C Middle channel 5600MHz									
248.36	35.63	QP	315	1.2	H	-11.62	24.01	46.00	-21.99
248.36	41.14	QP	63	1.4	V	-11.62	29.52	46.00	-16.48
4511.85	38.28	PK	121	1.2	H	-1.94	36.34	74.00	-37.66
4511.85	35.97	Ave	121	1.2	H	-1.94	34.03	54.00	-19.97
5130.73	49.68	PK	357	1.0	H	-1.06	48.62	74.00	-25.38
5130.73	37.00	Ave	357	1.0	H	-1.06	35.94	54.00	-18.06
11200.00	39.23	PK	71	1.9	H	5.21	44.44	74.00	-29.56
11200.00	34.60	Ave	71	1.9	H	5.21	39.81	54.00	-14.19

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11n(HT20) U-NII-2C High channel 5700MHz									
248.36	34.38	QP	98	1.9	H	-11.62	22.76	46.00	-23.24
248.36	41.40	QP	107	1.8	V	-11.62	29.78	46.00	-16.22
4511.90	36.81	PK	339	1.9	H	-2.24	34.57	74.00	-39.43
4511.90	34.80	Ave	339	1.9	H	-2.24	32.56	54.00	-21.44
5116.84	49.86	PK	305	1.9	H	-1.09	48.77	74.00	-25.23
5116.84	36.97	Ave	305	1.9	H	-1.09	35.88	54.00	-18.12
11400.00	38.43	PK	35	1.4	H	5.14	43.57	74.00	-30.43
11400.00	34.21	Ave	35	1.4	H	5.14	39.35	54.00	-14.65
802.11n(HT20) U-NII-3 Low Channel 5745MHz									
248.36	31.69	QP	284	1.5	H	-11.62	20.07	46.00	-25.93
248.36	34.19	QP	101	1.9	V	-11.62	22.57	46.00	-23.43
4535.14	40.50	PK	105	1.6	H	-2.06	38.44	74.00	-35.56
4535.14	44.98	Ave	105	1.6	H	-2.06	42.92	54.00	-11.08
5386.62	37.08	PK	113	1.1	H	5.93	43.01	74.00	-30.99
5386.62	37.80	Ave	113	1.1	H	5.93	43.73	54.00	-10.27
11490.00	46.88	PK	141	1.7	H	-1.25	45.63	74.00	-28.37
11490.00	37.35	Ave	141	1.7	H	-1.25	36.10	54.00	-17.90

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11n(HT20) U-NII-3 middle channel 5785MHz									
248.36	30.02	QP	162	1.6	H	-11.62	18.40	46.00	-27.60
248.36	45.43	QP	295	1.7	V	-11.62	33.81	46.00	-12.19
4537.63	37.35	PK	104	1.9	H	-2.03	35.32	74.00	-38.68
4537.63	45.14	Ave	104	1.9	H	-2.03	43.11	54.00	-10.89
5387.21	37.45	PK	140	1.9	H	5.81	43.26	74.00	-30.74
5387.21	38.44	Ave	140	1.9	H	5.81	44.25	54.00	-9.75
11570.00	46.84	PK	89	2.0	H	-1.22	45.62	74.00	-28.38
11570.00	37.66	Ave	89	2.0	H	-1.22	36.44	54.00	-17.56
802.11n(HT20) U-NII-3 High channel 5825MHz									
248.36	37.77	QP	274	1.6	V	-11.62	26.15	46.00	-19.85
4517.94	38.84	PK	1	1.9	H	-1.84	37.00	74.00	-37.00
4517.94	44.40	Ave	1	1.9	H	-1.84	42.56	54.00	-11.44
5350.37	36.86	PK	201	1.9	H	5.84	42.70	74.00	-31.30
5350.37	38.68	Ave	201	1.9	H	5.84	44.52	54.00	-9.48
11650.00	46.63	PK	138	1.3	H	-1.30	45.33	74.00	-28.67
11650.00	39.64	Ave	138	1.3	H	-1.30	38.34	54.00	-15.66
5440.98	45.90	PK	263	1.9	H	-1.36	44.54	74.00	-29.46

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11n(HT40) U-NII-1 Low Channel 5190MHz									
248.36	29.19	QP	265	1.6	H	-11.62	17.57	46.00	-28.43
248.36	39.30	QP	188	1.1	V	-11.62	27.68	46.00	-18.32
4527.44	42.21	PK	250	1.4	H	-1.89	40.32	74.00	-33.68
4527.44	35.06	Ave	250	1.4	H	-1.89	33.17	54.00	-20.83
5133.39	46.01	PK	93	1.6	H	-1.06	44.95	74.00	-29.05
5133.39	41.27	Ave	93	1.6	H	-1.06	40.21	54.00	-13.79
10380.00	40.36	PK	37	1.9	H	5.26	45.62	74.00	-28.38
10380.00	34.82	Ave	37	1.9	H	5.26	40.08	54.00	-13.92
802.11n(HT40) U-NII-1 High channel 5230MHz									
248.36	28.32	QP	87	1.5	H	-11.62	16.70	46.00	-29.30
248.36	38.75	QP	308	1.7	V	-11.62	27.13	46.00	-18.87
4519.61	41.65	PK	6	1.7	H	-1.94	39.71	74.00	-34.29
4519.61	35.24	Ave	6	1.7	H	-1.94	33.30	54.00	-20.70
5110.15	47.59	PK	218	1.0	H	-1.06	46.53	74.00	-27.47
5110.15	42.43	Ave	218	1.0	H	-1.06	41.37	54.00	-12.63
10460.00	40.88	PK	195	1.6	H	5.28	46.16	74.00	-27.84
10460.00	38.13	Ave	195	1.6	H	5.28	43.41	54.00	-10.59

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11n(HT40) U-NII-2A Low Channel 5270MHz									
248.36	28.41	QP	151	1.8	H	-11.62	16.79	46.00	-29.21
248.36	37.93	QP	179	1.5	V	-11.62	26.31	46.00	-19.69
4535.41	40.79	PK	116	1.8	H	-1.89	38.90	74.00	-35.10
4535.41	38.21	Ave	116	1.8	H	-1.89	36.32	54.00	-17.68
5149.27	48.34	PK	1	1.9	H	-1.06	47.28	74.00	-26.72
5149.27	39.83	Ave	1	1.9	H	-1.06	38.77	54.00	-15.23
10540.00	44.75	PK	11	1.6	H	5.26	50.01	74.00	-23.99
10540.00	37.33	Ave	11	1.6	H	5.26	42.59	54.00	-11.41
802.11n(HT40) U-NII-2A High channel 5310MHz									
248.36	28.22	QP	40	1.5	H	-11.62	16.60	46.00	-29.40
248.36	38.07	QP	346	1.8	V	-11.62	26.45	46.00	-19.55
4534.85	41.56	PK	225	1.5	H	-1.94	39.62	74.00	-34.38
4534.85	37.69	Ave	225	1.5	H	-1.94	35.75	54.00	-18.25
5127.74	49.10	PK	280	1.1	H	-1.06	48.04	74.00	-25.96
5127.74	39.92	Ave	280	1.1	H	-1.06	38.86	54.00	-15.14
10620.00	41.32	PK	74	1.7	H	5.28	46.60	74.00	-27.40
10620.00	37.04	Ave	74	1.7	H	5.28	42.32	54.00	-11.68

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11n(HT40) U-NII-2C Low Channel 5510MHz									
248.36	28.48	QP	65	2.0	H	-11.62	16.86	46.00	-29.14
248.36	38.58	QP	143	1.5	V	-11.62	26.96	46.00	-19.04
4537.13	41.83	PK	314	1.6	H	-1.89	39.94	74.00	-34.06
4537.13	37.54	Ave	314	1.6	H	-1.89	35.65	54.00	-18.35
5126.99	45.80	PK	82	1.7	H	-1.06	44.74	74.00	-29.26
5126.99	37.19	Ave	82	1.7	H	-1.06	36.13	54.00	-17.87
11020.00	43.58	PK	40	2.0	H	5.26	48.84	74.00	-25.16
11020.00	35.32	Ave	40	2.0	H	5.26	40.58	54.00	-13.42
802.11n(HT40) U-NII-2C Middle channel 5550MHz									
248.36	27.89	QP	195	1.1	H	-11.62	16.27	46.00	-29.73
248.36	38.90	QP	255	1.3	V	-11.62	27.28	46.00	-18.72
4538.18	42.76	PK	287	1.5	H	-1.94	40.82	74.00	-33.18
4538.18	37.94	Ave	287	1.5	H	-1.94	36.00	54.00	-18.00
5146.85	47.37	PK	218	1.6	H	-1.06	46.31	74.00	-27.69
5146.85	36.66	Ave	218	1.6	H	-1.06	35.60	54.00	-18.40
11100.00	45.59	PK	131	2.0	H	5.28	50.87	74.00	-23.13
11100.00	38.56	Ave	131	2.0	H	5.28	43.84	54.00	-10.16
802.11n(HT40) U-NII-2C High channel 5670MHz									
248.36	27.00	QP	82	1.2	H	-11.62	15.38	46.00	-30.62
248.36	38.77	QP	16	1.8	V	-11.62	27.15	46.00	-18.85
4502.51	42.78	PK	264	1.0	H	-1.94	40.84	74.00	-33.16
4502.51	38.77	Ave	264	1.0	H	-1.94	36.83	54.00	-17.17
5115.77	46.38	PK	139	1.1	H	-1.06	45.32	74.00	-28.68
5115.77	36.35	Ave	139	1.1	H	-1.06	35.29	54.00	-18.71
11340.00	41.60	PK	109	1.0	H	5.28	46.88	74.00	-27.12
11340.00	32.91	Ave	109	1.0	H	5.28	38.19	54.00	-15.81

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11n(HT40) U-NII-3 Low Channel 5755MHz									
248.36	29.32	QP	214	1.7	H	-11.62	17.70	46.00	-28.30
248.36	38.56	QP	92	1.4	V	-11.62	26.94	46.00	-19.06
4512.53	39.00	PK	196	1.8	H	-1.96	37.04	74.00	-36.96
4512.53	33.66	Ave	196	1.8	H	-1.96	31.70	54.00	-22.30
5376.54	39.62	PK	268	2.0	H	5.88	45.50	74.00	-28.50
5376.54	34.93	Ave	268	2.0	H	5.88	40.81	54.00	-13.19
11510.00	45.40	PK	118	1.4	H	-1.01	44.39	74.00	-29.61
11510.00	39.98	Ave	118	1.4	H	-1.01	38.97	54.00	-15.03
802.11n(HT40) U-NII-3 High Channel 5795MHz									
248.36	30.06	QP	250	1.0	H	-11.62	18.44	46.00	-27.56
248.36	37.59	QP	96	1.4	V	-11.62	25.97	46.00	-20.03
4505.04	38.34	PK	194	1.3	H	-1.92	36.42	74.00	-37.58
4505.04	33.34	Ave	194	1.3	H	-1.92	31.42	54.00	-22.58
5389.85	41.65	PK	258	1.2	H	5.63	47.28	74.00	-26.72
5389.85	37.83	Ave	258	1.2	H	5.63	43.46	54.00	-10.54
11590.00	45.72	PK	17	1.3	H	-1.04	44.68	74.00	-29.32
11590.00	38.70	Ave	17	1.3	H	-1.04	37.66	54.00	-16.34

Test Frequency: 12GHz~40GHz

The measurements were more than 20 dB below the limit and not reported.

9 Band Edge

Test Requirement:	FCC 47CFR Part 15 Section 15.407
Test Method:	ANSI C63.10-2020+A1-2024
Test Limit:	For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27dBm/MHz. For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. For transmitters operating in the 5.725-5.85 GHz band: (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge. (ii) Devices certified before March 2, 2017 with antenna gain greater than 10 dBi may demonstrate compliance with the emission limits in §15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease by March 2, 2018. Devices certified before March 2, 2018 with antenna gain of 10 dBi or less may demonstrate compliance with the emission limits in §15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease before March 2, 2020.
Test Result:	PASS


9.1 Test Produce

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.


9.2 Test Result

Test result plots shown as follows:


802.11a U-NII-1 Band edge-left side




802.11a U-NII-1 Band edge-right side




802.11a U-NII-2A Band edge-left side




802.11a U-NII-2A Band edge-right side




802.11a U-NII-2C Band edge-left side




802.11a U-NII-2C Band edge-right side




802.11a U-NII-3 Band edge-left side




802.11a U-NII-3 Band edge-right side




802.11n(HT20) U-NII-1 Band edge-left side




802.11n(HT20) U-NII-1 Band edge-right side




802.11n(HT20) U-NII-2A Band edge-left side




802.11n(HT20) U-NII-2A Band edge-right side




802.11n(HT20) U-NII-2C Band edge-left side




802.11n(HT20) U-NII-2C Band edge-right side




802.11n(HT20) U-NII-3 Band edge-left side




802.11n(HT20) U-NII-3 Band edge-right side




802.11n(HT40) U-NII-1 Band edge-left side




802.11n(HT40) U-NII-1 Band edge-right side




802.11n(HT40) U-NII-2A Band edge-left side




802.11n(HT40) U-NII-2A Band edge-right side




802.11n(HT40) U-NII-2C Band edge-left side




802.11n(HT40) U-NII-2C Band edge-right side



802.11n(HT40) U-NII-3 Band edge-left side



802.11n(HT40) U-NII-3 Band edge-right side



10 6 dB Bandwidth

Test Requirement: FCC 47CFR Part 15 Section 15.407(e)
 KDB662911 D01 Multiple Transmitter Output v02r01
 Test Method: KDB789033 D02 General U-NII Test Procedures New Rules v02r01
 Section C
 Test Limit: ≥ 500 kHz
 Test Result: PASS

10.1 Test Procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz

10.2 Test Result


Band	Operation mode	6 dB Bandwidth (MHz)		
		Low	Middle	High
U-NII-3	802.11a	16.39	16.41	16.39
	802.11n(HT20)	17.59	17.59	17.59
	802.11n(HT40)	36.36	/	36.41

Test result plots shown as follows:


802.11a U-NII-3 Low channel




802.11a U-NII-3 Middle channel




802.11a U-NII-3 High channel




802.11n(HT20) U-NII-3 Low channel




802.11n(HT20) U-NII-3 Middle channel




802.11n(HT20) U-NII-3 High channel



802.11n(HT40) U-NII-3 Low channel



802.11n(HT40) U-NII-3 High channel



11 26 dB Bandwidth and 99% Occupied Bandwidth

Test Requirement:	FCC 47CFR Part 15 Section 15.407 (a) KDB662911 D01 Multiple Transmitter Output v02r01
Test Method:	KDB789033 D02 General U-NII Test Procedures New Rules v02r01 Section D
Test Limit:	No restriction limits
Test Result:	PASS

11.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 1% to 5% of the OBW, VBW = 3x RBW

11.2 Test Result

Band	Operation mode	26 dB Bandwidth (MHz)			99% Bandwidth (MHz)		
		Low	Middle	High	Low	Middle	High
U-NII-1	802.11a	23.51	23.55	23.62	16.918	16.871	16.851
	802.11n(HT20)	25.48	24.71	24.29	17.957	17.996	17.957
	802.11n(HT40)	46.81	/	47.49	36.389	/	36.407

Band	Operation mode	26 dB Bandwidth (MHz)			99% Bandwidth (MHz)		
		Low	Middle	High	Low	Middle	High
U-NII-2A	802.11a	23.50	23.35	23.66	16.907	16.943	16.957
	802.11n(HT20)	25.19	25.48	25.65	17.997	17.953	17.968
	802.11n(HT40)	44.50	/	48.37	36.350	/	36.444


Band	Operation mode	26 dB Bandwidth (MHz)			99% Bandwidth (MHz)		
		Low	Middle	High	Low	Middle	High
U-NII-2C	802.11a	25.36	21.77	21.82	16.986	16.929	16.864
	802.11n(HT20)	25.53	23.59	22.78	17.994	17.926	17.955
	802.11n(HT40)	58.23	36.53	57.26	36.418	36.487	36.447

Band	Operation mode	26 dB Bandwidth (MHz)			99% Bandwidth (MHz)		
		Low	Middle	High	Low	Middle	High
U-NII-3	802.11a	23.73	23.62	24.69	16.911	16.959	16.960
	802.11n(HT20)	27.50	27.55	25.00	17.991	17.990	17.993
	802.11n(HT40)	59.38	/	56.54	36.424	/	36.465


Test result plots shown as follows:

Bandwidth


802.11a U-NII-1 Low channel




802.11a U-NII-1 Middle channel




802.11a U-NII-1 High channel




802.11n(HT20) U-NII-1 Low channel




802.11n(HT20) U-NII-1 Middle channel




802.11n(HT20) U-NII-1 High channel




802.11n(HT40) U-NII-1 Low channel




802.11n(HT40) U-NII-1 High channel




802.11a U-NII-2A Low channel




802.11a U-NII-2A Middle channel




802.11a U-NII-2A High channel




802.11n(HT20) U-NII-2A Low channel




802.11n(HT20) U-NII-2A Middle channel




802.11n(HT20) U-NII-2A High channel




802.11n(HT40) U-NII-2A Low channel




802.11n(HT40) U-NII-2A High channel




802.11a U-NII-2C Low channel




802.11a U-NII-2C Middle channel




802.11a U-NII-2C High channel




802.11n(HT20) U-NII-2C Low channel




802.11n(HT20) U-NII-2C Middle channel




802.11n(HT20) U-NII-2C High channel





802.11n(HT40) U-NII-2C Low channel




802.11n(HT40) U-NII-2C Middle channel







802.11a U-NII-3 Middle channel




802.11a U-NII-3 High channel




802.11n(HT20) U-NII-3 Low channel




802.11n(HT20) U-NII-3 Middle channel




802.11n(HT20) U-NII-3 High channel



802.11n(HT40) U-NII-3 Low channel





12 Conducted Output Power

Test Requirement:	FCC 47CFR Part 15 Section 15.407(a) KDB662911 D01 Multiple Transmitter Output v02r01
Test Method:	KDB789033 D02 General U-NII Test Procedures New Rules v02r01 Section E
Test Limit:	For the band 5.15-5.25 GHz For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. For the 5.25-5.35 GHz and 5.47-5.725 GHz bands For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. For the band 5.725-5.850 GHz For the band 5.725-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.
Test Result:	PASS Conducted output power= measurement power+10log(1/x)
Remark:	X is duty cycle=1, so $10\log(1/1)=0$ Conducted output power= measurement power

12.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 1 MHz. VBW = 3 MHz. Sweep = auto; Detector Function = Peak, Set the span to fully encompass the DTS bandwidth.
3. Keep the EUT in transmitting at lowest, medium and highest channel individually. Record the max value.

12.2 Test Result

Band	Operation mode	Channel	Measurements (dBm)	Duty Cycle Factor (dB)	Conducted Output Power (dBm)
U-NII-1	802.11a	Low	16.12	0.08	16.20
		Middle	15.79		15.87
		High	15.94		16.02
	802.11n(HT20)	Low	15.86	0.09	15.95
		Middle	15.77		15.86
		High	15.56		15.65
	802.11n(HT40)	Low	15.78	0.15	15.93
		Middle	/		/
		High	15.64		15.79

Band	Operation mode	Channel	Measurements (dBm)	Duty Cycle Factor (dB)	Conducted Output Power (dBm)
U-NII-2A	802.11a	Low	15.35	0.08	15.43
		Middle	14.85		14.93
		High	13.69		13.77
	802.11n(HT20)	Low	15.21	0.10	15.31
		Middle	14.68		14.78
		High	13.55		13.65
	802.11n(HT40)	Low	14.95	0.15	15.10
		Middle	/		/
		High	13.69		13.84


Band	Operation mode	Channel	Measurements (dBm)	Duty Cycle Factor (dB)	Conducted Output Power (dBm)
U-NII-2C	802.11a	Low	10.86	0.11	10.97
		Middle	9.58		9.69
		High	10.24		10.35
	802.11n(HT20)	Low	10.48	0.13	10.61
		Middle	9.40		9.53
		High	10.15		10.28
	802.11n(HT40)	Low	10.28	0.38	10.66
		Middle	10.11		10.49
		High	10.42		10.80

Band	Operation mode	Channel	Measurements (dBm)	Duty Cycle Factor (dB)	Conducted Output Power (dBm)
U-NII-3	802.11a	Low	11.05	0.08	11.13
		Middle	10.94		11.02
		High	11.75		11.83
	802.11n(HT20)	Low	10.86	0.09	10.95
		Middle	11.02		11.11
		High	11.87		11.96
	802.11n(HT40)	Low	10.70	0.17	10.87
		Middle	/		/
		High	10.92		11.09


* All transmit signals are completely uncorrelated with each other, Directional gain = G_{ANT} which is less than 6dBi. So the limit does not be reduced.

Test result plots shown as follows:


802.11a U-NII-1 Low channel




802.11a U-NII-1 Middle channel




802.11a U-NII-1 High channel




802.11n(HT20) U-NII-1 Low channel




802.11n(HT20) U-NII-1 Middle channel




802.11n(HT20) U-NII-1 High channel




802.11n(HT40) U-NII-1 Low channel




802.11n(HT40) U-NII-1 High channel




802.11a U-NII-2A Low channel




802.11a U-NII-2A Middle channel




802.11a U-NII-2A High channel




802.11n(HT20) U-NII-2A Low channel




802.11n(HT20) U-NII-2A Middle channel




802.11n(HT20) U-NII-2A High channel




802.11n(HT40) U-NII-2A Low channel




802.11n(HT40) U-NII-2A High channel




802.11a U-NII-2C Low channel




802.11a U-NII-2C Middle channel




802.11a U-NII-2C High channel




802.11n(HT20) U-NII-2C Low channel




802.11n(HT20) U-NII-2C Middle channel




802.11n(HT20) U-NII-2C High channel




802.11n(HT40) U-NII-2C Low channel




802.11n(HT40) U-NII-2C Middle channel




802.11n(HT40) U-NII-2C High channel




802.11a U-NII-3 Low channel




802.11a U-NII-3 Middle channel




802.11a U-NII-3 High channel




802.11n(HT20) U-NII-3 Low channel




802.11n(HT20) U-NII-3 Middle channel




802.11n(HT20) U-NII-3 High channel



802.11n(HT40) U-NII-3 Low channel





13 Power Spectral density

Test Requirement:	FCC 47CFR Part 15 Section 15.407(a)
Test Method:	KDB 789033 D02 General U-NII Test Procedures New Rules v02r01
Test Limit:	For the band 5.15-5.25 GHz For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. For an indoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. For client devices in the 5.15-5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. For the 5.25-5.35 GHz and 5.47-5.725 GHz bands The maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. For the band 5.725-5.850 GHz The maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.
Test Result:	PASS

13.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer:
U-NII-1
RBW = 1MHz, VBW $\geq 3 \times$ RBW Sweep = auto; Detector Function = Peak. Trace = Max hold.
U-NII-3
RBW = 510KHz, VBW $\geq 3 \times$ RBW Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section
Submit this plot.

13.2 Test Result

Band	Operation mode	Channel	Measurements (dBm/MHz)	Duty Cycle Factor (dB)	Power Spectral Density (dBm/MHz)
U-NII-1	802.11a	Low	5.362	0.08	5.442
		Middle	5.176		5.256
		High	5.187		5.267
	802.11n(HT20)	Low	5.379	0.09	5.469
		Middle	5.165		5.255
		High	5.245		5.335
	802.11n(HT40)	Low	2.504	0.15	2.654
		Middle	/		/
		High	2.984		3.134

Band	Operation mode	Channel	Measurements (dBm/MHz)	Duty Cycle Factor (dB)	Power Spectral Density (dBm/MHz)
U-NII-2A	802.11a	Low	4.880	0.08	4.960
		Middle	4.656		4.736
		High	3.351		3.431
	802.11n(HT20)	Low	4.676	0.10	4.776
		Middle	4.330		4.430
		High	3.489		3.589
	802.11n(HT40)	Low	1.736	0.15	1.886
		Middle	/		/
		High	0.082		0.232


Band	Operation mode	Channel	Measurements (dBm/MHz)	Duty Cycle Factor (dB)	Power Spectral Density (dBm/MHz)
U-NII-2C	802.11a	Low	0.115	0.11	0.225
		Middle	-1.347		-1.237
		High	-0.046		0.064
	802.11n(HT20)	Low	0.005	0.13	0.135
		Middle	-0.785		-0.655
		High	-0.219		-0.089
	802.11n(HT40)	Low	-3.299	0.38	-2.919
		Middle	-3.639		-3.259
		High	-3.143		-2.763

Band	Operation mode	Channel	Measurements (dBm/MHz)	Duty Cycle Factor (dB)	Power Spectral Density (dBm/MHz)
U-NII-3	802.11a	Low	-1.598	0.08	-1.518
		Middle	-1.900		-1.820
		High	-0.911		-0.831
	802.11n(HT20)	Low	-1.363	0.09	-1.273
		Middle	-1.347		-1.257
		High	0.645		0.735
	802.11n(HT40)	Low	-4.637	0.17	-4.467
		Middle	/		/
		High	-4.631		-4.461


* All transmit signals are completely uncorrelated with each other, Directional gain = G_{ANT} which is less than 6dBi. So the limit does not be reduced.

Test result plots shown as follows:


802.11a U-NII-1 Low channel




802.11a U-NII-1 Middle channel




802.11a U-NII-1 High channel




802.11n(HT20) U-NII-1 Low channel




802.11n(HT20) U-NII-1 Middle channel




802.11n(HT20) U-NII-1 High channel




802.11n(HT40) U-NII-1 Low channel




802.11n(HT40) U-NII-1 High channel




802.11a U-NII-2A Low channel




802.11a U-NII-2A Middle channel




802.11a U-NII-2A High channel




802.11n(HT20) U-NII-2A Low channel




802.11n(HT20) U-NII-2A Middle channel




802.11n(HT20) U-NII-2A High channel




802.11n(HT40) U-NII-2A Low channel




802.11n(HT40) U-NII-2A High channel




802.11a U-NII-2C Low channel




802.11a U-NII-2C Middle channel




802.11a U-NII-2C High channel




802.11n(HT20) U-NII-2C Low channel




802.11n(HT20) U-NII-2C Middle channel




802.11n(HT20) U-NII-2C High channel




802.11n(HT40) U-NII-2C Low channel




802.11n(HT40) U-NII-2C Middle channel




802.11n(HT40) U-NII-2C High channel




802.11a U-NII-3 Low channel




802.11a U-NII-3 Middle channel




802.11a U-NII-3 High channel




802.11n(HT20) U-NII-3 Low channel



802.11n(HT20) U-NII-3 Middle channel




802.11n(HT20) U-NII-3 High channel



802.11n(HT40) U-NII-3 Low channel



802.11n(HT40) U-NII-3 High channel



14 Frequency Stability

Test Requirement:	FCC 47CFR Part 15 Section 15.407(g)
Test Method:	ANSI C63.10-2020+A1-2024
Test Limit:	Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual or 20ppm.
Test Result:	PASS

14.1 Test Procedure

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
EUT have transmitted absence of unmodulation signal and fixed channelise. Set the spectrum analyzer span to view the entire absence of modulation emissions bandwidth. Set RBW = 10 kHz, VBW = 10 kHz with peak detector and maxhold settings. f_c is declaring of channel frequency. Then the frequency error formula is $(f_c - f)/f_c \times 10^6$ ppm and the limit is less than ± 20 ppm The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value.
2. Extreme temperature rule is 0°C~ 40°C.

14.2 Test Result

U-NII-1 Test Frequency:5180MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (MHz)	Frequency Error (ppm)	Limit (ppm)
40	12.0	-0.0039	-0.75	20
30		-0.0060	-1.15	20
20		0.0000	0.00	20
10		-0.0064	-1.23	20
0		-0.0025	-0.49	20
-10		0.0075	1.45	20
-15		-0.0052	-1.01	20
-30		-0.0021	-0.41	20
20	10.8	-0.0032	-0.62	20
20	13.2	0.0061	1.17	20

U-NII-2A Test Frequency:5260MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (MHz)	Frequency Error (ppm)	Limit (ppm)
40	12.0	0.0032	0.60	20
30		0.0012	0.22	20
20		0.0000	0.00	20
10		-0.0082	-1.57	20
0		-0.0019	-0.36	20
-10		0.0040	0.76	20
-15		-0.0068	-1.30	20
-30		0.0082	1.55	20
20	10.8	0.0035	0.66	20
20	13.2	0.0012	0.22	20

U-NII-2C Test Frequency:5500MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (MHz)	Frequency Error (ppm)	Limit (ppm)
40	12.0	-0.0002	-0.04	20
30		0.0079	1.43	20
20		0.0000	0.00	20
10		-0.0030	-0.54	20
0		0.0047	0.86	20
-10		-0.0007	-0.12	20
-15		0.0051	0.93	20
-30		0.0011	0.20	20
20	10.8	-0.0076	-1.37	20
20	13.2	-0.0042	-0.77	20

U-NII-3 Test Frequency:5785MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (MHz)	Frequency Error (ppm)	Limit (ppm)
40	12.0	0.0068	1.18	20
30		0.0029	0.50	20
20		0.0000	0.00	20
10		0.0042	0.73	20
0		0.0060	1.04	20
-10		0.0041	0.71	20
-15		-0.0038	-0.66	20
-30		0.0008	0.13	20
20	10.8	0.0033	0.57	20
20	13.2	0.0023	0.40	20

15 Antenna Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

This product has a FPC antenna fulfil the requirement of this section.

16 RF Exposure

Remark: refer to SAR test report: WTX25X01014044W002.

17 Photographs of test setup and EUT.

Note: Please refer to appendix: Appendix-BeneVision VP10-Photos.

=====End of Report=====