



Test Report No.: SA180319W001



RF EXPOSURE REPORT

Product: LTE module

Model Name: L850-GL

FCC ID: ZMOL850GL

Applicant: Fibocom Wireless Inc.

Address: 5/F, Tower A, Technology Building II, 1057 Nanhai Blvd, Nanshan, Shenzhen, China

Manufacturer: Fibocom Wireless Inc.

Address: 5/F, Tower A, Technology Building II, 1057 Nanhai Blvd, Nanshan, Shenzhen, China

Prepared by: BV 7Layers Communications Technology (Shenzhen) Co. Ltd

Lab Location: No.B102, Dazu Chuangxin Mansion, North of Beihuan Avenue, North Area, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, China

TEL: +86 755 8869 6566

FAX: +86 755 8869 6577

E-MAIL: customerservice.dg@cn.bureauveritas.com

Report No.: SA180319W001

Received Date: Jan. 06, 2017

Test Date: Feb. 20, 2017

Issued Date: Mar. 20, 2018

This report should not be used by the client to claim product certification, approval, or endorsement by A2LA or any government agencies.

Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.



Test Report No.: SA180319W001

TABLE OF CONTENTS

RF EXPOSURE REPORT.....	1
RELEASE CONTROL RECORD	3
1 CERTIFICATION	4
2 GENERAL INFORMATION	5
2.1 GENERAL DESCRIPTION OF EUT	5
3 RF EXPOSURE	6
3.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)	6
3.2 MPE CALCULATION FORMULA	6
3.3 CLASSIFICATION	6
3.4 CALCULATION RESULT OF MAXIMUM CONDUCTED POWER.....	7



Test Report No.: SA180319W001

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA170106C02	Original release	Aug. 30, 2017
SA180319W001	Base on the original report SA170106C02 adjusting Max. tune-up power, the measured conduct power always keep unchanged.	Mar. 20, 2018



Test Report No.: SA180319W001

1 CERTIFICATION

PRODUCT: LTE module

BRAND NAME: Fibocom

MODEL NAME: L850-GL

APPLICANT: Fibocom Wireless Inc.

TESTED: Feb. 20, 2017

TEST SAMPLE: Identical Prototype

STANDARDS: FCC Part 2 (Section 2.1091)

FCC OET Bulletin 65, Supplement C (01-01)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1

The above equipment has been tested by **Bureau Veritas Consumer Products Service (H.K.) Ltd., Taoyuan Branch – Lin Kou Laboratories**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report, this report has been issued by **BV 7Layers Communications Technology (Shenzhen) Co. Ltd.**

PREPARED BY :  , **DATE:** Mar. 20, 2018
(Yuqiang Yin/ Engineer)

APPROVED BY :  , **DATE:** Mar. 20, 2018
(Bill Yao / Manager)



2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	LTE module	
MODEL NAME	L850-GL	
NOMINAL VOLTAGE	DC 3.3V	
OPERATING TEMPERATURE RANGE	-10 ~ 55°C	
MODULATION TYPE	WCDMA	BPSK/QPSK
	LTE	QPSK/16QAM
OPERATING FREQUENCY	WCDMA	1852.4MHz ~ 1907.6MHz (FOR WCDMA II) 1712.4MHz ~ 1752.6MHz (FOR WCDMA IV) 826.4MHz ~ 846.6MHz (FOR WCDMA V)
	LTE	1850.7MHz ~ 1909.3MHz (FOR LTE Band2) 1710.7MHz ~ 1754.3MHz (FOR LTE Band4) 824.7MHz ~ 848.3MHz (FOR LTE Band5) 2502.5MHz ~ 2567.5MHz (FOR LTE Band7) 699.7MHz ~ 715.3MHz (FOR LTE Band12) 779.5MHz ~ 784.5MHz (FOR LTE Band13) 706.5MHz ~ 713.5MHz (FOR LTE Band17) 814.7MHz ~ 848.3MHz (FOR LTE Band26) 2307.5MHz ~ 2312.5MHz (FOR LTE Band30) 2572.5MHz ~ 2617.5MHz (FOR LTE Band38) 2498.5MHz ~ 2687.5MHz (FOR LTE Band41) 1710.7MHz ~ 1779.3MHz (FOR LTE Band66)
ANTENNA TYPE	External Antenna	
HW VERSION	V1.0.4	
SW VERSION	18500.5001.00.01.01.09	
I/O PORTS	Refer to user's manual	
CABLE SUPPLIED	N/A	

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.



3 RF EXPOSURE

3.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

3.2 MPE CALCULATION FORMULA

$$Pd = (Pout \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

3.3 CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Modular Approval**.



Test Report No.: SA180319W001

3.4 CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

WCDMA & LTE

Band	Antenna Gain (dBi)	Tune-up Power (dBm)	E.I.R.P Power (mW)	Power Density (mW/cm^2)	limit (mW/cm^2)	PASS / FAIL
WCDMA II	5	24.5	891.25	0.18	1.00	PASS
WCDMA IV	5	24.5	891.25	0.18	1.00	PASS
WCDMA V	3	24.5	562.341	0.11	0.55	PASS
LTE Band 2	5	24.0	794.33	0.16	1.00	PASS
LTE Band 4	5	24.0	794.33	0.16	1.00	PASS
LTE Band 5	3	24.0	501.19	0.10	0.55	PASS
LTE Band 7	5	24.0	794.33	0.16	1.00	PASS
LTE Band 12	3	24.0	501.19	0.10	0.47	PASS
LTE Band 13	3	24.0	501.19	0.10	0.52	PASS
LTE Band 17	3	24.0	501.19	0.10	0.47	PASS
LTE Band 26	3	24.0	501.19	0.10	0.54	PASS
LTE Band 30	5	24.0	794.33	0.16	1.00	PASS
LTE Band 38	5	24.0	794.33	0.16	1.00	PASS
LTE Band 41	5	24.0	794.33	0.16	1.00	PASS
LTE Band 66	5	24.0	794.33	0.16	1.00	PASS