

TEST REPORT

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR21-SRF0151-A
Page (1) of (8)

KCTL

1. Client

- Name : Fibocom Wireless Inc.
- Address : 1101, Tower A, Building 6, Shenzhen International Innovation Valley Dashi 1st Rd, Nanshan, Shenzhen, China
- Date of Receipt : 2021-06-03

2. Use of Report : Class II Permissive change

3. Name of Product / Model : Notebook PC / XE345XDA

4. Series Model : XE345XDA-LA1VZ

5. Manufacturer / Country of Origin : Fibocom Wireless Inc. / China

6. FCC ID : ZMOL850GLD

7. Date of Test : 2021-06-25 to 2021-06-28

8. Location of Test : Permanent Testing Lab On Site Testing
(Address: 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea)

9. Test method used : FCC Part 1.1310

10. Test Result : Refer to the test result in the test report

Affirmation	Tested by Name : Kwonse Kim 	Technical Manager Name : Seungyong Kim 
-------------	--	---

2021-07-13

KCTL Inc.

As a test result of the sample which was submitted from the client, this report does not guarantee the whole product quality. This test report should not be used and copied without a written agreement by KCTL Inc.

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR21-SRF0151-A
Page (2) of (8)

**REPORT REVISION HISTORY**

Date	Revision	Page No
2021-07-06	Originally issued	-
2021-07-13	Modified hardware version and simultaneous transmission analysis	4, 8

This report shall not be reproduced except in full, without the written approval of KCTL Inc. This document may be altered or revised by KCTL Inc. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KCTL Inc. will constitute fraud and shall nullify the document. This test report is a general report that does not use the KOLAS accreditation mark and is not related to KS Q ISO/IEC 17025 and KOLAS accreditation.

Note. The report No. KR21-SRF0151 is superseded by the report No. KR21-SRF0151-A.

General remarks for test reports**Statement concerning the uncertainty of the measurement systems used for the tests**

(may be required by the product standard or client)

Internal procedure used for type testing through which traceability of the measuring uncertainty has been established:

Procedure number, issue date and title:

Calculations leading to the reported values are on file with the testing laboratory that conducted the testing.

Statement not required by the standard or client used for type testing

CONTENTS

1. General information	4
2. Device information	4
2.1. Additional WLAN/Bluetooth Module information	5
2.2. Simultaneous Transmission Configurations	5
3. RF Exposure.....	6
4. Test Result	7
4.1 Calculation result of RF exposure	8
4.2 Simultaneous Transmission Analysis	8

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR21-SRF0151-A
Page (4) of (8)



1. General information

Client : Fibocom Wireless Inc.
Address : 1101, Tower A, Building 6, Shenzhen International Innovation Valley, Dashi 1st Rd, Nanshan, Shenzhen, China
Manufacturer : Fibocom Wireless Inc.
Address : 1101, Tower A, Building 6, Shenzhen International Innovation Valley, Dashi 1st Rd, Nanshan, Shenzhen, China
Laboratory : KCTL Inc.
Address : 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea
Accreditations : FCC Site Designation No: KR0040, FCC Site Registration No: 687132
VCCI Registration No. : R-20080, G-20078, C-20059, T-20056
CAB Identifier: KR0040
ISED Number: 8035A
KOLAS No.: KT231

2. Device information

Equipment under test : Notebook PC
Model : XE345XDA
Series Model : XE345XDA-LA1VZ
Integrated WWAN Module : Fibocom
L850-GL
ZMOL850GLD
Modulation technique : LTE_QPSK, 16QAM
WCDMA_QPSK
Power source : DC 7.72 V
Antenna specification : LTE_FPCB Antenna
Frequency range : LTE Band 2_1 850 MHz ~ 1 910 MHz
LTE Band 4_1 710 MHz ~ 1 755 MHz
LTE Band 5_824 MHz ~ 849 MHz
LTE Band 13_777 MHz ~ 787 MHz
Software version : Chrome OS
Hardware version : REV5
Test device serial No. : 4W619FAR500023N
Operation temperature : 10 °C ~ 35 °C

Note.

1. In this report is based on original report FCC ID: ZMOL850GLD, additional simultaneous transmission analysis with intel module AX201D2W which is also integrated into this host was reported in test report.
- SAR Report No.: KR21-SPF0050 (Intel Mobile Communications / AX201D2W / FCC ID: PD9AX201D2)
2. Series model: the SKU model name is a 5-digit identification number that is added after the basic model name (8 digits), and serves as a memo to indicate detailed specifications/businesses.

2.1. Additional WLAN/Bluetooth Module information

Manufacturer	: Intel Mobile Communications	
Model	: AX201D2W	
FCC ID	: PD9AX201D2	
Modulation technique	: DSSS, OFDM, OFDMA	
Frequency range	802.11b/g/n/ax	2.4 GHz Band (2 400.0 – 2 483.5 MHz)
	802.11a/n/ac/ax	5.15 GHz Band (5 150.0 – 5 250.0 MHz)
		5.25 GHz Band (5 250.0 – 5 350.0 MHz)
		5.47 GHz Band (5 470.0 – 5 725.0 MHz)
		5.725 GHz Band (5 725.0 – 5 850.0 MHz)
	Bluetooth/Low Energy	2.4 GHz Band (2 400.0 – 2 483.5 MHz)
Antenna Information	: Chain A: WLAN 2.4 GHz & 5 GHz and Bluetooth Chain B: WLAN 2.4 GHz & 5 GHz	

2.2. Simultaneous Transmission Configurations

No	Scenario
1	Bluetooth (Aux) + WWAN

Note.

- WWAN does not work simultaneously with WIFI.
- For the simultaneous analysis the highest ratio among the channels and modes of cellular module L850-GL and SAR values of the unlicensed module AX201D2W was selected for the RF exposure.

3. RF Exposure

3.1 Regulation

This document is prepared to show compliance with the RF Exposure requirements as required in §1.1310 of the FCC rules and Regulations.

The limit for Maximum Permissible Exposure (MPE), specified in FCC §1.1310, is listed in Table 1-1. According to FCC §1.1310: the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b).

Table 1 – Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength [V/m]	Magnetic Field Strength [A/m]	Power Density [mW/cm ²]	Averaging Time [minute]
(A) Limits for Occupational / Controlled Exposure				
0.3 ~ 3.0	614	1.63	*100	6
3.0 ~ 30	1842/f	4.89/f	*900/f ²	6
30 ~ 300	61.4	0.163	1.0	6
300 ~ 1 500	/	/	f/300	6
1 500 ~ 15 000	/	/	5	6
(B) Limits for General Population / Uncontrolled Exposure				
0.3 ~ 1.34	614	1.63	*100	30
1.34 ~ 30	824/f	2.19/f	*180/f ²	30
30 ~ 300	27.5	0.073	0.2	30
300 ~ 1 500	/	/	f/1 500	30
1 500 ~ 15 000	/	/	1.0	30

f=frequency in MHz, * = plane-wave equivalent power density

3.2 MPE (Maximum Permissive Exposure) Prediction

Predication of MPE limit at a given distance: Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2 \quad (\Rightarrow R = \sqrt{PG/4\pi S})$$


S = power density [mW/cm²]

P = Power input to antenna [mW]

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna [cm]

3.3 Antenna Position



The antenna of this product, under normal use condition, is at least 20 cm away from bottom. So, this device is classified as Mobile device.

3.4 Simultaneous transmission

According to KDB 447498 D01v06, When one of the following test exclusion conditions is satisfied for all combinations of simultaneous transmission configurations, further equipment approval is not required to incorporate transmitter modules in host devices that operate in the mixed mobile and portable host platform exposure conditions.

- a) The $[\sum \text{ of (the highest measured or estimated SAR for each standalone antenna configuration, adjusted for maximum tune-up tolerance)} / 1.6 \text{ W/kg}] + [\sum \text{ of MPE ratios}]$ is ≤ 1.0
- b) The SAR to peak location separation ratios of all simultaneously transmitting antenna pairs operating in portable device exposure conditions are all ≤ 0.04 , and the $[\sum \text{ of MPE ratios}]$ is ≤ 1.0 .

Test exclusion condition a):

$$\frac{\sum \text{ of Highest Reported SAR(Bluetooth)}}{\text{Limit}} + \frac{\text{Highest Max.tune up of cellular band}}{\text{Limit}} = < 1.0$$

4. Test Result

4.1 Calculation result of RF exposure

Band	Frequency range [MHz]	Max. Tune-up Power [dBm]	Ant. Gain [dBi]	Distance [cm]	Power density [mW/cm ²]	Limit [mW/cm ²]
LTE Band 2	1 850 – 1 910	24	2.15	20	0.081 984	1.00
LTE Band 4	1 710 – 1 755	24	1.84	20	0.076 336	1.00
LTE Band 5	824 – 849	24	0.33	20	0.053 918	0.55
LTE Band 13	777 – 787	24	0.45	20	0.055 428	0.51

Note.

1. The power density P_d at a distance of 20 cm calculated from the friis transmission.

4.2 Simultaneous Transmission Analysis

Mode	Exposure Condition / Position	Scaled 1g SAR (W/kg)	Power density (mW/cm ²)	Ratio
Bluetooth	Body SAR / Rear	0.190	N/A	0.119
Cellular Band (LTE B13)	MPE		0.055	0.108
Summation (Bluetooth SAR Ratio + LTE B13 MPE Ratio)				0.227

Note.

1. When the sum of ratios of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the 1.0 the additional equipment approval is not required.
2. Ratio calculation
 - Bluetooth: $0.190 / 1.6 = 0.119$
 - LTE Band 13: $0.055 / 0.51 = 0.108$
3. Simultaneous transmission of RF exposure.
 - $0.119 + 0.108 = 0.227$

End of test report