

TEST REPORT

Applicant: Fibocom Wireless Inc.
Address: 1101, Tower A, Building 6, Shenzhen International
Innovation Valley, Dashi 1st Rd, Nanshan,
Shenzhen, China
Equipment Type: LTE Module
Model Name: LE270-LA1
Brand Name: Fibocom
FCC ID: ZMOLE270LA1
Test Standard: 47 CFR Part 15 Subpart B
ANSI C63.4-2014
Sample Arrival Date: Jun. 20, 2025
Test Date: Jun. 26, 2025 - Jul. 08, 2025
Date of Issue: Jul. 18, 2025

ISSUED BY:


Shenzhen BALUN Technology Co., Ltd.

Tested by: Qiu Yongjing

Checked by: Liyao Zong

Approved by: Tolan Tu
(Technical Director)







Revision History

Version	Issue Date	Revisions
<u>Rev. 01</u>	<u>Jul. 18, 2025</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION.....	4
1.1	Test Laboratory	4
1.2	Test Location	4
2	PRODUCT INFORMATION	5
2.1	Applicant Information	5
2.2	Manufacturer Information.....	5
2.3	General Description for Equipment under Test (EUT).....	5
2.4	Ancillary Equipment.....	5
2.5	Technical Information	5
3	SUMMARY OF TEST RESULTS	6
3.1	Test Standards	6
3.2	Verdict	6
3.3	Test Uncertainty	6
4	GENERAL TEST CONFIGURATIONS	7
4.1	Test Enclosure List.....	7
4.2	Test Configurations	7
4.3	Test Setups	8
5	TEST ITEMS	10
5.1	Emission Tests	10
ANNEX A	TEST RESULTS.....	15
A.1	Radiated Emission.....	15
A.2	Conducted Emission, AC Ports.....	22
ANNEX B	TEST SETUP PHOTOS	26
ANNEX C	EUT EXTERNAL PHOTOS.....	26

ANNEX D	EUT INTERNAL PHOTOS.....	26
---------	--------------------------	----

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	☒ Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
	☐ 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196. The certification body is American Association for Laboratory Accreditation (A2LA).

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Fibocom Wireless Inc.
Address	1101,Tower A, Building 6, Shenzhen International Innovation Valley, Dashu 1st Rd, Nanshan, Shenzhen , China

2.2 Manufacturer Information

Manufacturer	Fibocom Wireless Inc.
Address	1101,Tower A, Building 6, Shenzhen International Innovation Valley, Dashu 1st Rd, Nanshan, Shenzhen , China

2.3 General Description for Equipment under Test (EUT)

EUT Name	LTE Module
Model Name Under Test	LE270-LA1
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	V1.2
Software Version	12007.7001.00.04.59.02
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.4 Ancillary Equipment

Note: Not applicable.

2.5 Technical Information

Network and Wireless connectivity	4G Network LTE FDD Band 2/4/5/12/13/17/66 WiFi SCAN
Classification of equipment	Class B
The highest internal frequency of EUT	2483.5 MHz

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15 Subpart B	Unintentional Radiators
2	ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

3.2 Verdict

No.	Description	FCC Rule	Test Verdict	Remark
1	Radiated Emission	15.109	Pass	--
2	Conducted Emission, AC Ports	15.107	Pass	--

3.3 Test Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Measurement	Value
Conducted emissions (9 kHz-30 MHz)	3.2 dB
Radiated emissions (30 MHz-1 GHz)-966#2	4.4 dB
Radiated emissions (1 GHz-18 GHz)-966#2	5.0 dB

4 GENERAL TEST CONFIGURATIONS

4.1 Test Enclosure List

Description	Manufacturer	Model	Serial No.	Length	Description	Use
RF Cable	N/A	N/A	N/A	N/A	N/A	☒
Antenna	N/A	N/A	N/A	N/A	N/A	☒
Adapter	N/A	N/A	N/A	N/A	N/A	☒
USB Cable	N/A	N/A	N/A	N/A	N/A	☒
Earphone	N/A	N/A	N/A	N/A	N/A	☒
PCB Board	N/A	N/A	N/A	N/A	N/A	☒

4.2 Test Configurations


All test modes of EUT are listed in the table below.

Test Mode Configuration	Description
Mode 1	<u>The Standby Test Mode</u> EUT + PCB Board + Adapter + USB Cable + RF Cable + Antenna + Earphone
Mode 2	<u>The Normal Operating Test Mode</u> EUT + PCB Board + Adapter + USB Cable + RF Cable + Antenna + Earphone


Test Case	Test Mode Configuration	Worst Mode
Radiated Emission	Mode 1~Mode 2	2
Conducted Emission, AC Ports	Mode 1~Mode 2	2
Note: All operation modes were tested, but only test data of the worst mode was presented in this report.		

4.3 Test Setups


Test Setup 1



Radiated Emission (30 MHz-1 GHz)



Radiated Emission (above 1 GHz)

Test Setup 2

Conducted Emissions, AC Ports

5 TEST ITEMS

5.1 Emission Tests

5.1.1 Radiated Emission

5.1.1.1 Limit

Frequency range (MHz)	Class B (at 3 m)		Class A (at 3 m)
	Field Strength ($\mu\text{V/m}$)	Field Strength (dB $\mu\text{V/m}$)	Field Strength (dB $\mu\text{V/m}$)
30 - 88	100	40	49.5
88 - 216	150	43.5	54
216 - 960	200	46	56.9
Above 960	500	54	60

NOTE:

- 1) Field Strength (dB $\mu\text{V/m}$) = $20 \cdot \log [\text{Field Strength } (\mu\text{V/m})]$.
- 2) In the emission tables above, the tighter limit applies at the band edges.
- 3) For 30 MHz to 1000 MHz, the CISPR quasi-peak is employed.

For above 1000 MHz, according to the requirements of FCC 15.35, unless otherwise specified, the limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test.

Frequency range (GHz)	Class B (at 3 m)			Class A (at 3 m)	
	Field Strength ($\mu\text{V/m}$)	Field Strength Average (dB $\mu\text{V/m}$)	Field Strength Peak (dB $\mu\text{V/m}$)	Field Strength Average (dB $\mu\text{V/m}$)	Field Strength Peak (dB $\mu\text{V/m}$)
1 - F_M	500	54	74	60	80

Note 1: The highest measurement frequency, F_M , in GHz, shall be determined as next Table.

Note 2: Average Class A limit at 3m L_{3m} is determined by the following conversion formula:

$$L_{3m} = L_{10m} + 20 \cdot \log(d_{10m}/d_{3m})$$
Where:
 L_{3m} is Average Class A limit at 3m;
 L_{10m} is Average Class A limit at 10m;
 d_{10m} is Measurement distance in 10m;
 d_{3m} is Measurement distance in 3m.
For this case: $L_{3m} = 49.5 + 20 \cdot \log(10/3) = 60$ (dB $\mu\text{V/m}$).

Highest internal frequency (F_X)	Highest measurement frequency (F_M)
$F_X \leq 108 \text{ MHz}$	1 GHz
$108 \text{ MHz} \leq F_X \leq 500 \text{ MHz}$	2 GHz
$500 \text{ MHz} \leq F_X \leq 1 \text{ GHz}$	5 GHz
$F_X \geq 1 \text{ GHz}$	$5 * F_X$ or 40 GHz, whichever is lower.
Note: F_X is Highest frequency generated or used in the device or on which the device operates or tunes.	

5.1.1.2 Test Setup

Refer to 4.3 section (test setup 1) for radiated emission test, the photo of test setup please refer to ANNEX B.

5.1.1.3 Test Procedure

All Radiated Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

An initial pre-scan was performed in the chamber using the EMI Receiver in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by Bi-Log antenna with 2 orthogonal polarities.

The measurement frequency range is from 30 MHz to the 5th harmonic of the maximum frequency of the EUT internal source. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1 \text{ GHz}$, 100 kHz for $f < 1 \text{ GHz}$

VBW $\geq$ RBW

Sweep = auto

Detector function = peak for $f < 1 \text{ GHz}$, peak & RMS Average for $f \geq 1 \text{ GHz}$

Trace = max hold

5.1.1.4 Test Result and Test Equipment List

Please refer to ANNEX A.1.

NOTE:

1. Results (dB μ V/m) = Reading (dB μ V) + Factor (dB/m)

The reading level is calculated by software which is not shown in the sheet

2. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain (dB)

3. Margin = Limit - Results

5.1.2 Conducted Emission, AC Ports

5.1.2.1 Test Limit

Frequency range (MHz)	Class A	
	Quasi-peak (dB μ V)	Average (dB μ V)
0.15 - 0.50	79	66
0.50 - 30	73	60

Frequency range (MHz)	Class B	
	Quasi-peak (dB μ V)	Average (dB μ V)
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

- 1) The lower limit shall apply at the band edges.
- 2) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50 MHz.

5.1.2.2 Test Setup

Refer to 4.3 section test (test setup 2) for conducted emission, the photo of test setup please refer to ANNEX B.

5.1.2.3 Test Procedure

The EUT is connected to the power mains through a LISN which provides 50 Ω /50 μ H of coupling impedance for the measuring instrument. The test frequency range is from 150 kHz to 30 MHz. The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels that are more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

Use the following spectrum analyzer settings:

RBW = 9 kHz

VBW $\geq$ RBW

Sweep = 10ms

Detector function = peak & Average

Trace = max hold

5.1.2.4 Test Result and Test Equipment List

Please refer to ANNEX A.2.

NOTE:

1. Results (dB μ V) = Reading (dB μ V) + Factor (dB)

The reading level is calculated by software which is not shown in the sheet

2. Factor = Insertion loss + Cable loss

3. Margin = Limit - Results

ANNEX A TEST RESULTS

A.1 Radiated Emission


Note 1: The symbol of “--” in the table which means not application.

Note 2: For the test data above 1 GHz, according the ANSI C63.4-2014, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Sample No.	S04	Temperature	23.7℃
Humidity	55%RH	Pressure	101kPa
Test Engineer	Chen Jingran	Test Date	2025.07.09


Test Mode 2

1) Test Antenna Vertical, 30 MHz – 1 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	42.804	34.81	-26.18	40.0	5.19	Peak	147.00	100	Vertical	Pass
2	49.303	27.24	-26.76	40.0	12.76	Peak	163.00	100	Vertical	Pass
3	78.694	21.44	-30.08	40.0	18.56	Peak	100.00	100	Vertical	Pass
4	160.368	19.71	-24.59	43.5	23.79	Peak	184.00	100	Vertical	Pass
5	214.736	19.58	-27.77	43.5	23.92	Peak	353.00	100	Vertical	Pass
6	924.437	31.64	-9.17	46.0	14.36	Peak	316.00	200	Vertical	Pass

2) Test Antenna Horizontal, 30 MHz – 1 GHz




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	39.458	22.48	-27.66	40.0	17.52	Peak	317.00	200	Horizontal	Pass
2	128.115	26.52	-26.30	43.5	16.98	Peak	352.00	200	Horizontal	Pass
3	213.766	23.27	-27.74	43.5	20.23	Peak	220.00	100	Horizontal	Pass
4	342.922	25.47	-23.15	46.0	20.53	Peak	277.00	100	Horizontal	Pass
5	437.012	23.66	-20.27	46.0	22.34	Peak	244.00	100	Horizontal	Pass
6	969.202	30.86	-8.41	54.0	23.14	Peak	275.00	100	Horizontal	Pass

Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
Frequency Below 1 GHz						
EMI Receiver	Keysight	N9038A	MY55330120	2024.08.01	2025.07.31	☒
Amplifier (30-1GHz)	COM-MV	ZT30-1000M	B2017119081	2024.11.28	2025.11.27	☒
Test Antenna- Bi-Log	SCHWARZB ECK	VULB 9168	9168-00883	2025.03.23	2028.03.22	☒
Anechoic Chamber (#2)	YiHeng	9m*6m*6m	142	2024.07.21	2027.07.20	☒
Description	Supplier	Name	Version	/		Use
Test Software	BALUN	BL410-E	V22.930	/		☒

Sample No.	S04	Temperature	21.7°C
Humidity	50%RH	Pressure	101kPa
Test Engineer	Chen Jingran	Test Date	2025.07.09


Test Mode 2

3) Test Antenna Vertical, 1 GHz – 12.5 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1424.710	40.62	-15.55	74.0	33.38	Peak	155.00	100	Vertical	Pass
1**	1424.710	29.94	-15.55	54.0	24.06	AV	155.00	100	Vertical	Pass
2	3223.780	47.93	-6.34	74.0	26.07	Peak	0.00	100	Vertical	Pass
2**	3223.780	37.78	-6.34	54.0	16.22	AV	0.00	100	Vertical	Pass
3	5759.740	54.83	0.94	74.0	19.17	Peak	46.00	100	Vertical	Pass
3**	5759.740	43.73	0.94	54.0	10.27	AV	46.00	100	Vertical	Pass
4	7006.920	53.55	-0.33	74.0	20.45	Peak	342.00	100	Vertical	Pass
4**	7006.920	43.05	-0.33	54.0	10.95	AV	342.00	100	Vertical	Pass
5	9339.500	53.87	2.15	74.0	20.13	Peak	115.00	100	Vertical	Pass
5**	9339.500	44.28	2.15	54.0	9.72	AV	115.00	100	Vertical	Pass
6	11935.612	54.86	2.54	74.0	19.14	Peak	310.00	100	Vertical	Pass
6**	11935.612	45.30	2.54	54.0	8.70	AV	310.00	100	Vertical	Pass

4) Test Antenna Horizontal, 1 GHz – 6 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1382.070	39.65	-15.50	74.0	34.35	Peak	255.00	100	Horizontal	Pass
1**	1382.070	30.13	-15.50	54.0	23.87	AV	255.00	100	Horizontal	Pass
2	3116.400	47.98	-6.54	74.0	26.02	Peak	188.00	100	Horizontal	Pass
2**	3116.400	37.50	-6.54	54.0	16.50	AV	188.00	100	Horizontal	Pass
3	3992.260	50.42	-1.76	74.0	23.58	Peak	173.00	100	Horizontal	Pass
3**	3992.260	40.29	-1.76	54.0	13.71	AV	173.00	100	Horizontal	Pass
4	5684.720	54.10	0.87	74.0	19.90	Peak	258.00	100	Horizontal	Pass
4**	5684.720	43.77	0.87	54.0	10.23	AV	258.00	100	Horizontal	Pass
5	7920.140	53.77	0.71	74.0	20.23	Peak	154.00	100	Horizontal	Pass
5**	7920.140	43.90	0.71	54.0	10.10	AV	154.00	100	Horizontal	Pass
6	9337.125	54.32	2.16	74.0	19.68	Peak	116.00	100	Horizontal	Pass
6**	9337.125	44.53	2.16	54.0	9.47	AV	116.00	100	Horizontal	Pass

Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
Frequency Above 1 GHz						
EMI Receiver	Keysight	N9038A	MY55330120	2024.08.01	2025.07.31	☒
Amplifier (1-12GHz)	Advanced Microwave	WLA652A	1740103	2024.11.28	2025.11.27	☒
Amplifier (0.8-21GHz)	Mini-Circuits	ZVA-213-S+	225321316	2024.11.28	2025.11.27	☒
Test Antenna- Horn	SCHWARZB ECK	BBHA 9120D	01917	2025.05.20	2028.05.19	☒
Description	Supplier	Name	Version	/		Use
Test Software	BALUN	BL410-E	V22.930	/		☒


A.2 Conducted Emission, AC Ports

Note: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.

Sample No.	S04	Temperature	23.7℃
Humidity	55%RH	Pressure	101kPa
Test Engineer	Yang Panxia	Test Date	2025.07.08


Test Mode 2

1) AC Ports - L Phase



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.200	40.71	10.03	63.61	22.90	Peak	L	Pass
1**	0.200	26.23	10.03	53.61	27.38	AV	L	Pass
2	0.460	38.49	10.50	56.69	18.20	Peak	L	Pass
2**	0.460	26.40	10.50	46.69	20.29	AV	L	Pass
3	0.634	35.78	10.41	56.00	20.22	Peak	L	Pass
3**	0.634	24.14	10.41	46.00	21.86	AV	L	Pass
4	10.098	56.01	12.26	60.00	3.99	Peak	L	Pass
4**	10.098	36.78	12.26	50.00	13.22	AV	L	Pass
5	10.626	56.08	12.31	60.00	3.92	Peak	L	Pass
5**	10.626	36.62	12.31	50.00	13.38	AV	L	Pass
6	11.372	56.95	12.44	60.00	3.05	Peak	L	Pass
6**	11.372	23.37	12.44	50.00	26.63	AV	L	Pass

2) AC Ports - N Phase



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.246	46.00	10.03	61.89	15.89	Peak	N	Pass
1**	0.246	24.95	10.03	51.89	26.94	AV	N	Pass
2	0.488	38.40	10.37	56.20	17.80	Peak	N	Pass
2**	0.488	24.22	10.37	46.20	21.98	AV	N	Pass
3	0.592	38.14	10.63	56.00	17.86	Peak	N	Pass
3**	0.592	22.32	10.63	46.00	23.68	AV	N	Pass
4	10.232	56.17	12.30	60.00	3.83	Peak	N	Pass
4**	10.232	18.84	12.30	50.00	31.16	AV	N	Pass
5	10.600	55.50	12.24	60.00	4.50	Peak	N	Pass
5**	10.600	21.16	12.24	50.00	28.84	AV	N	Pass
6	11.288	55.18	12.65	60.00	4.82	Peak	N	Pass
6**	11.288	31.61	12.65	50.00	18.39	AV	N	Pass

Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
EMI Receiver	KEYSIGHT	N9010B	MY57110309	2024.08.01	2025.07.31	☒
LISN	SCHWARZB ECK	NSLK 8127	8127-687	2025.04.29	2026.04.28	☒
Shielded Room	YiHeng Electronic Co., Ltd	3.5m*3.1m*2. 8m	112	2025.02.14	2028.02.13	☒
Description	Supplier	Name	Version	/		Use
Test Software	BALUN	BL410-E	V22.930	/		☒

ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-SZ261074-AE.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-SZ261074-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-SZ261074-AI.PDF”.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--