

RF Exposure Report

Report No.: SA161208E07A

FCC ID: ZMYDSL2401HN2E1C

Test Model: DSL-2401HN2-E1C

Received Date: Dec. 08, 2016

Test Date: Dec. 19, 2016

Issued Date: Mar. 28, 2017

Applicant: MitraStar Technology Corporation

Address: 1-1# Minshan Road, Wuxi New Wu District Jiangsu, China

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.

Table of Contents

| | |
|---|------------------|
| Release Control Record | 3 |
| 1 Certificate of Conformity..... | 4 |
| 2 RF Exposure..... | 5 |
| 2.1 Limits for Maximum Permissible Exposure (MPE)..... | 5 |
| 2.2 MPE Calculation Formula | 5 |
| 2.3 Classification | 5 |
| 2.4 Antenna Gain Table..... | 5 |
| 2.5 Directional Gain Table | 5 錯誤! 尚未定義書籤。 |
| 3 Calculation Result of Conducted Power | 6 |

Release Control Record

| Issue No. | Description | Date Issued |
|--------------|-------------------|---------------|
| SA161208E07A | Original release. | Mar. 28, 2017 |

1 Certificate of Conformity

Product: VDSL IAD

Brand: MitraStar

Test Model: DSL-2401HN2-E1C

Sample Status: ENGINEERING SAMPLE

Applicant: MitraStar Technology Corporation

Test Date: Dec. 19, 2016


Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : , **Date:** Mar. 28, 2017

Cindy Hsin / Specialist

Approved by : , **Date:** Mar. 28, 2017

May Chen / Manager

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm ²) | Average Time (minutes) |
|---|-------------------------------|-------------------------------|-------------------------------------|------------------------|
| Limits For General Population / Uncontrolled Exposure | | | | |
| 300-1500 | ... | ... | F/1500 | 30 |
| 1500-100,000 | ... | ... | 1.0 | 30 |

F = Frequency in MHz

2.2 MPE Calculation Formula

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user.

So, this device is classified as **Mobile Device**.

2.4 Antenna Gain Table

| Antenna No. | Chain No. | Antenna Gain(dBi) | Frequency range (GHz ~ GHz) | Antenna Type | Connector Type | Cable Length (mm) |
|-------------|-----------|-------------------|-----------------------------|--------------|----------------|-------------------|
| 1 | Chain 0 | 2.46 | 2.4~2.4835 | Dipole | NA | 177.7 |
| 2 | Chain 1 | 2.36 | 2.4~2.4835 | | NA | 42.7 |

3 Calculation Result of Conducted Power

| Frequency (MHz) | Conducted Power (mW) | Directional Gain (dBi) | Distance (cm) | Power Density (mW/cm ²) | Limit (mW/cm ²) |
|-----------------|----------------------|------------------------|---------------|-------------------------------------|-----------------------------|
| 2412-2462 | 575.232 | 5.42 | 20 | 0.39863 | 1 |

NOTE:

$$\text{Directional gain} = 10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 5.42 \text{dBi}$$

--- END ---