




China




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1		4824.310	43.85	5.29	49.14	74.00	-24.86	peak
2	*	4824.310	31.53	5.29	36.82	54.00	-17.18	AVG



China

Above 1GHz:

Model:	My7	Result:	PASS
Temperature:	25°C	Relative Humidity:	58 %
Pressure:	1009 hPa	Test voltage:	120Vac
Test Mode :	Transmitting mode (802.11g/2412MHz)	Antenna polarity:	Vertical




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2390.000	21.02	31.91	52.93	74.00	-21.07	peak
2		2390.000	11.27	31.91	43.18	54.00	-10.82	AVG
3	X	2417.250	62.51	31.89	94.40	74.00	20.40	peak
4	*	2417.250	42.99	31.89	74.88	54.00	20.88	AVG



China

80.0 dBuV/m




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4824.520	45.81	5.29	51.10	74.00	-22.90	peak
2	*	4824.520	33.12	5.29	38.41	54.00	-15.59	AVG



China

Below 1GHz:

Model:	My7	Result:	PASS
Temperature:	23°C	Relative Humidity:	51 %
Pressure:	1001 hPa	Test voltage:	120Vac
Test Mode :	Transmitting mode (802.11g/2437MHz)	Antenna polarity:	Horizontal




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		337.9750	47.81	-11.14	36.67	46.00	-9.33	peak
2		384.0500	44.70	-9.60	35.10	46.00	-10.90	peak
3		507.7250	45.06	-7.07	37.99	46.00	-8.01	peak
4	*	556.2250	43.62	-5.34	38.28	46.00	-7.72	peak
5		774.4750	38.26	-2.23	36.03	46.00	-9.97	peak
6		822.9750	35.24	-1.42	33.82	46.00	-12.18	peak



China

Below 1GHz:

Model:	My7	Result:	PASS
Temperature:	23°C	Relative Humidity:	51 %
Pressure:	1001 hPa	Test voltage:	120Vac
Test Mode :	Transmitting mode (802.11g/2437MHz)	Antenna polarity:	Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		265.2250	46.47	-13.55	32.92	46.00	-13.08	peak
2		434.9750	48.07	-8.39	39.68	46.00	-6.32	peak
3	!	459.2250	48.96	-7.97	40.99	46.00	-5.01	peak
4	*	507.7250	48.82	-7.07	41.75	46.00	-4.25	peak
5		774.4750	37.53	-2.23	35.30	46.00	-10.70	peak
6		871.4750	39.70	-0.53	39.17	46.00	-6.83	peak



China

Above 1GHz:


Model:	My7	Result:	PASS
Temperature:	25°C	Relative Humidity:	58 %
Pressure:	1009 hPa	Test voltage:	120Vac
Test Mode :	Transmitting mode (802.11g/2437MHz)	Antenna polarity:	Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	X	2430.500	61.26	31.87	93.13	74.00	19.13	peak
2	*	2430.500	41.77	31.87	73.64	54.00	19.64	AVG



China




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		4873.620	43.60	5.47	49.07	74.00	-24.93	peak
2	*	4873.620	31.44	5.47	36.91	54.00	-17.09	AVG



China

Above 1GHz:

Model:	My7	Result:	PASS
Temperature:	25°C	Relative Humidity:	58 %
Pressure:	1009 hPa	Test voltage:	120Vac
Test Mode :	Transmitting mode (802.11g/2437MHz)	Antenna polarity:	Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	X	2430.250	62.90	31.87	94.77	74.00	20.77	peak
2	*	2431.750	43.24	31.87	75.11	54.00	21.11	AVG



China

80.0 dBuV/m




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4874.020	45.58	5.47	51.05	74.00	-22.95	peak
2	*	4874.020	32.14	5.47	37.61	54.00	-16.39	AVG



China

Below 1GHz:

Model:	My7	Result:	PASS
Temperature:	23°C	Relative Humidity:	51 %
Pressure:	1001 hPa	Test voltage:	120Vac
Test Mode :	Transmitting mode (802.11g/2462MHz)	Antenna polarity:	Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		265.2250	46.51	-13.55	32.96	46.00	-13.04	peak
2		337.9750	48.31	-11.14	37.17	46.00	-8.83	peak
3	*	507.7250	45.56	-7.07	38.49	46.00	-7.51	peak
4		556.2250	43.62	-5.34	38.28	46.00	-7.72	peak
5		774.4750	38.76	-2.23	36.53	46.00	-9.47	peak
6		861.7750	35.90	-0.69	35.21	46.00	-10.79	peak



China

Below 1GHz:

Model:	My7	Result:	PASS
Temperature:	23°C	Relative Humidity:	51 %
Pressure:	1001 hPa	Test voltage:	120Vac
Test Mode :	Transmitting mode (802.11g/2462MHz)	Antenna polarity:	Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		71.2250	44.63	-18.46	26.17	40.00	-13.83	peak
2		265.2250	46.47	-13.55	32.92	46.00	-13.08	peak
3		301.6000	46.25	-12.03	34.22	46.00	-11.78	peak
4	!	459.2250	48.96	-7.97	40.99	46.00	-5.01	peak
5	*	507.7250	48.32	-7.07	41.25	46.00	-4.75	peak
6		871.4750	37.70	-0.53	37.17	46.00	-8.83	peak



China

Above 1GHz:

Model:	My7	Result:	PASS
Temperature:	25°C	Relative Humidity:	58 %
Pressure:	1009 hPa	Test voltage:	120Vac
Test Mode :	Transmitting mode (802.11g/2462MHz)	Antenna polarity:	Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	X	2467.500	41.85	31.82	73.67	54.00	19.67	AVG
2	*	2468.000	62.16	31.82	93.98	74.00	19.98	peak
3		2483.500	22.47	31.80	54.27	74.00	-19.73	peak
4		2483.500	11.26	31.80	43.06	54.00	-10.94	AVG



China

80.0 dBuV/m




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4924.020	43.98	5.65	49.63	74.00	-24.37	peak
2	*	4924.020	31.98	5.65	37.63	54.00	-16.37	AVG



China

Above 1GHz:


Model:	My7	Result:	PASS
Temperature:	25°C	Relative Humidity:	58 %
Pressure:	1009 hPa	Test voltage:	120Vac
Test Mode :	Transmitting mode (802.11g/2462MHz)	Antenna polarity:	Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	2455.750	63.60	31.84	95.44	74.00	21.44	peak
2	X	2456.500	43.08	31.84	74.92	54.00	20.92	AVG
3		2483.500	20.04	31.80	51.84	74.00	-22.16	peak
4		2483.500	11.44	31.80	43.24	54.00	-10.76	AVG



China



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		4924.380	46.16	5.65	51.81	74.00	-22.19	peak
2	*	4924.380	36.47	5.65	42.12	54.00	-11.88	AVG

Remark:

- (1) All readings are Peak unless otherwise stated QP in column of [Note] . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency. "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
From 30MHz to 1GHz, read the field strength of the emissions with RBW=120KHz.
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
Read the Peak field strength through RBW=1MHz, VBW=3MHz in spectrum analyzer setting.
Read the Average field strength through RBW=1MHz, VBW=10Hz in spectrum analyzer setting.
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna



China

6.4 6dB BANDWIDTH TEST

6.4.1 APPLIED PROCEDURES / LIMIT

Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

6.4.2 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov.26.2011

Remark: " N/A" denotes No Model Name. , Serial No. or No Calibration specified.


6.4.3 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 100KHz, VBW=100KHz, Sweep time = 5 ms.

6.4.4 DEVIATION FROM STANDARD

No deviation.

6.4.5 TEST SETUP



6.4.6 EUT OPERATION CONDITIONS

The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.




China

6.4.7 TEST RESULTS



Model:	My7	Result:	PASS
Temperature:	20°C	Relative Humidity:	55 %
Pressure:	1001 hPa	Test voltage:	120Vac
Test Mode :	Continuously transmitting mode.		

Frequency (MHz)	Mode	Bandwidth	Data Rate	Measurement (MHz)	Limit	Result
2412	802.11b	6dB	1 Mbps	9.8	≥500KHz	Pass
2437		6dB	1 Mbps	9.9		Pass
2462		6dB	1 Mbps	9.9		Pass
2412	802.11g	6dB	6 Mbps	16.5	≥500KHz	Pass
2437		6dB	6 Mbps	16.5		Pass
2462		6dB	6 Mbps	16.5		Pass







China





China





China

