



**FCC 47 CFR PART 15 SUBPART C
INDUSTRY CANADA RSS-210 ISSUE 8**

**C2PC CERTIFICATION TEST REPORT
FOR
GSM/CDMA/WCDMA/LTE Phone + Bluetooth &
WLAN (2.4GHz & 5GHz) and NFC**

**MODEL NUMBER: LG-D820, LGD820 and D820
FCC ID: ZNFD820
IC: 2703C-D820**

**REPORT NUMBER: 13U15778-2, Revision B
ISSUE DATE: September 17, 2013**

Prepared for
**LG ELECTRONICS MOBILECOMM U.S.A., INC.
1000 SYLVAN AVENUE
ENGLEWOOD CLIFFS, NJ 07632**

Prepared by
**UL VERIFICATION SERVICES INC.
47173 BENICIA STREET
FREMONT, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888**



NVLAP LAB CODE 200065-0

Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
--	8/13/13	Initial Issue	P. Kim
A	9/12/13	Updated Section 5.4 Software and Firmware	AAumentado
B	9/17/13	Updated the section 7.2 investigate frequency range	P. Kim

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	4
2. TEST METHODOLOGY	5
3. FACILITIES AND ACCREDITATION	5
4. CALIBRATION AND UNCERTAINTY	5
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	<i>5</i>
4.2. <i>SAMPLE CALCULATION</i>	<i>5</i>
4.3. <i>MEASUREMENT UNCERTAINTY.....</i>	<i>5</i>
5. EQUIPMENT UNDER TEST	6
5.1. <i>DESCRIPTION OF EUT</i>	<i>6</i>
5.2. <i>MAXIMUM OUTPUT POWER.....</i>	<i>6</i>
5.3. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i>	<i>6</i>
5.4. <i>SOFTWARE AND FIRMWARE.....</i>	<i>6</i>
5.5. <i>WORST-CASE CONFIGURATION AND MODE.....</i>	<i>7</i>
5.6. <i>DESCRIPTION OF TEST SETUP.....</i>	<i>8</i>
6. TEST AND MEASUREMENT EQUIPMENT	10
7. RADIATED TEST RESULTS.....	11
7.1. <i>LIMITS AND PROCEDURE</i>	<i>11</i>
7.2. <i>TRANSMITTER ABOVE 1 GHz.....</i>	<i>12</i>
7.2.1. <i>BASIC DATA RATE GFSK MODULATION</i>	<i>12</i>
7.2.2. <i>ENHANCED DATA RATE 8PSK MODULATION</i>	<i>26</i>
7.3. <i>WORST-CASE BELOW 1 GHz.....</i>	<i>40</i>
8. SETUP PHOTOS.....	43

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: LG ELECTRONICS MOBILECOMM U.S.A., INC.
1000 SYLVAN AVENUE
ENGLEWOOD CLIFFS, NEW JERSEY 07632

EUT DESCRIPTION: GSM/CDMA/WCDMA + LTE Phone Bluetooth, WLAN (2.4GHz & 5GHz) and NFC

MODEL: LG-D820, LGD820 and D820

SERIAL NUMBER: (01EEE7E020C97E30) RADIATED #1
(01EB815C20C97E15) RADIATED #2

DATE TESTED: July 29 – August 9, 2013

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Pass
INDUSTRY CANADA RSS-210 ISSUE 8	Pass
INDUSTRY CANADA RSS-GEN ISSUE 3	Pass

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Verification Services Inc. By:

Tested By:



PHILIP KIM
EMC SUPERVISOR
UL Verification Services Inc.

CHARLES VERGONIO
WISE LAB TECHNICIAN
UL Verification Services Inc.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10-2009, FCC CFR 47 Part 2, FCC CFR 47 Part 15, RSS-GEN Issue 3, and RSS-210 Issue 8.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 Benicia Street, Fremont, California, USA.

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://www.ccsenc.com>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	3.52 dB
Radiated Disturbance, 30 to 1000 MHz	4.94 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a LTE Phone Bluetooth, WLAN(2.4GHz & 5GHz) and NFC

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum peak conducted output power as follows:

Frequency Range (MHz)	Mode	Output Power (dBm)	Output Power (mW)
2402 - 2480	Basic GFSK	10.12	10.28
2402 - 2480	Enhanced 8PSK	9.11	8.15

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes an FPCB antenna, with a maximum gain of -1.96 dBi.

5.4. SOFTWARE AND FIRMWARE

Android OS Version: 3.40-gbab8bca-00002-gd1a7716.
Kernel Version: M8974A-0.0.19.0.05.

5.5. WORST-CASE CONFIGURATION AND MODE

Radiated emission and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

The fundamental of the EUT was investigated in three orthogonal orientations X,Y,Z, it was determined that Y orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in Y orientation.

5.6. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
AC Adapter	LG	MCS.01WR	EAY62768913	N/A
Earphone	QuadBeat	LE 410	EAB62729001	N/A


I/O CABLES

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	Mini-USB	Shielded	1.2m	N/A
2	Audio	1	Mini-Jack	Unshielded	1m	N/A

TEST SETUP

The EUT is continuously communicating to the Bluetooth tester during the tests. EUT was set in the Hidden menu mode to enable BT communications.

SETUP DIAGRAM FOR TESTS



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List					
Description	Manufacturer	Model	Asset	Cal Date	Cal Due
Antenna, Biconolog, 30MHz-1 GHz	Sunol Sciences	JB1	C01171	03/23/12	02/13/14
Antenna, Horn, 18GHz	EMCO	3115	C00783	10/25/12	10/25/13
Antenna, Horn, 25.5 GHz	ARA	MWH-1826/B	C00980	11/14/12	11/14/13
Preamplifier, 1300 MHz	Agilent / HP	8447D	C00580	01/28/13	01/28/14
Preamplifier, 26.5 GHz	Agilent / HP	8449B	C01052	10/22/12	10/22/13
Spectrum Analyzer, 44 GHz	Agilent / HP	E4446A	C01069	12/20/12	12/20/13
CBT Bluetooth Tester	R & S	CBT	None	07/12/13	07/12/14
Peak Power Meter	Agilent / HP	E4416A	C00963	12/13/12	12/13/13
Peak / Average Power Sensor	Agilent / HP	E9327A	C00964	12/13/12	12/13/13
LISN, 30 MHz	FCC	50/250-25-2	C00626	01/14/13	01/14/14
Reject Filter, 2.4GHz	Micro-Tronics	BRM50702	N02684	CNR	CNR

7. RADIATED TEST RESULTS

7.1. LIMITS AND PROCEDURE

LIMITS

FCC §15.205 and §15.209

IC RSS-210 Clause 2.6 (Transmitter)

IC RSS-GEN Clause 6 (Receiver)

Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46
Above 960	500	54

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.4. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 1 MHz for peak measurements and $\geq 1/0.003(\text{On Time}) = 330\text{Hz}$ for average measurements.


The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.


The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

7.2. TRANSMITTER ABOVE 1 GHz


7.2.1. BASIC DATA RATE GFSK MODULATION


RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)







RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)







RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)






RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)





HARMONICS AND SPURIOUS EMISSIONS

LOW CHANNEL
 VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T346 (dB/m)	Amp/Cbl/ 3GHz HPF (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Height (cm)	Polarity
1	4.796	41.2	PK	34.4	-31.5	44.1	53.97	-9.87	74	-29.9	199	H
4	7.216	38.73	PK	36	-29.4	45.33	53.97	-8.64	74	-28.67	199	H
2	4.806	40.92	PK	34.4	-31.6	43.72	53.97	-10.25	74	-30.28	199	V
3	7.212	38.85	PK	36	-29.4	45.45	53.97	-8.52	74	-28.55	100	V
7	12.005	29.99	PK	39.1	-24.9	44.19	53.97	-9.78	74	-29.81	199	H
8	12.021	30.4	PK	39.1	-25.3	44.2	53.97	-9.77	74	-29.8	199	V


PK - Peak detector

MID CHANNEL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T346 (dB/m)	Amp/Cbl/ 3GHz HPF (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Height (cm)	Polarity
1	4.491	41.16	PK	34.3	-31.9	43.56	53.97	-10.41	74	-30.44	100	H
2	7.326	37.98	PK	36	-28.4	45.58	53.97	-8.39	74	-28.42	199	H
4	4.483	41.23	PK	34.3	-31.8	43.73	53.97	-10.24	74	-30.27	100	V
5	7.316	38.76	PK	36	-28.6	46.16	53.97	-7.81	74	-27.84	199	V
7	12.206	29.54	PK	39.2	-25.2	43.54	53.97	-10.43	74	-30.46	100	H
8	12.388	30.23	PK	39.1	-25.6	43.73	53.97	-10.24	74	-30.27	100	V

PK - Peak detector

HIGH CHANNEL
VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL DATA


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T346 (dB/m)	Amp/Cbl/ 10dB Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Height (cm)	Polarity
10	2.699	37.24	PK	33.1	-23.9	46.44	53.97	-7.53	74	-27.56	199	H
11	2.701	36.52	PK	33.1	-23.9	45.72	53.97	-8.25	74	-28.28	199	V


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T346 (dB/m)	Amp/Cbl/ 3GHz HPF (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Height (cm)	Polarity
2	5.006	41.26	PK	34.4	-31	44.66	53.97	-9.31	74	-29.34	199	H
3	7.453	39.4	PK	36.1	-29.2	46.3	53.97	-7.67	74	-27.7	100	H
5	4.985	42.89	PK	34.4	-31.1	46.19	53.97	-7.78	74	-27.81	199	V
6	7.476	40.21	PK	36.1	-29.4	46.91	53.97	-7.06	74	-27.09	100	V
8	12.5	29.83	PK	39.1	-24.9	44.03	53.97	-9.94	74	-29.97	100	H
9	12.543	29.98	PK	39.1	-24.6	44.48	53.97	-9.49	74	-29.52	100	V

PK - Peak detector


7.2.2. ENHANCED DATA RATE 8PSK MODULATION


RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)







RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)







RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)






RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)





HARMONICS AND SPURIOUS EMISSIONS

LOW CHANNEL
 HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.


LOW CHANNEL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T346 (dB/m)	Amp/Cbl/ 10dB Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Height (cm)	Polarity
11	2.544	36.44	PK	32.8	-23.9	45.34	53.97	-8.63	74	-28.66	199	H
12	2.543	37.08	PK	32.8	-23.9	45.98	53.97	-7.99	74	-28.02	199	V

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T346 (dB/m)	Amp/Cbl/ 3GHz HPF (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Height (cm)	Polarity
3	4.434	42.57	PK	34.2	-31.3	45.47	53.97	-8.5	74	-28.53	100	H
4	6.974	40.57	PK	36	-28.6	47.97	53.97	-6	74	-26.03	199	H
6	4.787	42.43	PK	34.4	-31.4	45.43	53.97	-8.54	74	-28.57	199	V
7	7.813	40.45	PK	36.2	-28.8	47.85	53.97	-6.12	74	-26.15	199	V
9	13.61	32.07	PK	39.2	-26.6	44.67	53.97	-9.3	74	-29.33	100	H
10	13.058	30.43	PK	39.1	-25.9	43.63	53.97	-10.34	74	-30.37	199	V

PK - Peak detector

MID CHANNEL
HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.


MID CHANNEL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T346 (dB/m)	Amp/Cbl/ 10dB Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Height (cm)	Polarity
11	1.906	39.43	PK	31.5	-24.8	46.13	53.97	-7.84	74	-27.87	199	H
12	2.516	37.94	PK	32.7	-24.2	46.44	53.97	-7.53	74	-27.56	100	V

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T346 (dB/m)	Amp/Cbl/ 3GHz HPF (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Height (cm)	Polarity
3	4.357	43.62	PK	34.1	-31	46.72	53.97	-7.25	74	-27.28	199	H
4	7.889	39.89	PK	36.2	-28.2	47.89	53.97	-6.08	74	-26.11	199	H
6	4.402	42.99	PK	34.2	-31.2	45.99	53.97	-7.98	74	-28.01	100	V
7	6.312	40.53	PK	35.9	-29.2	47.23	53.97	-6.74	74	-26.77	199	V
9	12.19	29.68	PK	39.2	-25.4	43.48	53.97	-10.49	74	-30.52	100	H
10	14.352	31.99	PK	39.8	-26.5	45.29	53.97	-8.68	74	-28.71	100	V

PK - Peak detector

HIGH CHANNEL
 VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL DATA


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T346 (dB/m)	Amp/Cbl/ 10dB Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Height (cm)	Polarity
9	2.719	36.85	PK	33.1	-23.9	46.05	53.97	-7.92	74	-27.95	100	H
10	2.228	36.98	PK	32.4	-24.5	44.88	53.97	-9.09	74	-29.12	199	V


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T346 (dB/m)	Amp/Cbl/ 3GHz HPP (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Height (cm)	Polarity
3	5.904	41.56	PK	35.6	-30.5	46.66	53.97	-7.31	74	-27.34	100	H
5	6.342	40.46	PK	35.9	-29	47.36	53.97	-6.61	74	-26.64	199	V
7	15.165	30.57	PK	40	-25.3	45.27	53.97	-8.7	74	-28.73	199	H
8	11.78	30.22	PK	38.8	-25.1	43.92	53.97	-10.05	74	-30.08	199	V

PK - Peak detector

7.3. WORST-CASE BELOW 1 GHz

GFSK SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, HORIZONTAL)





DATA

Frequency (MHz)	Meter Reading (dBuV)	Det	AF T477 (dB/m)	Amp/Cb/Filtr/Pad (dB)	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
146.3225	34.09	PK	12.4	-26.6	19.89	43.52	-23.63	0-360	200	H
153.4625	35.67	PK	12.3	-26.5	21.47	43.52	-22.05	0-360	200	H
80.915	44.79	PK	7.6	-27.1	25.29	40	-14.71	0-360	100	V
176.9225	31.15	PK	11.5	-26.3	16.35	43.52	-27.17	0-360	100	V
199.9575	31.42	PK	12.3	-26.1	17.62	43.52	-25.9	0-360	100	V
668	30.27	PK	19.2	-22.8	26.67	46.02	-19.35	0-360	100	H
779.1	36.15	PK	20.5	-22.6	34.05	46.02	-11.97	0-360	400	H
461.6	37.25	PK	16.7	-24.7	29.25	46.02	-16.77	0-360	200	V
830.8	42.02	PK	21.2	-22.4	40.82	46.02	-5.2	0-360	400	V

PK - Peak detector